

Container Restaurant - Technical Specifications and Price List

Canonical URL: <https://www.samanportable.com/product/container-cafe/container-restaurant>

Six approved sizes and prices

SIZE	AREA (SQ FT)	COVERS	RATE EX-GST	EX-GST	INCL. 18% GST
10x10x8.5 ft	100	8 diners	INR 2,200/sq ft	INR 2,20,000	INR 2,59,600
20x8x8.5 ft	160	13 diners	INR 2,200/sq ft	INR 3,52,000	INR 4,15,360
20x10x8.5 ft	200	17 diners	INR 2,000/sq ft	INR 4,00,000	INR 4,72,000
40x8x8.5 ft	320	27 diners	INR 1,880/sq ft	INR 6,01,600	INR 7,09,888
40x10x8.5 ft	400	33 diners	INR 1,880/sq ft	INR 7,52,000	INR 8,87,360
40x12x8.5 ft	480	40 diners	INR 1,840/sq ft	INR 8,83,200	INR 10,42,176

Base specification price - customisations quoted separately. Ex-factory, ex-GST.

Steel Structure

COMPONENT	DETAIL
Bottom frame	150×75×5 mm MS C-channel or engineered built-up base
Bottom stiffeners	100×50×4 mm channels with local cooking-equipment and counter supports
Floor frame	100×50×3 mm primary and 80×40×3 mm secondary floor members
Top frame	80×40×3 mm MS top perimeter
Roof stiffeners	60×40×3 mm roof members with hood, duct and signage reinforcement
Corner posts / walls	60×60×3 mm posts with wide service-opening reinforcement
Lifting / handling	Designed MS lifting hooks or lugs matched to the completed unit weight; handle only by the approved lifting and support-point drawing.
Welding & fabrication	Welded MS fabrication with cleaned joints, safe edges, dimensional inspection and coating touch-up before panel closure and dispatch.

Walls, Roof, Floor & Insulation

COMPONENT	DETAIL
Exterior walls	1.6 mm corrugated MS structural sheet with ACP/HPL/WPC/wood-finish over-cladding
Roof	1.6 mm corrugated MS sheet
Interior walls	10–12 mm fibre-cement board with stainless-steel kitchen-zone lining
Ceiling	8–10 mm fibre-cement or 0.50 mm washable metal-liner ceiling
Floor base	24 mm cement board with waterproofing
Floor finish	Anti-skid tile, 3–4 mm PU flooring or heavy safety vinyl
Wall insulation	75 mm mineral wool
Roof insulation	100 mm mineral wool
Decorative / external finish	4 mm FR-grade ACP/HPL façade, service canopy, signage frame and stainless-steel kitchen-zone lining.
Fasteners & sealing	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.

Doors, Windows, Electrical & Services

COMPONENT	DETAIL
Main door / service door	Staff/customer door plus lockable service counter or shutter.
Windows / service opening	Large aluminium service glazing with lockable counter opening.
Grills / mosquito mesh	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.
Electrical wiring	Concealed PVC-insulated copper wiring, typically 1.5 sq.mm lighting, 2.5 sq.mm sockets and 4 sq.mm higher-load or AC circuits, subject to the final load schedule.

COMPONENT	DETAIL
Electrical protection	Distribution board with MCB/RCCB protection, earthing and segregation of lighting, socket, wet-area and AC circuits according to the approved electrical drawing.
Electrical fittings	LED lighting, signage supply, multiple 6A/16A appliance sockets, dedicated equipment circuits and DB/MCB protection.
Ventilation / AC	Exhaust-hood/duct provision, fresh-air opening and optional AC for the customer zone.
Plumbing / sanitary	Sink/handwash, CPVC water supply, UPVC waste and equipment connection points according to layout.
Layout / configuration	Front service counter with separate staff preparation and storage zones.
Painting / coating	One red-oxide primer coat followed by two compatible anti-rust enamel coats on prepared MS surfaces; project exposure may require an upgraded coating system.
Quality checks	Pre-dispatch checks cover dimensions, member and sheet identification, welds, coating, roof drainage, weather sealing, doors, windows, electrical continuity and functional operation.
Warranty	5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

Warranty and contacts

Warranty: 5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

South: +91 88616 22859 | sales@samanportable.com

North: +91 87960 39938 | ncr@samanportable.com

Generated: 08 August 2026