

Food Truck Containers - Technical Specifications and Price List

Canonical URL: <https://www.samanportable.com/product/container-cafe/food-truck-containers>

Six approved sizes and prices

SIZE	AREA (SQ FT)	COVERS	RATE EX-GST	EX-GST	INCL. 18% GST
10x10x8.5 ft	100	8 covers	INR 1,760/sq ft	INR 1,76,000	INR 2,07,680
20x8x8.5 ft	160	13 covers	INR 1,760/sq ft	INR 2,81,600	INR 3,32,288
20x10x8.5 ft	200	17 covers	INR 1,600/sq ft	INR 3,20,000	INR 3,77,600
20x12x8.5 ft	240	20 covers	INR 1,536/sq ft	INR 3,68,640	INR 4,34,995
30x10x8.5 ft	300	25 covers	INR 1,536/sq ft	INR 4,60,800	INR 5,43,744
40x10x8.5 ft	400	33 covers	INR 1,504/sq ft	INR 6,01,600	INR 7,09,888

Base specification price - customisations quoted separately. Ex-factory, ex-GST.

Steel Structure

COMPONENT	DETAIL
Bottom frame	150×75×5 mm MS C-channel with reinforced lifting and relocation zones
Bottom stiffeners	100×50×4 mm channels, 80×40×3 mm tubes and additional corner gussets
Floor frame	100×50×3 mm primary floor members
Top frame	80×40×3 mm MS top perimeter with additional lifting support
Roof stiffeners	60×40×2.5 mm roof members
Corner posts / walls	60×60×3 mm corner posts and 50×50×3 mm wall posts
Lifting / handling	Designed MS lifting hooks or lugs matched to the completed unit weight; handle only by the approved lifting and support-point drawing.
Welding & fabrication	Welded MS fabrication with cleaned joints, safe edges, dimensional inspection and coating touch-up before panel closure and dispatch.

Walls, Roof, Floor & Insulation

COMPONENT	DETAIL
Exterior walls	1.25–1.6 mm corrugated MS sheet
Roof	1.6 mm corrugated MS sheet
Interior walls	8 mm pre-laminated plywood or fibre-cement board
Ceiling	8 mm pre-laminated or fibre-cement ceiling
Floor base	18–24 mm cement board
Floor finish	2 mm commercial vinyl or anti-skid finish
Wall insulation	50 mm mineral wool
Roof insulation	75 mm mineral wool
Decorative / external finish	Lightweight ACP/HPL decorative façade with transport-safe signage and removable canopy.
Fasteners & sealing	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.

Doors, Windows, Electrical & Services

COMPONENT	DETAIL
Main door / service door	Staff/customer door plus lockable service counter or shutter.
Windows / service opening	Large aluminium service glazing with lockable counter opening.
Grills / mosquito mesh	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.
Electrical wiring	Concealed PVC-insulated copper wiring, typically 1.5 sq.mm lighting, 2.5 sq.mm sockets and 4 sq.mm higher-load or AC circuits, subject to the final load schedule.

COMPONENT	DETAIL
Electrical protection	Distribution board with MCB/RCCB protection, earthing and segregation of lighting, socket, wet-area and AC circuits according to the approved electrical drawing.
Electrical fittings	LED lighting, signage supply, multiple 6A/16A appliance sockets, dedicated equipment circuits and DB/MCB protection.
Ventilation / AC	Exhaust-hood/duct provision, fresh-air opening and optional AC for the customer zone.
Plumbing / sanitary	Sink/handwash, CPVC water supply, UPVC waste and equipment connection points according to layout.
Layout / configuration	Front service counter with separate staff preparation and storage zones. All loose items and openings require transport locking.
Painting / coating	One red-oxide primer coat followed by two compatible anti-rust enamel coats on prepared MS surfaces; project exposure may require an upgraded coating system.
Quality checks	Pre-dispatch checks cover dimensions, member and sheet identification, welds, coating, roof drainage, weather sealing, doors, windows, electrical continuity and functional operation.
Warranty	5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

Warranty and contacts

Warranty: 5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

South: +91 88616 22859 | sales@samanportable.com

North: +91 87960 39938 | ncr@samanportable.com

Generated: 08 August 2026