

# Low Cost Porta Cabin — Technical Specifications & Price List

Canonical URL: <https://www.samanportable.com/product/porta-cabins/low-cost-porta-cabin>

Newly fabricated at our own works from MS sheet, MS pipe framing and aluminium sections — not a converted shipping container.

## Sizes & Prices

| SIZE         | AREA      | RATE / SQ FT | EX-GST    | INCL. 18% GST |
|--------------|-----------|--------------|-----------|---------------|
| 10x10×8.5 ft | 100 sq ft | ₹1,320       | ₹1,32,000 | ₹1,55,760     |
| 20x8×8.5 ft  | 160 sq ft | ₹1,320       | ₹2,11,200 | ₹2,49,216     |
| 20x10×8.5 ft | 200 sq ft | ₹1,200       | ₹2,40,000 | ₹2,83,200     |
| 20x12×8.5 ft | 240 sq ft | ₹1,152       | ₹2,76,480 | ₹3,26,246     |
| 30x10×8.5 ft | 300 sq ft | ₹1,152       | ₹3,45,600 | ₹4,07,808     |
| 40x8×8.5 ft  | 320 sq ft | ₹1,128       | ₹3,60,960 | ₹4,25,933     |
| 20x20×8.5 ft | 400 sq ft | ₹1,128       | ₹4,51,200 | ₹5,32,416     |
| 40x10×8.5 ft | 400 sq ft | ₹1,128       | ₹4,51,200 | ₹5,32,416     |
| 40x12×8.5 ft | 480 sq ft | ₹1,104       | ₹5,29,920 | ₹6,25,306     |

Base specification price — customisations quoted separately. Prices are supply-only and ex-factory; freight and installation are confirmed at quotation.

## 30-row Technical Specification

Rows marked “DIFFERS” are different from the Porta Cabins reference specification.

### Steel Structure

|                       |                                                                                                                                                                                          |  |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Bottom frame          | 100×50×3 mm MS C-channel primary base frame, ISI-standard or approved equivalent, fabricated as the load-bearing chassis.                                                                |  |
| Bottom stiffeners     | 100×50 mm C-channels, 50×50 mm MS angles, 75×40 mm channels and approved square-pipe supports, typically coordinated at about 4 ft intervals to the final floor load and lifting design. |  |
| Floor frame           | MS base and cross-member grid supporting an 18 mm Bison/cement-fibre floor board fixed with approved self-tapping fasteners; spacing follows the final drawing and design load.          |  |
| Top frame             | 50×50×1.6 mm MS square-pipe top perimeter frame of approved make or equivalent.                                                                                                          |  |
| Roof stiffeners       | 50×50×1.2 mm MS square-pipe roof stiffeners with 50×40, 40×40, 50×25 or 25×25 mm secondary members where required by span, ceiling support and drainage slope.                           |  |
| Corner posts / walls  | 50×50×2 mm MS square-pipe corner and wall posts or approved 60×60 mm MS-angle alternative, with reinforced door and window openings and an approximately 60 mm wall cavity.              |  |
| Lifting / handling    | Designed MS lifting hooks or lugs matched to the completed unit weight; handle only by the approved lifting and support-point drawing.                                                   |  |
| Welding & fabrication | Welded MS fabrication with cleaned joints, safe edges, dimensional inspection and coating touch-up before panel closure and dispatch.                                                    |  |

### Walls, Roof, Floor & Insulation

|                |                                  |         |
|----------------|----------------------------------|---------|
| Exterior walls | 0.8–1.0 mm corrugated MS sheet   | DIFFERS |
| Roof           | 1.2 mm corrugated MS sheet       | DIFFERS |
| Interior walls | 6 mm pre-laminated plywood/board | DIFFERS |
| Ceiling        | 6 mm pre-laminated ceiling board | DIFFERS |
| Floor base     | 18 mm BWP plywood                | DIFFERS |
| Floor finish   | 1.5 mm vinyl flooring            | DIFFERS |

|                              |                                                                                                                                 |         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------|---------|
| Wall insulation              | 25 mm glass wool                                                                                                                | DIFFERS |
| Roof insulation              | 50 mm glass wool                                                                                                                | DIFFERS |
| Decorative / external finish | Standard anti-rust enamel exterior finish in an approved colour combination.                                                    |         |
| Fasteners & sealing          | Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it. |         |

## Doors, Windows, Electrical & Services

|                           |                                                                                                                                                                                                        |         |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Main door / service door  | 32 mm waterproof flush door with MS frame and standard hardware                                                                                                                                        | DIFFERS |
| Windows / service opening | Powder-coated aluminium sliding windows with 3 mm glass                                                                                                                                                | DIFFERS |
| Grills / mosquito mesh    | Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.                                                                        |         |
| Electrical wiring         | Concealed PVC-insulated copper wiring, typically 1.5 sq.mm lighting, 2.5 sq.mm sockets and 4 sq.mm higher-load or AC circuits, subject to the final load schedule.                                     |         |
| Electrical protection     | Distribution board with MCB/RCCB protection, earthing and segregation of lighting, socket, wet-area and AC circuits according to the approved electrical drawing.                                      |         |
| Electrical fittings       | LED lights, modular switches, 6A/16A sockets, fan points and AC provision according to the approved layout.                                                                                            |         |
| Ventilation / AC          | Natural cross ventilation with fan, exhaust and AC provision as required.                                                                                                                              |         |
| Plumbing / sanitary       | Not included unless shown in the approved scope.                                                                                                                                                       |         |
| Layout / configuration    | Open single-room layout with furniture and partitions finalized by approved drawing.                                                                                                                   |         |
| Painting / coating        | One red-oxide primer coat followed by two compatible anti-rust enamel coats on prepared MS surfaces; project exposure may require an upgraded coating system.                                          |         |
| Quality checks            | Pre-dispatch checks cover dimensions, member and sheet identification, welds, coating, roof drainage, weather sealing, doors, windows, electrical continuity and functional operation.                 |         |
| Warranty                  | Warranty period and exclusions are confirmed only in the final quotation; relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise. |         |

## Commercial & Company Facts

Warranty: 5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation.

Turnaround: Delivery in 7–21 working days; fixed-price quotation in 48 hours.

Certifications: ISO 9001:2015 · ISO 14001:2015 · ISO 45001:2018 · NSIC SPRS · Udyam UDYAM-KR-03-0172770 · ZED Bronze · DPIIT Startup India · GST registered.

Bengaluru (South): +91 88616 22859 · +91 80886 85440 · sales@samanportable.com

Greater Noida (North): +91 87960 39938 · +91 97089 89937 · ncr@samanportable.com

Generated: 26 July 2026