



SAMAN POS INDIA Pvt. Ltd.

Our Solutions that are portable...

Fabricating Specifications for MS Fabricated Portable Cabin ANNEXURE - 1,

Sl. No.	Components	Descriptions
1	Bottom Frame	125x65 mm formed GI Channel of 3mm thick.
2	Stiffener Bottom	100X50 C Channel, 100x50mm, 80x40mm & 50x50mm MS Square pipes.
3	Top Frame	Frame made of 50x50mm MS square pipes.
4	Stiffener Top	50x50 mm, 40x40 mm, 50x25mm & 25x25mm MS Square pipes.
5	Side Wall Stiffeners	The paneling of side walls and roof shall be of 8 mm MDF Board & all vertically and horizontal corners shall be neatly & smoothly finished with Aluminum sections.
6	Paneling Outside	Specially corrugated GI sheet 1.2mm thick sheet welded on MS frame
7	Internal Wall Paneling	The paneling of side walls and roof shall be of 8mm MDF boards with Patti Paint & all vertically and horizontal corners shall be neatly & smoothly finished with patti paint.
8	Roof Outside	1.2mm thick GI sheet properly one way sloped & water tight.
9	Bottom Flooring	On the bottom frame 18 mm thick Bison panel i.e. Cemented bonded fiber sheets shall be fixed by means of self-taping screw & 1.3 mm thick PVC vinyl Carpet shall be fixed on the panel. (100% water, termite & dimensional proof with vinyl Carpet)
10	Windows Size:4'x3'	Aluminium sliding with safety grill and 4mm tinted glass & 4" canopy for all side windows and door
11	Main Doors Size:7'x3'	The door shall be of external opening type made out of the same material as wall panels & canopy above the door. Frame work by tubular pipe of 30 x 30 & the door interior shall be finished with same material matching with that of the Cabin interior. Door with std hardware locks & handles
12	Insulation	50mm Glass wool density of 24 kg/m ³ with insulation for top & 25 mm density of 16 kg/m ³ or 8-10mm Heatlon and Foam
13	Wiring	All wiring shall be concealed and shall be PVC insulated copper wires of ISI quality, suitable for 240 volt, 50 HZ single phase AC power supply. 1mm & 2.5 mm thick cable for lighting, 5amp switches with 3pin Sockets, bulk head light above the door, 4mm thick cable for main electrical supply & with MCB protection.
14	Electrical Fittings	All electrical fittings in the portable cabin shall be 220-240V. · LED Tube light – As per drawing. · Bulk head door light – As per drawing. · Cabin Fans – As per drawing. · 3pin Socket with Switchboard – As per drawing. · Split AC Provisions –
15	Painting	All components are painted with a coat of primer & 2 coats of corrosion free paint i.e. synthetic enamel paint.
16	Hooks	Specially formed for easy lift & shift.