

Porta Cabin — Technical Specifications & Price List

Factory-built MS corrugated cabins · Bengaluru & Greater Noida · samanportable.com

Every SAMAN porta cabin is factory-fabricated on a welded mild-steel frame at our Bengaluru and Greater Noida units. The specification below is our standard build — the same sheet we submit for tenders and client approvals. Anything not listed is confirmed at quotation.

Sizes & Prices (ex-GST, base specification)

Size	Dimensions	Area (sq ft)	Capacity	Price (Rs, ex-GST)
10×10 ft	10×10×8.5 ft	100	2–3 people	1,37,500
20×8 ft	20×8×8.5 ft	160	3–4 people	2,20,000
20×10 ft	20×10×8.5 ft	200	4–6 people	2,50,000
20×12 ft	20×12×8.5 ft	240	5–7 people	2,88,000
30×10 ft	30×10×8.5 ft	300	6–8 people	3,60,000
40×8 ft	40×8×8.5 ft	320	7–9 people	3,76,000
20×20 ft	20×20×8.5 ft	400	8–10 people	4,70,000
40×10 ft	40×10×8.5 ft	400	8–10 people	4,70,000
40×12 ft	40×12×8.5 ft	480	10–12 people	5,52,000

Prices are complete-cabin base-specification prices (roughly Rs 1,150–1,375 per sq ft ex-GST). GST 18% extra · HSN 9406 (prefabricated buildings). Customisations, interior fit-out, transport and installation are quoted separately. Delivery and erection across South & North India in 7–21 working days. 5-year structural warranty; 1–2 years on finishing.

Steel Structure

Component	Section / Size / Material
Bottom frame	100×50×3 mm MS C-channel
Bottom stiffeners	100×50 mm C-channels, 50×50 mm MS angles, 75×40 mm channels and MS square pipes
Floor frame	100×50, 80×40 and 50×50 mm MS square pipes as required
Top frame	50×50×1.6 mm MS square-pipe top frame
Roof stiffeners	50×50×1.2 mm plus 50×40, 40×40, 50×25 and 25×25 mm MS members
Corner posts / walls	50×50×2 mm MS square-pipe posts or 60×60 mm MS angles
Lifting hooks	As per approved cabin weight and lifting design
Welding & fabrication	As per approved fabrication drawing

Walls, Roof, Floor & Insulation

Component	Section / Size / Material
Exterior walls	1.2 mm specially corrugated MS sheet
Roof	1.4 mm corrugated MS sheet
Interior walls	8 mm pre-laminated MDF board with aluminium joint sections
Ceiling	8 mm pre-laminated MDF ceiling
Floor base	18 mm Bison panel
Floor finish	1.3 mm vinyl flooring
Wall insulation	25 mm glass wool or 12 mm heaton
Roof insulation	50 mm glass wool, nominal density 42 kg/m³

Component	Section / Size / Material
Decorative / external finish	Standard anti-rust enamel exterior finish in an approved colour combination.
Fasteners & sealing	As required

Doors, Windows, Electrical & Services

Component	Section / Size / Material
Main door / service door	7×3 ft externally opening MS-framed door using 30×30 mm MS tubular sections
Windows / service opening	Two-track powder-coated aluminium sliding windows with 4 mm glass
Grills / mosquito mesh	MS safety grill and mosquito mesh selectable according to site requirements.
Electrical wiring	1.5 sq.mm lighting; 2.5 sq.mm sockets; 4 sq.mm AC/high-load circuits
Electrical protection	Circuit rating as per final load schedule
Electrical fittings	LED lights, modular switches, 6A/16A sockets, fan points and AC provision according to the approved layout.
Ventilation / AC	Natural cross ventilation with fan, exhaust and AC provision as required.
Plumbing / sanitary	Not included unless shown in the approved scope.
Layout / configuration	Open single-room layout with furniture and partitions finalized by approved drawing.
Painting	1 primer coat + 2 enamel coats
Quality checks	Checklist basis
Warranty	12 months unless otherwise agreed

Get a fixed-price quote in 48 hours

South — Bengaluru: +91 88616 22859 · sales@samanportable.com | North — Greater Noida: +91 87960 39938 · ncr@samanportable.com

SAMAN POS India Private Limited · GSTIN (KA) 29ABBCS7101B1ZR · GSTIN (UP) 09ABBCS7101B1ZT · www.samanportable.com