🛒 MeserBazar — Complete Project Blueprint
> Zatiqeasy-এর মতো Website Builder SaaS | সম্পূর্ণ Free Stack

---

📦 Tech Stack (সব Free)

Layer	Tool	Free Limit
Frontend Framework	**Next.js 14 (App Router)**	—
Hosting	**Firebase Hosting**	10GB/month
Database	**Firebase Firestore**	1GB storage, 50k reads/day
Auth	**Firebase Auth**	10k users/month
File Storage	**Firebase Storage**	5GB
Domain	`meserbazar.web.app`	Free forever
Custom Domain	`meserbazar.com` (পরে)	তোমার কেনা

🏗️ Architecture

```
meserbazar.web.app/            ← Landing Page (public)
meserbazar.web.app/login       ← User Login
meserbazar.web.app/register    ← User Register
meserbazar.web.app/dashboard   ← User Dashboard (shop admin)
meserbazar.web.app/superadmin  ← Super Admin Panel (তুমি)

── Sister Sites (Firestore-based routing) ──
meserbazar.web.app/shop/[shopSlug]  ← প্রতিটি user এর দোকান
                                      (subdomain পরে)
```

📁 Full Folder Structure

```
meserbazar/
├── .env.local                  ← Firebase config (secret)
├── .firebaserc                 ← Firebase project link
├── firebase.json               ← Hosting + Firestore rules
├── firestore.rules             ← DB security rules
├── firestore.indexes.json      ← DB indexes
├── next.config.js              ← Next.js config
├── package.json
├── tailwind.config.js
├── postcss.config.js
│
├── public/
│   └── logo.svg
│
└── src/
    ├── app/
    │   ├── layout.js           ← Root layout
    │   ├── page.js             ← Landing page (/)
    │   ├── globals.css
    │   │
    │   ├── (auth)/
    │   │   ├── login/
    │   │   │   └── page.js
    │   │   └── register/
    │   │       └── page.js
    │   │
    │   ├── dashboard/          ← User Shop Admin
    │   │   ├── layout.js
    │   │   ├── page.js         ← Dashboard home
    │   │   ├── products/
    │   │   │   ├── page.js     ← All products
    │   │   │   └── new/
    │   │   │       └── page.js ← Add product
    │   │   ├── orders/
    │   │   │   └── page.js
```

```
│   │   ├── customers/
│   │   │   └── page.js
│   │   ├── categories/
│   │   │   └── page.js
│   │   ├── settings/
│   │   │   └── page.js          ← Shop settings + domain
│   │   ├── analytics/
│   │   │   └── page.js
│   │   └── billing/
│   │       └── page.js
│   │
│   ├── superadmin/              ← Super Admin (তুমি)
│   │   ├── layout.js
│   │   ├── page.js              ← All shops overview
│   │   ├── users/
│   │   │   └── page.js
│   │   └── settings/
│   │       └── page.js
│   │
│   └── shop/
│       └── [shopSlug]/          ← Sister site (public store)
│           ├── page.js          ← Shop home
│           ├── product/
│           │   └── [productId]/
│           │       └── page.js
│           └── cart/
│               └── page.js
│
├── components/
│   ├── ui/
│   │   ├── Button.jsx
│   │   ├── Input.jsx
│   │   ├── Modal.jsx
│   │   ├── Card.jsx
│   │   └── Badge.jsx
│   ├── dashboard/
│   │   ├── Sidebar.jsx
```

```
│   │   ├── Header.jsx
│   │   ├── QuickActions.jsx
│   │   ├── AnalyticsCard.jsx
│   │   └── ProductCard.jsx
│   ├── shop/
│   │   ├── ShopHeader.jsx
│   │   ├── ProductGrid.jsx
│   │   ├── CartDrawer.jsx
│   │   └── OrderForm.jsx
│   └── landing/
│       ├── Hero.jsx
│       ├── Features.jsx
│       └── Pricing.jsx
│
├── lib/
│   ├── firebase.js          ← Firebase init
│   ├── firestore.js         ← DB helpers
│   ├── auth.js              ← Auth helpers
│   └── storage.js           ← File upload helpers
│
├── hooks/
│   ├── useAuth.js
│   ├── useShop.js
│   └── useProducts.js
│
└── context/
    ├── AuthContext.jsx
    └── ShopContext.jsx
```

📄 সব ফাইলের কোড

---

1. `package.json`

```json
{
  "name": "meserbazar",
  "version": "0.1.0",
  "private": true,
  "scripts": {
    "dev": "next dev",
    "build": "next build",
    "start": "next start",
    "deploy": "next build && firebase deploy"
  },
  "dependencies": {
    "next": "14.2.3",
    "react": "^18",
    "react-dom": "^18",
    "firebase": "^10.12.0",
    "react-hot-toast": "^2.4.1",
    "lucide-react": "^0.383.0",
    "clsx": "^2.1.1"
  },
  "devDependencies": {
    "tailwindcss": "^3.4.1",
    "postcss": "^8",
    "autoprefixer": "^10.0.1",
    "eslint": "^8",
    "eslint-config-next": "14.2.3"
  }
}
```

---

2. `.env.local` (তোমার Firebase values দিয়ে replace করো)

```env
NEXT_PUBLIC_FIREBASE_API_KEY=your_api_key
```

```
NEXT_PUBLIC_FIREBASE_AUTH_DOMAIN=your_project.firebaseapp.com
NEXT_PUBLIC_FIREBASE_PROJECT_ID=your_project_id
NEXT_PUBLIC_FIREBASE_STORAGE_BUCKET=your_project.appspot.com
NEXT_PUBLIC_FIREBASE_MESSAGING_SENDER_ID=your_sender_id
NEXT_PUBLIC_FIREBASE_APP_ID=your_app_id

NEXT_PUBLIC_SITE_URL=https://meserbazar.web.app
NEXT_PUBLIC_SHOP_BASE_URL=https://meserbazar.web.app/shop
NEXT_PUBLIC_SUPER_ADMIN_EMAIL=your@email.com
```

---

3. `next.config.js`

```js
/** @type {import('next').NextConfig} */
const nextConfig = {
  images: {
    domains: ['firebasestorage.googleapis.com'],
  },
  output: 'export', // Static export for Firebase Hosting
}

module.exports = nextConfig
```

---

4. `firebase.json`

```json
{
  "hosting": {
    "public": "out",
    "ignore": ["firebase.json", "**/.*", "**/node_modules/**"],
    "rewrites": [
```

```
    {
      "source": "**",
      "destination": "/index.html"
    }
  ],
  "headers": [
    {
      "source": "**/*.@(js|css)",
      "headers": [{"key": "Cache-Control", "value": "max-age=31536000"}]
    }
  ]
},
"firestore": {
  "rules": "firestore.rules",
  "indexes": "firestore.indexes.json"
}
}
```

---

5. `.firebaserc`

```json
{
  "projects": {
    "default": "your-firebase-project-id"
  }
}
```

---

6. `firestore.rules`

```
rules_version = '2';
```

```
service cloud.firestore {
  match /databases/{database}/documents {

    // Users collection
    match /users/{userId} {
      allow read, write: if request.auth != null && request.auth.uid == userId;
    }

    // Shops collection
    match /shops/{shopId} {
      allow read: if true; // Public read for shop pages
      allow write: if request.auth != null &&
        (request.auth.uid == resource.data.ownerId ||
         get(/databases/$(database)/documents/users/$(request.auth.uid)).data.role ==
'superadmin');
    }

    // Products collection
    match /shops/{shopId}/products/{productId} {
      allow read: if true;
      allow write: if request.auth != null &&
        get(/databases/$(database)/documents/shops/$(shopId)).data.ownerId == request.auth.uid;
    }

    // Orders collection
    match /shops/{shopId}/orders/{orderId} {
      allow read: if request.auth != null &&
        get(/databases/$(database)/documents/shops/$(shopId)).data.ownerId == request.auth.uid;
      allow create: if true; // Anyone can place order
    }

    // Categories
    match /shops/{shopId}/categories/{categoryId} {
      allow read: if true;
      allow write: if request.auth != null &&
        get(/databases/$(database)/documents/shops/$(shopId)).data.ownerId == request.auth.uid;
    }
```

```
  }
}
```

---

7. `firestore.indexes.json`

```json
{
  "indexes": [
    {
      "collectionGroup": "products",
      "queryScope": "COLLECTION",
      "fields": [
        {"fieldPath": "shopId", "order": "ASCENDING"},
        {"fieldPath": "createdAt", "order": "DESCENDING"}
      ]
    },
    {
      "collectionGroup": "orders",
      "queryScope": "COLLECTION",
      "fields": [
        {"fieldPath": "shopId", "order": "ASCENDING"},
        {"fieldPath": "createdAt", "order": "DESCENDING"}
      ]
    }
  ],
  "fieldOverrides": []
}
```

---

8. `tailwind.config.js`

```js
```

```
/** @type {import('tailwindcss').Config} */
module.exports = {
  content: [
    './src/pages/**/*.{js,ts,jsx,tsx,mdx}',
    './src/components/**/*.{js,ts,jsx,tsx,mdx}',
    './src/app/**/*.{js,ts,jsx,tsx,mdx}',
  ],
  theme: {
    extend: {
      colors: {
        primary: {
          50: '#f0f0ff',
          500: '#5533FF',
          600: '#4422ee',
          700: '#3311dd',
        }
      },
      fontFamily: {
        sans: ['var(--font-inter)'],
      }
    },
  },
  plugins: [],
}
```

---

9. `src/lib/firebase.js`

```js
import { initializeApp, getApps } from 'firebase/app'
import { getAuth } from 'firebase/auth'
import { getFirestore } from 'firebase/firestore'
import { getStorage } from 'firebase/storage'

const firebaseConfig = {
```

```
  apiKey: process.env.NEXT_PUBLIC_FIREBASE_API_KEY,
  authDomain: process.env.NEXT_PUBLIC_FIREBASE_AUTH_DOMAIN,
  projectId: process.env.NEXT_PUBLIC_FIREBASE_PROJECT_ID,
  storageBucket: process.env.NEXT_PUBLIC_FIREBASE_STORAGE_BUCKET,
  messagingSenderId: process.env.NEXT_PUBLIC_FIREBASE_MESSAGING_SENDER_ID,
  appId: process.env.NEXT_PUBLIC_FIREBASE_APP_ID,
}

const app = getApps().length === 0 ? initializeApp(firebaseConfig) : getApps()[0]

export const auth = getAuth(app)
export const db = getFirestore(app)
export const storage = getStorage(app)
export default app
```

---

10. `src/lib/auth.js`

```js
import {
  createUserWithEmailAndPassword,
  signInWithEmailAndPassword,
  signOut,
  onAuthStateChanged,
} from 'firebase/auth'
import { doc, setDoc, getDoc, serverTimestamp } from 'firebase/firestore'
import { auth, db } from './firebase'

export const registerUser = async (email, password, name) => {
  const userCredential = await createUserWithEmailAndPassword(auth, email, password)
  const user = userCredential.user

  // Create user document in Firestore
  await setDoc(doc(db, 'users', user.uid), {
    uid: user.uid,
```

```
    email,
    name,
    role: email === process.env.NEXT_PUBLIC_SUPER_ADMIN_EMAIL ? 'superadmin' : 'user',
    createdAt: serverTimestamp(),
    subscription: 'free',
  })

  // Auto-create a shop for the user
  const shopSlug = name.toLowerCase().replace(/\s+/g, '-') + '-' + Date.now()
  await setDoc(doc(db, 'shops', user.uid), {
    ownerId: user.uid,
    shopName: name + "'s Shop",
    shopSlug,
    description: '',
    logoUrl: '',
    bannerUrl: '',
    // Domain settings
    subdomainSlug: shopSlug,        // meserbazar.web.app/shop/[slug]
    customSubdomain: '',            // user.meserbazar.com (পরে)
    customDomain: '',               // user's own domain (পরে)
    domainType: 'platform',         // 'platform' | 'customSubdomain' | 'customDomain'
    // Shop config
    currency: 'BDT',
    phone: '',
    address: '',
    isActive: true,
    isLive: true,
    // Stats
    totalOrders: 0,
    totalRevenue: 0,
    createdAt: serverTimestamp(),
  })

  return user
}

export const loginUser = (email, password) =>
```

```
  signInWithEmailAndPassword(auth, email, password)

export const logoutUser = () => signOut(auth)

export const getCurrentUser = () => auth.currentUser

export const getUserData = async (uid) => {
  const snap = await getDoc(doc(db, 'users', uid))
  return snap.exists() ? snap.data() : null
}

export const onAuthChange = (callback) =>
  onAuthStateChanged(auth, callback)
```

---

11. `src/lib/firestore.js`

```js
import {
  collection, doc, addDoc, setDoc, getDoc, getDocs,
  updateDoc, deleteDoc, query, where, orderBy,
  limit, serverTimestamp, onSnapshot,
} from 'firebase/firestore'
import { db } from './firebase'

// ── SHOP ──────────────────────────────────────────────────────────
export const getShop = async (shopId) => {
  const snap = await getDoc(doc(db, 'shops', shopId))
  return snap.exists() ? { id: snap.id, ...snap.data() } : null
}

export const getShopBySlug = async (slug) => {
  const q = query(collection(db, 'shops'), where('shopSlug', '==', slug))
  const snap = await getDocs(q)
  if (snap.empty) return null
```

```
  return { id: snap.docs[0].id, ...snap.docs[0].data() }
}

export const updateShop = async (shopId, data) =>
  updateDoc(doc(db, 'shops', shopId), { ...data, updatedAt: serverTimestamp() })

export const getAllShops = async () => {
  const snap = await getDocs(collection(db, 'shops'))
  return snap.docs.map(d => ({ id: d.id, ...d.data() }))
}

// ── PRODUCTS ──────────────────────────────────────────────────────────
export const getProducts = async (shopId) => {
  const q = query(
    collection(db, 'shops', shopId, 'products'),
    orderBy('createdAt', 'desc')
  )
  const snap = await getDocs(q)
  return snap.docs.map(d => ({ id: d.id, ...d.data() }))
}

export const addProduct = async (shopId, productData) =>
  addDoc(collection(db, 'shops', shopId, 'products'), {
    ...productData,
    shopId,
    createdAt: serverTimestamp(),
  })

export const updateProduct = async (shopId, productId, data) =>
  updateDoc(doc(db, 'shops', shopId, 'products', productId), {
    ...data,
    updatedAt: serverTimestamp(),
  })

export const deleteProduct = async (shopId, productId) =>
  deleteDoc(doc(db, 'shops', shopId, 'products', productId))
```

```
// ── CATEGORIES ──────────────────────────────────────────────
export const getCategories = async (shopId) => {
  const snap = await getDocs(collection(db, 'shops', shopId, 'categories'))
  return snap.docs.map(d => ({ id: d.id, ...d.data() }))
}

export const addCategory = async (shopId, data) =>
  addDoc(collection(db, 'shops', shopId, 'categories'), {
    ...data,
    createdAt: serverTimestamp(),
  })

export const deleteCategory = async (shopId, categoryId) =>
  deleteDoc(doc(db, 'shops', shopId, 'categories', categoryId))

// ── ORDERS ──────────────────────────────────────────────────
export const getOrders = async (shopId) => {
  const q = query(
    collection(db, 'shops', shopId, 'orders'),
    orderBy('createdAt', 'desc')
  )
  const snap = await getDocs(q)
  return snap.docs.map(d => ({ id: d.id, ...d.data() }))
}

export const placeOrder = async (shopId, orderData) =>
  addDoc(collection(db, 'shops', shopId, 'orders'), {
    ...orderData,
    shopId,
    status: 'pending',
    createdAt: serverTimestamp(),
  })

export const updateOrderStatus = async (shopId, orderId, status) =>
  updateDoc(doc(db, 'shops', shopId, 'orders', orderId), { status })

// ── CUSTOMERS ───────────────────────────────────────────────
```

```
export const getCustomers = async (shopId) => {
  const snap = await getDocs(collection(db, 'shops', shopId, 'customers'))
  return snap.docs.map(d => ({ id: d.id, ...d.data() }))
}

// ── REALTIME ──────────────────────────────────────────────────────────
export const subscribeOrders = (shopId, callback) =>
  onSnapshot(
    query(collection(db, 'shops', shopId, 'orders'), orderBy('createdAt', 'desc'), limit(50)),
    snap => callback(snap.docs.map(d => ({ id: d.id, ...d.data() })))
  )
```

---

12. `src/lib/storage.js`

```js
import { ref, uploadBytes, getDownloadURL, deleteObject } from 'firebase/storage'
import { storage } from './firebase'

export const uploadImage = async (file, path) => {
  const storageRef = ref(storage, path)
  const snapshot = await uploadBytes(storageRef, file)
  return getDownloadURL(snapshot.ref)
}

export const uploadProductImage = async (shopId, file) => {
  const path = `shops/${shopId}/products/${Date.now()}_${file.name}`
  return uploadImage(file, path)
}

export const uploadShopLogo = async (shopId, file) => {
  const path = `shops/${shopId}/logo_${Date.now()}`
  return uploadImage(file, path)
}
```

---

13. `src/context/AuthContext.jsx`

```jsx
'use client'
import { createContext, useContext, useEffect, useState } from 'react'
import { onAuthChange, getUserData } from '@/lib/auth'

const AuthContext = createContext({})

export function AuthProvider({ children }) {
  const [user, setUser] = useState(null)
  const [userData, setUserData] = useState(null)
  const [loading, setLoading] = useState(true)

  useEffect(() => {
    const unsub = onAuthChange(async (firebaseUser) => {
      setUser(firebaseUser)
      if (firebaseUser) {
        const data = await getUserData(firebaseUser.uid)
        setUserData(data)
      } else {
        setUserData(null)
      }
      setLoading(false)
    })
    return unsub
  }, [])

  return (
    <AuthContext.Provider value={{ user, userData, loading }}>
      {children}
    </AuthContext.Provider>
  )
}
```

```
export const useAuth = () => useContext(AuthContext)
```

---

14. `src/app/layout.js`

```jsx
import { Inter } from 'next/font/google'
import './globals.css'
import { AuthProvider } from '@/context/AuthContext'
import { Toaster } from 'react-hot-toast'

const inter = Inter({ subsets: ['latin'], variable: '--font-inter' })

export const metadata = {
  title: 'MeserBazar — আপনার অনলাইন দোকান',
  description: 'সহজে অনলাইন দোকান খুলুন। বিনামূল্যে শুরু করুন।',
}

export default function RootLayout({ children }) {
  return (
    <html lang="bn">
      <body className={inter.variable}>
        <AuthProvider>
          {children}
          <Toaster position="top-right" />
        </AuthProvider>
      </body>
    </html>
  )
}
```

---

15. `src/app/globals.css`

```css
@tailwind base;
@tailwind components;
@tailwind utilities;

:root {
  --primary: #5533FF;
  --primary-dark: #4422ee;
}

* {
  box-sizing: border-box;
  padding: 0;
  margin: 0;
}

body {
  font-family: var(--font-inter), sans-serif;
  background: #f8f8ff;
  color: #1a1a2e;
}

.btn-primary {
  @apply bg-[#5533FF] text-white px-4 py-2 rounded-lg font-medium hover:bg-[#4422ee] transition-colors;
}

.card {
  @apply bg-white rounded-2xl shadow-sm border border-gray-100 p-4;
}
```

---

16. `src/app/page.js` — Landing Page

```jsx
'use client'
import Link from 'next/link'
import { ShoppingBag, BarChart2, Globe, Zap } from 'lucide-react'

export default function LandingPage() {
  return (
    <div className="min-h-screen bg-white">
      {/* Navbar */}
      <nav className="flex items-center justify-between px-6 py-4 border-b border-gray-100">
        <div className="flex items-center gap-2">
          <div className="w-8 h-8 bg-[#5533FF] rounded-lg flex items-center justify-center">
            <span className="text-white font-bold text-sm">M</span>
          </div>
          <span className="font-bold text-lg">MeserBazar</span>
        </div>
        <div className="flex gap-3">
          <Link href="/login" className="px-4 py-2 text-gray-600 hover:text-[#5533FF] transition-
colors">
            লগিন
          </Link>
          <Link href="/register" className="btn-primary text-sm">
            ফ্রি শুরু করুন
          </Link>
        </div>
      </nav>

      {/* Hero */}
      <section className="text-center py-20 px-6 bg-gradient-to-b from-[#f0f0ff] to-white">
        <div className="inline-block bg-[#5533FF]/10 text-[#5533FF] text-xs px-3 py-1 rounded-full
mb-4 font-medium">
          🚀 বিনামূল্যে শুরু করুন
        </div>
        <h1 className="text-4xl md:text-5xl font-bold text-gray-900 mb-4 leading-tight">
          আপনার অনলাইন দোকান<br />
          <span className="text-[#5533FF]">মিনিটেই তৈরি</span>
```

```
    </h1>
    <p className="text-gray-500 text-lg mb-8 max-w-md mx-auto">
      পণ্য যোগ করুন, অর্ডার নিন, কাস্টমার ম্যানেজ করুন — সব এক জায়গায়।
    </p>
    <Link href="/register" className="btn-primary text-base px-8 py-3 rounded-xl">
      এখনই দোকান খুলুন →
    </Link>
  </section>

  {/* Features */}
  <section className="py-16 px-6 max-w-4xl mx-auto">
    <h2 className="text-2xl font-bold text-center mb-10">কী কী পাবেন?</h2>
    <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
      {[
        { icon: ShoppingBag, title: 'প্রোডাক্ট ম্যানেজ', desc: 'সহজে পণ্য যোগ করুন' },
        { icon: BarChart2, title: 'Analytics', desc: 'বিক্রির রিপোর্ট দেখুন' },
        { icon: Globe, title: 'নিজের সাইট', desc: 'ফ্রি সাবডোমেইন' },
        { icon: Zap, title: 'দ্রুত অর্ডার', desc: 'রিয়েলটাইম নোটিফিকেশন' },
      ].map(({ icon: Icon, title, desc }) => (
        <div key={title} className="card text-center">
          <div className="w-10 h-10 bg-[#5533FF]/10 rounded-xl flex items-center justify-center mx-
auto mb-3">
            <Icon className="w-5 h-5 text-[#5533FF]" />
          </div>
          <p className="font-semibold text-sm">{title}</p>
          <p className="text-gray-400 text-xs mt-1">{desc}</p>
        </div>
      ))}
    </div>
  </section>

  {/* Pricing */}
  <section className="py-16 px-6 bg-gray-50 text-center">
    <h2 className="text-2xl font-bold mb-2">মূল্য পরিকল্পনা</h2>
    <p className="text-gray-500 mb-8">শুরুতে সম্পূর্ণ বিনামূল্যে</p>
    <div className="max-w-xs mx-auto card border-2 border-[#5533FF]">
      <div className="text-[#5533FF] font-bold text-xl mb-1">ফ্রি প্ল্যান</div>
```

```
        <div className="text-3xl font-bold mb-4">৳০ <span className="text-sm text-gray-400">/
মাস</span></div>
        <ul className="text-sm text-gray-600 space-y-2 mb-6 text-left">
          {['পণ্য যোগ করুন', 'অর্ডার ম্যানেজ', 'ফ্রি সাবডোমেইন', 'Analytics'].map(f => (
            <li key={f} className="flex items-center gap-2">
              <span className="text-green-500">✓</span> {f}
            </li>
          ))}
        </ul>
        <Link href="/register" className="btn-primary w-full block text-center py-3 rounded-xl">
          শুরু করুন
        </Link>
      </div>
    </section>

    {/* Footer */}
    <footer className="text-center py-8 text-gray-400 text-sm border-t">
      © 2026 MeserBazar. Powered by Firebase + Next.js
    </footer>
  </div>
 )
}
```

---

17. `src/app/(auth)/register/page.js`

```jsx
'use client'
import { useState } from 'react'
import { useRouter } from 'next/navigation'
import Link from 'next/link'
import { registerUser } from '@/lib/auth'
import toast from 'react-hot-toast'

export default function RegisterPage() {
```

```
  const router = useRouter()
  const [form, setForm] = useState({ name: '', email: '', password: '' })
  const [loading, setLoading] = useState(false)

  const handleSubmit = async (e) => {
    e.preventDefault()
    setLoading(true)
    try {
      await registerUser(form.email, form.password, form.name)
      toast.success('দোকান তৈরি হয়েছে! 🎉')
      router.push('/dashboard')
    } catch (err) {
      toast.error(err.message)
    } finally {
      setLoading(false)
    }
  }

  return (
    <div className="min-h-screen flex items-center justify-center bg-gradient-to-b from-[#f0f0ff] to-
white p-4">
      <div className="w-full max-w-sm card border border-[#5533FF]/20">
        <div className="text-center mb-6">
          <div className="w-12 h-12 bg-[#5533FF] rounded-2xl flex items-center justify-center mx-auto
mb-3">
            <span className="text-white font-bold text-xl">M</span>
          </div>
          <h1 className="text-xl font-bold">দোকান খুলুন বিনামূল্যে</h1>
          <p className="text-gray-400 text-sm">MeserBazar-এ যোগ দিন</p>
        </div>

        <form onSubmit={handleSubmit} className="space-y-4">
          <div>
            <label className="text-sm font-medium text-gray-700 block mb-1">আপনার নাম</label>
            <input
              type="text"
              required
```

```
          value={form.name}
          onChange={e => setForm({...form, name: e.target.value})}
          placeholder="যেমন: Rahim Uddin"
          className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF] focus:ring-1 focus:ring-[#5533FF]"
        />
      </div>
      <div>
        <label className="text-sm font-medium text-gray-700 block mb-1">ইমেইল</label>
        <input
          type="email"
          required
          value={form.email}
          onChange={e => setForm({...form, email: e.target.value})}
          placeholder="email@example.com"
          className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF] focus:ring-1 focus:ring-[#5533FF]"
        />
      </div>
      <div>
        <label className="text-sm font-medium text-gray-700 block mb-1">পাসওয়ার্ড</label>
        <input
          type="password"
          required
          value={form.password}
          onChange={e => setForm({...form, password: e.target.value})}
          placeholder="কমপক্ষে ৬ অক্ষর"
          className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF] focus:ring-1 focus:ring-[#5533FF]"
        />
      </div>
      <button
        type="submit"
        disabled={loading}
        className="btn-primary w-full py-3 rounded-xl text-base disabled:opacity-50"
      >
        {loading ? 'তৈরি হচ্ছে...' : 'দোকান তৈরি করুন →'}
```

```
        </button>
      </form>

      <p className="text-center text-sm text-gray-400 mt-4">
        আগে থেকে আছেন?{' '}
        <Link href="/login" className="text-[#5533FF] font-medium">লগিন করুন</Link>
      </p>
    </div>
  </div>
 )
}
```

---

18. `src/app/(auth)/login/page.js`

```jsx
'use client'
import { useState } from 'react'
import { useRouter } from 'next/navigation'
import Link from 'next/link'
import { loginUser } from '@/lib/auth'
import toast from 'react-hot-toast'

export default function LoginPage() {
  const router = useRouter()
  const [form, setForm] = useState({ email: '', password: '' })
  const [loading, setLoading] = useState(false)

  const handleSubmit = async (e) => {
    e.preventDefault()
    setLoading(true)
    try {
      await loginUser(form.email, form.password)
      const isSuperAdmin = form.email === process.env.NEXT_PUBLIC_SUPER_ADMIN_EMAIL
      router.push(isSuperAdmin ? '/superadmin' : '/dashboard')
```

```
    } catch (err) {
      toast.error('ইমেইল বা পাসওয়ার্ড ভুল')
    } finally {
      setLoading(false)
    }
  }

  return (
    <div className="min-h-screen flex items-center justify-center bg-gradient-to-b from-[#f0f0ff] to-
white p-4">
      <div className="w-full max-w-sm card border border-[#5533FF]/20">
        <div className="text-center mb-6">
          <div className="w-12 h-12 bg-[#5533FF] rounded-2xl flex items-center justify-center mx-auto
mb-3">
            <span className="text-white font-bold text-xl">M</span>
          </div>
          <h1 className="text-xl font-bold">আবার স্বাগতম!</h1>
          <p className="text-gray-400 text-sm">আপনার দোকানে প্রবেশ করুন</p>
        </div>

        <form onSubmit={handleSubmit} className="space-y-4">
          <div>
            <label className="text-sm font-medium text-gray-700 block mb-1">ইমেইল</label>
            <input
              type="email"
              required
              value={form.email}
              onChange={e => setForm({...form, email: e.target.value})}
              className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none
focus:border-[#5533FF] focus:ring-1 focus:ring-[#5533FF]"
            />
          </div>
          <div>
            <label className="text-sm font-medium text-gray-700 block mb-1">পাসওয়ার্ড</label>
            <input
              type="password"
              required
```

```
            value={form.password}
            onChange={e => setForm({...form, password: e.target.value})}
            className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none
focus:border-[#5533FF] focus:ring-1 focus:ring-[#5533FF]"
          />
        </div>
        <button
          type="submit"
          disabled={loading}
          className="btn-primary w-full py-3 rounded-xl text-base disabled:opacity-50"
        >
          {loading ? 'লগিন হচ্ছে...' : 'লগিন করুন →'}
        </button>
      </form>

      <p className="text-center text-sm text-gray-400 mt-4">
        নতুন?{' '}
        <Link href="/register" className="text-[#5533FF] font-medium">বিনামূল্যে শুরু করুন</Link>
      </p>
    </div>
  </div>
  )
}
```

---

19. `src/app/dashboard/layout.js`

```jsx
'use client'
import { useEffect } from 'react'
import { useRouter } from 'next/navigation'
import { useAuth } from '@/context/AuthContext'
import Sidebar from '@/components/dashboard/Sidebar'

export default function DashboardLayout({ children }) {
```

```
  const { user, loading } = useAuth()
  const router = useRouter()

  useEffect(() => {
    if (!loading && !user) router.push('/login')
  }, [user, loading, router])

  if (loading) return (
    <div className="min-h-screen flex items-center justify-center">
      <div className="w-8 h-8 border-4 border-[#5533FF] border-t-transparent rounded-full animate-
spin" />
    </div>
  )

  if (!user) return null

  return (
    <div className="flex min-h-screen bg-gray-50">
      <Sidebar />
      <main className="flex-1 overflow-auto">
        {children}
      </main>
    </div>
  )
}
```

---

20. `src/components/dashboard/Sidebar.jsx`

```jsx
'use client'
import Link from 'next/link'
import { usePathname, useRouter } from 'next/navigation'
import {
  Home, Package, ShoppingCart, Users, Tag,
```

```
  Store, BarChart2, CreditCard, HelpCircle, LogOut, Settings
} from 'lucide-react'
import { logoutUser } from '@/lib/auth'
import { clsx } from 'clsx'

const navItems = [
  { href: '/dashboard', icon: Home, label: 'হোম' },
  { href: '/dashboard/products', icon: Package, label: 'Products' },
  { href: '/dashboard/orders', icon: ShoppingCart, label: 'Orders' },
  { href: '/dashboard/customers', icon: Users, label: 'Customers' },
  { href: '/dashboard/categories', icon: Tag, label: 'Categories' },
  { href: '/dashboard/analytics', icon: BarChart2, label: 'Analytics' },
  { href: '/dashboard/settings', icon: Settings, label: 'Manage Shop' },
  { href: '/dashboard/billing', icon: CreditCard, label: 'Billing' },
]

export default function Sidebar() {
  const pathname = usePathname()
  const router = useRouter()

  const handleLogout = async () => {
    await logoutUser()
    router.push('/login')
  }

  return (
    <aside className="w-64 bg-white border-r border-gray-100 min-h-screen flex flex-col hidden
md:flex">
      {/* Logo */}
      <div className="p-5 border-b border-gray-100">
        <div className="flex items-center gap-2">
          <div className="w-8 h-8 bg-[#5533FF] rounded-lg flex items-center justify-center">
            <span className="text-white font-bold text-sm">M</span>
          </div>
          <span className="font-bold">MeserBazar</span>
        </div>
      </div>
```

```
      {/* Nav */}
      <nav className="flex-1 p-3 space-y-1">
        {navItems.map(({ href, icon: Icon, label }) => (
          <Link
            key={href}
            href={href}
            className={clsx(
              'flex items-center gap-3 px-3 py-2.5 rounded-xl text-sm font-medium transition-colors',
              pathname === href
                ? 'bg-[#5533FF] text-white'
                : 'text-gray-600 hover:bg-gray-50 hover:text-gray-900'
            )}
          >
            <Icon className="w-4 h-4" />
            {label}
          </Link>
        ))}
      </nav>

      {/* Logout */}
      <div className="p-3 border-t border-gray-100">
        <button
          onClick={handleLogout}
          className="flex items-center gap-3 px-3 py-2.5 rounded-xl text-sm font-medium text-red-500
hover:bg-red-50 w-full transition-colors"
        >
          <LogOut className="w-4 h-4" />
          লগআউট
        </button>
      </div>
    </aside>
  )
}
```

---

21. `src/app/dashboard/page.js` — Dashboard Home

```jsx
'use client'
import { useEffect, useState } from 'react'
import { useAuth } from '@/context/AuthContext'
import { getShop, getOrders, getProducts } from '@/lib/firestore'
import { ShoppingBag, CheckCircle, DollarSign, Eye, ExternalLink } from 'lucide-react'
import Link from 'next/link'

export default function DashboardPage() {
  const { user } = useAuth()
  const [shop, setShop] = useState(null)
  const [orders, setOrders] = useState([])
  const [products, setProducts] = useState([])

  useEffect(() => {
    if (!user) return
    getShop(user.uid).then(setShop)
    getOrders(user.uid).then(setOrders)
    getProducts(user.uid).then(setProducts)
  }, [user])

  const shopUrl = `${process.env.NEXT_PUBLIC_SITE_URL}/shop/${shop?.shopSlug}`
  const todayOrders = orders.filter(o => {
    const today = new Date().toDateString()
    return o.createdAt?.toDate?.()?.toDateString() === today
  })

  return (
    <div className="p-6 max-w-4xl mx-auto">
      {/* Header */}
      <div className="flex items-center justify-between mb-6">
        <div>
          <p className="text-gray-400 text-sm">Good Evening</p>
          <h1 className="text-2xl font-bold">{shop?.shopName || 'আপনার দোকান'}</h1>
```

```
      </div>
      <div className="w-10 h-10 bg-[#5533FF] rounded-full flex items-center justify-center text-
white font-bold">
        {user?.email?.[0]?.toUpperCase()}
      </div>
    </div>

    {/* Quick Actions */}
    <div className="mb-6">
      <h2 className="font-bold text-lg mb-3">Quick Actions</h2>
      <div className="grid grid-cols-4 gap-3">
        {[
          { label: 'Categories', href: '/dashboard/categories', color: 'bg-purple-100', emoji: '📂' },
          { label: 'Customers', href: '/dashboard/customers', color: 'bg-green-100', emoji: '👥' },
          { label: 'Manage Shop', href: '/dashboard/settings', color: 'bg-pink-100', emoji: '🏪' },
          { label: 'Analytics', href: '/dashboard/analytics', color: 'bg-orange-100', emoji: '📊' },
        ].map(item => (
          <Link
            key={item.label}
            href={item.href}
            className={`${item.color} rounded-2xl p-4 text-center hover:scale-105 transition-
transform`}
          >
            <div className="text-2xl mb-2">{item.emoji}</div>
            <p className="text-xs font-medium">{item.label}</p>
          </Link>
        ))}
      </div>
    </div>

    {/* Shop URL */}
    {shop && (
      <div className="card bg-gradient-to-r from-[#5533FF] to-[#7c5cff] text-white mb-6">
        <div className="flex items-center gap-3 mb-3">
          <div className="w-8 h-8 bg-white/20 rounded-lg flex items-center justify-center">🏪</div>
          <div>
            <p className="font-bold">Your Online Store</p>
```

```
            <p className="text-xs text-white/70 flex items-center gap-1">
              <span className="w-2 h-2 bg-green-400 rounded-full inline-block" />
              Live & Active
            </p>
          </div>
        </div>
        <p className="text-xs text-white/70 mb-2">Store URL</p>
        <div className="bg-white/10 rounded-xl px-3 py-2 text-sm mb-3 font-mono truncate">
          {shopUrl}
        </div>
        <div className="flex gap-2">
          <a
            href={shopUrl}
            target="_blank"
            className="flex-1 bg-white text-[#5533FF] text-sm font-medium py-2 rounded-xl text-
center flex items-center justify-center gap-2"
          >
            <ExternalLink className="w-4 h-4" /> Visit Store
          </a>
        </div>
      </div>
    )}

    {/* Today's Analytics */}
    <div className="mb-6">
      <h2 className="font-bold text-lg mb-3">Today's Analytics</h2>
      <div className="grid grid-cols-2 gap-3">
        {[
          { label: 'Total Orders', value: `${todayOrders.length}.0 ৳`, icon: ShoppingBag, color: 'text-
purple-500 bg-purple-50' },
          { label: 'Completed', value: todayOrders.filter(o => o.status === 'completed').length, icon:
CheckCircle, color: 'text-green-500 bg-green-50' },
          { label: 'Total Amount', value: `${todayOrders.reduce((s, o) => s + (o.total || 0), 0)} ৳`, icon:
DollarSign, color: 'text-pink-500 bg-pink-50' },
          { label: 'Products', value: products.length, icon: Eye, color: 'text-blue-500 bg-blue-50' },
        ].map(({ label, value, icon: Icon, color }) => (
          <div key={label} className="card">
```

```
          <div className={`w-8 h-8 ${color} rounded-xl flex items-center justify-center mb-2`}>
            <Icon className="w-4 h-4" />
          </div>
          <p className="text-gray-400 text-xs">{label}</p>
          <p className="font-bold text-lg">{value}</p>
        </div>
      ))}
    </div>
  </div>

  {/* Recent Orders */}
  <div>
    <div className="flex justify-between items-center mb-3">
      <h2 className="font-bold text-lg">Recent Orders</h2>
      <Link href="/dashboard/orders" className="text-[#5533FF] text-sm">সব দেখুন</Link>
    </div>
    {orders.length === 0 ? (
      <div className="card text-center text-gray-400 py-8">
        <p>এখনো কোনো অর্ডার নেই</p>
      </div>
    ) : (
      <div className="space-y-3">
        {orders.slice(0, 5).map((order, i) => (
          <div key={order.id} className="card flex items-center justify-between">
            <div>
              <p className="font-medium text-sm">Order #{i + 1}</p>
              <p className="text-gray-400 text-xs">{order.customerName} • {order.customerPhone}
</p>
            </div>
            <div className="text-right">
              <p className="font-bold">{order.total} ৳</p>
              <span className={`text-xs px-2 py-0.5 rounded-full font-medium ${
                order.status === 'completed' ? 'bg-green-100 text-green-600' :
                order.status === 'pending' ? 'bg-yellow-100 text-yellow-600' :
                'bg-gray-100 text-gray-600'
              }`}>
                {order.status}
```

```
              </span>
            </div>
          </div>
        ))}
      </div>
    )}
  </div>
 </div>
)
}
```

---

22. `src/app/dashboard/products/page.js`

```jsx
'use client'
import { useEffect, useState } from 'react'
import { useAuth } from '@/context/AuthContext'
import { getProducts, deleteProduct } from '@/lib/firestore'
import Link from 'next/link'
import { Plus, Share2, ChevronDown, Trash2 } from 'lucide-react'
import toast from 'react-hot-toast'

export default function ProductsPage() {
  const { user } = useAuth()
  const [products, setProducts] = useState([])
  const [loading, setLoading] = useState(true)

  useEffect(() => {
    if (!user) return
    getProducts(user.uid).then(p => { setProducts(p); setLoading(false) })
  }, [user])

  const handleDelete = async (productId) => {
    if (!confirm('পণ্যটি মুছে ফেলবেন?')) return
```

```
    await deleteProduct(user.uid, productId)
    setProducts(products.filter(p => p.id !== productId))
    toast.success('পণ্য মুছে ফেলা হয়েছে')
  }

  return (
    <div className="p-6">
      <div className="flex items-center justify-between mb-6">
        <h1 className="text-xl font-bold">All Products <span className="text-gray-400 text-sm font-
normal">{products.length}</span></h1>
        <Link href="/dashboard/products/new" className="btn-primary text-sm flex items-center gap-
1">
          <Plus className="w-4 h-4" /> Add
        </Link>
      </div>

      {loading ? (
        <div className="text-center py-12 text-gray-400">লোড হচ্ছে...</div>
      ) : products.length === 0 ? (
        <div className="text-center py-12 text-gray-400">
          <p className="text-4xl mb-3">📦</p>
          <p>এখনো কোনো পণ্য নেই</p>
          <Link href="/dashboard/products/new" className="btn-primary text-sm mt-4 inline-block">
            প্রথম পণ্য যোগ করুন
          </Link>
        </div>
      ) : (
        <div className="space-y-3">
          {products.map(product => (
            <div key={product.id} className="card flex items-center gap-3">
              {product.imageUrl ? (
                <img src={product.imageUrl} alt={product.name} className="w-14 h-14 rounded-xl
object-cover" />
              ) : (
                <div className="w-14 h-14 bg-gray-100 rounded-xl flex items-center justify-center text-
2xl">📦</div>
              )}
```

```
            <div className="flex-1">
              <p className="font-medium">{product.name}</p>
              <p className="text-red-500 text-xs">Available: {product.stock || 0}</p>
              <p className="text-gray-400 text-xs">Price: ৳{product.price}</p>
            </div>
            <div className="flex gap-2">
              <button className="text-gray-400 hover:text-gray-600">
                <Share2 className="w-4 h-4" />
              </button>
              <button onClick={() => handleDelete(product.id)} className="text-red-400 hover:text-red-
600">
                <Trash2 className="w-4 h-4" />
              </button>
            </div>
          </div>
        ))}
      </div>
    )}
  </div>
 )
}
```

---

23. `src/app/dashboard/products/new/page.js`

```jsx
'use client'
import { useState } from 'react'
import { useRouter } from 'next/navigation'
import { useAuth } from '@/context/AuthContext'
import { addProduct } from '@/lib/firestore'
import { uploadProductImage } from '@/lib/storage'
import toast from 'react-hot-toast'
import { ImagePlus } from 'lucide-react'
```

```
export default function NewProductPage() {
  const { user } = useAuth()
  const router = useRouter()
  const [loading, setLoading] = useState(false)
  const [imageFile, setImageFile] = useState(null)
  const [imagePreview, setImagePreview] = useState(null)
  const [form, setForm] = useState({
    name: '', category: '', status: 'active',
    description: '', price: '', regularPrice: '',
    buyingPrice: '', stock: '', sku: '', brand: '', warranty: '',
  })

  const handleImage = (e) => {
    const file = e.target.files[0]
    if (!file) return
    setImageFile(file)
    setImagePreview(URL.createObjectURL(file))
  }

  const handleSubmit = async (e) => {
    e.preventDefault()
    setLoading(true)
    try {
      let imageUrl = ''
      if (imageFile) imageUrl = await uploadProductImage(user.uid, imageFile)
      await addProduct(user.uid, { ...form, imageUrl })
      toast.success('পণ্য যোগ হয়েছে! ✅')
      router.push('/dashboard/products')
    } catch (err) {
      toast.error('সমস্যা হয়েছে: ' + err.message)
    } finally {
      setLoading(false)
    }
  }

  const field = (key, label, type = 'text', placeholder = '') => (
    <div>
```

```
    <label className="text-sm font-medium text-gray-700 block mb-1">{label}</label>
    <input
      type={type}
      value={form[key]}
      onChange={e => setForm({...form, [key]: e.target.value})}
      placeholder={placeholder}
      className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none
focus:border-[#5533FF]"
    />
  </div>
)

return (
  <div className="p-6 max-w-2xl mx-auto">
    <h1 className="text-xl font-bold mb-6">নতুন পণ্য যোগ করুন</h1>

    <form onSubmit={handleSubmit} className="space-y-4">
      {/* Image Upload */}
      <div className="card text-center">
        <label className="cursor-pointer">
          {imagePreview ? (
            <img src={imagePreview} className="w-full h-48 object-contain rounded-xl" alt="preview"
/>
          ) : (
            <div className="py-8">
              <div className="w-12 h-12 bg-[#5533FF] rounded-full flex items-center justify-center mx-
auto mb-2">
                <ImagePlus className="w-6 h-6 text-white" />
              </div>
              <p className="text-gray-400 text-sm">Supported: JPG, PNG, Max 4MB</p>
            </div>
          )}
          <input type="file" accept="image/*" onChange={handleImage} className="hidden" />
        </label>
      </div>

      {/* General */}
```

```
      <div className="card space-y-4">
        <h2 className="font-bold">General</h2>
        {field('name', 'Product Name', 'text', 'পণ্যের নাম লিখুন...')}
        {field('category', 'Product Category', 'text', 'Category')}
        <div className="grid grid-cols-2 gap-4">
          <div>
            <label className="text-sm font-medium text-gray-700 block mb-1">Status</label>
            <select
              value={form.status}
              onChange={e => setForm({...form, status: e.target.value})}
              className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF]"
            >
              <option value="active">Active</option>
              <option value="inactive">Inactive</option>
            </select>
          </div>
        </div>
        <div>
          <label className="text-sm font-medium text-gray-700 block mb-1">Description</label>
          <textarea
            value={form.description}
            onChange={e => setForm({...form, description: e.target.value})}
            rows={4}
            className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF]"
          />
        </div>
      </div>

      {/* Pricing */}
      <div className="card space-y-4">
        <h2 className="font-bold">Pricing</h2>
        <div className="grid grid-cols-2 gap-4">
          {field('price', 'Sell/Current Price', 'number', '0')}
          {field('regularPrice', 'Regular/Old Price', 'number', '0')}
          {field('buyingPrice', 'Buying Price', 'number', '0')}
```

```
        </div>
      </div>

      {/* Inventory */}
      <div className="card space-y-4">
        <h2 className="font-bold">Inventory</h2>
        <div className="grid grid-cols-2 gap-4">
          {field('sku', 'Product Code (SKU)')}
          {field('brand', 'Brand')}
          {field('stock', 'Quantity (Stock)', 'number', '0')}
          {field('warranty', 'Warranty')}
        </div>
      </div>

      <button
        type="submit"
        disabled={loading}
        className="btn-primary w-full py-4 rounded-xl text-base disabled:opacity-50"
      >
        {loading ? 'সংরক্ষণ হচ্ছে...' : 'Create Product ✅'}
      </button>
    </form>
  </div>
 )
}
```

---

24. `src/app/dashboard/settings/page.js` — Domain Settings

```jsx
'use client'
import { useEffect, useState } from 'react'
import { useAuth } from '@/context/AuthContext'
import { getShop, updateShop } from '@/lib/firestore'
import { uploadShopLogo } from '@/lib/storage'
```

```
import toast from 'react-hot-toast'

export default function SettingsPage() {
  const { user } = useAuth()
  const [shop, setShop] = useState(null)
  const [loading, setLoading] = useState(false)

  useEffect(() => {
    if (user) getShop(user.uid).then(setShop)
  }, [user])

  const handleSave = async (e) => {
    e.preventDefault()
    setLoading(true)
    try {
      await updateShop(user.uid, shop)
      toast.success('সংরক্ষণ হয়েছে ✅')
    } catch (err) {
      toast.error('সমস্যা: ' + err.message)
    } finally {
      setLoading(false)
    }
  }

  if (!shop) return <div className="p-6 text-gray-400">লোড হচ্ছে...</div>

  const platformUrl = `${process.env.NEXT_PUBLIC_SITE_URL}/shop/${shop.shopSlug}`

  return (
    <div className="p-6 max-w-2xl mx-auto">
      <h1 className="text-xl font-bold mb-6">Manage Shop</h1>

      <form onSubmit={handleSave} className="space-y-4">
        {/* Basic Info */}
        <div className="card space-y-4">
          <h2 className="font-bold">Shop Basic Info</h2>
          <div>
```

```
          <label className="text-sm font-medium mb-1 block">Shop Name</label>
          <input
            value={shop.shopName || ''}
            onChange={e => setShop({...shop, shopName: e.target.value})}
            className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF]"
          />
        </div>
        <div>
          <label className="text-sm font-medium mb-1 block">Description</label>
          <textarea
            value={shop.description || ''}
            onChange={e => setShop({...shop, description: e.target.value})}
            rows={3}
            className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF]"
          />
        </div>
        <div>
          <label className="text-sm font-medium mb-1 block">Phone</label>
          <input
            value={shop.phone || ''}
            onChange={e => setShop({...shop, phone: e.target.value})}
            className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none focus:border-[#5533FF]"
          />
        </div>
      </div>

      {/* Domain Settings */}
      <div className="card space-y-4">
        <h2 className="font-bold">🌐 Domain Settings</h2>

        {/* Current platform URL */}
        <div className="bg-blue-50 rounded-xl p-3">
          <p className="text-xs text-blue-600 font-medium mb-1">আপনার বর্তমান ফ্রি Store URL:</p>
          <p className="text-sm font-mono text-blue-800 break-all">{platformUrl}</p>
```

```
      </div>

      {/* Domain type selector */}
      <div>
        <label className="text-sm font-medium mb-2 block">Domain Type বেছে নিন</label>
        <div className="space-y-2">
          {[
            { value: 'platform', label: '🆓 Platform URL (Free)', desc:
`meserbazar.web.app/shop/${shop.shopSlug}` },
            { value: 'customSubdomain', label: '🔗 Custom Subdomain (আমাদের Domain-এ)', desc:
'yourshop.meserbazar.com (যদি আমরা domain কিনি)' },
            { value: 'customDomain', label: '🌍 নিজের Domain', desc: 'yourshop.com বা
shop.yoursite.com' },
          ].map(opt => (
            <label key={opt.value} className={`flex items-start gap-3 p-3 rounded-xl border-2 cursor-
pointer transition-colors ${
              shop.domainType === opt.value ? 'border-[#5533FF] bg-[#5533FF]/5' : 'border-gray-200'
            }`}>
              <input
                type="radio"
                name="domainType"
                value={opt.value}
                checked={shop.domainType === opt.value}
                onChange={e => setShop({...shop, domainType: e.target.value})}
                className="mt-0.5"
              />
              <div>
                <p className="text-sm font-medium">{opt.label}</p>
                <p className="text-xs text-gray-400">{opt.desc}</p>
              </div>
            </label>
          ))}
        </div>
      </div>

      {/* Custom subdomain input */}
      {shop.domainType === 'customSubdomain' && (
```

```
        <div>
          <label className="text-sm font-medium mb-1 block">Subdomain Name</label>
          <div className="flex items-center border border-gray-200 rounded-xl overflow-hidden">
            <input
              value={shop.customSubdomain || ''}
              onChange={e => setShop({...shop, customSubdomain:
e.target.value.toLowerCase().replace(/\s/g, '')})}
              placeholder="yourshop"
              className="flex-1 px-4 py-3 text-sm focus:outline-none"
            />
            <span className="bg-gray-50 px-3 py-3 text-sm text-gray-400 border-l border-gray-200">
              .meserbazar.com
            </span>
          </div>
          <p className="text-xs text-orange-500 mt-1">⚠️ এটা কাজ করবে যখন meserbazar.com কেনা
হবে</p>
        </div>
      )}

      {/* Custom domain input */}
      {shop.domainType === 'customDomain' && (
        <div>
          <label className="text-sm font-medium mb-1 block">আপনার Domain বা
Subdomain</label>
          <input
            value={shop.customDomain || ''}
            onChange={e => setShop({...shop, customDomain: e.target.value})}
            placeholder="shop.yourdomain.com অথবা yourdomain.com"
            className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none
focus:border-[#5533FF]"
          />
          <div className="bg-yellow-50 rounded-xl p-3 mt-2">
            <p className="text-xs text-yellow-700 font-medium">DNS Setup করুন:</p>
            <p className="text-xs text-yellow-600 mt-1">
              আপনার domain-এ CNAME record যোগ করুন:<br />
              <code className="bg-yellow-100 px-1 rounded">meserbazar.web.app</code>
            </p>
```

```
          </div>
        </div>
      )}
    </div>

    {/* Shop Policy */}
    <div className="card space-y-3">
      <h2 className="font-bold">Shop Policy</h2>
      <div>
        <label className="text-sm font-medium mb-1 block">Return Policy</label>
        <textarea
          value={shop.returnPolicy || ''}
          onChange={e => setShop({...shop, returnPolicy: e.target.value})}
          rows={3}
          className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-none
focus:border-[#5533FF]"
          placeholder="আপনার return policy লিখুন..."
        />
      </div>
    </div>

    <button
      type="submit"
      disabled={loading}
      className="btn-primary w-full py-4 rounded-xl text-base disabled:opacity-50"
    >
      {loading ? 'সংরক্ষণ হচ্ছে...' : 'Save Settings ✅'}
    </button>
  </form>
 </div>
)
}
```

---

25. `src/app/dashboard/orders/page.js`

```jsx
'use client'
import { useEffect, useState } from 'react'
import { useAuth } from '@/context/AuthContext'
import { subscribeOrders, updateOrderStatus } from '@/lib/firestore'
import toast from 'react-hot-toast'

const STATUS_COLORS = {
  pending: 'bg-yellow-100 text-yellow-700',
  confirmed: 'bg-blue-100 text-blue-700',
  shipped: 'bg-purple-100 text-purple-700',
  completed: 'bg-green-100 text-green-700',
  cancelled: 'bg-red-100 text-red-700',
}

export default function OrdersPage() {
  const { user } = useAuth()
  const [orders, setOrders] = useState([])
  const [filter, setFilter] = useState('all')

  useEffect(() => {
    if (!user) return
    const unsub = subscribeOrders(user.uid, setOrders)
    return unsub
  }, [user])

  const filtered = filter === 'all' ? orders : orders.filter(o => o.status === filter)

  const handleStatus = async (orderId, status) => {
    await updateOrderStatus(user.uid, orderId, status)
    toast.success('Status updated')
  }

  return (
    <div className="p-6">
      <div className="flex items-center justify-between mb-6">
```

```
      <h1 className="text-xl font-bold">Orders</h1>
      <select
        value={filter}
        onChange={e => setFilter(e.target.value)}
        className="border border-gray-200 rounded-xl px-3 py-2 text-sm focus:outline-none
focus:border-[#5533FF]"
      >
        <option value="all">সব</option>
        <option value="pending">Pending</option>
        <option value="confirmed">Confirmed</option>
        <option value="completed">Completed</option>
        <option value="cancelled">Cancelled</option>
      </select>
    </div>

    {filtered.length === 0 ? (
      <div className="text-center py-12 text-gray-400">
        <p className="text-4xl mb-3">📋</p>
        <p>কোনো অর্ডার নেই</p>
      </div>
    ) : (
      <div className="space-y-3">
        {filtered.map((order, i) => (
          <div key={order.id} className="card">
            <div className="flex justify-between items-start mb-2">
              <div>
                <p className="text-[#5533FF] font-medium text-sm">Order #{i + 1}</p>
                <p className="text-gray-400 text-xs">{order.createdAt?.toDate?.
()?.toLocaleDateString('bn-BD')}</p>
              </div>
              <span className={`text-xs px-2 py-1 rounded-full font-medium
${STATUS_COLORS[order.status] || 'bg-gray-100 text-gray-600'}`}>
                {order.status}
              </span>
            </div>
            <p className="text-sm"><span className="text-gray-400">Customer:</span>
{order.customerName}</p>
```

```
            <p className="text-sm"><span className="text-gray-400">Phone:</span> {order.customerPhone}</p>
            <p className="text-sm"><span className="text-gray-400">Total:</span> <strong>৳{order.total}</strong></p>

            <div className="flex gap-2 mt-3">
              {['confirmed', 'shipped', 'completed', 'cancelled'].map(s => (
                <button
                  key={s}
                  onClick={() => handleStatus(order.id, s)}
                  className={`text-xs px-2 py-1 rounded-lg border transition-colors ${
                    order.status === s
                      ? 'bg-[#5533FF] text-white border-[#5533FF]'
                      : 'border-gray-200 text-gray-600 hover:border-[#5533FF] hover:text-[#5533FF]'
                  }`}
                >
                  {s}
                </button>
              ))}
            </div>
          </div>
        ))}
      </div>
    )}
  </div>
  )
}
```

---

26. `src/app/shop/[shopSlug]/page.js` — Public Sister Site

```jsx
import { getShopBySlug, getProducts, getCategories } from '@/lib/firestore'
import ShopClient from './ShopClient'
```

```
export default async function ShopPage({ params }) {
  const shop = await getShopBySlug(params.shopSlug)
  if (!shop) return (
    <div className="min-h-screen flex items-center justify-center text-gray-400">
      <div className="text-center">
        <p className="text-5xl mb-4">🏪</p>
        <p className="text-xl font-bold">দোকান পাওয়া যায়নি</p>
      </div>
    </div>
  )

  const [products, categories] = await Promise.all([
    getProducts(shop.id),
    getCategories(shop.id),
  ])

  return <ShopClient shop={shop} products={products} categories={categories} />
}
```

---

27. `src/app/shop/[shopSlug]/ShopClient.jsx`

```jsx
'use client'
import { useState } from 'react'
import { placeOrder } from '@/lib/firestore'
import { ShoppingCart, Phone, X, Plus, Minus } from 'lucide-react'
import toast from 'react-hot-toast'

export default function ShopClient({ shop, products, categories }) {
  const [cart, setCart] = useState([])
  const [activeCategory, setActiveCategory] = useState('all')
  const [showCart, setShowCart] = useState(false)
  const [orderForm, setOrderForm] = useState({ name: '', phone: '', address: '' })
  const [showOrderForm, setShowOrderForm] = useState(false)
```

```
const [placing, setPlacing] = useState(false)

const addToCart = (product) => {
  setCart(prev => {
    const existing = prev.find(i => i.id === product.id)
    if (existing) return prev.map(i => i.id === product.id ? {...i, qty: i.qty + 1} : i)
    return [...prev, { ...product, qty: 1 }]
  })
  toast.success(`${product.name} কার্টে যোগ হয়েছে`)
}

const removeFromCart = (id) => setCart(prev => prev.filter(i => i.id !== id))
const updateQty = (id, delta) => setCart(prev =>
  prev.map(i => i.id === id ? {...i, qty: Math.max(1, i.qty + delta)} : i)
)

const total = cart.reduce((s, i) => s + i.price * i.qty, 0)
const filtered = activeCategory === 'all'
  ? products
  : products.filter(p => p.category === activeCategory)

const handleOrder = async (e) => {
  e.preventDefault()
  if (cart.length === 0) return toast.error('কার্টে পণ্য নেই')
  setPlacing(true)
  try {
    await placeOrder(shop.id, {
      customerName: orderForm.name,
      customerPhone: orderForm.phone,
      customerAddress: orderForm.address,
      items: cart,
      total: total + (shop.deliveryCharge || 0),
      status: 'pending',
    })
    toast.success('অর্ডার সফলভাবে হয়েছে! 🎉')
    setCart([])
    setShowOrderForm(false)
```

```
    setShowCart(false)
  } catch (err) {
    toast.error('সমস্যা হয়েছে')
  } finally {
    setPlacing(false)
  }
}

return (
  <div className="min-h-screen bg-gray-50">
    {/* Shop Header */}
    <header className="bg-white border-b border-gray-100 sticky top-0 z-10">
      <div className="px-4 py-3 flex items-center justify-between">
        <div className="flex items-center gap-3">
          {shop.logoUrl ? (
            <img src={shop.logoUrl} className="w-10 h-10 rounded-xl object-cover" alt="logo" />
          ) : (
            <div className="w-10 h-10 bg-[#5533FF] rounded-xl flex items-center justify-center text-
white font-bold">
              {shop.shopName?.[0]}
            </div>
          )}
          <div>
            <p className="font-bold text-sm">{shop.shopName}</p>
            {shop.phone && <p className="text-xs text-gray-400">{shop.phone}</p>}
          </div>
        </div>
        <button
          onClick={() => setShowCart(true)}
          className="relative bg-[#5533FF] text-white w-10 h-10 rounded-xl flex items-center justify-
center"
        >
          <ShoppingCart className="w-5 h-5" />
          {cart.length > 0 && (
            <span className="absolute -top-1 -right-1 w-5 h-5 bg-red-500 text-white text-xs rounded-
full flex items-center justify-center">
              {cart.length}
```

```
          </span>
        )}
      </button>
    </div>
  </header>

  {/* Categories */}
  {categories.length > 0 && (
    <div className="flex gap-2 px-4 py-3 overflow-x-auto">
      <button
        onClick={() => setActiveCategory('all')}
        className={`px-4 py-1.5 rounded-full text-sm font-medium whitespace-nowrap transition-colors ${
          activeCategory === 'all' ? 'bg-[#5533FF] text-white' : 'bg-white text-gray-600 border border-gray-200'
        }`}
      >
        সব
      </button>
      {categories.map(cat => (
        <button
          key={cat.id}
          onClick={() => setActiveCategory(cat.name)}
          className={`px-4 py-1.5 rounded-full text-sm font-medium whitespace-nowrap transition-colors ${
            activeCategory === cat.name ? 'bg-[#5533FF] text-white' : 'bg-white text-gray-600 border border-gray-200'
          }`}
        >
          {cat.name}
        </button>
      ))}
    </div>
  )}

  {/* Products */}
  <div className="p-4">
```

```
      {filtered.length === 0 ? (
        <div className="text-center py-12 text-gray-400">
          <p className="text-4xl mb-3">📦</p>
          <p>এই দোকানে এখনো পণ্য নেই</p>
        </div>
      ) : (
        <div className="grid grid-cols-2 gap-3">
          {filtered.map(product => (
            <div key={product.id} className="bg-white rounded-2xl overflow-hidden shadow-sm">
              {product.imageUrl ? (
                <img src={product.imageUrl} alt={product.name} className="w-full h-40 object-cover" />
              ) : (
                <div className="w-full h-40 bg-gray-100 flex items-center justify-center text-4xl">📦
</div>
              )}
              <div className="p-3">
                <p className="font-medium text-sm">{product.name}</p>
                <p className="text-[#5533FF] font-bold text-sm mt-1">৳{product.price}</p>
                {product.regularPrice && (
                  <p className="text-gray-400 text-xs line-through">৳{product.regularPrice}</p>
                )}
                <button
                  onClick={() => addToCart(product)}
                  className="btn-primary w-full mt-2 py-2 text-xs rounded-xl"
                >
                  কার্টে যোগ করুন
                </button>
              </div>
            </div>
          ))}
        </div>
      )}
    </div>

    {/* Cart Drawer */}
    {showCart && (
      <div className="fixed inset-0 z-50 flex">
```

```
      <div className="flex-1 bg-black/50" onClick={() => setShowCart(false)} />
      <div className="w-80 bg-white h-full flex flex-col">
        <div className="flex items-center justify-between p-4 border-b">
          <h2 className="font-bold">কার্ট ({cart.length})</h2>
          <button onClick={() => setShowCart(false)}><X className="w-5 h-5" /></button>
        </div>
        <div className="flex-1 overflow-auto p-4 space-y-3">
          {cart.length === 0 ? (
            <p className="text-center text-gray-400 py-8">কার্ট খালি</p>
          ) : cart.map(item => (
            <div key={item.id} className="flex items-center gap-3 card">
              <div className="flex-1">
                <p className="text-sm font-medium">{item.name}</p>
                <p className="text-[#5533FF] text-sm">৳{item.price * item.qty}</p>
              </div>
              <div className="flex items-center gap-2">
                <button onClick={() => updateQty(item.id, -1)} className="w-6 h-6 bg-gray-100 rounded-
full flex items-center justify-center">
                  <Minus className="w-3 h-3" />
                </button>
                <span className="text-sm w-6 text-center">{item.qty}</span>
                <button onClick={() => updateQty(item.id, 1)} className="w-6 h-6 bg-gray-100 rounded-
full flex items-center justify-center">
                  <Plus className="w-3 h-3" />
                </button>
                <button onClick={() => removeFromCart(item.id)} className="text-red-400">
                  <X className="w-4 h-4" />
                </button>
              </div>
            </div>
          ))}
        </div>
        {cart.length > 0 && (
          <div className="p-4 border-t">
            <div className="flex justify-between mb-3">
              <span className="font-medium">মোট:</span>
              <span className="font-bold text-[#5533FF]">৳{total}</span>
```

```
          </div>
          <button
            onClick={() => setShowOrderForm(true)}
            className="btn-primary w-full py-3 rounded-xl"
          >
            অর্ডার করুন
          </button>
        </div>
      )}
    </div>
  </div>
)}

{/* Order Form Modal */}
{showOrderForm && (
  <div className="fixed inset-0 z-50 flex items-end">
    <div className="flex-1 bg-black/50 h-full" onClick={() => setShowOrderForm(false)} />
    <div className="absolute bottom-0 left-0 right-0 bg-white rounded-t-3xl p-6">
      <h2 className="font-bold text-lg mb-4">অর্ডার করুন</h2>
      <form onSubmit={handleOrder} className="space-y-3">
        {[
          { key: 'name', label: 'আপনার নাম', placeholder: 'পূর্ণ নাম' },
          { key: 'phone', label: 'মোবাইল নম্বর', placeholder: '01XXXXXXXXX' },
          { key: 'address', label: 'ঠিকানা', placeholder: 'বিস্তারিত ঠিকানা' },
        ].map(f => (
          <div key={f.key}>
            <label className="text-sm font-medium mb-1 block">{f.label}</label>
            <input
              required
              value={orderForm[f.key]}
              onChange={e => setOrderForm({...orderForm, [f.key]: e.target.value})}
              placeholder={f.placeholder}
              className="w-full border border-gray-200 rounded-xl px-4 py-3 text-sm focus:outline-
none focus:border-[#5533FF]"
            />
          </div>
        ))}
```

```
          <div className="flex justify-between text-sm mb-2">
            <span>মোট পণ্য:</span><span>৳{total}</span>
          </div>
          {shop.deliveryCharge > 0 && (
            <div className="flex justify-between text-sm mb-2">
              <span>ডেলিভারি:</span><span>৳{shop.deliveryCharge}</span>
            </div>
          )}
          <div className="flex justify-between font-bold">
            <span>সর্বমোট:</span>
            <span className="text-[#5533FF]">৳{total + (shop.deliveryCharge || 0)}</span>
          </div>
          <button
            type="submit"
            disabled={placing}
            className="btn-primary w-full py-3 rounded-xl mt-2 disabled:opacity-50"
          >
            {placing ? 'অর্ডার হচ্ছে...' : 'অর্ডার কনফার্ম করুন ✅'}
          </button>
        </form>
      </div>
    </div>
  )}
 </div>
)
}
```

---

28. `src/app/superadmin/page.js` — Super Admin

```jsx
'use client'
import { useEffect, useState } from 'react'
import { useAuth } from '@/context/AuthContext'
import { useRouter } from 'next/navigation'
```

```
import { getAllShops } from '@/lib/firestore'
import { Store, Users, ShoppingBag } from 'lucide-react'

export default function SuperAdminPage() {
  const { user, userData, loading } = useAuth()
  const router = useRouter()
  const [shops, setShops] = useState([])

  useEffect(() => {
    if (!loading) {
      if (!user || userData?.role !== 'superadmin') router.push('/dashboard')
      else getAllShops().then(setShops)
    }
  }, [user, userData, loading, router])

  return (
    <div className="p-6 max-w-4xl mx-auto">
      <h1 className="text-2xl font-bold mb-6">🛡️ Super Admin Panel</h1>

      <div className="grid grid-cols-3 gap-4 mb-8">
        {[
          { label: 'Total Shops', value: shops.length, icon: Store, color: 'bg-purple-100 text-purple-600' },
          { label: 'Active Shops', value: shops.filter(s => s.isActive).length, icon: Users, color: 'bg-green-
100 text-green-600' },
          { label: 'Total Orders', value: '-', icon: ShoppingBag, color: 'bg-blue-100 text-blue-600' },
        ].map(({ label, value, icon: Icon, color }) => (
          <div key={label} className="card text-center">
            <div className={`w-10 h-10 ${color} rounded-xl flex items-center justify-center mx-auto mb-
2`}>
              <Icon className="w-5 h-5" />
            </div>
            <p className="font-bold text-xl">{value}</p>
            <p className="text-gray-400 text-xs">{label}</p>
          </div>
        ))}
      </div>
```

```
    <h2 className="font-bold text-lg mb-3">All Shops</h2>
    <div className="space-y-3">
      {shops.map(shop => (
        <div key={shop.id} className="card flex items-center justify-between">
          <div>
            <p className="font-medium">{shop.shopName}</p>
            <p className="text-xs text-gray-400">/shop/{shop.shopSlug}</p>
            {shop.customDomain && (
              <p className="text-xs text-[#5533FF]">🌍 {shop.customDomain}</p>
            )}
          </div>
          <div className="text-right">
            <span className={`text-xs px-2 py-1 rounded-full ${shop.isActive ? 'bg-green-100 text-
green-600' : 'bg-gray-100 text-gray-600'}`}>
              {shop.isActive ? 'Active' : 'Inactive'}
            </span>
            <p className="text-xs text-gray-400 mt-1">{shop.domainType}</p>
          </div>
        </div>
      ))}
    </div>
  </div>
 )
}
```

🚀 Setup & Deploy Guide

Step 1: Project তৈরি করো
```bash
npx create-next-app@latest meserbazar
cd meserbazar
npm install firebase react-hot-toast lucide-react clsx
```

Step 2: Firebase Project তৈরি করো
1. https://console.firebase.google.com → New Project → "meserbazar"
2. Authentication → Enable Email/Password
3. Firestore Database → Create in production mode
4. Storage → Enable
5. Project Settings → Web App → Config copy করো `.env.local`-এ

Step 3: Firebase CLI
```bash
npm install -g firebase-tools
firebase login
firebase init
# Hosting: yes, Firestore: yes, Storage: yes
# Public dir: out
# Single page app: yes
```

Step 4: Deploy
```bash
npm run build
firebase deploy
```

Step 5: Custom Domain (পরে কিনলে)
Firebase Console → Hosting → Add custom domain → `meserbazar.com`

📊 Firestore Database Structure

```
firestore/
├── users/
│   └── {uid}/
│       ├── name, email, role
│       └── subscription: 'free'
│
```

```
└── shops/
    └── {uid}/  ← shopId = ownerId (simplicity)
        ├── shopName, shopSlug, ownerId
        ├── domainType: 'platform'|'customSubdomain'|'customDomain'
        ├── customSubdomain: 'myshop' → myshop.meserbazar.com
        ├── customDomain: 'shop.mysite.com'
        │
        ├── products/
        │   └── {productId}/ → name, price, stock, imageUrl...
        │
        ├── orders/
        │   └── {orderId}/ → customerName, items, total, status...
        │
        └── categories/
            └── {categoryId}/ → name, imageUrl...
```

🎯 Sister Site Flow

```
User registers → Shop auto-created → shopSlug = "rahim-shop-1234"
Sister site URL: meserbazar.web.app/shop/rahim-shop-1234
Customers visit → Add to cart → Place order
Shop owner sees order in dashboard (realtime)
```

💡 ভবিষ্যতে যোগ করতে পারো

Feature	কীভাবে
Subdomain routing	Cloudflare Workers (free)
SMS notification	Twilio free tier
Payment gateway	bKash/Nagad API

| Analytics | Firebase Analytics |
| PWA (App-like) | Next.js PWA plugin |
```
```