

OpenCore v0.6.3 Intel Coffee Lake Sanity Check

Show Raw XML

https://dortania.github.io/OpenCore-Install-Guide/config.plist/coffee-lake.html

ACPI

Add

- **⊘** SSDT-AWAC.aml Make sure this file is in your OC/ACPI directory
- **SSDT-EC-USBX-DESKTOP.aml** Make sure this file is in your OC/ACPI directory
- **⊘** SSDT-PLUG-DRTNIA.aml Make sure this file is in your OC/ACPI directory
- **⊘** SSDT-PMC.aml Make sure this file is in your OC/ACPI directory

Delete

Patch

Quirks

- \bigcirc FadtEnableReset = No
- \bigcirc NormalizeHeaders = No
- \bigcirc RebaseRegions = No
- \bigcirc ResetHwSig = No
- **⊘** ResetLogoStatus = No

Booter

MmioWhitelist

Quirks

- \bigcirc AvoidRuntimeDefrag = Yes
- **⊘** DevirtualiseMmio = Yes
- \bigcirc DisableSingleUser = No
- **⊘** DisableVariableWrite = No
- \bigcirc DiscardHibernateMap = No
- **⊘** EnableSafeModeSlide = Yes
- **⊘** EnableWriteUnprotector = No
- **⊘** ForceExitBootServices = No
- **⊘** ProtectMemoryRegions = No
- **⊘** ProtectSecureBoot = No
- **⊘** ProtectUefiServices = Yes
- **⊘** ProvideCustomSlide = Yes
- \bigcirc ProvideMaxSlide = 0
- \bigcirc RebuildAppleMemoryMap = Yes
- \bigcirc SetupVirtualMap = Yes
- \bigcirc SignalAppleOS = No
- **⊘** SyncRuntimePermissions = Yes

DeviceProperties

Add

⊘ AAPL,ig-platform-id = **00009b3e** iGPU set correctly

Delete

Kernel

Add

- ② Lilu.kext make sure this Kext is in your OC/Kexts directory and the first kext listed here
- **⊘** VirtualSMC.kext make sure this Kext is in your OC/Kexts directory

- **⊘** AppleALC.kext make sure this Kext is in your OC/Kexts directory
- ☑ IntelMausi.kext make sure this Kext is in your OC/Kexts directory
- **⊘** WhateverGreen.kext make sure this Kext is in your OC/Kexts directory

Block

Emulate

⊘ DummyPowerManagement = No

Force

Patch

Quirks

- \bigcirc AppleCpuPmCfgLock = No
- **⊘** AppleXcpmCfgLock = Yes You should disable CFG-Lock in your bios instead of using this
- \bigcirc AppleXcpmExtraMsrs = No
- **⊘** AppleXcpmForceBoost = No
- **⊘** CustomSMBIOSGuid = No If you have a Dell or VIAO motherboard, please enable this
- \bigcirc DisableIoMapper = Yes
- **⊘** DisableRtcChecksum = No
- **⊗** ExtendBTFeatureFlags = No
- **⊘** LegacyCommpage = No
- **⊗** ExternalDiskIcons = No
- **⊘** ForceSecureBootScheme = No
- **⊘** IncreasePciBarSize = No
- **⊘** LapicKernelPanic = No If you have an HP laptop, please enable this
- \bigcirc PanicNoKextDump = Yes
- **⊘** PowerTimeoutKernelPanic = Yes
- **⊘** ThirdPartyDrives = No
- **⊘ XhciPortLimit** = **Yes** turn off after USB port mapping

Scheme

Misc

BlessOverride

Boot

- \bigcirc ConsoleAttributes = 0
- **⊘** PollAppleHotKeys = No
- \bigcirc ShowPicker = Yes
- \bigcirc TakeoffDelay = 0
- \bigcirc HibernateMode = None
- **⊘** PickerMode = Builtin
- **⊘** HideAuxiliary = No
- **⊘** PickerAttributes = 1
- \bigcirc PickerAudioAssist = No
- \bigcirc Timeout = 5

Debug

- \bigcirc AppleDebug = Yes
- \bigcirc ApplePanic = Yes
- \bigcirc DisableWatchDog = Yes
- \bigcirc Target = 67
- ② **DisplayLevel** see <u>Debugging Docs</u> for more info debug display levels
- \bigcirc DisplayDelay = 0

Entries

Security

- **⊘** AllowNvramReset = Yes
- **⊘** AllowSetDefault = Yes

- \bigcirc ApECID = 0
- **⊘** AuthRestart = No
- **⊘** BootProtect = Bootstrap
- **⊘** DmgLoading = Signed
- \bigcirc EnablePassword = No
- **⊘** Vault = Optional
- **⊘** SecureBootModel = Default SecureBootModel set correctly
- **⊘** HaltLevel = <u>2147483648</u>
- **⊘** ExposeSensitiveData = 6
- \odot ScanPolicy = 0

Tools

✓ You removed the tool EFIs

NVRAM

- **⊘** LegacyEnable = No
- **⊘** LegacyOverwrite = No
- **⊘** WriteFlash = Yes

Add

- \bigcirc UIScale = 01
- \bigcirc DefaultBackgroundColor = $\underline{00000000}$
- **⊘** boot-args = -v keepsyms=1 debug=0x100 alcid=1
- \bigcirc run-efi-updater = No
- \bigcirc csr-active-config = $\underline{00000000}$
- **⊘** prev-lang:kbd = -blank- (-blank-)
- **⊘** SystemAudioVolume = 46

Delete

LegacySchema

PlatformInfo

- **⊘** Automatic = Yes
- \bigcirc UpdateDataHub = Yes
- \bigcirc UpdateNVRAM = Yes
- \bigcirc UpdateSMBIOS = Yes
- **②** UpdateSMBIOSMode = Create If you have a Dell or VIAO motherboard, please set this to Custom

CustomMemory

Generic

- \bigcirc SpoofVendor = Yes
- \bigcirc AdviseWindows = No
- \bigcirc ProcessorType = 0
- **⊘** SystemMemoryStatus = Auto
- **⊘** SystemProductName = iMac19,1
- **MLB** is set
- **ROM** is set
- **⊘** SystemSerialNumber is set
- **⊘** SystemUUID is set

Memory

UEFI

⊘ ConnectDrivers = Yes

Drivers

- **⊘** HfsPlus.efi
- **⊘** OpenRuntime.efi

APFS

- **⊘** EnableJumpstart = Yes
- **②** GlobalConnect = No If you have an HP motherboard and can't see APFS drives in OpenCore, please enable this
- \bigcirc HideVerbose = Yes
- **⊘** JumpstartHotPlug = No
- \bigcirc MinDate = 0
- \bigcirc MinVersion = 0

Audio

- \bigcirc AudioSupport = No
- \bigcirc AudioDevice = PciRoot(0x0)/Pci(0x1b,0x0)
- \bigcirc AudioCodec = 0
- \bigcirc AudioOut = 0
- **⊘** MinimumVolume = 20
- **⊘** PlayChime = No
- \bigcirc VolumeAmplifier = 0

Input

- **⊘** KeyFiltering = No
- \bigcirc KeyForgetThreshold = 5
- \bigcirc KeyMergeThreshold = 2
- \bigcirc KeySupport = Yes
- **⊗** KeySupportMode = Auto
- \bigcirc KeySwap = No
- \bigcirc PointerSupport = No
- **⊘** PointerSupportMode = ASUS
- \bigcirc TimerResolution = 50000

Output

- **⊘** TextRenderer = BuiltinGraphics
- **⊘** ConsoleMode = -blank-
- \bigcirc Resolution = Max
- \bigcirc ForceResolution = No
- **⊘** ClearScreenOnModeSwitch = No
- \bigcirc IgnoreTextInGraphics = No
- \bigcirc ProvideConsoleGop = Yes
- \bigcirc DirectGopRendering = No
- \bigcirc ReconnectOnResChange = No
- **⊗** ReplaceTabWithSpace = No
- **⊘** SanitiseClearScreen = No
- \bigcirc UgaPassThrough = No

ProtocolOverrides

- \bigcirc AppleAudio = No
- \bigcirc AppleBootPolicy = No
- \bigcirc AppleDebugLog = No
- \bigcirc AppleEvent = No
- \bigcirc AppleFramebufferInfo = No
- \bigcirc AppleImageConversion = No
- **⊘** AppleImg4Verification = No
- \bigcirc AppleKeyMap = No
- \bigcirc AppleRtcRam = No
- \bigcirc AppleSecureBoot = No
- \bigcirc AppleSmcIo = No
- **⊘** AppleUserInterfaceTheme = No
- \bigcirc DataHub = No
- **Our Device Properties = No**
- **⊘ FirmwareVolume** = **No** If you plan to use FileVault2, please enable this
- **⊘** HashServices = No If you plan to use FileVault2, please enable this
- \bigcirc OSInfo = No

⊘ UnicodeCollation = No

Quirks

- \bigcirc DeduplicateBootOrder = Yes
- \bigcirc ExitBootServicesDelay = 0
- \bigcirc IgnoreInvalidFlexRatio = No
- \bigcirc ReleaseUsbOwnership = No
- \bigcirc RequestBootVarRouting = Yes
- \bigcirc TscSyncTimeout = 0
- **②** UnblockFsConnect = No If you have an HP system, please enable this

Reserved Memory