

CAD 9.3.0 Database Schema

Generated: 2014-08-01 09:39:20 CD

Table Definitions (348)

- [abandoned_calls](#)
- [abandoned_calls_history](#)
- [act_device](#)
- [act equip](#)
- [act_persl](#)
- [act_restriction](#)
- [act_station_persl](#)
- [active broker calls](#)
- [agence](#)
- [agency case number](#)
- [agency deplo plan](#)
- [agency_dgroup](#)
- [agency_esz](#)
- [agency_event](#)
- [agency_event_added_req](#)
- [agency_event_history](#)
- [agency_event_resp_plan](#)
- [alarm](#)
- [alarm_log](#)
- [alarm_log2](#)
- [alarmcom](#)
- [alsec_an_al](#)
- [an_al](#)
- [app_access](#)
- [app_display](#)
- [area_mun](#)
- [attachment_content](#)
- [attachment_info](#)
- [audit_log](#)
- [avl_poll_grp](#)
- [backup_beat_list](#)
- [banntlkerp](#)
- [beat](#)
- [boat](#)
- [boundary_a](#)
- [boundary_b](#)
- [broad_xref](#)
- [broadcast](#)
- [broadcast_last_viewed](#)
- [bulk_load_status](#)
- [call_attachment](#)
- [call_data](#)
- [call_history](#)
- [call_info](#)
- [call_info_history](#)
- [call_text](#)
- [call_transition](#)
- [callgroup](#)
- [case_num](#)
- [cast_nar](#)
- [cast_subject](#)
- [cast_vehicle](#)
- [cctv_action_def](#)
- [cctv_camera_def](#)
- [cctv_monitor_def](#)
- [cctv_monitor_term_restrictions](#)
- [cctv_runtime_parameters](#)
- [cd_crews](#)
- [cd_edge_a](#)
- [cd_edge_b](#)
- [cd_node_a](#)
- [cd_node_b](#)
- [cd_turns_a](#)
- [cd_turns_b](#)
- [cd_units](#)
- [cfg_column_list](#)
- [cfg_dialog_mapping](#)
- [cfg_files](#)
- [cfg_id_descr](#)
- [cfg_param_lists](#)
- [cfg_param_table_rows](#)
- [cfg_param_tables](#)
- [cfg_restriction](#)
- [cfg_table_list](#)
- [change_item](#)
- [change_record](#)
- [chat](#)
- [co_pl_a](#)
- [co_pl_b](#)
- [common_event](#)
- [common_event_call](#)
- [common_event_call_history](#)
- [common_event_history](#)
- [conceptual_model_history](#)
- [conn_trans_count](#)
- [cont_name](#)
- [dashboardlog](#)
- [dashboardmode](#)
- [data_guard_role_change](#)
- [db_process](#)
- [db_table_status](#)
- [def_agency_page](#)
- [def_device](#)
- [def equip](#)
- [def_page](#)
- [def_pgroup](#)
- [def_station](#)
- [def_station_crew](#)
- [def_station_crew_restriction](#)
- [def_station_persl](#)
- [def_unit](#)
- [def_unit_restr_ag_avail](#)
- [def_unit_type](#)
- [def_vhic](#)
- [deplo_plan](#)
- [destinations](#)
- [det_ev_ty](#)
- [device_loc_history](#)
- [directory](#)
- [dispass_event](#)
- [dispass_sched_event](#)
- [display_filter_config](#)
- [disposition_type](#)
- [divert](#)
- [eisecc](#)
- [esz](#)
- [ev_dispo](#)
- [ev_ty_alias](#)
- [evcom](#)
- [event_attachment](#)
- [event_attachment_history](#)
- [event_group](#)
- [event_type](#)
- [event_type_alarm_level](#)
- [evgraph](#)
- [extension_list](#)
- [external_request_for_resources](#)
- [external_requested_resource](#)
- [firelinkcasenum](#)
- [firelinkevent](#)
- [firelinkunit](#)
- [fnc_data](#)
- [fs_alert](#)
- [fs_reports](#)
- [fs_status](#)
- [gun](#)
- [help_usage_log](#)
- [highlight_keyword](#)
- [hit_det_tst_not](#)
- [hit_detect_not](#)
- [hit_detect_test](#)
- [hydrt_a](#)
- [hydrt_b](#)
- [incident_tracking](#)
- [infgroup](#)
- [infgroup_member](#)
- [infinketable](#)
- [infori](#)
- [infsec](#)
- [infsignon](#)
- [infuser](#)
- [infxmlparse](#)
- [infxmlparsecet](#)
- [infxmlscheme](#)
- [infxmlsetscheme](#)
- [inter_a](#)
- [inter_b](#)
- [inter_str_a](#)
- [inter_str_b](#)
- [iqa_log](#)
- [iragencydgroup](#)
- [ircadobject](#)
- [irmanual](#)
- [irtcsgroup](#)
- [iruser](#)
- [linemap](#)
- [lineup](#)
- [lineup_crews](#)
- [lineup_device](#)
- [lineup equip](#)
- [lineup_persl](#)
- [loi_data](#)
- [loi_rows](#)
- [loi_search](#)
- [loi_sent](#)
- [loi_status](#)
- [lv_session](#)
- [macro_cmds](#)
- [macro_params](#)
- [mailgateway](#)
- [majevt_act](#)
- [majevt_hst](#)
- [map_switch_table](#)
- [map_views](#)
- [mcgedata](#)
- [mdt_logged_on_persl](#)
- [mdtapcddata](#)
- [mdtbroadcast](#)
- [mdtcommand](#)
- [mdtcommandline](#)
- [mdtcommandmap](#)
- [mdtcommandrouting](#)
- [mdterror](#)
- [mdtfield](#)
- [mdtfieldenumeration](#)
- [mdtfieldenumerationvalues](#)
- [mdtgroup](#)
- [mdtgroupmap](#)
- [mdtvalidation](#)
- [mdtvalidationtype](#)
- [messa](#)
- [message_attachment](#)
- [message_dest](#)
- [message_receive](#)
- [mi_plan_table](#)
- [mi_task_list_table](#)
- [mobile_pda_msg_inbound](#)
- [mobile_pda_msg_outbound](#)
- [mobileclientcomputeridentity](#)
- [mobileclientsysteminformation](#)
- [mr_pending_push_messages](#)
- [mr_unit_response_state](#)
- [mscatalog_a](#)
- [mscatalog_b](#)
- [msg_group](#)
- [netfea_a](#)
- [netfea_b](#)
- [mmsalarm](#)
- [noden](#)
- [numbr](#)
- [oma_mlp_tlr](#)
- [out_of_service_type](#)
- [out_of_service_type_agency](#)
- [page_cond](#)
- [page_cond_interval](#)
- [page_cond1](#)
- [page_keyword](#)
- [page_notify_priority](#)
- [parse_data](#)
- [persl](#)
- [persl_skill](#)
- [perso](#)
- [print_templates](#)
- [priority_times](#)
- [propt](#)
- [pswrd_hist](#)
- [recom_hist](#)
- [remote_event](#)
- [remote_event_comments](#)
- [resp_plan](#)
- [resp_plan_poly](#)
- [resp_req](#)
- [resp_req_res](#)
- [resp_tme](#)
- [road_restrict](#)
- [road_restrict_hist](#)
- [road_restrict_seg](#)
- [road_restrict_seg_hist](#)
- [roster](#)
- [rot equip](#)
- [rot_hist](#)
- [rotate](#)
- [rotate_phone](#)
- [run_card](#)
- [s_calendar](#)
- [save_abandon](#)
- [save_stack](#)
- [save_vw](#)
- [scheduled_dest](#)
- [scheduled_hist](#)
- [scheduled_interval](#)
- [scheduled_items](#)
- [scr_text](#)
- [scratch](#)
- [scrrgp](#)
- [secure_acc](#)
- [seg_alias_a](#)
- [seg_alias_b](#)
- [segrme_a](#)
- [segrme_b](#)
- [sms_pspap_group](#)
- [sms_user](#)
- [sp_ad_a](#)
- [sp_ad_b](#)
- [sp_ad_co_pl_change_log](#)
- [sp_ad_event_type](#)
- [sp_st](#)
- [sp_st_ag](#)
- [sp_st_poly](#)
- [sp_st_type](#)
- [sp_st_type_priority](#)
- [spad_cont_name](#)
- [spad_perso](#)
- [spad_propt](#)
- [spad_vhic](#)
- [sql_audit_log](#)
- [ssgroup](#)
- [ssplan](#)
- [ssplanlev](#)
- [sspost](#)
- [st_cd_a](#)
- [st_cd_b](#)
- [state_badge](#)
- [state_image](#)
- [state_log](#)
- [state_query](#)
- [state_resp](#)
- [station_persl_history](#)
- [subscriber](#)
- [subscription](#)
- [subscription_change_item](#)
- [supp_row](#)
- [supp_srch_crit](#)
- [supp_table10](#)
- [supp_table11](#)
- [supp_table12](#)
- [supp_table13](#)
- [supp_table14](#)
- [supp_table15](#)
- [supp_table16](#)
- [supp_table17](#)
- [supp_table18](#)
- [supp_table19](#)
- [supp_table20](#)
- [supp_table9](#)
- [svvw_ras](#)
- [svvw_ref](#)
- [sys_hist](#)
- [talk_groups_mgmt](#)
- [task_force](#)
- [task_unit](#)
- [telergroupmap](#)
- [term](#)
- [term_alias](#)
- [term_special_app](#)
- [timer](#)
- [timer_history](#)
- [tooltip_file](#)
- [tow_req_and_vhic_history](#)
- [tow_request](#)
- [tow_request_history](#)
- [tow_request_vehicle](#)
- [tow_request_vehicle_history](#)
- [trans_des](#)
- [un_hi](#)
- [un_hi_child_change](#)
- [un_hi_device](#)
- [un_hi_device_loc](#)
- [un_hi_persl](#)
- [unit_wkload](#)
- [update_status](#)
- [ushis](#)
- [usrgrp](#)
- [valid_device](#)
- [valid_unit](#)
- [vehic](#)
- [vivistanodes](#)
- [xref](#)

View Definitions (7)

- [aeven](#)
- [ev_ty](#)
- [map_switch](#)
- [nodeassign](#)
- [event](#)
- [multi_response_view](#)
- [time_zone_info](#)

Conceptual Model Entity Types (233)

- [AbandonedCall](#)
- [AbandonedCallHistory](#)
- [AbandonedEvent](#)
- [ActiveBrokerCall](#)
- [ActiveCrew](#)
- [ActiveCrewRestriction](#)
- [ActiveStationEmployee](#)
- [ActiveStationEmployeeHistory](#)
- [ActiveUnit](#)
- [ActiveUnitChildChangeHistory](#)
- [BroadcastViewingTerminal](#)
- [CallAttachment](#)
- [CallInfo](#)
- [CallInfoHistory](#)
- [CallText](#)
- [CallTransition](#)
- [CatalogedAlarm](#)
- [CatalogedAlarmCommentLine](#)
- [CatalogedAlarmContact](#)
- [CatalogedAlarmPerson](#)
- [CommonEventSupplement19History](#)
- [CommonEventSupplement20](#)
- [CommonEventSupplement20History](#)
- [CommonEventSupplement9](#)
- [CommonEventSupplement9History](#)
- [CommonEventVehicle](#)
- [CommonEventVehicleHistory](#)
- [CommonPlaceContact](#)
- [CommonPlacePerson](#)
- [CommonPlaceProperty](#)
- [MapSpecialAddress](#)
- [MapStreet](#)
- [MdtLoggedOnEmployee](#)
- [Message](#)
- [MessageAttachment](#)
- [MessageDestination](#)
- [MessageGroupMember](#)
- [MessageReceive](#)
- [MultiEventTransportLocation](#)
- [NextNumber](#)

- [ActiveUnitDevice](#)

• [ActiveUnitDeviceHistory](#)

• [ActiveUnitEmployee](#)

• [ActiveUnitEmployeeDevice](#)

• [ActiveUnitEmployeeDeviceHist](#)

• [ActiveUnitEmployeeHistory](#)

• [ActiveUnitEquipment](#)

• [ActiveUnitHistory](#)

• [Agency](#)

• [AgencyCaseNumber](#)

• [AgencyDeploymentPlan](#)

• [AgencyDispatchGroup](#)

• [AgencyEvent](#)

• [AgencyEventAccess](#)

• [AgencyEventAccessHistory](#)

• [AgencyEventAddedRequirement](#)

• [AgencyEventCaseId](#)

• [AgencyEventDetailedEventType](#)

• [AgencyEventDisposition](#)

• [AgencyEventDispositionHistory](#)

• [AgencyEventDispositionType](#)

• [AgencyEventGroup](#)

• [AgencyEventHistory](#)

• [AgencyEventPriorityTimeDefault](#)

• [AgencyEventResponsePlan](#)

• [AgencyEventSchedule](#)

• [AgencyEventScheduleHistory](#)

• [AgencyEventTimer](#)

• [AgencyEventTimerHistory](#)

• [AgencyEventType](#)

• [AgencyEventTypeAlias](#)

• [AgencyEventTypeResponse](#)

• [AgencyRosterUnitEmployee](#)

• [AniAicallInfo](#)

• [ApplicationDispatchGroupAccess](#)

• [ApplicationDisplay](#)

• [AttachmentContent](#)

• [AttachmentInfo](#)

• [Broadcast](#)

• [BroadcastCommentLine](#)

• [BroadcastDestination](#)

• [BroadcastHistory](#)

• [BroadcastPerson](#)

• [BroadcastPersonHistory](#)

• [BroadcastReference](#)

• [BroadcastReferenceHistory](#)

• [BroadcastVehicle](#)

• [BroadcastVehicleHistory](#)

• [CatalogedAlarmProperty](#)

• [CatalogedAlarmVehicle](#)

• [ChangeItem](#)

• [ChangeSubscriber](#)

• [ChangeSubscription](#)

• [ChangeSubscriptionChangeItem](#)

• [CommandHistory](#)

• [CommonEvent](#)

• [CommonEventAttachment](#)

• [CommonEventAttachmentHistory](#)

• [CommonEventBoat](#)

• [CommonEventBoatHistory](#)

• [CommonEventCall](#)

• [CommonEventCallHistory](#)

• [CommonEventCommentLine](#)

• [CommonEventContact](#)

• [CommonEventContactHistory](#)

• [CommonEventGun](#)

• [CommonEventGunHistory](#)

• [CommonEventHistory](#)

• [CommonEventIncidentState](#)

• [CommonEventIncidentStateHist](#)

• [CommonEventIqaStep](#)

• [CommonEventIqaStepHistory](#)

• [CommonEventLvSession](#)

• [CommonEventPerson](#)

• [CommonEventPersonHistory](#)

• [CommonEventProperty](#)

• [CommonEventPropertyHistory](#)

• [CommonEventSupplement10](#)

• [CommonEventSupplement10History](#)

• [CommonEventSupplement11](#)

• [CommonEventSupplement11History](#)

• [CommonEventSupplement12](#)

• [CommonEventSupplement12History](#)

• [CommonEventSupplement13](#)

• [CommonEventSupplement13History](#)

• [CommonEventSupplement14](#)

• [CommonEventSupplement14History](#)

• [CommonEventSupplement15](#)

• [CommonEventSupplement15History](#)

• [CommonEventSupplement16](#)

• [CommonEventSupplement16History](#)

• [CommonEventSupplement17](#)

• [CommonEventSupplement17History](#)

• [CommonEventSupplement18](#)

• [CommonEventSupplement18History](#)

• [CommonEventSupplement19](#)

• [CommonPlaceVehicle](#)

• [CrossReference](#)

• [DefinedCrew](#)

• [DefinedCrewRestriction](#)

• [DefinedDevice](#)

• [DefinedEmployee](#)

• [DefinedEmployeeAccessHistory](#)

• [DefinedEmployeePasswordHistory](#)

• [DefinedEmployeeSkill](#)

• [DefinedEmployeeStatus](#)

• [DefinedEmployeeTerminalAccess](#)

• [DefinedGroupEmployee](#)

• [DefinedPager](#)

• [DefinedPagerGroupMember](#)

• [DefinedStation](#)

• [DefinedStationEmployee](#)

• [DefinedUnit](#)

• [DefinedUnitType](#)

• [DefinedVehicle](#)

• [DefinedVehicleEquipment](#)

• [DeploymentBeat](#)

• [DeploymentPlan](#)

• [DeploymentResponse](#)

• [DeploymentResponseBackupBeat](#)

• [DeploymentRunCardUnit](#)

• [Destination](#)

• [DispatchAssignedEvent](#)

• [DispatchGroupResponseTime](#)

• [ExternalRequestedResource](#)

• [ExternalRequestForResources](#)

• [FireStationAlert](#)

• [FireStationReport](#)

• [GeneralTimer](#)

• [GeneralTimerHistory](#)

• [HospitalDiversion](#)

• [LineupCrew](#)

• [LineupUnit](#)

• [LineupUnitDevice](#)

• [LineupUnitEmployee](#)

• [LineupUnitEmployeeDevice](#)

• [LineupUnitEquipment](#)

• [LocationOfInterestData](#)

• [LocationOfInterestSearch](#)

• [LocationOfInterestSearchStatus](#)

• [MapCommonPlace](#)

• [MapEdge](#)

• [MapNode](#)

• [MapSegment](#)

• [OutOfServiceType](#)

• [OutOfServiceTypeAgency](#)

• [RecommendHistory](#)

• [RemoteAgencyEvent](#)

• [RemoteAgencyEventComment](#)

• [ResponsePlanPolygon](#)

• [ResponsePlanRequirement](#)

• [ResponseReqCriterionResource](#)

• [ResponseRequirementCriterion](#)

• [RoadRestriction](#)

• [RoadRestrictionHistory](#)

• [RoadRestrictionSegment](#)

• [RoadRestrictionSegmentHistory](#)

• [RotationalServiceCompany](#)

• [RotationalServiceCompanyPhone](#)

• [RotationalServiceEquipment](#)

• [RotationalServiceInstance](#)

• [ScheduledDispatchAssignedEvent](#)

• [ScheduledItem](#)

• [ScheduledItemDestination](#)

• [ScheduledItemHistory](#)

• [ScheduledItemInterval](#)

• [ScratchPad](#)

• [ScratchPadGroup](#)

• [ScratchPadTextLine](#)

• [SpecialAddressContact](#)

• [SpecialAddressEventType](#)

• [SpecialAddressPerson](#)

• [SpecialAddressProperty](#)

• [SpecialAddressVehicle](#)

• [SpecialSituation](#)

• [SpecialSituationAgency](#)

• [SpecialSituationType](#)

• [SpecialSituationTypePriority](#)

• [StackedEvent](#)

• [Terminal](#)

• [TerminalSpecialApplication](#)

• [TowRequest](#)

• [TowRequestAndVehicleHistory](#)

• [TowRequestHistory](#)

• [TowRequestVehicle](#)

• [TowRequestVehicleHistory](#)

• [TransportLocation](#)

• [UnitAgencyRestriction](#)

• [UnitTimer](#)

• [UnitTimerHistory](#)

• [UnitWorkload](#)

• [ValidDevice](#)

• [ValidUnit](#)
- Functions (50)
- Procedures (9)
- Oracle Sequences (1)
- Oracle Packages (1)
- Database Procedural Code (19)
- Miscellaneous Items (5)
- Conceptual Model Database Procedural Code (6)
-  [Top](#)
- | Table Name - abandoned_calls | | | | | | |
|---|---|-----------------|------|-------------------|--|--|
| Description | This table stores abandoned calls. An abandoned call is an incoming call that is terminated before an operator has the chance to answer it. | | | | | |
| Copy Type | ALL | | | | | |
| Columns | | | | | | |
| Column Name | Oracle Type | Sql Server Type | NULL | Constraint | Description | |
| abandoned_dts | varchar2(16) | varchar(16) | no | ipsTimestamp | Abandoned time - when abandoned call record is created in database. | |
| abandonments | number(10,0) | int | no | nonNegativeNumber | Number of calls from this phone number that have been abandoned. | |
| call_id | varchar2(20) | varchar(20) | no | | Call id for the current abandoned call | |
| callback_attempt_dts | varchar2(16) | varchar(16) | yes | ipsTimestamp | Date and time of last callback attempt | |
| callback_attempts [default = 0] | number(10,0) | int | no | nonNegativeNumber | Number of callback attempts | |
| caller_phone | varchar2(20) | varchar(20) | no | | Caller's number | |
| first_abandoned_dts | varchar2(16) | varchar(16) | no | ipsTimestamp | When first abandoned call arrived in the system | |
|  first_call_id | varchar2(20) | varchar(20) | no | | Unique Call ID in CAD system for the first call from this number. Serves as a unique id for a set of abandoned calls | |
| location | varchar2(512) | varchar(512) | yes | | Location (address or X_Uors/Y_Uors) of caller. | |
| psap_id | varchar2(10) | varchar(10) | no | | Id of the PSAP the call came in on. | |
| received_dts | varchar2(16) | varchar(16) | no | ipsTimestamp | Date and Time of when the call appeared on the system | |
| rev_num | number(10,0) | int | no | nonNegativeNumber | Revision number for this record | |
| vendor | varchar2(20) | varchar(20) | no | | The telephone vendor of the call. | |
| Key Constraints | | | | | | |
| Constraint Name | Columns | | | Constraint Type | Sql Server Clustered | |
| abandoned_calls_pk | first_call_id | | | primaryKey | no | |
| abandoned_calls_uk | caller_phone, psap_id | | | uniqueKey | yes | |
-  [Top](#)
- | Table Name - abandoned_calls_history | | | | | | |
|--------------------------------------|---|-----------------|------|-------------------|---|--|
| Description | This table stores the history of abandoned calls. | | | | | |
| Copy Type | INSERT | | | | | |
| Columns | | | | | | |
| Column Name | Oracle Type | Sql Server Type | NULL | Constraint | Description | |
| abandoned_dts | varchar2(16) | varchar(16) | no | ipsTimestamp | Abandoned time - when abandoned call record is created in database. | |
| abandonments | number(10,0) | int | no | nonNegativeNumber | Number of calls from this phone number that have been abandoned. | |
| call_id | varchar2(20) | varchar(20) | no | | Call id for the current abandoned call | |
| callback_attempt_dts | varchar2(16) | varchar(16) | yes | ipsTimestamp | Date and time of last callback attempt | |
- 2 de 200
- 21/9/2026, 11:47

callback_attempts [default = 0]	number(10,0)	int	no	nonNegativeNumber	Number of callback attempts
caller_phone	varchar2(20)	varchar(20)	no		Caller's number
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Time row was created
comments	varchar2(256)	varchar(256)	yes		Comments
connect_terminal	varchar2(15)	varchar(15)	yes		If not null, the terminal that successfully called back or answered a call from the number.
connect_type [default = 0]	number(5,0)	smallint	no	connect_type >= 0 and connect_type <= 10	Connection type. Values may include: 0 = This number never connected; 1 = Successfully called back; 2 = Successfully answered via voice; 3 = Successfully answered via SMS -
first_abandoned_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	When first abandoned call arrived in the system
 first_call_id	varchar2(20)	varchar(20)	no		Unique Call ID in CAD system for the first call from this number. Serves as a unique id for a set of abandoned calls.
location	varchar2(512)	varchar(512)	yes		Location (address or X_Uors/Y_Uors) of caller.
psap_id	varchar2(10)	varchar(10)	no		ID of the PSAP the call came in on
received_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date and Time of when the call appeared on the system
 rev_num	number(10,0)	int	no	nonNegativeNumber	Revision number for this record
vendor	varchar2(20)	varchar(20)	no		The telephone vendor of the call.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
abandoned_calls_his_phone_psap	caller_phone, psap_id		no	yes	
abandoned_calls_history_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
abandoned_calls_history_pk	first_call_id, rev_num		primaryKey		no

 [Top](#)

Table Name - act_device					
Description	Act_device stores devices associated with logged on units, unit personnel, and unit vehicles. When units are logged on, the devices such as GPS Device, and radio alias may be pulled from def_device (or lineup_device if logging on units from a lineup), or the user can manually override the device information. MDT Server should be the only application that inserts, updates or deletes MDT ID rows. When signing on people to units, the person's defined devices, such as HT Radio, can be pulled from def_device/ lineup_device or manually overridden by the user. I/Tracker updates the location fields in this table, and CAD can update the other fields. The history information for the location fields is in un_hi_device_loc and the history of changes to the other device columns is in un_hi_device. CR 1-6PGD42: PLT				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
altitude	binary_double	float(53)	yes		Distance above mean sea level (+ above)
apodata	varchar2(64)	varchar(64)	yes		IP Address and port last received by the MDT Server from the Client
bearing	binary_double	float(53)	yes	bearing between 0 and 360	Clockwise angle from true North range [0, 360.0]
clientid	varchar2(64)	varchar(64)	yes		Contains the unique ID provided by the MPS Client
description	varchar2(50)	varchar(50)	yes		Description
device_alias	varchar2(20)	varchar(20)	yes		User-friendly alias name for device
 device_id	varchar2(40)	varchar(40)	no		Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
 device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
empid	number(10,0)	int	yes	nonNegativeNumber	If owner =1, employee that owns this device. Links to act_persl.empid
fix_age	number(5,0)	smallint	yes	fix_age between 0 and 2	Code for age of fix when this location was recorded (not the current age of the data). 0=unknown, 1=10 seconds or greater, 2=less than 10 seconds
fix_type	number(5,0)	smallint	yes	fix_type in (0,1,2,3,6,8,9)	GPS source (fix type) indicator. 0=2D, 1=3D, 2=2D-differential, 3=3D-differential, 6=dead reckoning, 8=degraded, 9=unknown/invalid
gps_date	varchar2(8)	varchar(8)	yes		Date of last GPS data from the device, in YYYYMMDD format
gps_protocol [default = 0]	number(5,0)	smallint	no	nonNegativeNumber	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols
gps_time	number(10,0)	int	yes		Time of last GPS data from the device, stored in seconds since midnight UTC
horizontal_precision	number(5,0)	smallint	yes	horizontal_precision between 0 and 50	Horizontal dilution of precision: 1=ideal, 2-3=excellent, 4-6=good, 7-8=moderate, 9-20=fair, 21-50=poor
is_master_mdt [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	From MDT Server's perspective, is this the master device for this unit? 1= Master device, 0= Not master device.
is_trackable [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	Is device trackable? 0 = False, 1 = True
latitude	binary_double	float(53)	yes		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
loc_updated_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Datetime when location was last updated
loc_x	number(10,0)	int	yes		Last known x-coordinate of the device
loc_y	number(10,0)	int	yes		Last known y-coordinate of the device
location	varchar2(80)	varchar(80)	yes		Location, derived from reverse geocoding the device's coordinates.
longitude	binary_double	float(53)	yes		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
owner	number(5,0)	smallint	no	owner between 0 and 1	Device's owner. 0 = unit, 1 = employee
sat_count	number(10,0)	int	yes	nonNegativeNumber	Number of satellites used in fix
sensor	varchar2(150)	varchar(150)	yes		Sensor data. Previously called device in old avl_log table
smartphone_device_id	varchar2(64)	varchar(64)	yes		Physical device id of the Apple iOS, Android, Windows Phone, etc. device
smartphone_os	number(10,0)	int	yes	smartphone_os between 0 and 3	Type of smartphone. 0= Apple iOS, 1= Android, 2= BlackBerry, 3= Windows
smartphone_push_token	varchar2(256)	varchar(256)	yes		Token used to push data back to the device
speed_bearing	binary_double	float(53)	yes		Speed along the bearing (+ forward, - reverse).
speed_vertical	binary_double	float(53)	yes		Speed vertical (+ up, - down)
tdevice_for_emp	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False
tdevice_for_unit	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False
 unid	varchar2(10)	varchar(10)	no		Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.
units_of_measurement [default = 0]	number(5,0)	smallint	no	units_of_measurement between 0 and 2	Units of measurement. 0=unknown, 1=metric (meters/KPH), 2=imperial (feet/MPH)
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
act_device_clientid	clientid		no	no	
act_device_owner	owner		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
act_device_pk	unid, device_id, device_type, device_sub_type			primaryKey	yes
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
act_device_is_master_mdt_type		Yes	(is_master_mdt = 1 and device_type = 6) or is_master_mdt = 0		(is_master_mdt = 1 and device_type = 6) or is_master_mdt = 0
act_device_latlon_ck		Yes	(loc_x is null and loc_y is null and latitude is null and longitude is null) or (loc_x is not null and loc_y is not null and latitude is not null and longitude is not null)		(loc_x is null and loc_y is null and latitude is null and longitude is null) or (loc_x is not null and loc_y is not null and latitude is not null and longitude is not null)

act_device_mdt_smt_id_ck	Yes	(device_type not in (5,6)) or (regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$'))	(device_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)
act_device_owner2_ck	Yes	(owner = 0 and empid is null) or (owner = 1 and empid is not null)	(owner = 0 and empid is null) or (owner = 1 and empid is not null)
act_device_tdevice_ck	Yes	(is_trackable = 1 or (tdevice_for_emp = 0 and tdevice_for_unit = 0)) and (owner = 1 or tdevice_for_emp = 0)	(is_trackable = 1 or (tdevice_for_emp = 0 and tdevice_for_unit = 0)) and (owner = 1 or tdevice_for_emp = 0)
Triggers			
Trigger Name	Required	Trigger Type	Description
act_device_trig	Yes	Custom	Populates valid_device with new device id, device type, device sub-type values
act_device_trig2	No	Custom	Verifies that each device is only used once

[Top](#)

Table Name - act_equip					
Description	This table holds the equipment present on the all the currently active units in the system. It is managed in exactly the same manner as the cd_units table and works in conjunction with that table				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 equip	varchar2(10)	varchar(10)	no		Equipment present on this unit
num_equip	number(10,0)	int	no	nonNegativeNumber	Number of pieces of this equipment
 unid	varchar2(10)	varchar(10)	no		Unit identification - this column provides a link to the cd_units table record
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
act_equip_primary_key	unid, equip			primaryKey	yes

[Top](#)

Table Name - act_persl					
Description	The employees assigned to this unit. There must be at least one per unit.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 empid	number(10,0)	int	no	nonNegativeNumber	Employee assigned to this unit.
prev_unid	varchar2(10)	varchar(10)	yes		The previous unit id that the employee was in prior to the current unit. This information is set to NULL during each log on.
primary_empid [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Primary employee. T = True, F = False
 unid	varchar2(10)	varchar(10)	no		Unit id
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
act_persl_primary_key	unid, empid			primaryKey	yes

[Top](#)

Table Name - act_restriction						
Description		This table contains the restrictions on all the currently active crews. It is managed in exactly the same manner as the cd_crews table and works in conjunction with that table.				
Copy Type		ALL				
Column Name		Oracle Type	Sql Server Type	NULL	Constraint	Description
	crew_id	varchar2(30)	varchar(30)	no		Crew ID. This column links to the crew_id column in the cd_crews table.
	restriction	varchar2(10)	varchar(10)	no		Crew Restriction when crew is logged on. This may be a unit id or a unit type based on the crew's restriction_type attribute.
Key Constraints						
Constraint Name		Columns		Constraint Type		Sql Server Clustered
act_restriction primary key		crew_id, restriction		primaryKey		yes

[Top](#)

Table Name - act_station_persl					
Description	Personnel who are currently logged on to a station. Station personnel can be explicitly logged on via the logon station personnel command, or implicitly logged on when personnel are assigned to a unit via logon unit or unit properties, and that unit is associated with a station. When a station person is assigned to a unit, the unit id can be found in the act_persl table. Added for CR 1-4UUSDH				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
delay_value [default = 0]	number(10,0)	int	no	nonNegativeNumber	Delay, in minutes. Amount of time it would take this person to get to the station.
description	varchar2(200)	varchar(200)	yes		Description or comment
 empid	number(10,0)	int	no	nonNegativeNumber	Employee id
logon_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Logged on timestamp
logon_method	number(10,0)	int	no	booleanNumber1Or0	The method by which the person was logged on to the station. 0= Logged on implicitly by Logon Unit or Unit Properties. 1= Logged on explicitly by dispatcher using Logon Station Personnel command.
recommended_unid	varchar2(10)	varchar(10)	yes		Unit for which the employee has been recommended. Recommend Unit will set this column.
station	varchar2(10)	varchar(10)	no		Station id
status	number(10,0)	int	no	status in (0,1,2,3)	Current status. 0= available, 1= unavailable (due to a break or other temporary reason), 2= unavailable because the person is currently assigned to a unit, 3 = unavailable because Recommend Unit has recommended this person for a unit (recommended_unid contains the recommended unit id).
status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Time when person changed to current status.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
act_station_persl_pk	empid			primaryKey	yes
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
act_station_persl_status_un_ck		Yes	(status = 3 and recommended_unid is not null) or (status !=3 and recommended_unid is null)		(status = 3 and recommended_unid is not null) or (status !=3 and recommended_unid is null)

[Top](#)

Table Name - active_broker_calls					
Description	Internal table used by Intergraph Communications Controller to persist internal caches in support of failovers				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
broker_message	clob	varchar(max)	no		Message sent from client to broker persisted to database, used to restore BrokerCore caches in the case of failover.
call_id	varchar2(20)	varchar(20)	yes		Unique Call ID in CAD for the call from this number.

cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Time message is received by the BrokerCore.
term	varchar2(15)	varchar(15)	no		The terminal of the client that the message came from
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Unique ID for a row in the table
vendor	varchar2(20)	varchar(20)	no		The telephone vendor name from the message received by the BrokerCore.
vendor_local_call_id	varchar2(64)	varchar(64)	no		Vendor specific local call id from the client terminal from the message received by the BrokerCore.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
act_broke_calls_vlci_term_vend	vendor_local_call_id, term, vendor		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
active_broker_calls_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - agenc					
Description	This table contains a record for each agency defined in the I/CAD system. The active deployment plan and active lineup columns are modified to reflect active plans.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
act_pln	varchar2(30)	varchar(30)	no		Active deployment plan. Defines the deployment plan that is currently used for this agency.
ag_add	varchar2(30)	varchar(30)	yes		Agency address
ag_city	varchar2(20)	varchar(20)	yes		Agency city.
 ag_id	varchar2(9)	varchar(9)	no		Unique Agency ID number used throughout I/CAD
ag_nme	varchar2(50)	varchar(50)	yes		Agency's full name
ag_st	varchar2(4)	varchar(4)	yes		Agency state.
ag_typ	varchar2(8)	varchar(8)	yes		Agency type. Police, fire, etc. This value is used in the agency list gadget on the calltaker/dispatcher form and other forms commands as necessary.
ag_zip	varchar2(10)	varchar(10)	yes		Agency zip code.
contact	varchar2(20)	varchar(20)	yes		Agency contact person.
lineup_name	varchar2(30)	varchar(30)	yes		Active line-up for agency
num_1	number(10,0)	int	no		Identifies row in numbr table containing next available event number for agency. Written to num_1 column in agency_event table for all events created for agency
num_2	number(10,0)	int	yes		Identifies row in numbr table containing Dispatch Number Table ID for this agency
permxfer [default = 'F']	varchar2(1)	varchar(1)	no	booleanTorF	Permanent Transfer Flag. (T) = permanent unit transfer to another dispatch group, (F) = temporary transfer
phone	varchar2(14)	varchar(14)	yes		Agency telephone number.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
agenc_primary_key	ag_id			primaryKey	yes

 [Top](#)

Table Name - agency_case_number						
Description		The agency_case_number table is used to allow any number of case types to be defined for an agency.				
Copy Type		ALL_WITH_CHECK				
Columns						
Column Name		Oracle Type	Sql Server Type	NULL	Constraint	Description
	ag_id	varchar2(9)	varchar(9)	no		The ag_id column specifies the agency identifier the case number specification is to be associated with.
	cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The cdts column specifies the creation date, time stamp of the record.
	num	number(10,0)	int	no		The num column specifies the numbr table that will be used to retrieve case numbers.
Key Constraints						
Constraint Name		Columns		Constraint Type		Sql Server Clustered
agency_case_number_primary_key		ag_id, num		primaryKey		yes

 [Top](#)

Table Name - agency_deplo_plan					
Description	Defines what deployment plans are valid for each agency.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency ID
 deplo_plan_name	varchar2(30)	varchar(30)	no		Deployment plan name
description	varchar2(50)	varchar(50)	yes		User-defined comment or description. For example, this column might explain when the agency uses this deployment plan.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
agency_deplo_plan_pk	ag_id, deplo_plan_name			primaryKey	yes

 [Top](#)

Table Name - agency_dgroup					
Description	Stores information about the valid dispatch groups for each agency. CADDDBM uses this table to ensure that users enter valid dispatch groups.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency ID
description	varchar2(50)	varchar(50)	yes		Description for dispatch group
 dgroup	varchar2(5)	varchar(5)	no		Dispatch Group
page_id	varchar2(12)	varchar(12)	yes		Pager ID or Pager Group ID from def_page. If the page_id is not specified in the page_notify_priority table, I/Page will look for the page_id in this table. I/Page sends notifications to this page identifier when new events are created with the specified agency and dispatch group.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
agency_dgroup_pk	ag_id, dgroup			primaryKey	yes

 [Top](#)

Table Name - agency_esz	
Description	Used to translate system ESZ values into agency ESZ values.
Copy Type	ALL_WITH_CHECK
Columns	

Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
a_esz	number(10,0)	int	no		Agency emergency service zone. Links to esz in esz table.
ag_id	varchar2(9)	varchar(9)	no		Agency id.
s_esz	number(10,0)	int	no		System emergency service zone. This value is generated from the numbr table using num_id -12.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
agency_esz_primary_key	s_esz, ag_id		primaryKey		yes

 [Top](#)

Table Name - agency_event					
Description	This table holds event information specific to agencies assigned to events. The records are created by I/CAD only.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
acknowledge_timer	number(10,0)	int	no	acknowledge_timer between 0 and 32766	Acknowledge Alarm Timer. How long a unit on this event can be in the acknowledgement status before an alarm sounds.
ad_sec	number(19,0)	bigint	no		Ad_ts time stamp stored in epoch seconds
ad_ts	varchar2(16)	varchar(16)	no	ipsTimestamp	Time event was actually added into system
ad_ts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Time event was actually added into system
accust1	varchar2(50)	varchar(50)	yes		Agency event custom column 1
accust2	varchar2(50)	varchar(50)	yes		Agency event custom column 2
accust3	varchar2(50)	varchar(50)	yes		Agency event custom column 3
accust4	varchar2(50)	varchar(50)	yes		Agency event custom column 4
ag_id	varchar2(9)	varchar(9)	no		Agency ID for the agency associated with the event
alarm_lvl	number(10,0)	int	no	nonNegativeNumber	Alarm Level for the event
appt_alarm_until	varchar2(16)	varchar(16)	yes	ipsTimestamp	Datetime stamp for next appointment alarm time
appt_end_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Appointment end date/time stamp. Appointment is to be completed by this date/time.
appt_start_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Appointment start date/time stamp. The earlier time in an appointment window. For an appointment this will be a fixed, default time, typically at the beginning of the work day.
ar_sec	number(19,0)	bigint	yes		Ar_ts time stamp stored in epoch secs
ar_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time that the first unit arrived on the scene
arrive_timer	number(10,0)	int	no	arrive_timer between 0 and 32766	Arrive alarm timer. How long a unit on this event can be in the arrive status before an alarm sounds.
assigned_units	number(5,0)	smallint	no	nonNegativeNumber	This column is used to keep track of the number of units assigned to the event.
callback_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Event call back timer expiration date time stamp. Null if no timer.
cbtime2 [default = 0]	number(10,0)	int	no		Event repeat call back timer value. Zero if no timer.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp.
closing_allowed [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Indicates that there are no items pending that would prevent the event from being closed.T or F
cpers	number(10,0)	int	no		Creating person empid number
cterm	varchar2(15)	varchar(15)	no		Creating Terminal
dest_cid	number(10,0)	int	yes		Scheduled Event destination. This is a secondary event record for a scheduled event which holds its final destination. The starting point is in the first event record.
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group handling event
dispass_unit	varchar2(10)	varchar(10)	yes		ID of Unit event is dispatch assigned to (NULL if event is not dispatch assigned)
dispatch_timer	number(10,0)	int	no	dispatch_timer between 0 and 32766	Dispatch Alarm Timer. How long a unit on this event can be in the dispatched status before an alarm sounds.
ds_sec	number(19,0)	bigint	yes		Ds_ts time stamp stored in epoch seconds
ds_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Dispatched Time Stamp. Time that the first unit was dispatched to the event.
due_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Due date/time stamp. The latest time that an event can be scheduled, typically an internal constraint. Typically not used to record an agreement between two
eid	number(10,0)	int	no	positiveNumber	Unique Event Id Number generated by the system
en_sec	number(19,0)	bigint	yes		En_ts time stamp stored in epoch seconds
en_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time first unit was enroute to event
enroute_timer	number(10,0)	int	no	enroute_timer between 0 and 32766	Enroute Alarm Timer. How long a unit on this type of event can be in the enroute status before an alarm sounds
esz [default = -1]	number(10,0)	int	no		Emergency Service Zone for verified location. Level 1 area code from deployment table.
eta	number(10,0)	int	yes		Estimated Time of Arrival. For AutoDispatch events, the ETA is the estimated time in minutes from the current time that it will take for a unit to arrive at the event.
evt_rev_num	number(10,0)	int	no		Common event revision number corresponding to this agency event revision.
ex_evt [default = 'F']	varchar2(1)	varchar(1)	no	booleanTorF	Exempt event flag, identifies events exempt from contracted time limits for response. (T) if exempt, (F) otherwise.
external_event_id	varchar2(30)	varchar(30)	yes		InterCAD column, event id from a foreign system
flags [default = 0]	number(10,0)	int	no	flags between 0 and 127	Flags column contains event attributes. Each bit represents a boolean value. 1 = Secure access, 2 = Event has graphics, 4 = Event has common graphics, 8 = Units have been dispatched to event, 16 = Event has SOP, 32 = Event's location is a special address using specific map levels, 64 = Event has attachments
group_id	varchar2(12)	varchar(12)	yes		The id of the group that this event belongs to
group_order	number(10,0)	int	yes		Order of event in group.
hold_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/Time when held/agreed response event will become a pending event
hold_type [default = 0]	number(10,0)	int	no	hold_type between 0 and 3	Held Event Type Code indicates hold status of the event: 0 = not held, 1 = held , 2 = agreed response, 3 = broadcast held
hold_unt	varchar2(10)	varchar(10)	yes		ID of unit event is held for
is_open	varchar2(1)	varchar(1)	no	booleanTorF	T if the event is open, F otherwise
is_rec_enabled [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Controls whether additional unit recommendations are performed for the event. T - recommendations are generated, F - further recommendations are disabled
is_rec_preempt_enabled [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Controls whether unit recommendations for the event can suggest units to be preempted. T - preempts are allowed, F - preempts are disabled
late_run [default = 'F']	varchar2(1)	varchar(1)	no	booleanTorF	Late run event. (T) indicates response time requirement for event was not met and late run information is present in the evcom table. F otherwise
lev2	varchar2(6)	varchar(6)	yes		Level 2 area code from the deployment table
lev3	varchar2(7)	varchar(7)	yes		Beat (Level 3 area code from the deployment table)
lev4	varchar2(5)	varchar(5)	yes		Zone (Level 4 area code from the deployment table)
lev5	varchar2(5)	varchar(5)	yes		District (Level 5 area code from the deployment table)
loi_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the agency_event record will no longer be retrieved by LOI searches.
majevt_evty	varchar2(10)	varchar(10)	yes		Major event type. Identifies this event as a major event. It is set based on the major event id from the event table and points to a major event plan. Major event software must be running for this to work.
majevt_loc	varchar2(10)	varchar(10)	yes		Major Event Location. It is set based on the major event id from the alarm or sp_ad table (retrieved by Location Verify) and points to a major event plan. Major event software must be running for this to function.
multi_event_id [default = '0']	varchar2(12)	varchar(12)	no		For Multi-Response events, this column contains the agency event ID (num_1) from the master event, which ties together all rows that belong to a particular multi-response event. If the row is not part of a multi-response event, the multi_event_id is set to 0.

multi_event_response	varchar2(1)	varchar(1)	yes	multi_event_response in ('B', 'D', 'M', 'O')	Multi-Event Response (MRE) flag: 'O' = Starting Origin- the trans_des.origin_location of this row defines the starting origin of the MRE. 'D' = Final Destination - the trans_des.location of this row defines the final destination of the MRE. 'B' = Both - the trans_des row represents both the origin and the destination of the entire MRE. 'M' = Master Event record. NULL = Intermediate response, or event is not part of a MRE.
mun	varchar2(40)	varchar(40)	yes		Municipality (Level 6 area code from the deployment table)
 num_1	varchar2(12)	varchar(12)	no		Agency "event" number
pend_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Pending Event Date/Time Stamp is the time at which the pending events alarm will go off.
pending_timer	number(10,0)	int	no	pending_timer between 0 and 32766	Pending Alarm Timer. How long this event can stay pending before an alarm sounds.
planned_task_end_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Planned task end time. Used by the Resource Scheduler
planned_task_start_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Planned task start time. Used by Resource Scheduler
prim_member	number(10,0)	int	yes		Employee id number of primary unit member (if a primary unit is assigned) or the operator id (if a primary unit is not assigned)
prim_unit	varchar2(10)	varchar(10)	yes		Primary Unit. ID of unit that reported disposition code, requested case number via Assign Case Number, or arrived on the scene with the case number.
priority	number(10,0)	int	no	priority between 0 and 9	Event Priority (0-9) for agency from event_type table.
priority_changed_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The last time that the priority changed.
probe_flag	varchar2(16)	varchar(16)	yes	ipsTimestamp	Probe Data Indicator Flag. Timestamp used to indicate when event data was transferred to RMS. May be used by I/LEADS-Link, FireLink or CADLink.
proqa_case_num	varchar2(12)	varchar(12)	yes		ProQA case number received from ProQA Paramount
proqa_case_type	varchar2(10)	varchar(10)	yes	proqa_case_type in ('MEDICAL', 'FIRE', 'POLICE')	ProQA case type
rec_fea_mslink [default = 0]	number(10,0)	int	no		Special feature ID to use when recommending units for the event
rec_select_mode [default = 3]	number(10,0)	int	no	rec_select_mode in (0,1,2,3)	Unit selection mode for recommendations. 0 - use available only, 1 - use assigned units to fill missing requirements, 2 - use any unit, 3 - use default
rec_x_cord [default = 0]	number(10,0)	int	no		Special X coordinate to use when recommending units for the event
rec_y_cord [default = 0]	number(10,0)	int	no		Special Y coordinate to use when recommending units for the event
recom_incomplete [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	'T' when last unit recommendation was incomplete for event, 'F' otherwise
recommend_mode [default = 3]	number(10,0)	int	no	recommend_mode in (0,1,2,3)	Recommendation mode for event. 0 - beats, 1 - street network, 2 - closest, 3 - use default
reopen	varchar2(1)	varchar(1)	no	booleanTOrF	This column will be used to indicate that an agency event has been reopened. The column will have a value of 'F' to indicate that the event has not been reopened. The column will have a value of 'T' to indicate that the event has been reopened.
resp_down [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Response Time Down Flag. (T) indicates this condition was in effect during lifetime of event due to exempting coditions for late run time. Set using Response Time Down command in I/CAD. (F) otherwise
response_order [default = 0]	number(10,0)	int	no	nonNegativeNumber	The order of the responses of a multi-response event
rev_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date timestamp when this revision was created. Note that some updates to agency_event do not create a new revision.
rev_num	number(10,0)	int	no	positiveNumber	Revision Number of Record. Used to provide an audit trail to trace the evolution of an event.
rev_pers	number(10,0)	int	no		Employee ID of person who created this revision
rev_sec	number(19,0)	bigint	no		Rev_dts time stamp stored in epoch seconds
rev_term	varchar2(15)	varchar(15)	no		Terminal that created this revision
scdts	varchar2(16)	varchar(16)	no	ipsTimestamp	This column represents the "status change" date time stamp. It contains the time at which an event changes status. This should correspond to the re-setting of an event's timer.
sdt	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time stamp when the user enters the initial location or event type for a new event to indicate the beginning of event data entry
sitfind	varchar2(16)	varchar(16)	yes		Situation Found. Event type (from event_type table) that is found at the scene if it differs from the event type that was initially reported.
ssec	number(19,0)	bigint	yes		Sdts time stamp stored in epoch seconds
status_code	number(10,0)	int	no	status_code between 7 and 21	Current event status. 7 = Pending, 8 = Assigned, 9 = Held, 10 = Broadcast and Held, 11 = Broadcast and Cancel, 12 = Cancel, 13 = Station Alert, 14 = Duplicate and Cancel, 15 = Agreed Response, 16 = Closed, 17 = Awaiting Closure, 18 = Dispatch Assigned, 20 = Dependent Status (used by InService to track dependencies between jobs), 21 = Scheduled. The mnemonic values are defined in the cad StatusDisplay parameter list.
sub_eng	varchar2(80)	varchar(80)	yes		The textual description of the sub_type
sub_sitfind	varchar2(16)	varchar(16)	yes		The sub-type of the sitfind event type.
sub_tycode [default = 'default']	varchar2(16)	varchar(16)	no		The sub-type of the event type.
suggested_unit	varchar2(10)	varchar(10)	yes		The unit preferred to service this response of a multi-response event. If this row is not part of a multi-response event, or it is the master event for a multi-response event, the suggested_unit will be null.
supp_info [default = 0]	number(10,0)	int	no		Supplemental Information Identifier. This mask indentifies the supplemental tables that have records tied to this event. This is configurable and is defined in the parameter file.
ta_sec	number(19,0)	bigint	yes		Ta_ts time stamp stored in epoch seconds
ta_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Transport Arrived Time Stamp. Time that the first unit transport arrived for the event.
talk_group_label	varchar2(15)	varchar(15)	yes		MCGE talkchannel associated to this event. Used by I/Radio.
temp_lock [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Used to temporarily lock a record. T= row is locked. F = row is not locked. The committed value in the database should always be F
tr_sec	number(19,0)	bigint	yes		Tr_ts time stamp stored in epoch seconds
tr_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Transport Time Stamp. Time that the first unit transported for the event.
tycod	varchar2(16)	varchar(16)	no		Agency specified event type used to describe the event which has occurred
typ_eng	varchar2(80)	varchar(80)	yes		Verbose description of the event type
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp.
upers	number(10,0)	int	yes		ID of person updating event.
uterm	varchar2(15)	varchar(15)	yes		Terminal which updated event.
vdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	First view Date/time stamp.
vsec	number(19,0)	bigint	yes		Vdts time stamp stored in epoch seconds.
xcmt	varchar2(80)	varchar(80)	yes		Closing Comments
xdow	number(10,0)	int	yes	xdow between 1 and 7	Closing Day of the week, Sunday - Saturday (1-7), where Sunday = 1 and Saturday = 7
xdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Closing Date/Time Stamp.
xpers	number(10,0)	int	yes		ID of person who closed the event.
xsec	number(19,0)	bigint	yes		Xdts time stamp stored in epoch seconds.
xterm	varchar2(15)	varchar(15)	yes		Terminal which closed the event.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
agency_event_ad_ts	ad_ts		no	no	
agency_event_ad_ts2	Oracle: string_to_datetimeoffset(ad_ts) SQL Server: ad_ts2		no	no	
agency_event_ag_id_dgroup	ag_id_dgroup		no	no	
agency_event_cdtsudts	cdts, udts		no	no	
agency_event_eid	eid		no	no	
agency_event_external_event_id	external_event_id		no	no	
agency_event_group_id	group_id		no	no	
agency_event_hold_unt	hold_unt		no	no	

agency_event_is_open [Oracle only]	Oracle: case is_open when 'T' then 1 when 'F' then 0 else null end SQL Server:	no	no	
agency_event_is_open_status	is_open,status_code	no	no	
agency_event_probe_flag	probe_flag	no	no	
agency_event_xdts	xdts	no	no	
agency_event_xsec	xsec	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type	Sql Server Clustered	
agency_event_pk	num_1	primaryKey	yes	
Check Constraints				
Constraint Name	Required	Oracle Definition	Sql Server Definition	
agency_event_x_open_ck	Yes	(is_open = 'T' and status_code != 21 and xdts is null and xsec is null and xdow is null) or (is_open = 'F' and status_code != 21 and xdts is not null and xsec is not null and xdow is not null) or (status_code = 21 and xdts is null and xsec is null and xdow is null)	(is_open = 'T' and status_code != 21 and xdts is null and xsec is null and xdow is null) or (is_open = 'F' and status_code != 21 and xdts is not null and xsec is not null and xdow is not null) or (status_code = 21 and xdts is null and xsec is null and xdow is null)	
Triggers				
Trigger Name	Required	Trigger Type	Description	
agency_event_priority_dts_trig	No	Custom	When an update modifies the priority, verify that it also sets priority_changed_dts.	
agency_event_rev_trig	No	Custom	When updating rev_num, you must also set rev_ columns.	

 [Top](#)

Table Name - agency_event_added_req					
Description	Defines additional response plan requirements added to a specific agency event and alarm level. Added for CAD 9.1 Recommend Unit CRs.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alarm_lev	number(10,0)	int	no		Alarm level for the event
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation timestamp
is_deleted [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	T if requirement has been deleted, F otherwise
 num_1	varchar2(12)	varchar(12)	no		Agency event number
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
req_name	varchar2(50)	varchar(50)	no		Name of unit ID or nested response plan added to default requirements
 req_number	number(10,0)	int	no	nonNegativeNumber	Sequential order of requirement beginning with zero
req_type	number(10,0)	int	no	req_type in (0,1)	Type of requirement. 0 for unit ID, 1 for nested response plan
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
unique_id	raw(16)	varbinary(16)	no		Unique ID of added requirement. This value is used when writing results to the recom_hist table.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
agency_event_add_req_cdtsudts	cdts, udts		no	no	
agency_event_added_req_udts	udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
agency_event_added_req_pk	num_1, alarm_lev, req_number			primaryKey	yes
agency_event_added_req_uk	unique_id, recovery_unique_id			uniqueKey	no

 [Top](#)

Table Name - agency_event_history					
Description	This table contains historical agency event records. When an agency_event record is updated, a snapshot of its previous contents are recorded in this table.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
acknowledge_timer	number(10,0)	int	no	acknowledge_timer between 0 and 32766	Acknowledge Alarm Timer. How long a unit on this event can be in the acknowledgement status before an alarm sounds.
ad_sec	number(19,0)	bigint	no		Ad_ts time stamp stored in epoch seconds
ad_ts	varchar2(16)	varchar(16)	no	ipsTimestamp	Time event was actually added into system
aecust1	varchar2(50)	varchar(50)	yes		Agency event custom column 1
aecust2	varchar2(50)	varchar(50)	yes		Agency event custom column 2
aecust3	varchar2(50)	varchar(50)	yes		Agency event custom column 3
aecust4	varchar2(50)	varchar(50)	yes		Agency event custom column 4
ag_id	varchar2(9)	varchar(9)	no		Agency ID for the agency associated with the event
alarm_lev	number(10,0)	int	no	nonNegativeNumber	Alarm Level for the event
appt_alarm_until	varchar2(16)	varchar(16)	yes	ipsTimestamp	Datetime stamp for next appointment alarm time
appt_end_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Appointment end date/time stamp. Appointment is to be completed by this date/time.
appt_start_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Appointment start date/time stamp. The earlier time in an appointment window. For an appointment this will be a fixed, default time, typically at the beginning of the work day.
ar_sec	number(19,0)	bigint	yes		Ar_ts time stamp stored in epoch secs
ar_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time that the first unit arrived on the scene
arrive_timer	number(10,0)	int	no	arrive_timer between 0 and 32766	Arrive alarm timer. How long a unit on this event can be in the arrive status before an alarm sounds.
assigned_units	number(5,0)	smallint	no	nonNegativeNumber	This column is used to keep track of the number of units assigned to the event.
callback_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Event call back timer expiration date time stamp. Null if no timer.
cbtime2 [default = 0]	number(10,0)	int	no		Event repeat call back timer value. Zero if no timer.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp of this history row. The CDTS column shows up as UDTS in the aeven compatibility view.
closing_allowed [default = 'T']	varchar2(1)	varchar(1)	no	booleanToRF	Indicates that there are no items pending that would prevent the event from being closed.T or F

cpers	number(10,0)	int	no		Employee ID of person creating this history row. The CPERS column shows up as UPERS in the aeven compatibility view.
cterm	varchar2(15)	varchar(15)	no		Terminal creating this history row. The CTERM column shows up as UTERM in the aeven compatibility view.
dest_eid	number(10,0)	int	yes		Scheduled Event destination. This is a secondary event record for a scheduled event which holds its final destination. The starting point is in the first event record.
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group handling event
dispass_unit	varchar2(10)	varchar(10)	yes		ID of Unit event is dispatch assigned to (NULL if event is not dispatch assigned)
dispatch_timer	number(10,0)	int	no	dispatch_timer between 0 and 32766	Dispatch Alarm Timer. How long a unit on this event can be in the dispatched status before an alarm sounds.
ds_sec	number(19,0)	bigint	yes		Ds_ts time stamp stored in epoch seconds
ds_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Dispatched Time Stamp. Time that the first unit was dispatched to the event.
due_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Due date/time stamp. The latest time that an event can be scheduled, typically an internal constraint. Typically not used to record an agreement between two
eid	number(10,0)	int	no	positiveNumber	Unique Event Id Number generated by the system
en_sec	number(19,0)	bigint	yes		En_ts time stamp stored in epoch seconds
en_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time first unit was enroute to event
enroute_timer	number(10,0)	int	no	enroute_timer between 0 and 32766	Enroute Alarm Timer. How long a unit on this event can be in the enroute status before an alarm sounds
esz [default = -1]	number(10,0)	int	no		Emergency Service Zone for verified location. Level 1 area code from deployment table.
eta	number(10,0)	int	yes		Estimated Time of Arrival. For AutoDispatch events, the ETA is the estimated time in minutes from the current time that it will take for a unit to arrive at the event.
evt_rev_num	number(10,0)	int	no		Common event revision number corresponding to this agency event revision.
ex_evt [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Exempt event flag, identifies events exempt from contracted time limits for response. (T) if exempt, (F) otherwise.
external_event_id	varchar2(30)	varchar(30)	yes		InterCAD column, event id from a foreign system
flags [default = 0]	number(10,0)	int	no	flags between 0 and 127	Flags column contains event attributes. Each bit represents a boolean value. 1 = Secure access, 2 = Event has graphics, 4 = Event has common graphics, 8 = Units have been dispatched to event, 16 = Event has SOP, 32 = Event's location is a special address using specific map levels, 64 = Event has attachments
group_id	varchar2(12)	varchar(12)	yes		The id of the group that this event belongs to
group_order	number(10,0)	int	yes		Order of event in group.
hold_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/Time when held/agreed response event will become a pending event
hold_type [default = 0]	number(10,0)	int	no	hold_type between 0 and 3	Held Event Type Code indicates hold status of the event: 0 = not held, 1 = held , 2 = agreed response, 3 = broadcast held
hold_unt	varchar2(10)	varchar(10)	yes		ID of unit event is held for
is_open	varchar2(1)	varchar(1)	no	booleanToRF	T if the event is open, F otherwise
is_rec_enabled [default = 'T']	varchar2(1)	varchar(1)	no	booleanToRF	Controls whether additional unit recommendations are performed for the event. T - recommendations are generated, F - further recommendations are disabled
is_rec_preempt_enabled [default = 'T']	varchar2(1)	varchar(1)	no	booleanToRF	Controls whether unit recommendations for the event can suggest units to be preempted. T - preempts are allowed, F - preempts are disabled
late_run [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Late run event. (T) indicates response time requirement for event was not met and late run information is present in the evcom table. (F) otherwise
lev2	varchar2(6)	varchar(6)	yes		Level 2 area code from the deployment table
lev3	varchar2(7)	varchar(7)	yes		Beat (Level 3 area code from the deployment table)
lev4	varchar2(5)	varchar(5)	yes		Zone (Level 4 area code from the deployment table)
lev5	varchar2(5)	varchar(5)	yes		District (Level 5 area code from the deployment table)
loi_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the agency_event record will no longer be retrieved by LOI searches.
majevt_evty	varchar2(10)	varchar(10)	yes		Major event type. Identifies this event as a major event. It is set based on the major event id from the event table and points to a major event plan. Major event software must be running for this to work.
majevt_loc	varchar2(10)	varchar(10)	yes		Major Event Location. It is set based on the major event id from the alarm or sp_ad table (retrieved by Location Verify) and points to a major event plan. Major event software must be running for this to function.
multi_event_id [default = '0']	varchar2(12)	varchar(12)	no		For Multi-Response events, this column contains the agency event ID (num_1) from the master event, which ties together all rows that belong to a particular multi-response event. If the row is not part of a multi-response event, the multi_event_id is set to 0.
multi_event_response	varchar2(1)	varchar(1)	yes	multi_event_response in ('B', 'D', 'M', 'O')	Multi-Event Response (MRE) flag: 'O' = Starting Origin- the trans_des.origin_location of this row defines the starting origin of the MRE. 'D' = Final Destination - the trans_des.location of this row defines the final destination of the MRE. 'B' = Both - the trans_des row represents both the origin and the destination of the entire MRE. 'M' = Master Event record. NULL = Intermediate response, or event is not part of a MRE.
mun	varchar2(40)	varchar(40)	yes		Municipality (Level 6 area code from the deployment table)
 num_1	varchar2(12)	varchar(12)	no		Agency "event" number
original_cpers	number(10,0)	int	no		Empid of the person who originally created the event. After event creation, this value should never be changed. Maps to create_pers in the aeven compatibility view
original_cterm	varchar2(15)	varchar(15)	no		Terminal which originally created this event. After event creation, this value should never be changed. Maps to create_term in aeven view.
pend_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Pending Event Date/Time Stamp is the time at which the pending events alarm will go off.
pending_timer	number(10,0)	int	no	pending_timer between 0 and 32766	Pending Alarm Timer. How long this event can stay pending before an alarm sounds.
planned_task_end_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Planned task end time. Used by the Resource Scheduler
planned_task_start_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Planned task start time. Used by the Resource Scheduler
prim_member	number(10,0)	int	yes		Employee id number of primary unit member (if a primary unit is assigned) or the operator id (if a primary unit is not assigned)
prim_unit	varchar2(10)	varchar(10)	yes		Primary Unit. ID of unit that reported disposition code, requested case number via Assign Case Number, or arrived on the scene with the case number.
priority	number(10,0)	int	no	priority between 0 and 9	Event Priority (0-9) for agency from event_type table.
priority_changed_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The last time the priority changed.
probe_flag	varchar2(16)	varchar(16)	yes	ipsTimestamp	Probe Data Indicator Flag. Timestamp used to indicate when event data was transferred to RMS. May be used by I/LEADS-Link, FireLink or CADLink.
proqa_case_num	varchar2(12)	varchar(12)	yes		ProQA case number received from ProQA Paramount
proqa_case_type	varchar2(10)	varchar(10)	yes	proqa_case_type in ('MEDICAL', 'FIRE', 'POLICE')	ProQA case type

rec_fea_mslink [default = 0]	number(10,0)	int	no		Special feature ID to use when recommending units for the event
rec_select_mode [default = 3]	number(10,0)	int	no	rec_select_mode in (0,1,2,3)	Unit selection mode for recommendations. 0 - use available only, 1 - use assigned units to fill missing requirements, 2 - use any unit, 3 - use default
rec_x_cord [default = 0]	number(10,0)	int	no		Special X coordinate to use when recommending units for the event
rec_y_cord [default = 0]	number(10,0)	int	no		Special Y coordinate to use when recommending units for the event
recom_incomplete [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	'T' when last unit recommendation was incomplete for event, 'F' otherwise
recommend_mode [default = 3]	number(10,0)	int	no	recommend_mode in (0,1,2,3)	Recommendation mode for event. 0 - beats, 1 - street network, 2 - closest, 3 - use default
reopen	varchar2(1)	varchar(1)	no	booleanTOrF	This column will be used to indicate that an agency event has been reopened. The column will have a value of 'F' to indicate that the event has not been reopened. The column will have a value of 'T' to indicate that the event has been reopened.
resp_down [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Response Time Down Flag. (T) indicates this condition was in effect during lifetime of event due to exempting coditions for late run time. Set using Response Time Down command in I/CAD. (F) otherwise
response_order [default = 0]	number(10,0)	int	no	nonNegativeNumber	The order of the responses of a multi-response event
rev_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation timestamp for this revision. The rev_dts column is copied from the agency_event udts column. This column is shown as cpts in the aeven view.
 rev_num	number(10,0)	int	no	positiveNumber	Revision Number of Record. Used to provide an audit trail to trace the evolution of an event.
rev_pers	number(10,0)	int	no		The person who created this revision. The rev_pers column is copied from the agency_event upers column. This column is shown as cpers in the aeven view.
rev_sec	number(19,0)	bigint	no		The creation timestamp, in epoch seconds, for this revision. The rev_sec column is copied from the agency_event usec column. This column is shown as csec in the aeven view.
rev_term	varchar2(15)	varchar(15)	no		The rev_term column is copied from the agency_event uterm column. This column is shown as cterm in the aeven view.
sdts	varchar2(16)	varchar(16)	no	ipsTimestamp	This column represents the "status change" date time stamp. It contains the time at which an event changes status. This should correspond to the re-setting of an event's timer.
sdt	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time stamp when the user enters the initial location or event type for a new event to indicate the beginning of event data entry
sitfnd	varchar2(16)	varchar(16)	yes		Situation Found. Event type (from event_type table) that is found at the scene if it differs from the event type that was initially reported.
ssec	number(19,0)	bigint	yes		Sdts time stamp stored in epoch seconds
status_code	number(10,0)	int	no	status_code between 7 and 21	Current event status. 7 = Pending, 8 = Assigned, 9 = Held, 10 = Broadcast and Held, 11 = Broadcast and Cancel, 12 = Station Alert, 13 = Duplicate and Cancel, 15 = Agreed Response, 16 = Closed, 17 = Awaiting Closure, 18 = Dispatch Assigned, 20 = Dependent Status (used by InService to track dependencies between jobs), 21 = Scheduled The mnemonic values are defined in the cad StatusDisplay parameter list.
sub_eng	varchar2(80)	varchar(80)	yes		The textual description of the sub_type
sub_sitfnd	varchar2(16)	varchar(16)	yes		The sub-type of the sitfnd event type.
sub_tycod [default = 'default']	varchar2(16)	varchar(16)	no		The sub-type of the event type.
suggested_unit	varchar2(10)	varchar(10)	yes		The unit preferred to service this response of the multi-response event. If this row is not part of a multi-response event, or it is the master event for a multi-response event, the suggested_unit will be null.
supp_info [default = 0]	number(10,0)	int	no		Supplemental Information Identifier. This mask indentifies the supplemental tables that have records tied to this event. This is configurable and is defined in the parameter file.
ta_sec	number(19,0)	bigint	yes		Ta_ts time stamp stored in epoch seconds
ta_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Transport Arrived Time Stamp. Time that the first unit transport arrived for the event.
talk_group_label	varchar2(15)	varchar(15)	yes		MCGE talkchannel associated to this event. Used by I/Radio.
tr_sec	number(19,0)	bigint	yes		Tr_ts time stamp stored in epoch seconds
tr_ts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Transport Time Stamp. Time that the first unit transported for the event.
tycod	varchar2(16)	varchar(16)	no		Agency specified event type used to describe the event which has occurred
typ_eng	varchar2(80)	varchar(80)	yes		Verbose description of the event type
vdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	First view Date/time stamp.
vsec	number(19,0)	bigint	yes		Vdts time stamp stored in epoch seconds.
xcmt	varchar2(80)	varchar(80)	yes		Closing Comments
xdow	number(10,0)	int	yes	xdow between 1 and 7	Closing Day of the week, Sunday - Saturday (1-7), where Sunday = 1 and Saturday = 7
xdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Closing Date/Time Stamp
xpers	number(10,0)	int	yes		ID of person closing event
xsec	number(19,0)	bigint	yes		Xdts time stamp stored in epoch seconds.
xterm	varchar2(15)	varchar(15)	yes		Terminal which closed event

Indexes				
Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
agency_event_his_ad_ts	ad_ts	no	no	
agency_event_his_ag_id_dgroup	ag_id,dgroup	no	no	
agency_event_his_cdts	cdts	no	no	
agency_event_his_eid	eid	no	no	
agency_event_his_group_id	group_id	no	no	
agency_event_his_is_open	is_open	no	no	
agency_event_his_probe_flag	probe_flag	no	no	
agency_event_his_xdts	xdts	no	no	
agency_event_his_xsec	xsec	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type	Sql Server Clustered	
agency_event_history_pk	num_1,rev_num	primaryKey	yes	
Check Constraints				
Constraint Name	Required	Oracle Definition	Sql Server Definition	
agency_event_his_x_open_ck	Yes	(is_open = 'T' and status_code != 21 and xdts is null and xsec is null and xdow is null) or (is_open = 'F' and status_code != 21 and xdts is not null and xsec is not null and xdow is not null) or (status_code = 21 and xdts is null and xsec is null and xdow is null)	(is_open = 'T' and status_code != 21 and xdts is null and xsec is null and xdow is null) or (is_open = 'F' and status_code != 21 and xdts is not null and xsec is not null and xdow is not null) or (status_code = 21 and xdts is null and xsec is null and xdow is null)	

 [Top](#)

Table Name - agency_event_resp_plan					
Description	Explicitly defines response plans to use for unit recommendation for specific agency events and alarm levels, overriding normal response plan selection. Added for CAD 9.1 Recommend Unit CRs.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alarm_lev	number(10,0)	int	no		Alarm level for the event
 num_1	varchar2(12)	varchar(12)	no		Agency event number
resp_plan_name	varchar2(50)	varchar(50)	no		Response plan to use
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
agency_event_resp_plan_pk	num_1, alarm_lev			primaryKey	yes

 [Top](#)

Table Name - alarm					
Description	This table contains alarm- related data used along with information from the segme table for the location verification of a cataloged alarm. A cataloged alarm can be created through CADDDBM.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
address	varchar2(80)	varchar(80)	yes		Address
al_const	varchar2(10)	varchar(10)	yes		Used by IABL during alarm data bulk load.
al_status	varchar2(10)	varchar(10)	yes		Alarm Status
 alarm_id	varchar2(80)	varchar(80)	no		Unique ID number of alarm
aptnum	varchar2(5)	varchar(5)	yes		Apartment Number
call_sour	varchar2(8)	varchar(8)	yes		Call Source.
company	varchar2(21)	varchar(21)	yes		Name of company where the alarm is located
data_source	varchar2(5)	varchar(5)	yes		Source
fea_mslink	number(10,0)	int	yes		Segment containing street address of the alarm location
majevt_id	varchar2(10)	varchar(10)	yes		Major Event Identifier. Pointer to major event plan if this alarm is a major event. NULL otherwise
mslink	number(10,0)	int	yes		Map Linkage. Links graphics cell for the alarm to a specific location.
name	varchar2(25)	varchar(25)	yes		Premise Name if provided by the input system. Only populated by IABL.
priority	number(10,0)	int	yes	priority between 0 and 9	Alarm priority code.
soundex	varchar2(4)	varchar(4)	yes		The soundex code for the cataloged alarm name
spad_mslink	number(10,0)	int	no		Special Address Map Link.
str_num	varchar2(15)	varchar(15)	yes		Street number of alarm address
sub_tycode	varchar2(16)	varchar(16)	yes		The sub-type of the event type.
tycode	varchar2(16)	varchar(16)	yes		Event Type Code for alarm from the event_type table
update_action	varchar2(3)	varchar(3)	yes		Update action
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
alarm_mslink	mslink		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
alarm_primary_key	alarm_id			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
alarm_tycode_sub_tycode_ck	Yes	not (tycode is not null and sub_tycode is null)		not (tycode is not null and sub_tycode is null)	

 [Top](#)

Table Name - alarm_log					
Description	This table contains specific information related to alarms received in I/CAD.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alarm_eid	number(10,0)	int	no		Unique Alarm Event Identifier (system-generated)
alarm_record	number(10,0)	int	yes		Alarm record number (join column to common_event record)
alm_area	varchar2(2)	varchar(2)	yes		Alarm area
alm_area_coid	varchar2(6)	varchar(6)	yes		Identifier of company located in area where alarm occurred.
alm_badge_name	varchar2(26)	varchar(26)	yes		Alarm Badge Holder Name
alm_badge_num	varchar2(7)	varchar(7)	yes		Unique, visible badge number
alm_bld_loc	varchar2(2)	varchar(2)	yes		Building location where alarm occurred
alm_camer_num	number(10,0)	int	yes		Number of camera closest to alarm location
alm_ctid	varchar2(12)	varchar(12)	yes		User ID of calltaker who took the alarm
alm_device	varchar2(10)	varchar(10)	yes		Alarm device. Common alarm device that is used at the location of the alarm.
alm_dt_stamp	varchar2(27)	varchar(27)	yes		Date/Time Stamp at which alarm was entered into system
alm_point	varchar2(30)	varchar(30)	yes		Point where alarm occurred
alm_point_loc	varchar2(20)	varchar(20)	yes		Alarm Point Location
alm_point_sub	varchar2(15)	varchar(15)	yes		Alarm Point Sublocation
alm_priority	number(10,0)	int	yes	alm_priority between 0 and 9	Alarm Priority assigned to event type
alm_remarks	varchar2(240)	varchar(240)	yes		Alarm Remarks
alm_seq_num	number(10,0)	int	yes		Unique Sequence Number of event with which alarm is associated.
alm_type	varchar2(20)	varchar(20)	yes		Alarm Event Type
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
alarm_log_primary key	alarm_eid			primaryKey	yes

 [Top](#)

Table Name - alarm_log2					
Description	This table is used by Amtrak I/Alarm to log the event creation. Customers may add columns to store other alarm data.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alarmdate	varchar2(8)	varchar(8)	yes		Alarm Date. This value comes from the incoming data stream. Typical formats are mm/dd/yy or mmdyyy.
alarmid	varchar2(24)	varchar(24)	no		Alarm id received from incoming data stream
alarmtime	varchar2(6)	varchar(6)	yes		Alarm time. This value comes from the incoming data stream. Typical formats are hh:mm or hhmmss.
cadeventeid	number(10,0)	int	no		Event eid created for this alarm
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Unique identifier
Indexes					

Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
alarm_log2_alarmid	alarmid	no	yes	
Key Constraints				
Constraint Name	Columns	Constraint Type		Sql Server Clustered
alarm_log2_pk	unique_id	primaryKey		no

 [Top](#)

Table Name - alarmcom						
Description	This table contains the comments associated with an alarm that was processed by I/CAD.					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 alarm_id	varchar2(80)	varchar(80)	no		Unique Alarm id number	
comm	varchar2(80)	varchar(80)	no		Comments text.	
 lin_ord	number(10,0)	int	no		Line Order Number assigned to comments records to maintain the order in which they were entered on the form	
Key Constraints						
Constraint Name	Columns			Constraint Type		Sql Server Clustered
alarmcom_primary_key	alarm_id, lin_ord			primaryKey		yes

 [Top](#)

Table Name - asec_an_al						
Description	Records all the ALSEC packets received. Used by ALSEC Server.					
Copy Type	INSERT					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
address1	varchar2(64)	varchar(64)	yes		The first line of the Location Address	
address2	varchar2(64)	varchar(64)	yes		The second line of the Location Address	
address3	varchar2(64)	varchar(64)	yes		The third line of the Location Address	
address4	varchar2(64)	varchar(64)	yes		The fourth line of the Location Address	
address5	varchar2(64)	varchar(64)	yes		The fifth line of the Location Address	
address6	varchar2(64)	varchar(64)	yes		The sixth line of the Location Address	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time stamp at which the location information packet is received	
clname	varchar2(32)	varchar(32)	yes		Caller's name	
clnum	varchar2(32)	varchar(32)	yes		Caller's phone number	
loc_type	varchar2(10)	varchar(10)	no	loc_type in ('LANDLINE', 'PHASE_I', 'PHASE_II', 'INVALID')	Type of the location record. Valid values: landline, phase_I and Phase_II	
local_date_time	varchar2(16)	varchar(16)	yes	ipsTimestamp	Defines the local Date/Time the location associated with this lookup was measured. Only available for mobile call.	
post_code	varchar2(8)	varchar(8)	yes		Postcode of the Location Address	
request_date_time	varchar2(16)	varchar(16)	yes		Defines the Date and Time that the lookup for this record was issued. The values come from the packets aniali receives, not our products. The format is customized with the aniali vender.	
request_id	number(10,0)	int	no		Request identifier	
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies rows	
x_long	varchar2(15)	varchar(15)	yes		Longitude for a mobile call	
y_lat	varchar2(15)	varchar(15)	yes		Latitude for a mobile call	
Indexes						
Index Name	Columns		Is Unique		Sql Server Clustered	Sql Server Where Clause
asec_an_al_request_id	request_id		no		yes	
Key Constraints						
Constraint Name	Columns			Constraint Type		Sql Server Clustered
asec_an_al_pk	unique_id			primaryKey		no

 [Top](#)

Table Name - an_al						
Description	This table contains all ANI/ALI information that was ever viewed through the ANI/ALI interface. The data is stored here automatically by the ANI/ALI process as soon as a calltaker picks up on an ANI/ALI line (E911 call).					
Copy Type	INSERT					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 ani_num	number(10,0)	int	no		Unique ANI/ALI Number to identify each entry (system- generated).	
call_num	varchar2(20)	varchar(20)	no		A unique identifying number assigned from the numbr table for a call. Links to call_data.call_num or common_event_call.call_id. If there are multiple ANI/ALI spills for a call, the call_num may be the same for multiple an_al records.	
callback	varchar2(14)	varchar(14)	yes		The callback number for cell calls: This column is configured through the parameter file.	
ccity	varchar2(32)	varchar(32)	yes		City of caller. This column is configured through the parameter file.	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation data/time stamp	
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation data/time stamp	
cell_id	varchar2(8)	varchar(8)	yes		Cell ID of the cell phone - Only available from specific carriers. This column is configured through the parameter file.	
clname	varchar2(32)	varchar(32)	yes		Caller name. This column is configured through the parameter file.	
clnum	varchar2(14)	varchar(14)	yes		Phone number of caller. This column is configured through the parameter file.	
county	varchar2(5)	varchar(5)	yes		County - if available . This column is configured through the parameter file.	
date_stamp	varchar2(10)	varchar(10)	yes		Date of call. This column is configured through the parameter file.	
edirpre	varchar2(2)	varchar(2)	yes		Street Prefix or Number Suffix	
edirsuf	varchar2(4)	varchar(4)	yes		Direction suffix. This column is configured through the parameter file.	
efeanme	varchar2(60)	varchar(60)	yes		Feature name. This column is configured through the parameter file.	
efeatyp	varchar2(4)	varchar(4)	yes		Feature type This column is configured through the parameter file.	
esn	varchar2(5)	varchar(5)	yes		Emergency service number. This column is configured through the parameter file.	
esn_text	varchar2(175)	varchar(175)	yes		ESN text. Lists Agencies responsible for this area. This column is configured through the parameter file.	
estnum	varchar2(15)	varchar(15)	yes		House number. This column is configured through the parameter file.	
house_num_suf	varchar2(5)	varchar(5)	yes		House number suffix. This column is configured through the parameter file.	
lnp_alt	varchar2(14)	varchar(14)	yes		Local number portability alternate number: This column is configured through the parameter file.	
loc_id	varchar2(20)	varchar(20)	yes		Location information. This column is configured through the parameter file.	
otc	varchar2(70)	varchar(70)	yes		Operating Telephone Company - Obsolete? This column is configured through the parameter file.	
pilot_nnx	varchar2(14)	varchar(14)	yes		Pilot telephone number. This column is configured through the parameter file.	
position_id	varchar2(10)	varchar(10)	yes		Id of position where the ANI/ALI packet was sent. Links to term.mux_id	
sector_id	varchar2(2)	varchar(2)	yes		Sector ID - Tower Sector for Phase 1 information. This column is configured through the parameter file.	
service	varchar2(35)	varchar(35)	yes		Class of service. This column is configured through the parameter file.	
state	varchar2(4)	varchar(4)	yes		State. This column is configured through the parameter file.	
term	varchar2(15)	varchar(15)	no		ID of Terminal which picked up the call.	

time_stamp	varchar2(8)	varchar(8)	yes		Time of the call. This column is configured through the parameter file.
x_long	varchar2(15)	varchar(15)	yes		Longitude value from AniAli packet
xy_uors	varchar2(30)	varchar(30)	yes		UOR data generated from Lat/Long and map by the I/AniAli process in the form "XY=(<x-uor>,<y-uor>)"< td=""></x-uor>,<y-uor>)"<>
y_lat	varchar2(15)	varchar(15)	yes		Latitude value form AniAli packet
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
an_al_call_num	call_num		no	no	
an_al_cdts	cdts		no	no	
an_al_cdts2	Oracle: string_to_datetimeoffset(cdts) SQL Server: cdts2		no	no	
an_al_term	term		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
an_al_primary_key	ani_num		primaryKey		yes

 [Top](#)

Table Name - app_access					
Description	This table stores information about application access to agency/ dispatch groups. Dispatcher, Calltaker, CADDDBM and the Recommend Unit Service restrict access based on the terminal node running the application. NetViewer, NetDispatcher and NetCommander restrict access based on the employee running the application.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency ID. Contains the agency id of the dispatch group.
 app_type	varchar2(15)	varchar(15)	no	app_type in ('call', 'disp', 'caddbm', 'mdt_server', 'NetViewer', 'NetCommander', 'recunitsvc') or app_type like 'recunitsvc%'	Application type: call (Calltaker), disp (Dispatcher), caddbm, mdt_server (MDT Server), NetCommander, NetViewer (NetViewer or NetDispatcher), recunitsvc% (Recommend Unit Service)
current_access [default = 'N']	varchar2(1)	varchar(1)	no	current_access in ('C', 'L', 'N', 'R', 'W')	Current Access: Contains a C (cover), R (read), W (Write) if this application type and access are signed on for the user. N means no access. L means terminal is 'locked' by the Change Operator command. Old lflag column
current_access_saved	varchar2(1)	varchar(1)	yes	current_access_saved in ('C','R','W')	Saved value of current_access column. The Change Operator command in CAD sets current_access_saved to current_access, and then sets current_access to L to indicate terminal is locked. Value is NULL when app is not in Change Operator mode.
current_visibility [default = 'N']	varchar2(1)	varchar(1)	no	current_visibility in ('L', 'N', 'Y')	Current Visibility. Column is set to 'L' for loaded but not visible, 'Y' for loaded and visible or 'N' for not loaded. Old curassign column
default_access [default = 'R']	varchar2(1)	varchar(1)	no	default_access in ('C', 'R', 'W')	Default access. Defines whether the user may monitor (R) events and units of an agency/ dispatch group or update (W) them or (C) cover them. For the Recommend Unit Service, (R) is not used, (W) means units in agency/dgroups with this access level will be considered for recommendations, but events will be ignored and (C) means events in agency/dgroups with this access level will have recommendations generated, and units in agency/dgroups with this access level will be considered for recommendations. This value is set by CADDDBM. Old readwrite column
default_visibility [default = 'Y']	varchar2(1)	varchar(1)	no	default_visibility in ('L', 'N', 'Y')	Default visibility. Contains a Y if agency dispatch group is to be visible at signon. Contains an L for Loaded but not visible. When this is set to N, state can still be modified through the Define Node command. Old defaultassign column
 dgroup	varchar2(5)	varchar(5)	no		Dispatch group
 empid [default = 0]	number(10,0)	int	no	(id_type = 'T' and empid = 0) or (id_type = 'E' and empid = to_number(id))	This column contains the numeric representation of the employee id in the id column if id_type is E or zero if id type is T.
 id	varchar2(15)	varchar(15)	no		This column contains either the terminal node name or the employee id
id_type	varchar2(1)	varchar(1)	no	id_type in ('E', 'T')	ID Type. E = employee id. T = terminal node.
max_access [default = 'R']	varchar2(1)	varchar(1)	no	max_access in ('C', 'R', 'W')	Maximum access allowed to agency / dispatch group, as defined in CADDDBM. Defines the allowed access transitions through the "Define Node" command. Values are R (Read), W (Write), and C (Cover). Old max_readwrite column
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
app_access_ag_dgroup_app_cur	ag_id, dgroup, app_type, current_access		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
app_access_pk	id, empid, ag_id, dgroup, app_type		primaryKey		yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
app_access_app_type_def_acc_ck	Yes	not(app_type in('call', 'NetViewer', 'NetCommander') and default_access = 'C')		not(app_type in('call', 'NetViewer', 'NetCommander') and default_access = 'C')	
app_access_app_type_def_vis_ck	Yes	not(app_type in('NetViewer', 'NetCommander') and default_visibility='L')		not(app_type in('NetViewer', 'NetCommander') and default_visibility='L')	
app_access_app_type_id_type_ck	Yes	(app_type in ('NetViewer', 'NetCommander') and id_type='E') or ((app_type in ('call', 'disp', 'caddbm', 'mdt_server', 'recunitsvc') or app_type like 'recunitsvc%') and id_type = 'T')		(app_type in ('NetViewer', 'NetCommander') and id_type='E') or ((app_type in ('call', 'disp', 'caddbm', 'mdt_server', 'recunitsvc') or app_type like 'recunitsvc%') and id_type = 'T')	
app_access_app_type_max_acc_ck	Yes	not(app_type in('NetViewer', 'NetCommander') and max_access = 'C')		not(app_type in('NetViewer', 'NetCommander') and max_access = 'C')	
app_access_rec_app_def_acc_ck	Yes	not(app_type like 'recunitsvc%' and default_access='R')		not(app_type like 'recunitsvc%' and default_access='R')	
app_access_rec_app_max_acc_ck	Yes	not(app_type like 'recunitsvc%' and max_access='R')		not(app_type like 'recunitsvc%' and max_access='R')	

 [Top](#)

Table Name - app_display					
Description		Used to store window locations when a user signs off so that the locations can be restored when the user logs in on a different machine.			
Copy Type		ALL			
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 app_type	varchar2(20)	varchar(20)	no		Executable name, such as IDISP or ICALL
 display_set	varchar2(20)	varchar(20)	no		User application set name, such as arrange or startup
 item_data	varchar2(4000)	varchar(4000)	no		Xy locations, num maps, etc.
 item_name	varchar2(80)	varchar(80)	no		Item Name, such as mainframe, ssm, num_maps, etc.
 usr_id	varchar2(20)	varchar(20)	no		User's id from persl.usr_id
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
app_display_primary key	usr_id, app_type, display_set, item_name			primaryKey	yes

 [Top](#)

Table Name - area_mun	
Description	This table is used in the verification of the area and municipality entered by the user.
Copy Type	ALL_WITH_CHECK
Columns	

Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
area_soundex	varchar2(4)	varchar(4)	yes		Soundex value for the area.
 area_value	varchar2(40)	varchar(40)	no		Valid Area value used to verify against
mun_soundex	varchar2(4)	varchar(4)	yes		Municipality soundex value
 mun_value	varchar2(40)	varchar(40)	no		Valid Municipality value used to verify against
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
area_mun_primary_key	area_value, mun_value			primaryKey	yes

 [Top](#)

Table Name - attachment_content					
Description	This table stores attachment contents for items such as calls, events, and messages				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 attachment_id	raw(16)	varbinary(16)	no		Uniquely identifies an attachment
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time when the attachment record was created
content	blob	varbinary(max)	no	length(content) <= 52428800	The binary data that represents the attachment
cpers	number(10,0)	int	no	nonNegativeNumber	The employee id of the person that created this record
cterm	varchar2(15)	varchar(15)	no		The terminal that was used to create this record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
attachment_content_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
attachment_content_pk	attachment_id			primaryKey	yes

 [Top](#)

Table Name - attachment_info					
Description	This table stores metadata associated with the content data stored in the attachment_content table				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 attachment_id	raw(16)	varbinary(16)	no		Uniquely identifies an attachment
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time when the attachment record was created
content_size	number(10,0)	int	no	content_size >= 0 and content_size <= 52428800	The number of bytes contained in the attachment. The absolute maximum of an attachment is 50 MB, but it may be limited in support of other requirements
content_type	varchar2(255)	varchar(255)	no		The mime-type of the file attachment. The size comes from RFC 4288
cpers	number(10,0)	int	no	nonNegativeNumber	The employee id of the person that created this record
cterm	varchar2(15)	varchar(15)	no		The terminal that was used to create this record
name	varchar2(260)	varchar(260)	no		A user provided name for the attachment that may default to the file name. The size is MAX_PATH
original_file_name	varchar2(260)	varchar(260)	yes		The original file name if the attachment originated as a file
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
attachment_info_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
attachment_info_pk	attachment_id			primaryKey	yes

 [Top](#)

Table Name - audit_log					
Description	Contains the output of the CAD auditing mechanism.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
button_caption	varchar2(64)	varchar(64)	no		Caption of button being audited
button_id	number(10,0)	int	no		Numeric button ID of audited dialog
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Audit record creation date/time stamp
cterm	varchar2(15)	varchar(15)	no		Creating terminal
dialog_caption	varchar2(128)	varchar(128)	no		Caption of dialog being audited
dialog_id	number(10,0)	int	no		Numeric button ID of audited dialog
empid	number(10,0)	int	no	nonNegativeNumber	Employee id of operator creating the audit record
 group_id	number(10,0)	int	no		Unique identifier for each audit record
 proc_name	varchar2(30)	varchar(30)	no		Process generating the audit records
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
audit_log_primary_key	proc_name, group_id			primaryKey	yes

 [Top](#)

Table Name - avl_poll_grp					
Description	Contains information used to determine the polling interval to be assigned to an AVL equipped vehicle. The information contained in the table is used to determine the polling interval: agency ID, dispatch group, unit ID, unit status, event type, and last velocity. The polling interval is maintained in the matching row in the value column, or in some installations, in the delta distance/time column. A unit's current description in regards to unit identifier, unit status, agency identifier, dispatch group identifier, event type identifier, and last reported velocity are used to find matching entries within the poll group table. The poll group table is traversed sequentially until an entry is found which matches all of the above criteria. Additional columns in the table for this matching row will define whether delta distance and/or delta time are to be set for this poll group. An entry for this row of the poll group table, defines the polling interval for this unit. Based on the delta distance/delta time parameter found in the matching row, the interval value relates to time and distance based reporting, therefore, this will be the expected reporting intervals. A message will be sent to the GPS device when the device supports dynamic updates. A wildcard character ("*") is supported in the poll group table in order to support "accept all" conditions. For example, if the event type identifier is not to be considered when defining a polling interval, the column for the event type, for all rows of the poll group table, shall contain the wildcard character. The final row of the poll group table contains all wildcard characters with the exception of the polling interval value entry. This final row defines the default polling interval for all units. If no rows in the poll group table match the unit's current description, the polling interval contained in the last row of the poll group table shall become the default polling interval for the unit. For systems that include velocity in the position report, the last reported velocity may also be used to determine the GPS reporting behavior. Note that in this mode, the determination of when to generate a position report is still left to the individual GPS receivers (based on its current programming). Trimble's AVL Manager is one of the systems which use the velocity.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Agency ID
delatadistance	number(10,0)	int	yes	nonNegativeNumber	Distance in meters
deltatime	number(10,0)	int	yes	nonNegativeNumber	Time in seconds
dgroup	varchar2(5)	varchar(5)	yes		Dispatch Group

eventtype	varchar2(16)	varchar(16)	yes		Event Type
lastvelocity	varchar2(1)	varchar(1)	yes	lastvelocity in ('0', '1', '2', '3', '4', '5', '6', '7', '8')	Set only when velocity is used to determine the GPS reporting behavior.
 sequencenum	number(10,0)	int	no		Unique identifier
unid	varchar2(10)	varchar(10)	yes		Unit ID
unit_status	varchar2(2)	varchar(2)	yes		Unit status
value	number(10,0)	int	yes	nonNegativeNumber	Polling interval time
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
avl_poll_grp_pk	sequencenum			primaryKey	yes

 [Top](#)

Table Name - backup_beat_list					
Description	The ordered list of backup beats associated with a row in the esz table.				
Copy Type	PSEUDO_DELETE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
backup_beat	varchar2(7)	varchar(7)	no		Backup beat from which units may be dispatched if none are available from the primary beat.
backup_order	number(5,0)	smallint	no		The order in which the backup beats are used.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The create datetime stamp
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTOrF	T= Current, F = Deleted
delete_id [default = '0']	raw(16)	varbinary(16)	no		A unique id that is set that when the row is deleted.
deplo_plan_name	varchar2(30)	varchar(30)	no		The deployment plan name
esz_rec_id	raw(16)	varbinary(16)	no		Unique record id (unique_id) from the esz table.
min_units [default = 0]	number(10,0)	int	no	nonNegativeNumber	The minimum number of available units a beat must contain.
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The update datetime stamp
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
backup_beat_list_cdtsudts	cdts, udts		no	no	
backup_beat_list_curent	curent		no	no	
backup_beat_list_rcvr_uniqueid	recovery_unique_id		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
backup_beat_list_primary_key	unique_id			primaryKey	no
backup_beat_list_unique	esz_rec_id, backup_beat, delete_id, recovery_unique_id			uniqueKey	no
backup_beat_list_unique2	esz_rec_id, backup_order, delete_id, recovery_unique_id			uniqueKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
backup_beat_list_cur_del_ck	Yes	(curent = 'T' and delete_id = '00') or (curent = 'F' and delete_id != '00')		([curent] = 'T' and [delete_id] = 0x00) or ([curent] = 'F' and [delete_id] != 0x00)	

 [Top](#)

Table Name - banntlkgrp					
Description	This table defines which talkgroup content is displayed for a given CAD terminal. This table is used by the Banner application.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 prefix	varchar2(9)	varchar(9)	no		The "prefix" is used to disambiguate between multiple radio systems that may overlap in some or all of their talkgroup ID values, but still need to be treated as distinct.
 talkgroup	varchar2(16)	varchar(16)	no		Talkgroup name
 term	varchar2(15)	varchar(15)	no		Terminal nodename
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
banntlkgrp_pk	term, talkgroup, prefix			primaryKey	yes

 [Top](#)

Table Name - beat					
Description	The beats for a deployment plan				
Copy Type	PSEUDO_DELETE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The create datetime stamp
comm	varchar2(80)	varchar(80)	yes		Comments about this record.
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTOrF	T = Current, F = Deleted
delete_id [default = '0']	raw(16)	varbinary(16)	no		A unique id that is set when the row is deleted.
deplo_plan_name	varchar2(30)	varchar(30)	no		The deployment plan name
lev3	varchar2(7)	varchar(7)	no		Beat
lev4	varchar2(5)	varchar(5)	yes		Division (zone level) that encompasses the beat.
lev5	varchar2(5)	varchar(5)	yes		Jurisdiction (command level) that encompasses the beat.
map_no	varchar2(8)	varchar(8)	yes		This column contains a deployment plan design file name that will be displayed if this deployment is used.
mun	varchar2(40)	varchar(40)	yes		Municipality (level 6 area) in which this beat is loacted.
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The update datetime stamp
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					

Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
beat_cdtssdts	cdts, udtss	no	no	
beat_curent	curent	no	no	
beat_rcvr_unique_id	recovery_unique_id	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type	Sql Server Clustered	
beat_primary_key	unique_id	primaryKey	no	
beat_unique	depln_plan_name, lev3, delete_id, recovery_unique_id	uniqueKey	yes	
Check Constraints				
Constraint Name	Required	Oracle Definition	Sql Server Definition	
beat_cur_del_ck	Yes	(curent = 'T' and delete_id = '00') or (curent = 'F' and delete_id != '00')	{[curent] = 'T' and [delete_id] = 0x00} or ([curent] = 'F' and [delete_id] != 0x00)	

 [Top](#)

Table Name - boat					
Description	Supplemental boat table that can be used by informer				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Dts when record was created
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Empid of person creating record
cterm	varchar2(15)	varchar(15)	no		Terminal creating record
curent	varchar2(1)	varchar(1)	no	booleanTOrF	T=record is current, F=earlier record
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTOrF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Eid of event
hull_num	varchar2(50)	varchar(50)	yes		Hull number of boat
id_num	varchar2(50)	varchar(50)	yes		Id number of boat
info_scope	varchar2(12)	varchar(12)	yes		If not null, it is the creating agency
juris	varchar2(10)	varchar(10)	yes		Jurisdiction
make	varchar2(50)	varchar(50)	yes		Make of boat
reg_num	varchar2(50)	varchar(50)	yes		Registration number of boat
remarks	varchar2(20)	varchar(20)	yes		Remarks
res	varchar2(2)	varchar(2)	yes		Unknown
 rev_num	number(10,0)	int	no	positiveNumber	Revision number
 row_num	number(10,0)	int	no		Row number
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	DTS when record expires
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Dts when record was updated
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Dts when record was updated
unid	varchar2(10)	varchar(10)	yes		Unit id of MDT creating supp record
updt_flag	varchar2(15)	varchar(15)	no		Update flag
upers	number(10,0)	int	yes	nonNegativeNumber	Empid of person updating record
uterm	varchar2(15)	varchar(15)	yes		Terminal updating record
Indexes					
Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause	
boat_cdtss2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udtss2	no	no		
boat_cdtssdts	cdts, udtss	no	no		
Key Constraints					
Constraint Name	Columns	Constraint Type	Sql Server Clustered		
boat_primary_key	eid, row_num, rev_num	primaryKey	yes		

 [Top](#)

Table Name - boundary_a					
Description	This table is used to define the boundaries used by Network Builder.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
from_node	number(10,0)	int	no		MSlink of from node record.
 mslink	number(10,0)	int	no		Map Linkage. Linked to graphics nodes generated by Network Builder.
to_node	number(10,0)	int	no		MSlink of the to node record
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
boundary_a_primary_key	mslink			primaryKey	yes

 [Top](#)

Table Name - boundary_b					
Description	This table is used to define the boundaries used by Network Builder.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
from_node	number(10,0)	int	no		MSlink of from node record.
 mslink	number(10,0)	int	no		Map Linkage. Linked to graphics nodes generated by Network Bulider.
to_node	number(10,0)	int	no		MSlink of the to node record
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
boundary_b_primary_key	mslink			primaryKey	yes

 [Top](#)

Table Name - broad_xref					
Description	This table contains information about case and event numbers cross- referenced to a broadcast.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 broadcast_num	number(10,0)	int	no		Unique ID for the broadcast
case_num	varchar2(12)	varchar(12)	yes		Unique ID for the case number which is cross-referenced to this broadcast
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date-Time stamp for this record

cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of person who created this record
cterm	varchar2(15)	varchar(15)	no		Terminal from which this record was created
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Current Flag.
num_1	varchar2(12)	varchar(12)	yes		Unique ID for the event cross- referenced to this broadcast
 rev_num [default = 1]	number(10,0)	int	no	positiveNumber	Revision Number of Record. Used to provide an audit trail to trace the evolution of a broadcast.
sub_tycod	varchar2(16)	varchar(16)	yes		The sub-type of the event type.
tycod	varchar2(16)	varchar(16)	yes		Type of event cross-referenced to this broadcast
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date-time stamp
upers	number(10,0)	int	yes	nonNegativeNumber	ID of person updating broadcast cross reference
uterm	varchar2(15)	varchar(15)	yes		Terminal updating broadcast cross reference
Indexes					
Index Name		Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
broad_xref_cdtssdts	cdts, udts		no	no	
Key Constraints					
Constraint Name		Columns	Constraint Type		Sql Server Clustered
broad_xref_primary_key	broadcast_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - broadcast					
Description	The broadcast table contains the common data associated with each broadcast message issued. This information is tied to specific information in cast_nar, cast_subject, broad_xref, and cast_vehicle via the broadcast_num column.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID (from agenc table) for the dispatch group authorizing broadcast
 broadcast_num	number(10,0)	int	no		Unique ID for the broadcast
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Create Date/Time Stamp.
cpers	number(10,0)	int	no	nonNegativeNumber	Person creating broadcast
cterm	varchar2(15)	varchar(15)	no		Terminal creating broadcast
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTORf	Current Record Indicator
location	varchar2(150)	varchar(150)	yes		Location associated to a broadcast
lookout_typ	varchar2(8)	varchar(8)	no		Lookout Type.
reg_fname	varchar2(50)	varchar(50)	yes		First Name of person on whose authority broadcast is sent
reg_lname	varchar2(50)	varchar(50)	yes		Last Name of person on whose authority broadcast is sent
reg_mi	varchar2(1)	varchar(1)	yes		Middle Initial of person on whose authority this broadcast is being sent
reg_num	number(10,0)	int	yes		Employee Id number of person on whose authority broadcast is being issued.
reg_other	varchar2(20)	varchar(20)	yes		Other Authority authorizing broadcast to be sent
reg_unit	varchar2(10)	varchar(10)	yes		Registering Unit on whose authority broadcast is sent
 rev_num [default = 1]	number(10,0)	int	no	positiveNumber	Revision Number of Record. Used to provide an audit trail to trace the evolution of a broadcast.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Dts of when record was updated
updt_flag	varchar2(15)	varchar(15)	no		Update Flag, contains the nodename of the terminal which has locked the record for updating, or NULLTERM if it is not locked
upers	number(10,0)	int	yes	nonNegativeNumber	ID of person updating broadcast
uterm	varchar2(15)	varchar(15)	yes		Terminal updating broadcast
xcmt	varchar2(40)	varchar(40)	yes		Closing Comments
xdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Cancel Date/Time Stamp
xpers	number(10,0)	int	yes	nonNegativeNumber	Cancelling Person
xterm	varchar2(15)	varchar(15)	yes		Cancelling Terminal
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
broadcast_cdtssdts2	Oracle: string_to_datetimeoffset(cdtss), string_to_datetimeoffset(udts) SQL Server: cdtss2, udts2		no	no	
broadcast_cdtssdts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
broadcast_primary_key	broadcast_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - broadcast_last_viewed					
Description	This table stores the broadcast's last viewing time for terminals. This table keeps one record for each terminal and broadcast number.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 broadcast_num	number(10,0)	int	no		The broadcast number
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date and time when the record was created.
 cterm	varchar2(15)	varchar(15)	no		The terminal
last_viewed_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The last time a terminal viewed a certain broadcast
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date and time when the record was updated.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
broadcast_last_viewed_pk	broadcast_num, cterm			primaryKey	yes

 [Top](#)

Table Name - bulk_load_status					
Description	Stores the status of Bulk Load operations				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date timestamp when this row was inserted
commit_interval	number(10,0)	int	no	positiveNumber	Commit interval. Commit after processing this number of rows.
 cpers	number(10,0)	int	no	nonNegativeNumber	Employee id of person who started the Bulk Load

cterm	varchar2(15)	varchar(15)	no		Creation Terminal. Terminal where Bulk Load was started
data_file	varchar2(256)	varchar(256)	no		Data file name, including path
end_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Ending date timestamp
existing_data_option	varchar2(30)	varchar(30)	no	existing_data_option in ('CreateIfNotExists', 'CreateOrReplace', 'DeleteSiblingRows', 'CreateOrUpdate')	CreateIfNotExists, CreateOrUpdate, CreateOrReplace or DeleteSiblingRows
first_data_row [default = 1]	number(10,0)	int	no	positiveNumber	First_data_row identifies the row at which to start loading. This option is useful when a previous load partially completed, and you may want to skip some rows when you restart the load.
num_rows_already_existed [default = 0]	number(10,0)	int	no	nonNegativeNumber	Number of rows that already existed. If existing_data_option is CreateOrReplace, or DeleteSiblingRows, this column contains the number of rows that were replaced. If existing_data_option is CreateIfNotExists, this column contains that number of rows that already existed (and thus were not loaded). If existing_data_option is CreateOrUpdate, this column contains the number of rows that were updated.
num_rows_inserted [default = 0]	number(10,0)	int	no	nonNegativeNumber	Number of rows inserted
num_rows_with_errors [default = 0]	number(10,0)	int	no	nonNegativeNumber	Number of rows that were rejected (not loaded) due to errors.
 start_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Start date timestamp
table_load_status	varchar2(30)	varchar(30)	no	table_load_status in ('Started', 'Loading', 'Finished', 'Aborted', 'Cancelled')	Table load status. Started, Loading, Finished, Cancelled, Aborted. Started means that the user has started a load, and the load process is being initialized. Loading means that rows are being inserted into the database. Cancelled means that the load was cancelled by the user. Aborted means that the load halted due to an error.
 table_name	varchar2(30)	varchar(30)	no		Name of database table into which data was loaded
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date timestamp for when this row was last updated
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
bulk_load_status_primary_key	table_name, start_dts, cpers			primaryKey	yes

 [Top](#)

Table Name - call_attachment					
Description	Association between a call and its attachments.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 attachment_id	raw(16)	varbinary(16)	no		The key for the attachment
 call_id	varchar2(20)	varchar(20)	no		The key for the call
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time the attachment was associated with the call
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person adding the attachment to the call
cterm	varchar2(15)	varchar(15)	no		Terminal where the attachment was added to the call
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_attachment_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
call_attachment_pk	call_id, attachment_id			primaryKey	yes

 [Top](#)

Table Name - call_data					
Description	Contains one entry for each call received or made on the I/Telephone system. Two records will be present for one call if a Link record is created.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_group	varchar2(17)	varchar(17)	yes		This is geographic-based groups similar to beats. You can be a member of more than one call group.
call_link	varchar2(11)	varchar(11)	yes		This will usually be NULL. If a call is queued and a client answers it before the server is able to assign a number to it, the client will create a call_data record. If it then gets notification from the server that the server has assigned a number, it puts the server assigned number in the call_link field. In this case, the call will have two call_data records and the second one will be linked to the first one.
 call_num	varchar2(11)	varchar(11)	no		Unique identifying number assigned from numbr table. This number will also appear in the an_al record for that call if one exists.
call_type	varchar2(3)	varchar(3)	yes	call_type in ('I', 'E', 'O', 'U')	"I" Incoming Internal call, "E" Incoming External call, "O" Outgoing call, "U" Don't know. Data not available
cdts	varchar2(18)	varchar(18)	no	ipsTimestamp	Date and time of call appearance on system.
destaddr	varchar2(20)	varchar(20)	yes		Called number
line_name	varchar2(20)	varchar(20)	yes		The name of the line the call was received on
line_type	varchar2(10)	varchar(10)	yes		The line type the call was received from
srcaddr	varchar2(20)	varchar(20)	yes		Caller's number
term	varchar2(17)	varchar(17)	yes		The terminal that owns the line that the call appears on or is dialed from. For queues this will be the server. For an operator dialing out it will be the workstation's name.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date timestamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_data_call_link	call_link		no	no	
call_data_call_type	call_type		no	no	
call_data_cdtsudts	cdts, udts		no	no	
call_data_term	term		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
call_data_pk	call_num			primaryKey	yes

 [Top](#)

Table Name - call_history					
Description	The call_history records call transitions. One record is written per transition. The call_num field identifies the call and allows the call_history records to be linked to call_data records. I/Telephone uses this table.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_num	varchar2(11)	varchar(11)	no		Link to a call_data record and other call_history records
cdts	varchar2(18)	varchar(18)	no	ipsTimestamp	Time of transition occurrence.

consult	varchar2(3)	varchar(3)	yes	booleanTorF	T' or 'F. T - consult call, F - Not a consult call
destaddr	varchar2(20)	varchar(20)	yes		The destination number of a call. On an incoming call this would be the called number. On a transfer it would be the number the call was transferred to. Not populated for all transitions
srcaddr	varchar2(20)	varchar(20)	yes		The source number. On an answer this would be the callers number on a transfer this would be the number transferred from. Not populated for all transitions
term	varchar2(17)	varchar(17)	yes		The terminal of the Client that created the record. This is the client that has control of the call at the time of the transition.
transition	varchar2(10)	varchar(10)	yes		The record transition. The values are configurable. The default transitions are: Conn: Call Connected, Discon: Call Disconnect (hangup), Busy: Call Busy, Hold: Call Hold, Recall: Call Callback, Ans: Call Answer, Aband: Call Abandoned, Conf: Call Conference, Trans: Call Transfer, RingIn: Call Offering (Incoming call ringing), RingOut: Call Ringback (Outgoing call ringing), ConfIdle: Conference call itself goes idle - 2 part call may still exist, Idle: Call went idle (one or both parties hung-up or call was transferred), Park: Call Park, Mon: Call Monitor, Unkn: Unknown, QAns
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies rows
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_history_call_num	call_num		no	no	
call_history_cdts	cdts		no	no	
call_history_term	term		no	yes	
call_history_transition	transition		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
call_history_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - call_info					
Description	This table holds the information regarding calls that came in via the phone system.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_direction	number(5,0)	smallint	no	call_direction between 0 and 3	The direction of the call. 0 - "U" Don't know. Data not available, 1 - "I" Incoming Internal call, 2 - "E" Incoming External call, 3 - "O" Outgoing call
 call_id	varchar2(20)	varchar(20)	no		The key for the call
call_link	varchar2(20)	varchar(20)	yes		This will usually be NULL. If a call is queued and a client answers it before the server is able to assign a number to it, the client will create a call_data record. If it then gets notification from the server that the server has assigned a number, it puts the server assigned number in the call_link field. In this case, the call will have two call_data records and the second one will be linked to the first one.
call_type	number(5,0)	smallint	no	call_type between 0 and 3	The type of the call. Valid values are: Text - 0, Voice - 1, Alarm - 2, RadioTalk - 3
called_phone	varchar2(20)	varchar(20)	yes		Called number
caller_phone	varchar2(20)	varchar(20)	yes		Caller's number
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time
cdts2 [SQL Server only]		datetimeoffset	no		Creation time
conversation_expire_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time after which the conversation is no longer available from the vendor
conversation_id	varchar2(40)	varchar(40)	yes		Refers to a conversation file.
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person adding the call to the system
cterm	varchar2(15)	varchar(15)	no		Terminal where the call was added to the system
is_emergency	number(5,0)	smallint	no	booleanNumber1Or0	1 if this call is an emergency call, else 0
is_wireless	number(5,0)	smallint	no	booleanNumber1Or0	1 if this call is a wireless call, else 0
line_name	varchar2(20)	varchar(20)	yes		The name of the line the call was received on
line_type	varchar2(10)	varchar(10)	yes		The line type the call was received from
received_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date and time that the call appeared on the Call Control system.
rev_num	number(10,0)	int	no	positiveNumber	Revision number of the record
term	varchar2(15)	varchar(15)	yes		The terminal that owns the line that the call appears on or is dialed from. For queues, this will be the server. For an operator dialing out, it will be the workstation's name.
text_type	number(5,0)	smallint	yes	text_type between 0 and 3	The type of the text call. Valid values are: TTY - 0, SMS - 1, RTT - 2, IM - 3. If the call is not a text call, the value is null.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/Time stamp of when record updated
udts2 [SQL Server only]		datetimeoffset	yes		Date/Time stamp of when record updated
upers	number(10,0)	int	yes	nonNegativeNumber	Employee Id of user updating record
uterm	varchar2(15)	varchar(15)	yes		Terminal name at which update made
vendor	varchar2(20)	varchar(20)	yes		The telephone vendor of the call.
vendor_local_call_id	varchar2(64)	varchar(64)	yes		Local Call ID from the vendor.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_info_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
call_info_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
call_info_pk	call_id			primaryKey	yes

 [Top](#)

Table Name - call_info_history					
Description	This table holds the complete history of information regarding calls that came in via the phone system				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_direction	number(5,0)	smallint	no	call_direction between 0 and 3	The direction of the call. 0 - "U" Don't know. Data not available, 1 - "I" Incoming Internal call, 2 - "E" Incoming External call, 3 - "O" Outgoing
 call_id	varchar2(20)	varchar(20)	no		The key for the call
call_link	varchar2(20)	varchar(20)	yes		This will usually be NULL. If a call is queued and a client answers it before the server is able to assign a number to it, the client will create a call_data record. If it then gets notification from the server that the server has assigned a number, it puts the server assigned number in the call_link field. In this case, the call will have two call_data records and the second one will be linked to the first one.
call_type	number(5,0)	smallint	no	call_type between 0 and 3	The type of the call. Valid values are: Text - 0, Voice - 1, Alarm - 2, RadioTalk - 3
called_phone	varchar2(20)	varchar(20)	yes		Called number
caller_phone	varchar2(20)	varchar(20)	yes		Caller's number
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time
conversation_expire_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time after which the conversation is no longer available from the vendor

conversation_id	varchar2(40)	varchar(40)	yes		Refers to a conversation file.
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person adding the call to the system
cterm	varchar2(15)	varchar(15)	no		Terminal where the call was added to the system
is_emergency	number(5,0)	smallint	no	booleanNumber1Or0	1 if this call is an emergency call, else 0
is_wireless	number(5,0)	smallint	no	booleanNumber1Or0	1 if this call is a wireless call, else 0
line_name	varchar2(20)	varchar(20)	yes		The name of the line the call was received on
line_type	varchar2(10)	varchar(10)	yes		The line type the call was received from
received_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date and time that the call appeared on the Call Control system.
 rev_num	number(10,0)	int	no	positiveNumber	Revision number of the record
term	varchar2(15)	varchar(15)	yes		The terminal that owns the line that the call appears on or is dialed from. For queues this will be the server. For an operator dialing out it will be the workstation's name.
text_type	number(5,0)	smallint	yes	text_type between 0 and 3	The type of the text call. Valid values are: TTY - 0, SMS - 1, RTT - 2, IM - 3. If the call is not a text call, the value is null.
vendor	varchar2(20)	varchar(20)	yes		The telephone vendor of the call.
vendor_local_call_id	varchar2(64)	varchar(64)	yes		Local Call ID from the vendor.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_info_history_cdt	cdts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
call_info_history_pk	call_id, rev_num		primaryKey		yes

 [Top](#)

Table Name - call_text					
Description	Contains text conversations for text or TTY calls				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 call_id	varchar2(20)	varchar(20)	no		Unique Call ID in CAD system.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time
 conversation_order	number(10,0)	int	no	nonNegativeNumber	The sequence of the text in the conversation for the same call.
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person adding the text to the call
cterm	varchar2(15)	varchar(15)	no		Terminal where the text was added to the call
source	number(5,0)	smallint	no	source between 0 and 1	The source of the text. Valid values are: caller - 0, receiver - 1
text	varchar2(256)	varchar(256)	no		The text string from one transmission
transmission_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Transmission Time. Date and time that the text was sent or received by the Call Control system.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_text_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
call_text_pk	call_id, conversation_order			primaryKey	yes

 [Top](#)

Table Name - call_transition					
Description	Contains the history of the transitions that a call goes through.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_id	varchar2(20)	varchar(20)	no		Unique Call ID in CAD system.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time
conference_phone	varchar2(20)	varchar(20)	yes		Conference phone number
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person making the transition on the call
cterm	varchar2(15)	varchar(15)	no		Terminal where the transition on the call was made
is_consult	number(5,0)	smallint	no	booleanNumber1Or0	1 - consult call, 0 - Not a consult call.
received_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date and time of the call transition received on the Call Control system.
transfer_phone	varchar2(20)	varchar(20)	yes		Transfer phone number
transition	number(5,0)	smallint	no	transition between 0 and 16	Unkn: Unknown - 0, Conn: Call Connected - 1, Discon: Call Disconnect (hangup) - 2, Busy: Call Busy - 3, Hold: Call Hold - 4, Recall: Call Callback - 5, Ans: Call Answer - 6, Aband: Call Abandoned - 7, Conf: Call Conference - 8, Trans: Call Transfer - 9, RingIn: Call Offering (Incoming call ringing) - 10, RingOut: Call Ringback (Outgoing call ringing) - 11, Conflde: Conference call itself goes idle - 2 part call may still exist - 12, Idle: Call went idle (one or both parties hung-up or call was transferred) - 13, Park: Call Park - 14, Mon: Call Monitor - 15, QAns - 16
 unique_id	raw(16)	varbinary(16)	no		Primary key
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
call_transition_cdt	cdts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
call_transition_pk	unique_id		primaryKey		yes

 [Top](#)

Table Name - callgroup					
Description	Lists all of the Call Groups that are used on the system. This table is used mainly by CAD Interface applications.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
mute [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	The mute field indicates if the ring tone is muted for calls in that callgroup. 0=not muted, 1=muted. Note that the mute column will be used in a future version.

name	varchar2(15)	varchar(15)	no		Call Group name
status	number(10,0)	int	no		Display priority. 0 = Not Displayed.
term	varchar2(19)	varchar(19)	no		Terminal configured to use this Call Group
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
callgroup_name_term	name, term		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
callgroup_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - case_num					
Description	The case_num table holds records which document events which occurred and were handled by a particular agency.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		ID of agency (from agenc table) handling the event associated with this record.
 case_num	varchar2(12)	varchar(12)	no		Unique id number for case
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp
cpers	number(10,0)	int	no	nonNegativeNumber	ID of person creating record
cterm	varchar2(15)	varchar(15)	no		Terminal creating record
curent	varchar2(1)	varchar(1)	no	booleanTOrf	Current Record Indicator Flag
dgroup	varchar2(5)	varchar(5)	yes		Dispatch Group. Queried by Firelink Interface application. Populated using Svrcmds.
eid	number(10,0)	int	no	positiveNumber	Unique id (system-generated) for the associated event
 num_1	varchar2(12)	varchar(12)	no		Corresponds to num_1 column in agency_event table and uniquely IDs the event as defined by the responsible agency
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
upers	number(10,0)	int	yes	nonNegativeNumber	ID of person updating record
uterm	varchar2(15)	varchar(15)	yes		Terminal updating record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
case_num_cdtsudts	cdts, udts		no	no	
case_num_eid	eid		no	no	
case_num_num_1	num_1		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
case_num_primary_key	case_num, num_1			primaryKey	yes

 [Top](#)

Table Name - cast_nar					
Description	This table contains the narration, or comments, pertaining to individual broadcasts.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 broadcast_num	number(10,0)	int	no		Unique ID of broadcast to which the information in this record pertains
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp
comm	varchar2(80)	varchar(80)	no		One line of the text entered in the narrative gadget on any of the broadcast forms
cpers	number(10,0)	int	no	nonNegativeNumber	Creation Person
cterm	varchar2(15)	varchar(15)	no		Creation Terminal
 lin_ord	number(10,0)	int	no		Line Order used to assemble entries from the comm column into a complete description.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date time stamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cast_nar_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cast_nar_primary_key	broadcast_num, lin_ord			primaryKey	yes

 [Top](#)

Table Name - cast_subject					
Description	The cast_subject table contains records which are descriptive of the persons who were the subjects of the individual broadcasts.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
additional	varchar2(80)	varchar(80)	yes		Additional Subject Info not found in other columns
age	number(10,0)	int	yes		Age of broadcast subject
 broadcast_num	number(10,0)	int	no		Unique broadcast ID to which the information in this record pertains
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp
clothing	varchar2(80)	varchar(80)	yes		Subject clothing
cpers	number(10,0)	int	no	nonNegativeNumber	Creation Person
cterm	varchar2(15)	varchar(15)	no		Creation Terminal
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Current Record Indicator
date_ob	varchar2(10)	varchar(10)	yes		Date of Birth of subject
eye	varchar2(3)	varchar(3)	yes		Eye color of subject
fname	varchar2(50)	varchar(50)	yes		First Name of subject
hair	varchar2(3)	varchar(3)	yes		Hair Color of subject
height	number(10,0)	int	yes		Height of broadcast subject.
lname	varchar2(50)	varchar(50)	yes		Last Name of the subject
physical	varchar2(80)	varchar(80)	yes		Physical description of the subject
race	varchar2(1)	varchar(1)	yes		Racial group of subject
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row number of the form gadget which contains the subject information
sex	varchar2(1)	varchar(1)	yes		Sex of the broadcast subject
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
weight	number(10,0)	int	yes		Physical weight of subject

Indexes				
Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
cast_subject_cdtstuds	cdts, udtst	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type	Sql Server Clustered	
cast_subject_primary_key	broadcast_num, row_num, rev_num	primaryKey	yes	

 [Top](#)

Table Name - cast_vehicle					
Description	The cast_vehicle table contains records which describe the vehicles involved within the individual broadcasts.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
additional	varchar2(45)	varchar(45)	yes		Additional vehicle info not found in other columns
 broadcast_num	number(10,0)	int	no		Unique ID of broadcast to which information in this record pertains
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp
color_1	varchar2(7)	varchar(7)	yes		Main color of the vehicle
color_2	varchar2(7)	varchar(7)	yes		Secondary vehicle color
cpers	number(10,0)	int	no	nonNegativeNumber	Creation Person
cterm	varchar2(15)	varchar(15)	no		Creation Terminal
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator
license	varchar2(9)	varchar(9)	yes		License number of vehicle
make	varchar2(4)	varchar(4)	yes		Abbreviated vehicle make info
model	varchar2(3)	varchar(3)	yes		Abreviated vehicle model info
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row number of form gadget containing vehicle info
state	varchar2(4)	varchar(4)	yes		State where vehicle licensed
style	varchar2(3)	varchar(3)	yes		Vehicle Style (4dr, 2dr,etc)
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
year_lic	number(10,0)	int	yes		Year of the vehicle license
year_veh	number(10,0)	int	yes		Model year of the vehicle
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cast_vehicle_cdtstuds	cdts, udtst		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cast_vehicle_primary_key	broadcast_num, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - cctv_action_def					
Description	This table holds the strings sent to the video controller when the user initiates an action. The actions can contain special char sequences that are substituted with values at runtime. The substitution sequences are "%c", "%m" and "%u". The "%c" is substituted with the selected camera's "raw_id". The "%m" is substituted with the selected monitor's "raw_id". The "%u" is substituted with user data typed into an edit box by the user. Actions that contain "%m" cause the CCTV dialog to present the user with a pick list of available monitors. Actions that contain "%u" cause the CCTV dialog to prompt users for a user data string. The string "%%" is used to represent the char "%" in an action.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 action_name	varchar2(32)	varchar(32)	no		String used to display an action in the CCTV dialog box. The name uniquely identifies an action.
raw_action	varchar2(128)	varchar(128)	no		String as transmitted to video controller. See above for discussion of substitutions.
user_data_label	varchar2(32)	varchar(32)	no		Label for user data prompt.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cctv_action_def_pk	action_name			primaryKey	yes

 [Top](#)

Table Name - cctv_camera_def					
Description	This table holds definitions for CCTV cameras.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 camera_name	varchar2(32)	varchar(32)	no		String used to display a camera in the CCTV dialog box. The name uniquely identifies a camera.
description	varchar2(80)	varchar(80)	no		Displayed next to the camera name in the CCTV dialog box.
file_association	varchar2(128)	varchar(128)	no		Used by cad to launch the cctvclient application. This must be the unique name of an existing file. The file should have a .ctv extension. The .ctv extension is associated with the cctvclient executable.
mslink	number(10,0)	int	yes		Linkage to graphic cell on the map.
raw_id	varchar2(80)	varchar(80)	no		String used to identify a camera to the video controller. This string is in the format required for a specific video controller.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cctv_camera_def_pk	camera_name		primaryKey		yes
cctv_camera_def_uk	file_association		uniqueKey		no
cctv_camera_def_uk2	mslink		uniqueKey		no

 [Top](#)

Table Name - cctv_monitor_def					
Description	This table holds definitions for CCTV monitors.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 monitor_name	varchar2(32)	varchar(32)	no		String used to display a monitor in the CCTV dialog box. The name uniquely identifies a monitor.
raw_id	varchar2(80)	varchar(80)	no		String used to identify a monitor to the video controller. This string is in the format required for a specific video controller.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cctv_monitor_def_pk	monitor_name		primaryKey		yes

 [Top](#)

Table Name - cctv_monitor_term_restrictions

Description	This table holds records that restrict the list of monitors available to a particular terminal.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 monitor_name	varchar2(32)	varchar(32)	no		This monitor will be available in the CCTV dialog box of the specified terminal. The name must match a monitor in cctv_monitor_def.
 term_name	varchar2(16)	varchar(16)	no		Name of the terminal running the CCTV client where the list of monitors needs to be restricted.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cctv_monitor_term_restrict_pk	term_name,monitor_name		primaryKey		yes

 [Top](#)

Table Name - cctv_runtime_parameters					
Description	This table holds definitions for the CCTV runtime parameters. Both the server and the clients read this table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
client_in_service	varchar2(16)	varchar(16)	no		Service name for the socket where the clients recieve responses from the server. This name has to be added to the services file of the server and each client.
client_out_service	varchar2(16)	varchar(16)	no		Service name for the socket where clients send requests to the server. This name has to be added to the services file of the server and each client.
 config_name	varchar2(32)	varchar(32)	no		Unique identifier. This matches the config specified on the command line.
cs_read_bufsize	number(10,0)	int	no	nonNegativeNumber	Number of bytes for the read buffer in the client/server communication link.
cs_retries	number(10,0)	int	no	nonNegativeNumber	Number of retries for the client/server communication link.
cs_timeout	number(10,0)	int	no	nonNegativeNumber	Number of milliseconds for client/server communication link timeout.
cs_write_bufsize	number(10,0)	int	no	nonNegativeNumber	Number of bytes for the write buffer in the client/server communication link.
primary_server	varchar2(16)	varchar(16)	no		Host name running the primary server process.
secondary_server	varchar2(16)	varchar(16)	no		Host name running the secondary server process. If not configured for redundancy, this name should be the same as the primary server name.
server_in_service	varchar2(16)	varchar(16)	no		Service name for the socket where the server recieves client requests. This name has to be added to the services file of the server and each client.
server_out_service	varchar2(16)	varchar(16)	no		Service name for the socket where the server sends responses to the clients. This name has to be added to the services file of the server and each client.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cctv_runtime_parameters_pk	config_name			primaryKey	yes

 [Top](#)

Table Name - cd_crews					
Description	This table describes crews within the CAD system. There is one record for every crew that is currently logged on.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID for which the crew is defined. This column links to the ag_id column in the def_station_crew table.
avail_stn_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Available Station Date Time. Date and time when crew last became available at station headquarters.
 crew_id	varchar2(30)	varchar(30)	no		Crew ID. This column links to the crew_id column in the def_station_crew table.
crew_status [default = 'UNASSGN']	varchar2(10)	varchar(10)	no	crew_status in ('ASSGN', 'UNASSGN')	Crew Status. Values are ASSGN, UNASSGN.
dgroup	varchar2(5)	varchar(5)	yes		Dispatch Group for which the crew is defined. This column links to the dgroup column in the def_station_crew table.
lineup_name	varchar2(30)	varchar(30)	yes		Lineup Name. Crew was logged on with this lineup.
log_off [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Tor F. If this column is T, then the crew will be logged off when it is cleared from the unit to which it is assigned.
lon_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date Time Stamp when the crew was logged on.
restriction_type	varchar2(5)	varchar(5)	yes	restriction_type in ('ID','TYPE')	Restriction Type. This column links to the restriction_type column in the def_station_crew table.
station	varchar2(10)	varchar(10)	no		Station ID.
unit	varchar2(10)	varchar(10)	yes		Unit ID of assigned unit.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cd_crews_primary key	crew_id			primaryKey	yes

 [Top](#)

Table Name - cd_edge_a					
Description	Geographic and traffic information about each individual street segment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
blockage_mask	number(10,0)	int	yes		Info about impediments to forward progress at both ends of street segment 1 = wrong way forward 2 = hard block forward 4 = soft block forward 256 = wrong way backward 512 = hard block backward 1024 = soft block backward
edge_length	float(126)	float(53)	yes		Length of street segment in map UORs(units of resolution)
entry_angle	number(10,0)	int	yes		Direction travelled to enter street from its beginning- node end.
exit_angle	number(10,0)	int	yes		Direction travelled to exit street segment at its terminal node end.
fcode	varchar2(12)	varchar(12)	yes		Identifier for feature type this record represents. For example, fcode = 1 might translate to Interstate, fcode = S might translate to Shoreline.
fea_mslink	number(10,0)	int	yes		Link to corresponding segme record containing location info for the street segment
from_node	number(10,0)	int	yes		Link to the cd_node record describing coordinates at the begin point of the street segment
height	float(126)	float(53)	yes		Maximum vehicle height street segment can accomodate
 mslink	number(10,0)	int	no		Unique identifier for each individual cd_edge record.
obstacle_mask	number(10,0)	int	yes		Info describing obstacles which delay, but do not completely impede, forward progress at the begin and/or end node of street segment. 1 = stop sign forward 2 = caution light forward 4 = red light forward 8 = flashing red forward 16 = no right on red forward 256 = stop sign backward 512 = caution light backward 1024 = red light backward 2048 = flashing red backward 4096 = no right on red backward
riskcost	float(126)	float(53)	yes		Assigned value indicating the risk involved traversing the street segment. For example, there is more risk traversing a street with an elementary school than there is traversing a country road.
speedlimit	number(5,0)	smallint	yes		Maximum speed a vehicle may legally travel along street segment.
text_id	number(10,0)	int	yes		Actual name of the street represented in part or in full by segment described in this record

tile_num	number(10,0)	int	yes		The tile in which an edge is located.
timecost	float(126)	float(53)	yes		Number of seconds it takes to traverse the street segment.
timefactor	float(126)	float(53)	yes		Factor applied to timecost at certain times of day. For example, at 3 pm it may take twice as long as normal to traverse the segment
to_node	number(10,0)	int	yes		Link to cd_node record describing the coordinate location of the street segment termination point.
turn_mask	number(10,0)	int	yes		Info describing limitations on forward progress at both begin and end nodes of the street segment 1= no straight ahead forward 2 = no bear right forward 4 = no right turn forward 8 = no hard right forward 16 = no u turn forward 32 = no hard left forward 64 = no left turn forward 128 = no bear left forward 256 = no straight ahead backward 512 = no bear right backward 1024 = no right turn backward 2048 = no hard right backward 4096 = no u turn backward 8192 = no hard left backward 16384 = no left turn backward 32768 = no bear left backward
weight	float(126)	float(53)	yes		Maximum vehicle weight the street segment can sustain.
width	float(126)	float(53)	yes		Maximum vehicle width street segment can accomodate.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cd_edge_a_fcode	fcode		no	no	
cd_edge_a_fea_mslink	fea_mslink		no	no	
cd_edge_a_from_node	from_node		no	no	
cd_edge_a_text_id	text_id		no	no	
cd_edge_a_to_node	to_node		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cd_edge_a_primary_key	mslink		primaryKey		yes

 [Top](#)

Table Name - cd_edge_b					
Description	Geographic and traffic information about each individual street segment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
blockage_mask	number(10,0)	int	yes		Info about impediments to forward progress at both ends of street segment 1 = wrong way forward 2 = hard block forward 4 = soft block forward 256 = wrong way backward 512 = hard block backward 1024 = soft block backward
edge_length	float(126)	float(53)	yes		Length of street segment in map UORs(units of resolution)
entry_angle	number(10,0)	int	yes		Direction travelled to enter street from its beginning- node end.
exit_angle	number(10,0)	int	yes		Direction travelled to exit street segment at its terminal node end.
fcode	varchar2(12)	varchar(12)	yes		Identifier for feature type this record represents. For example, fcode = 1 might translate to Interstate, fcode = S might translate to Shoreline.
fea_mslink	number(10,0)	int	yes		Link to corresponding segme record containing location info for the street segment
from_node	number(10,0)	int	yes		Link to the cd_node record describing coordinates at the begin point of the street segment
height	float(126)	float(53)	yes		Maximum vehicle height street segment can accomodate
 mslink	number(10,0)	int	no		Unique identifier for each individual cd_edge record.
obstacle_mask	number(10,0)	int	yes		Info describing obstacles which delay, but do not completely impede, forward progress at the begin and/or end node of street segment. 1 = stop sign forward 2 = caution light forward 4 = red light forward 8 = flashing red forward 16 = no right on red forward 256 = stop sign backward 512 = caution light backward 1024 = red light backward 2048 = flashing red backward 4096 = no right on red backward
riskcost	float(126)	float(53)	yes		Assigned value indicating the risk involved traversing the street segment. For example, there is more risk traversing a street with an elementary school than there is traversing a country road.
speedlimit	number(5,0)	smallint	yes		Maximum speed a vehicle may legally travel along street segment.
text_id	number(10,0)	int	yes		Actual name of the street represented in part or in full by segment described in this record
tile_num	number(10,0)	int	yes		The tile in which an edge is located.
timecost	float(126)	float(53)	yes		Number of seconds it takes to traverse the street segment.
timefactor	float(126)	float(53)	yes		Factor applied to timecost at certain times of day. For example, at 3 pm it may take twice as long as normal to traverse the segment
to_node	number(10,0)	int	yes		Link to cd_node record describing the coordinate location of the street segment termination point.
turn_mask	number(10,0)	int	yes		Info describing limitations on forward progress at both begin and end nodes of the street segment 1= no straight ahead forward 2 = no bear right forward 4 = no right turn forward 8 = no hard right forward 16 = no u turn forward 32 = no hard left forward 64 = no left turn forward 128 = no bear left forward 256 = no straight ahead backward 512 = no bear right backward 1024 = no right turn backward 2048 = no hard right backward 4096 = no u turn backward 8192 = no hard left backward 16384 = no left turn backward 32768 = no bear left backward
weight	float(126)	float(53)	yes		Maximum vehicle weight the street segment can sustain.
width	float(126)	float(53)	yes		Maximum vehicle width street segment can accomodate.
Indexes					
Index Name	Columns	Is Unique	Sql Server Clustered		Sql Server Where Clause
cd_edge_b_fcode	fcode	no	no		
cd_edge_b_fea_mslink	fea_mslink	no	no		
cd_edge_b_from_node	from_node	no	no		
cd_edge_b_text_id	text_id	no	no		
cd_edge_b_to_node	to_node	no	no		
Key Constraints					
Constraint Name	Columns	Constraint Type		Sql Server Clustered	
cd_edge_b_primary_key	mslink	primaryKey		yes	

 [Top](#)

Table Name - cd_node_a					
Description	Describes the end of every segment, including blockages, intersections, and coordinates. There is one record for every end of every segment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
fea_mslink	number(10,0)	int	yes		Map Linkage. Mslink of associated inter record.
 mslink	number(10,0)	int	no		Unique graphic cell id
node_mask	number(10,0)	int	yes		Mask indicating blockages. 1 = node blocked 2 = use overrides 4 = use obstacle costs
tile_num	number(10,0)	int	yes		The tile in which a node is located.
xvalue	number(10,0)	int	yes		X-coordinate of the node.
yvalue	number(10,0)	int	yes		Y-coordinate of the node.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cd_node_a_fea_mslink	fea_mslink		no	no	
cd_node_a_xvalue	xvalue		no	no	
cd_node_a_yvalue	yvalue		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered

cd_node_a_primary_key	mslink	primaryKey	yes
-----------------------	--------	------------	-----

 [Top](#)

Table Name - cd_node_b					
Description	Describes the end of every segment, including blockages, intersections, and coordinates. There is one record for every end of every segment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
fea_mslink	number(10,0)	int	yes		Map Linkage. Mslink of associated inter record.
 mslink	number(10,0)	int	no		Unique graphic cell id
node_mask	number(10,0)	int	yes		Mask indicating blockages. 1 = node blocked 2 = use overrides 4 = use obstacle costs
tile_num	number(10,0)	int	yes		The tile in which a node is located.
xvalue	number(10,0)	int	yes		X-coordinate of the node.
yvalue	number(10,0)	int	yes		Y-coordinate of the node.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cd_node_b_fea_mslink	fea_mslink		no	no	
cd_node_b_xvalue	xvalue		no	no	
cd_node_b_yvalue	yvalue		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cd_node_b_primary_key	mslink		primaryKey		yes

 [Top](#)

Table Name - cd_turns_a					
Description	MGNA table that defines edge-to-edge traversal which is used for routing functionality.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 from_edge	number(10,0)	int	no		Mslink of one edge that is connected to node identified by the column node_id.
inter_mask	number(10,0)	int	yes		Defines which turns allowed at the intersection, used by the routing software.
node_id	number(10,0)	int	yes		The mslink of related node.
 to_edge	number(10,0)	int	no		Mslink of one edge that is connected to node identified by the column node_id.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cd_turns_a primary key	from edge, to edge			primaryKey	yes

 [Top](#)

Table Name - cd_turns_b					
Description	MGNA table that defines edge-to-edge traversal which is used for routing functionality.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 from_edge	number(10,0)	int	no		Mslink of one edge that is connected to node identified by the column node_id.
inter_mask	number(10,0)	int	yes		Defines which turns allowed at the intersection, used by the routing software.
node_id	number(10,0)	int	yes		The mslink of related node.
 to_edge	number(10,0)	int	no		Mslink of one edge that is connected to node identified by the column node_id.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cd_turns_b primary key	from_edge, to_edge		primaryKey		yes

 [Top](#)

Table Name - cd_units					
Description	This table describes units within the CAD system. There is one record for every unit that is currently logged on.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ack_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time (in minutes) that this unit should be in the acknowledge status
ag_id	varchar2(9)	varchar(9)	no		Agency ID to which the unit is assigned.
alarm_rung [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Is set to N or Y based upon whether the alarm has been sounded for the unit.
alarm_time [default = 0]	number(10,0)	int	no	nonNegativeNumber	Time (in minutes) after a unit status change occurs that the alarm will go off.
arrive_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time (in minutes) that the unit should be in the arrive status
attr_equip_chng	varchar2(1)	varchar(1)	yes		Flag indicating if unit has the same or different attributes and equipment as the logon defaults. The actual character in the column depends on the EquipAttrChanged and EquipAttrSame parameters in the StatusDisplay parameter table.
avail_rec	varchar2(1)	varchar(1)	yes	avail_rec='T'	Defines whether unit is available for recommendation. AVAIL_REC only applies to units assigned to an event. 'T' indicates that the unit is still available for recommendation even though it is on another event.
avail_stn_tm	number(10,0)	int	yes		Available Station Time. Time (in seconds) that a unit was available at station headquarters.
bay	varchar2(3)	varchar(3)	yes		Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table.
carid	varchar2(12)	varchar(12)	yes		Agency vehicle id number.
court_am	varchar2(1)	varchar(1)	yes	court_am = 'T'	'T' if the unit has a court appearance in the morning. This field applies to MDT units only.
court_pm	varchar2(1)	varchar(1)	yes	court_pm = 'T'	'T' if the unit has a court appearance in the PM. This field applies only to MDT units.
cover_unit	varchar2(10)	varchar(10)	yes		Unit id (unid) of the unit that is covering this unit.
crew_id	varchar2(30)	varchar(30)	yes		ID of crew assigned to unit.
delay_value [default = 0]	number(10,0)	int	no		Delay value, in seconds. This value will be added to the unit's time/distance when recommending units by the road network
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group. This column links to the dgroup column in the def_unit, lineup, app_access, roster, esz, agency_event, and un_hi tables.
disp_alarm_lev	number(10,0)	int	yes	nonNegativeNumber	Alarm Level of the event when the unit was dispatched
disp_num	varchar2(12)	varchar(12)	yes		A unique dispatch number is assigned per agency when the unit is dispatched. This number is unique per unit per event.
disp_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time (in minutes) that this unit should be in the dispatch status
eid	number(10,0)	int	yes	positiveNumber	Event number to which the unit is dispatched
emergency	varchar2(1)	varchar(1)	yes	emergency='T'	Flag indicating if unit is in an emergency situation. If field is 'T', then this is a unit emergency.
emg_evnt_cnt	number(5,0)	smallint	no	nonNegativeNumber	Number of emergency events worked since unit logged on.
enroute_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time (in minutes) that this unit should be in the enroute status
evnt_wk_tm	number(10,0)	int	yes	nonNegativeNumber	Total amount of time (in seconds) that the unit has spent on events since log on

ext_unitattr	raw(32)	varbinary(32)	no	lengthb(ext_unitattr) = 64	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).
fail_resp	varchar2(1)	varchar(1)	yes	fail_resp='T'	Failure to Respond. Flags whether unit failed to respond to last transmission.
group_id	varchar2(10)	varchar(10)	yes		This column represents the unit id (group leader) of the unit for which this unit is a member of. If this unit is a group leader, this column will contain its own unit id.
lastxor [default = 0]	number(10,0)	int	no		Last known x-coordinate of the unit.
lastyor [default = 0]	number(10,0)	int	no		Last known y-coordinate of the unit.
latitude [default = 0.0]	binary_double	float(53)	no		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
lev3	varchar2(7)	varchar(7)	yes		Current post lev_3 unit is geographically assigned to. Often referred to as a beat.
lev4	varchar2(5)	varchar(5)	yes		Current post lev_4 unit is geographically assigned to. Often referred to as a zone.
lineup_name	varchar2(30)	varchar(30)	yes		Populated at unit log on to indicate the lineup the, unit was associated with.
loc_changed	varchar2(1)	varchar(1)	yes	loc_changed='T'	'T' indicates that a change location has been executed on this unit.
loc_comm	varchar2(40)	varchar(40)	yes		Location comment. Defines permanent deployment location
location	varchar2(80)	varchar(80)	yes		Last known location of unit.
locked	varchar2(1)	varchar(1)	yes	locked='T'	Locked Flag, used to lock a unit record for update. The updt_term column will allow locking a unit record and updating it while locked.
log_off	varchar2(1)	varchar(1)	yes	log_off='T'	If this column is 'T', then the unit will be logged off when it is cleared from the event it is assigned to.
lon_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date-time stamp of when the unit was logged on.
longitude [default = 0.0]	binary_double	float(53)	no		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
max_ht	number(10,0)	int	yes	nonNegativeNumber	Maximum height of unit.
max_wd	number(10,0)	int	yes	nonNegativeNumber	Maximum width of unit.
max_wt	number(10,0)	int	yes	nonNegativeNumber	Maximum weight of unit.
mdt_status_ind	varchar2(1)	varchar(1)	yes		The status of the MDT.
mdthostname	varchar2(24)	varchar(24)	yes		System name of the mobile terminal. Used by I/MDT and Informer to route Informer responses when "node-locked" ORI authorization is necessary.
mileage	varchar2(8)	varchar(8)	yes		Indicates initial mileage of the unit at log on. This value can also indicate the mileage of the unit at the time of a status change.
name_chng	varchar2(1)	varchar(1)	yes	name_chng='T'	Indicates if the name of the unit has changed.
num_1	varchar2(12)	varchar(12)	yes		Agency event number that the unit is currently assigned to.
oag_id	varchar2(9)	varchar(9)	yes		The old agency id for a transferred unit.
edgroup	varchar2(5)	varchar(5)	yes		Original dispatch group that the unit was assigned to - in case of transfer event/unit.
outtype	varchar2(16)	varchar(16)	yes		Out of service type code.
page_id	varchar2(12)	varchar(12)	yes		Pager ID or Pager Group ID from def_page.
page_unit_person [default = 0]	number(5,0)	smallint	no	page_unit_person in (0,1,2)	0 - Page unit only, 1 - Page Employee only, 2 - Page both unit and Employee
perm_station	varchar2(10)	varchar(10)	yes		Permanent station id.
post_status [default = '0']	varchar2(1)	varchar(1)	no	booleanString1Or0	Set value to 1 if dispatching this unit will cause the system to be out of compliance with the system status plan, otherwise set to 0.
proc_count	number(10,0)	int	no	nonNegativeNumber	Process counter incremented when this row is updated.
reloc_crew_id	varchar2(30)	varchar(30)	yes		Contains the crew_id when the unit is relocated and sharing is allowed at a relocated station.
resp_stop [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	If Y then the unit is associated with late run functionality.
shared_crew [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Indicates that this is a shared crew unit. If shared crew = Y, then the unit's employees can be assigned to other shared crew units.
shift_delta	number(10,0)	int	yes		Difference in time of true start of shift from scheduled start of shift.
shift_duration	number(10,0)	int	yes		Shift duration stored in seconds.
shift_start	varchar2(16)	varchar(16)	yes	ipsTimestamp	Scheduled shift start date/time stamp.
spec_contact	varchar2(40)	varchar(40)	yes		Special contact message.
station	varchar2(10)	varchar(10)	yes		Current station/post id.
status_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time/date stamp when unit status changed to the current status.
stn_move_cnt	number(5,0)	smallint	yes	nonNegativeNumber	Total number of station/post moves.
sub_tycod	varchar2(16)	varchar(16)	yes		The sub-type of the event type.
symnum	number(10,0)	int	no	symnum between 0 and 255	Symbol number. The symbol number is used to select a bitmap from the resource file. The bitmap is displayed on the map as the unit's symbol.
tot_evtnt_cnt	number(5,0)	smallint	yes		Number of events worked.
track_personnel [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Are the unit's personnel being tracked separately from the unit? Y= Yes, N= No
transferred	varchar2(1)	varchar(1)	yes	transferred='T'	If 'T', then the unit has been temporarily transferred.
transp_cnt	number(5,0)	smallint	yes	nonNegativeNumber	Total number of transports that a unit has worked since logon.
transxor	number(10,0)	int	yes		This column holds the x coordinate of a unit's transport destination. It is set when a unit is transported with a verified location. It is then used by the Transport Arrive command to set a unit's x coordinate.
transyor	number(10,0)	int	yes		This column holds the y coordinate of a unit's transport destination. It is set when a unit is transported to a verified destination. It is then used by the Transport Arrive command to set the unit's y coordinate.
tycod	varchar2(16)	varchar(16)	yes		When the unit is on an event, this column contains the event type code.
type_avail	number(5,0)	smallint	no		This will be the unit's default available status. The possible values for this column come from the cad UnitStatus parameter table.
ucust1	varchar2(50)	varchar(50)	yes		Unit custom column 1
ucust2	varchar2(50)	varchar(50)	yes		Unit custom column 2
ucust3	varchar2(50)	varchar(50)	yes		Unit custom column 3
ucust4	varchar2(50)	varchar(50)	yes		Unit custom column 4
uhiscm	varchar2(40)	varchar(40)	yes		The latest unit history comment.
un_hi_child_change_id	raw(16)	varbinary(16)	no		Unit history child change ID. Links to child change id column in un_hi_device and un_hi_persl. This column will always have a value, even if the unit has no devices or personnel
un_hi_rec_id	raw(16)	varbinary(16)	no		Latest un_hi row for this unit. Used when writing un_hi_device_loc records, and when joining un_hi with un_hi_device_loc
unavail_rec	varchar2(1)	varchar(1)	yes	unavail_rec = 'T'	'T' if unit unavailable for recommendation, NULL if available. UNAVAIL_REC only applies to available units. 'T' indicates that the unit is NOT available for recommendation even though it's not assigned to an event.
unavail_tm	number(10,0)	int	yes		Total time (in seconds) that the unit has been unavailable, not including out of service time, since logon.
 unid	varchar2(10)	varchar(10)	no		Unit id.
unit_status	number(5,0)	smallint	no		The current status of the unit.
unityp	varchar2(6)	varchar(6)	yes		Unit type (patrol, pumper, etc).
updt_term	varchar2(15)	varchar(15)	yes		If not NULL, then the record is locked by the terminal id that is in this column.
vflag [default = 'Y']	varchar2(1)	varchar(1)	no	booleanYOrN	MDT Voice Flag. This field defines whether the MDT unit is available on voice (radio). Y = Yes, N = No.
warning	varchar2(40)	varchar(40)	yes		Dispatch warning message.

Indexes				
Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
cd_units_ag_id_dgroup	ag_id,dgroup	no	no	
cd_units_cover_unit	cover_unit	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type	Sql Server Clustered	
cd_units_primary_key	unid	primaryKey	yes	
Triggers				
Trigger Name	Required	Trigger Type	Description	
cd_units_trig	Yes	Custom	Populates valid_unit with new unid values	

Table Name - cfg_column_list					
Description	List of columns used in configurable SQL statements				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
 cfg_name	varchar2(20)	varchar(20)	no		Configuration name (used for overrides)
col_display_name	varchar2(256)	varchar(256)	yes		Display name for column. Used in places like event chronology form in Dispatcher. Also used by the CADDDBM Bulk Loader. When generating a data file from the database, the Bulk Loader outputs the column name and the display name.
col_name	varchar2(30)	varchar(30)	no		Column name
 col_position	number(5,0)	smallint	no	nonNegativeNumber	Position of column in list
col_type	varchar2(1)	varchar(1)	no	col_type in('C', 'T', 'S', 'L', 'D', 'R', 'V', 'd', 't', 'b', 'z', 'n', 'e')	Column data type or display format. C: Character, I: Integer, S: Smallint, L:Long long (64bit integer), D: Double, R: Real, V: Binary, d: date format, t: time format, b: both date and time format, z: date with time zone format, e: event status format, n: null for default format
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
 id_num	number(5,0)	smallint	no		Config id
 set_name	varchar2(20)	varchar(20)	no		Set Name. Replaces old XXconfig.txt file name
table_name	varchar2(30)	varchar(30)	yes		Table name or table alias
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_column_list_primary_key	set_name, id_num, cfg_name, col_position			primaryKey	yes

 [Top](#)

Table Name - cfg_dialog_mapping					
Description	Mapping between dialogs and columns used in configurable SQL statements				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
 cfg_name	varchar2(20)	varchar(20)	no		Configuration name (used for overrides)
 col_pos_or_restr_id	number(5,0)	smallint	no	nonNegativeNumber	Col_position from cfg_column_list or retriction_id from cfg_restriction
 col_pos_or_restr_type	number(5,0)	smallint	no	booleanNumber1Or0	0 = col_position, 1 = restriction_id
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
dialog_box	number(10,0)	int	no		Resource editor id of the dialog box to read from or write to
gadget	number(10,0)	int	no		Dialog box gadget id
gadget_col	number(5,0)	smallint	yes		Dialog box gadget column number
gadget_row	number(5,0)	smallint	yes		Dialog box gadget row number
 id_num	number(5,0)	smallint	no		Config id
 set_name	varchar2(20)	varchar(20)	no		Set Name. Replaces old XXconfig.txt file name
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_dialog_mapping_primary_key	set_name, id_num, cfg_name, col_pos_or_restr_id, col_pos_or_restr_type			primaryKey	yes

 [Top](#)

Table Name - cfg_files					
Description	The cfg_files table will store entire files in the database. Typically, a file will be transferred from the database to the client workstations when a newer version of the file is loaded into the database. CADDDBM will provide a mechanism for loading and unloading individual files to/from the cfg_files table. The Configuration and Parameter Utility will provide a mechanism for loading and unloading the files.				
Copy Type	PSEUDO_DELETE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
app_name	varchar2(30)	varchar(30)	no		Application name, such as dispatcher, bip, etc.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date and time that the record was created.
cfg_name	varchar2(20)	varchar(20)	no		Configuration name. Either default or an override name.
client_access	varchar2(10)	varchar(10)	no	client_access in ('read_only', 'read_write')	File access on client machines. Valid values are read_only and read_write.
cterm	varchar2(15)	varchar(15)	no		Terminal that created the record.
curent	varchar2(1)	varchar(1)	no	booleanTOrF	T = current row, F = deleted row.
delete_id [default = '0']	raw(16)	varbinary(16)	no		Uniquely identifies a deleted row.
descr	varchar2(1024)	varchar(1024)	yes		File description
file_attributes	varchar2(30)	varchar(30)	yes		Optional additional attributes
file_contents	blob	varbinary(max)	yes		Contents of file stored as binary data.
file_created	varchar2(16)	varchar(16)	yes		Creation date and time of the file.
file_modified	varchar2(16)	varchar(16)	yes		Date and time that file was last modified
file_size	number(10,0)	int	no		The size of the file in bytes.
file_transfer_condition	varchar2(10)	varchar(10)	no	file_transfer_condition in ('always','never','if_diff')	Condition under which file should be transferred to the client. Valid values are always, never and if_diff.
logical_file_name	varchar2(30)	varchar(30)	no		The logical name of the file, such as cad_resource
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
relative_client_file_path	varchar2(256)	varchar(256)	no		Relative portion of file path on client, including the actual file name. For example, \\caddbm\bin\dbmres.dll.
set_name	varchar2(20)	varchar(20)	no		Set name, such as cad or caddbm.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date and time that the record was last updated.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
uterm	varchar2(15)	varchar(15)	yes		Terminal that updated the record.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cfg_files_rcvr_unique_id	recovery_unique_id		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_files_primary_key	unique_id			primaryKey	no
cfg_files_unique	set_name, cfg_name, app_name, logical_file_name, delete_id, recovery_unique_id			uniqueKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
cfg_files_file_size_ck	Yes	(file_size = 0 and file_created is null and file_modified is null) or (file_size > 0 and file_created is not null and file_modified is not null)		(file_size = 0 and file_created is null and file_modified is null) or (file_size > 0 and file_created is not null and file_modified is not null)	

 [Top](#)

Table Name - cfg_id_descr					
Description	Description of config IDs				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
descr	varchar2(2000)	varchar(2000)	yes		Important info and rules about id number records
 id_num	number(5,0)	smallint	no		Config ID
 set_name	varchar2(20)	varchar(20)	no		Set Name. Replaces old XXconfig.txt file name
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_id_descr_primary_key	set_name, id_num			primaryKey	yes

 [Top](#)

Table Name - cfg_param_lists					
Description	The parameter lists				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
 cfg_name	varchar2(20)	varchar(20)	no		Configuration name (used for overrides)
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
list_descr	varchar2(1024)	varchar(1024)	yes		The description of a list
 list_name	varchar2(30)	varchar(30)	no		Parameter List Name
param_descr	varchar2(1024)	varchar(1024)	yes		Description of the parameter
param_max	varchar2(23)	varchar(23)	yes		Maximum value allowed
param_min	varchar2(23)	varchar(23)	yes		Minimum value allowed
 param_name	varchar2(30)	varchar(30)	no		Name of the parameter
param_precision	number(5,0)	smallint	yes		Significant digits
param_type	varchar2(1)	varchar(1)	no	param_type in ('C', 'T', 'S', 'D', 'R', 'B', 'L','E')	Parameter Type. C: Character, I: Integer, S: Smallint, D: Double, R: Real, B: Bitmap, L: Long long (64 bit integer), E: Encrypted
param_units	varchar2(8)	varchar(8)	yes		Units of the value, e.g. miles or ounces
param_value	varchar2(1500)	varchar(1500)	yes		Actual parameter in character form
 set_name	varchar2(20)	varchar(20)	no		Set Name.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_param_lists_primary_key	set_name, list_name, cfg_name, param_name			primaryKey	yes

 [Top](#)

Table Name - cfg_param_table_rows					
Description	Parameter table data. Each row represents a single row in a parameter table. This table replaces the cfg_param_recs table. CA-410				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time
 cfg_name	varchar2(20)	varchar(20)	no		Configuration name
col0_value	varchar2(4000)	varchar(4000)	yes		Value of column 0 in character format
col10_value	varchar2(4000)	varchar(4000)	yes		Value of column 10 in character format
col11_value	varchar2(4000)	varchar(4000)	yes		Value of column 11 in character format
col12_value	varchar2(4000)	varchar(4000)	yes		Value of column 12 in character format
col13_value	varchar2(4000)	varchar(4000)	yes		Value of column 13 in character format
col14_value	varchar2(4000)	varchar(4000)	yes		Value of column 14 in character format
col1_value	varchar2(4000)	varchar(4000)	yes		Value of column 1 in character format
col2_value	varchar2(4000)	varchar(4000)	yes		Value of column 2 in character format
col3_value	varchar2(4000)	varchar(4000)	yes		Value of column 3 in character format
col4_value	varchar2(4000)	varchar(4000)	yes		Value of column 4 in character format
col5_value	varchar2(4000)	varchar(4000)	yes		Value of column 5 in character format
col6_value	varchar2(4000)	varchar(4000)	yes		Value of column 6 in character format
col7_value	varchar2(4000)	varchar(4000)	yes		Value of column 7 in character format
col8_value	varchar2(4000)	varchar(4000)	yes		Value of column 8 in character format
col9_value	varchar2(4000)	varchar(4000)	yes		Value of column 9 in character format
 col_row	number(10,0)	int	no	col_row >= -1	Column row
cpers	number(10,0)	int	no	nonNegativeNumber	Creation person
cterm	varchar2(15)	varchar(15)	no		Creation terminal
 set_name	varchar2(20)	varchar(20)	no		Set name
 table_name	varchar2(30)	varchar(30)	no		Parameter table name
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time
upers	number(10,0)	int	yes	nonNegativeNumber	Update person
uterm	varchar2(15)	varchar(15)	yes		Update terminal
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_param_table_rows_pk	table_name, set_name, cfg_name, col_row			primaryKey	yes

 [Top](#)

Table Name - cfg_param_tables	
Description	Contains information about the columns that make up the parameter tables. A parameter table can have up to 15 columns. The parameter table rows are stored in cfg_param_table_rows.
Copy Type	ALL_WITH_CHECK
Columns	

Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
col_descr	varchar2(1024)	varchar(1024)	yes		Description of the column
col_max	varchar2(23)	varchar(23)	yes		Maximum value allowed
col_min	varchar2(23)	varchar(23)	yes		Minimum value allowed
col_name	varchar2(30)	varchar(30)	no		The name of the parameter table column
col_position	number(5,0)	smallint	no	col_position between 0 and 14	Column position. The column position is used to match up the columns with the data. The column with position 0 has its data stored in cfg_param_table_rows.col0_value, and so on.
col_precision	number(5,0)	smallint	yes		Significant digits
col_type	varchar2(1)	varchar(1)	no	col_type in ('C', 'T', 'S', 'D', 'R', 'B', 'L', 'E')	Column Type. C: Character, I: Integer, S: Smallint, D: Double, R: Real, B: Bitmap, L: Long long (64 bit integer), E: Encrypted
col_units	varchar2(8)	varchar(8)	yes		Units of the value, e.g. miles or ounces
col_width	number(5,0)	smallint	no	col_width between 1 and 4000	Column width. For character columns, this is the maximum number of characters that the user can specify.
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
set_name	varchar2(20)	varchar(20)	no		Set Name
table_descr	varchar2(1024)	varchar(1024)	yes		The description of the parameter table
table_name	varchar2(30)	varchar(30)	no		The name of the parameter table
tdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_param_tables_primary_key	set_name, table_name, col_name			primaryKey	yes
cfg_param_tables_unique	set_name, table_name, col_position			uniqueKey	no

[Top](#)

Table Name - cfg_restriction					
Description	Restrictions in where clauses of queries. Used in configurable SQL statements				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
binary_op	varchar2(16)	varchar(16)	yes		Binary operator, such as '>', '<'
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
 cfg_name	varchar2(20)	varchar(20)	no		Configuration name (used for overrides)
col_name	varchar2(30)	varchar(30)	no		Column name
col_type	varchar2(1)	varchar(1)	no	col_type in('C', 'T', 'S', 'L', 'D', 'R', 'V', 'd', 't', 'b', 'z', 'n', 'e')	Column data type or display format. C: Character, I: Integer, S: Smallint, L: Long long (64 bit integer), D: Double, R: Real, V: Binary, d: date format, t: time format, b: both date and time format, z: date with time zone format, e: event status format, n: null for default format
constant_value	varchar2(128)	varchar(128)	yes		Constant value to match
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
 id_num	number(5,0)	smallint	no		Config ID
negate_string	varchar2(3)	varchar(3)	yes	negate_string = 'NOT'	Negate string. 'NOT' or NULL
 restriction_id	number(5,0)	smallint	no	nonNegativeNumber	ID of this particular restriction
 set_name	varchar2(20)	varchar(20)	no		Set Name. Replaces old XXconfig.txt file name
table_name	varchar2(30)	varchar(30)	yes		Table name or table alias
tdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
unary_op	varchar2(16)	varchar(16)	yes		Unary operator, such as 'IS NULL' or 'IS NOT NULL'
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_restriction_primary_key	set_name, id_num, cfg_name, restriction_id			primaryKey	yes

[Top](#)

Table Name - cfg_table_list					
Description	List of tables used in configurable SQL statements				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time (used for tracking changes to data)
cterm	varchar2(15)	varchar(15)	no		Creation terminal (used for tracking changes to data)
 id_num	number(5,0)	smallint	no		Config id
 set_name	varchar2(20)	varchar(20)	no		Set Name. Replaces old XXconfig.txt file name
 table_alias	varchar2(30)	varchar(30)	no		Table alias (can be the table name)
table_name	varchar2(30)	varchar(30)	no		Table name
tdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time (used for tracking changes to data)
uterm	varchar2(15)	varchar(15)	yes		Update terminal (used for tracking changes to data)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cfg_table_list_primary_key	set_name, id_num, table alias			primaryKey	yes

[Top](#)

Table Name - change_item					
Description	Identifies the entities and properties in which subscriptions are interested. This table is used by the Change Publisher Service.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
entity_type_name	varchar2(45)	varchar(45)	no		The entity type name of interest
 id	raw(16)	varbinary(16)	no		Uniquely identifies the change item
navigation_property_name	varchar2(30)	varchar(30)	yes		The name of the navigation property that must be used to access the property if it is hidden
principal_entity_type_name	varchar2(45)	varchar(45)	yes		The principal entity type name associated with the navigation property
principal_property_name	varchar2(30)	varchar(30)	yes		The principal property name associated with the navigation property
property_name	varchar2(30)	varchar(30)	no		The property name of interest
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
change_item_pk	id			primaryKey	yes
change_item_uk	entity_type_name, property_name, navigation_property_name			uniqueKey	no

[Top](#)

Table Name - change_record					
Description	The change_record table is used to record changes to monitored tables. This table is populated via triggers. The Change Publisher Service reads this table and propagates this information to the CAD clients.				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
change_data	xmltype	xml	no		Change information, formatted as XML.
 change_id	number(19,0)	bigint	no		The change identifier uniquely identifies each row. This id is used by the Change Subscription facility to order changes.
change_time [default = systimestamp]	timestamp(6)	datetimeoffset	no		Time when change was recorded. This column is used to identify old records for purging.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
change_record_change_time	change_time		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
change_record_pk	change_id		primaryKey		yes

[Top](#)

Table Name - chat					
Description	This table defines the actual Chat groups				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 id	number(10,0)	int	no		Unique ID of the Chat Group
name	varchar2(64)	varchar(64)	yes		Public Chat Group Name
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
chat_name_unique	name		yes	no	name is not null
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
chat_primary_key	id			primaryKey	yes

[Top](#)

Table Name - co_pl_a					
Description	The co_pl table contains common place related data used for location verification. CADDDBM has facilities for maintaining common place names by utilizing this table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 com_nme	varchar2(80)	varchar(80)	no		Common name assigned to a common place.
fea_mslink	number(10,0)	int	yes		Mslink of street segment
location_subtype	varchar2(10)	varchar(10)	yes		location type for MPS
location_type	varchar2(10)	varchar(10)	yes		location type for MPS
msg	varchar2(2000)	varchar(2000)	yes		This column contains a message about the commonplace name.
mslink	number(10,0)	int	yes		Link to graphic cell of the common place.
soundex	varchar2(4)	varchar(4)	yes		Soundex of common name that is assigned to common place.
 spad_mslink	number(10,0)	int	no		The mslink of the associated special address.
str_num	varchar2(15)	varchar(15)	yes		Street number at common place
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
co_pl_a_fea_mslink	fea_mslink		no	no	
co_pl_a_mslink	mslink		no	no	
co_pl_a_soundex	soundex		no	no	
co_pl_a_spad_mslink	spad_mslink		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
co_pl_a_primary_key	com_nme, spad_mslink			primaryKey	yes
Triggers					
Trigger Name	Required		Trigger Type	Description	
co_pl_a_log_trig	No		Custom	Log inserts, updates and deletes to sp_ad_co_pl_change_log. CR 1-53EYH6	

[Top](#)

Table Name - co_pl_b					
Description	The co_pl table contains common place related data used for location verification. CADDDBM has facilities for maintaining common place names by utilizing this table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 com_nme	varchar2(80)	varchar(80)	no		Common name assigned to a common place.
fea_mslink	number(10,0)	int	yes		Mslink of street segment
location_subtype	varchar2(10)	varchar(10)	yes		location subtype for MPS
location_type	varchar2(10)	varchar(10)	yes		location type for MPS
msg	varchar2(2000)	varchar(2000)	yes		This column contains a message about the commonplace name.
mslink	number(10,0)	int	yes		Link to graphic cell of the common place.
soundex	varchar2(4)	varchar(4)	yes		Soundex of common name that is assigned to common place.
 spad_mslink	number(10,0)	int	no		The mslink of the associated special address.
str_num	varchar2(15)	varchar(15)	yes		Street number at common place
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
co_pl_b_fea_mslink	fea_mslink		no	no	
co_pl_b_mslink	mslink		no	no	
co_pl_b_soundex	soundex		no	no	
co_pl_b_spad_mslink	spad_mslink		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
co_pl_b_primary_key	com_nme, spad_mslink			primaryKey	yes
Triggers					
Trigger Name	Required		Trigger Type	Description	
co_pl_b_log_trig	No		Custom	Log inserts, updates and deletes to sp_ad_co_pl_change_log. CR 1-53EYH6	

 [Top](#)

Table Name - common_event					
Description	The common_event table contains information common to all agencies that may be assigned to an event. The records in this table are created by I/CAD only.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time this record was inserted
cecust1	varchar2(50)	varchar(50)	yes		Common event custom column 1
cecust2	varchar2(50)	varchar(50)	yes		Common event custom column 2
cecust3	varchar2(50)	varchar(50)	yes		Common event custom column 3
cecust4	varchar2(50)	varchar(50)	yes		Common event custom column 4
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person responsible for creating the record
cterm	varchar2(15)	varchar(15)	no		Terminal on which the record was created
dow	varchar2(1)	varchar(1)	no	dow between 1 and 7	Day of week on which the event was reported
eapt	varchar2(5)	varchar(5)	yes		Apartment number component of event's location
earca	varchar2(40)	varchar(40)	yes		Area component of the event's location
ecompl	varchar2(80)	varchar(80)	yes		Commonplace name associated with the event's location
edirpre	varchar2(2)	varchar(2)	yes		Direction prefix component of the event's location
edirsuf	varchar2(2)	varchar(2)	yes		Direction suffix component of the event's location
efeanme	varchar2(30)	varchar(30)	yes		Feature name component (street name) of the event's location
efeatyp	varchar2(4)	varchar(4)	yes		Feature type component of the event's location
 eid	number(10,0)	int	no	positiveNumber	System event number for the event.
eloc_fld1	varchar2(5)	varchar(5)	yes		Generic location field
eloc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
eloc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
eloc_fld4	varchar2(5)	varchar(5)	yes		Generic location field
elocation	varchar2(450)	varchar(450)	no		Event location string
emun	varchar2(40)	varchar(40)	yes		Municipality component of the event's location
estnum	varchar2(15)	varchar(15)	yes		Street number (house number) component of the event's location
fea_mslink	number(10,0)	int	yes		Source feature map link
hash	number(10,0)	int	yes		The hash value of the address. The hash uses the direction prefix, street name, street type, and direction suffix for street addresses. For intersections, it uses those values from both streets.
latitude	binary_double	float(53)	no		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
loc_com	varchar2(80)	varchar(80)	yes		Location comments.
loc_ver	varchar2(1)	varchar(1)	no	booleanToRF	The location verified status for the event. T means the location was successfully verified. F means the location was not verified.
loi_event [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Loi_event is used to identify if the selected event has related events found via a DBServer search of the event tables. It is used to light the Location button or the Ev button on the Event dialogs in CAD.
loi_inf [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Loi_inf is used to identify if the selected event has related Informer information found via Informer searches. It is used to light the Location button or the Inf button on the Event dialogs in CAD.
loi_specsit [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Loi_specsit is used to identify if the selected event has related special situation data found via a DBServer search of the special situation table. It is used to light the Location button or the SS button on the Event dialogs in CAD.
longitude	binary_double	float(53)	no		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
maplevs	varchar2(200)	varchar(200)	yes		Map level(s) assigned to the event due to special address as location
parse_type [default = -1]	number(10,0)	int	no	parse_type in (-1,0,1,2,3,4)	Parse type. Indicates how the location was parsed. -1= unknown, 0= street, 1= intersection, 2= commonplace, 3= alarm, 4= X,Y location.
patient	varchar2(45)	varchar(45)	yes		Patient's name if this event is a scheduled event
pcad_case_num	varchar2(12)	varchar(12)	yes		CAD case number generated for ProQA case
rev_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date timestamp when this revision was created. Note that not all updates generate a new revision.
rev_num	number(10,0)	int	no	positiveNumber	Record revision number.
rev_pers	number(10,0)	int	no	nonNegativeNumber	Employee ID of person who created this revision.
rev_sec	number(19,0)	bigint	no		Rev_dts time stamp stored in epoch seconds.
rev_term	varchar2(15)	varchar(15)	no		Terminal on which this revision was created.
s_esz [default = -1]	number(10,0)	int	yes		Stores the system esz value from the verified event location.
temp_lock [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	Used to temporarily lock the row. T= row is locked. F = row is not locked. The committed value in the database should always be F
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time of when this record was last updated.
updt_flag	varchar2(15)	varchar(15)	no		Mutual exclusion column for event updating. If event is not being updated, value is set to NULLTERM.
upers	number(10,0)	int	yes	nonNegativeNumber	Employee ID of the person responsible for updating the record.
uterm	varchar2(15)	varchar(15)	yes		Terminal on which the record was updated.
x_cord	number(10,0)	int	no		X map coordinate for the event's location
xstreet1	varchar2(34)	varchar(34)	yes		Feature name and type of one street which intersects the event's location
xstreet2	varchar2(34)	varchar(34)	yes		Feature name and type of one street which intersects the event's location
y_cord	number(10,0)	int	no		Y map coordinate for the event's location
zip	varchar2(10)	varchar(10)	yes		Zip Code. Queried by Firelink Interface application.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
common_event_cdtsudts	cdts, udts		no	no	
common_event_efeanme_num_typ	efeanme, estnum, efeatyp, emun, hash		no	no	
common_event_eid_x_cord_y_cord	eid, x_cord, y_cord		no	no	
common_event_hash	hash		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type	Sql Server Clustered	
common_event_pk	eid		primaryKey	yes	
Triggers					
Trigger Name	Required	Trigger Type	Description		
common_event_rev_trig	No	Custom	When updating rev_num, you must also set rev_ columns.		

 [Top](#)

Table Name - common_event_call					
Description	This table holds a record for every call that comes in about an event. Calls can come in via multiple sources, and regardless of the source they will have a call record in this table.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_id	varchar2(20)	varchar(20)	yes		Unique Call ID in CAD system. Links to an_al.call_num
call_sour	varchar2(8)	varchar(8)	yes		Call source. Ani/Ali, Radio, Walk-in,etc.
ccity	varchar2(25)	varchar(25)	yes		Caller city. May also contain caller state and zip code. (From ANI/ALI or operator entered)
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time the event was associated with the call
clname	varchar2(50)	varchar(50)	yes		Actual caller name (From ANI/ALI or operator entered)
clnum	varchar2(20)	varchar(20)	yes		Phone number (From ANI/ALI or operator entered)

cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person adding the call to the event
cstr_add	varchar2(80)	varchar(80)	yes		Caller location (From ANI/ALI or operator entered)
cterm	varchar2(15)	varchar(15)	no		Terminal where the call was added to the event
eid	number(10,0)	int	no	positiveNumber	Event Identification Number
 event_call_id	number(10,0)	int	no		Unique id for this call. Generated via numbr table entry
first_call	number(5,0)	smallint	no	booleanNumber1Or0	1 if First Caller, else 0
rev_num	number(10,0)	int	no	positiveNumber	Revision number of the record
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/Time stamp of when record updated
upers	number(10,0)	int	yes	nonNegativeNumber	Employee Id of user updating record
uterm	varchar2(15)	varchar(15)	yes		Terminal name at which update made
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
common_event_call_call_id	call_id		no	no	
common_event_call_cdtsum	cdts, udts		no	no	
common_event_call_cname	cname		no	no	
common_event_call_clnum	clnum		no	no	
common_event_call_eid	eid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
common_event_call_pk	event_call_id			primaryKey	yes

 [Top](#)

Table Name - common_event_call_history					
Description	This table holds a record for every change to every call that comes in about an event. Calls can come in via multiple sources, and regardless of the source they will have a call record in this table. This table contains the current record, as well as all the history records.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
call_id	varchar2(20)	varchar(20)	yes		Unique Call ID in CAD system. Optional. Links to an_al.call_num
call_sour	varchar2(8)	varchar(8)	yes		Call source. Ani/AlI, Radio, Walk-in,etc.
ccity	varchar2(25)	varchar(25)	yes		Caller city. May also contain caller state and zip code. (From ANI/ALI or operator entered)
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time the event was associated with the call
cname	varchar2(50)	varchar(50)	yes		Actual caller name (From ANI/ALI or operator entered)
clnum	varchar2(20)	varchar(20)	yes		Phone number (From ANI/ALI or operator entered)
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person adding the call to the event
cstr_add	varchar2(80)	varchar(80)	yes		Caller location (From ANI/ALI or operator entered)
cterm	varchar2(15)	varchar(15)	no		Terminal where the call was added to the event
eid	number(10,0)	int	no	positiveNumber	Event Identification Number
 event_call_id	number(10,0)	int	no		Unique id for this call. Generated via numbr table entry
first_call	number(5,0)	smallint	no	booleanNumber1Or0	1 if First Caller, else 0
 rev_num	number(10,0)	int	no	positiveNumber	Revision number of the record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
common_event_call_his_call_id	call_id		no	no	
common_event_call_his_cname	cname		no	no	
common_event_call_his_clnum	clnum		no	no	
common_event_call_his_eid	eid		no	no	
common_event_call_history_cdtsum	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
common_event_call_history_pk	event_call_id, rev_num			primaryKey	yes

 [Top](#)

Table Name - common_event_history					
Description	The event table contains historical common event records. When a common_event record is updated, a snapshot of its previous contents are recorded in this table.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp of this history row.
cecust1	varchar2(50)	varchar(50)	yes		Common event custom column 1
cecust2	varchar2(50)	varchar(50)	yes		Common event custom column 2
cecust3	varchar2(50)	varchar(50)	yes		Common event custom column 3
cecust4	varchar2(50)	varchar(50)	yes		Common event custom column 4
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person responsible for creating this history record
cterm	varchar2(15)	varchar(15)	no		Terminal on which this history record was created
dow	varchar2(1)	varchar(1)	no	dow between 1 and 7	Day of week on which the event was reported
eapt	varchar2(5)	varchar(5)	yes		Apartment number component of event's location
earea	varchar2(40)	varchar(40)	yes		Area component of the event's location
ecompl	varchar2(80)	varchar(80)	yes		Commonplace name associated with the event's location
edirpre	varchar2(2)	varchar(2)	yes		Direction prefix component of the event's location
edirsuf	varchar2(2)	varchar(2)	yes		Direction suffix component of the event's location
efeanme	varchar2(30)	varchar(30)	yes		Feature name component (street name) of the event's location
efeatyp	varchar2(4)	varchar(4)	yes		Feature type component of the event's location
 eid	number(10,0)	int	no	positiveNumber	System event number for the event.
eloc_fld1	varchar2(5)	varchar(5)	yes		Generic location field
eloc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
eloc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
eloc_fld4	varchar2(5)	varchar(5)	yes		Generic location field
elocation	varchar2(450)	varchar(450)	no		Event location string
emun	varchar2(40)	varchar(40)	yes		Municipality component of the event's location
estnum	varchar2(15)	varchar(15)	yes		Street number (house number) component of the event's location
fea_mslink	number(10,0)	int	yes		Source feature map link
hash	number(10,0)	int	yes		The hash value of the address. The hash uses the direction prefix, street name, street type, and direction suffix for street addresses. For intersections, it uses those values from both streets.
latitude	binary_double	float(53)	no		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
loc_com	varchar2(80)	varchar(80)	yes		Location comments.
loc_ver	varchar2(1)	varchar(1)	no	booleanTOrF	The location verified status for the event. T means the location was successfully verified. F means the location was not verified.
loi_event [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Loi_event is used to identify if the selected event has related events found via a DBServer search of the event tables. It is used to light the Location button or the Ev button on the Event dialogs in CAD.

loi_inf [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Loi_inf is used to identify if the selected event has related Informer information found via Informer searches. It is used to light the Location button or the Inf button on the Event dialogs in CAD.
loi_specsit [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Loi_specsit is used to identify if the selected event has related special situation data found via a DBServer search of the special situation table. It is used to light the Location button or the SS button on the Event dialogs in CAD.
longitude	binary_double	float(53)	no		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
maplevs	varchar2(200)	varchar(200)	yes		Map level(s) assigned to the event due to special address as location
parse_type [default = -1]	number(10,0)	int	no	parse_type in (-1,0,1,2,3,4)	Parse type. Indicates how the location was parsed. -1= unknown, 0= street, 1= intersection, 2= commonplace, 3= alarm, 4= X,Y location.
patient	varchar2(45)	varchar(45)	yes		Patient's name if this event is a scheduled event
pcad_case_num	varchar2(12)	varchar(12)	yes		CAD case number generated for ProQA case
rev_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation timestamp for this revision. The rev_dts column is copied from the common_event udt's column. This column is shown as cdts in the event view.
 rev_num	number(10,0)	int	no	positiveNumber	Record revision number.
rev_pers	number(10,0)	int	no	nonNegativeNumber	The person who created this revision. The rev_pers column is copied from the common_event upers column. This column is shown as cpers in the event view.
rev_sec	number(19,0)	bigint	no		The creation timestamp, in epoch seconds, for this revision. The rev_sec column is copied from the common_event usec column. This column is shown as csec in the event view.
rev_term	varchar2(15)	varchar(15)	no		The terminal that created this revision. The rev_term column is copied from the common_event uterm column. This column is shown as sterm in the event view.
s_esz [default = -1]	number(10,0)	int	yes		Stores the system esz value from the verified event location.
x_cord	number(10,0)	int	no		X map coordinate for the event's location
xstreet1	varchar2(34)	varchar(34)	yes		Feature name and type of one street which intersects the event's location
xstreet2	varchar2(34)	varchar(34)	yes		Feature name and type of one street which intersects the event's location
y_cord	number(10,0)	int	no		Y map coordinate for the event's location
zip	varchar2(10)	varchar(10)	yes		Zip Code. Queried by Firelink Interface application.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
common_event_his_cdts	cdts		no	no	
common_event_his_hash	hash		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
common_event_history_pk	eid, rev_num		primaryKey		yes

 [Top](#)

Table Name - conceptual_model_history					
Description	Stores the history of generating the conceptual model database objects, using the CAD Database Utility. Added for CR 1-569SFV				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no		Start time for creating the conceptual model database objects.
cterm	varchar2(15)	varchar(15)	no		The terminal where the CAD Database Utility was run.
definition_file_contents	blob	varbinary(max)	no		Definition file contents, compressed.
definition_file_path	varchar2(256)	varchar(256)	no		Complete path of the definition file that is being used to generate the conceptual model. Typically the definition file name is db_schema_both.xml
errors	number(10,0)	int	no	nonNegativeNumber	The number of uncorrected errors that occurred.
gen_subscription_objects	varchar2(1)	varchar(1)	no	booleanTorF	Did the user choose to generate the subscription objects? T= Yes, F= No
gen_views_and_triggers	varchar2(1)	varchar(1)	no	booleanTorF	Did the user choose to generate the entity views and triggers? T= Yes, F= No
os_user	varchar2(256)	varchar(256)	no		Operating system user
status	varchar2(30)	varchar(30)	no	status in ('started', 'finished', 'cancelled')	Status of the creation process: started, finished, cancelled
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	End time for creating the conceptual model database objects.
 unique_id	raw(16)	varbinary(16)	no		Unique identifier for the row
version	varchar2(11)	varchar(11)	no	regexp_like(version, ''[0-9][0-9][0-9][0-9][0-9][0-9][0-9][0-9][0-9]\$') and substr(version,7,5) >= 0 and substr(version,7,5) <= 65535	4-part conceptual model version. The first 3 parts come from the CAD DB Utility's version. The last part comes from the definition file's entity assembly version.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
conceptual_model_history_cdts	cdts		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
conceptual_model_history_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - conn_trans_count					
Description	Used to determine if a transaction has successfully been committed. CADDAC only uses this table for connections that require CADDAC to retry failed transactions.				
Copy Type	NO_ENTRY				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 connection_id	raw(16)	varbinary(16)	no		A GUID that uniquely identifies a connection
trans_count	number(10,0)	int	no		The total number of transactions executed by this connection
udts	varchar2(16)	varchar(16)	no		The date and time when the record was created or updated
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
conn_trans_count_udts	udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
conn_trans_count_pk	connection_id		primaryKey		yes

 [Top](#)

Table Name - cont_name					
Description	The cont_name table contains information describing the contact of persons due to the occurrence of various alarms.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
clname	varchar2(45)	varchar(45)	yes		Full name of the contacted individual.
clnum	varchar2(14)	varchar(14)	yes		Telephone number of the contacted individual.
co_date	varchar2(10)	varchar(10)	yes		Records date the individual named in the clname column was contacted about alarm.

co_time	varchar2(5)	varchar(5)	yes		Records time the individual named in clname column was contacted about the alarm.
cpers	number(10,0)	int	no	nonNegativeNumber	ID number creating person.
cstr_add	varchar2(36)	varchar(36)	yes		Full street address of the contacted individual.
cterm	varchar2(15)	varchar(15)	no		Creation terminal
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Status of this record. When T = current record, F = old record
 eid	number(10,0)	int	no	positiveNumber	Unique integer value which identifies this record.
info_scope	varchar2(12)	varchar(12)	yes		Indicates/limits availability of record contents to particular agencies.
priority	number(10,0)	int	yes		Indicates priority order in which person named within this record was to be contacted in the event of an alarm.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Uniquely identifies the supplemental information for this contacted individual and alarm.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Dts of when record was updated
updt_flag	varchar2(15)	varchar(15)	no		Used by CAD to temporarily lock this record for update.
upers	number(10,0)	int	yes	nonNegativeNumber	Updating person
uterm	varchar2(15)	varchar(15)	yes		Updating terminal
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
cont_name_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
cont_name_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
cont_name_primary_key	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - dashboardlog					
Description	Used to log changes to modes using I/Dashboard				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Agency ID. If ag_id is set and dgroup is null, all dgroups and terminals that are part of this agency, will now be set to the modestatus value of this record.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Dts when record was created
cterm	varchar2(15)	varchar(15)	no		Terminal creating record
curent	varchar2(1)	varchar(1)	no	booleanToRF	T=record is curent, F=earlier record
dgroup	varchar2(5)	varchar(5)	yes		Dispatch group. If dgroup is set and terminal is null, all terminals that are part of this dispatch group will now be set to the modestatus value of this record.
empid	number(10,0)	int	no	nonNegativeNumber	Employee id of person making the modestatus change
modestatus	varchar2(32)	varchar(32)	no		New mode status of agency ID and/or dgroup or the terminal
num_1	varchar2(12)	varchar(12)	yes		Agency event id. If num_1 is set, then an emergency event caused a modestatus change
previousmode	varchar2(32)	varchar(32)	no		Previous mode status of agency ID and/or dgroup or the terminal
remarks	varchar2(256)	varchar(256)	yes		Reason for mode status change
term	varchar2(15)	varchar(15)	yes		Terminal. If term is set and dgroup and ag_id are null, then only this terminal will be set to the new modestatus value.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
upers	number(10,0)	int	yes	nonNegativeNumber	Update employee id
uterm	varchar2(15)	varchar(15)	yes		Update terminal
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
dashboardlog_cdtsudts	cdts, udts		no	no	
dashboardlog_curagiddgroupterm	curent, ag_id, dgroup, term		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
dashboardlog_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - dashboardmode					
Description	Dashboard Mode table				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
color	varchar2(32)	varchar(32)	no		Defines the UI color for a particular ModeStatus
modestatus	varchar2(32)	varchar(32)	no		Name of the mode status - such as Emergency, Normal, Training, Degraded.
priority	number(10,0)	int	no		A numeric priority used when defining rules.
rules	varchar2(32)	varchar(32)	no		A list of priorities that defines whether a change in modeStatus from one mode to another can occur. For example, if the priority is 2 and the rules are set to 1,3, then a change in modeStatus can only occur for 1,3.
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
dashboardmode_modestatus	modestatus		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
dashboardmode_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - data_guard_role_change					
Description	This table logs Data Guard role changes. The role change trigger inserts data into this table.				
Copy Type	NO_ENTRY				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no		Date and time when row was written. This should correspond to when the database was started.
db_unique_name	varchar2(30)	varchar(30)	no		Database unique name
machine_name	varchar2(64)	varchar(64)	no		Server machine name where database is running.
log_sequence# [Oracle only]	number(38,0)	int	no		Current log sequence#

standby_became_primary_scn [Oracle only]	number(38,0)	decimal(10,)	yes		SCN when standby became primary
current_scn [Oracle only]	number(38,0)	decimal(10,)	no		Current system change number
activation# [Oracle only]	number(38,0)	int	yes		Number assigned to the database instantiation
fs_failover_current_target	varchar2(30)	varchar(30)	yes		DB_UNIQUE_NAME of the standby that is the current FSFO target standby for the Data Guard configuration
fs_failover_observer_host	varchar2(512)	varchar(512)	yes		Machine name that is currently hosting the observer process
fs_failover_observer_present	varchar2(7)	varchar(7)	yes		YES - Observer is currently connected to the local database NO - Observer is not connected to the local database
fs_failover_status	varchar2(21)	varchar(21)	yes		Fast-start failover status
fs_failover_threshold	number(10,0)	int	yes		Time in seconds that the observer will attempt to reconnect with a disconnected primary before attempting FSFO with the target standby
protection_mode	varchar2(20)	varchar(20)	yes		Protection mode currently in effect for database.
protection_level	varchar2(20)	varchar(20)	yes		Aggregated protection mode currently in effect for the database
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		GUID used for primary key
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
data_guard_role_change_pk	Oracle: unique_id SQL Server:		primaryKey		yes

 [Top](#)

Table Name - db_process					
Description	This table is used to track the progress of DBCOPY processes				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 cdt	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp
copy_file	varchar2(256)	varchar(256)	yes		Is used to record the copy file path name specified by an instance of DBCopy.
cterm	varchar2(15)	varchar(15)	no		Creating terminal
delta	varchar2(1)	varchar(1)	yes	booleanTOF	Is used to record the presence of the delta flag in an instance of DBCopy.
dest_db	varchar2(30)	varchar(30)	no		Name of the database configuration that is being copied to.
from_date	varchar2(16)	varchar(16)	no		The beginning of the copy time interval
 proc_name	varchar2(30)	varchar(30)	no		Full description of process that created this record.
proc_status	varchar2(1)	varchar(1)	no	proc_status in('S','F','R','I')	Status of the process at the time the record is written. S = start, F = finish, R = recommended time, I = inactive recommended time
purge	varchar2(1)	varchar(1)	yes	purge in('P','N','O')	Is used to record the value of the purge option specified by an instance of DBCopy.
source_db	varchar2(30)	varchar(30)	no		Name of the database configuration that is being copied from.
to_date	varchar2(16)	varchar(16)	yes	ipsTimestamp	The end of the copy time interval
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
db_process_primary_key	proc_name, cdt			primaryKey	yes

 [Top](#)

Table Name - db_table_status					
Description	This table is used by the DBCOPY processes to track each database table's state as the table is being copied				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp.
 proc_cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Key into db_process table to identify a unique db_process record (establishes a connection to a specific db_process record).
 proc_name	varchar2(30)	varchar(30)	no		The name of the instance of DBCopy that created this row. This value is used as part of the key to join with the db_process table.
row_count	number(10,0)	int	yes	row_count >= -1	The number of rows copied
 table_name	varchar2(30)	varchar(30)	no		Name of table being copied
table_status	varchar2(1)	varchar(1)	no	table_status in('S','C','F')	Status of table being copied. Initial value is S (start). As copying continues, status will be set to C (continuing) and finally to F (finished) when copying stops.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
db_table_status_primary_key	proc_cdts, proc_name, table_name			primaryKey	yes

 [Top](#)

Table Name - def_agency_page					
Description	This table defines the page ids to be toned for the agency, event type, and event sub-type combination.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id [default = 'default']	varchar2(9)	varchar(9)	no		Agency ID. The paging code interprets the value 'default' as a 'wildcard' that means 'don't consider this column in the select criteria'
default_page [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOF	Is Default (T/F)
dgroup	varchar2(5)	varchar(5)	yes		Dispatch Group
 esz [default = -1]	number(10,0)	int	no		Emergency Service Zone
label	varchar2(32)	varchar(32)	no		Label
 page_id	varchar2(12)	varchar(12)	no		Pager ID or Pager Group ID
sort_order [default = 0]	number(5,0)	smallint	no		Sort Order
 sub_tycod [default = 'default']	varchar2(16)	varchar(16)	no		Event Sub-type
 tycod [default = 'default']	varchar2(16)	varchar(16)	no		Event Type. The paging code interprets the value 'default' as a 'wildcard' that means 'don't consider this column in the select criteria'
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_agency_page_pk	ag_id, tycod, sub_tycod, esz, page_id			primaryKey	yes

 [Top](#)

Table Name - def_device	
Description	Def_device stores the defined devices for units, vehicles and people. Defined devices may include MDTs, GPS devices such as AVLS, vehicle-mounted radios (radio aliases), and HT radios. CR 1-6PGD42: PLT

Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Agency ID. If owner = 3, the agency that owns this device, else null.
carid	varchar2(12)	varchar(12)	yes		If owner = 2, vehicle that owns this device, else null
description	varchar2(50)	varchar(50)	yes		Device description
device_alias	varchar2(20)	varchar(20)	yes		User-friendly alias name for device
 device_id	varchar2(40)	varchar(40)	no		Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For HT radios, this may be the radio id. This may also be a GUID or UUID received from an external system
 device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
empid	number(10,0)	int	yes	nonNegativeNumber	If owner = 1, employee that owns this device, else null
gps_protocol [default = 0]	number(5,0)	smallint	no	nonNegativeNumber	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols
is_trackable	number(5,0)	smallint	no	booleanNumber1Or0	Is device trackable? 0 = False, 1 = True
owner	number(5,0)	smallint	no	owner between 0 and 3	Owner. 0 = unit, 1 = employee, 2 = Vehicle, 3 = Agency
tdevice_for_owner	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the owner. 1= True, 0 = False
unid	varchar2(10)	varchar(10)	yes		If owner = 0, the unit that owns this device, else null
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
def_device_ag_id	ag_id		no	no	
def_device_carid	carid		no	no	
def_device_empid	empid		no	no	
def_device_unid	unid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_device_pk	device_id, device_type, device_sub_type			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
def_device_mdt_smt_id_ck	Yes	(device_type not in (5,6)) or (regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$'))		(device_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)	
def_device_owner2_ck	Yes	(owner = 0 and unid is not null and empid is null and carid is null and ag_id is null) or (owner = 1 and unid is null and empid is not null and carid is null and ag_id is null) or (owner = 2 and unid is null and empid is null and carid is not null and ag_id is null) or (owner = 3 and unid is null and empid is null and carid is null and ag_id is not null)		(owner = 0 and unid is not null and empid is null and carid is null and ag_id is null) or (owner = 1 and unid is null and empid is not null and carid is null and ag_id is null) or (owner = 2 and unid is null and empid is null and carid is not null and ag_id is null) or (owner = 3 and unid is null and empid is null and carid is null and ag_id is not null)	
def_device_tdevice_ck	Yes	(owner != 3 and is_trackable = 1) or tdevice_for_owner = 0		(owner != 3 and is_trackable = 1) or tdevice_for_owner = 0	
Triggers					
Trigger Name	Required	Trigger Type		Description	
def_device_trig2	Yes	Custom		Populates valid_device with new device id, device type, device sub-type values	

 [Top](#)

Table Name - def_equip					
Description		The equipment associated with vehicles.			
Copy Type		ALL_WITH_CHECK			
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 carid	varchar2(12)	varchar(12)	no		The id for a vehicle
 equip	varchar2(10)	varchar(10)	no		This column contains a piece of equipment in this vehicle.
num_equip	number(10,0)	int	no	positiveNumber	Number of pieces of this equipment
Key Constraints					
Constraint Name		Columns		Constraint Type	Sql Server Clustered
def_equip_primary_key		carid, equip		primaryKey	yes

 [Top](#)

Table Name - def_page					
Description	This is the paging definition table. Def_page defines the individual pagers and pager groups. The page_id value (which may be an individual pager id or goup id) is used in other tables such as cd_units, agency_dgroup, and esz. The pager group members are defined in def_pgroup.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cond_id	varchar2(12)	varchar(12)	yes		An id for a conditional expression in the page_cond table. Can only be specified for individual pagers (id_type = 'P')
description	varchar2(30)	varchar(30)	yes		Description. The page_id may be cryptic. This column can provide a more user-friendly description of the pager or pager group.
id_type	varchar2(1)	varchar(1)	no	id_type in ('P','G')	Defines whether the page_id refers to an individual pager (P) or a pager group (G).
page_code	varchar2(80)	varchar(80)	yes		The actual page code to be sent to the controlling device. Must be specified for individual pagers (id_type = 'P')
 page_id	varchar2(12)	varchar(12)	no		Pager ID or pager group ID. The id_type column specifies whether this value is a pager ID or pager group ID.
page_order [default = 9999]	number(10,0)	int	no	nonNegativeNumber	Paging order. When a CAD command lists multiple pager ids, then this column determines the order in which the pages are sent. Pagers and pager groups with smaller page_order values will get sent pages first.
page_type	varchar2(120)	varchar(120)	yes		The page interface/controller type such as zetron or tap. Tap is a protocol supported by many controllers such as Glenayre. Use caddbm to populate. Must be specified for individual pagers (id_type = 'P')
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_page_primary_key	page_id			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
def_page_cond_id_ck	Yes	not (id_type = 'G' and cond_id is not null)		not (id_type = 'G' and cond_id is not null)	
def_page_page_code_ck	Yes	(id_type='G' and page_code is null) or (id_type='P' and page_code is not null)		(id_type='G' and page_code is null) or (id_type='P' and page_code is not null)	
def_page_page_type_ck	Yes	(id_type='G' and page_type is null) or (id_type='P' and page_type is not null)		(id_type='G' and page_type is null) or (id_type='P' and page_type is not null)	

 [Top](#)

Table Name - def_pgroup					

Description	This table defines pager group members. A group can contain individual pagers as well as groups of pagers, so the page_id column can contain either a page_id or a group_id. The def_page table contains the definitions of the pager_groups as well as the individual pager ids.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 group_id	varchar2(12)	varchar(12)	no		The group id defines a group of pager ids.
member_order [default = 9999]	number(10,0)	int	no	nonNegativeNumber	Member order. Determines the order in which pages are sent. Members with a smaller value will be sent pages first.
 page_id	varchar2(12)	varchar(12)	no		Pager ID or Group ID. This column can contain a page_id or a group_id.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_pgroup_primary_key	group_id, page_id			primaryKey	yes

 [Top](#)

Table Name - def_station					
Description	The def_station table defines stations and/or posts that are used within CAD. Stations and Posts are usually locations or places associated with Fire and EMS agencies.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ack_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit at this station should be in acknowledge status
ag_id	varchar2(9)	varchar(9)	no		Identification for agency to which a station is assigned
arrive_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit at this station should be in arrive status
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person
cterm	varchar2(15)	varchar(15)	no		Creating Terminal
dgroup	varchar2(5)	varchar(5)	no		Station's dispatch group
disp_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit at this station should be in dispatch status
enroute_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit at this station should be in enroute status
lev3	varchar2(7)	varchar(7)	yes		This column contains an identifier for beat or service area to which this station is assigned.
loc_x [default = 0.0]	float(126)	float(53)	no		X coordinate of station's physical location (in Master Units)
loc_y [default = 0.0]	float(126)	float(53)	no		Y coordinate of station's physical location (in Master Units)
page_id	varchar2(12)	varchar(12)	yes		Pager ID or Pager Group ID from def_page.
phone_no	varchar2(14)	varchar(14)	yes		Phone number for this station
prt_addr	varchar2(80)	varchar(80)	yes		Print queue address of this station.
prt_type	varchar2(1)	varchar(1)	yes	prt_type in ('A', 'B', 'C', 'D', 'E', 'F')	Indicates to Fire Station Printing what type of output prt_addr references. Legal values are: A-ASCII text, B-FSA print packet, C-RTF, D-Email address, E-Windows executable F- Motorola's PMDC interface.
s_name	varchar2(30)	varchar(30)	yes		Name of this station
 station	varchar2(10)	varchar(10)	no		Unique id for this station. It is the key for this table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_station_primary_key	station			primaryKey	yes

 [Top](#)

Table Name - def_station_crew						
Description		This table contains crew definitions.				
Copy Type		ALL_WITH_CHECK				
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
ag_id	varchar2(9)	varchar(9)	no		Agency ID for which the crew is defined.	
 crew_id	varchar2(30)	varchar(30)	no		Crew ID.	
dgroup	varchar2(5)	varchar(5)	yes		Dispatch Group for which the crew is defined.	
restriction_type	varchar2(5)	varchar(5)	yes	restriction_type in ('ID','TYPE')	Restriction Type. Values are <NULL>, ID, TYPE.	
Key Constraints						
Constraint Name		Columns			Constraint Type	Sql Server Clustered
def_station_crew_primary_key		crew_id			primaryKey	yes

 [Top](#)

Table Name - def_station_crew_restriction					
Description	This table contains crew restrictions. It is managed in exactly the same manner as the def_station_crew table and works in conjunction with that table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 crew_id	varchar2(30)	varchar(30)	no		Crew ID. This column links back to the crew_id column in the def_station_crew table.
 restriction	varchar2(10)	varchar(10)	no		Crew Restriction. This may be a unit id or a unit type based on the crew's restriction_type attribute.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_statn_crew_res_primary_key	crew_id, restriction			primaryKey	yes

 [Top](#)

Table Name - def_station_persl					
Description	Defines the personnel associated with each station. When a person is logged onto to a station, the data from this table is typically copied to act_station_persl. Note that you can define associations between a person and multiple stations. However, a person can only log onto to a single station. Added for CR 1-4UUSDH				
Copy Type	ALL WITH CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
default_status [default = 0]	number(10,0)	int	no	default_status in (0,1)	Default status. When a person is logged on to a station, the person will be put in this status. 0= available, 1= unavailable
delay_value [default = 0]	number(10,0)	int	no	nonNegativeNumber	Delay, in minutes. Amount of time it would take this person to get to the station.
description	varchar2(200)	varchar(200)	yes		Description or comment. When a station person is logged on, this description is copied to act_station_persl, unless the dispatcher specifies a new comment.
 empid	number(10,0)	int	no	nonNegativeNumber	Employee id
 station	varchar2(10)	varchar(10)	no		Station id.

 [Top](#)

 [Top](#)

 [Top](#)

 [Top](#)

Table Name - def_vehic					
Description	This table defines any physical vehicles used in CAD. All police cars, fire trucks, etc. are defined here.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ack_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The time in minutes that a vehicle can be in acknowledge status.
ag_id	varchar2(9)	varchar(9)	no		Agency to which vehicle belongs
arrive_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit with this vehicle should be in arrive status
 carid	varchar2(12)	varchar(12)	no		Unique id for this vehicle.
delay_value [default = 0]	number(10,0)	int	no	nonNegativeNumber	This value will be added to the unit's time/distance when recommending units by the road network
disp_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit with this vehicle should be in dispatch status.
enroute_timer [default = 0]	number(10,0)	int	no	nonNegativeNumber	The maximum time a unit with this vehicle should be in enroute status
max_ht [default = 0]	number(10,0)	int	no	nonNegativeNumber	Maximum height for vehicle
max_wd [default = 0]	number(10,0)	int	no	nonNegativeNumber	Maximum width for vehicle
max_wt [default = 0]	number(10,0)	int	no	nonNegativeNumber	Maximum weight of vehicle.
page_id	varchar2(12)	varchar(12)	yes		The pager id or pager group id associated with the vehicle. This value is carried forward into the unit at log on.
page_unit_person [default = 0]	number(5,0)	smallint	no	page_unit_person in (0,1,2)	0 - Page unit only 1 - Page Employee only 2 - Page both unit & Employee
vflag [default = 'Y']	varchar2(1)	varchar(1)	no	booleanYOrN	MDT Voice Flag. This field defines whether the MDT unit is available on voice (radio). Y = Yes, N = No.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
def_vehic_primary_key	carid			primaryKey	yes

 [Top](#)

Table Name - deplo_plan					
Description	Defines all the valid deployment plans in the system.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 deplo_plan_name	varchar2(30)	varchar(30)	no		Deployment plan name
description	varchar2(50)	varchar(50)	yes		Description
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
deplo_plan_pk	deplo_plan_name			primaryKey	yes

 [Top](#)

Table Name - destinations					
Description	This table stores the destinations for a specified command type and instance. Used by broadcast.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation date time stamp.
command_code	number(10,0)	int	no	command_code in (1,3)	Integer value indicating for which command this destination is relevant. 1=Broadcast, 3=Scratch Pad
curent	varchar2(1)	varchar(1)	no	booleanTorF	T/F, indicates if row is active or deleted
delete_id [default = '0']	raw(16)	varbinary(16)	no		An arbitrary value that uniquely identifies a deleted row
destination	varchar2(80)	varchar(80)	no		A destination such as a nodename, mdt-id, page-id, email address, etc.
item_number	number(10,0)	int	no		Unique item number for the command which stores its information in this table.
main_type	varchar2(8)	varchar(8)	no	main_type in ('TERM','PERSON','PAGER', 'STATION','GROUP','EMPID','FILTER')	TERM, PERSON, PAGER, STATION, GROUP, EMPID, or FILTER.
msg_status	varchar2(1)	varchar(1)	no	msg_status in ('B','H','R','N','S')	B/H/R/N/S, Indicating broadcast, scheduled, read, not read, or saved.
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
sub_type	varchar2(15)	varchar(15)	yes		CAD, MDT, PAGER, or other application.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The update date time stamp.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
destinations_cdtsudts	cdts, udts		no	no	
destinations_command_code	command_code		no	no	
destinations_destination	destination		no	no	
destinations_rcvr_unique_id	recovery_unique_id		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
destinations_primary_key	unique_id			primaryKey	no
destinations_unique	item_number, command_code, destination, main_type, delete_id, recovery_unique_id			uniqueKey	yes

 [Top](#)

Table Name - det_ev_ty					
Description	This table contains information used for assigning results codes to events using the assign result code command in CAD. This data is created using the Detailed Event Types command in CADDDBM.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Unique id (from agenc table) for the agency associated with the event. This allows agencies to have different detailed event type information for the same event type.
 det_code	varchar2(8)	varchar(8)	no		Defines valid detailed type codes to be used by the Assign Result Code command.
det_literal	varchar2(40)	varchar(40)	yes		This column contains the literal description of the detailed event type.
 tycod	varchar2(16)	varchar(16)	no		Type code. Joins to the event_type table tycod column. Used by the Assign Result Code command to select the valid records based on the ag_id and tycod of the selected event.

Key Constraints			
Constraint Name	Columns	Constraint Type	Sql Server Clustered
det_ev_ty_primary_key	ag_id, tycode, det_code	primaryKey	yes

 [Top](#)

Table Name - device_loc_history						
Description	I/Tracker can use this table to write location history information it receives for devices not being tracked or for orphan devices (devices not found in the system). In other words, device_loc_history can store the data which I/Tracker logs to the Agency_NoTrack and Orphan track files. CR 1-6PGD42: PLT					
Copy Type	INSERT					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
altitude	binary_double	float(53)	yes		Distance above mean sea level (+ above).	
bearing	binary_double	float(53)	yes		Clockwise angle from true North range [0, 360.0]	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation timestamp for this record.	
device_id	varchar2(40)	varchar(40)	no		Unique device id.	
device_sub_type	number(5,0)	smallint	yes		Device sub type.	
device_type	number(5,0)	smallint	yes	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT.	
fix_age	number(5,0)	smallint	yes	fix_age between 0 and 2	Code for age of fix when this location was recorded (not the current age of the data). 0=unknown, 1=10 seconds or greater, 2=less than 10 seconds	
fix_type	number(5,0)	smallint	yes	fix_type in (0,1,2,3,6,8,9)	GPS source (fix type) indicator. 0=2D, 1=3D, 2=2D-differential, 3=3D-differential, 6=dead reckoning, 8=degraded, 9=unknown/invalid	
gps_date	varchar2(8)	varchar(8)	yes		Date of last GPS data from the device, in YYYYMMDD format	
gps_time	number(10,0)	int	yes		Time of last GPS data from the device, stored in seconds since midnight UTC	
horizontal_precision	number(5,0)	smallint	yes	horizontal_precision between 0 and 50	Horizontal dilution of precision: 1=ideal, 2-3=excellent, 4-6=good, 7-8=moderate, 9-20=fair, 21=50=poor	
is_orphan	number(5,0)	smallint	no	booleanNumber1Or0	Is this an orphan device? 0 = not orphan, 1 = orphan	
latitude	binary_double	float(53)	yes		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)	
loc_x	number(10,0)	int	yes		X-Coordinate of the device	
loc_y	number(10,0)	int	yes		Y Coordinate of the device	
location	varchar2(80)	varchar(80)	yes		Location, derived from reverse geocoding the device's coordinates.	
longitude	binary_double	float(53)	yes		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)	
sat_count	number(5,0)	smallint	yes	nonNegativeNumber	Number of satellites used in fix	
sensor	varchar2(150)	varchar(150)	yes		Sensor data. Previously called device in old avl_log table	
speed_bearing	binary_double	float(53)	yes		Speed along the bearing (+ forward, - reverse). Units depends on what is supported by the AVL system	
speed_vertical	binary_double	float(53)	yes		Speed vertical (+ up, - down). Units depends on what is supported by the AVL system	
 unique_id	raw(16)	varbinary(16)	no		Unique identifier	
units_of_measurement	number(5,0)	smallint	no	units_of_measurement between 0 and 2	Units of measurement. 0=unknown, 1=metric (meters/KPH), 2=imperial (feet/MPH)	
Indexes						
Index Name	Columns		Is Unique		Sql Server Clustered	Sql Server Where Clause
device_loc_his_cdts_dev	cdts, device_id		no		yes	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
device_loc_history_pk	unique_id			primaryKey	no	
Check Constraints						
Constraint Name		Required	Oracle Definition		Sql Server Definition	
device_loc_hist_latlon_ck		Yes	(loc_x is null and loc_y is null and latitude is null and longitude is null) or (loc_x is not null and loc_y is not null and latitude is not null and longitude is not null)		(loc_x is null and loc_y is null and latitude is null and longitude is null) or (loc_x is not null and loc_y is not null and latitude is not null and longitude is not null)	

 [Top](#)

Table Name - directory						
Description	Contains the location information used by Local Lookup for query location. The Directory process is used to modify this table. This table is mainly used by the I/Telephone product. This table may also used by the LocalLookup dll in custom applications.					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
area	varchar2(5)	varchar(5)	yes		City (area) code of number	
clip	varchar2(16)	varchar(16)	yes		Required	
country	varchar2(5)	varchar(5)	yes		Country code of phone number	
emp_num	varchar2(18)	varchar(18)	yes		This entry is NULL except for private entries. For private entries it contains the owners emp_id number. Cannot be used for Speed Dial.	
fname	varchar2(12)	varchar(12)	yes		The first Name of entry	
house_number	varchar2(5)	varchar(5)	yes		Number	
lang	varchar2(1)	varchar(1)	yes		Language indicator	
level1	varchar2(20)	varchar(20)	yes		First level of the Tree View in directory.exe	
level10	varchar2(20)	varchar(20)	yes		Tenth level of the Tree View in directory.exe	
level2	varchar2(20)	varchar(20)	yes		Second level of the Tree View in directory.exe	
level3	varchar2(20)	varchar(20)	yes		Third level of the Tree View in directory.exe	
level4	varchar2(20)	varchar(20)	yes		Fourth level of the Tree View in directory.exe	
level5	varchar2(20)	varchar(20)	yes		Fifth level of the Tree View in directory.exe	
level6	varchar2(20)	varchar(20)	yes		Sixth level of the Tree View in directory.exe	
level7	varchar2(20)	varchar(20)	yes		Seventh level of the Tree View in directory.exe	
level8	varchar2(20)	varchar(20)	yes		Eighth level of the Tree View in directory.exe	
level9	varchar2(20)	varchar(20)	yes		Nineth level of the Tree View in directory.exe	
ln_soundex	varchar2(6)	varchar(6)	yes		Soundex value for last name	
lname	varchar2(17)	varchar(17)	yes		The last name of entry.	
mi	varchar2(20)	varchar(20)	yes		Middle Initial of entry Used by ASTRID as Category	
municipality	varchar2(50)	varchar(50)	yes		City or town	
phone	varchar2(16)	varchar(16)	yes		The phone number	
postal_code	varchar2(16)	varchar(16)	yes		Postal code (Belgium)	
speed_dial	varchar2(1)	varchar(1)	yes	booleanTOrF	T - Enter in Speed Dial list, F - Do not enter in Speed Dial list	
speed_label	varchar2(17)	varchar(17)	yes		Label to be displayed in Speed Dial list.	
str_soundex	varchar2(6)	varchar(6)	yes		Soundex value for street name	
street_name	varchar2(50)	varchar(50)	yes		Name of street	
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies rows	
Index Name		Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
directory_speed_dial_emp_num		speed_dial, emp_num		no	yes	
Key Constraints						

Constraint Name	Columns	Constraint Type	Sql Server Clustered
directory_pk	unique_id	primaryKey	no

[Top](#)

Table Name - dispass_event					
Description	This table is used by the Dispatch Assigned (DAed) functionality to maintain the order in which events are dispatch assigned to units. This table is not for historical use. Records are removed as DA events are dispatched (DPed)				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alarm_time [default = 0]	number(10,0)	int	no		Minutes after last status change when unit goes into an alarm state
disp_num	varchar2(12)	varchar(12)	yes		Unique dispatch number assigned to dispatch assigned event
list_pos	number(10,0)	int	no		This column represents the position in which an event was Dispatch Assigned to a unit in relation to other DA events for that unit. Ordering starts at 0 but may go negative if DA events are moved to the top of the list
num_1	varchar2(12)	varchar(12)	no		This field represents the agency event number for any event that is Dispatch Assigned to a unit.
status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time of last status change
trans_location	varchar2(80)	varchar(80)	yes		Transport location text
transxor [default = 0]	number(10,0)	int	no		Verified X coordinate of transport location
transyor [default = 0]	number(10,0)	int	no		Verified Y coordinate of transport location
unid	varchar2(10)	varchar(10)	no		This field represents the unit number for a unit that has an event dispatch assigned to it.
unit_status	number(10,0)	int	no		This column will allow a unit status to be assigned for each dispatch assigned event.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
dispass_event_primary_key	num_1			primaryKey	yes
dispass_event unique	unid, list_pos			uniqueKey	no

[Top](#)

Table Name - dispass_sched_event					
Description	Lists dispatch assigned events for units scheduled for future log-on as part of a lineup				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
lineup_name	varchar2(30)	varchar(30)	yes		Lineup name containing unit
list_pos	number(10,0)	int	no	nonNegativeNumber	Zero-based index of agency event within dispatch assigned list
 num_1	varchar2(12)	varchar(12)	no		Agency event number of assigned event
status [default = 0]	number(10,0)	int	no	status = 0 or status = 1	Status of the event scheduled for dispatch assign. 0 = Planned, 1 = Committed
unid	varchar2(10)	varchar(10)	no		Unit's ID
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
dispass_sched_event_unid_pos	unid, list_pos		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
dispass_sched_event_pk	num_1		primaryKey		yes

[Top](#)

Table Name - display_filter_config					
Description	Stores information on custom display information which is restored when the user logs in on the same or different machine.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
display_def	blob	varbinary(max)	yes		Custom configuration for the display(filter)
display_def_size	number(10,0)	int	no		Size of data stored in display_def column
 display_def_type	number(10,0)	int	no		Type of display
 display_name	varchar2(870)	varchar(870)	no		Name of the particular display
 usr_id	varchar2(20)	varchar(20)	no		User's id from persl table
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
display_filter_config_pk	usr_id, display_name, display_def_type			primaryKey	yes

[Top](#)

Table Name - disposition_type					
Description	This table contains disposition type codes. Previously, this data was stored in ev_ty where e_u_type = 'D'				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency Id
case_num_id	number(10,0)	int	yes	positiveNumber	Case Number Identifier. This column defines where to receive the case number for this disposition. This column links to the num_id column in the numbr table.
eng	varchar2(80)	varchar(80)	yes		English Description. This column contains the textual description of the disposition type.
 tycod	varchar2(16)	varchar(16)	no		The disposition type code.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
disposition_type_pk	ag_id, tycod			primaryKey	yes

[Top](#)

Table Name - divert					
Description	The divert table stores the hospital divert statuses.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
caller	varchar2(30)	varchar(30)	yes		Caller Name.
 cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp

cpers	number(10,0)	int	no	nonNegativeNumber	Creation Person
cterm	varchar2(15)	varchar(15)	no		Creation Terminal
d_comm	varchar2(40)	varchar(40)	yes		Diversion Comment.
 d_type	varchar2(10)	varchar(10)	no		Diversion type.
location	varchar2(200)	varchar(200)	yes		Hospital location
 mslink	number(10,0)	int	no		Map Graphics Link. Graphics link to a specific location.
open_record	varchar2(1)	varchar(1)	no	booleanToRF	T indicates the diversion is active, F indicates it has been closed
phone_num	varchar2(14)	varchar(14)	yes		Phone Number of the caller
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
x_caller	varchar2(30)	varchar(30)	yes		Name of clearing authority
x_comm	varchar2(40)	varchar(40)	yes		Clearing Comments.
xdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Close Date/Time Stamp
xpers	number(10,0)	int	yes	nonNegativeNumber	Clearing person
xterm	varchar2(15)	varchar(15)	yes		Clearing Terminal
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
divert_cdtudts	cdts, udts		no	no	
divert_open_record	open_record		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
divert_primary_key	mslink, d_type, cdts			primaryKey	yes

 [Top](#)

Table Name - eisec					
Description	Contains the password for EISECServer. Should only contain one row.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 password	varchar2(26)	varchar(26)	no		Password
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
eisec_pk	password			primaryKey	yes

 [Top](#)

Table Name - esz					
Description	The esz table is used to store information about what type of equipment must be deployed when certain events happen in certain areas. There will be a record for each deployment plan and esz combination. There may also be overrides for certain event types.				
Copy Type	PSEUDO_DELETE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alarm_lev [default = -1]	number(10,0)	int	no		Alarm level for a specified Event Type within an Emergency Service Zone. If no alarm level is specified this will be set to -1.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The create datetime stamp
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTOrF	T = Current, F = Deleted
delete_id [default = '0']	raw(16)	varbinary(16)	no		A unique id that is set when the row is deleted
depo_plan_name	varchar2(30)	varchar(30)	no		The deployment plan name
dgroup	varchar2(5)	varchar(5)	yes		Unique id for dispatch group of the ESZ of this record.
esz	number(10,0)	int	no	nonNegativeNumber	Emergency Service Zone. (level one area)
lev2	varchar2(6)	varchar(6)	yes		Reporting area/ census track/ grid in which this ESZ is located.
lev3	varchar2(7)	varchar(7)	no		Beat/district in which the esz is located.
page_id	varchar2(12)	varchar(12)	yes		Associated Pager ID or Pager Group ID
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
resp_plan_name	varchar2(50)	varchar(50)	yes		Response plan which will be used when an event happens in this ESZ.
sub_tycode [default = 'default']	varchar2(16)	varchar(16)	no		The sub-type of the event type. If no event sub-type is specified this will be set to default.
tycode [default = 'default']	varchar2(16)	varchar(16)	no		Event type code for which this record is written. If no event type is specified this will be set to default.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The update datetime stamp.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
esz_cdtstudts	cdts, udts		no	no	
esz_curent	curent		no	no	
esz_rcvr_unique_id	recovery_unique_id		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
esz_primary_key	unique_id			primaryKey	no
esz_unique	depo_plan_name, esz, tycode, sub_tycode, alarm_lev, delete_id, recovery_unique_id			uniqueKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
esz_alarm_lev_tycode_ck	Yes	{alarm_lev = -1 and tycode = 'default'} OR {alarm_lev >= 0 and tycode != 'default'}		{[alarm_lev] = -1 and [tycode] = 'default'} OR {[alarm_lev] >= 0 and [tycode] != 'default'}	
esz_cur_del_ck	Yes	{curent = 'T' and delete_id = '00'} OR {curent = 'F' and delete_id != '00'}		{[curent] = 'T' and [delete_id] = 0x00} OR {[curent] = 'F' and [delete_id] != 0x00}	

 [Top](#)

Table Name - ev_dispo					
Description	Event dispositions and result codes associated with events in agency_event				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
case_num	varchar2(12)	varchar(12)	yes		Unique id number for case
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time this record was inserted
cpers	number(10,0)	int	no	nonNegativeNumber	Empid of the person who created the event disposition.
cterm	varchar2(15)	varchar(15)	no		Terminal name on which an event disposition was created.
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Flag to indicate whether or not this record is the most current revision for this disposition code for a given event
dispo [default = 'default']	varchar2(16)	varchar(16)	no		Closing Disposition or result code.

eid	number(10,0)	int	no	positiveNumber	Unique Event Id Number generated by the system
member_id	number(10,0)	int	yes		This column stores the employee id of a person assigned to the associated unit.
 num_1	varchar2(12)	varchar(12)	no		Agency "event" number
qual1	varchar2(8)	varchar(8)	yes		Assign Result Code qualifier
qual2	varchar2(3)	varchar(3)	yes		Assign Result Code qualifier
qual3	varchar2(3)	varchar(3)	yes		Assign Result Code qualifier
 rev_num	number(10,0)	int	no	positiveNumber	Revision Number of Record. Used to provide an audit trail.
 row_num	number(10,0)	int	no		Row Number. This column identifies which disposition this row is associated with. The first row is the primary disposition.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time of when this record was last updated
unit_id	varchar2(10)	varchar(10)	yes		ID of unit that reported disposition code
upers	number(10,0)	int	yes	nonNegativeNumber	ID of person updating event disposition
uterm	varchar2(15)	varchar(15)	yes		Terminal which updated event disposition
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
ev_dispo_cdtstuds	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
ev_dispo_primary_key	num_1, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - ev_ty_alias					
Description	Contains agency-specific aliases for event types.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alias_ag_id	varchar2(9)	varchar(9)	no		Agency id of aliased event type
alias_sub_tycod [default = 'default']	varchar2(16)	varchar(16)	no		Sub-type of aliased event type. Will contain 'default' if there is no sub-type.
alias_tycod	varchar2(16)	varchar(16)	no		Aliased event type
 sub_tycod [default = 'default']	varchar2(16)	varchar(16)	no		Sub-type of event type. Will contain 'default' if there is no sub-type.
 tycod	varchar2(16)	varchar(16)	no		Event type
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
ev_ty_alias_primary_key	tycod, sub_tycod, alias_ag_id		primaryKey		yes

 [Top](#)

Table Name - evcom					
Description	This table contains comments entered when the event was created/updated in I/CAD. They can be seen by all agencies or marked as agency specific, making them visible only to the agency responding to the event.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmsszz) at which this record was inserted into the database.
comm	varchar2(4000)	varchar(4000)	no		Segment of the comment entered by the user
comm_key [default = 0]	number(10,0)	int	no		Indicates if this is a system comment (comm_key > 0)
comm_scope	varchar2(12)	varchar(12)	yes		Readership scope for the comment. This column is NULL when the information is common, or the ID of the agency for which the information is specific to.
cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID of the person responsible for creating the record.
csec	number(19,0)	bigint	no		Cdts time stamp stored in epoch seconds
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The nodename of the terminal on which the record was created.
eid	number(10,0)	int	no	positiveNumber	Event Identification Number. Internal system event number to which this comment belongs. This column links to the eid column in the event, agency_event, vehic, perso, un_hi, and propt tables.
lin_grp	number(10,0)	int	no		Unique identifier for a group of lines of event comments. An individual line of comment will have a value of zero. A group of lines of the same comment will have an integer value generated from the numbr table.
lin_ord	number(10,0)	int	no		Linear order for this comment segment. This value is used in the reconstruction of the comment by selecting all records with the same eid, cterm and cdts.
 unique_id	raw(16)	varbinary(16)	no		Unique identifier
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
evcom_cdtstuds	cdts		no	no	
evcom_comm_scope	comm_scope		no	no	
evcom_eid	eid		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
evcom_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - event_attachment					
Description	Associates an event with an attachment				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 attachment_id	raw(16)	varbinary(16)	no		Uniquely identifies an attachment
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time when this record was created
cpers	number(10,0)	int	no	nonNegativeNumber	The employee id of the person that created this record
cterm	varchar2(15)	varchar(15)	no		The terminal that was used to create this record
curent	varchar2(1)	varchar(1)	no	booleanTorF	Flag to indicate if the attachment is to be considered attached to the event
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number
info_scope	varchar2(12)	varchar(12)	yes		The agency this attachment is visible to, or null if visible to agencies that see the event
rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The time when this record was updated
upers	number(10,0)	int	yes	nonNegativeNumber	The employee id of the person that updated this record
uterm	varchar2(15)	varchar(15)	yes		The terminal that was used to update this record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
event_attachment_cdtstuds	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered

event_attachment_pk	cid, attachment_id	primaryKey	yes
---------------------	--------------------	------------	-----

 [Top](#)

Table Name - event_attachment_history					
Description		Represents the addition or removal of an attachment to an event			
Copy Type		INSERT			
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 attachment_id	raw(16)	varbinary(16)	no		Uniquely identifies an attachment
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time when this record was created
cpers	number(10,0)	int	no	nonNegativeNumber	The employee id of the person that created this record
cterm	varchar2(15)	varchar(15)	no		The terminal that was used to create this record
curent	varchar2(1)	varchar(1)	no	booleanTorF	Flag to indicate if the attachment is to be considered attached to the event
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number
info_scope	varchar2(12)	varchar(12)	yes		The agency this attachment is visible to, or null if visible to agencies that see the event
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
event_attachment_history_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
event_attachment_history_pk	eid, attachment_id, rev_num			primaryKey	yes

 [Top](#)

Table Name - event_group					
Description	The event_group table is used to store overall information about event groups. CR 1-4UUUAM 1-4UUDT8 - Event Groups				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp.
cpers	number(10,0)	int	no	positiveNumber	Creation employee id.
cterm	varchar2(15)	varchar(15)	no		Creation terminal.
description	varchar2(50)	varchar(50)	yes		Group description.
 group_id	varchar2(12)	varchar(12)	no		Unique group id.
group_status [default = 'A']	varchar2(1)	varchar(1)	no	group_status in ('A','C')	Status of event group - values are 'A' - Active (default), 'C' - Closed
group_type	number(5,0)	smallint	no		Group type.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp.
upers	number(10,0)	int	yes	positiveNumber	Update employee id.
uterm	varchar2(15)	varchar(15)	yes		Update terminal.
xdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Closing Date/Time Stamp.
xpers	number(10,0)	int	yes		ID of person who closed the event group.
xterm	varchar2(15)	varchar(15)	yes		Terminal which closed the event group.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
event_group_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
event_group_pk	group_id			primaryKey	yes

 [Top](#)

Table Name - event_type					
Description	This table contains event type codes. This info is used at I/CAD startup to build various associated lists such as the Event Type field on the main dispatcher form. Previously, this data was stored in ev_ty where e_u_type = 'E'				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
acknowledge_timer [default = 0]	number(10,0)	int	no	acknowledge_timer between 0 and 32766	Acknowledge Alarm Timer. How long a unit on this type of event can be in the acknowledgement status before an alarm sounds. Previously called ev_ty.time5
advised_event [default = 'F']	varchar2(1)	varchar(1)	no	booleanTorF	Create events of this type as advised events.
 ag_id	varchar2(9)	varchar(9)	no		Agency Id. Different agencies may have different type information for the same event type. For example, police might respond to a murder with priority 1, but EMS may respond with a priority of 3
arrive_timer [default = 0]	number(10,0)	int	no	arrive_timer between 0 and 32766	Arrive alarm timer. How long a unit on this type of event can be in the arrive status before an alarm sounds. Previously called ev_ty.time4
assign_case_state [default = 0]	number(10,0)	int	no	assign_case_state in (0,2,4,8,16,32,64)	Bitmap for states that automatically assign case numbers to an event. 0 = Undefined, 2 = Dispatch, 4 = Arrive, 8 = Transport, 16 = Transport arrive, 32 = Available, 64 = Assign Case
auto_response [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	When an event of this type is created, should this agency automatically be configured to respond. T= Automatically respond. F = do not automatically respond.
case_num_id	number(10,0)	int	yes	positiveNumber	Case Number Identifier. This column defines where to receive the case number for this disposition. This column links to the num_id column in the numbr table.
days_avail [default = 0]	number(10,0)	int	no	nonNegativeNumber	Days Available. This column contains the number of days available for LOI searches.
disp_req [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Required Disposition Code. This column is used to determine if a disposition is required for the event type. This code is set to (Y) if a disposition is required, else N.
dispatch_timer [default = 0]	number(10,0)	int	no	dispatch_timer between 0 and 32766	Dispatch Alarm Timer. How long a unit on this type of event can be in the dispatched status before an alarm sounds. Previously called ev_ty.time2
eng	varchar2(80)	varchar(80)	yes		English Description. This column contains the textual description of the event type.
enroute_timer [default = 0]	number(10,0)	int	no	enroute_timer between 0 and 32766	Enroute Alarm Timer. How long a unit on this type of event can be in the enroute status before an alarm sounds. Previously called ev_ty.time3
initial_callback_timer [default = 0]	number(10,0)	int	no		Event type default initial call back timer value. Initialized to 0. Previously called ev_ty.cbtime1
loi_dist	float(21)	float(24)	yes	loi_dist between 0.0 and 9999999.0	The distance that DBserver uses for Area Location of Interest searches
majevt_id	varchar2(10)	varchar(10)	yes		Major Event Identifier. This column contains the ID pointer to a major incident plan.
near_dist	float(21)	float(24)	yes	near_dist between 0.0 and 9999999.0	The distance that the Nearby Event(Duplicate Event) command uses for nearby event searches
pending_timer [default = 0]	number(10,0)	int	no	pending_timer between 0 and 32766	Pending Alarm Timer. How long an event of this type can stay pending before an alarm sounds. Previously called ev_ty.time1
pending_timer_default [default = 0]	number(10,0)	int	no	pending_timer_default between 0 and 32766	Default value for pending_timer. Previously called ev_ty.time1_def
priority [default = 9]	number(10,0)	int	no	priority between 0 and 9	Priority Number. This column contains the priority code to use with the event types only. Valid values are 0 to 9

 repeat_callback_timer [default = 0]	number(10,0)	int	no		Event type default repeat call back timer value. Initialized to 0. Previously called ev_ty.cbtime2
 sub_eng	varchar2(80)	varchar(80)	yes		The textual description of the sub-type.
 sub_tycod [default = 'default']	varchar2(16)	varchar(16)	no	instr(sub_tycod, ' ') = 0	The sub-type of the event type. 'default' if not specified
 tycod	varchar2(16)	varchar(16)	no	instr(tycod, ' ') = 0	Event type code
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
event_type_tycod_sub_tycod	tycod, sub_tycod		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
event_type_pk	ag_id, tycod, sub_tycod		primaryKey		yes
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
event_type_sub_tycod_eng_ck		Yes	NOT (sub_tycod ='default' and sub_eng is not null)		NOT (sub_tycod = 'default' and sub_eng is not null)

 [Top](#)

Table Name - event_type_alarm_level					
Description	This table contains the alarm level and response plan information for event type codes. This table links back to the event_type table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
additional_events	varchar2(80)	varchar(80)	yes		InterCAD column, a coded ASCII string with event type and sub type
 ag_id	varchar2(9)	varchar(9)	no		Agency Id. Different agencies may have different type information for the same event type. For example, police might respond to a murder with priority 1, but EMS may respond with a priority of 3
 alarm_lev [default = 0]	number(10,0)	int	no	nonNegativeNumber	Alarm Level. This defines the alarm level for the event type. The value must be greater than or equal to 0.
fs_icode	varchar2(4)	varchar(4)	yes		The incident code that will be added to the ZIR protocol packet. If the ZIR protocol version is Westnet Firstin 11, this string must be exactly four characters long Examples: I001, I004, I250, etc. Or if the ZIR protocol version is Westnet Firstin 8, this string must be exactly three characters long Examples: I01, I04, or I99, and the 'I' must be capitalized. Each I- code maps directly to a specific type code (tycod)
fs_icodessage	varchar2(50)	varchar(50)	yes		A description of the incident code. Examples: structure fire, animal bite, toxic waste spill, etc. This field cannot be longer than 50 characters
fs_rcode	varchar2(4)	varchar(4)	yes		The response code that will be added to the ZIR protocol packet. Each R-code corresponds to a specific severity level. If the ZIR protocol is Westnet Firstin 11, this string must be exactly four characters long. Examples: R001, R004, R250, etc. Or if the ZIR protocol is Westnet Firstin 8, this string must be exactly two characters long. Examples: R1, R4, or R8, and the 'R' must be capitalized. R-codes are mapped to a valid alarm level and tycod combination. If there are identical fs_icode entries, they will have different R-Code combinations.
fs_rcodessage	varchar2(60)	varchar(60)	yes		A description of the R-Code. This field cannot be longer than 60 characters
intercadsend	varchar2(1)	varchar(1)	yes		InterCAD column, indicates if InterCAD sends events out to a third party
msg	varchar2(80)	varchar(80)	yes		Message. This column is information specific of the event type to be displayed at time of unit recommendation.
page_id	varchar2(12)	varchar(12)	yes		Pager ID or Pager Group ID. If the page_id is not specified in the esz table, I/Page will look for the page_id in this table. I/Page sends notifications to this page identifier when new events are created with the specified agency, event type, sub-type and alarm level.
resp_plan_name	varchar2(50)	varchar(50)	yes		Response plan which will be used when an event of this type is created.
 sub_tycod [default = 'default']	varchar2(16)	varchar(16)	no		The sub-type of the event type. 'default' if not specified
 tycod	varchar2(16)	varchar(16)	no		Event type code
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
event_type_alarm_level_pk	tycod, sub_tycod, alarm_lev, ag_id			primaryKey	yes

 [Top](#)

Table Name - cvgraph					
Description	Instructions for displaying graphics overlays for events.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create time stamp
cpers	number(10,0)	int	no	nonNegativeNumber	Create person
cterm	varchar2(15)	varchar(15)	no		Create term
curent	varchar2(1)	varchar(1)	no	booleanTOrF	T if active record, else F
eid	number(10,0)	int	yes	nonNegativeNumber	Event number link. A value of 0 indicates that there is no associated event.
 gra_id	number(10,0)	int	no		Unique id of graphic set
gra_name	varchar2(15)	varchar(15)	yes		Name of graphic set
gra_scope	varchar2(12)	varchar(12)	yes		Agency name, if graphic set is agency-specific
graphics	varchar2(240)	varchar(240)	no		Instructions for creating graphics
 lin_ord	number(10,0)	int	no		Order of this record in constructing full instruction set.
 rev_num	number(10,0)	int	no	nonNegativeNumber	Revision number of record
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time stamp
updt_flag	varchar2(15)	varchar(15)	no		Lock terminal for update
upers	number(10,0)	int	yes	nonNegativeNumber	Empid of updating person
uterm	varchar2(15)	varchar(15)	yes		Updating terminal
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
cvgraph_primary_key	gra_id, lin_ord, rev_num			primaryKey	yes

 [Top](#)

Table Name - extension_list					
Description	This is a list of telephone extensions local to the PBX. This table is used when extensions cannot be identified by length so they must be listed. This table is used mainly by CAD Interface applications.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 extension	varchar2(5)	varchar(5)	no		The extensions phone number as a string
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
extension_list_pk	extension			primaryKey	yes

 [Top](#)

Table Name - external_request_for_resources						
Description	This table records requests for resources (units) that are made by external systems via BizTalk and IFCAD. For example, if a nearby agency, running a different CAD system, requests units for mutual aid, this table records that request. The external_requested_resource table has the list of resources that were requested. Added for CR 1-5ZJQK4					
Copy Type	UPDATE					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date timestamp	
cpers	number(10,0)	int	no	nonNegativeNumber	Person that created this record	
cterm	varchar2(15)	varchar(15)	no		Terminal that created the record	
external_event_id	varchar2(64)	varchar(64)	no		External event ID	
external_system_id [default = 'default']	varchar2(64)	varchar(64)	no		External system ID	
local_event_id	varchar2(12)	varchar(12)	no		Agency event ID (num_1) on local system, that corresponds to the external event.	
request_closed [default = 'F']	varchar2(1)	varchar(1)	no	booleanTorF	Is request closed (T) or open (F)	
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp	
upers	number(10,0)	int	yes	nonNegativeNumber	Update person	
uterm	varchar2(15)	varchar(15)	yes		Update terminal	
Indexes						
Index Name	Columns			Is Unique	Sql Server Clustered	Sql Server Where Clause
external_request_for_res_cl	request_closed			no	no	
external_request_for_res_ext_e	external_event_id, external_system_id			no	no	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
external_request_for_res_pk	local_event_id			primaryKey	yes	

 [Top](#)

Table Name - external_requested_resource					
Description	This table contains the resources (units) that were requested by the external system, as well as the status of that request. Added for CR 1-5ZJQK4				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date timestamp
cpers	number(10,0)	int	no	nonNegativeNumber	Person that created this record
cterm	varchar2(15)	varchar(15)	no		Terminal that created this record
 local_event_id	varchar2(12)	varchar(12)	no		Agency event ID (num_1) on local system, that corresponds to the external event.
request_status	varchar2(1)	varchar(1)	no	request_status in ('A', 'O', 'R', 'T', 'U', 'W')	Status of the request. "A" = Accepted, "O" = Overridden (the external system's ability to change the unit's status has been overridden), "R" = Rejected, "T" = Timed Out, "U" = Unreachable, "W" = Waiting
status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Status Time. Contains the time that this request was created or last updated.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
 unit_id	varchar2(10)	varchar(10)	no		Unit requested by external system
upers	number(10,0)	int	yes	nonNegativeNumber	Update person
uterm	varchar2(15)	varchar(15)	yes		Update terminal
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
external_requested_resource_pk	local_event_id, unit_id			primaryKey	yes

 [Top](#)

Table Name - firelinkcasenum					
Description	Firelink for case_num				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID
agency_event_rev_num	number(10,0)	int	no	positiveNumber	The related revision number of the event from the agency_event table. This column is populated by Firelink when a record is inserted, and updated by Firelink when a record is updated. Note that this value may not match the current agency_event.rev_num value.
 case_num	varchar2(12)	varchar(12)	no		Case Number
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Timestamp
 config_id	varchar2(16)	varchar(16)	no		Configuration ID of the Firelink instance
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group
eid	number(10,0)	int	no	positiveNumber	Common Event Number
 num_1	varchar2(12)	varchar(12)	no		Agency Event Number
resend [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	Should Firelink resend this row? 1= True, resend. 0 = False, do not resend.
sent_state	varchar2(1)	varchar(1)	no	sent_state in ('1','3')	1 is for INC01 sent, 3 is for INC03 sent
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Timestamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
firelinkcasenum_cdtsudts	cdts, udts		no	no	
firelinkcasenum_num1	num_1		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
firelinkcasenum_pk	case_num, config_id, num_1			primaryKey	yes

 [Top](#)

Table Name - firelinkevent					
Description	Firelink for agency_event				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID
agency_event_rev_num	number(10,0)	int	no	positiveNumber	The related revision number of the event from the agency_event table. Note that this value may not match the current agency_event.rev_num value.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Timestamp
 config_id	varchar2(16)	varchar(16)	no		Configuration ID of the Firelink instance

eid	number(10,0)	int	no	positiveNumber	Common event number
 num_1	varchar2(12)	varchar(12)	no		Agency event number
resend [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	Should Firelink resend this row? 1= True, resend. 0 = False, do not resend
sent_state	varchar2(1)	varchar(1)	no	sent_state in ('1','3')	1 is for INC01 sent, 3 is for INC03 sent
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
firelinkevent_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
firelinkevent_pk	num_1, config_id		primaryKey		yes

 [Top](#)

Table Name - firelinkunit					
Description	Firelink for un_hi				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID
case_num	varchar2(12)	varchar(12)	yes		Case number
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create timestamp
config_id	varchar2(16)	varchar(16)	no		Configuration ID of the Firelink instance
dgroup	varchar2(5)	varchar(5)	no		Dispatch group
eid	number(10,0)	int	no	positiveNumber	Common event number
num_1	varchar2(12)	varchar(12)	no		Agency event number
resend [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	Should Firelink resend this row? 1= True, resend. 0 = False, do not resend
sent_flag	varchar2(1)	varchar(1)	no	sent_flag in ('T','T','X')	I represents intermediate unit statuses where the unit has not yet been cleared from the event. Once the unit is cleared, Firelink will update all these unit statuses to T to show that the whole dispatch cycle for this unit has been sent. X represents unit statuses that are tracked, but aren't sent in a Firelink message. The value X is necessary because of the "Dispatch Cycles" configuration in Firelink.
status_time	varchar2(16)	varchar(16)	no		Same as cdts in un_hi for this unit status
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
unid	varchar2(10)	varchar(10)	no		Unit Id
 unique_id	raw(16)	varbinary(16)	no		Unique identifier for row
unit_status	varchar2(2)	varchar(2)	no		Unit's Current Status. The current status of the unit as it is defined in the parameter data. For example, "AV" for "available on radio", "ER" for "enroute", and so on.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
firelinkunit_cdtsudts	cdts, udts		no	no	
firelinkunit_cdtsunid	cdts, unid		no	yes	
firelinkunit_num1	num_1		no	no	
firelinkunit_status_time	status_time		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
firelinkunit_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - fnc_data					
Description	Temporary data used to pass list of mslink values from foreground to background during a fence report command.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 empid	number(10,0)	int	no		ID of employee performing a fence report.
 mslink	number(10,0)	int	no		An mslink value to be used in a fence report
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
fnc_data_primary_key	empid, mslink			primaryKey	yes

 [Top](#)

Table Name - fs_alert					
Description	The fs_alert table contains the alert address, station, bay and alert order information for all alertable units. Each row represents an individual unit at a fire station, at a particular alert order. Each unit id (unid) in cd_units to be alerted should correspond to a station and bay in fs_alert. If the primary address is unreachable, an alert will be sent to the alternate address				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alert_address	varchar2(24)	varchar(24)	no		Contains the address for alertable units. Unique for each station/bay/type/alert_order combination. Format varies for each controller.
 alert_order [default = 1]	number(10,0)	int	no	alert_order in (1,2)	Order in which to alert this address. 1 = Primary, 2 = Alternate
 bay	varchar2(3)	varchar(3)	no		Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table
 station	varchar2(10)	varchar(10)	no		Unit's station
type	varchar2(10)	varchar(10)	no		Type of controller. Current possible values include: CENTRACOM, FRAP, LOCUTION, MODBUS, MOSCAD, PAGER, WESTNET, ZETRON, and ZETRONXML. If type = PAGER, then this must be an alternate alert address (alert_order = 2)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
fs_alert_pk	station, bay, type, alert_order			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
fs_alert_type_alert_order	Yes	not (type = 'PAGER' and alert_order = 1)		not (type = 'PAGER' and alert_order = 1)	

 [Top](#)

Table Name - fs_reports					
Description	The FS_REPORTS table supports specific dispatch, clear or administrative report formats per station. The FS_REPORTS contains Station, Report_type, ASP_FileName, and XSL_FileName information for each station. Each row represents a valid station that has customized ASP and XSL file info that is used to print a specific report format at fire station.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
asp_filename	varchar2(50)	varchar(50)	no		The custom ASP filename. This file contains the specific ASP format for a fire station.
quantity [default = 1]	number(10,0)	int	no	nonNegativeNumber	This defines how many reports to print for a given station printer.
 report_type	varchar2(1)	varchar(1)	no	report_type in ('A', 'C', 'D')	Type of report - 'D' for dispatch, 'C' for clear, or 'A' for administrative
 station	varchar2(10)	varchar(10)	no		Unit's station ID
xsl_filename	varchar2(50)	varchar(50)	no		The custom XSL filename. This file contains the specific XSL format for a fire station.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
fs_reports_pk	station, report_type			primaryKey	yes

 [Top](#)

Table Name - fs_status					
Description	This table is used to decode the station status messages that are received from the FEP by I/FSA and send ESMD messages. Typically, there are 64 rows (one for each byte of the 64 status flags in the station status message). This table is different for each site.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
status_desc	varchar2(80)	varchar(80)	no		A brief description of the status bit's purpose.
 status_id	number(10,0)	int	no		The bit number of the status flag. This ranges from "1" to "64".
status_message	varchar2(240)	varchar(240)	yes		The message that is sent to ESMD in the event of an error or an advisory. Used to assign priority to the ESMD message. The ranges from "1" to "3".
status_notification_interval	number(10,0)	int	yes		The interval, in seconds, at with the ESMD message is sent. The default is 5.
status_severity_level	number(10,0)	int	yes		1 = general message 2 = advisory message 3 = fatal error message
status_type	number(10,0)	int	yes		Used to determine whether an ESMD message is to be sent. 1 = Normally OPEN (flag is normally open), 2 = Normally Closed (flag is normally 1), 3 = Active, 4 = ManACK (Used for manual acknowledgements from the station), 5 = Radio Communication Failed
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
fs_status_pk	status_id			primaryKey	yes

 [Top](#)

Table Name - gun					
Description	Supplemental table for guns that Informer will use to generate queries.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
caliber	varchar2(5)	varchar(5)	yes		Caliber of gun
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Dts when record was created
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Empid of person creating record
cterm	varchar2(15)	varchar(15)	no		Terminal creating record
curent	varchar2(1)	varchar(1)	no	booleanTOrF	T=record is curent, F=earlier record
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTOrF	T= Do not run auto query against this record. Used by Informer.
dob	varchar2(8)	varchar(8)	yes		Date of birth of gun owner
 eid	number(10,0)	int	no	positiveNumber	Eid of event
info_scope	varchar2(12)	varchar(12)	yes		If not null, creating agency
juris	varchar2(10)	varchar(10)	yes		Jurisdiction
make	varchar2(50)	varchar(50)	yes		Make of gun
model	varchar2(50)	varchar(50)	yes		Model of gun
nme	varchar2(100)	varchar(100)	yes		Name of gun owner
oln	varchar2(50)	varchar(50)	yes		Operator license number of gun owner
remarks	varchar2(20)	varchar(20)	yes		Remarks
 rev_num	number(10,0)	int	no	positiveNumber	Revision number
 row_num	number(10,0)	int	no		Row number
serialnum	varchar2(50)	varchar(50)	yes		Serial number of gun
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	DTS when record expires
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Dts of when record was updated
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Dts of when record was updated
unid	varchar2(10)	varchar(10)	yes		Unit id of officer creating supp info record
updt_flag	varchar2(15)	varchar(15)	no		Update flag
upers	number(10,0)	int	yes	nonNegativeNumber	Empid of person updating record
uterm	varchar2(15)	varchar(15)	yes		Terminal updating record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
gun_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
gun_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
gun_primary_key	eid, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - help_usage_log					
Description	Logs the usage of F1 Help. An entry is written every time a user presses the F1 key in Dispatcher to launch the Help. This information can help identify which users need additional training. This table is only populated if the LogUserHelpUsage parameter in the cad GeneralDetails is set to Y. Added for CR 1-4UN4Y3				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date and time when the user clicked the F1 key

cpers	number(10,0)	int	no	nonNegativeNumber	Employee ID. This is the employee who pressed the F1 Key.
cterm	varchar2(15)	varchar(15)	no		Terminal on which the user was running Dispatcher.
help_topic	varchar2(256)	varchar(256)	no		This column contains the help topic's HTML file name. The help topic corresponds to the CAD command for which the user requested Help.
 unique_id	raw(16)	varbinary(16)	no		Unique id to uniquely identify each row.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
help_usage_log_cdt	cdts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
help_usage_log_pk	unique_id		primaryKey		yes

 [Top](#)

Table Name - highlight_keyword						
Description		These strings are used for highlighting words on the Informer and Mobile for Pulbic Safety clients. Added for CR 1-4VXIEM				
Copy Type		ALL_WITH_CHECK				
Columns						
Column Name		Oracle Type	Sql Server Type	NULL	Constraint	Description
 text		varchar2(80)	varchar(80)	no		The string to highlight
Key Constraints						
Constraint Name		Columns			Constraint Type	Sql Server Clustered
highlight_keyword_pk		text			primaryKey	yes

 [Top](#)

Table Name - hit_det_tst_not					
Description	Informer hit detect test notification table				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL/Constraint	Description	
 notify_id	number(10,0)	int	no	Notification id in hit_detect_not table	
 test_set_id	number(10,0)	int	no	Test set id number in hit_detect_test table	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
hit_det_tst_not_pk	notify_id, test_set_id			primaryKey	no

 [Top](#)

Table Name - hit_detect_not					
Description	Informer hit detection notification table. Informer server loads all the data in the hit_detect tables into memory at start up. When the server gets a response from an external database and the registry indicates that hit detection is on, the server code searches the response for the string specified in hit_detect_test.search_tag. If the string comparison succeeds then Informer flags the response as a hit and delivers the hit based on the message_delivery specified. The search_type column supports differentiating the type of hit.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
delivery_condition	number(10,0)	int	no	delivery_condition in (0,1,2)	Delivery condition based on query origin. 0=always deliver, 1=deliver only if query originated from MDT, 2=deliver only if query originated from CAD/Informer. This column can be used for all message delivery types.
esmd_priority	number(10,0)	int	yes		ESMD message priority. This column is only used if the message delivery type is ESMD.
hit_message	varchar2(240)	varchar(240)	no		If set to ***HIT and msg delivery is 5, then msg will be in red on Informer client. Can be anything for other delivery settings. This column can be used for all message delivery types.
hit_message_dest	varchar2(80)	varchar(80)	yes		Can be node, agency, dgroup- it depends on the message delivery. This column can be used for all message delivery types.
message_delivery	number(10,0)	int	no	message_delivery in (0,1,2,3,4,5)	Message delivery type. 0=banner,1=ESMD,2=Send Message, 3=Listener Packet, 4=Event Remarks, 5=Informer Broadcast.
 notify_id	number(10,0)	int	no		Notification id number - UNIQUE
search_type [default = 0]	number(10,0)	int	no	search_type in (0,1,2)	Type of response, based on search string specified in hit_detect_test.search_tag. 0 (Hit), 1 (Error/Alert), 2 (Admin). This column is currently used for the broadcast delivery type
send_message_crit	number(10,0)	int	yes	send_message_crit in (0,1)	Send Message critical setting. 1=Critical, 0 or NULL is not critical. This column is only used if the message deliver type is Send Message.
send_message_prior	varchar2(20)	varchar(20)	yes		Send message priority. This column is only used if the message deliver type is Send Message.
send_message_subj	varchar2(80)	varchar(80)	yes		Send message subject. This column is only used if the message deliver type is Send Message.
send_message_type	number(10,0)	int	yes	send_message_type in (0,1,2)	Used for delivery type of Send Message: 0=person, 1=group, 2=terminal or nodename. This column is only used if the message deliver type is Send Message.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
hit_detect_not_pk	notify_id			primaryKey	yes

 [Top](#)

Table Name - hit_detect_test					
Description	Informer hit detection test table				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
column_number	number(10,0)	int	yes		Column to search for in response file. NULL searches all columns
line_number	number(10,0)	int	yes		Line number in resonse to search for. If NULL, search all lines
search_tag	varchar2(80)	varchar(80)	no		String to search for in Informer response
test_set_id	number(10,0)	int	no		Test set id number used to specify test combinations
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
hit_detect_test_pk	unique_id			primaryKey	no
hit_detect_test_uk	search_tag, column_number, line_number			uniqueKey	yes

 [Top](#)

Table Name - hydrt_a					
Description	This table is used to store information about fire hydrants or any other static equipment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
esz	number(10,0)	int	yes		Emergency Service Zone. This column contains the esz of the hydrant.

fea_mslink	number(10,0)	int	yes		Feature Map Link. This is the linkage to the street segment of the hydrant.
msg	varchar2(80)	varchar(80)	yes		Message. This column defines information about the hydrant (for example, the last service date).
 mslink	number(10,0)	int	no		Map Link. This column allows the placement of a special symbol in the map to designate a hydrant. The symbol may be graphically selected to review this information.
st_num	varchar2(15)	varchar(15)	yes		Street Number. The street number of the hydrant.
symnum	varchar2(30)	varchar(30)	yes		Symbol number of symbol (from resource) used to display hydrant locations on the map
x_coord	number(10,0)	int	yes		X-coordinate.
y_coord	number(10,0)	int	yes		Y-coordinate.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
hydrt_a_esz	esz		no	no	
hydrt_a_fea_mslink	fea_mslink		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
hydrt_a_primary_key	mslink		primaryKey		yes

 [Top](#)

Table Name - hydrt_b					
Description	This table is used to store information about fire hydrants or any other static equipment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
esz	number(10,0)	int	yes		Emergency Service Zone. This column contains the esz of the hydrant.
fea_mslink	number(10,0)	int	yes		Feature Map Link. This is the linkage to the street segment of the hydrant.
msg	varchar2(80)	varchar(80)	yes		Message. This column defines information about the hydrant (for example, the last service date).
 mslink	number(10,0)	int	no		Map Link. This column allows the placement of a special symbol in the map to designate a hydrant. The symbol may be graphically selected to review this information.
st_num	varchar2(15)	varchar(15)	yes		Street Number. The street number of the hydrant.
symnum	varchar2(30)	varchar(30)	yes		Symbol number of symbol (from resource) used to display hydrant locations on the map
x_coord	number(10,0)	int	yes		X-coordinate.
y_coord	number(10,0)	int	yes		Y-coordinate.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
hydrt_b_esz	esz		no	no	
hydrt_b_fea_mslink	fea_mslink		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
hydrt_b_primary_key	mslink		primary/Key		yes

 [Top](#)

Table Name - incident_tracking					
Description	The incident_tracking table contains incident command state information which is related to the event and is added using the Incident Command Tracking form and is displayed on the Event Supplement Form in I/CAD.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the personnel identification number of the person who created the record.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The nodename of the terminal from which the record was created.
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Current Record Indicator. The current flag contains a (T) if this is the most recent version of the record, an (F) if it is an older version.
 eid	number(10,0)	int	no	positiveNumber	Event Indentification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the incident state.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the property information will be displayed.
set_name	varchar2(50)	varchar(50)	yes		Set Name. This column contains the name that describes the set of incident states.
state_desc	varchar2(200)	varchar(200)	yes		State Description. This column contains a description of the incident state.
state_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/Time Stamp. This column contains the date/time (yyyymmddhhmmss) at which state was achieved.
state_sec	number(19,0)	bigint	yes		Time stamp at which state was achieved, stored in epoch seconds
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
timer_value	float(126)	float(53)	yes		Timer Value. This column stores the value of the timer in minutes.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated the record.
upers	number(10,0)	int	yes	nonNegativeNumber	Updating Person. The ID of the person updating the event.
user_gen	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates if the record was generated by the user or the system. (T) if this record was generated by the user (state button click), or an (F) if it was generated by the system (timer expired or dialog closed with active timer).
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. The terminal from which the record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
incident_tracking_cdts2udts2	Oracle: string to_datetimeoffset(cdts), string to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
incident_tracking_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
incident_tracking_primary_key	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - infgroup					

Description	This table contains I/INFORMER configuration data. This table defines the group attributes for each group id; the members of the group are defined in the infgroup_member table. A group may be specified in the infori.fallbackgroupid column. If a group is designated as a fallback group, then in situations where the Informer server cannot deliver a response to a client, the Informer server will send the response to the members (nodes and/or printers) of the fallback group. Previously, the fallback destinations were listed in the registry on the Informer server machine.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
description	varchar2(32)	varchar(32)	yes		Description for the group.
groupid	varchar2(15)	varchar(15)	no		Group id. A group may be designated as the fallback recipient for Informer responses.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infgroup_pk	groupid			primaryKey	yes

[Top](#)

Table Name - infgroup_member					
Description	This table contains I/INFORMER configuration data. This table defines the group members. Nodes and printers can be defined as group members. A group may be specified as a fallback group in infori.fallbackgroupid.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 groupid	varchar2(15)	varchar(15)	no		Group id.
 nodename	varchar2(15)	varchar(15)	no		If printerName is "NONE", this is the destination nodename. If printerName is not "NONE", this is the nodename associated with the printer.
 printername [default = 'NONE']	varchar2(80)	varchar(80)	no		The printer name. This is the printer to which the message should be printed.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infgroup_member_pk	groupid, nodename, printername			primaryKey	yes

[Top](#)

Table Name - infmktetable					
Description	This table is used by Informer to configure queries that are formatted using a fixed position, blank padded query to a message switch. Could also be used to format input that is fixed position (i.e. does not contain mnemonics on each field).				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
dtype	varchar2(2)	varchar(2)	yes		Type of fld - A for Ascii, AN, AS
fldpos	number(10,0)	int	yes		Position of field on input - when using fixed position input without mnemonics.
mdesc	varchar2(50)	varchar(50)	yes		Optional field description
mke	varchar2(5)	varchar(5)	no		The mnemonic of the query. Ex - DQ, QW, QV
mne	varchar2(6)	varchar(6)	yes		Field mnemonic label. When unlabeled fields are input, this mnemonic is prepended to the field in the Query formatter: NAM/<name value>.
moffset	number(10,0)	int	yes		Used if output fields must begin at a specific place.
msize	number(10,0)	int	yes		Maximum OUTPUT field size
outpos	number(10,0)	int	yes		Used if needed to position fields in a specific order. Default is in order of input
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Unique identifier
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
infmktetable_mke	mke		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
infmktetable_pk	unique_id		primaryKey		no

[Top](#)

Table Name - infori					
Description	This table contains I/INFORMER configuration data at a workstation (nodename) and/or mobile unit level.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
altid	varchar2(15)	varchar(15)	no		Terminal identifier or mnemonic assigned by the state.
bcastmsg [default = 0]	number(10,0)	int	no	booleanNumber1Or0	If set to 1, then admin messages that are to be 'broadcast' will be received by this node.
dtidx [default = 0]	number(10,0)	int	no	dtidx between 0 and 7	Used to define the transport of responses to the appropriate client. Defaults are 0 = Informer, 1 = MobileTCOMS, 2 = Informer Public API, 3 = MPSPAN_TRANS, 4 = MPSPAN, 5 = MobileResponder. MPSPAN_TRANS is used for older versions of MPS and is used during the transition of MPS to the latest version installed at site.
fallbackgroupid	varchar2(15)	varchar(15)	yes		The fallback group id. If the Informer server cannot deliver a response to the client, then the Informer server will send the response to the members (nodes and/or printers) of this fallback group.
hit_det_disable [default = 1]	number(10,0)	int	no	booleanNumber1Or0	If set to 0, then responses from msg switches bound for this node will be checked for hit detection. If set to 1, then responses will not be checked for hits.
 id	varchar2(15)	varchar(15)	no		Terminal name, unit id, or vehicle id
 id_type	number(5,0)	smallint	no	id_type between -1 and 2	Indicates if id is a terminal name, unit id, or a vehicle id. 0 = terminal, 1 = unit id, 2 = vehicle id, -1 = unknown
ori	varchar2(9)	varchar(9)	no		State assigned value used to identify a workstation, user, or agency.
switchnodedestination	varchar2(32)	varchar(32)	yes		If SwitchNodeDestination is set, then Informer will route messages from the remote database based upon the id or altid to this 'Node Destination' as defined in the switch file. Used by ILeads when routing is not supported from a message switch for proper delivery of messages.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infori_pk	id, id_type			primaryKey	yes

[Top](#)

Table Name - infsec					
Description	Informer security table				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 cmdtype	varchar2(15)	varchar(15)	no		Query MKE
 seclev	number(10,0)	int	no		Security Level
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infsec_pk	cmdtype, seclev			primaryKey	yes

 [Top](#)

Table Name - infsignon					
Description	This table stores information about clients who are currently signed on to Informer server. Informer server uses this information to reconnect clients whenever the Informer server restarts. Added for CR 1-4XEJC9				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
empid	number(10,0)	int	no	nonNegativeNumber	Employee that is running Informer client.
logon_sec	number(19,0)	bigint	no	positiveNumber	Time at which the Informer client signed on to the Informer server. This time is recorded in epoch seconds.
 nodename	varchar2(15)	varchar(15)	no		Node on which the Informer client is running
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infsignon_pk	nodename			primaryKey	yes
infsignon_uk	empid			uniqueKey	no

 [Top](#)

Table Name - infuser					
Description	Informer table used to store the remote DB user information.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 empid	number(10,0)	int	no	nonNegativeNumber	Cad employee id that is logging into the remote database msg switch.
password	varchar2(128)	varchar(128)	yes		Password used when logging into the remote database message switch
password_alg_id	varchar2(128)	varchar(128)	yes		Password encryption algorithm identifier or 'Legacy' if not using the new encryption mechanism
 remotedb	varchar2(32)	varchar(32)	no		Registry key name of the remote database message switch
userid	varchar2(32)	varchar(32)	no		User id of cad empid that is logging into the remote database message switch
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infuser_pk	empid, remotedb			primaryKey	yes
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
infuser_password_alg_ck		Yes	(password is null and password_alg_id is null) or (password is not null and password_alg_id is not null)		(password is null and password_alg_id is null) or (password is not null and password_alg_id is not null)

 [Top](#)

Table Name - infxmlparse					
Description	Informer table used to parse responses into XML				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
data_mask	varchar2(100)	varchar(100)	yes		Describes the handling of the data following the target - Targeted Reformatting only.
length	number(10,0)	int	yes		Length of the value found at the specified position - Positional reformatting only.
node_action	varchar2(100)	varchar(100)	yes		Used to either create a new node in the XML file or to cause the tagged values to be placed in a specified node in the XML file.
node_level	number(10,0)	int	yes		Numeric level of the node to be created or be set as the current node
position	number(10,0)	int	yes		Position in response of the value to be extracted - Positional reformatting only
set_name	varchar2(100)	varchar(100)	no		Name of parsing set to which this entry belongs
tag	varchar2(25)	varchar(25)	no		XML tag to place around the data
tag_type	varchar2(25)	varchar(25)	yes		Flags that data requires special formatting
target	varchar2(100)	varchar(100)	yes		For Targeted reformatting, it specifies the textual search target with data to follow. Targets can be used in conjunction with node_action and node_level columns to specify that either a new node is to be created or to become the current node (in the XML file). When used in this manner, the data after the tag is ignored.
target_type	number(10,0)	int	yes		Target type
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
infxmlparse_set_name	set_name		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
infxmlparse_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - infxmlparseset					
Description	Informer table used to parse responses into XML				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
scheme_name	varchar2(25)	varchar(25)	no		Scheme name as specified in the INFxmlscheme table
set_name	varchar2(100)	varchar(100)	no		Set name in the INFXMLParse table
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
infxmlparseset_set_name_scheme	set_name, scheme_name		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infxmlparseset_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - infxmlscheme					
---------------------------	--	--	--	--	--

Description	Informer table used to parse responses into XML				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
comments	varchar2(2000)	varchar(2000)	yes		Specifies optional comments that can be added to the XML file
default_tag	varchar2(15)	varchar(15)	yes		Used for targeted reformatting and to tag text that either had no target or fell outside the range of the specified targets
new_line_nodes	number(10,0)	int	yes		If set to 1, causes the parser to add new line nodes to the XML file for each line being parsed in the response file. This applies to targeted reformatting only
parse_type	number(10,0)	int	no	parse_type in (1,2)	1 = Targeted reformatting. 2 = Positional reformatting
scheme_name	varchar2(25)	varchar(25)	no		Name of scheme for reformatting and root node in XML file
title	varchar2(80)	varchar(80)	yes		Optional text marked by TITLE tags in XML file. Required for responses sent to I/Mobile
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infxmlscheme_pk	unique_id			primaryKey	no
infxmlscheme_uk	scheme_name			uniqueKey	yes

 [Top](#)

Table Name - infxmlsetscheme					
Description	Informer table used to parse responses into XML				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
remotetype	varchar2(25)	varchar(25)	yes		Can be used if multiple remotes and route codes are available
scheme_name	varchar2(25)	varchar(25)	no		Scheme name as specified in the INFxmlscheme table
searchend	number(10,0)	int	yes		Byte (character) position in response to stop searching
searchstart	number(10,0)	int	yes		Byte position in response to start searching
searchstring	varchar2(25)	varchar(25)	no		Unique string in response
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
infxmlsetscheme_scheme_name	scheme_name		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
infxmlsetscheme_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - inter_a					
Description	This table contains information-related data used for location verification. The information in this table is generated by map data.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
esz	number(10,0)	int	yes		Emergency Service Zone. This column contains the ESZ value for the intersection.
loc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4	varchar2(5)	varchar(5)	yes		Generic location field
lv_area	varchar2(40)	varchar(40)	yes		Area Identifier. This column contains the assigned area of the intersection.
 mslink	number(10,0)	int	no		Map Link. This column contains the link to Map graphics elements of the segment.
mun	varchar2(40)	varchar(40)	yes		Municipality. The municipality containing the intersection.
nodeid	number(10,0)	int	yes		Node ID. The identification number of the node at the intersection of the appropriate street segments.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
inter_a_nodeid	nodeid		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
inter_a_primary_key	mslink		primaryKey		yes

 [Top](#)

Table Name - inter_b					
Description	This table contains information-related data used for location verification. The information in this table is generated by map data.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
esz	number(10,0)	int	yes		Emergency Service Zone. This column contains the ESZ value for the intersection.
loc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4	varchar2(5)	varchar(5)	yes		Generic location field
lv_area	varchar2(40)	varchar(40)	yes		Area Identifier. This column contains the assigned area of the intersection.
 mslink	number(10,0)	int	no		Map Link. This column contains the link to Map graphics elements of the segment.
mun	varchar2(40)	varchar(40)	yes		Municipality. The municipality containing the intersection.
nodeid	number(10,0)	int	yes		Node ID. The identification number of the node at the intersection of the appropriate street segments.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
inter_b_nodeid	nodeid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
inter_b_primary_key	mslink			primaryKey	yes

 [Top](#)

Table Name - inter_str_a					
Description	This table contains data generated by the UPDATE INTERSECTION command. It contains the nodes of the streets that converge at the intersection.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description

 node_id	number(10,0)	int	no		Node ID. This column contains the node ID of the intersection.
 pri_text_id	number(10,0)	int	no		The text_id of the primary street name st_cd record.
 text_id	number(10,0)	int	no		Text ID. This column contains the text ID of the streets that converge at the intersection.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
inter_str_a_text_id	text_id		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
inter_str_a_primary key	node_id, pri_text_id, text_id		primaryKey		yes

 [Top](#)

Table Name - inter_str_b					
Description	This table contains data generated by the UPDATE INTERSECTION command. It contains the nodes of the streets that converge at the intersection.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 node_id	number(10,0)	int	no		Node ID. This column contains the node ID of the intersection.
 pri_text_id	number(10,0)	int	no		The text_id of the primary street name st_cd record.
 text_id	number(10,0)	int	no		Text ID. This column contains the text ID of the streets that converge at the intersection.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
inter_str_b_text_id	text_id		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
inter_str_b_primary_key	node_id, pri_text_id, text_id		primaryKey		yes

 [Top](#)

Table Name - iqa_log					
Description	The iqa_log table contains audit logs of I/QA protocol sessions.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
action	varchar2(20)	varchar(20)	no		The type of action taken at this step.
ats	varchar2(16)	varchar(16)	yes		The time at which the step was performed.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date-time stamp of when the record was added to the database
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created
cpers	number(10,0)	int	no	nonNegativeNumber	ID number of creating person
cterm	varchar2(15)	varchar(15)	no		Creation terminal
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTOrF	Status of this record. T when current, F when old.
 eid	number(10,0)	int	no	positiveNumber	ID of event with which this record is associated
info_scope	varchar2(12)	varchar(12)	yes		Indicates/limits availability of record contents to particular agencies.
rev_num	number(10,0)	int	no	positiveNumber	The revision number for the row.
 row_num	number(10,0)	int	no		Sequence number of this step of the protocol for this event.
rslt	varchar2(50)	varchar(50)	yes		The result of the step - may be the answer to the question, or DONE or SKIPPED, etc.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
text	varchar2(240)	varchar(240)	yes		The text of the step. Either the text of the question, instructions, or command.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update date/time stamp
updt_flag [default = 'NULLTERM']	varchar2(15)	varchar(15)	no		Used by CAD to temporarily lock this record for update.
upers	number(10,0)	int	yes	nonNegativeNumber	ID of updating person.
uterm	varchar2(15)	varchar(15)	yes		Updating terminal.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
iqa_log_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
iqa_log_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
iqa_log_primary_key	eid, row_num		primaryKey		yes

 [Top](#)

Table Name - iragencydgroup					
Description	This table defines a list of agency and/or agency_dgroup pairs which comprise an agencyDgroup set. This table is used by I/Radio				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
evalue	varchar2(32)	varchar(32)	no		Either the agency or agency_dgroup
 objectid	varchar2(32)	varchar(32)	no		AgencyDgroupSet name
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
iragencydgroup_pk	objectid			primaryKey	yes

 [Top](#)

Table Name - ircadobject					
Description	The ircadobject table defines the relationship between radio system talkgroups/talkchannels and I/CAD entities such as units, events, etc. This table is used by I/Radio.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
grpId	varchar2(32)	varchar(32)	yes		String representing radio system talkchannel/talkgroup
managemembers [default = 'F']	varchar2(1)	varchar(1)	no	booleanTORF	Defines whether the I/Radio server should automatically manage the talkgroup membership as the CAD object members change
 objectid	varchar2(32)	varchar(32)	no		CAD Object name. Depending on the otype, this is the name of the unit, event etc.
otype	varchar2(32)	varchar(32)	no		CAD object type
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered

ircadobject_pk	objectid	primaryKey	yes
----------------	----------	------------	-----

 [Top](#)

Table Name - irmanual					
Description	This table defines additional radioid which should be included in the talkgroup member in addition to those derived by the normal CADObject relationship. For example, additional radios which aren't associated with a logged on CAD unit. This table is used by I/Radio.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 objectid	varchar2(32)	varchar(32)	no		CAD object name
 rdioid	varchar2(32)	varchar(32)	no		String representation of the radio Identity
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
irmanual_pk	objectid, rdioid			primaryKey	yes

 [Top](#)

Table Name - irtcsgruop					
Description	This table defines a snapshot of the TCS talkgroup definitions. If the TCS information is unavailable, this information is used to seed the TCS client. This table is used by I/Radio				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
mnemonic	varchar2(32)	varchar(32)	no		TCS talkgroup for display
 name	varchar2(32)	varchar(32)	no		TCS talkgroup name
ssi	number(10,0)	int	no		TCS internal talkgroup identity
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
irtcsgruop_pk	name			primaryKey	yes

 [Top](#)

Table Name - iruser					
Description	This table defines the mapping between a CAD empld and the TCS login credentials. This table is used by I/Radio.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 employeeid	number(10,0)	int	no	nonNegativeNumber	CAD employee id (empld)
rpassword	varchar2(32)	varchar(32)	no		TCS password
rusername	varchar2(32)	varchar(32)	no		TCS username
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
iruser_pk	employeeid			primaryKey	yes

 [Top](#)

Table Name - linemap					
Description	Defines a mapping of node name to their default line name. This table is used mainly by CAD Interface applications.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
configuration	number(10,0)	int	no		The configuration id of server.
name	varchar2(80)	varchar(80)	no		The PBX assigned line name. It is not necessary to enter Primary VDNs or VDN queue pairs in the linemap table.
term	varchar2(17)	varchar(17)	no		The terminal name (position name). For queues, this should be the Keyword "Server".
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies a row.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
linemap_configuration	configuration		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
linemap_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - lineup					
Description	The lineup table defines the units, equipment, and personnel which are available per workshift. All units, vehicles and personnel must be defined in CADDDBM prior to using them in a lineup.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID. Defines the agency to which the units/ personnel belong.
bay	varchar2(3)	varchar(3)	yes		Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table
carid	varchar2(12)	varchar(12)	yes		Car Identification. This column defines the agency vehicle identification.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date. This column is the date/time stamp (yyyymmddhhmmss) in which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column contains the personnel identification number (empid) of the person who created the record.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The nodename of the terminal at which the record was created.
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Flag used to reflect whether the lineup is active. (T) represents active lineup, (F) represents an inactive lineup
delay_value [default = 0]	number(10,0)	int	no		This value will be added to the unit's time/distance when recommending units by the road network
descript	varchar2(80)	varchar(80)	yes		Description. This column contains a description of the lineup.
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group. Defines the dispatch group which is responsible for this unit in the lineup.
ext_unitattr [default = '00']	raw(32)	varbinary(32)	no	lengthb(ext_unitattr) = 64	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list. The value must be 32 bytes (64 bytes as a hex string).
lev3	varchar2(7)	varchar(7)	yes		Level 3 Area. This column defines the current beat assignment.

 lineup_name	varchar2(30)	varchar(30)	no		Lineup Name. This column defines the name of the lineup. The names should contain a definition of time and group. However, this is not a requisite.
loc_comm	varchar2(40)	varchar(40)	yes		Location Comment. The name of the permanent deployment location. This may be displayed in the Status Monitor in I/CAD when a unit is available.
loc_x [default = 0.0]	float(126)	float(53)	no		Location X-coordinate. Defines the x-coordinate in map units of the permanent deployment location. This is the location on the map where the unit will be displayed when available for dispatch.
loc_y [default = 0.0]	float(126)	float(53)	no		Location Y-coordinate. Defines the y-coordinate in map units of the permanent deployment location. This is the location on the map where the unit will be displayed when it is available for dispatch.
max_ht [default = 0]	number(10,0)	int	no	nonNegativeNumber	Maximum Height. Defines the maximum height of the vehicle. Will be used with the router in conjunction with street restrictions.
max_wd [default = 0]	number(10,0)	int	no	nonNegativeNumber	Maximum Width. Defines the maximum width of the vehicle. Will be used with the router in conjunction with street restrictions.
max_wt [default = 0]	number(10,0)	int	no	nonNegativeNumber	Maximum Weight. Defines the maximum weight of the vehicle. Will be used with the router in conjunction with street restrictions.
page_id	varchar2(12)	varchar(12)	yes		The unit's pager id or pager group id. This value is carried forward at log on time.
page_unit_person [default = 0]	number(5,0)	smallint	no	page_unit_person in (0,1,2)	0 - Page unit only 1 - Page Employee only 2 - Page both unit & Employee
rec_num	number(5,0)	smallint	yes		Record Number. Unique identifier for each record in the table. Used by Skill and Roster when creating lineups.
resp_stop [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Response Stop Flag. Flag to indicate if associated with a late run. (Y)-- associated with a late run, (N)-- not associated with a late run.
shared_crew [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Indicates whether or not this unit is a shared crew unit. Y = unit is a shared crew unit. N = unit is not a shared crew unit.
shift_duration [default = 0]	number(10,0)	int	no	Shift_duration between 0 and 360000	Scheduled shift length. Note that this value is in seconds, whereas the "Shift Duration" field on the CADDDBM Lineup dialog is in hours.
shift_start	varchar2(16)	varchar(16)	yes	ipsTimestamp	Scheduled shift start.
sp_detail	varchar2(80)	varchar(80)	yes		Special Detail. Defines any special detail that is assigned.
station	varchar2(10)	varchar(10)	yes		Station Name. This column contains the currently assigned station name.
symnum [default = 0]	number(10,0)	int	no	Symnum between 0 and 255	Symbol number. The symbol number is used to select a bitmap from the resource file. The bitmap is displayed on the map as the unit's symbol.
type_avail [default = 0]	number(5,0)	smallint	no		Default availability status. This will be the unit's status when it is cleared from an event, returned to service, or another change occurs that makes it available. The possible values for this column come from the cad UnitStatus parameter list.
ucust1	varchar2(50)	varchar(50)	yes		Unit custom column 1
ucust2	varchar2(50)	varchar(50)	yes		Unit custom column 2
ucust3	varchar2(50)	varchar(50)	yes		Unit custom column 3
ucust4	varchar2(50)	varchar(50)	yes		Unit custom column 4
 unid	varchar2(10)	varchar(10)	no		Unit ID. This column contains the unit identification, usually the call letters.
unit_status [default = 0]	number(5,0)	smallint	no		The unit's status when it is first logged on. The possible values for this column come from the cad UnitStatus parameter list.
unityp	varchar2(6)	varchar(6)	yes		Unit Type. Defines the type of unit (for example: Patrol, Pumper, and ALS).
vflag	varchar2(1)	varchar(1)	yes	booleanYOrN	MDT Voice Flag. This field defines whether the MDT unit is available on voice (radio). Y = Yes, N = No.
work_shift	varchar2(5)	varchar(5)	yes		Work Shift. When creating the lineup, CADDDBM considers shift and only selects the employees who are scheduled to work that shift.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
lineup_cds	cdts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type	Sql Server Clustered	
lineup_primary_key	lineup_name, unid		primaryKey	yes	
Triggers					
Trigger Name	Required	Trigger Type		Description	
lineup_trig	Yes	Custom		Populates valid_unit with new unid values	

 [Top](#)

Table Name - lineup_crews					
Description	This table contains crew IDs associated with crews added to lineups.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID.
 crew_id	varchar2(30)	varchar(30)	no		Crew ID.
 lineup_name	varchar2(30)	varchar(30)	no		Lineup name.
station	varchar2(10)	varchar(10)	no		Station ID.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
lineup_crews_pk	lineup_name, crew_id			primaryKey	yes

 [Top](#)

Table Name - lineup_device						
Description	Stores devices used by units, vehicles and personnel in a lineup. CR 1-6PGD42: PLT					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
description	varchar2(50)	varchar(50)	yes		Description	
device_alias	varchar2(20)	varchar(20)	yes		User-friendly alias name for device	
 device_id	varchar2(40)	varchar(40)	no		Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system	
 device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.	
 device_type	number(5,0)	smallint	no	device_type between 0 and 5	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT	

empid	number(10,0)	int	yes	nonNegativeNumber	If owner = 1, this column has the employee that owns the device. Links to lineup_persl.empid
gps_protocol [default = 0]	number(5,0)	smallint	no	nonNegativeNumber	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols
is_trackable	number(5,0)	smallint	no	booleanNumber1Or0	Is device trackable? 0 = False, 1 = True
 lineup_name	varchar2(30)	varchar(30)	no		Lineup name
owner	number(5,0)	smallint	no	owner between 0 and 1	Owner. 0 = unit, 1 = employee
tdevice_for_emp	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False
tdevice_for_unit	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False
 unid	varchar2(10)	varchar(10)	no		Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
lineup_device_owner	owner		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
lineup_device_pk	lineup_name, unid, device_id, device_type, device_sub_type			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
lineup_device_owner2_ck	Yes	(owner = 0 and empid is null) or (owner = 1 and empid is not null)		(owner = 0 and empid is null) or (owner = 1 and empid is not null)	
lineup_device_smt_id_ck	Yes	(device_type not in (5)) or (regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$'))		(device_type not in (5)) or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)	
lineup_device_tdevice_ck	Yes	(is_trackable = 1 or (tdevice_for_emp = 0 and tdevice_for_unit = 0)) and (owner = 1 or tdevice_for_emp = 0)		(is_trackable = 1 or (tdevice_for_emp = 0 and tdevice_for_unit = 0)) and (owner = 1 or tdevice_for_emp = 0)	
Triggers					
Trigger Name	Required	Trigger Type		Description	
lineup_device_trig2	Yes	Custom		Populates valid_device with new device id, device type, device sub-type values	

 [Top](#)

Table Name - lineup_equip					
Description	The equipment for a unit in a given lineup				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 equip	varchar2(10)	varchar(10)	no		The equipment
 lineup_name	varchar2(30)	varchar(30)	no		Lineup name
num_equip	number(10,0)	int	no	positiveNumber	Number of pieces of this equipment
 unid	varchar2(10)	varchar(10)	no		The unit identifier
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
lineup_equip_primary_key	lineup_name, unid, equip			primaryKey	yes

 [Top](#)

Table Name - lineup_persl					
Description	The employees associated with a unit for a given lineup.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 empid	number(10,0)	int	no	nonNegativeNumber	Employee id
 lineup_name	varchar2(30)	varchar(30)	no		The lineup name
primary_empid [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Primary employee on unit. T = True, F = False
 unid	varchar2(10)	varchar(10)	no		The unit identifier
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
lineup_persl_primary key	lineup_name, unid, empid			primaryKey	yes

 [Top](#)

Table Name - loi_data					
Description	This table contains information about the type of data and where it is stored for the Location of Interest function in I/CAD.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Contains the date/time of when the record was created.
curent	varchar2(1)	varchar(1)	no	booleanTOrF	T/F, indicates if row is active or deleted
db_config	varchar2(30)	varchar(30)	yes		The source database configuration name
dtype	varchar2(1)	varchar(1)	no		Data Type of LOI response. The valid values are defined in the CAD SearchInfo parameter table.
edts	varchar2(16)	varchar(16)	no	ipsTimestamp	Associated data creation date/time stamp.
eid	number(10,0)	int	no		The employee or event id for which the search is conducted, note that employee ids are represented as negative numbers to distinguish them from event ids
idx	number(10,0)	int	no		Contains the event id of a recent event or special situation mlsink or an Informer rec_num.
loc	varchar2(80)	varchar(80)	yes		Location. Location found in the location of interest search.
loi_schema	varchar2(1)	varchar(1)	yes	loi_schema in ('C', 'R')	Location of Interest schema. Indicates whether the schema for loi data is (C)ad or (R)ms.
num_1	varchar2(12)	varchar(12)	yes		Agency Event Number. Contains the number corresponding to the events which occurred at the same location.
priority	varchar2(1)	varchar(1)	yes		Contains the priority value assigned to the location of interest data.
remarks	varchar2(20)	varchar(20)	yes		This column is retrieved from the remarks column in the special situation table.
row_num	number(10,0)	int	yes		This holds the row number associated with a supplemental table specified in the loi search.
source	varchar2(16)	varchar(16)	yes		Defines the source event type or special situation type, or Informer.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time stamp.
 unique_id	raw(16)	varbinary(16)	no		A binary value that uniquely identifies each row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
loi_data_cdtsudts	cdts, udts		no	no	
loi_data_eidcurent	eid, curent		no	yes	
Key Constraints					

Constraint Name	Columns	Constraint Type	Sql Server Clustered
loi_data_primary_key	unique_id	primaryKey	no

[Top](#)

Table Name - loi_rows						
Description	Shows what Informer responses have been shown in a LOI report for an event.					
Copy Type	INSERT					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 app_config_name	varchar2(24)	varchar(24)	no		Name of configuration being used by interface application that issued LOI report request	
 app_name	varchar2(24)	varchar(24)	no		Name of interface application that issued LOI report request	
 app_nodename	varchar2(15)	varchar(15)	no		Nodename of server system that issued the LOI report request	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp. Contains the date/time (yyyymmddhhmss) of when the record was created.	
 eid	number(10,0)	int	no		The employee or event id for which the search is conducted, note that employee ids are represented as negative numbers to distinguish them from event ids	
 loirow	number(10,0)	int	no		Informer response row id that corresponds to the event.	
Key Constraints						
Constraint Name	Columns			Constraint Type		Sql Server Clustered
loi_rows_primary_key	eid, loirow, app_name, app_config_name, app_nodename			primaryKey		yes

[Top](#)

Table Name - loi_search						
Description	Stores location information needed for Location of Interest (LOI) searches					
Copy Type	UPDATE					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
apt	varchar2(128)	varchar(128)	yes		Apartment number component of the location	
area	varchar2(128)	varchar(128)	yes		Area component of the location	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The timestamp when the record was created	
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Indicates if record is active	
dirpre	varchar2(128)	varchar(128)	yes		Direction prefix component of the location	
dirsuf	varchar2(128)	varchar(128)	yes		Direction suffix component of the location	
feaname	varchar2(240)	varchar(240)	yes		Feature name component (street name) of the location	
featype	varchar2(128)	varchar(128)	yes		Feature type component of the location	
 id	raw(16)	varbinary(16)	no		Guid to uniquely identify row	
loc_fld1	varchar2(128)	varchar(128)	yes		Generic location component of the location	
loc_fld2	varchar2(128)	varchar(128)	yes		Generic location component of the location	
loc_fld3	varchar2(128)	varchar(128)	yes		Generic location component of the location	
loc_fld4	varchar2(128)	varchar(128)	yes		Generic location field	
mun	varchar2(128)	varchar(128)	yes		Municipality component of the location	
no_loi_search	varchar2(1)	varchar(1)	no	booleanTorF	LOI Search Flag from the sp_ad table. If TRUE (T), no LOI search is conducted for events at this location	
null_p_data	varchar2(1)	varchar(1)	no	booleanString1Or0	T if null p_data passed in	
parse_type	number(10,0)	int	no	parse_type in (-1,0,1,2,3,4)	Parse type. Indicates how the location was parsed. -1= unknown, 0= street, 1= intersection, 2= commonplace, 3= alarm, 4= X,Y location.	
search_flag	varchar2(1)	varchar(1)	no	booleanTorF	Special Situation Seach flag from the sp_ad table. If TRUE(T), a Special Situation search is conducted for events at this location.	
stnum	varchar2(128)	varchar(128)	yes		Street number house number) component of the location	
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The timestamp when the record was updated	
x_cord	number(10,0)	int	no		X map coordinate for the location	
xstreet1	varchar2(128)	varchar(128)	yes		Feature name and type of one street which intersects the location	
xstreet2	varchar2(128)	varchar(128)	yes		Feature name and type of one street which intersects the location	
y_cord	number(10,0)	int	no		Y map coordinate for the location	
Indexes						
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause	
loi_search_cdtsudts	cdts, udts		no	no		
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
loi_search_pk	id			primaryKey	yes	

[Top](#)

Table Name - loi_sent						
Description	Determines if LOI Reports have been written for events, and what was written (except for Informer data) in the report so far.					
Copy Type	UPDATE					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 app_config_name	varchar2(24)	varchar(24)	no		Name of configuration being used by interface application that issued LOI report request	
 app_name	varchar2(24)	varchar(24)	no		Name of interface application that issued LOI report request	
 app_nodename	varchar2(15)	varchar(15)	no		Nodename of server system that issued the LOI report request	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp. Contains the date/time (yyyymmddhhmmss) of when the record was created.	
 eid	number(10,0)	int	no		The employee or event id for which the search is conducted, note that employee ids are represented as negative numbers to distinguish them from event ids	
rel_events	varchar2(16)	varchar(16)	yes		Corresponds to the cdts of the last row used in an loi_data query for a specific event. If a new loi report is generated because of new information added to loi_data table, this column is checked to prevent older information from being duplicated.	
spec_sit	varchar2(1)	varchar(1)	no	booleanTOrF	Set to 'T' if special situations data has been written to the LOI report for the event, 'F' otherwise.	
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. Contains the date/time (yyyymmddhhmmss) of when the record was updated.	
written	varchar2(1)	varchar(1)	no	booleanTOrF	Set to 'T' if a LOI report has been written, 'F' if an event is open, but the LOI report has not been done yet.	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
loi_sent_primary_key	eid, app_name, app_config_name, app_nodename			primaryKey	yes	

[Top](#)

Table Name - loi_status						
Description	Holds the status information for location of interest searches corresponding to an employee or event id.					
Copy Type	UPDATE					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp	
curent	varchar2(1)	varchar(1)	no	booleanTOrF	T/F, indicates if the row is active or deleted	

db_config	varchar2(30)	varchar(30)	no		The database configuration fo the search
id	number(10,0)	int	no		The employee or event id for which the search is conducted, note that employee ids are represented as negative numbers to distinguish them from event ids
is_eid	varchar2(1)	varchar(1)	no	booleanString1Or0	0/1 - 0 for employee id, 1 for event id
search_type	varchar2(2)	varchar(2)	no		The type of search being conducted, such as SU (supplemental) or SS (special situation)
search_type_text	varchar2(30)	varchar(30)	no		Search type description
status	varchar2(1)	varchar(1)	no		The status of the search. Defaults are: S= Started, O= Ok (finished successfully), F=Failed, but these defaults can be overridden in the cad LoiStatusTypes parameter list.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
 unique_id	raw(16)	varbinary(16)	no		An arbitrary unique identifier for the row
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
loi_status_cdtstatus	cdts, udts		no	no	
loi_status_idcurrent	id, curent		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
loi_status_primary_key	unique_id		primaryKey		no
Check Constraints					
Constraint Name		Required	Oracle Definition	Sql Server Definition	
loi_status_ck		Yes	id > 0 and is_eid = '1' or id <= 0 and is_eid = '0'	id > 0 and is_eid = '1' or id <= 0 and is_eid = '0'	

 [Top](#)

Table Name - lv_session					
Description	This table stores location verify (LV) choices presented to the user during event creation. When the user enters an address in CAD, CAD may display location verify dialogs, asking the user for more information. CAD stores the address originally submitted by the user, plus the list of location verify addresses offered by CAD. If a user modifies an event's location on the main event information dialog, CAD will record the subsequent LV exchanges as a separate LV session. This table is only populated if you turn on the EnableLVSessionLog parameter in the cad GeneralDetails parameter list. Added for CR1-4HLEEQ.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation timestamp
cpers	number(10,0)	int	no	nonNegativeNumber	Employee id of the person in this location verify session.
cterm	varchar2(15)	varchar(15)	no		Creation terminal
eid	number(10,0)	int	no	positiveNumber	Event id
session_data	clob	varchar(max)	no		Location verify session data. For Intergraph Development use only.
 session_id	raw(16)	varbinary(16)	no		Unique session id
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
lv_session_pk	session_id			primaryKey	yes

 [Top](#)

Table Name - macro_cmds					
Description	Contains user-defined macro scripts containing one or more CAD commands.				
Copy Type	ALL WITH CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency associated with macro, NULL if common to all agencies
 cmd_order	number(5,0)	smallint	no	nonNegativeNumber	Zero-based index of command within macro definition
command	varchar2(500)	varchar(500)	no		CAD command
 name	varchar2(80)	varchar(80)	no		User-defined macro name
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
macro_cmds_primary_key	name, ag_id, cmd_order			primaryKey	yes

 [Top](#)

Table Name - macro_params					
Description	Contains user-defined parameters that are referenced by the macro with the same name and agency ID.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency associated with macro, NULL if common to all agencies
 name	varchar2(80)	varchar(80)	no		User-defined macro name
param_descip	varchar2(80)	varchar(80)	no		User-defined description of macro parameter
 param_order	number(5,0)	smallint	no	nonNegativeNumber	Zero-based index of parameter within macro definition
param_reqd	number(5,0)	smallint	no	booleanNumber1Or0	1 if parameter must be non-blank when macro is executed, 0 if it can be omitted
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
macro_params_primary_key	name, ag_id, param_order			primaryKey	yes

 [Top](#)

Table Name - mailgateway					
Description	This table holds Profile information of all the CAD users who want to receive inbound email from I/Mail. This table can be used by the I/Mail Application				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
empid	number(10,0)	int	no	nonNegativeNumber	Employee ID
profile	varchar2(32)	varchar(32)	no		Profile of the CAD user.
pswr	varchar2(32)	varchar(32)	yes		Password of the CAD user
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Unique identifier
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
mailgateway_empid	empid		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mailgateway_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - majevt_act					
Description	Used to process task action items for Major Event.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date time stamp of the action item been selected and locked in the database.
cpers	number(10,0)	int	no	nonNegativeNumber	User id of the person who selected the action item.
cterm	varchar2(15)	varchar(15)	no		Terminal name of which the item was selected
eid	number(10,0)	int	yes	positiveNumber	Event id of the active major event.
list_id	number(10,0)	int	yes		The list id of which this action item is associated to.
task_action	varchar2(80)	varchar(80)	yes		Task description
task_comment	varchar2(80)	varchar(80)	yes		Comment entered for this task
task_id	varchar2(10)	varchar(10)	yes		Task id associate to the task
task_status	number(10,0)	int	no		Status of this task item (available, hold, closed or selected)
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Major Event task list update date time stamp.
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		
updt_flag	varchar2(15)	varchar(15)	no		Set to NULLTERM if the item is available, otherwise set to the terminal that is currently processing the item.
xdt	varchar2(16)	varchar(16)	yes	ipsTimestamp	Closing date time stamp
xpers	number(10,0)	int	yes	nonNegativeNumber	Closing user id
xterm	varchar2(15)	varchar(15)	yes		Closing terminal
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
majevt_act_eid	eid		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
majevt_act_pk	unique_id			primary/Key	no

 [Top](#)

Table Name - majevt_hst					
Description	Used for Major Event task processing history.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date time stamp of the record been created.
cpers	number(10,0)	int	no	nonNegativeNumber	User id of whom created the record.
cterm	varchar2(15)	varchar(15)	no		Terminal that the record got created.
current	varchar2(1)	varchar(1)	no	booleanTorF	Current flag
eid	number(10,0)	int	no	positiveNumber	Event id of the active major event.
info_scope	varchar2(9)	varchar(9)	yes		This column contains the scope of the supplemental information.
list_id	number(10,0)	int	no		Active list id
rev_num	number(10,0)	int	no	positiveNumber	Record revision number
 row_num	number(10,0)	int	no		Row position of where this task is display on the form.
task_action	varchar2(80)	varchar(80)	yes		Task description.
task_comment	varchar2(80)	varchar(80)	yes		Task processing comment.
task_id	varchar2(10)	varchar(10)	no		Task id of the active task.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date time stamp.
updt_flag	varchar2(15)	varchar(15)	no		Update terminal.
upers	number(10,0)	int	yes	nonNegativeNumber	User id of the person that is updating the record.
uterm	varchar2(15)	varchar(15)	yes		The terminal that is updating the record.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
majevt_hst_primary_key	row_num			primaryKey	yes

 [Top](#)

Table Name - map_switch_table					
Description	This table shows the current map source and the history of the map source changes.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp
cterm	varchar2(15)	varchar(15)	no		Terminal that created the record
is_map_db	varchar2(1)	varchar(1)	no	is_map_db = 'F'	Indicates if this is a map staging database T/F
 rev_num	number(10,0)	int	no	positiveNumber	The revision number which is incremented each time a row is inserted
source	varchar2(1)	varchar(1)	no	source in ('A','B')	Is set to either A or B
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
map_switch_table_primary_key	rev_num			primaryKey	yes

 [Top](#)

Table Name - map_views					
Description	Defines the map views that will be managed by the MapSwitch utility				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 view_name	varchar2(30)	varchar(30)	no		The name of a map view
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
map_views_primary_key	view_name			primaryKey	yes

 [Top](#)

Table Name - mcgedata					
Description	For the MCGE system, this table defines the inputs for private calls and group calls based on a CAD unit Id. These are initiated from the Iradiocmd module within I/Disp. This table is used by I/Radio.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
privatecallchannel	varchar2(32)	varchar(32)	no		MCGE channel for private call placement

radioid	varchar2(32)	varchar(32)	no		MCGE radioid for private call placement
selectchannel	varchar2(32)	varchar(32)	no		Default MCGE channel used for group communication for this Cad unit
 unid	varchar2(32)	varchar(32)	no		CAD unit id
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mcegedata_pk	unid			primaryKey	yes

 [Top](#)

Table Name - mdt_logged_on_persl					
Description	The employees that have been logged on via an MDT.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 device_id	varchar2(40)	varchar(40)	no	regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$')	Unique device id for the specified device type. For MDTs the device ID must be a positive integer.
 device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 device_type	number(5,0)	smallint	no	device_type = 6	Device type. 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
 empid	number(10,0)	int	no	nonNegativeNumber	The employee that was logged on via the MDT.
primary_empid	number(5,0)	smallint	no	booleanNumber1Or0	Is primary employee for the MDT. 1 = True, 0 = False. The primary employee is used to determine the security context for the MDT.
 unid	varchar2(10)	varchar(10)	no		The unit id associated with the MDT.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdt_logged_on_persl_pk	empid, unid, device_id, device_type, device_sub_type			primaryKey	yes

 [Top](#)

Table Name - mdtapcdata					
Description	The mdtapcdata table is used to store active MPS client information. Only active signed on MPS clients are in the table. It is used as a persistent store for client ID to IP Address mappings. The data in this table is kept up to date by Mdtisvr during Sign On and Sign Off and anytime the IP Address has changed for an authorized client.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
apcdata	varchar2(64)	varchar(64)	no		IP Address and port last received from the Client
authorizedmdtid	varchar2(24)	varchar(24)	no		The Mdt ID assigned to this client when it was authorized
 clientid	varchar2(64)	varchar(64)	no		Contains the unique ID provided by the MPS Client
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdtapcdata_pk	clientid			primaryKey	yes

 [Top](#)

Table Name - mdtbroadcast					
Description	This table is used for messaging and generic broadcasts to groups of MDT's.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 address	varchar2(10)	varchar(10)	no		The address in HEX to be affiliated with the Name/Group pair.
agency	varchar2(9)	varchar(9)	yes		Agency that is affiliated with the Name/Subgroup Pair
name	varchar2(9)	varchar(9)	no		Special broadcast name. In some cases can be thought of as analogous to Agency.
subgroup	varchar2(5)	varchar(5)	no		Identifies a partitioning of the group defined by Name.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdtbroadcast_primary_key	address			primaryKey	yes
mdtbroadcast_unique	agency			uniqueKey	no
mdtbroadcast_unique2	name, subgroup			uniqueKey	no

 [Top](#)

Table Name - mdtcommand					
Description	This table defines the actual MDT commands issued by the Mobile Unit				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
banner	varchar2(16)	varchar(16)	yes		Contains the text to be sent to the banner software.
blocking [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOF	If set to true "T," indicates that subsequent commands issued by or on behalf of the same unit be discarded if they are identical to an active command The Default is false "F."
cannedmessagenumber	number(10,0)	int	yes		Contains the number of the canned message to be displayed on the MDT.
displaylocation	number(10,0)	int	yes		Contains the MDT specific code that identifies the location where the results should be displayed on the mobile user's display. i.e., status bar, message, popup dialog, etc.
displayname	varchar2(32)	varchar(32)	yes		Contains the display name for the command messages. If required, this field includes messages that are sent on behalf of the command. If a display name is required but this field is not defined, the Type field will be used.
displaypriority	number(10,0)	int	yes		Contains the MDT specific priority code used when displaying results.
esmdnode	varchar2(16)	varchar(16)	yes		Contains the node identifier where the ESMD message is sent. If this column is left blank no ESMD message is sent for this command.
flags [default = 0]	number(10,0)	int	no		Defines the flags word that controls the behavior of the command. See the site specific command SQL file for a description of the bit setting. The LSB 28 bits can apply to any command. The 4 MSB are specific to that command type.
formpath	varchar2(128)	varchar(128)	yes		Contains the form path. This is a relative path name including the file name that defined the downloadable form file. The relative path is appended to MDTSVR_PATH\FORM\
formtag	varchar2(32)	varchar(32)	yes		Contains the form tag used as a key for the command lookup.
 id	number(10,0)	int	no		Contains the UNIQUE command identifier.
mnemonic	varchar2(16)	varchar(16)	yes		Contains the mnemonic used as a key for the command lookup
securitylevel	number(10,0)	int	yes		Contains the security level that governs access to the command. defined in the Persl table
serverid	number(10,0)	int	yes		Contains the server identifier for the process targeted for the command. Typically this is the identifier of the RPC server.
statuscode	number(10,0)	int	yes		Contains the status code used as a key for the command lookup.

statusindicator	varchar2(1)	varchar(1)	yes		Contains the status character displayed on the Unit/Event Status dialog box in CAD.
type	varchar2(32)	varchar(32)	no		Contains the command type. This is an alphanumeric description of the command type (for example, SIGN ON). These types are predefined.
userdata1	varchar2(128)	varchar(128)	yes		Contains user data specific to a command. Assign Case Number might contain the table_id in Userdata1.
userdata2	varchar2(128)	varchar(128)	yes		Contains additional user data.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
mdtcommand_primary_key	id		primaryKey		yes

[Top](#)

Table Name - mdtcommandline					
Description	This table identifies the valid fields acceptable for command line entry.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 commandid	number(10,0)	int	no		Contains the command identifier. - Links to ID in MDTCOMMAND
 position	number(10,0)	int	no		Position on the command line.
typename	varchar2(20)	varchar(20)	no		The type of field. This field along with the commandid is used to index into the Mdtfield table to validate command line entry. There MUST BE a corresponding entry in the Mdtfield table for this field.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
mdtcommandline_pk	commandid, position		primaryKey		yes

[Top](#)

Table Name - mdtcommandmap					
Description	This table associates commands with a specific MDT group. This table is only required if more than one MDT group is defined.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 commandid	number(10,0)	int	no		Contains the command identifier.
 groupid	number(10,0)	int	no		Contains the group identifier. Links to ID in MDTGROUP.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
mdtcommandmap_primary_key	groupid, commandid		primaryKey		yes

[Top](#)

Table Name - mdtcommandrouting						
Description		The table maps command identifiers to I/Switch node names.				
Copy Type		ALL_WITH_CHECK				
Columns						
Column Name		Oracle Type	Sql Server Type	NULL	Constraint	Description
	destnode	varchar2(16)	varchar(16)	no		Contains the I/Switch destination node.
	id	number(10,0)	int	no		Contains the command identifier.
Key Constraints						
Constraint Name		Columns			Constraint Type	Sql Server Clustered
mdtcommandrouting_primary_key		id, destnode			primaryKey	yes

[Top](#)

Table Name - mdterror					
Description	Record errors and the contents of the MDTSVR related command that induced the error.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time stamp when row was created
client_time	varchar2(16)	varchar(16)	yes		Time when request was made on the client that caused the failure. If this is not an inbound command from then client, this column will be null.
command_name	varchar2(32)	varchar(32)	no		The MDT command name.
commandid	number(10,0)	int	no		The MDT command id
error_desc	varchar2(126)	varchar(126)	no		Description of the error
inbound	varchar2(1)	varchar(1)	no	booleanYOrN	Y if command from client to server, N if from server to client
switchxml	clob	varchar(max)	no		The switch message from the failed command convert to XML.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time stamp when row was updated
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies rows
unitid	varchar2(10)	varchar(10)	no		The unit associated with the command
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
mdterror_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdterror_pk	unique_id			primaryKey	yes

[Top](#)

Table Name - mdtfield					
Description	This table defines the specified field constraints associated with a command in MDT.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 commandid	number(10,0)	int	no		Contains the command identifier.
 fieldid	number(10,0)	int	no		Contains the field identifier.
lastparameter [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates that this is the last field for command parsing. The default is 'F'.
name	varchar2(20)	varchar(20)	yes		Contains the name of the field. Display name for the field used in error reporting.
position	number(10,0)	int	no		Contains the position number of the field.

relatedfield	number(10,0)	int	yes		Contains the identifier for the related field bound by the constraint defined in relatedfieldconstraint.
relatedfieldconstraint	varchar2(3)	varchar(3)	yes	relatedfieldconstraint in ('XOR','AND','OR')	Contains any relation field constraints ('XOR','AND','OR') to define this fields relationship with the relatedfield.
required [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates if the field is required. Default is false "F."
truncatetomax [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates that the field should be truncated to the Maximum length as defined through its validationtypeid. The default is false "F".
typename	varchar2(20)	varchar(20)	no		Contains the field type name. This value is used to infer the type of data that is stored in this field.
validationtypeid	number(10,0)	int	yes		Contains the validation type identifier used to join the mdtvalidationtype table.

Key Constraints				
Constraint Name	Columns		Constraint Type	Sql Server Clustered
mdtfield_primary_key	commandid, fieldid		primaryKey	yes
mdtfield_unique	commandid, position		uniqueKey	no
mdtfield_unique2	commandid, typename		uniqueKey	no
Check Constraints				
Constraint Name	Required	Oracle Definition	Sql Server Definition	
mdtfield_relatedfield_ck	Yes	(relatedfieldconstraint is null and relatedfield is null) or (relatedfieldconstraint is not null and relatedfield is not null)	([relatedfieldconstraint] is null and [relatedfield] is null) or ([relatedfieldconstraint] is not null and [relatedfield] is not null)	

[Top](#)

Table Name - mdtfieldenumeration					
Description		This table defines the field enumerations.			
Copy Type		ALL_WITH_CHECK			
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 id	number(10,0)	int	no		Contains the ID of the field enumeration.
name	varchar2(20)	varchar(20)	no		Contains the name of the field.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdtfieldenum_primary_key	id			primaryKey	yes
mdtfieldenum_unique	name			uniqueKey	no

[Top](#)

Table Name - mdtfieldenumerationvalues					
Description	This table defines the field enumeration values.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 id	number(10,0)	int	no		Contains the ID of the field enumeration. Used to join the mdtfieldenumeration table.
 value	varchar2(20)	varchar(20)	no		Contains the field value.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdtfieldenumvalues_primary_key	id, value			primaryKey	yes

[Top](#)

Table Name - mdtgroup					
Description	This table is used to identify the MDT groups. Group ID's must be sequential starting with a value of one (1).				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 id	number(10,0)	int	no		Contains the I/MDT group identifier.
name	varchar2(16)	varchar(16)	no		Contains the group name.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdtgroup_primary key	id			primaryKey	yes
mdtgroup unique	name			uniqueKey	no

[Top](#)

Table Name - mdtgroupmap						
Description	This table associates the MDT group with a specific agency and dispatch group.					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
agency	varchar2(9)	varchar(9)	no		Contains the name of the agency associated with the MDT group.	
dgroup	varchar2(5)	varchar(5)	yes		Contains the name of the dispatch group associated with the MDT group. If not specified, all of the DGROUPS for the specified agency are assumed. There can be no other record in this table that lists the same AGENCY.	
id	number(10,0)	int	no		Contains the I/MDT group identifier.	
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no			
Indexes						
Index Name	Columns			Is Unique	Sql Server Clustered	Sql Server Where Clause
mdtgroupmap_id	id			no	yes	
Key Constraints						
Constraint Name	Columns			Constraint Type		Sql Server Clustered
mdtgroupmap_pk	unique_id			primaryKey		no

[Top](#)

Table Name - mdtvalidation					
Description	This table provides the first level of validation for command processing.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 commandid	number(10,0)	int	no		Contains the command identifier.

downloadableform [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates if the form is downloadable. Default is "F".
logonrequired [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates that the unit must be signed on before this command can be executed. Default is false "F".
romform [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates that the form is in Read Only Memory of the physical MDT. Default is false "F".
unlockrequired [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates that the MDT must be unlocked for this command to be executed Default is false "F".
validationrequired [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates if the command requires additional validation that is defined through the mdtfld, mdvalidationtype, mdtfldenumeration, and mdtfldenumerationtypes tables. Default is false "F".
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
mdtvalidation_primary_key	commandid		primaryKey		yes

 [Top](#)

Table Name - mdtvalidationtype					
Description	This table is for future use. This table defines common validation types used that can be used by any command.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
data1	number(10,0)	int	yes		Contains the field data.
data2	number(10,0)	int	yes		Contains the field data
enumerationtype	number(10,0)	int	yes		Contains the enumeration type.
maximumlength	number(10,0)	int	yes		Contains the maximum length of the type identifier.
minimumlength	number(10,0)	int	yes		Contains the minimum length of the type identifier.
name	varchar2(20)	varchar(20)	no		Contains the type identifier name.
 typeid	number(10,0)	int	no		Contains the command type identifier.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mdtvalidationtype_primary_key	typeid			primaryKey	yes
mdtvalidationtype_unique	name			uniqueKey	no

 [Top](#)

Table Name - messa					
Description	Holds all messages sent between nodes. The Messa table holds the message origination information and the text of the message. The message_dest and message_receive tables hold message destination information.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time when the record was created
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		The time when the record was created
cpers	number(10,0)	int	no	nonNegativeNumber	Employee id number of the person originating the message. The id of the person logged on and sending the message comes from the persl table or the employee is of the person in the unit if it is from a MDT.
critical [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	T/F, critical, want receipt.
cterm	varchar2(15)	varchar(15)	no		Terminal of the Originating Message. The nodename of the sender.
event_call_id	number(10,0)	int	yes		For callback messages this is the associated event call
flags [default = 0]	number(10,0)	int	no	flags between 0 and 1	Flags column contains message attributes. Each bit represents a boolean value. 1 = Message has attachments
fwd from msg_num	number(10,0)	int	yes		Message number from which this message was forwarded
message_send_type	number(5,0)	smallint	no	message_send_type between 0 and 3	Indicates how this message was sent: 0 - Regular message, 1 - Scheduled message, 2 - Active recurring message template, 3 - Inactive recurring message template
 msg_num	number(10,0)	int	no		Message number. Unique number generated by CAD (ndxnum of message table) Used as the main pointer to all messages, lets receiver get messages from database. Only data sent in packets for administrative messages
msg_prior [default = '9']	varchar2(1)	varchar(1)	no	msg_prior in ('0','1','2','3','4','5','6','7','8','9')	0-9, The message priority specified by the sender.
msg_text	clob	varchar(max)	yes	length(msg_text) <= 65536	The text of the message. This column requires a full text search index so that the contains predicate can be used in queries.
msg_type [default = 0]	number(10,0)	int	no	msg_type in (0,1,2)	0 (regular message) 1 (system message) 2 (notification message)
num_1	varchar2(12)	varchar(12)	yes		The agency event number associated with the CAD message
orig_msg_num	number(10,0)	int	no		The original message number from which the message came
reply_to_msg_num	number(10,0)	int	yes		Message number that was acknowledged (replied to)
send_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time stamp when message was actually sent
subject	varchar2(40)	varchar(40)	yes		Subject Header of Message. This field is seen on the Send Message and Receive Message forms.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The time when the record was updated
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		The time when the record was updated
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
messa_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
messa_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
messa_primary_key	msg_num			primaryKey	yes
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
messa_event_call_id_ck		Yes	event_call_id is null or msg_type = 1		event_call_id is null or msg_type = 1

 [Top](#)

Table Name - message_attachment					
Description	Associates a message with an attachment				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 attachment_id	raw(16)	varbinary(16)	no		Uniquely identifies an attachment
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The time when this record was created
cpers	number(10,0)	int	no	nonNegativeNumber	The employee id of the person that created this record
cterm	varchar2(15)	varchar(15)	no		The terminal that was used to create this record
 msg_num	number(10,0)	int	no		Message number
Indexes					

Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
message_attachment_cdt\$	cdts	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type	Sql Server Clustered	
message_attachment_pk	msg_num, attachment_id	primaryKey	yes	

 [Top](#)

Table Name - message_dest					
Description	This table holds the message destination information. The messa table holds the message origination information and the text of the message.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp of this record
cpers	number(10,0)	int	no	nonNegativeNumber	Employee that created the record
cterm	varchar2(15)	varchar(15)	no		Terminal where record was created
 destination	varchar2(80)	varchar(80)	no		If destination_type is not a group or filter - the actual destination. If destination_type is a group or filter - the overall destination.
destination_subtype	number(5,0)	smallint	no	destination_subtype between -1 and 10	Destination subtype. -1: Unknown, 0: CAD, 1: DISP, 2: CALL, 3: STATIC, 4: BG,CALLBACK, 5: MDT, 6: MDT_SERVER, 7: NETVIEWER, 8: EMAIL, 9: PAGER, 10: PRINTER. Parameter data maps the number to a user-configurable display name
 destination_type	number(5,0)	smallint	no	destination_type between 0 and 6	Destination main type: 0 = TERM, 1 = PERSON, 2 = PAGER, 3 = STATION, 4 = EMPID, 5 = GROUP, 6 = FILTER
 msg_num	number(10,0)	int	no		Message number, a unique identifier for the message
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
message_dest_cdt\$	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
message_dest_pk	msg_num, destination_type, destination			primaryKey	yes

 [Top](#)

Table Name - message_receive					
Description	This table is related to the message_dest table. Destinations are detailed from the message_dest table at a more granular (device/terminal or person) level. Status and auditing information is recorded.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp of this record
cpers	number(10,0)	int	no	nonNegativeNumber	Employee that created the record
cterm	varchar2(15)	varchar(15)	no		Terminal where record was created
deleted_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time stamp when message was deleted
deleted_pers	number(10,0)	int	yes	nonNegativeNumber	Person who deleted the message
deleted_term	varchar2(15)	varchar(15)	yes		Terminal on which the message was deleted
delivered_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time stamp when message was delivered (Mobile users)
delivered_pers	number(10,0)	int	yes	nonNegativeNumber	Person to whom message was delivered (Mobile users)
delivered_term	varchar2(15)	varchar(15)	yes		Terminal or unit to which the message was delivered (Mobile users)
 destination	varchar2(80)	varchar(80)	no		More granular level of message_dest.destination
 destination_type	number(5,0)	smallint	no	destination_type between 0 and 4	0 = TERM, 1 = PERSON, 2 = PAGER, 3 = STATION, 4 = EMPID
 msg_num	number(10,0)	int	no		Message number, a unique identifier for the message
read_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time stamp when message was read
read_pers	number(10,0)	int	yes	nonNegativeNumber	Person who read the message
read_term	varchar2(15)	varchar(15)	yes		Terminal on which message was read
received_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date/time stamp when message was received.
received_pers	number(10,0)	int	yes	nonNegativeNumber	Person who received the message
received_term	varchar2(15)	varchar(15)	yes		Terminal on which the message was received
status	number(5,0)	smallint	no	status between -1 and 3	Latest status of the message. -1 = Not Received, 0 = Received and New (not read), 1 = Delivered, 2 = Read, 3 = Deleted
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp of this record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
message_receive_cdt\$udts	cdts, udts		no	no	
message_receive_dest_type_sta	destination, destination_type, status		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
message_receive_pk	msg_num, destination_type, destination			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
message_receive_deleted_ck	Yes	(deleted_dts is null and deleted_term is null and deleted_pers is null) OR (deleted_dts is not null and deleted_term is not null and deleted_pers is not null)		(deleted_dts is null and deleted_term is null and deleted_pers is null) OR (deleted_dts is not null and deleted_term is not null and deleted_pers is not null)	
message_receive_delivered_ck	Yes	(delivered_dts is null and delivered_term is null and delivered_pers is null) OR (delivered_dts is not null and delivered_term is not null and delivered_pers is not null)		(delivered_dts is null and delivered_term is null and delivered_pers is null) OR (delivered_dts is not null and delivered_term is not null and delivered_pers is not null)	
message_receive_read_ck	Yes	(read_dts is null and read_term is null and read_pers is null) OR (read_dts is not null and read_term is not null and read_pers is not null)		(read_dts is null and read_term is null and read_pers is null) OR (read_dts is not null and read_term is not null and read_pers is not null)	
message_receive_receive_ck	Yes	(received_dts is null and received_term is null and received_pers is null) OR (received_dts is not null and received_term is not null and received_pers is not null)		(received_dts is null and received_term is null and received_pers is null) OR (received_dts is not null and received_term is not null and received_pers is not null)	
message_receive_status2_ck	Yes	(status = -1 and received_dts is null and read_dts is null and deleted_dts is null) OR (status = 0 and received_dts is not null and read_dts is null and deleted_dts is null) OR (status = 1 and delivered_dts is not null and read_dts is null and deleted_dts is null) OR (status = 2 and received_dts is not null and read_dts is not null and deleted_dts is null)		(status = -1 and received_dts is null and read_dts is null and deleted_dts is null) OR (status = 0 and received_dts is not null and read_dts is null and deleted_dts is null) OR (status = 1 and delivered_dts is not null and read_dts is null and deleted_dts is null) OR (status = 2 and received_dts is not null and read_dts is not null and deleted_dts is not null and	

OR (status = 3 and deleted_dts is not null)

|deleted_dts is null) OR (status = 3 and deleted_dts is not null)

 [Top](#)

Table Name - mi_plan_table					
Description	Used to store Major Event plan associated information generated by caddbm.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
dg_task_list_name	varchar2(20)	varchar(20)	yes		Task List assigned to the Dispatch Group
fo_task_list_name	varchar2(20)	varchar(20)	yes		Task List assigned to the First Officer
mi_plan_descr	varchar2(80)	varchar(80)	yes		Textual plan description
 mi_plan_id	varchar2(10)	varchar(10)	no		Unique plan identifier
og_task_list_name	varchar2(20)	varchar(20)	yes		Task List assigned to 'Other' Group
pl_task_list_name	varchar2(20)	varchar(20)	yes		Task List assigned based on the Plan Type / Location
support_0_scrindex	number(10,0)	int	yes		Index to Support Article
support_1_scrindex	number(10,0)	int	yes		Index to Support Article
support_2_scrindex	number(10,0)	int	yes		Index to Support Article
support_3_scrindex	number(10,0)	int	yes		Index to Support Article
support_4_scrindex	number(10,0)	int	yes		Index to Support Article
support_5_scrindex	number(10,0)	int	yes		Index to Support Article
support_6_scrindex	number(10,0)	int	yes		Index to Support Article
support_7_scrindex	number(10,0)	int	yes		Index to Support Article
support_8_scrindex	number(10,0)	int	yes		Index to Support Article
support_9_scrindex	number(10,0)	int	yes		Index to Support Article
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mi_plan_table_primary_key	mi_plan_id			primaryKey	yes

 [Top](#)

Table Name - mi_task_list_table					
Description	Used to store Major Event task item information generated using caddbm.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ai_scrindex	number(10,0)	int	yes		Index to Associated Information for this task.
 task_id	varchar2(10)	varchar(10)	no		The ID for the task described within this particular record.
 task_list_name	varchar2(20)	varchar(20)	no		Name of the Task List
task_text	varchar2(80)	varchar(80)	yes		Text describing the task.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mi_task_list_table_primary_key	task_list_name, task_id			primaryKey	yes

 [Top](#)

Table Name - mobile_pda_msg_inbound					
Description	Holds messages and requests sent in to the CAD system from remote MobilePDA clients.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
data	varchar2(4000)	varchar(4000)	yes		Databody of message
datestamp	varchar2(30)	varchar(30)	no		Date/time of insertion. Format is YYYY-MM-DD HH:MM:SS.MMM
 id	number(19,0)	bigint	no		Unique record id
type	varchar2(16)	varchar(16)	yes		Type of message (SON, SOFF, etc)
unitid	varchar2(50)	varchar(50)	no		Unit id sending message
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mobile_pda_msg_inbound_pk	id			primaryKey	yes

 [Top](#)

Table Name - mobile_pda_msg_outbound					
Description	Holds messages and requests sent from the CAD system and destined to remote MobilePDA clients				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
data	clob	varchar(max)	yes		Databody of message
datestamp	varchar2(30)	varchar(30)	no		Date/time of insertion. The format is YYYY-MM-DD HH:MM:SS.MMM
 id	number(19,0)	bigint	no		Unique record id
type	varchar2(16)	varchar(16)	yes		Type of message
unitid	varchar2(50)	varchar(50)	no		Unit id receiving message
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mobile_pda_msg_outbound_pk	id			primaryKey	yes

 [Top](#)

Table Name - mobileclientcomputeridentity					
Description	Computer identity for the MobilePublicSafety Content Management System. Each row identifies a mobile client computer. Added for CR 1-4XMERB.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Timestamp for record creation
cmscomputerdescription	varchar2(255)	varchar(255)	yes		Optional description
 cmscomputerid	varchar2(50)	varchar(50)	no		Uniquely identifies a mobile computer.
cmscomputername	varchar2(50)	varchar(50)	no		Name assigned to the id.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Timestamp for record update.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mobileclientcomputerid_pk	cmscomputerid			primaryKey	yes

[Top](#)

Table Name - mobileclientsysteminformation					
Description	System Information for each mobile computer. This table is used by the MobilePublicSafety Content Management System. Added for CR 1-4XMERB.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Timestamp for record creation
 cmscomputerid	varchar2(50)	varchar(50)	no		Uniquely identifies a mobile computer.
domain	varchar2(255)	varchar(255)	yes		Windows domain
locale	varchar2(50)	varchar(50)	no		Current windows locale setting
osname	varchar2(75)	varchar(75)	no		Operating system name
osversion	varchar2(255)	varchar(255)	no		Operating system version
systemmanufacturer	varchar2(255)	varchar(255)	yes		Hardware manufacturer
systemmodel	varchar2(255)	varchar(255)	yes		Hardware model
systemname	varchar2(50)	varchar(50)	yes		Computer name
timezone	number(10,0)	int	yes		Positive, negative or zero offset in minutes from UTC.
totalphysicalmemory	number(19,0)	bigint	no		Total size of physical memory in bytes.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Timestamp for record update.
workgroup	varchar2(255)	varchar(255)	yes		Windows workgroup
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mobileclientsysteminfo_pk	cmscomputerid			primaryKey	yes

[Top](#)

Table Name - mr_pending_push_messages					
Description	Mobile Responder table to hold pending push notifications for delivery to the client. The device ID, type and sub_type columns allow Mobile Responder to support multi-device configurations that MDT supports.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
additional_data	varchar2(200)	varchar(200)	yes		Additional data for the message
device_id	varchar2(40)	varchar(40)	no		Device ID. Typically this will be an MDTID.
device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type.
device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT
message	varchar2(200)	varchar(200)	no		Message to push to device
 message_id	number(10,0)	int	no		Message id
smartphone_os	number(10,0)	int	no	smartphone_os between 0 and 3	Type of smartphone. 0= Apple iOS, 1= Android, 2= Blackberry, 3= Windows
smartphone_push_token	varchar2(256)	varchar(256)	no		Token used to push data back to the device
state	varchar2(1)	varchar(1)	no		State of the message
type	varchar2(64)	varchar(64)	yes		Message type
 unid	varchar2(10)	varchar(10)	no		Unit id
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
mr_pending_push_msg_dev_ty_sub	device_id, device_type, device_sub_type		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mr_pending_push_messages_pk	message_id, unid			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
mr_pend_push_msg_mdt_smt_id_ck	Yes	(device_type not in (5,6)) or (regexp_like(device_id, ''[0-9A-Fa-f]{1,10}\$'))		(device_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)	

[Top](#)

Table Name - mr_unit_response_state					
Description	Mobile Responder table to hold the current state of the unit with respect to the processing of event/unit reports. Used internally by the report engine. The device ID, type and sub_type columns allow Mobile Responder to support multi-device configurations that MDT supports.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency id of the unit
device_id	varchar2(40)	varchar(40)	no		Device ID. Typically this will be an MDTID.
device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type.
device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT
state	number(10,0)	int	no	state between 0 and 1	Current operating state of the unit. Either soliciting data (0), or accepting unsolicited data (1).
 unid	varchar2(10)	varchar(10)	no		Unit id of the unit
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
mr_unit_resp_st_dev_ty_sub	device_id, device_type, device_sub_type		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mr_unit_response_state_pk	unid			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
mr_unit_resp_st_mdt_smt_id_ck	Yes	{device_type not in (5,6)} or (regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$'))		{device_type not in (5,6)} or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)	

[Top](#)

Table Name - mscatalog_a					
Description	Used to link geographic elements to database records. Used to generate unique mslink values.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
dastable	varchar2(32)	varchar(32)	yes		This field specifies table that maps displayable attribute types to corresponding SQL stmts and screen forms. Used to define what attributes will be in displayable attribute text nodes.

 entitynum	number(10,0)	int	no		Entity Number. The unique number associated with the database table.
fencefilter	varchar2(240)	varchar(240)	yes		This column is used with fence operations.
nextocc	number(10,0)	int	yes		This field contains the next available mslink
reporttable	varchar2(64)	varchar(64)	yes		This column is used with fence operations.
screenform	varchar2(64)	varchar(64)	yes		This column is used for attribute review operations
sqlreview	varchar2(240)	varchar(240)	yes		This column is used with the Review Database Attributes command.
tablename	varchar2(32)	varchar(32)	yes		Table name. Name of the database table.
tabletype	number(10,0)	int	yes		Indicates graphic, non-graphic, or system table
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
mscatalog_a_primary_key	entitynum		primaryKey		yes

 [Top](#)

Table Name - mscatalog_b					
Description	Used to link geographic elements to database records.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
dastable	varchar2(32)	varchar(32)	yes		This field specifies table that maps displayable attribute types to corresponding SQL stmts and screen forms. Used to define what attributes will be in displayable attribute text nodes.
 entitynum	number(10,0)	int	no		Entity Number. The unique number associated with the database table.
fencefilter	varchar2(240)	varchar(240)	yes		This column is used with fence operations.
nextocc	number(10,0)	int	yes		This field contains the next available mslink
reporttable	varchar2(64)	varchar(64)	yes		This column is used with fence operations.
screenform	varchar2(64)	varchar(64)	yes		This column is used for attribute review operations
sqlreview	varchar2(240)	varchar(240)	yes		This column is used with the Review Database Attributes command.
tablename	varchar2(32)	varchar(32)	yes		Table name. Name of the database table.
tabletype	number(10,0)	int	yes		Indicates graphic, non-graphic, or system table
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
mscatalog_b_primary_key	entitynum			primaryKey	yes

 [Top](#)

Table Name - msg_group					
Description	Used in caddbm and cad to define a group to which messages can be sent.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp.
destination	varchar2(80)	varchar(80)	yes		The node name, unit id, page id, email address, etc.
empid	number(10,0)	int	yes	nonNegativeNumber	Used to store empid when the message type is PERSON to ensure a unique selection.
filter	varchar2(15)	varchar(15)	yes		Used in CADDDBM and CAD for message group. The user defined Static group can associate to a filter and by selecting a filtered type, the group list is smaller and more specific.
fname	varchar2(50)	varchar(50)	yes		The first name of a person.
grp_name	varchar2(15)	varchar(15)	no		The name of a group.
lname	varchar2(50)	varchar(50)	yes		The last name of a person.
main_type	varchar2(8)	varchar(8)	no	main_type in ('EMPID', 'GROUP', 'PAGER', 'PERSON', 'RADIO', 'STATION', 'TERM')	Destination type, such as PERSON, PAGER, STATION, or GROUP.
mi	varchar2(1)	varchar(1)	yes		The middle initial of a person.
sub_type	varchar2(15)	varchar(15)	yes		Destination sub-type, such as CAD, MDT, PAGER, EMAIL, or other application
 unique_id	raw(16)	varbinary(16)	no		Unique identifier
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
msg_group_grp_name	grp_name		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
msg_group_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - netfea_a					
Description	This table is used by the Network Builder (netbuilder) command to assign the class and symbology to the street segments.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
category	number(10,0)	int	yes		Category name. This is a required field that is the join column for the category table. It holds the category number for the feature.
celllibrary	varchar2(14)	varchar(14)	yes		Path to the cell library if feature places a cell
cellscale	float(126)	float(53)	yes		Scale value for cell placement
comp_feature_id	number(10,0)	int	yes		No longer used
def_height_limit	float(126)	float(53)	yes		Default value for maximum vehicle height allowed on the feature type described by this netfea record.
def_riskcost	float(126)	float(53)	yes		Default feature traffic parameter: riskcost
def_speedlimit	number(5,0)	smallint	yes		Default feature traffic parameter: speedlimit
def_timefactor	float(126)	float(53)	yes		Default feature traffic parameter: timefactor
def_weight_limit	float(126)	float(53)	yes		Default value for maximum vehicle weight allowed on the feature type described by this netfea record.
def_width_limit	float(126)	float(53)	yes		Default value for maximum vehicle width allowed on the feature type described by this netfea record.
digcmd	varchar2(240)	varchar(240)	yes		The Map key-in command for placing an element
fangle	varchar2(16)	varchar(16)	yes		Angle of the element when placed.
fcellname	varchar2(6)	varchar(6)	yes		Name of the cell in the cell library.
 fcode	varchar2(12)	varchar(12)	no		Feature code. Street class definition. This is a required field.
fcolor	number(5,0)	smallint	yes		Feature Color. Graphic color for element placement.
fdatatype	number(5,0)	smallint	yes		Type value for displayable attributes.
felement	number(5,0)	smallint	yes		Map element type for the feature
ffont	number(5,0)	smallint	yes		Map font for the feature if type label
fheight	float(126)	float(53)	yes		Text height.
fjustification	varchar2(3)	varchar(3)	yes		Text justification.
flevel	number(5,0)	smallint	yes		Feature level. Graphic level for element placement.

flinespace	float(126)	float(53)	yes		Text spacing
fname	varchar2(32)	varchar(32)	yes		Feature name. Street class name. Optional field for storing a more descriptive name for the feature than the feature code.
fstyle	number(5,0)	smallint	yes		Feature Style. Graphic style for element placement.
fsymbol	varchar2(6)	varchar(6)	yes		This field not accessed by I/CAD.
ftype	number(10,0)	int	yes		Feature Type. I/CAD uses two types: 0 - point feature (intersection) and 1- line feature (street segments, etc)
fweight	number(5,0)	smallint	yes		Feature Weight. Graphic style for element placement.
fwidth	float(126)	float(53)	yes		Text width
is_optional	varchar2(1)	varchar(1)	yes		This field not accessed by I/CAD.
is_repeating	varchar2(1)	varchar(1)	yes		This field is not accessed by I/CAD.
linelength	number(5,0)	smallint	yes		Line length for text.
max_displayscale	number(10,0)	int	yes		This field not accessed by I/CAD.
min_displayscale	number(10,0)	int	yes		This field is not accessed by I/CAD.
mslink	number(10,0)	int	no		Number that links the database record to the street segments.
newdup	number(5,0)	smallint	yes		This field not accessed by I/CAD.
snaptolerance	number(5,0)	smallint	yes		This field is not accessed by I/CAD.
snaptype	number(5,0)	smallint	yes		This field not accessed by I/CAD.
streamdelta	float(126)	float(53)	yes		This field not accessed by I/CAD.
streamtolerance	float(126)	float(53)	yes		This field not accessed by I/CAD.
streamunit	varchar2(15)	varchar(15)	yes		This field not accessed by I/CAD.
tablename	varchar2(32)	varchar(32)	yes		Table Name. Database table that contains attribute data for this feature. In I/CAD, this is either segme or inter.
tcolor	number(5,0)	smallint	yes		Color to be used for text when placing street names for the feature type described by this netfea record.
textunit	varchar2(15)	varchar(15)	yes		Units for text placement.
tlevel	number(5,0)	smallint	yes		Level on which to place text when placing street names for the feature type described by this netfea record
tweight	number(5,0)	smallint	yes		Weight to be assigned to text when placing street names for the feature type described by this netfea record.
use_range	varchar2(1)	varchar(1)	yes		This field not accessed by I/CAD.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
netfea_a_primary_key	fcode		primaryKey		yes

 [Top](#)

Table Name - netfea_b					
Description	This table is used by the Network Builder (netbuilder) command to assign the class and symbology to the street segments.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
category	number(10,0)	int	yes		Category name. This is a required field that is the join column for the category table. It holds the category number for the feature.
celllibrary	varchar2(14)	varchar(14)	yes		Path to the cell library if feature places a cell
cellscale	float(126)	float(53)	yes		Scale value for cell placement
comp_feature_id	number(10,0)	int	yes		No longer used
def_height limit	float(126)	float(53)	yes		Default value for maximum vehicle height allowed on the feature type described by this netfea record.
def_riskcost	float(126)	float(53)	yes		Default feature traffic parameter: riskcost
def_speedlimit	number(5,0)	smallint	yes		Default feature traffic parameter: speedlimit
def_timefactor	float(126)	float(53)	yes		Default feature traffic parameter: timefactor
def_weight limit	float(126)	float(53)	yes		Default value for maximum vehicle weight allowed on the feature type described by this netfea record.
def_width limit	float(126)	float(53)	yes		Default value for maximum vehicle width allowed on the feature type described by this netfea record.
digcmd	varchar2(240)	varchar(240)	yes		The Map key-in command for placing an element
fangle	varchar2(16)	varchar(16)	yes		Angle of the element when placed.
fcellname	varchar2(6)	varchar(6)	yes		Name of the cell in the cell library.
 fcode	varchar2(12)	varchar(12)	no		Feature code. Street class definition. This is a required field.
fcolor	number(5,0)	smallint	yes		Feature Color. Graphic color for element placement.
fdastype	number(5,0)	smallint	yes		Type value for displayable attributes.
felement	number(5,0)	smallint	yes		Map element type for the feature
ffont	number(5,0)	smallint	yes		Map font for the feature if type label
fheight	float(126)	float(53)	yes		Text height.
fjustification	varchar2(3)	varchar(3)	yes		Text justification.
flevel	number(5,0)	smallint	yes		Feature level. Graphic level for element placement.
flinespace	float(126)	float(53)	yes		Text spacing
fname	varchar2(32)	varchar(32)	yes		Feature name. Street class name. Optional field for storing a more descriptive name for the feature than the feature code.
fstyle	number(5,0)	smallint	yes		Feature Style. Graphic style for element placement.
fsymbol	varchar2(6)	varchar(6)	yes		This field not accessed by I/CAD.
ftype	number(10,0)	int	yes		Feature Type. I/CAD uses two types: 0 - point feature (intersection) and 1- line feature (street segments, etc)
fweight	number(5,0)	smallint	yes		Feature Weight. Graphic style for element placement.
fwidth	float(126)	float(53)	yes		Text width
is_optional	varchar2(1)	varchar(1)	yes		This field not accessed by I/CAD.
is_repeating	varchar2(1)	varchar(1)	yes		This field is not accessed by I/CAD.
linelength	number(5,0)	smallint	yes		Line length for text.
max_displayscale	number(10,0)	int	yes		This field not accessed by I/CAD.
min_displayscale	number(10,0)	int	yes		This field is not accessed by I/CAD.
mslink	number(10,0)	int	no		Number that links the database record to the street segments.
newdup	number(5,0)	smallint	yes		This field not accessed by I/CAD.
snaptolerance	number(5,0)	smallint	yes		This field is not accessed by I/CAD.
snaptype	number(5,0)	smallint	yes		This field not accessed by I/CAD.
streamdelta	float(126)	float(53)	yes		This field not accessed by I/CAD.
streamtolerance	float(126)	float(53)	yes		This field not accessed by I/CAD.
streamunit	varchar2(15)	varchar(15)	yes		This field not accessed by I/CAD.
tablename	varchar2(32)	varchar(32)	yes		Table Name. Database table that contains attribute data for this feature. In I/CAD, this is either segme or inter.
tcolor	number(5,0)	smallint	yes		Color to be used for text when placing street names for the feature type described by this netfea record.
textunit	varchar2(15)	varchar(15)	yes		Units for text placement.
tlevel	number(5,0)	smallint	yes		Level on which to place text when placing street names for the feature type described by this netfea record
tweight	number(5,0)	smallint	yes		Weight to be assigned to text when placing street names for the feature type described by this netfea record.
use_range	varchar2(1)	varchar(1)	yes		This field not accessed by I/CAD.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
netfea_b_primary_key	fcode			primaryKey	yes

 [Top](#)

Table Name - nmsalarm					
Description	Contains one record for each alarm and alarm cleared notification from the NMS server. This table is used by the Itel_Server_NMS product.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
active_timedate	varchar2(21)	varchar(21)	yes		Time date stamp indicating the ACOM system time that the alarm was reported

alarm_code	varchar2(10)	varchar(10)	yes		Textual numeric code that represents the type of alarm being generated. May be null if not configured
alarm_desc	varchar2(56)	varchar(56)	yes		Description of alarm being generated may be null if not configured
alarm_num	varchar2(20)	varchar(20)	yes		Unique alarm ID generated from the numbr table
alarm_title	varchar2(56)	varchar(56)	yes		Title of alarm being generated may be null if not configured
cdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date and time of Alarm appearance on system.
clear_timestamp	varchar2(21)	varchar(21)	yes		Timestamp indicating the ACOM system time that the alarm was cleared
dev_addr	varchar2(56)	varchar(56)	yes		Newwork address of device reporting the alarm. May be null if not configured.
dev_desc	varchar2(56)	varchar(56)	yes		Description of device reporting the alarm. May be null if not configured.
dev_title	varchar2(56)	varchar(56)	yes		The title of the device reporting the alarm. May be null if not configured.
dev_type	varchar2(56)	varchar(56)	yes		Alphanumeric code that represents the type of device reporting the alarm. May be null if not configured.
eid	number(10,0)	int	yes	positiveNumber	Event ID (EID) number of generated CAD event. May be null if not configured or event not generated.
sever_code	varchar2(10)	varchar(10)	yes		Textual numeric code representing the severity of the alarm being generated. may be null if not
sever_desc	varchar2(56)	varchar(56)	no		Full description of the Severity type. May be null if not configured.
sever_title	varchar2(56)	varchar(56)	yes		Title of alarm being generated may be null if not configured.
site_desc	varchar2(56)	varchar(56)	yes		Full text description of the site generating the Alarm. May be null if not configured.
site_id	varchar2(10)	varchar(10)	yes		The site Id of the Alarm - Should correspond to a special address in CAD
site_title	varchar2(56)	varchar(56)	yes		Alphanumeric Title for site - May be null if not configured
status	varchar2(10)	varchar(10)	yes		Either "Active" for newly generated alarm of "Inactive" for cleared alarm.
sys_desc	varchar2(56)	varchar(56)	yes		Full description of the system reporting the Alarm. May be null if not configured.
sys_id	varchar2(10)	varchar(10)	yes		Ascii Numeric value representing the System Id of the system reporting the Alarm. May be null if not configured.
sys_title	varchar2(56)	varchar(56)	yes		Title of the system reporting the Alarm. May be null if not configured.
sys_type	varchar2(56)	varchar(56)	yes		Alphanumeric code representing the type of device reporting the alarm.
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies rows
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
nmsalarm_cdts	cdts		no	no	
nmsalarm_site_sys_dev_alarm	site_id, sys_id, dev_type, dev_addr, alarm_code		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
nmsalarm_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - noden					
Description	This table holds records for all employees who require access to the I/CAD product. No columns here may be changed within I/CAD. CADDDBM modifies data in this table				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 empid	number(10,0)	int	no		Employee ID. The employee identification number is the unique identifier which links back to the persl record.
 term	varchar2(15)	varchar(15)	no		Terminal Node Name. The terminal(s) at which the employee may run applications. If the employee may run applications on any terminal, an (A) is put in this column.
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
noden_primary key	empid, term		primaryKey		yes

 [Top](#)

Table Name - numbr					
Description	The numbr table provides I/CAD with a means of generating unique sequential numerical identifiers. This table is used to generate a variety of sequences, including Event ID numbers (eid), which are used internally. The rows in this table are created in CADDDBM.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
curent	varchar2(1)	varchar(1)	no	curent in ('O', 'T')	Busy Indicator. This flag prevents waiting on the next available number. The applications set curent='O' to temporarily lock the record.
dsply_msg	varchar2(1)	varchar(1)	yes	booleanTorF	Display Message Flag. A (T) in this column indicates that a realtime message is displayed. If the column contains an (F), no realtime message is displayed.
expire [default = -1]	number(19,0)	bigint	no		The epoch time that the current number sequence expires and needs to rollover to a new sequence
n_num	varchar2(11)	varchar(11)	no		Next Number. The next number to be returned. These numbers must be greater than 0.
 num_id	number(10,0)	int	no		Number ID. The number ID is the unique identifier for the number generator. There MUST be a num_id of zero in the database. Negative values are used internally by CAD. Positive values are used by customers for event numbers, case numbers, etc.
pre_id	varchar2(1)	varchar(1)	yes		Prefix. This is an optional column containing a prefix value that will precede the generated number (for example, f28). The eid generator (num_id = []) requires that this field be empty.
purpose	varchar2(40)	varchar(40)	yes		Purpose. Identifies what the num_id is used for, that is, Broadcast, Alarm, Messages, and so on.
rollover	varchar2(20)	varchar(20)	yes		The format of the number to be used when a rollover occurs due to reaching the time in expire
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
numbr_primary_key	num_id			primaryKey	yes

 [Top](#)

Table Name - oma_mlp_tlr					
Description	This table stores information about I/Tracker's communication with an external tracking system. This table is only used when I/Tracker is configured to use the OMA/MLP interface. CR 1-6PGD42: PLT				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Record creation time
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Is this record still active? T= Yes, F= False
 device_id	varchar2(40)	varchar(40)	no		Device ID
 reqid	varchar2(30)	varchar(30)	no		Request ID
 tracker_system_id [default = 0]	number(5,0)	smallint	no		I/Tracker system identifier. If there are multiple I/Tracker systems talking to different OMA/MLP systems, this identifier ensures that the device ID is unique.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The time when this record was updated
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
oma_mlp_tlr_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered

oma_mlp_tlrr_pk	device_id, reqid, tracker_system_id	primaryKey	yes
-----------------	-------------------------------------	------------	-----

 [Top](#)

Table Name - out_of_service_type						
Description	This table contains unit out-of-service types. Previously, this data was stored in ev_ty where e_u_type = 'U'					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
can_dispatch [default = 'F']	varchar2(1)	varchar(1)	no	booleanTORF	Unit Dispatch Flag. Flag used to indicate if a unit can be dispatched while it is out of service. (T) = can dispatch, (F) = cannot dispatch while out of service.	
eng	varchar2(80)	varchar(80)	yes		English Description. This column contains the textual description of the event type.	
 tycod	varchar2(16)	varchar(16)	no		The unit out-of-service type code.	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
out_of_service_type_pk	tycod			primaryKey	yes	

 [Top](#)

Table Name - out_of_service_type_agency					
Description	This table contains agency-specific (timer) information for unit out-of-service types. This table joins back to out_of_service_type. Previously, this data was stored in ev_ty where e_u_type = 'U'				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency Id
alert_timer [default = 0]	number(10,0)	int	no	alert_timer between 0 and 480	The alert timer. Previously called ev_ty.time1
 tycod	varchar2(16)	varchar(16)	no		The unit out-of-service type code.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
out_of_service_type_ag_pk	ag_id,tycod			primaryKey	yes

 [Top](#)

Table Name - page_cond						
Description	A table to be used for page conditions for a particular page id. page_id will link to the particular pager and expression will define the condition for paging.					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 cond_id	varchar2(12)	varchar(12)	no		A identifier used to link back to the def_page table for a particular condition expression.	
expression	varchar2(240)	varchar(240)	no		The expression to evaluate for TRUE if paging of a particular pager_id is to take place. Must be populated with CADDDBM using keywords as defined in the page_keyword table.	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
page_cond_primary_key	cond_id			primaryKey	yes	

 [Top](#)

Table Name - page_cond1						
Description	A table to be used for page conditions for a particular page id. page_id will link to the particular pager and expression will define the condition for paging.					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 cond_id	varchar2(12)	varchar(12)	no		A identifier used to link back to the def_page table for a particular condition expression.	
expression	varchar2(240)	varchar(240)	no		The expression to evaluate for TRUE if paging of a particular pager_id is to take place. Must be populated with CADDDBM using keywords as defined in the page_keyword table.	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
page_cond1_primary_key	cond_id			primaryKey	yes	

 [Top](#)

Table Name - page_cond_interval					
Description	The time intervals for when page conditions are in effect.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 cond_id	varchar2(12)	varchar(12)	no		The page condition id
from_hour	number(5,0)	smallint	no	from_hour between 0 and 23	The start hour for the interval, 0 - 23
from_minute	number(5,0)	smallint	no	from_minute between 0 and 59	The start minute for the interval, 0 - 59
from_weekday	number(5,0)	smallint	no	from_weekday between 1 and 7	The start day for the interval, 1 - 7 where Sunday is 1
 interval_number	number(5,0)	smallint	no		The interval number that unqiely identifies the interval for a given page condition
to_hour	number(5,0)	smallint	no	to_hour between 0 and 23	The ending hour for the interval, 0 - 23
to_minute	number(5,0)	smallint	no	to_minute between 0 and 59	The ending minute for the interval, 0 - 59
to_weekday	number(5,0)	smallint	no	to_weekday between 1 and 7	The ending day for the interval, 1 - 7 where Sunday is 1
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
page_cond_interval_primary_key	cond_id, interval_number			primaryKey	yes

 [Top](#)

Table Name - page_keyword						
Description	A list of keywords to be used by CADDBM for building page expressions in the page_cond table.					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 keyword	varchar2(25)	varchar(25)	no		Page expression keywords for evaluating to determine if paging is to be done for a particular pager. CADDBM uses this to build the expression field in page_cond table.	
Key Constraints						

Constraint Name	Columns	Constraint Type	Sql Server Clustered
page_keyword_primary_key	keyword	primaryKey	yes

 [Top](#)

Table Name - page_notify_priority					
Description	The pager IDs (which may resolve to an individual pager or pager group) that should be notified whenever an event is created or updated to the event priority, in the given agency/dispatch group, irrespective of its location or type.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency identifier
 dgroup	varchar2(5)	varchar(5)	no		Dispatch group
page_id	varchar2(12)	varchar(12)	yes		Page identifier or page group identifier
 priority	number(10,0)	int	no	priority between 0 and 9	Event priority
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
page_notify_prior_primary_key	ag_id, dgroup, priority			primaryKey	yes

 [Top](#)

Table Name - parse_data					
Description	This table is used to hold stacked event information in a structure that I/CAD can use for processing.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
apt_name	varchar2(80)	varchar(80)	yes		Apartment Number. This column is used to store the number of an apartment if the location address entered was from an apartment complex.
comm	varchar2(240)	varchar(240)	yes		Comments. This column is used to store any comments that may have been entered at the end of the location information entry.
commonplace	varchar2(80)	varchar(80)	yes		Commonplace Name. This column is used to store the common place name if that is what was entered for the event location.
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator Flag. This columnn contains the current record indicator flag. (T) denotes current record whereas (F) indicates an older record.
esz	number(10,0)	int	yes		Emergency Service Zone. This column contains the emergency service zone of the event location.
exp_time	varchar2(16)	varchar(16)	yes	ipsTimestamp	Expiration Time. This column contains the date/time stamp at which the stacked events will expire.
fea_mslink	number(10,0)	int	yes		Segme mslink number.
loc_fld1	varchar2(80)	varchar(80)	yes		Generic location field
majevt_evty	varchar2(10)	varchar(10)	yes		Major Event Type. This column contains the pointer to a major event type.
majevt_loc	varchar2(10)	varchar(10)	yes		Major Event Location. This column contains the pointer to a major event location.
msg	varchar2(2000)	varchar(2000)	yes		Location remarks
parse_error	number(10,0)	int	yes		Parsing Error. This column is used to flag an error that occurred in the Location Verification of the address information that was furnished. Valid values are 0 for no error or 1 for the occurence of an error.
parse_type	number(10,0)	int	yes	parse_type between -1 and 4	Type of Parsing. This column reflects the type of parsing that is done on the location information entered. Valid values are -1 for uninitialized, 0 for street address parsing, 1 for intersection, 2 for common place name, 3 for alarm and 4 for X,Y location.
st1_alias	varchar2(80)	varchar(80)	yes		Street Alias. This column is used to store the alias for the street if one exists.
st1_area	varchar2(80)	varchar(80)	yes		Street Area. This column is used to store the area in which the street is located.
st1_direct	varchar2(80)	varchar(80)	yes		Street Direction. This column is used to store the direction of the street.
st1_fld2	varchar2(80)	varchar(80)	yes		Generic location field
st1_fld3	varchar2(80)	varchar(80)	yes		Generic location field
st1_fld4	varchar2(80)	varchar(80)	yes		Generic location field
st1_mun	varchar2(80)	varchar(80)	yes		Street Municipality. This columnn is used to store the municipality in which the street is located.
st1_name	varchar2(240)	varchar(240)	yes		Street Name. This column is used to store the name of the street.
st1_number	varchar2(80)	varchar(80)	yes		Street Number. This column is used to store the street number of the address.
st1_quad	varchar2(80)	varchar(80)	yes		Street Quadrant. This column is used to store the quadrant in which the street is located.
st1_type	varchar2(80)	varchar(80)	yes		Street Type. This column is used to store the type of the street such as avenue, boulevard, and so on.
st2_alias	varchar2(80)	varchar(80)	yes		Other Street Alias. This column is used to store the alias for the second street if one exists.
st2_area	varchar2(80)	varchar(80)	yes		Other Street Area. This column is used to store the area location of the second street if the location entered was an intersection.
st2_direct	varchar2(80)	varchar(80)	yes		Other Street Direction. This column is used to store the street direction of the second street if the location entered was an intersection.
st2_fld2	varchar2(80)	varchar(80)	yes		Generic location field
st2_fld3	varchar2(80)	varchar(80)	yes		Generic location field
st2_fld4	varchar2(80)	varchar(80)	yes		Generic location field
st2_mun	varchar2(80)	varchar(80)	yes		Other Street Municipality. This column is used to store the municipality of the second street if the location entered was an intersection.
st2_name	varchar2(240)	varchar(240)	yes		Other Street Name. This column is used to store the street name of the second street if the location entered was an intersection.
st2_number	varchar2(80)	varchar(80)	yes		Other Street Number. This column is used to store the street number of the second street if the location entered was an intersection.
st2_quad	varchar2(80)	varchar(80)	yes		Other Street Quadrant. This column is used to store the street quadrant of the second street if the location entered was an intersection.
st2_type	varchar2(80)	varchar(80)	yes		Other Street Type. This column is used to store the street type of the second street if the location entered was an intersection.
 stack_id	number(10,0)	int	no		Stack Identification Number. This column contains a unique number that is assigned to a stacked event so it can be retrieved at a later date for processing.
x_position	number(10,0)	int	yes		X-coordination Position. This column contains the X coordinate position in UORs of the location of the street.
xstreet1	varchar2(240)	varchar(240)	yes		Cross Street. This column is used to store the name of the first cross street if one exists.
xstreet2	varchar2(240)	varchar(240)	yes		Second Cross Street. This column is used to store the name of the second cross street if one exists.
y_position	number(10,0)	int	yes		Y-coordinate Position. This column contains the Y coordinate position in UORs of the location of the event
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
parse_data_primary_key	stack_id			primaryKey	yes

 [Top](#)

Table Name - persl					
Description	The persl table holds a record for each employee who requires access to the I/CAD product or is listed as an employee of a unit. Most of this information is set in CADDBM. I/CAD updates the app_type, logged_on, ldts, lodts and term columns when the user logs on. The pswrd and pass_date columns are updated when the user changes his/her password.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID. The agency ID in the personel table shows the agency for which the employee works (Police, Fire). The info pertaining to the agency is stored in the agenc table. The persl and agenc tables are linked together by the agency ID.
app_type	varchar2(30)	varchar(30)	yes		Application type. This field is set when a person logs on to an application.
bl_typ	varchar2(5)	varchar(5)	yes		Blood Type. The blood type of the employee is stored in this column in case of an emergency.
cad_cmd_mask [default = 0]	number(10,0)	int	no		CAD Command Mask. This column contains the key that limits access to I/CAD commands.
chatid	number(10,0)	int	yes		Contains the CHAT GROUP the user is currently in
curent [default = 'T']	varchar2(1)	varchar(1)	no	booleanTOrF	This column reflects whether the personnel record is active. (T) represents an active employee, (F) represents an inactive employee

dbm_cmd_mask [default = 0]	number(10,0)	int	no		CADDBM Command Mask. This column contains the key that limits access to the CADDBM commands.
default_unid	varchar2(10)	varchar(10)	yes		The default unit id for the employee to use when the employee transfers from one unit to another. The primary purpose of this is to give each employee a unit id if they are acting as a single employee unit.
delex	number(10,0)	int	no	Delex between 0 and 9999	Expiration of Password. The delex column contains the number of days until the expiration of the password.
delno	number(10,0)	int	no	Delno between 0 and 9998	Notification of Password. This column is the number of days from the creation time when the employee is to be notified of the expiration date date of the current password.
domain	varchar2(64)	varchar(64)	yes		User's domain. Used for single sign on domain verification.
email	varchar2(80)	varchar(80)	yes		An email address for this person.
emp_add	varchar2(30)	varchar(30)	yes		Employee's street address.
emp_city	varchar2(20)	varchar(20)	yes		City in which the employee resides.
emp_num	varchar2(16)	varchar(16)	yes		This is an optional employee identifier that can contain letters as well as numbers. The empid column is still used to uniquely identify a person.
emp_st	varchar2(4)	varchar(4)	yes		State in which the employee resides.
 empid	number(10,0)	int	no	nonNegativeNumber	Employee ID. This is the unique identifier of the persl table. It is stored in several tables when the identity of the person who created the record is needed for further information or S/he is assoc with a unit.
fname	varchar2(50)	varchar(50)	yes		First name of the employee.
host_term	varchar2(15)	varchar(15)	yes		Terminal name of host computer for remote session. This is NULL if CAD is running as a normal local process.
ldts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Login Date/Time Stamp. When the employee successfully logs on to I/CAD, the date/ time stamp will be updated in that employee's record. This stamp is formatted for easier reading when the user sees it.
lname	varchar2(50)	varchar(50)	yes		Last name of the employee.
lodts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Logoff Date/Time Stamp. This column contains the date/ time at which the employee successfully logged out of I/CAD.
logged_on [default = 'F']	varchar2(1)	varchar(1)	no	booleanToIF	T indicates the employee is logged on, F indicates the employee is logged off
mi	varchar2(1)	varchar(1)	yes		Middle Initial of the employee.
not_add	varchar2(30)	varchar(30)	yes		Address of Person to Notify in case of an emergency involving the employee.
not_city	varchar2(20)	varchar(20)	yes		City of the person to notify in case of an emergency involving the employee.
not_nme	varchar2(25)	varchar(25)	yes		Name of the person to Notify in case of an emergency involving the employee.
not_ph	varchar2(14)	varchar(14)	yes		Phone number of the person to notify in case of an emergency involving the employee.
not_st	varchar2(4)	varchar(4)	yes		State of the person to notify in case of an emergency involving the employee.
page_id	varchar2(12)	varchar(12)	yes		The Pager ID or Pager Group ID associated with this person.
pass_date	number(19,0)	bigint	no		Date of Password Creation or Password Update. This date is important in finding out when a password will expire or when the employee needs to be notified of the expiration date. The date is stored in epoch seconds.
pcust1	varchar2(50)	varchar(50)	yes		Person custom column 1
pcust2	varchar2(50)	varchar(50)	yes		Person custom column 2
pcust3	varchar2(50)	varchar(50)	yes		Person custom column 3
pcust4	varchar2(50)	varchar(50)	yes		Person custom column 4
phone	varchar2(14)	varchar(14)	yes		Home Telephone Number. This column contains the home phone number in case the employee needs to be contacted when off duty, for example, if s/he is the only one in the department with a certain needed skill.
pid	number(10,0)	int	yes		Process ID, when logged into a remote session. NULL otherwise.
pswrd	varchar2(128)	varchar(128)	yes		Password. For the employee to be able to log on to the I/CAD system, s/he must first enter the right combination of user id and password. If it is incorrect, the employee will not gain access to I/CAD.
pswrd_hash_id	number(10,0)	int	yes	pswrd_hash_id in (0,1,2)	Password hash algorithm ID. 0 = Legacy CDencrypt, 1 = MD5, 2 = SHA512
rms_id	number(10,0)	int	yes		RMS employee ID. Used by CAD-inPURSUIT integration and Business Intelligence to link employee records in the CAD and RMS systems.
soundex	varchar2(4)	varchar(4)	yes		This column contains the soundex value of the employee name.
term	varchar2(15)	varchar(15)	yes		Terminal Node Name. This column contains the terminal node where the employee is currently logged on.
usr_id	varchar2(20)	varchar(20)	no		Users ID.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
persl_logged_on	logged_on		no	no	
persl_pswrd	pswrd		no	no	
persl_term_app_type	term, app_type		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
persl_primary_key	empid		primaryKey		yes
persl_unique	usr_id		uniqueKey		no
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
persl_delex_gt_delno_ck	Yes	Delex > delno		Delex > delno	
persl_pswrd_hash_null_ck	Yes	(pswrd is null and pswrd_hash_id is null) or (pswrd is not null and pswrd_hash_id is not null)		(pswrd is null and pswrd_hash_id is null) or (pswrd is not null and pswrd_hash_id is not null)	

 [Top](#)

Table Name - persl_skill					
Description	The skills that an employee has.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
description	varchar2(80)	varchar(80)	yes		Description or comment regarding this employee's skill.
 empid	number(10,0)	int	no		The employee identifier
 skill	varchar2(8)	varchar(8)	no		A skill that the employee possesses
skill_priority [default = 3]	number(10,0)	int	no	skill_priority between 1 and 5	A relative priority used during unit recommendation to rank skills assigned to a person. Valid values are from 1 to 5, with 1 being the highest priority.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
persl_skill_primary_key	empid, skill			primaryKey	yes

 [Top](#)

Table Name - perso					
Description	The perso table contains person information which is related to the event and is displayed, added, and updated on the Event Supplement Form in I/CAD. Column 2 is user- configurable and may be added to or removed as necessary.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
age	number(10,0)	int	yes		This column contains the age of the person related to the event.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. This column stores the date/ time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.

curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
dob	varchar2(10)	varchar(10)	yes		Date Of Birth. The date that the person related to the event was born.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
eye	varchar2(3)	varchar(3)	yes		Eye color of the person related the event.
hair	varchar2(3)	varchar(3)	yes		Hair color of the person related to the event.
height	number(10,0)	int	yes		Height of the person related to the event.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
nme	varchar2(50)	varchar(50)	yes		Name of the person related to the event.
oln	varchar2(20)	varchar(20)	yes		Operator License Number
race	varchar2(1)	varchar(1)	yes		Race of the person related to the event.
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
sex	varchar2(1)	varchar(1)	yes		Sex of the person related to the event.
soc	varchar2(9)	varchar(9)	yes		Social security number
state	varchar2(2)	varchar(2)	yes		State of the Operator License Number
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
weight	number(10,0)	int	yes		Weight of the person related to the event.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
perso_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
perso_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
perso_primary key	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - print_templates					
Description	Contains print template information, which is used for printing data from I/CAD dialogs				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create date timestamp
template_data	blob	varbinary(max)	yes		This column contains the complete definition of the printing template.
 template_name	varchar2(50)	varchar(50)	no		Name of the template
template_size	number(10,0)	int	no	nonNegativeNumber	Size of the template_data
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
print_templates_primary_key	template_name			primaryKey	yes

 [Top](#)

Table Name - priority_times					
Description	Contains timer values set on events in memory. These timer values are applied when timer values are not defined in the event_type table. Timer values are defined for one to ten priority codes for an agency.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency identifier. An agency can have 1 to 10 records (priorities "0" to "9").
 priority	number(10,0)	int	no	priority between 0 and 9	Priority Number. The event priority code for which the timer values in the record will be applied.
time1 [default = 0]	number(10,0)	int	no	time1 between 0 and 32766	Timer 1, same as in event_type.pending_timer
time2 [default = 0]	number(10,0)	int	no	time2 between 0 and 32766	Timer 2, same as in event_type.dispatch_timer
time3 [default = 0]	number(10,0)	int	no	time3 between 0 and 32766	Timer 3, same as in event_type.enroute_timer
time4 [default = 0]	number(10,0)	int	no	time4 between 0 and 32766	Timer 4, same as in event_type.arrive_timer
time5 [default = 0]	number(10,0)	int	no	time5 between 0 and 32766	Timer 5, same as in event_type.acknowledge_timer
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
priority_times_primary_key	ag_id,priority			primaryKey	yes

 [Top](#)

Table Name - propt					
Description	This table contains property info related to the event and is displayed, added, and updated on the Supplemental Information Form in I/CAD. Col 2 is user-configurable an may be added to or removed as necessary.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
epers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the the personnel identification number of the person who created the record.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The nodename of the terminal from which the record was created.
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Current Record Indicator. The current flag contains a (T) if this is the most recent version of the record, an (F) if it is an older version.
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTOrF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
item	varchar2(10)	varchar(10)	yes		Item Description. This column contains a description of the item not covered by other columns.
remarks	varchar2(20)	varchar(20)	yes		Remarks about the Property. This column stores remarks regarding items of property.

 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the property information will be displayed.
serialnum	varchar2(20)	varchar(20)	yes		Serial Number of the Item.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated the record.
upers	number(10,0)	int	yes	nonNegativeNumber	Updating Person. The ID of the person updating the event.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. The terminal from which the record was updated.
value	varchar2(10)	varchar(10)	yes		Monetary value of the property item.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
propt_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
propt_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
propt_primary_key	cid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - pswrd_hist					
Description	Contains password history information				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Change date/time stamp
 empid	number(10,0)	int	no		Employee id from persl.empid
pswrd	varchar2(128)	varchar(128)	yes		New password
 rev_num	number(10,0)	int	no		Password revision number
usr_id	varchar2(20)	varchar(20)	no		User's id from persl.usr_id
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
pswrd_hist_primary_key	empid, rev_num			primaryKey	yes

 [Top](#)

Table Name - recom_hist					
Description	Contains unit recommendation history				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alarm_lev	number(10,0)	int	no	nonNegativeNumber	Alarm level
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time of insertion
cpers	number(10,0)	int	no		Employee ID of person who created this record
disp_flag	varchar2(1)	varchar(1)	no	booleanYOrN	Y - unit dispatched. N - unit recommended but not dispatched
item_col	number(10,0)	int	no		Item display column in response plan editor that unit was recommended for, or -1 for manually dispatched unit
item_id	number(10,0)	int	no		Item ID unit recommended for, or 1 for manually dispatched unit
item_row	number(10,0)	int	no		Item display row in response plan editor that unit was recommended for, or -1 for manually dispatched unit
num_1	varchar2(12)	varchar(12)	no		Event number
req_name	varchar2(500)	varchar(500)	yes		This is either the requirement group description or a concatenated string of requirement names within the group
resp_plan_unique_id	raw(16)	varbinary(16)	no		UNIQUE_ID of item in RESP_PLAN table that this unit was recommended for
routed_to_unid	varchar2(10)	varchar(10)	yes		When routing between units, specifies the unit ID to which this unit was routed, or NULL if unit was routed straight to event
unid	varchar2(10)	varchar(10)	no		Recommended unit ID
 unique_id	raw(16)	varbinary(16)	no		Unique ID for each row in table
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
recom_hist_Nm1_almlv_unid_itid	num_1, alarm_lev, unid, item_id		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
recom_hist_primary_key	unique_id			primaryKey	no

 [Top](#)

Table Name - remote_event					
Description	This table holds information about events created on remote systems. It is only used by IFCAD.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation date-time stamp of the record.
 external_event_id	varchar2(30)	varchar(30)	no		A unique identifier for the event provided by the remote system.
message	clob	varchar(max)	yes		An artifact exchanged between systems that records information about the event.
message_type	varchar2(32)	varchar(32)	yes		A label distinguishing different kinds of messages.
num_1	varchar2(12)	varchar(12)	no		The agency event number for the local event.
remote_organization_id	varchar2(64)	varchar(64)	no		An identifier for the organization from which the event originated.
remote_organization_name	varchar2(64)	varchar(64)	no		The name of the organization from which the event originated.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The update date-time stamp of the record.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
remote_event_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
remote_event_pk	external_event_id		primaryKey		yes

 [Top](#)

Table Name - remote_event_comments	
Description	This table holds information about comments added to events on remote systems. It tracks which comments have already been added so that duplicates don't occur in the local system. It is only used by IFCAD.
Copy Type	INSERT

Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation date-time stamp of the record.
 comment_id	varchar2(64)	varchar(64)	no		An identifier supplied by a remote system that uniquely identifies a comment for a particular event.
 external_event_id	varchar2(30)	varchar(30)	no		A unique identifier supplied by a remote system for the event associated with the comment.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
remote_event_comments_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
remote_event_comments_pk	external_event_id, comment_id			primaryKey	yes

 [Top](#)

Table Name - resp_plan					
Description	Defines response plans for unit recommendation				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alt_unit_count [default = 0]	number(10,0)	int	no		Number of alternate units to recommend for the requirement group
comm	varchar2(80)	varchar(80)	yes		User-supplied comment string associated with the response plan and displayed during Recommend Unit
cond_type [default = 0]	number(10,0)	int	no	cond_type between 0 and 2	0 - date/time condition, 1 - recommended requirement, 2 - already assigned requirement
failure_item_id	number(10,0)	int	no		ID of next item to process on failure
from_day [default = 0]	number(5,0)	smallint	no	from_day between 0 and 31	From day (1-31). 0 means that day does not factor into the response plan condition.
from_hour [default = 24]	number(5,0)	smallint	no	from_hour between 0 and 24	From hour (0-23). 24 means that neither the hour nor the minute factors into the response plan condition.
from_minute [default = 0]	number(5,0)	smallint	no	from_minute between 0 and 59	From minute (0-59)
from_month [default = 0]	number(5,0)	smallint	no	from_month between 0 and 12	From month (1=January, 12=December). 0 means that the month does not factor into the response plan condition.
from_weekday [default = 7]	number(5,0)	smallint	no	from_weekday between 0 and 7	From weekday (0=Sunday, 6=Saturday). 7 means that the weekday does not factor into the response plan condition.
item_col	number(10,0)	int	no		Item display column in response plan editor
 item_id	number(10,0)	int	no		ID of item within plan
item_row	number(10,0)	int	no		Item display row in response plan editor
item_type	number(10,0)	int	no	item_type between 0 and 3	0 - no-op condition item, 1 - requirement group item, 2 - condition item, 3 - nested response plan item
plan_ref	varchar2(50)	varchar(50)	yes		Descriptive name for nested response plan
recommend_mode [default = 3]	number(10,0)	int	no	recommend_mode in (0,1,3)	Overrides default recommendation mode set for event. 0 - beats, 1 - street network, 3 - use default
req_descrip	varchar2(50)	varchar(50)	yes		Optional description of requirements within a requirement group
req_display_order [default = 0]	number(10,0)	int	no		Optional override for ordering recommended units
req_max_beat [default = 0]	number(10,0)	int	no		Maximum beat for the requirement
req_max_route [default = 0]	float(126)	float(53)	no		Maximum route (distance or time) for the requirement
req_name	varchar2(50)	varchar(50)	yes		Descriptive name for response requirement
 req_number	number(10,0)	int	no	nonNegativeNumber	Requirement number within response plan item beginning with zero
req_quan [default = 0]	number(10,0)	int	no		Requirement quantity
 resp_plan_name	varchar2(50)	varchar(50)	no		Descriptive name for response plan
resp_type [default = 0]	number(10,0)	int	no	resp_type in (0,1)	Response Plan Type. 0 = Normal, 1 = Displayed on Additional Unit Recommend dialog.
success_item_id	number(10,0)	int	no		ID of next item to process on success
to_day [default = 0]	number(5,0)	smallint	no	to_day between 0 and 31	To day (1-31). 0 means that day does not factor into the response plan condition.
to_hour [default = 24]	number(5,0)	smallint	no	to_hour between 0 and 24	To hour (0-23). 24 means that neither the hour nor the minute factors into the response plan condition.
to_minute [default = 0]	number(5,0)	smallint	no	to_minute between 0 and 59	To minute (0-59)
to_month [default = 0]	number(5,0)	smallint	no	to_month between 0 and 12	To month (1=January, 12=December). 0 means that the month does not factor into the response plan condition.
to_weekday [default = 7]	number(5,0)	smallint	no	to_weekday between 0 and 7	To weekday (0=Sunday, 6=Saturday). 7 means that the weekday does not factor into the response plan condition.
unique_id	raw(16)	varbinary(16)	no		Unique ID for each row in table (can be joined to RESP_PLAN_UNIQUE_ID in RECOM_HIST table to identify history records that go with this response plan item)
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
resp_plan_primary_key	resp_plan_name, item_id, req_number			primaryKey	yes
resp_plan_unique	unique_id			uniqueKey	no

 [Top](#)

Table Name - resp_plan_poly					
Description	Defines response plans for polygons contained in a special response plan polygon file used by unit recommendation. Added for CAD 9.1 Recommend Unit CRs.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Event's agency
 alarm_lev	number(10,0)	int	no		Event's alarm level
comm	varchar2(80)	varchar(80)	yes		Special dispatching info
 polygon_id	number(10,0)	int	no		ID of polygon from response plan polygon file
resp_plan_name	varchar2(50)	varchar(50)	no		Response plan to use
 sub_tycode [default = 'default']	varchar2(16)	varchar(16)	no		Event's subtype code
 tycode	varchar2(16)	varchar(16)	no		Event's type code
Key Constraints					

Constraint Name	Columns	Constraint Type	Sql Server Clustered
resp_plan_poly_pk	ag_id, tycode, sub_tycode, alarm_lev, polygon_id	primaryKey	yes

[Top](#)

Table Name - resp_req						
Description	Defines response requirements used in response plans					
Copy Type	ALL_WITH_CHECK					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
attr_opt	number(10,0)	int	no	booleanNumber1Or0	0 - unit must match all attributes, 1 - unit must match at least one attribute	
beat_opt	number(10,0)	int	no	beat_opt between 0 and 3	0 - unit can come from any beat, 1 - unit can only come from primary beat, 2 - unit can only come from backup beat, 3 - unit can only come from beat defined in this criteria row (LEV3 must be non-null)	
ext_unitattr	raw(32)	varbinary(32)	no	lengthb(ext_unitattr) = 64	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).	
has_res	number(10,0)	int	no	booleanNumber1Or0	0 - criteria does not include equipment or skills. 1 - criteria includes equipment and/or skills	
lev3	varchar2(7)	varchar(7)	yes		Beat criteria	
 line_number	number(10,0)	int	no	nonNegativeNumber	Criteria line number within requirement definition, with zero being the first line	
quan	number(10,0)	int	no		Criteria quantity	
 req_name	varchar2(50)	varchar(50)	no		Descriptive name for response requirement	
resource_restrict [default = 1]	number(10,0)	int	no	resource_restrict in (0,1)	Defines the way equipment and skills are matched to units. 0 - equipment and skills must come from a single unit, 1 - equipment and skills can come from any unit	
route_target [default = 0]	number(10,0)	int	no	route_target in (0,1)	Defines the target where the unit will be routed. 0 - route to event, 1 - route to next unit in requirement	
same_beat	number(10,0)	int	no	same_beat between 0 and 2	0 - units recommended for this requirement can come from any beat. 1 - units recommended for this requirement must come from same beat. 2 - units recommended for this requirement must come from different beats	
skill_restrict [default = 0]	number(10,0)	int	no	skill_restrict in (0,1)	Defines the way skills are filled by personnel. 0 - skills can be filled by any person, 1 - each skill requires a unique person	
station	varchar2(10)	varchar(10)	yes		Station ID criteria	
unid	varchar2(10)	varchar(10)	yes		Unit ID criteria	
unityp	varchar2(6)	varchar(6)	yes		Unit type criteria	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
resp_req_primary_key	req_name, line_number			primaryKey	yes	

[Top](#)

Table Name - resp_req_res						
Description		Defines resources included in response requirements				
Copy Type		ALL_WITH_CHECK				
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 line_number	number(10,0)	int	no	nonNegativeNumber	Criteria line number within requirement definition beginning with zero	
 req_name	varchar2(50)	varchar(50)	no		Descriptive name for response requirement	
res_name	varchar2(10)	varchar(10)	no		Resource name	
 res_order	number(10,0)	int	no	nonNegativeNumber	Order of resource within criteria beginning with zero	
res_type	number(10,0)	int	no	res_type between 1 and 2	Resource type. 1 - equipment resource, 2 - skills resource	
Key Constraints						
Constraint Name		Columns		Constraint Type		Sql Server Clustered
resp_req_res_primary_key		req_name, line_number, res_order		primaryKey		yes

[Top](#)

Table Name - resp_tme						
Description		The resp_tme table defines the estimated time of arrival for an agency and dispatch group based on the day of the week and the hour of the day. The data in this table can be managed using the Deployment-> ETA Table command in CADDBM.				
Copy Type		ALL_WITH_CHECK				
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
 ag_id	varchar2(9)	varchar(9)	no		Agency Identification. This column stores the name of the agency.	
 dgroup	varchar2(5)	varchar(5)	no		Dispatch Group. This column defines the dispatch group.	
 dow	varchar2(1)	varchar(1)	no	dow between 1 and 7	Day of the Week. This column defines the day of the week, where 1 = Sunday and 7 = Saturday.	
eta	number(10,0)	int	no		Estimated Time of Arrival. This column defines the estimated time of arrival for a given time on a given day of the week.	
 hod	varchar2(2)	varchar(2)	no		Hour of the Day. This column defines the hour of the day in military time.	
Key Constraints						
Constraint Name		Columns			Constraint Type	Sql Server Clustered
resp_tme_primary_key		ag_id, dgroup, dow, hod			primaryKey	yes

[Top](#)

Table Name - road_restrict						
Description	Road restrictions that override the base values in cd_edge. Added for CR 1-4UUSBR - Road Restrictions.					
Copy Type	ALL					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
active	varchar2(1)	varchar(1)	no	booleanTorF	T/ F, indicates if restriction is active	
average_speed	number(5,0)	smallint	yes	positiveNumber	The average speed that should be applied to all of the segments in the restriction	
base_average_speed	number(5,0)	smallint	no	nonNegativeNumber	The base average speed for all of the segments in the restriction	
base_total_travel_time	binary_double	float(53)	yes	nonNegativeNumber	The base total travel time for a restriction that corresponds to a route	
calltaker_notified	varchar2(20)	varchar(20)	yes		Calltaker that was notified of the restriction	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	When the restriction was created	
cpers	number(10,0)	int	no	nonNegativeNumber	The person that created the restriction	
cterm	varchar2(15)	varchar(15)	no		The terminal that created the restriction	
dest_segment_id	number(10,0)	int	yes		The destination segment for a route	
dest_use_from_node	varchar2(1)	varchar(1)	yes	booleanTorF	T if using from node, F is using to node	
direction	varchar2(10)	varchar(10)	yes	direction in ('TW','OWFS','OWFD','C')	TW = Two Way, OWFS = One Way From Source, OWFD = One Way From Dest, C = Closed	
notify_source	varchar2(40)	varchar(40)	yes		Source of notification	
remarks	varchar2(80)	varchar(80)	yes		Remarks for the restriction	

 restrict_id	raw(16)	varbinary(16)	no		A unique identifier that uniquely identifies a restriction
restrict_name	varchar2(60)	varchar(60)	no		A name that uniquely identifies the restriction
restrict_shape	varchar2(10)	varchar(10)	no	restrict_shape in ('route','fence')	Route or Fence
restrict_type	varchar2(30)	varchar(30)	no		One of the values from the RoadRestrictionType parameter table
source_segment_id	number(10,0)	int	no		The source node for a route
source_use_from_node	varchar2(1)	varchar(1)	no	booleanTorF	T if using from node, F if using to node
speed_limit	number(5,0)	smallint	yes	positiveNumber	The speed limit that should be applied to all of the segments in the restriction
total_travel_time	binary_double	float(53)	yes	positiveNumber	The total travel time for a restriction that corresponds to a route
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
road_restrict_pk	restrict_id			primaryKey	yes
road_restrict_uk	restrict_name			uniqueKey	no
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
road_restrict_fence_ck	Yes	restrict_shape <> 'fence' or (dest_segment_id is null and dest_use_from_node is null and base_total_travel_time is null and total_travel_time is null and (direction is null or direction = 'C'))		restrict_shape <> 'fence' or (dest_segment_id is null and dest_use_from_node is null and base_total_travel_time is null and total_travel_time is null and (direction is null or direction = 'C'))	
road_restrict_max_restrict_ck	Yes	(average_speed is null and speed_limit is null) or (average_speed is null and total_travel_time is null) or (speed_limit is null and total_travel_time is null)		(average_speed is null and speed_limit is null) or (average_speed is null and total_travel_time is null) or (speed_limit is null and total_travel_time is null)	
road_restrict_min_restrict_ck	Yes	average_speed is not null or speed_limit is not null or total_travel_time is not null or direction is not null		average_speed is not null or speed_limit is not null or total_travel_time is not null or direction is not null	
road_restrict_route_ck	Yes	restrict_shape <> 'route' or (dest_segment_id is not null and dest_use_from_node is not null and base_total_travel_time is not null)		restrict_shape <> 'route' or (dest_segment_id is not null and dest_use_from_node is not null and base_total_travel_time is not null)	

 [Top](#)

Table Name - road_restrict_hist					
Description	Records the changes that have been made to road restrictions. Added for CR 1-4UUSBR - Road Restrictions.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
active	varchar2(1)	varchar(1)	no	booleanTorF	T/ F, indicates if restriction is active
average_speed	number(5,0)	smallint	yes	positiveNumber	The average speed that should be applied to all of the segments in the restriction
base_average_speed	number(5,0)	smallint	no	nonNegativeNumber	The average speed that should be applied to all of the segments in the restriction
base_total_travel_time	binary_double	float(53)	yes	nonNegativeNumber	The base total travel time for a restriction that corresponds to a route
calltaker_notified	varchar2(20)	varchar(20)	yes		Calltaker that was notified of the restriction.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	When the restriction was changed
 change_id	raw(16)	varbinary(16)	no		Uniquely identifies each row in the table
change_type	varchar2(10)	varchar(10)	no	change_type in ('insert','update','delete')	Insert, Update, or Delete
cpers	number(10,0)	int	no	nonNegativeNumber	The person that changed the restriction
cterm	varchar2(15)	varchar(15)	no		The terminal that changed the restriction
dest_segment_id	number(10,0)	int	yes		The destination segment for a route
dest_use_from_node	varchar2(1)	varchar(1)	yes	booleanTorF	T if using from node, F is using to node
direction	varchar2(10)	varchar(10)	yes	direction in ('TW','OWFS','OWFD','C')	TW = Two Way, OWFS = One Way From Source, OWFD = One Way From Dest, C = Closed
notify_source	varchar2(40)	varchar(40)	yes		Source of notification
remarks	varchar2(80)	varchar(80)	yes		Remarks for the restriction
restrict_id	raw(16)	varbinary(16)	no		The unique identifier that uniquely identifies a restriction
restrict_name	varchar2(60)	varchar(60)	no		The name that uniquely identified a restriction before it was removed
restrict_shape	varchar2(10)	varchar(10)	no	restrict_shape in ('route','fence')	Route or Fence
restrict_type	varchar2(30)	varchar(30)	no		One of the values from the RoadRestrictionType parameter table
source_segment_id	number(10,0)	int	no		The source segment for a route
source_use_from_node	varchar2(1)	varchar(1)	no	booleanTorF	T if using from node, F if using to node
speed_limit	number(5,0)	smallint	yes	positiveNumber	The speed limit that should be applied to all of the segments in the restriction
total_travel_time	binary_double	float(53)	yes	positiveNumber	The total travel time for a restriction that corresponds to a route
Indexes					
Index Name	Columns		Is Unique		Sql Server Clustered
road_restrict_hist_cdts	cdts		no		no
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
road_restrict_hist_pk	change_id			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
road_res_hist_fence_ck	Yes	restrict_shape <> 'fence' or (dest_segment_id is null and dest_use_from_node is null and base_total_travel_time is null and total_travel_time is null and (direction is null or direction = 'C'))		restrict_shape <> 'fence' or (dest_segment_id is null and dest_use_from_node is null and base_total_travel_time is null and total_travel_time is null and (direction is null or direction = 'C'))	
road_res_hist_max_restrict_ck	Yes	(average_speed is null and speed_limit is null) or (average_speed is null and total_travel_time is null) or (speed_limit is null and total_travel_time is null)		(average_speed is null and speed_limit is null) or (average_speed is null and total_travel_time is null) or (speed_limit is null and total_travel_time is null)	
road_res_hist_min_restrict_ck	Yes	average_speed is not null or speed_limit is not null or total_travel_time is not null or direction is not null		average_speed is not null or speed_limit is not null or total_travel_time is not null or direction is not null	
road_res_hist_route_ck	Yes	restrict_shape <> 'route' or (dest_segment_id is not null and dest_use_from_node is not null and base_total_travel_time is not null)		restrict_shape <> 'route' or (dest_segment_id is not null and dest_use_from_node is not null and base_total_travel_time is not null)	

 [Top](#)

Table Name - road_restrict_seg					
Description	The segments associated with current restrictions. Added for CR 1-4USBR - Road Restrictions.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 map_segment_id	number(10,0)	int	no		The segment id from segme that is being restricted
 restrict_id	raw(16)	varbinary(16)	no		Uniquely identifies a restriction
segment_order	number(10,0)	int	yes		The order in which the segments are traversed for a route
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
road_restrict_seg_pk	restrict_id, map_segment_id			primaryKey	yes
road_restrict_seg_uk	map_segment_id			uniqueKey	no

 [Top](#)

Table Name - road_restrict_seg_hist	
Description	The segments associated with current and removed restrictions. Added for CR 1-4UUSBR - Road Restrictions.
Copy Type	INSERT

Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	When this restriction segment was removed
 map_segment_id	number(10,0)	int	no		The segment id from segme that is being restricted
 restrict_id	raw(16)	varbinary(16)	no		Uniquely identifies a restriction
segment_order	number(10,0)	int	yes		The order in which the segments are traversed for a route
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
road_restrict_seg_hist_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
road_restrict_seg_hist_pk	restrict_id, map_segment_id			primaryKey	yes

 [Top](#)

Table Name - roster					
Description	The roster table defines for each agency its employees, their work schedule and days off, their workshift, and the unit each is assigned to. This table provides the information from which the lineups are created.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency Identification. This column defines the name of the agency.
carid	varchar2(12)	varchar(12)	yes		Vehicle ID
daysoff	varchar2(7)	varchar(7)	yes	regexp_like(daysoff, '[1-7]{0,7}')	Days Off. This column defines the days off for each employee, where 1 = Sunday and 7 = Saturday.
descript	varchar2(80)	varchar(80)	yes		Description. This column contains descriptive information about the roster
 empid	number(10,0)	int	no	nonNegativeNumber	Employee ID. This column contains the personnel identification number for the employee.
 roster_name	varchar2(30)	varchar(30)	no		Roster Name. This column contains the name of the roster.
 unid	varchar2(10)	varchar(10)	no		Unit ID. This column contains the unit identification, usually the call letters.
work_shift	varchar2(5)	varchar(5)	yes		Work Shift. This column defines the workshift for each employee assignment.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
roster_primary_key	roster_name,empid,unid			primaryKey	yes

 [Top](#)

Table Name - rot equip					
Description	The rot equip table is populated via CADDDBM. It contains the rotational service equipment availability details for each company in the rotate table. The Rotational Service comands in CAD may update the last_dts, save_last_dts and select_flag columns.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 comp_id	number(10,0)	int	no	positiveNumber	Company ID. This is a unique, system-generated number designated by num_id of -6 in the numbr table. This is initiated at one(1).
 equip	varchar2(10)	varchar(10)	no		Equipment. This column defines the equipment type offered by the company.
esz	number(10,0)	int	yes	nonNegativeNumber	Emergency Service Zone. This column defines the Emergency Service Zone in which the company responds to calls.
fri_fr [default = 0]	number(10,0)	int	no	fri_fr between 0 and 2400	Friday From Time. Beginning hour of operation on Friday.
fri_to [default = 2400]	number(10,0)	int	no	fri_to between 0 and 2400	Friday To Time. Closing hour of operation on Friday.
last_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Last Date/Time Stamp. This column defines the date/time stamp at which the company was last used. CAD uses last_dts to order equipment when it needs to pick a piece of equipment for a job.
main_type	varchar2(8)	varchar(8)	yes		Main Type of Service. This column contains the main type of service offered by the company.
mon_fr [default = 0]	number(10,0)	int	no	mon_fr between 0 and 2400	Monday From Time. Beginning hour of operation on Monday.
mon_to [default = 2400]	number(10,0)	int	no	mon_to between 0 and 2400	Monday To Time. Closing hour of operation on Monday.
rot_status [default = 'Y']	varchar2(1)	varchar(1)	no	booleanYOrN	Y/N flag for of service acceptance.
row_id	number(10,0)	int	no		Row ID. This column defines the row in the multigadget control where the information is to be displayed. When inserting new rows, CADDDBM sets row_id based on the order in which the equipment is listed in the Equipment Record control on the Rotational Services dialog.
sat_fr [default = 0]	number(10,0)	int	no	sat_fr between 0 and 2400	Saturday From Time. Beginning hour of operation on Saturday.
sat_to [default = 2400]	number(10,0)	int	no	sat_to between 0 and 2400	Saturday To Time. Closing hour of operation on Saturday.
save_last_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Resets dts in case of reassignment.
select_flag [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Select Flag. This column defines whether the service is currently selected.
subserv_type	varchar2(8)	varchar(8)	yes		Secondary Service. This column defines the secondary type of service offered by the company.
sun_fr [default = 0]	number(10,0)	int	no	sun_fr between 0 and 2400	Sunday From Time. Beginning hour of operation on Sunday.
sun_to [default = 2400]	number(10,0)	int	no	sun_to between 0 and 2400	Sunday To Time. Closing hour of operation on Sunday.
thur_fr [default = 0]	number(10,0)	int	no	thur_fr between 0 and 2400	Thursday From Time. Beginning hour of operation on Thursdays.
thur_to [default = 2400]	number(10,0)	int	no	thur_to between 0 and 2400	Thursday To Time. Closing hour of operation on Thursdays.
tue_fr [default = 0]	number(10,0)	int	no	tue_fr between 0 and 2400	Tuesday From Time. Beginning hour of operation on Tuesdays.
tue_to [default = 2400]	number(10,0)	int	no	tue_to between 0 and 2400	Tuesday To Time. Closing hour of operation on Tuesdays.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp
updt_term	varchar2(15)	varchar(15)	yes		Locking terminal
upers	number(10,0)	int	yes	nonNegativeNumber	ID of person who last updated the corresponding record.
uterm	varchar2(15)	varchar(15)	yes		Terminal which updated the rotational equipment record.
wed_fr [default = 0]	number(10,0)	int	no	wed_fr between 0 and 2400	Wednesday From Time. Beginning hour of operation on Wednesdays.
wed_to [default = 2400]	number(10,0)	int	no	wed_to between 0 and 2400	Wednesday To Time. Closing hour of operation on Wednesdays.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
rot equip primary key	comp_id,equip			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
rot equip fri ck	Yes	fri_fr <= fri_to		fri_fr <= fri_to	
rot equip mon ck	Yes	mon_fr <= mon_to		mon_fr <= mon_to	
rot equip sat ck	Yes	sat_fr <= sat_to		sat_fr <= sat_to	

rot equip_sun_ck	Yes	sun_fr <= sun_to	sun_fr <= sun_to
rot equip_thur_ck	Yes	thur_fr <= thur_to	thur_fr <= thur_to
rot equip_tue_ck	Yes	tue_fr <= tue_to	tue_fr <= tue_to
rot equip_wed_ck	Yes	wed_fr <= wed_to	wed_fr <= wed_to

 [Top](#)

Table Name - rot_hist					
Description	This table contains the Rotational Services History information				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation date-time stamp that will hold the date when the given record was created (format YYYYMMDDHHMMSSZZ)
comp_id	number(10,0)	int	no	positiveNumber	The Company ID value
cpers	number(10,0)	int	no	nonNegativeNumber	The i.d. of the operator who created the given record (cf. column "empid" of "persl" table)
cterm	varchar2(15)	varchar(15)	no		Terminal i.d. of the terminal that created the given record
eid	number(10,0)	int	no	nonNegativeNumber	The System Event ID of the event requiring service (cf. column "eid" of "common_event" table). A value of 0 indicates that there is no associated event.
equip	varchar2(10)	varchar(10)	no		Will hold equipment type
est_time	number(10,0)	int	no		Will hold estimated time of arrival (eta)
location	varchar2(80)	varchar(80)	no		Service location
main_type	varchar2(8)	varchar(8)	yes		Main service type requested
person_con	varchar2(25)	varchar(25)	yes		Name of person contacted
reason	varchar2(8)	varchar(8)	yes		Reason for service
remarks	varchar2(80)	varchar(80)	yes		Remarks concerning service
rot_code	varchar2(8)	varchar(8)	no		Service code
subserv_type	varchar2(8)	varchar(8)	yes		Sub service type requested
unid	varchar2(10)	varchar(10)	yes		Unit ID requesting service
 unique_id	raw(16)	varbinary(16)	no		Unique identifier
vehic_desc	varchar2(80)	varchar(80)	yes		Description of vehicle which was serviced.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
rot_hist_cdts	cdts		no	no	
rot_hist_eid	eid		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
rot_hist_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - rotate					
Description	The rotate table is used to store information about the companies to be accessed for rotational services. The information is displayed in I/CAD using the Rotational Services Summary command. The Towing WPF dialogs in I/CAD also use the rotate table.				
Copy Type	ALL WITH CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
active_after_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date/time after which this company becomes active. By specifying a date/time in the near future, a user can temporarily mark a company as inactive. This column replaces the old curent column.
address	varchar2(80)	varchar(80)	yes		Company address
 comp_id	number(10,0)	int	no	positiveNumber	Company ID. This is a unique, system-generated number designated by num_id of -6 in the numbr table. This is initiated at one(1).
comp_name	varchar2(30)	varchar(30)	no		Company Name. This column contains the company name.
contact	varchar2(50)	varchar(50)	yes		Company contact information
default_tow_loc_ver [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Flag indicating if the company's default tow location was verified. T= location verified, F= location was not verified
default_tow_location	varchar2(80)	varchar(80)	yes		The default tow location for this company.
editor_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Rotation editor datetime stamp for this company
editor_pers	number(10,0)	int	yes	nonNegativeNumber	Rotation editor employee id for this company
editor_term	varchar2(15)	varchar(15)	yes		Rotation editor terminal for this company
instructions	varchar2(250)	varchar(250)	yes		Company special instructions
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
rotate_primary_key	comp_id			primaryKey	yes
rotate_unique	comp_name			uniqueKey	no

 [Top](#)

Table Name - rotate_phone					
Description	Phone Numbers for a rotational service company				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 comp_id	number(10,0)	int	no	positiveNumber	Company ID
 phone	varchar2(20)	varchar(20)	no		Phone number
phone_type	varchar2(15)	varchar(15)	no		Phone type
priority	number(5,0)	smallint	no		Phone number sort priority, starts with zero as the highest priority
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
rotate_phone_pk	comp_id, phone			primaryKey	yes
rotate_phone_uk	comp_id, priority			uniqueKey	no

 [Top](#)

Table Name - run_card					
Description	Contains run card definitions tied to deployment table, event type and beat/ESZ				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alarm_lvl	number(10,0)	int	no	nonNegativeNumber	Alarm level for unit

card_comment	varchar2(50)	varchar(50)	yes		User-supplied comment associated with run card definition (will be NULL except in the first row of run card definition)
 deplo_plan_name	varchar2(30)	varchar(30)	no		Deployment plan name that this run card is associated with
 esz	number(10,0)	int	no		ESZ, or -1 if record associated with a beat (LEV3 column cannot be "**")
 lev3	varchar2(7)	varchar(7)	no		Beat name, or "*" if record associated with an ESZ (ESZ column cannot be -1)
 sub_tycod	varchar2(16)	varchar(16)	no		Event subtype, or "default" if none
 tycod	varchar2(16)	varchar(16)	no		Event type for run card, or "default" if none
unit	varchar2(10)	varchar(10)	no		ID of unit assigned to run card
 unit_order	number(10,0)	int	no	nonNegativeNumber	Unit's order within alarm, beginning with zero
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
run_card_primary_key	deplo_plan_name, lev3, esz, tycod, sub_tycod, alarm_lev, unit_order		primaryKey		yes

 [Top](#)

Table Name - s_calendar					
Description	This table holds the scheduling information for CAD events created as scheduled.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
appt_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date-time stamp for the scheduled event appointment (this is an informational field only - not used in functionality)
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date-time stamp when the given record was created (in format YYYYMMDDHHMMSSZZ)
comm	varchar2(256)	varchar(256)	yes		Stores a comment for recurring events.
cpers	number(10,0)	int	no	nonNegativeNumber	The employee ID of the operator who created the given record (cf. column "empid" of "persl" table)
create_pers	number(10,0)	int	no	nonNegativeNumber	The employee id of the person who originally created scheduled event - will not change when row is updated
create_term	varchar2(15)	varchar(15)	no		The terminal where scheduled event was originally created - will not change when row is updated
cterm	varchar2(15)	varchar(15)	no		The terminal i.d. of the terminal that created the given record
curent	varchar2(1)	varchar(1)	no	booleanToF	Active record flag. Flag is set to "T" if this is the active record, and to "F" if this is a history record. "O" is used to temporarily lock the record.
event_no	varchar2(12)	varchar(12)	yes		The active CAD event (num_1 in the agency_event table) that corresponds to this schedule
is_cancelled [default = 'F']	varchar2(1)	varchar(1)	no	booleanToF	Is Cancelled. When T, scheduled event has been cancelled. When F, scheduled event is active.
next_schedid	varchar2(12)	varchar(12)	yes		Scheduled event id of next event for recurring event.
prev_schedid	varchar2(12)	varchar(12)	yes		Scheduled event id of previous event for recurring event.
return_schedid	varchar2(12)	varchar(12)	yes		Scheduled event id of the related event for round-trip event
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
rqst_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date-time stamp for the time requested for pick-up of the patient (what the caller requested) - the actual scheduled pick-up time will be found in the "sched_dts" column
sched_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date-time stamp of the time that the patient pick-up is scheduled for (which may be different than the time that had been requested by the patient - see "rqst_dts" column)
 sched_id	varchar2(12)	varchar(12)	no		The unique scheduled i.d. of the scheduled event that this specific record is associated with
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date-time stamp of the last time the given record had been updated (in format YYYYMMDDHHMMSSZZ)
unit	varchar2(10)	varchar(10)	yes		The unit i.d. of the unit that the event (when generated into a CAD event) will be held for
upers	number(10,0)	int	yes	nonNegativeNumber	The i.d. of the operator who last updated the given record (cf. column "empid" of "persl" table)
uterm	varchar2(15)	varchar(15)	yes		The terminal i.d. of the terminal that last updated the given record
xcmt	varchar2(20)	varchar(20)	yes		The closing comment when the given scheduled event has been cancelled
xdts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date-time stamp of the time when the given scheduled event had been cancelled (in format YYYYMMDDHHMMSSZZ)
xpers	number(10,0)	int	yes	nonNegativeNumber	The i.d. of the operator that was responsible for cancelling the given scheduled event (cf. column "empid" of "persl" table)
xterm	varchar2(15)	varchar(15)	yes		The name of the terminal that cancelled the given scheduled event
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
s_calendar_cdtsudts	cdts, udts		no	no	
s_calendar_event_no_curent_dts	event_no, curent, xdts, sched_dts		no	no	
s_calendar_sch_dts_cur_canc_ev	sched_dts, curent, is_cancelled, event_no		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
s_calendar_pk	sched_id, rev_num			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
s_calendar_xdts_is_cancelled	Yes	(xdts is null and is_cancelled='F') or (xdts is not null and is_cancelled='T')		(xdts is null and is_cancelled='F') or (xdts is not null and is_cancelled='T')	

 [Top](#)

Table Name - save_abandon					
Description	Abandoned event data. When a user chooses to abandon an event in Dispatcher, and the SaveAbandonInfo parameter in the cad GeneralDetails parameter list is on, Dispatcher will write data from the Event Information form to the save_abandon table.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 abandon_id	number(10,0)	int	no		Uniquely identifies an abandoned event
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/time stamp
cpers	number(10,0)	int	no	nonNegativeNumber	Creating operator employee id
cterm	varchar2(15)	varchar(15)	no		Creating terminal node
g_col	number(10,0)	int	no		Gadget column number
g_row	number(10,0)	int	no		Gadget row number
g_text	varchar2(4000)	varchar(4000)	yes		Gadget text
gadget	number(10,0)	int	no		Gadget id number
gui_type [default = 1]	number(5,0)	smallint	no	gui_type in (1,2)	Indicates the type of GUI associated with the data, 1 = MFC, 2 = WPF
 row_num	number(10,0)	int	no		Enumerates the rows for a given abandon_id
s_form	varchar2(40)	varchar(40)	yes		This column contains the form id or name
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
save_abandon_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered

save_abandon_primary_key abandon_id,row_num		primaryKey	yes
Check Constraints			
Constraint Name	Required	Oracle Definition	Sql Server Definition
save_abandon_ck	Yes	gui_type = 1 or (g_col = 0 and g_row = 0 and gadget = 0)	gui_type = 1 or (g_col = 0 and g_row = 0 and gadget = 0)

 [Top](#)

Table Name - save_stack					
Description	This table is used to save information about events that have been stacked (stored) within the I/CAD system for later processing. This allows pertinent information regarding the stacked event to not have to be re-entered again.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
g_col	number(10,0)	int	no		Gadget column number
g_row	number(10,0)	int	no		Gadget row number
g_text	varchar2(4000)	varchar(4000)	yes		The text on the gadget
gadget	number(10,0)	int	no		Gadget number on the form
gui_type [default = 1]	number(5,0)	smallint	no	gui_type in (1,2)	Indicates the type of GUI associated with the data, 1 = MFC, 2 = WPF
s_form	varchar2(40)	varchar(40)	yes		This column contains the form id or name
stack_id	number(10,0)	int	no		This is a unique number that is assigned to a stacked event so it can be retrieved at a later date for processing.
term	varchar2(15)	varchar(15)	no		Creating terminal node
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Uniquely identifies each row in the table
updt_flag	varchar2(15)	varchar(15)	no		Contains the update terminal or NULLTERM if it is not locked
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
save_stack_stack_id	stack_id		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
save_stack_pk	unique_id			primaryKey	no
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
save_stack_ck		Yes	gui_type = 1or (g_col = 0 and g_row = 0 and gadget = 0)		gui_type = 1or (g_col = 0 and g_row = 0 and gadget = 0)

 [Top](#)

Table Name - save_vw					
Description	This table contains the description of saved map views.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
autolevels	varchar2(64)	varchar(64)	yes		Autolevel setting for each map level.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create data/time stamp. The time at which this record was inserted into the database.
cpers	number(10,0)	int	no	nonNegativeNumber	ID of person saving the view.
cterm	varchar2(15)	varchar(15)	no		Creating terminal. Nodename of the terminal on which the view was saved.
deleted	varchar2(1)	varchar(1)	no	booleanTOrF	T if record (view) is deleted, F otherwise
has_ras	varchar2(1)	varchar(1)	no	booleanTOrF	T if raster files attached, F otherwise
has_ref	varchar2(1)	varchar(1)	no	booleanTOrF	T if reference files attached, F otherwise
levels	varchar2(64)	varchar(64)	no		Either A for autolevels, or a string of 64 ones and zeros for levels on and off.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update (delete) date/time stamp
upers	number(10,0)	int	yes	nonNegativeNumber	ID of person updating (deleting) the record
uterm	varchar2(15)	varchar(15)	yes		Terminal updating (deleting) the record.
 view_index	number(10,0)	int	no		Unique index, generated from the number table. This is the join column with svvw_ref and svvw_ras.
view_name	varchar2(32)	varchar(32)	no		Name of the view.
x_max	number(10,0)	int	no		Corner of the view, in UORs
x_min	number(10,0)	int	no		Corner of the view, in UORs
y_max	number(10,0)	int	no		Corner of the view, in UORs
y_min	number(10,0)	int	no		COrner of the view, in UORs
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
save_vw_primary_key	view_index			primaryKey	yes

 [Top](#)

Table Name - scheduled_dest						
Description		This table contains destinations for scheduled items referred to by the item number.				
Copy Type		ALL				
Columns						
Column Name		Oracle Type	Sql Server Type	NULL	Constraint	Description
	destination	varchar2(80)	varchar(80)	no		Destination name for scheduled item.
	item_number	number(10,0)	int	no		Scheduled item number from the scheduled_item table
Key Constraints						
Constraint Name		Columns		Constraint Type		Sql Server Clustered
scheduled_dest_primary_key		item_number, destination		primaryKey		yes

 [Top](#)

Table Name - scheduled_hist					
Description	This table contains information about the history of scheduler execution. This table is used only when the WriteHistory parameter in the sched GeneralDetails parameter list is set to Y.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		The unique identifier for the agency with which the scheduled item is associated.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation date/time stamp at which the record was created.
cmpl_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date/time stamp at which the scheduled item completed its final execution.
cpers	number(10,0)	int	no	nonNegativeNumber	The personnel identification number of the person who created this record.
cpid	number(10,0)	int	no		The process ID number of the scheduler process from which this record was created.
cterm	varchar2(15)	varchar(15)	no		The node name of the terminal from which this record was created.
dest_type	varchar2(1)	varchar(1)	yes	dest_type in ('0', '1','2', '3', '4', '5', '6', '7', '8', '9')	Type of destination for item. 0 = All, 1= Terminal, 2 = Dispatch group, 3 = Group, 4 = Bgroup, 5 = Unit, 6 = Verbal, 7 = Remote, 8 = Pager, 9 = Station
destination	varchar2(80)	varchar(80)	yes		The destination group to which the scheduled item was sent.

exec_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date/time stamp at which this instance of the scheduled item was scheduled to execute.
item	varchar2(240)	varchar(240)	yes		The actual item scheduled for execution. The field may contain a message scheduled to be sent, a command scheduled to executed and so on.
item_number	number(10,0)	int	no		The system generated number assigned to each scheduled item.
item_type	varchar2(1)	varchar(1)	no		The type of item which was scheduled.
sched_count	number(10,0)	int	no		The number of times that the item was scheduled to execute.
status_msg	varchar2(100)	varchar(100)	yes		The completion status for this instance of the items execution. It contains an error message if there was some problem with the execution of the item, otherwise if null, it was successful.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies rows
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
scheduled_hist_cdtscdts	cdts		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
scheduled_hist_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - scheduled_interval					
Description	This table contains information about the intervals for which items are scheduled for execution. Each item has a set of interval records that determines exactly when the next occurrence will take place.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 field_type	number(10,0)	int	no	field_type between 0 and 8	The type of interval information that this record contains. 0=minute, 1=hour, 2=day, 3=month, 4=year, 5=day of week, 6=week of month, 8=hourly.
field_value	number(10,0)	int	no		The actual value for the time interval.
 item_number	number(10,0)	int	no		The unique identification number associated with the scheduled item record.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
scheduled_interval_primary_key	item_number, field_type			primaryKey	yes

 [Top](#)

Table Name - scheduled_items					
Description	This table contains items which are scheduled for automatic execution for a particular day and time, or which are to occur every day at a set time.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Name of associated agency.
and_dow_day [default = 0]	number(10,0)	int	no	booleanNumber1Or0	The boolean variable indication whether or not the interval values for day and day of week should be ANDED together(1) or ORed together(0).
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp.
cpers	number(10,0)	int	no	nonNegativeNumber	Empid of creating person
cterm	varchar2(15)	varchar(15)	no		Creating terminal
dest_type	varchar2(1)	varchar(1)	no	dest_type in ('0', '1','2', '3', '4', '5', '6', '7', '8', '9')	Type of destination for item. 0 = All, 1= Terminal, 2 = Dispatch group, 3 = Group, 4 = Bgroup, 5 = Unit, 6 = Verbal, 7 = Remote, 8 = Pager, 9 = Station
destination	varchar2(80)	varchar(80)	yes		Destination for the item
dow	varchar2(1)	varchar(1)	yes	dow between 0 and 7	Day of week to schedule item. 0 = Sunday, 6 = Saturday, 7 = All days
exec_date	varchar2(8)	varchar(8)	yes		Date item is to be activated
exec_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The next time the scheduled item should be executed.
exec_time	varchar2(4)	varchar(4)	yes		Time item is to be activated
item	varchar2(240)	varchar(240)	no		Actual item scheduled
 item_number	number(10,0)	int	no		Unique scheduled item ID
item_type	varchar2(1)	varchar(1)	no	item_type in ('1', '2', '3', '4', '5', '8', '9')	Type of item scheduled. 1 = Command, 2 = Message, 3 = Broadcast, 4 = Late Unit, 5 = Change SSM Plan, 8 = Scheduled Event, 9 = Scheduled Event to Pending
last_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	This field is upper-bound date/time stamp. If set, then once the next execution date-time stamp goes beyond this data/time, the scheduled item will be cancelled.
one_time [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Schedule one time flag. T = schedule one time. F means schedule more than once.
sched_count	number(10,0)	int	no		The number of times that this item was scheduled to execute.
sds	varchar2(16)	varchar(16)	yes	ipsTimestamp	Time stamp when the user enters the initial data
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp.
updt_flag	varchar2(21)	varchar(21)	no		Terminal name locking record
upers	number(10,0)	int	yes	nonNegativeNumber	Person updating the record
uterm	varchar2(15)	varchar(15)	yes		Terminal updating record.
xds	varchar2(16)	varchar(16)	yes	ipsTimestamp	Inactive date/time stamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
scheduled_items_cdtstudts	cdts, udts		no	no	
scheduled_items_exec_dts	exec_dts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
scheduled_items_primary_key	item_number		primaryKey		yes

 [Top](#)

Table Name - scr_text					
Description	This table contains the Scratch Pad text that the employee wants to have access to in I/CAD. This table contains only the text and is linked to other info in the scratch table.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp
 line_num	number(10,0)	int	no		Line number of text on form
 scr_index	number(10,0)	int	no		Unique scratch pad index num
scr_text	varchar2(240)	varchar(240)	yes		Text retrieved from form
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
scr_text_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered

scr_text_primary_key	scr_index, line_num	primaryKey	yes
----------------------	---------------------	------------	-----

 [Top](#)

Table Name - scratch					
Description	This table contains the information that the employee wants to have kept by I/CAD. This table does not contain the text. The only way a record should get added to this table is through I/CAD.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
active	varchar2(1)	varchar(1)	yes	booleanTOrF	T = active scratch pad, F = inactive ("deleted")
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp
cpers	number(10,0)	int	no	nonNegativeNumber	ID of person creating record
cterm	varchar2(15)	varchar(15)	no		Terminal creating record
personal	number(10,0)	int	yes		Empid of creator if record is personal, NULL otherwise.
scr_class	varchar2(10)	varchar(10)	no		Scratch pad classification
 scr_index	number(10,0)	int	no		Unique id for scratch pad
scr_period	number(10,0)	int	no		Period of time scratch pad is to be active (in days).
scr_title	varchar2(30)	varchar(30)	no		Title of the scratch pad
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
upers	number(10,0)	int	yes	nonNegativeNumber	Person updating the record
uterm	varchar2(15)	varchar(15)	yes		Terminal updating record
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
scratch_cdtsudts	cdts, udts		no	no	
scratch_scr_classscr_title	scr_class, scr_title		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
scratch_primary_key	scr_index			primaryKey	yes

 [Top](#)

Table Name - scrgrp					
Description	This table contains the Scratch Pad text that the employee wants to have access to in I/CAD.This table contains only the text and is linked to other info in scratch table.Only way a re- cords added is through I/CAD				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp
cpers	number(10,0)	int	no		ID of person creating record
cterm	varchar2(15)	varchar(15)	no		Terminal creating record.
grp_access	varchar2(1)	varchar(1)	no		Group access code for scratch
 grp_id	varchar2(4)	varchar(4)	no		Access group for scratch pad
 scr_id	number(10,0)	int	no		Unique Scratch ID number
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
scrgrp_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
scrgrp_primary_key	scr_id, grp_id			primaryKey	yes

 [Top](#)

Table Name - secure_acc					
Description	This table is used to identify specific events that have a higher level of security access, than normal events in the agency/dispatch group, and the users that have access to that event.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp
current	varchar2(1)	varchar(1)	no	booleanTOrF	Used to determine if this is the active record (set to "T"), or if it is a history record (set to "F")
 empid	number(10,0)	int	no	nonNegativeNumber	Employee id of user that has been granted access to the event.
 grp_id	varchar2(31)	varchar(31)	no		Group identifier of a group of users that have been granted access to the event.
 num_1	varchar2(12)	varchar(12)	no		Event number for which security access has been limited to a user or group of users.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
secure_acc_primary_key	num_1, empid, grp_id, rev_num			primaryKey	yes

 [Top](#)

Table Name - seg_alias_a					
Description	This table contains all links between the alias street names stored in the st_cd database table and the segments to which they are aliased which are stored in the segme database table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alias	number(10,0)	int	no		Link to corresponding alias column in st_cd database table record.
 fea_mslink	number(10,0)	int	no		Link to corresponding mslink column in segme database table record.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
seg_alias_a primary key	alias, fea_mslink			primaryKey	yes

 [Top](#)

Table Name - seg_alias_b					
Description	This table contains all links between the alias street names stored in the st_cd database table and the segments to which they are aliased which are stored in the segme database table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alias	number(10,0)	int	no		Link to corresponding alias column in st_cd database table record.
 fea_mslink	number(10,0)	int	no		Link to corresponding mslink column in segme database table record.
Key Constraints					

Constraint Name	Columns	Constraint Type	Sql Server Clustered
seg_alias_b_primary_key	alias, fea_mslink	primaryKey	yes

 [Top](#)

Table Name - segme_a					
Description	This table contains street segment data. A street segment is most often the portion of a street bounded by two intersections. This table holds the necessary geographical info for each segment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
addtyp	number(10,0)	int	no		Address Type. This column defines the address type code. If set=0, then the street addresses are odd/even, if set=1, then street addresses are contiguous.
areal	varchar2(40)	varchar(40)	yes		Left Area. The area in which the left side of the street segment resides.
arear	varchar2(40)	varchar(40)	yes		Right Area. The area in which the right side of the street segment resides.
bkl	varchar2(8)	varchar(8)	yes		Left Census Block. Census block (small compact area bounded by streets and other prominent physical features with certain legal boundaries) associated with left side of segment. Not currently used by I/CAD.
bkr	varchar2(8)	varchar(8)	yes		Right Census Block. Census block (small compact area bounded by streets and other prominent physical features with certain legal boundaries) associated with right side of the segment. Not currently used by I/CAD.
class	varchar2(12)	varchar(12)	yes		Classification Code. The classification code of the segment describes the road type, the same as cfcc (Census Features Class Codes a census classification describing the road type).
copll	varchar2(80)	varchar(80)	yes		Commonplace name for left side of street segment
coplr	varchar2(80)	varchar(80)	yes		Commonplace name for right side of street segment
ctkl	number(10,0)	int	yes		Left Census Track. Small, locally delineated statistic area within the selected county, having stable bounds and designd to have homogenous demographic characteristics and associated w/ left side o segment. Not used by I/CAD.
ctkr	number(10,0)	int	yes		Right Census Track. Small, locally delineated statistic areas within selected county, having stable bounds and designed to have homogenous demographic characteristics and associated w/right side o segment. Not used by I/CAD.
eszl	number(10,0)	int	yes		Left Emergency Service Zone. The ESZ value in which the left side of the street segment resides.
eszr	number(10,0)	int	yes		Right Emergency Service Zone The ESZ value in which the right side of the street segment resides.
fraddl	varchar2(11)	varchar(11)	yes		Address at from node on left side.
fraddr	varchar2(11)	varchar(11)	yes		From Address Right. Stores the from address associated with the right side of the segment. Must be right justified.
loc_fld2l	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld2r	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3l	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3r	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4l	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4r	varchar2(5)	varchar(5)	yes		Generic location field
 mslink	number(10,0)	int	no		Map Link. A link to the Map graphics element of the street segment.
muncdl	number(10,0)	int	yes		Federal ID code on the left side of the segment. This column is a Minor Civil Division (MCD), which is a legally defined subcounty such as a town or township. Not currently used by I/CAD.
muncdr	number(10,0)	int	yes		Federal ID code on the right side of the segment. This column is a Minor Civil Division (MCD), which is a legally defined subcounty such as a town or township. Not currently used by I/CAD.
munl	varchar2(40)	varchar(40)	yes		Left Municipality. The municipality in which the left side of the segment resides.
munr	varchar2(40)	varchar(40)	yes		Right Municipality. The municipality in which the right side of the segment resides.
segid	number(10,0)	int	yes		Segment ID. The TIGER (Data) ID of the segment.
text_id	number(10,0)	int	no		Text ID. The text identification of the street name associated with this segment. This is the variable link to get information concerning the street from the st_cd table
toaddl	varchar2(11)	varchar(11)	yes		To Address Left. Stores the to address associated with the left side of the segment. Must be right justified.
toaddr	varchar2(11)	varchar(11)	yes		To Address Right. Stores the address associated with the right side of the segment. Must be right justified.
xst_id1	number(10,0)	int	yes		Cross Street ID 1. The text_id of the cross_street at the from node. Using this value the street information can be retrieved from the st_cd table.
xst_id2	number(10,0)	int	yes		Cross Street ID 2. The text_id of the cross_street at the to_node. Using this value the street information can be retrieved from the st_cd table.
zipl	varchar2(10)	varchar(10)	yes		Zip Code on Left. The zip code in which the left side of the segment resides.
zipr	varchar2(10)	varchar(10)	yes		Zip Code on Right. The zip code in which the right side of the segment resides.

Indexes				
Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause
segme_a_areal	areal	no	no	
segme_a_arear	arear	no	no	
segme_a_class	class	no	no	
segme_a_fraddl	fraddl	no	no	
segme_a_fraddr	fraddr	no	no	
segme_a_munl	munl	no	no	
segme_a_munr	munr	no	no	
segme_a_text_id	text_id	no	no	
segme_a_toaddl	toaddl	no	no	
segme_a_toaddr	toaddr	no	no	

Key Constraints			
Constraint Name	Columns	Constraint Type	Sql Server Clustered
segme_a_primary_key	mslink	primaryKey	yes

 [Top](#)

Table Name - segme_b					
Description	This table contains street segment data. A street segment is most often the portion of a street bounded by two intersections. This table holds the necessary geographical info for each segment.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
addtyp	number(10,0)	int	no		Address Type. This column defines the address type code. If set=0, then the street addresses are odd/even, if set=1, then street addresses are contiguous.
areal	varchar2(40)	varchar(40)	yes		Left Area. The area in which the left side of the street segment resides.
arear	varchar2(40)	varchar(40)	yes		Right Area. The area in which the right side of the street segment resides.
bkl	varchar2(8)	varchar(8)	yes		Left Census Block. Census block (small compact area bounded by streets and other prominent physical features with certain legal boundaries) associated with left side of segment. Not currently used by I/CAD.
bkr	varchar2(8)	varchar(8)	yes		Right Census Block. Census block (small compact area bounded by streets and other prominent physical features with certain legal boundaries) associated with right side of the segment. Not currently used by I/CAD.
class	varchar2(12)	varchar(12)	yes		Classification Code. The classification code of the segment describes the road type, the same as cfcc (Census Features Class Codes a census classification describing the road type).
copll	varchar2(80)	varchar(80)	yes		Commonplace name for left side of street segment
coplr	varchar2(80)	varchar(80)	yes		Commonplace name for right side of street segment
ctkl	number(10,0)	int	yes		Left Census Track. Small, locally delineated statistic area within the selected county, having stable bounds and designed to have homogenous demographic characteristics and associated w/ left side o segment. Not used by I/CAD.
ctkr	number(10,0)	int	yes		Right Census Track. Small, locally delineated statistic areas within selected county, having stable bounds and designed to have homogenous demographic characteristics and associated w/right side o segment. Not used by I/CAD.

eszl	number(10,0)	int	yes		Left Emergency Service Zone. The ESZ value in which the left side of the street segment resides.
eszr	number(10,0)	int	yes		Right Emergency Service Zone The ESZ value in which the right side of the street segment resides.
fraddl	varchar2(11)	varchar(11)	yes		Address at from node on left side.
fraddr	varchar2(11)	varchar(11)	yes		From Address Right. Stores the from address associated with the right side of the segment. Must be right justified.
loc_fld2l	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld2r	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3l	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3r	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4l	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4r	varchar2(5)	varchar(5)	yes		Generic location field
 mslink	number(10,0)	int	no		Map Link. A link to the Map graphics element of the street segment.
muncdl	number(10,0)	int	yes		Federal ID code on the left side of the segment. This column is a Minor Civil Division (MCD), which is a legally defined subcounty such as a town or township. Not currently used by I/CAD.
muncdr	number(10,0)	int	yes		Federal ID code on the right side of the segment. This column is a Minor Civil Division (MCD), which is a legally defined subcounty such as a town or township. Not currently used by I/CAD.
munl	varchar2(40)	varchar(40)	yes		Left Municipality. The municipality in which the left side of the segment resides.
munr	varchar2(40)	varchar(40)	yes		Right Municipality. The municipality in which the right side of the segment resides.
segid	number(10,0)	int	yes		Segment ID. The TIGER (Data) ID of the segment.
text_id	number(10,0)	int	no		Text ID. The text identification of the street name associated with this segment. This is the variable link to get information concerning the street from the st_cd table
toaddl	varchar2(11)	varchar(11)	yes		To Address Left. Stores the to address associated with the left side of the segment. Must be right justified.
toaddr	varchar2(11)	varchar(11)	yes		To Address Right. Stores the address associated with the right side of the segment. Must be right justified.
xst_id1	number(10,0)	int	yes		Cross Street ID 1. The text_id of the cross_street at the from node. Using this value the street information can be retrieved from the st_cd table.
xst_id2	number(10,0)	int	yes		Cross Street ID 2. The text_id of the cross_street at the to_node. Using this value the street information can be retrieved from the st_cd table.
zipl	varchar2(10)	varchar(10)	yes		Zip Code on Left. The zip code in which the left side of the segment resides.
zipr	varchar2(10)	varchar(10)	yes		Zip Code on Right. The zip code in which the right side of the segment resides.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	
segme_b_areal	areal		no	no	
segme_b_arear	arear		no	no	
segme_b_class	class		no	no	
segme_b_fraddl	fraddl		no	no	
segme_b_fraddr	fraddr		no	no	
segme_b_munl	munl		no	no	
segme_b_munr	munr		no	no	
segme_b_text_id	text_id		no	no	
segme_b_toaddl	toaddl		no	no	
segme_b_toaddr	toaddr		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
segme_b_primary_key	mslink		primaryKey		yes

 [Top](#)

Table Name - sms_psap_group					
Description	Defines the mapping between the AGENT511 workstation client ID and the PSAP client ID. Used by TextDataServer to interface to AGENT511 system. CR 1-507H05.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 node_client_id	varchar2(11)	varchar(11)	no		Client ID used for workstation in AGENT511
 psap_client_id	varchar2(11)	varchar(11)	no		Client ID used for PSAP in AGENT511
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sms_psap_group_pk	node_client_id, psap_client_id			primaryKey	yes

 [Top](#)

Table Name - sms_user					
Description	Defines the mapping between the AGENT511 clientID and the Intergraph mux_id. Used by TextDataServer and Agent511AddIn to interface to AGENT511 system. CR 1-507H05				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 client_id	varchar2(11)	varchar(11)	no		Client ID used in AGENT511
identification_key	varchar2(50)	varchar(50)	no		Identification key used to logon to AGENT511
mux_id	number(10,0)	int	no		The mux_id used in the CAD system. This corresponds to the mux_id column in the term table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sms_user_pk	client_id			primaryKey	yes

 [Top](#)

Table Name - sp_ad_a					
Description	The special address table is used to assign a different ESZ than the street segment where the address resides. This table is searched during Location Verify.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alarm_sym	varchar2(6)	varchar(6)	yes		Alarm symbol
com_nme	varchar2(80)	varchar(80)	yes		Common Place Name. This column contains the name of a common place defined for the Location Verify.
copl_sym	varchar2(6)	varchar(6)	yes		Commonplace symbol
edts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The expiration date timestamp of a special address record
esz	number(10,0)	int	yes		Emergency Service Zone. The ESZ of the special address. This could specify a unique ESZ, as in a firebox for a highrise building. This value corresponds to an s_esz value in the agency_esz table.
fcode	varchar2(12)	varchar(12)	yes		Maps to the netfea record containing the symbol (cell) to be placed on the map for this special address record.
fea_mslink	number(10,0)	int	yes		Feature Mslink. This is the linkage to the street segment of the special address.
loc_fld1	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4	varchar2(5)	varchar(5)	yes		Generic location field
lv_apt	varchar2(5)	varchar(5)	yes		Apartment Number. This column contains the apartment number or suite number of the special address.

lv_area	varchar2(40)	varchar(40)	yes		Area Indicator. This column contains the area code for the special address.
majevt_id	varchar2(10)	varchar(10)	yes		Major Event Identification. This coulmn contains the pointer to the major incident plan.
maplevs	varchar2(200)	varchar(200)	yes		Assigned map level(s) for special address
msg	varchar2(2000)	varchar(2000)	yes		Message. This column contains a message about the special address.
 mslink	number(10,0)	int	no		Map Link. This column allows the placement of a special symbol in the map to designate a special address. The symbol could be graphically selected to review this information. The mslink value is generated from the mscatalog table.
mun	varchar2(40)	varchar(40)	yes		Municipality. This column defines the municipality of the special address.
no_loi_search	varchar2(1)	varchar(1)	yes	booleanToF	Location of Interest Search Flag. This column indicates whether a LOI search is to be conducted on the special address.
priority	number(10,0)	int	yes	priority between 0 and 9	Location priority. Null if no priority.
priority_edts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Priority expiration. Null if no expiration.
search_flag	varchar2(1)	varchar(1)	yes	booleanToF	Special Situation Search Flag Indicator. This column indicates whether a special situation table search is to conducted on this address.
spad_sym	varchar2(6)	varchar(6)	yes		Special address symbol
st_num	varchar2(15)	varchar(15)	yes		Street Number. The street number of the special address.
text_id [default = -1]	number(10,0)	int	no		Text ID. This is a join column to the st_cd table. It defines the street name. Text_id is set to -1 for special addresses that are only defined by (X,Y) coordinates.
text_id2 [default = -1]	number(10,0)	int	no		The link to the st_cd table for the second street in the intersection
x_cord [default = 0]	number(10,0)	int	no		X-coordinate. Location of the street segment which the special address references. X, Y coordinates will be set to (0,0) if user does not specify the coordinates.
y_cord [default = 0]	number(10,0)	int	no		Y-coordinate. Location of the street segment which the special address references. X, Y coordinates will be set to (0,0) if user does not specify the coordinates.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
sp_ad_a_esz	esz		no	no	
sp_ad_a_fea_mslink	fea_mslink		no	no	
sp_ad_a_text_id	text_id		no	no	
sp_ad_a_text_id2	text_id2		no	no	
sp_ad_a_x_cord	x_cord		no	no	
sp_ad_a_y_cord	y_cord		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
sp_ad_a_primary_key	mslink		primaryKey		yes
Check Constraints					
Constraint Name		Required	Oracle Definition	Sql Server Definition	
sp_ad_a_text_id_x_y_cord_ck		No	NOT (text_id = -1 and x_cord = 0 and y_cord = 0)	NOT (text_id = -1 and x_cord = 0 and y_cord = 0)	
Triggers					
Trigger Name	Required		Trigger Type	Description	
sp_ad_a_log_trig	No		Custom	Log inserts, updates and deletes to sp_ad_co_pl_change_log. CR 1-53EYH6	

 [Top](#)

Table Name - sp_ad_b					
Description	The special address table is used to assign a different ESZ than the street segment where the address resides. This table is searched during Location Verify.				
Copy Type	ALL_ WITH_ CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alarm_sym	varchar2(6)	varchar(6)	yes		Alarm symbol
com_nme	varchar2(80)	varchar(80)	yes		Common Place Name. This column contains the name of a common place defined for the Location Verify.
copl_sym	varchar2(6)	varchar(6)	yes		Commonplace symbol
edts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The expiration date timestamp of a special address record
esz	number(10,0)	int	yes		Emergency Service Zone. The ESZ of the special address. This could specify a unique ESZ, as in a firebox for a highrise building. This value corresponds to an s_esz value in the agency_esz table.
fcode	varchar2(12)	varchar(12)	yes		Maps to the netfea record containing the symbol (cell) to be placed on the map for this special address record.
fea_mslink	number(10,0)	int	yes		Feature Mslink. This is the linkage to the street segment of the special address.
loc_fld1	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4	varchar2(5)	varchar(5)	yes		Generic location field
lv_aprt	varchar2(5)	varchar(5)	yes		Apartment Number. This column contains the apartment number or suite number of the special address.
lv_area	varchar2(40)	varchar(40)	yes		Area Indicator. This column contains the area code for the special address.
majevt_id	varchar2(10)	varchar(10)	yes		Major Event Identification. This coulmn contains the pointer to the major incident plan.
maplevs	varchar2(200)	varchar(200)	yes		Assigned map level(s) for special address
msg	varchar2(2000)	varchar(2000)	yes		Message. This column contains a message about the special address.
 mslink	number(10,0)	int	no		Map Link. This column allows the placement of a special symbol in the map to designate a special address. The symbol could be graphically selected to review this information. The mslink value is generated from the mscatalog table.
mun	varchar2(40)	varchar(40)	yes		Municipality. This column defines the municipality of the special address.
no_loi_search	varchar2(1)	varchar(1)	yes	booleanTorF	Location of Interest Search Flag. This column indicates whether a LOI search is to be conducted on the special address.
priority	number(10,0)	int	yes	priority between 0 and 9	Location priority. Null if no priority.
priority_edts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Priority expiration. Null if no expiration.
search_flag	varchar2(1)	varchar(1)	yes	booleanTorF	Special Situation Search Flag Indicator. This column indicates whether a special situation table search is to conducted on this address.
spad_sym	varchar2(6)	varchar(6)	yes		Special address symbol
st_num	varchar2(15)	varchar(15)	yes		Street Number. The street number of the special address.
text_id [default = -1]	number(10,0)	int	no		Text ID. This is a join column to the st_cd table. It defines the street name. Text_id is set to -1 for special addresses that are only defined by (X,Y) coordinates.
text_id2 [default = -1]	number(10,0)	int	no		The link to the st_cd table for the second street in the intersection
x_cord [default = 0]	number(10,0)	int	no		X-coordinate. Location of the street segment which the special address references. X, Y coordinates will be set to (0,0) if user does not specify the coordinates.
y_cord [default = 0]	number(10,0)	int	no		Y-coordinate. Location of the street segment which the special address references. X, Y coordinates will be set to (0,0) if user does not specify the coordinates.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
sp_ad_b_esz	esz		no	no	
sp_ad_b_fea_mslink	fea_mslink		no	no	
sp_ad_b_text_id	text_id		no	no	
sp_ad_b_text_id2	text_id2		no	no	
sp_ad_b_x_cord	x_cord		no	no	
sp_ad_b_y_cord	y_cord		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
sp_ad_b_primary_key	mslink		primaryKey		yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	

sp_ad_b_text_id_x_y_cord_ck	No	NOT (text_id = -1 and x_cord = 0 and y_cord = 0)	NOT (text_id = -1 and x_cord = 0 and y_cord = 0)
Triggers			
Trigger Name	Required	Trigger Type	Description
sp_ad_b_log_trig	No	Custom	Log inserts, updates and deletes to sp_ad_co_pl_change_log. CR 1-53EYH6

 [Top](#)

Table Name - sp_ad_co_pl_change_log					
Description	Tracks changes to rows in the active sp_ad and co_pl tables. Each row in sp_ad and co_pl may have zero or one record in this table. If a sp_ad or co_pl row is modified multiple times, only the information about the last change is preserved. This table is populated by triggers on the active sp_ad and co_pl tables. CR 1-53EYH6				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
change_source	varchar2(128)	varchar(128)	no		Application that made the change.
command	varchar2(1)	varchar(1)	no	command in ('I', 'U', 'D')	SQL command. I= Insert, U = Update, D = Delete
cts	varchar2(16)	varchar(16)	no	ipsTimestamp	Timestamp of last command
 origin_id	varchar2(80)	varchar(80)	no		For co_pl records, this will contain the com_nme value. For sp_ad records, this will be 'sp_ad'
 origin_table	varchar2(30)	varchar(30)	no	origin_table in ('sp_ad', 'co_pl')	Table name
 spad_mslink	number(10,0)	int	no		Special address mslink value
term	varchar2(128)	varchar(128)	no		Terminal where command was run.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_ad_co_pl_change_log_pk	spad_mslink, origin_id, origin_table			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
sp_ad_co_pl_change_log_tbl_ck	Yes	(origin_table = 'sp_ad' and origin_id = 'sp_ad') or (origin_table = 'co_pl')		(origin_table = 'sp_ad' and origin_id = 'sp_ad') or (origin_table = 'co_pl')	

 [Top](#)

Table Name - sp_ad_event_type					
Description	This table contains overrides for special address, event type, and event subtype combinations.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
priority	number(10,0)	int	no	priority between 0 and 9	Event priority override
 sp_ad_mslink	number(10,0)	int	no		Special address mslink
 sub_tycode [default = 'default']	varchar2(16)	varchar(16)	no		Event subtype
 tycode	varchar2(16)	varchar(16)	no		Event type
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_ad_event_type_pk	sp_ad_mslink, tycode, sub_tycode			primaryKey	yes

 [Top](#)

Table Name - sp_st					
Description	The special situation table is used to store addresses where a special situation exists. This could be any situation for which the agency would need a special response.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp. Stores the date/time (yyyymmddhhmms) at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification number of the person who created the record.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. This column stores the nodename of the terminal from which the record was created.
dirpre	varchar2(2)	varchar(2)	yes		Direction Prefix. If applicable, this column stores the direction prefix of the street segment referenced by feature name.
dirsuf	varchar2(2)	varchar(2)	yes		Direction Suffix. If applicable, this column stores the direction suffix of the street segment referenced by feature name.
edts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Expiration Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmms) of when the special situation expires.
feanme	varchar2(30)	varchar(30)	yes		Feature Name. Defines the event feature name.
featyp	varchar2(4)	varchar(4)	yes		Feature Type. Defines the event feature type, for example, road or street.
hash	number(10,0)	int	no		Stores the numeric hashing value. Queries search on the hash value to improve response time.
highaddr	varchar2(11)	varchar(11)	yes		High address range for sp_st record
loc_fld1	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld2	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld3	varchar2(5)	varchar(5)	yes		Generic location field
loc_fld4	varchar2(5)	varchar(5)	yes		Generic location field.
lowaddr	varchar2(11)	varchar(11)	yes		Low address range for sp_st record
lv_apt	varchar2(5)	varchar(5)	yes		Apartment Number. Stores the apartment number of the referenced address.
lv_area	varchar2(40)	varchar(40)	yes		Area. Stores the area in which the special address is located.
mes_switch	varchar2(1)	varchar(1)	yes		Message Switch. This column defines what is stored in the message column. C = comment, T = temporary only, X = attached file name.
msg	varchar2(2000)	varchar(2000)	yes		Message. Stores the file name or comment as denoted by the mes_switch flag. File name could be used for a graphic file of floor plans or for a text file for additional information (the street names).
 mslink	number(10,0)	int	no		Map Link. This column allows the placement of a special symbol in the map to designate a special address. The symbol could be graphically selected to review this information. The mslink value is generated using the numbr table.
mun	varchar2(40)	varchar(40)	yes		Municipality. Stores the municipality in which the special situation occurs.
priority	number(10,0)	int	yes	priority between 1 and 9	Priority. This column contains the priority of the special situation.
remarks	varchar2(20)	varchar(20)	yes		A very brief summary of the information in the record.
req_id	number(10,0)	int	yes		Requestor ID. This column contains the ID of the requestor.
req_name	varchar2(30)	varchar(30)	yes		Requestor Name. This column contains the name of the requestor.
ss_area	varchar2(1)	varchar(1)	no	booleanTOrF	T/F is returned on area search
ss_typ	varchar2(16)	varchar(16)	yes		Special Situation Type. Specifies the type of special situation. Types are defined in the sp_st_type table.
st_num	varchar2(15)	varchar(15)	yes		Street Number. The street number of the special situation.
x_cord	number(10,0)	int	no		X-coordinate. Location of the street segment on which the special situation is located.
y_cord	number(10,0)	int	no		Y-coordinate. Location of the street segment on which the special situation is located.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
sp_st_cdts	cdts		no	no	
sp_st_edts	edts		no	no	
sp_st_hash	hash		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_st_primary_key	mslink			primaryKey	yes

 [Top](#)

Table Name - sp_st_ag					
Description	Stores information about which agencies have access to which special situation records				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 ag_id	varchar2(9)	varchar(9)	no		Agency ID
 mslink	number(10,0)	int	no		Unique identifier of special situation record. Used for joining with sp_st table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_st_ag_primary key	ag_id, mslink			primary/Key	yes

 [Top](#)

Table Name - sp_st_poly					
Description	Stores information about which polygon(s) define the regions(s) associated with a special situation and/or which special situation(s) are associated with a polygon				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 poly_id	number(10,0)	int	no		Unique identifier from special_situation.ply
 sp_st_mslink	number(10,0)	int	no		Unique identifier of special situation record. Used for joining with sp_st table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_st_poly_pk	sp_st_mslink, poly_id			primaryKey	yes

 [Top](#)

Table Name - sp_st_type					
Description	Defines the types of special situations. sp_st.ss_type will be restricted to these defined types. Added for CR 1-4URTWV.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
description	varchar2(50)	varchar(50)	yes		Optional description
image_resource_name	varchar2(255)	varchar(255)	yes		Image resource name. This image will be displayed on the map for this type of special situation.
 ss_typ	varchar2(16)	varchar(16)	no		Special situation type.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_st_type_pk	ss_type			primaryKey	yes

 [Top](#)

Table Name - sp_st_type_priority	
Description	Special situation type priority override. For a particular special situation type and priority, you can override the image displayed on the map. Added for CR 1-4URT WV.
Copy Type	ALL_WITH_CHECK

Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
image_resource_name	varchar2(255)	varchar(255)	no		Image resource name. This image will be displayed on the map for special situations of this type and priority. This overrides the normal image used for special situations of this type.
 priority	number(10,0)	int	no	priority between 1 and 9	Priority
 ss_type	varchar2(16)	varchar(16)	no		Special situation type.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sp_st_type_priority_pk	ss_type, priority			primaryKey	yes

 [Top](#)

Table Name - spad_cont_name					
Description	The CADDDB spad_cont_name table contains information describing the person to contact with respect to a special address, commonplace name, or alarm.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cname	varchar2(45)	varchar(45)	yes		Name of the individual to contact
clnum	varchar2(14)	varchar(14)	yes		Telephone number of the individual to contact
co_date	varchar2(10)	varchar(10)	yes		Records date the individual named in the cname column was contacted about the alarm.
co_time	varchar2(5)	varchar(5)	yes		Records time the individual named in cname column was contacted about the alarm.
cstr_add	varchar2(36)	varchar(36)	yes		Full street address of the individual to contact
data_source	varchar2(5)	varchar(5)	yes		Data source
 origin_id	varchar2(80)	varchar(80)	no		For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.
 origin_table	varchar2(30)	varchar(30)	no	origin_table in ('sp_ad','co_pl','alarm')	Table name associated with this contact
priority	number(10,0)	int	yes		Indicates priority order in which individual named within this record is to be contacted
 row_num	number(10,0)	int	no		Uniquely identifies the supplemental information for the individual to contact
 spad_mslink	number(10,0)	int	no		The associated special address mslink value
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
spad_cont_name_primary_key	origin_table, spad_mslink, origin_id, row_num			primaryKey	yes

 [Top](#)

Table Name - spad_perso					
Description	The CADDDB perso table contains person information which is related to the special address, commonplace name, or alarm.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
age	number(10,0)	int	yes		Age of the person related to the special address
dob	varchar2(10)	varchar(10)	yes		Date of birth of the person related to the special address
eye	varchar2(3)	varchar(3)	yes		Eye color of the person related to the special address
hair	varchar2(3)	varchar(3)	yes		Hair color of the person related to the special address
height	number(10,0)	int	yes		Height of the person related to the special address
nme	varchar2(50)	varchar(50)	yes		Name of the person related to the special address
oln	varchar2(20)	varchar(20)	yes		Operator license number related to the special address
 origin_id	varchar2(80)	varchar(80)	no		For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.
 origin_table	varchar2(30)	varchar(30)	no	origin_table in ('sp_ad','co_pl','alarm')	Table name associated with this person
race	varchar2(1)	varchar(1)	yes		Race of the person related to the special address
remarks	varchar2(20)	varchar(20)	yes		Descriptive remarks about the person related to the special address
 row_num	number(10,0)	int	no		Uniquely identifies the supplemental information for this person
sex	varchar2(1)	varchar(1)	yes		Sex of the person related to the special address
 spad_mslink	number(10,0)	int	no		The associated special address mslink value
state	varchar2(2)	varchar(2)	yes		State of the operator license number
weight	number(10,0)	int	yes		Weight of the person related to the special address
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
spad_perso_primary_key	origin table, spad mslink, origin id, row_num			primaryKey	yes

 [Top](#)

Table Name - spad_propt					
Description	This table contains property information related to special address, commonplace name, or alarm.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
item	varchar2(10)	varchar(10)	yes		Description of the item
 origin_id	varchar2(80)	varchar(80)	no		For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.
 origin_table	varchar2(30)	varchar(30)	no	origin_table in ('sp_ad','co_pl','alarm')	Table name associated with the item
remarks	varchar2(20)	varchar(20)	yes		Remarks about the property item
 row_num	number(10,0)	int	no		Uniquely identifies the supplemental information for the property
serialnum	varchar2(20)	varchar(20)	yes		Serial number of the item
 spad_mslink	number(10,0)	int	no		The associated special address mslink value
value	varchar2(10)	varchar(10)	yes		Monetary value of the property item
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
spad_propt_primary_key	origin_table,spad_mslink,origin_id,row_num			primaryKey	yes

 [Top](#)

Table Name - spad_vehicle					
Description	This table contains vehicle information which is related to the special address, commonplace name, or alarm.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
license	varchar2(8)	varchar(8)	yes		License Plate Number.
license_type	varchar2(10)	varchar(10)	yes		License Type. This column contains the type of vehicle license.
license_yr	varchar2(4)	varchar(4)	yes		License Year. This column contains the year of the license.
make	varchar2(5)	varchar(5)	yes		Make of the Vehicle.
model	varchar2(5)	varchar(5)	yes		Model of the Vehicle.
model_year	number(10,0)	int	yes		Year of the Vehicle.
 _origin_id	varchar2(80)	varchar(80)	no		For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.
 _origin_table	varchar2(30)	varchar(30)	no	origin_table in ('sp_ad','co_pl','alarm')	Table name associated with this vehicle
remarks	varchar2(20)	varchar(20)	yes		This column stores the remarks about the vehicle.
 _row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.
 _spad_mslink	number(10,0)	int	no		The associated special address mslink value
state	varchar2(4)	varchar(4)	yes		State Register of the Vehicle.
vehic_color	varchar2(7)	varchar(7)	yes		Vehicle Color. This column contains the color of the vehicle.
vin	varchar2(25)	varchar(25)	yes		Vehicle Identification Number
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
spad_vehicle_primary_key	origin_table, spad_mslink, origin_id, row_num			primaryKey	yes

 [Top](#)

Table Name - sql_audit_log					
Description	Contains the output from the Intergraph SQL auditing mechanism				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The creation date/time stamp.
connection_id	number(10,0)	int	no		An identifier for the type of connection that executed the SQL statement.
cterm	varchar2(15)	varchar(15)	no		The name of the machine that executed the SQL statement.
exe_name	varchar2(31)	varchar(31)	yes		The name of the executable that executed the SQL statement.
 _group_id	number(10,0)	int	no		The application specific statement group identifier.
 _proc_name	varchar2(30)	varchar(30)	no		The name of the process type that executed the SQL statement.
 _row_num	number(10,0)	int	no		Uniquely identifies the chunks of a long SQL statement that must be broken into multiple pieces.
sql_stmt	varchar2(2000)	varchar(2000)	no		The SQL statement that was executed.
 _stmt_id	number(10,0)	int	no		Uniquely identifies each statement that has been executed for a specific group_id.
thread_id	number(10,0)	int	no		The thread identifier for the thread that executed the SQL statement.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sql_audit_log_primary_key	proc_name, group_id, stmt_id, row_num			primaryKey	yes

 [Top](#)

Table Name - ssgroup					
Description	This table contains the plan group definition. This table is maintained by SSP and accessed by SSP and I/CAD and SSM.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Id of agency for the plan group.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time/date stamp.
cpers	number(10,0)	int	no	nonNegativeNumber	Emp id of person creating the record.
cterm	varchar2(15)	varchar(15)	no		Terminal on which the record was created.
cutoff	varchar2(1)	varchar(1)	no		Plan group cutoff level reached indicator.
dgroup	varchar2(5)	varchar(5)	no		Dispatch group for the plan group.
ext_unitattr	raw(32)	varbinary(32)	no	lengthb(ext_unitattr) = 64	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).
grpdesc	varchar2(40)	varchar(40)	yes		Description of plan group.
 _grpname	varchar2(30)	varchar(30)	no		Unique plan group name.
grpsym	number(10,0)	int	yes		Symbol number of symbol used to display the posts (in the map) of the plan belonging to the plan group.
maxreldist	float(126)	float(53)	no		Maximum relocation distance for a plan group.
planwt	number(10,0)	int	no		Weight of a plan group.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time/date stamp.
upers	number(10,0)	int	yes	nonNegativeNumber	Emp. id of person updating record.
uterm	varchar2(15)	varchar(15)	yes		Terminal on which record was updated.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
ssgroup_primary_key	grpname			primaryKey	yes

 [Top](#)

Table Name - ssplan					
Description	This table contains the information associated with a System Status Plan. The table is maintained by the System Status Planner and accessed by both SSP and SSM.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time/date stamp.
dow	varchar2(1)	varchar(1)	yes	dow between 1 and 7	Day of Week for which the plan is defined.The days go from 1- Sunday to 7 - Saturday.
 _grpname	varchar2(30)	varchar(30)	no		Name of plan group to which the plan belongs.

plan_active	varchar2(1)	varchar(1)	yes		Plan active flag.
 plan_id	varchar2(4)	varchar(4)	no		Unique identifier for a plan.
plan_name	varchar2(30)	varchar(30)	no		Name of a plan.
plan_time	varchar2(4)	varchar(4)	no		Time for which the plan is specified. The time is a string of the form hhmm.
spec_date	varchar2(8)	varchar(8)	yes		Date for which plan is specified. The date is a string of the form yyyymmdd.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
ssplan_primary_key	grpname, plan_id			primaryKey	yes

 [Top](#)

Table Name - ssplanlev					
Description	This table contains information associated with the levels of a System Status Plan. This table is maintained by the System Status Planner and is accessed by both SSP and SSM.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
callup_level	varchar2(1)	varchar(1)	no	booleanYOrN	This column represents the call up level and is set to Y (yes) or N (no).
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp.
cond_post1_id	varchar2(10)	varchar(10)	yes		This is the unique identifier of a conditional post that is part of post assignment for a plan level.
cond_post2_id	varchar2(10)	varchar(10)	yes		This is the unique identifier of a conditional post that is part of a post assignment for a plan level.
cutoff_level	varchar2(1)	varchar(1)	no	booleanYOrN	This column represents the cut off level and is set to Y (yes) or N (no).
log_operator	varchar2(3)	varchar(3)	yes		This is the logical operator that is a part of a post assignment in a plan. The operator can be "OR" or "AND".
 plan_id	varchar2(4)	varchar(4)	no		This is unique identifier of the plan to which the level belongs.
 plan_level	number(5,0)	smallint	no		This is the level of the plan and can be an integer between 1 and 63.
 post_id	varchar2(10)	varchar(10)	no		This is the id. of a post that is a part of a post assignment for a level.
post_priority	number(5,0)	smallint	no		This is the priority of a particular post assignment. The priorities for a given level x is from 0 to x-1.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
ssplanlev_primary_key	plan_id, plan_level, post_id			primaryKey	yes

 [Top](#)

Table Name - sspost					
Description	This table contains the information of all the active plans on the system. This table is maintained by SSM. I/CAD reads this table to display posts on a map for an active plan.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 grpname	varchar2(30)	varchar(30)	no		Plan group name. This is a unique identifier for a plan group.
next_lev	varchar2(1)	varchar(1)	yes		Indicates if the post is needed in the next level of the plan.
 plan_id	varchar2(4)	varchar(4)	no		Id of plan.
post_cond	varchar2(14)	varchar(14)	yes		Indicates the post conditionals in the plan. It is a string containing the names of posts involved in the condition and the logical operator.
post_pri	number(10,0)	int	no		Priority assigned to the post.
post_stat	number(10,0)	int	no	post_stat between 0 and 4	Post status. It is one of 5 possible statuses. 0 - post not in plan 1 - required and assigned 2 - required and unassigned 3 - conditional and assigned 4 - conditional and unassigned
 station	varchar2(10)	varchar(10)	no		Id of station (post). The id matches the id in def_station table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
sspost_primary_key	grpname, plan_id, station			primaryKey	yes

 [Top](#)

Table Name - st_cd_a					
Description	This table contains all unique street names. Note that two different streets do not have different entries if they have the same name, but are located in separate municipalities. Rows with virtualcode='F' are generated by map data. Rows with virtualcode='T' may be generated by CADDDBM. A row with virtualcode = 'T' may have the same feature name, feature type, direction prefix and direction suffix as a real row with virtualcode='F'.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alias	number(10,0)	int	yes		Alias Text ID. If this name is an alias for another street, the text_id of that street is stored in this field. Otherwise the field is NULL. The field is set when a street is assigned an alias.
dirpre	varchar2(2)	varchar(2)	yes		Direction Prefix. The direction prefix, N, NW, SE, and so on.
dirsuf	varchar2(2)	varchar(2)	yes		Direction Suffix. The direction suffix, N, NW, SE, and so on.
feanme	varchar2(30)	varchar(30)	yes		Feature Name. Stores the name of the street.
featyp	varchar2(4)	varchar(4)	yes		Feature Type. Stores the feature type. For example, road or street.
soundex	varchar2(4)	varchar(4)	yes		Soundex Code. The soundex code for the feature name.
 text_id	number(10,0)	int	no		Text ID. The text_id is a unique identifier assigned to each street name which is equal to the "text_id" column in the segme table.
virtualcode [default = 'F']	varchar2(1)	varchar(1)	no	booleanTORF	If virtualcode = 'T', then this is a virtual st_cd record with no link to the segme, cd_edge or cd_node tables. Instead, this row links to record(s) in sp_ad. If virtualcode = 'F', then this is a normal st_cd record.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
st_cd_a_alias	alias		no	no	
st_cd_a_feanme	feanme		no	no	
st_cd_a_featyp	featyp		no	no	
st_cd_a_soundex	soundex		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
st_cd_a_primary_key	text_id			primaryKey	yes
st_cd_a_unique	feanme, featyp, dirpre, dirsuf, virtualcode			uniqueKey	no

 [Top](#)

Table Name - st_cd_b					
Description	This table contains all unique street names. Note that two different streets do not have different entries if they have the same name, but are located in separate municipalities. Rows with virtualcode = 'F' are generated by map data. Rows with virtualcode = 'T' may be generated by CADDDBM. A row with virtualcode = 'T' may have the same feature name, feature type, direction prefix and direction suffix as a real row with virtualcode = 'F'.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
alias	number(10,0)	int	yes		Alias Text ID. If this name is an alias for another street, the text_id of that street is stored in this field. Otherwise the field is NULL. The field is set when a street is assigned an alias.

dirpre	varchar2(2)	varchar(2)	yes		Direction Prefix. The direction prefix, N, NW, SE, and so on.	
dirsuf	varchar2(2)	varchar(2)	yes		Direction Suffix. The direction suffix, N, NW, SE, and so on.	
feanme	varchar2(30)	varchar(30)	yes		Feature Name. Stores the name of the street.	
featyp	varchar2(4)	varchar(4)	yes		Feature Type. Stores the feature type. For example, road or street.	
soundex	varchar2(4)	varchar(4)	yes		Soundex Code. The soundex code for the feature name.	
 text_id	number(10,0)	int	no		Text ID. The text_id is a unique identifier assigned to each street name which is equal to the "text_id" column in the segme table.	
virtualcode [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	If virtualcode = 'T', then this is a virtual st_cd record with no link to the segme, cd_edge or cd_node tables. Instead, this row links to record(s) in sp_ad. If virtualcode = 'F', then this is a normal st_cd record.	
Indexes						
Index Name	Columns			Is Unique	Sql Server Clustered	Sql Server Where Clause
st_cd_b_alias	alias			no	no	
st_cd_b_feanme	feanme			no	no	
st_cd_b_featyp	featyp			no	no	
st_cd_b_soundex	soundex			no	no	
Key Constraints						
Constraint Name	Columns			Constraint Type		Sql Server Clustered
st_cd_b_primary_key	text_id			primaryKey		yes
st_cd_b_unique	feanme, featyp, dirpre, dirsuf, virtualcode			uniqueKey		no

 [Top](#)

Table Name - state_badge					
Description	This table contains badge identifiers related to queries to external databases. This table is used by I/Informer.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 badge	varchar2(16)	varchar(16)	no		Site specific identifier for query requestor.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date/time stamp
 rec_num	number(10,0)	int	no	nonNegativeNumber	Contains the record number of the message. It is used to join with the state_log table
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
state_badge_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
state_badge_pk	rec_num, badge			primaryKey	yes

 [Top](#)

Table Name - state_image					
Description	This table contains data received from external databases, such as state/federal criminal information systems. This table is used by I/Informer.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Agency ID. Only members of the specified agency can view this response.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation time/date stamp.
dgroup	varchar2(5)	varchar(5)	yes		Dispatch Group. Only members of the specified dispatch group can view this response.
image_data	blob	varbinary(max)	yes		Image data for the jpg, gif, etc
image_data_size [default = 0]	number(10,0)	int	no	nonNegativeNumber	Size of binary image_data
 rec_num	number(10,0)	int	no	nonNegativeNumber	Contains the record number of the message. It is used to join with the state_log table
 resp_num	number(10,0)	int	no	nonNegativeNumber	Used to join with state_resp. It will allow multiple image and/or tagged data file to be grouped together under a given db rec num.
 row_num	number(10,0)	int	no	nonNegativeNumber	Used to order the records
tagged_data	varchar2(4000)	varchar(4000)	yes		Contains non-binary data, such as data from an ASCII, HTML or XML file
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update date/time stamp
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
state_image_cdtsudts	cdts, udts		no	no	
state_image_resp_num	resp_num		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
state_image_primary_key	rec_num, row_num, resp_num			primaryKey	yes

 [Top](#)

Table Name - state_log					
Description	This table is used by I/Informer to record a log of the inquiries/responses to external databases, such as state/federal criminal information systems. When query_rec_num is equal to rec_num, the row corresponds to a query. The udts, upers, uterm columns are set when a record is attached to an event, causing eid and num_1 to also be set.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdevice_id	varchar2(40)	varchar(40)	yes		Create device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
cdevice_sub_type	number(5,0)	smallint	yes	nonNegativeNumber	Qualifier on the create device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
cdevice_type	number(5,0)	smallint	yes	cdevice_type between 0 and 6	Create Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date/time stamp of when the record was created.
cid_type	number(5,0)	smallint	no	cid_type between -1 and 2	Indicates if cterm is a terminal name, unit id, or a vehicle id. 0 = terminal, 1 = unit id, 2 = vehicle id, -1 = unknown
cpers	number(10,0)	int	no	nonNegativeNumber	Employee id of person who created the record.
cterm	varchar2(15)	varchar(15)	no		Creation terminal. Contains the node name of workstation, the unit id of the unit, or the vehicle id of the vehicle where the record was created.
eid	number(10,0)	int	yes	nonNegativeNumber	Event ID. This is a unique number used internally by CAD to keep track of events. A value of 0 indicates that there is no associated event.
hit_message	varchar2(256)	varchar(256)	yes		Specified message to be sent when a hit is found.
input_data	varchar2(256)	varchar(256)	yes		The data that is input by the user in order to run a query.
mke	varchar2(15)	varchar(15)	yes		Query transaction mnemonic - such as QV, QW, DQ
num_1	varchar2(12)	varchar(12)	yes		Agency 'Event' number. Contains the specific agency 'event' number.
ori_id	varchar2(12)	varchar(12)	yes		Contains the ORI for the originator of this query (where ORI use is applicable)

query_rec_num	number(10,0)	int	yes		Contains the db record number of the submitted query.
query_type	number(10,0)	int	no		Contains the number of the query type that is issued (for example, vehicle, person). Not used for retrieving or storing data. Information only.
 rec_num	number(10,0)	int	no	nonNegativeNumber	Contains the unique record number for the information returned by the external system.Software generated.
remotesource	varchar2(32)	varchar(32)	yes		Name of the remote message switch
search_type [default = -1]	number(10,0)	int	no	search_type in (-1,0,1,2)	Type of response, based on search string specified in hit_detect_test.search_tag. -1 (No hit), 0 (Hit), 1 (Error/Alert), 2 (Admin).
transactionnum	number(10,0)	int	yes	nonNegativeNumber	Transaction number of query - used to group responses.
udevice_id	varchar2(40)	varchar(40)	yes		Update device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
udevice_sub_type	number(5,0)	smallint	yes	nonNegativeNumber	Qualifier on the update device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
udevice_type	number(5,0)	smallint	yes	udevice_type between 0 and 6	Update Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date/time stamp of when the record was updated
uid_type	number(5,0)	smallint	yes	(udts is not null and uid_type between -1 and 2) or (udts is null and uid_type is null)	Indicates if uterm is a terminal name, unit id, or a vehicle id. 0 = terminal, 1 = unit id, 2 = vehicle id, -1 = unknown
upers	number(10,0)	int	yes	nonNegativeNumber	Update person. Contains the empid of the person attaching the response to an event.
uterm	varchar2(15)	varchar(15)	yes		Update terminal. Contains the node name of workstation, the unit id of the unit, or the vehicle id of the vehicle where the record was updated.

Indexes					
Index Name	Columns	Is Unique	Sql Server Clustered	Sql Server Where Clause	
state_log_cdt\$udts	cdts, udts	no	no		
state_log_num_1	num_1	no	no		
Key Constraints					
Constraint Name	Columns	Constraint Type	Sql Server Clustered		
state_log_primary_key	rec_num	primaryKey	yes		
Check Constraints					
Constraint Name	Required	Oracle Definition	Sql Server Definition		
state_log_cdev_mdt_smt_id_ck	Yes	(cdevice_type not in (5,6)) or (regexp_like(cdevice_id, ''{0-9A-Fa-f}{1,10}\$'))	(cdevice_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(cdevice_id,10) = 1)		
state_log_cdevice_ck	Yes	(cid_type in(-1,1,2) and cdevice_type is not null and cdevice_sub_type is not null and cdevice_id is not null) or (cid_type = 0 and cdevice_type is null and cdevice_sub_type is null and cdevice_id is null)	(cid_type in(-1,1,2) and cdevice_type is not null and cdevice_sub_type is not null and cdevice_id is not null) or (cid_type = 0 and cdevice_type is null and cdevice_sub_type is null and cdevice_id is null)		
state_log_udev_mdt_smt_id_ck	Yes	(udevice_type not in (5,6)) or (regexp_like(udevice_id, ''{0-9A-Fa-f}{1,10}\$'))	(udevice_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(udevice_id,10) = 1)		
state_log_udevice_ck	Yes	(uid_type in(-1,1,2) and (udts is null or (udevice_type is not null and udevice_sub_type is not null and udevice_id is not null))) or ((uid_type is null or uid_type = 0) and udevice_type is null and udevice_sub_type is null and udevice_id is null)	(uid_type in(-1,1,2) and (udts is null or (udevice_type is not null and udevice_sub_type is not null and udevice_id is not null))) or ((uid_type is null or uid_type = 0) and udevice_type is null and udevice_sub_type is null and udevice_id is null)		

 [Top](#)

Table Name - state_query					
Description	This table stores the text of the query sent to the external system. Previously, this data was stored in state_txt where type_flag was 'Q'. This table is used by I/Informer.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date/time stamp of when the record was created.
query_text	varchar2(1000)	varchar(1000)	yes		Query text sent to external system
 rec_num	number(10,0)	int	no	nonNegativeNumber	Contains the record number of the message. Is used to join the text information to the state_log table.
 row_num	number(10,0)	int	no	nonNegativeNumber	An internal number used for record tracking.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
state_query_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
state_query_primary_key	rec_num, row_num			primaryKey	yes

 [Top](#)

Table Name - state_resp					
Description	This table contains information about responses received from external database. This information is used to map the responses into sets to allow the responses to be matched to their original query. This table is used by I/Informer.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The date/time stamp of when the record was created.
data_type	number(10,0)	int	no	booleanNumber1Or0	Data Type. 0 = response file contains text. 1 = response file contains binary data. If data_type = 0, then the data in state_image for this rec_num, resp_num is text. Else it is binary.
file_ext	varchar2(3)	varchar(3)	no		Contains the three character file extension. i.e. txt, jpg, etc.
image_file	varchar2(240)	varchar(240)	yes	image_file != ''	Contains path and name of any permanently stored image files. Informer reads the data from state_image.image_data and stores the image using this file name.
 rec_num	number(10,0)	int	no	nonNegativeNumber	The record number of the query-response - joins with state_log and state txt.
 resp_num	number(10,0)	int	no	nonNegativeNumber	Used to join with state_image. It will allow multiple image and/or tagged data file to be grouped together under a given db rec num.
user_comment	varchar2(256)	varchar(256)	yes		This column holds the client user comments that will be displayed in the 'UserComment' column in the Responses Window on Informer Client.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
state_resp_cdts	cdts		no	no	
state_resp_image_file	image_file		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
state_resp_primary key	rec_num, resp_num			primaryKey	yes

 [Top](#)

Table Name - station_persl_history	
Description	Records the history for logged on station personnel. CAD inserts a history record whenever an active station personnel record in act_station_persl is inserted, updated or deleted. Added for CR 1-4UUSDH
Copy Type	INSERT

Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Timestamp when record was inserted into table.
change_code	number(10,0)	int	no	change_code in (0,1,2)	Code that describes what action on the active station person caused this history record to be written. 0= logon, 1= modify, 2= logoff
cpers	number(10,0)	int	no	nonNegativeNumber	Employee id of person creating this history record
cterm	varchar2(15)	varchar(15)	no		Terminal creating this history record
delay_value [default = 0]	number(10,0)	int	no	nonNegativeNumber	Delay, in minutes. Amount of time it would take this person to get to the station.
description	varchar2(200)	varchar(200)	yes		Description or comment
empid	number(10,0)	int	no	nonNegativeNumber	Employee id
logoff_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Timestamp for when person logged off.
logon_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Logged on timestamp
logon_method	number(10,0)	int	no	booleanNumber1Or0	The method by which the person was logged on to the station. 0= Logged on implicitly by Logon Unit or Unit Properties. 1= Logged on explicitly by dispatcher using Logon Station Personnel command.
recommended_unid	varchar2(10)	varchar(10)	yes		Unit for which the employee has been recommended. Recommend Unit will set this column.
station	varchar2(10)	varchar(10)	no		Station id
status	number(10,0)	int	no	status in (0,1,2,3)	Current status. 0= available, 1= unavailable (due to a break or other temporary reason), 2= unavailable because the person is currently assigned to a unit, 3= unavailable because Recommend Unit has recommended this person for a unit (recommended_unid contains the recommended unit id).
status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Time when person changed to current status.
 unique_id	raw(16)	varbinary(16)	no		Unique identifier for this record.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
station_persl_history_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
station_persl_history_pk	unique_id			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
station_persl_his_status_un_ck	Yes	(status = 3 and recommended_unid is not null) or (status !=3 and recommended_unid is null)		(status = 3 and recommended_unid is not null) or (status !=3 and recommended_unid is null)	

 [Top](#)

Table Name - subscriber					
Description	A client that is interested in a subscription. This table is used by the Change Publisher Service.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
agency_id	varchar2(9)	varchar(9)	yes		An agency identifier
application	varchar2(15)	varchar(15)	yes		Application that will receive the change information packets. The Change Subscription Publisher Service specifies the application when it sends Listener packets to the clients. So, the value in this column is actually the string that the application uses when it logs on to Listener.
dispatch_group	varchar2(6)	varchar(6)	yes		A dispatch group
 id	raw(16)	varbinary(16)	no		Uniquely identifies a subscriber
 subscription_id	raw(16)	varbinary(16)	no		Identifies the subscription of interest
terminal	varchar2(15)	varchar(15)	yes		The name of a terminal
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
subscriber_pk	id, subscription_id			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
subscriber_ck	Yes	(terminal is not null and agency_id is null and dispatch_group is null and application is null) or (terminal is null and agency_id is not null and dispatch_group is not null and application is null) or (terminal is null and agency_id is null and dispatch_group is null and application is not null)		(terminal is not null and agency_id is null and dispatch_group is null and application is null) or (terminal is null and agency_id is not null and dispatch_group is not null and application is null) or (terminal is null and agency_id is null and dispatch_group is null and application is not null)	

 [Top](#)

Table Name - subscription					
Description	Allows users to subscribe to database change notifications. This table is used by the Change Publisher Service.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 id	raw(16)	varbinary(16)	no		Uniquely identifies a subscription
is_active [default = 'T']	varchar2(1)	varchar(1)	no	booleanTOrF	Indicates if subscription is active (T/F)
name	varchar2(50)	varchar(50)	no		User friendly name that uniquely identifies a subscription
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
subscription_pk	id			primaryKey	no
subscription_uk	name			uniqueKey	yes

 [Top](#)

Table Name - subscription_change_item					
Description	Ties a subscription to a change item. This table is used by the Change Publisher Service.				
Copy Type	ALL				
			Columns		
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 change_item_id	raw(16)	varbinary(16)	no		Identifies the associated change item
 subscription_id	raw(16)	varbinary(16)	no		Identifies the subscription that is associated with this item
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
subscription_change_item_pk	subscription_id, change_item_id			primaryKey	yes

 [Top](#)

Table Name - supp_row						
Description	This table is used to control the inputting of data into the I/CAD supplemental tables.					
Copy Type	ALL					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
current	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator Flag. This column contains the current record indicator flag. (T) denotes current record whereas, (F) indicates an older record.	
 row_num	number(10,0)	int	no		Row Number. This column contains the supplemental row number.	
 stack_id	number(10,0)	int	no		Stack Identifier Number. This column contains the stacked event ID number.	
 tbl_num	number(10,0)	int	no		Table Number. This column contains the supplemental table number.	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
supp_row_primary_key	stack_id, tbl_num, row_num			primaryKey	yes	

 [Top](#)

Table Name - supp_srch_crit						
Description	This table supports saved search criteria for the Supplemental Search command in CAD.					
Copy Type	ALL					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
ag_id	varchar2(9)	varchar(9)	no		Agency ID for agency-specific search criteria, or "*" for common search criteria	
 descrip	varchar2(50)	varchar(50)	no		Descriptive name for the saved search criteria	
item_name	varchar2(30)	varchar(30)	no		Display name of supplemental info item as shown in the Item combo box on the Supplemental Search Criteria dialog	
 order_num	number(5,0)	smallint	no	nonNegativeNumber	Zero-based index of row within saved search criteria definition	
relation	varchar2(4)	varchar(4)	no		Operation for the search criteria as shown in the Relation combo box on the Supplemental Search Criteria dialog	
search_value	varchar2(30)	varchar(30)	yes		Value for search criteria, or NULL if no value saved with criteria	
table_name	varchar2(30)	varchar(30)	no		Display name of supplemental info table as shown in the Table combo box on the Supplemental Search Criteria dialog	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
supp_srch_crit_primary_key	descrip, order_num			primaryKey	yes	

 [Top](#)

Table Name - supp_table10						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS					
Copy Type	UPDATE					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.	
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.	
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.	
current	varchar2(1)	varchar(1)	no	booleanToRF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
disableautoquery	varchar2(1)	varchar(1)	yes	booleanToRF	T= Do not run auto query against this record. Used by Informer.	
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information	
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.	
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.	
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.	
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.	
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp	
unid	varchar2(10)	varchar(10)	yes		The unit related to the event	
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.	
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.	
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.	
Indexes						
Index Name	Columns			Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table10_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2			no	no	
supp_table10_cdtsudts	cdts, udts			no	no	
Key Constraints						
Constraint Name	Columns			Constraint Type	Sql Server Clustered	
supp_table10_pk	eid, row_num, rev_num			primaryKey	yes	

 [Top](#)

Table Name - supp_table11						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS					
Copy Type	UPDATE					
Columns						
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description	
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.	
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.	
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.	
current	varchar2(1)	varchar(1)	no	booleanTOrf	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTOrf	T= Do not run auto query against this record. Used by Informer.	
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information	
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.	
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.	
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.	
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.	
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	

udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table11_cds2udts2	Oracle: string_to_datetimeoffset(cds), string_to_datetimeoffset(udts) SQL Server: cds2, udts2		no	no	
supp_table11_cdsudts	cds, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
supp_table11_pk	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - supp_table12					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
current	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table12_cds2udts2	Oracle: string_to_datetimeoffset(cds), string_to_datetimeoffset(udts) SQL Server: cds2, udts2		no	no	
supp_table12_cdsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table12_pk	eid, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - supp_table13					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
current	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table13_cds2udts2	Oracle: string_to_datetimeoffset(cds), string_to_datetimeoffset(udts) SQL Server: cds2, udts2		no	no	
supp_table13_cdsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table13_pk	eid, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - supp_table14					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table14_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table14_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table14_pk	eid, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - supp_table15					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table15_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table15_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
supp_table15_pk	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - supp_table16					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.

 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table16_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table16_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
supp_table16_pk	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - supp_table17					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table17_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table17_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
supp_table17_pk	eid, row_num, rev_num		primaryKey		yes

 [Top](#)

Table Name - supp_table18					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table18_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table18_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table18_pk	eid, row_num, rev_num			primaryKey	yes

[Top](#)

Table Name - supp_table19					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table19_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table19_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table19_pk	eid, row_num, rev_num			primaryKey	yes

[Top](#)

Table Name - supp_table20					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTorF	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTorF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table20_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
supp_table20_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table20_pk	eid, row_num, rev_num			primaryKey	yes

[Top](#)

Table Name - supp_table9					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The node- name of the terminal from which the event was created.
curent	varchar2(1)	varchar(1)	no	booleanTOrf	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTOrf	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.

info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information
remarks	varchar2(20)	varchar(20)	yes		Remarks. This column contains descriptive remarks about the person related to the event.
 rev_num	number(10,0)	int	no	positiveNumber	The revision number that is incremented when a row is updated.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the person information will be displayed.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column stores the nodename of the terminal which updated this record.
upers	number(10,0)	int	yes	nonNegativeNumber	Update Person. ID of the person updating this record.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. Terminal from which this record was updated.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
supp_table9_cdtstuds2	Oracle: string_to_datetimeoffset(cdtst), string_to_datetimeoffset(udts) SQL Server: cdtst2, udts2		no	no	
supp_table9_cdtstuds	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
supp_table9_pk	eid, row_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - svvw_ras					
Description	This table contains the descriptions of raster file attachments for saved map views.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
bottom_side	number(10,0)	int	no		Bottom side of raster, in UOR coordinates.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create date/time stamp. The time the record was inserted into the database.
cpers	number(10,0)	int	no	nonNegativeNumber	ID of the person saving the view.
cterm	varchar2(15)	varchar(15)	no		Nodename of the terminal saving the view.
deleted	varchar2(1)	varchar(1)	no	booleanTOrF	T if record is deleted, F if available.
descript	varchar2(80)	varchar(80)	yes		The description of the raster file.
filepath	varchar2(240)	varchar(240)	no		The full file path of the raster file.
left_side	number(10,0)	int	no		Left side of raster, in UOR coordinates.
off_range	number(10,0)	int	no		Autolevel - display raster if window width is more than this UOR range.
on_range	number(10,0)	int	no		Autolevel - display raster if window width is less than this UOR range.
 ras_order	number(10,0)	int	no	nonNegativeNumber	The sequence number (0-based) of this raster file attachment within this saved view.
rasname	varchar2(32)	varchar(32)	no		The displayed name of the raster file.
right_side	number(10,0)	int	no		Right side of raster, in UOR coordinates.
top_side	number(10,0)	int	no		Top side of raster, in UOR coordinates.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The data/time stamp of when the record was updated (deleted).
upers	number(10,0)	int	yes	nonNegativeNumber	Th ID of the person updating (deleting) the record.
uterm	varchar2(15)	varchar(15)	yes		The nodename of the terminal updating (deleting)the record.
 view_index	number(10,0)	int	no		The join column to the save_vw table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
svvw_ras_primary_key	view_index, ras_order			primaryKey	yes

 [Top](#)

Table Name - svvw_ref					
Description	This table contains the descriptions of reference files for saved map views.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
autolevels	varchar2(64)	varchar(64)	no		Autolevel setting for each map level
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create date/time stamp. The time the record was inserted into the database.
cpers	number(10,0)	int	no	nonNegativeNumber	The ID of the person saving the view.
cterm	varchar2(15)	varchar(15)	no		The nodename of the terminal saving the view.
deleted	varchar2(1)	varchar(1)	no	booleanTorF	T if view is deleted, F if available.
descript	varchar2(80)	varchar(80)	yes		The description of the reference file.
filepath	varchar2(240)	varchar(240)	no		The full path to the reference file.
levels	varchar2(64)	varchar(64)	no		A if using autolevels, or a string of 64 zeros and ones for levels off and on.
 ref_order	number(10,0)	int	no	positiveNumber	Sequence number of this reference file within this saved view. (1-based)
refname	varchar2(32)	varchar(32)	no		The displayed name of the reference file.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	The date/time stamp of when the record was updated (deleted).
upers	number(10,0)	int	yes	nonNegativeNumber	The ID of the person updating (deleting) the record.
uterm	varchar2(15)	varchar(15)	yes		The nodename of the terminal updating (deleting) the record.
 view_index	number(10,0)	int	no		Join column with the save_vw table.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
svvw_ref_primary_key	view_index, ref_order			primaryKey	yes

 [Top](#)

Table Name - sys_hist					
Description	This table is used to track the system history of certain commands executed by I/CAD. These are: Define Node, Define Remote Node, Stack Event, Stack Event Alarm, Change Deployment Table, Change Password, Global Time, ETA Off, ETA On, Change Unit Number, Reset Password, Response Time Down, Response Time Clear, Transfer Unit, Unit Properties, and Logoff Unit.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Current Date/Time Stamp. This column contains the date/time stamp that represents the date and time this record was created.
cmd_name	varchar2(40)	varchar(40)	no		Command Name. Name of the command that was executed in I/CAD.
comments	varchar2(240)	varchar(240)	yes		Comments. This column contains the textual comments.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column contains the unique ID of the operator creating the record.
esec	number(19,0)	bigint	no		Cdts time stamp stored in epoch seconds
cterm	varchar2(15)	varchar(15)	no		Terminal Node Identifier. This column contains the name of the terminal node that created the record.
 unique_id	raw(16)	varbinary(16)	no		Unique id. Used to uniquely identify each row in the table.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause

sys_hist_cdt5	cdts	no	yes	
Key Constraints				
Constraint Name	Columns		Constraint Type	Sql Server Clustered
sys_hist_pk	unique_id		primaryKey	no

[Top](#)

Table Name - talk_groups_mgmt					
Description	This table defines the possible MCGE talkchannels which can be associated to a given CAD event for verbal communication.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 label	varchar2(15)	varchar(15)	no		MCGE talkchannel alias
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
talk_groups_mgmt_pk	label			primaryKey	yes

[Top](#)

Table Name - task_force					
Description	The task_force table allows the user to group several units (belonging to the previously defined agencies) into a single dispatchable "unit" or "task force".				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	no		Agency ID. Defines to which agency the task is associated.
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group. Defines the dispatch group with which the task force is associated.
lev_3	varchar2(7)	varchar(7)	yes		Level 3 Area. Defines the current beat assignment.
 taskid	varchar2(6)	varchar(6)	no		Task ID. The task ID is a unique identifier for the task force.
tasktype	varchar2(6)	varchar(6)	yes		Task Type. This column defines the type of task force being created (for example, SWAT, Station, and so on).
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
task_force_primary_key	taskid			primaryKey	yes

[Top](#)

Table Name - task_unit					
Description	The task_unit table defines the units which comprise the Task Force as described in the task_force table.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 taskid	varchar2(6)	varchar(6)	no		Task ID. The task_id is a unique identifier for the task force.
 unit_id	varchar2(10)	varchar(10)	no		Unit ID. This column defines the unit(s) which compromises the Task Force.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
task_unit_primary_key	taskid, unit_id			primaryKey	yes

[Top](#)

Table Name - telgroupmap					
Description	Defines the maps between the CAD Call Group and the 15-char Call Group used by the third-party. This feature is configurable. This table is used mainly by CAD Interface applications.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 dgroup	varchar2(5)	varchar(5)	no		CAD Call Group
telgroup	varchar2(15)	varchar(15)	no		Call Group used by the third-party.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
telgroupmap_dgroup	dgroup		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
telgroupmap_pk	dgroup			primaryKey	yes
telgroupmap_uk	telgroup			uniqueKey	no

[Top](#)

Table Name - term					
Description	This table contains information unique to each terminal node.				
Copy Type	ALL				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
current_callback_term [default = 'N']	varchar2(1)	varchar(1)	no	current_callback_term in ('L','N','Y')	Is this node currently a callback terminal? Y means node is currently a callback terminal, N means node is not currently a callback terminal, L means CAD is locked in Change Operator mode.
default_callback_term [default = 'N']	varchar2(1)	varchar(1)	no	default_callback_term in ('Y','N','D')	Default state of callback terminal status. This column is set by CADDDBM. Y means allowed but not set by default, N means Not allowed, D means allowed and assign by default.
description	varchar2(50)	varchar(50)	yes		Description for terminal node.
domain [default = 'default']	varchar2(50)	varchar(50)	no		Machine's domain name. If domain = 'default', Listener will check the DefaultDomain parameter in the ListenerConfig parameter list.
fsa_opid	number(10,0)	int	yes		The FSA_OPID column is used to define what console position (operator ID) orginated the alert. It is used for Fire Station Alerting-Moscad.
mux_id	number(10,0)	int	yes		Multiplexer ID Code. Defines the ani/ali node that corresponds to a phone line of the E-9-1-1 mux. The mux_id is called the Console Position in CADDDBM. Links to an al.position_id
remote_only [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Is the machine defined for remote access only? Y means machine is defined for remote access only, and cannot run the I/CAD Listener locally. N means machine can run the Listener locally.
 term	varchar2(15)	varchar(15)	no		Terminal Node Name
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
term_mux_id unique	mux_id		yes	no	mux_id is not null
Key Constraints					
Constraint Name	Columns		Constraint Type	Sql Server Clustered	
term_pk	term		primaryKey	yes	

[Top](#)

Table Name - term_alias					
Description	Table to hold list of alias names for CAD terminals. A record here is usually associated with a second Network Interface Card (NIC) in a workstation or server.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 alias	varchar2(15)	varchar(15)	no		Name associated with additional network interface card
domain [default = 'default']	varchar2(50)	varchar(50)	no		Domain name. If domain = 'default', Listener will check the DefaultDomain parameter in the ListenerConfig parameter list.
term	varchar2(15)	varchar(15)	no		Must match the term field in a record in the term table
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
term_alias_primary_key	alias			primaryKey	yes

 [Top](#)

Table Name - term_special_app					
Description	This table stores the special applications that are allowed to run on each terminal node. The list of valid special applications is stored in the caddbm NodesSpecApps parameter list.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 special_app	varchar2(15)	varchar(15)	no		Special application
 term	varchar2(15)	varchar(15)	no		Terminal Node Name
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
term_special_app_pk	term, special_app			primaryKey	yes

 [Top](#)

Table Name - timer					
Description	Used to maintain data about individual timers				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Agency timer is associated with
category	varchar2(2)	varchar(2)	no	category in ('EV','UN','GE')	EV = event, UN = unit, GE = general, not associated with event or unit
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date, time stamp of when timer is created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Date/ time stamp of when timer is created.
closing_text	varchar2(160)	varchar(160)	yes		Text string associated with closing of the timer.
cpers	number(10,0)	int	no		Employee id of creator
cterm	varchar2(15)	varchar(15)	no		Terminal node identifier of creator.
dgroup	varchar2(5)	varchar(5)	yes		Dispatch group timer is associated with
object_id	varchar2(30)	varchar(30)	no		For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
repeat	varchar2(1)	varchar(1)	no	booleanTorF	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.
rev_num	number(10,0)	int	no		Revision number of unique timer
set_name	varchar2(15)	varchar(15)	yes		Name of set that timer is associated.
start_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date, time stamp of when timer begins executing.
status_code	number(10,0)	int	no	status_code in (0,1,2,3)	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled
timeout	number(10,0)	int	no		Timer expiration in seconds. Range can be 1 to max int.
timeout_text	varchar2(160)	varchar(160)	yes		Text string associated with expiration of timer.
 timer_id	raw(16)	varbinary(16)	no		Uniquely identifies the row
type	number(10,0)	int	no		The type of timer
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date, time stamp of when timer is updated
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
upers	number(10,0)	int	yes		Employee id of updating person
uterm	varchar2(15)	varchar(15)	yes		Terminal node identifier of updater
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
timer_cdts2udts2	Oracle: string to datetimeoffset(cdts), string to datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
timer_cdtsudts	cdts, udts		no	no	
timer_rcvr_unique_id	recovery_unique_id		no	no	
timer_status_code	status_code		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
timer_pk	timer_id			primaryKey	no
timer_uk	category, object_id, type, recovery_unique_id			uniqueKey	yes

 [Top](#)

Table Name - timer_history					
Description	Used to maintain data about individual timer history				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
ag_id	varchar2(9)	varchar(9)	yes		Agency timer is associated with
category	varchar2(2)	varchar(2)	no	category in ('EV','UN','GE')	EV = event, UN = unit, GE = general, not associated with event or unit
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date, time stamp of when timer is created.
closing_text	varchar2(160)	varchar(160)	yes		Text string associated with closing of the timer.
cpers	number(10,0)	int	no		Employee id of creator
cterm	varchar2(15)	varchar(15)	no		Terminal node identifier of creator.
dgroup	varchar2(5)	varchar(5)	yes		Dispatch group timer is associated with
object_id	varchar2(30)	varchar(30)	no		For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name
repeat	varchar2(1)	varchar(1)	no	booleanTOrf	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.
 rev_num	number(10,0)	int	no		Revision number of unique timer
set_name	varchar2(15)	varchar(15)	yes		Name of set that timer is associated.
start_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Date, time stamp of when timer begins executing.
status_code	number(10,0)	int	no	status_code in (0,1,2,3)	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled

timeout	number(10,0)	int	no		Timer expiration in seconds. Range can be 1 to max int.
timeout_text	varchar2(160)	varchar(160)	yes		Text string associated with expiration of timer.
 timer_id	raw(16)	varbinary(16)	no		Uniquely identifies the row
type	number(10,0)	int	no		The type of timer
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
timer_history_pk	timer_id, rev_num		primaryKey		yes

 [Top](#)

Table Name - tooltip_file					
Description	Contains the contents of files used by the XML Tooltip feature. Most of these files will be XSL files.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation date timestamp
file_content	blob	varbinary(max)	yes		Contents of file
 file_name	varchar2(256)	varchar(256)	no		Name of file, without the path.
file_size	number(10,0)	int	no	nonNegativeNumber	Size of file in Kilobytes
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update time stamp
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
tooltip_file_primary_key	file_name			primaryKey	yes

 [Top](#)

Table Name - tow_req_and_vehic_history					
Description	Maintains the relationship between rows in tow_request_history and those in tow_request_vehicle_history				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create timestamp
request_num	number(10,0)	int	no		The request_num from tow_request_history
request_rev_num	number(10,0)	int	no		The rev_num from tow_request_history
rev_num	number(10,0)	int	no	positiveNumber	The revision number for this table
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies rows
vehicle_id	number(10,0)	int	yes		The vehicle_id from tow_request_vehicle_history
vehicle_request_num	number(10,0)	int	yes		The request_num from tow_request_vehicle_history
vehicle_rev_num	number(10,0)	int	yes		The rev_num from tow_request_vehicle_history
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
tow_req_and_vehic_history_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
tow_req_and_vehic_history_pk	unique_id			primaryKey	no
tow_req_and_vehic_history_uk	request_num, vehicle_id, rev_num, request_rev_num, vehicle_rev_num			uniqueKey	yes

 [Top](#)

Table Name - tow_request					
Description	This table is used to store information about a request for towing a particular vehicle associated with an event via vehic supplemental information.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cancel_requested [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	A request to cancel the tow request has been made
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Tow service request creation date time stamp
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Tow service request creation date time stamp.
comment_text	varchar2(200)	varchar(200)	yes		Tow request creation comment
cpers	number(10,0)	int	no	nonNegativeNumber	Employee id of operator creating the tow service request
cterm	varchar2(15)	varchar(15)	no		The tow service request creation terminal
eid	number(10,0)	int	no	positiveNumber	Id of associated event record
history_comment	varchar2(200)	varchar(200)	yes		Latest tow request history comment
num_1	varchar2(12)	varchar(12)	no		Event number for which vehicle tow service requested
pickup_loc_ver	varchar2(1)	varchar(1)	no	booleanToRF	Location verified status for the tow request pickup location
pickup_loc_x	number(10,0)	int	no		Pickup location x coordinate in uors
pickup_loc_y	number(10,0)	int	no		Pickup location y coordinate in uors
pickup_location	varchar2(80)	varchar(80)	no		Location for vehicle pickup
 request_num	number(10,0)	int	no		Tow service request number
request_status	number(5,0)	smallint	no	request_status >= 0 and request_status <= 99	Overall status of tow request. Pending=0, InProgress=1, PartialService=2, CompleteService=3, Closed=4, Canceled=5
status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date time stamp when request status changed to current status
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		Unit id assigned to event for which vehicle tow service requested
updt_term	varchar2(15)	varchar(15)	yes		If not NULL, then the record is locked by the terminal id in this column
upers	number(10,0)	int	yes	nonNegativeNumber	Update employee id
uterm	varchar2(15)	varchar(15)	yes		Update terminal
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
tow_request_cdts2udts2	Oracle: string_to_datetimeoffset(cdts), string_to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
tow_request_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
tow_request_pk	request_num			primaryKey	yes

 [Top](#)

Table Name - tow_request_history	
Description	This table is used to store information about a request for towing a particular vehicle associated with an event via vehic supplemental information.

Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cancel_requested [default = 'F']	varchar2(1)	varchar(1)	no	booleanToRF	A request to cancel the tow request has been made
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Tow service request creation date time stamp
comment_text	varchar2(200)	varchar(200)	yes		Tow request creation comment
cpers	number(10,0)	int	no	nonNegativeNumber	Employee id of operator creating the tow service request
cterm	varchar2(15)	varchar(15)	no		The tow service request creation terminal
eid	number(10,0)	int	no	positiveNumber	Id of associated event
history_comment	varchar2(200)	varchar(200)	yes		Latest tow request history comment
num_1	varchar2(12)	varchar(12)	no		Event number for which vehicle tow service requested
pickup_loc_ver	varchar2(1)	varchar(1)	no	booleanToRF	Location verified status for the tow request pickup location
pickup_loc_x	number(10,0)	int	no		Pickup location x coordinate in uors
pickup_loc_y	number(10,0)	int	no		Pickup location y coordinate in uors
pickup_location	varchar2(80)	varchar(80)	no		Location for vehicle pickup
 request_num	number(10,0)	int	no		Tow service request number
request_status	number(5,0)	smallint	no	request_status >= 0 and request_status <= 99	Overall status of tow request. Pending=0, InProgress=1, PartialService=2, CompleteService=3, Closed=4, Canceled=5
 rev_num	number(10,0)	int	no	positiveNumber	Revision number of record.
status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date time stamp when request status changed to current status
unitid	varchar2(10)	varchar(10)	yes		Unit id assigned to event for which vehicle tow service requested
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
tow_request_history_cdts	cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
tow_request_history_pk	request_num, rev_num			primaryKey	yes

 [Top](#)

Table Name - tow_request_vehicle					
Description	This table contains vehicle records that are associated with a tow request				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cancel_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Vehicle service cancellation date time stamp
cancel_pers	number(10,0)	int	yes	nonNegativeNumber	Vehicle service cancellation operator employee id
cancel_term	varchar2(15)	varchar(15)	yes		Vehicle service cancellation terminal
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Tow service request vehicle creation date time stamp
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Tow service request vehicle creation date time stamp.
company_id	number(10,0)	int	yes		Company numeric id
company_name	varchar2(30)	varchar(30)	yes		Name of company from Special Request or associated with company_id
cpers	number(10,0)	int	no	nonNegativeNumber	Creating employee id
cterm	varchar2(15)	varchar(15)	no		Creating terminal
equipment	varchar2(10)	varchar(10)	yes		Equipment type
eta	number(10,0)	int	yes		Estimated time of arrival for service
main_svc_type	varchar2(8)	varchar(8)	yes		Main service type
person_contacted	varchar2(25)	varchar(25)	yes		Name of the company contact
reason	varchar2(8)	varchar(8)	yes		Reason for service
remarks	varchar2(1000)	varchar(1000)	yes		Remarks concerning service
 request_num	number(10,0)	int	no		Tow service request number
rotation_code	varchar2(8)	varchar(8)	yes		Rotational service code
special_company [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	This is a special company request and any rotation is bypassed.
sub_svc_type	varchar2(8)	varchar(8)	yes		Sub service type
tow_status	number(5,0)	smallint	no	tow_status >= 0 and tow_status <= 99	Status of the tow equipment assigned to the tow request vehicle. The valid values come from the ID column in the cad UnitStatus parameter table. The towing user interface in Dispatcher shows the mnemonic value from UnitStatus. 0: AV (Available), 2: AP (Available on Pager), 7: DP (Dispatched), 8: ER (Enroute), 9: AR (arrive), 13: TR (Transport), 14: TA (Transport Arrive), 15: AK (Acknowledge)
tow_status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date time stamp when tow service changed to current status
towed_loc_ver [default = 'F']	varchar2(1)	varchar(1)	no	booleanTOrF	Location verified status for the vehicle's towed location
towed_location	varchar2(80)	varchar(80)	yes		Towed location for vehicle
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update timestamp
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
upers	number(10,0)	int	yes	nonNegativeNumber	Updating employee id
uterm	varchar2(15)	varchar(15)	yes		Updating terminal
vehic_eid	number(10,0)	int	no		Vehic supplemental information eid of vehicle
vehic_row_num	number(10,0)	int	no		Vehic supplemental information row_num of vehicle
 vehicle_id	number(10,0)	int	no		Vehicle numeric id for tow request
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
tow_request_vehicle_cdts2udts2	Oracle: string to_datetimeoffset(cdts), string to_datetimeoffset(udts) SQL Server: cdts2, udts2		no	no	
tow_request_vehicle_cdtsudts	cdts, udts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
tow_request_vehicle_pk	request_num, vehicle_id			primaryKey	yes

 [Top](#)

Table Name - tow_request_vehicle_history					
Description	This table contains history records about vehicles that are associated with a tow request				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cancel_dts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Vehicle service cancellation date time stamp
cancel_pers	number(10,0)	int	yes	nonNegativeNumber	Vehicle service cancellation operator employee id
cancel_term	varchar2(15)	varchar(15)	yes		Vehicle service cancellation terminal
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Tow service request vehicle creation date time stamp
company_id	number(10,0)	int	yes		Company numeric id
company_name	varchar2(30)	varchar(30)	yes		Name of company from Special Request or associated with company_id

cpers	number(10,0)	int	no	nonNegativeNumber	Creating employee id
cterm	varchar2(15)	varchar(15)	no		Creating terminal
equipment	varchar2(10)	varchar(10)	yes		Equipment type
eta	number(10,0)	int	yes		Estimated time of arrival for service
main_svc_type	varchar2(8)	varchar(8)	yes		Main service type
person_contacted	varchar2(25)	varchar(25)	yes		Name of the company contact
reason	varchar2(8)	varchar(8)	yes		Reason for service
remarks	varchar2(1000)	varchar(1000)	yes		Remarks concerning service
 request_num	number(10,0)	int	no		Tow service request number
 rev_num	number(10,0)	int	no	positiveNumber	Revision number of history record
rotation_code	varchar2(8)	varchar(8)	yes		Rotational service code
special_company	varchar2(1)	varchar(1)	no	booleanTOrf	This is a special company request and any rotation is bypassed.
sub_svc_type	varchar2(8)	varchar(8)	yes		Sub service type
tow_status	number(5,0)	smallint	no	tow_status >= 0 and tow_status <= 99	Status of tow service for vehicle
tow_status_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Date time stamp when tow service changed to current status
towed_loc_ver	varchar2(1)	varchar(1)	no	booleanTOrf	Location verified status for the vehicle's towed location
towed_location	varchar2(80)	varchar(80)	yes		Towed location for vehicle
vehic_eid	number(10,0)	int	no		Vehic supplemental information eid of vehicle
vehic_row_num	number(10,0)	int	no		Vehic supplemental information row_num of vehicle
 vehicle_id	number(10,0)	int	no		Vehicle numeric id for tow request
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
tow_request_vehic_history_cdt5	cdts		no	no	
Key Constraints					
Constraint Name	Columns		Constraint Type	Sql Server Clustered	
tow_request_vehicle_history_pk	request_num, vehicle_id, rev_num		primaryKey	yes	

 [Top](#)

Table Name - trans_des					
Description	This table stores a list of transport location information for use in Transport commands.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create date time stamp.
eid	number(10,0)	int	no	nonNegativeNumber	Unique Event Id Number generated by the system. A value of 0 indicates that there is no associated event.
location	varchar2(240)	varchar(240)	no		Transport location text.
num_1	varchar2(12)	varchar(12)	yes		Agency event number.
origin_location	varchar2(240)	varchar(240)	yes		Origin location text.
origin_verified [default = 'N']	varchar2(1)	varchar(1)	no	booleanYOrN	Origin verified flag
origin_x_coord [default = 0]	number(10,0)	int	no		X coordinate of the node associated with the origin
origin_y_coord [default = 0]	number(10,0)	int	no		Y coordinate of the node associated with the origin
sched_id	varchar2(12)	varchar(12)	yes		Scheduled event id.
 unique_id	raw(16)	varbinary(16)	no		
verified	varchar2(1)	varchar(1)	no	booleanYOrN	If the location verified. ("Y" or "N")
x_coord [default = 0]	number(10,0)	int	no		This column represents the X coordinate of the node associated with the transport destination.
y_coord [default = 0]	number(10,0)	int	no		This column represents the Y coordinate of the node associated with the transport destination.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
trans_des_cdt5	cdts		no	no	
trans_des_num_1	num_1		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
trans_des_pk	unique_id		primaryKey		no

 [Top](#)

Table Name - un_hi					
Description	This table contains a history of everything that has happened to all the units in the system. When data in the active unit's child tables act_persl or act_device is modified (other than location data), CAD records a new change id, and writes the latest personnel and device history, as well as unit history. The un_hi_child_change_id identifies a set of un_hi_persl and un_hi_device records, that are valid for one or more un_hi records.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
act_check	varchar2(1)	varchar(1)	yes		Load Flag. If this value is not NULL, the record is to be ignored at load time. For example, if values were loaded in using Manual Times in I/CAD, this value would be set to (F).
ag_id	varchar2(9)	varchar(9)	no		Agency id (from agenc table) that the unit is associated with.
agency_event_rev_num	number(10,0)	int	yes	positiveNumber	The revision number of the agency event. When the unit is assigned to an event, this column contains the revision number of the event at the time the unit history record is written.
carid	varchar2(12)	varchar(12)	yes		Car ID. The vehicle identification number. This could be the actual number painted on the car, or any other identification information about the unit.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp of when the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification number of the person who created the event.
crew_id	varchar2(30)	varchar(30)	yes		ID of crew assigned to unit.
csec	number(19,0)	bigint	no		Cdts time stamp stored in epoch seconds
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The nodename of the terminal from which the record was created.
dgroup	varchar2(5)	varchar(5)	no		Dispatch Group. The dispatch group to which the unit is assigned. It links to the dgroup columns in the app_access, agency_dgroup, cd_units, roster, esz, and agency_event tables.
disp_alarm_lev	number(10,0)	int	yes	nonNegativeNumber	Alarm Level of the event when the unit was dispatched
disp_num	varchar2(12)	varchar(12)	yes		Dispatch Number. This column contains the unique dispatch number for the unit for an event.
eid	number(10,0)	int	yes	positiveNumber	Event Identification Number. The system event number if the current record was generated while the unit was assigned to an event. It links to the eid column in the common_event, agency_event, evcom, vehic, perso, and propt tables.
lastxor	number(10,0)	int	no		Last known X-coordinate of the unit in "uors" (the Map design files coordinate system -- units of resolution). This is used for placing the unit symbol on the map screen.
lastyor	number(10,0)	int	no		Last known Y-coordinate of the unit in "uors" (the Map design files coordinate system -- units of resolution). This is used for placing the unit symbol on the map screen.
latitude	binary_double	float(53)	no		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)

location	varchar2(80)	varchar(80)	yes		Unit Location. This column contains the last known location of the unit. This value is displayed on the status monitor.
longitude	binary_double	float(53)	no		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
mdthostname	varchar2(24)	varchar(24)	yes		System name of the mobile terminal. Used by I/MDT and Informer to route Informer responses when "node-locked" ORI authorization is necessary.
mileage	varchar2(8)	varchar(8)	yes		Indicates initial mileage of the unit at log on. This value can also indicate the mileage of the unit at the time of a status change.
num_1	varchar2(12)	varchar(12)	yes		Agency "event" number that this unit history is associated with. It is linked to the num_1 column in the agency_event table.
oag_id	varchar2(9)	varchar(9)	yes		The old agency id for a transferred unit.
odgroup	varchar2(5)	varchar(5)	yes		Original dispatch group that the unit was assigned to - in case of transfer event/unit.
page_id	varchar2(12)	varchar(12)	yes		The page id used to link tables such as def_page and cd_units. Used to look up pager codes and system types and other specific paging info.
recovery_cdt [default = 'default']	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. Stores the date/time stamp of when the record was created. This is generally the same as cdt except for backdated (Manual Times) records.
station	varchar2(10)	varchar(10)	yes		Current station/post id.
sub_tycod	varchar2(16)	varchar(16)	yes		The sub-type of the event type.
track_personnel [default = 'N']	varchar2(1)	varchar(1)	no	booleanYORn	Are the unit's personnel being tracked separately from the unit? Y= Yes, N= No
tycod	varchar2(16)	varchar(16)	yes		Event Type Code. The type of the event if the current record was generated while the unit was assigned to an event. When the unit is out of service, this column contains the out of service code. May contain the disposition code in certain situations
ucust1	varchar2(50)	varchar(50)	yes		Unit custom column 1
ucust2	varchar2(50)	varchar(50)	yes		Unit custom column 2
ucust3	varchar2(50)	varchar(50)	yes		Unit custom column 3
ucust4	varchar2(50)	varchar(50)	yes		Unit custom column 4
uhiscm	varchar2(200)	varchar(200)	yes		Unit History Comment. Any comment associated with this unit's history record.
un_hi_child_change_id	raw(16)	varbinary(16)	no		Child change ID. Links to child change id column in un_hi_device and un_hi_persl. To reduce database writes, CAD only writes child records if some child data changes.
unid	varchar2(10)	varchar(10)	no		Unit ID. The unit name that is associated with this history record. It links to the unid column in the cd_units and roster tables.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a unit history row.
unit_status	varchar2(2)	varchar(2)	no		Unit's Status. The current status of the unit as it is defined in the cad UnitStatus parameter table and StatusDisplay parameter list. For example, "AV" for "available on radio", "ER" for "enroute", and so on. This column may contain why the history record was written, such as UE for "Unit employee update."
unityp	varchar2(6)	varchar(6)	yes		Unit type (patrol, pumper, etc).
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
un_hi_cdt2	Oracle: string_to_datetimeoffset(cdt) SQL Server: cdt2		no	no	
un_hi_cdt_unid	cdts, unid		no	yes	
un_hi_child_change_id_unid	un_hi_child_change_id, unid		no	no	
un_hi_cid	cid		no	no	
un_hi_num_1_ag_evt_rev_num	num_1, agency_event_rev_num		no	no	
un_hi_recovery_cdt	recovery_cdt		no	no	
un_hi_unid	unid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
un_hi_primary_key	unique_id			primaryKey	no
Check Constraints					
Constraint Name		Required	Oracle Definition		Sql Server Definition
un_hi_num_1_ag_evt_rev_num_ck		Yes	(num_1 is null and agency_event_rev_num is null) or (num_1 is not null and agency_event_rev_num is not null)		(num_1 is null and agency_event_rev_num is null) or (num_1 is not null and agency_event_rev_num is not null)
Triggers					
Trigger Name		Required	Trigger Type		Description
un_hi_default_trig		Yes	Custom		Converts default string to the current time since Oracle doesn't allow user defined functions in default values

 [Top](#)

Table Name - un_hi_child_change					
Description	Records the unit history child change IDs. CR 1-6PGD42: PLT				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation timestamp
 un_hi_child_change_id	raw(16)	varbinary(16)	no		Unit history child change id. A new ID is written when unit's personnel and/or unit's devices are modified, and new un_hi_persl and un_hi_device records are written
unid	varchar2(10)	varchar(10)	no		Unit ID
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
un_hi_child_change_cdt s _unid	cdts, unid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
un_hi_child_change_pk	un_hi_child_change_id			primaryKey	yes

 [Top](#)

Table Name - un_hi_device					
Description	This table contains history information, aside from location updates, for the unit's devices and the unit personnel's devices. The history of location changes is stored in un_hi_device_loc. CR 1-6PGD42: PLT				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
apedata	varchar2(64)	varchar(64)	yes		IP Address and port last received by the MDT Server from the Client
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Insert datetime
clientid	varchar2(64)	varchar(64)	yes		Contains the unique ID provided by the MPS Client
description	varchar2(50)	varchar(50)	yes		Description
device_alias	varchar2(20)	varchar(20)	yes		User-friendly alias name for device

 device_id	varchar2(40)	varchar(40)	no		Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
 device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
empid	number(10,0)	int	yes	nonNegativeNumber	If owner = 1, this column has the employee that owns the device.
gps_protocol [default = 0]	number(5,0)	smallint	no	nonNegativeNumber	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols
is_master_mdt [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	From MDT Server's perspective, is this the master device for this unit? 1= Master device, 0= Not master device.
is_trackable [default = 0]	number(5,0)	smallint	no	booleanNumber1Or0	Is device trackable? 0 = False, 1 = True
owner	number(5,0)	smallint	no	owner between 0 and 1	Device's owner. 0 = unit, 1 = employee
smartphone_device_id	varchar2(64)	varchar(64)	yes		Physical device id of the Apple iOS, Android, Windows Phone, etc. device
smartphone_os	number(10,0)	int	yes	smartphone_os between 0 and 3	Type of smartphone. 0= Apple iOS, 1= Android, 2= Blackberry, 3= Windows
tdevice_for_emp	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False
tdevice_for_unit	number(5,0)	smallint	no	booleanNumber1Or0	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False
 un_hi_child_change_id	raw(16)	varbinary(16)	no		Unit history child change id.
unid	varchar2(10)	varchar(10)	no		Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
un_hi_device_cdts_unid_empid	cdts, unid, empid		no	no	
un_hi_device_owner	owner		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
un_hi_device_pk	un_hi_child_change_id, device_id, device_type, device_sub_type			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
un_hi_device_is_master_mdt_type	Yes	(is_master_mdt = 1 and device_type = 6) or is_master_mdt = 0		(is_master_mdt = 1 and device_type = 6) or is_master_mdt = 0	
un_hi_device_mdt_smt_id_ck	Yes	(device_type not in (5,6)) or (regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$'))		(device_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)	
un_hi_device_owner2_ck	Yes	(owner = 0 and empid is null) or (owner = 1 and empid is not null)		(owner = 0 and empid is null) or (owner = 1 and empid is not null)	
un_hi_device_tdevice_ck	Yes	(is_trackable = 1 or (tdevice_for_emp = 0 and tdevice_for_unit = 0)) and (owner = 1 or tdevice_for_emp = 0)		(is_trackable = 1 or (tdevice_for_emp = 0 and tdevice_for_unit = 0)) and (owner = 1 or tdevice_for_emp = 0)	

 [Top](#)

Table Name - un_hi_device_loc					
Description	This table replaces the avl_log table. If the I/Tracker ArchiveToDatabase registry setting is enabled, then I/Tracker logs all processed AVL position reports, for units and unit personnel, to this table. The measurement units for the fields depend on what is supported by the tracking system. Note: some implementations of the I/Tracker interface product do not record information in all of the columns (because they are not included in the position report). CR 1-6PGD42: PLT				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
altitude	binary_double	float(53)	yes		Distance above mean sea level (+ above).
bearing	binary_double	float(53)	yes		Clockwise angle from true North range [0, 360.0]
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation timestamp for this record.
device_id	varchar2(40)	varchar(40)	no		Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT
empid	number(10,0)	int	yes	nonNegativeNumber	If owner = 1, this column has the employee that owns the device
fix_age	number(5,0)	smallint	yes	fix_age between 0 and 2	Code for age of fix when this location was recorded (not the current age of the data). 0=unknown, 1=10 seconds or greater, 2=less than 10 seconds
fix_type	number(5,0)	smallint	yes	fix_type in (0,1,2,3,6,8,9)	GPS source (fix type) indicator. 0=2D, 1=3D, 2=2D-differential, 3=3D-differential, 6=dead reckoning, 8=degraded, 9=unknown/invalid
gps_date	varchar2(8)	varchar(8)	yes		Date of last GPS data from the device, in YYYYMMDD format
gps_time	number(10,0)	int	yes		Time of last GPS data from the device, stored in seconds since midnight UTC
horizontal_precision	number(5,0)	smallint	yes	horizontal_precision between 0 and 50	Horizontal dilution of precision: 1=ideal, 2-3=excellent, 4-6=good, 7-8=moderate, 9-20=fair, 21-50=poor
latitude	binary_double	float(53)	yes		Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
loc_x	number(10,0)	int	yes		X-Coordinate of the device
loc_y	number(10,0)	int	yes		Y Coordinate of the device
location	varchar2(80)	varchar(80)	yes		Location, derived from reverse geocoding the device's coordinates.
longitude	binary_double	float(53)	yes		Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
owner	number(5,0)	smallint	no	owner between 0 and 1	Device's owner. 0 = unit, 1 = employee
sat_count	number(5,0)	smallint	yes	nonNegativeNumber	Number of satellites used in fix
sensor	varchar2(150)	varchar(150)	yes		Sensor data. Previously called device in old avl_log table
speed_bearing	binary_double	float(53)	yes		Speed along the bearing (+ forward, - reverse). Units depends on what is supported by the AVL system
speed_vertical	binary_double	float(53)	yes		Speed vertical (+ up, - down). Units depends on what is supported by the AVL system
un_hi_rec_id	raw(16)	varbinary(16)	no		The un_hi record which this location update corresponds to. Tracker reads this value from cd_units.un_hi_rec_id.
unid	varchar2(10)	varchar(10)	no		Unit ID
 unique_id	raw(16)	varbinary(16)	no		Unique identifier
units_of_measurement [default = 0]	number(5,0)	smallint	no	units_of_measurement between 0 and 2	0=unknown, 1=metric (meters/KPH), 2=imperial (feet/MPH)
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
un_hi_device_loc_cdt5_unid	cdts, unid		no	yes	
un_hi_device_loc_rec_id_unid	un_hi_rec_id, unid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
un_hi_device_loc_pk	unique_id			primaryKey	no

Check Constraints			
Constraint Name	Required	Oracle Definition	Sql Server Definition
un_hi_dev_loc_mdt_smt_id_ck	Yes	(device_type not in (5,6)) or (regexp_like(device_id, '[0-9A-Fa-f]{1,10}\$'))	(device_type not in (5,6)) or (\$var {mss_default_schema}.is_hex_number(device_id,10) = 1)
un_hi_device_loc_latlon_ck	Yes	((loc_x is null and loc_y is null and latitude is null and longitude is null) or (loc_x is not null and loc_y is not null and latitude is not null and longitude is not null))	((loc_x is null and loc_y is null and latitude is null and longitude is null) or (loc_x is not null and loc_y is not null and latitude is not null and longitude is not null))
un_hi_device_loc_owner2_ck	Yes	(owner = 0 and empid is null) or (owner = 1 and empid is not null)	(owner = 0 and empid is null) or (owner = 1 and empid is not null)

 [Top](#)

Table Name - un_hi_persl					
Description	History information for the employees assigned to the unit.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	The create datetime stamp
 empid	number(10,0)	int	no	nonNegativeNumber	This column stores the employee id of a person currently assigned to a unit.
primary_empid	varchar2(1)	varchar(1)	no	booleanToRF	Primary Employee. T = True, F = False
recovery_cdts [default = 'default']	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp. Stores the date/time stamp of when the record was created. This is generally the same as cdts except for backdated (Manual Times) records.
 un_hi_child_change_id	raw(16)	varbinary(16)	no		Unit history child change ID. Links row back to un_hi. To reduce database writes, we are only writing child data if some child data changes.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
un_hi_persl_cdts	cdts		no	no	
un_hi_persl_empid	empid		no	no	
un_hi_persl_recovery_cdts	recovery_cdts		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
un_hi_persl_primary_key	un_hi_child_change_id, empid			primaryKey	yes
Triggers					
Trigger Name	Required	Trigger Type		Description	
un_hi_persl_default_trig	Yes	Custom		Converts default string to the current time since Oracle doesn't allow user defined functions in default values	

 [Top](#)

Table Name - unit_wkload					
Description	This table stores statistics about unit workload. Statistics are maintained about a unit while the unit is logged on. When the unit logs off, the unit's workload statistics are inserted into this table for reporting purposes. Statistics are only written to this table if the UnitStatOut parameter in the cad GeneralDetails parameter list is set to Y.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
avail_station	number(10,0)	int	no		Available Station Time. Time a unit was available at station headquarters.
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Creation Date/Time Stamp for this record. This will correspond to the unit's log off time.
start_delta	number(10,0)	int	no		Difference in time of true start of shift from scheduled start of shift.
started_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	Scheduled shift start date/time stamp.
station_move	number(5,0)	smallint	no		Total number of station/post moves.
time_active	number(10,0)	int	no		Number of seconds the unit was logged on.
total_emg_wk	number(5,0)	smallint	no		Number of emergency events worked since unit logged on.
total_ev_time	number(10,0)	int	no		Total amount of time, in seconds, that unit has spent on events since log on.
total_evt_wk	number(5,0)	smallint	no		Number of events worked.
transp_count	number(5,0)	smallint	no		Total number of transports that a unit has worked since logon.
unavail_time	number(10,0)	int	no		Total time, in seconds, that the unit was unavailable, not including out of service time, since logon. Unavailable means that the unit was on an assignment and not available to be dispatched to a new event.
unid	varchar2(10)	varchar(10)	no		The unit id for which this record was inserted.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies rows
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
unit_wkload_cdts	cdts		no	yes	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
unit_wkload_pk	unique_id			primaryKey	no

 [Top](#)

Table Name - ushis					
Description	This table holds a history record for each employee who tries to access I/CAD. A record is written whenever an employee (attempts to) logs on or off. This table is used for inquiries on the employee.				
Copy Type	INSERT				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.
csec	number(19,0)	bigint	no		Cdts time stamp stored in epoch seconds
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. The nodename of the terminal from which the record was created.
dow	varchar2(1)	varchar(1)	no	dow between 1 and 7	Day of week. This column contains the numeric equivalent for the day of the week, with 1 = Sunday and 7 = Saturday.
empid	number(10,0)	int	yes		Employee ID. This column contains the unique identifier for the employee which traces back to the persl (personnel) table.
loflflag	varchar2(1)	varchar(1)	no	loflflag in ('N', 'F', 'M', 'I', 'S')	Logon/Logoff Transaction. This field indicates if the employee is logged on (N), logged off (F), logged off by the Free Person command (M), or an unsuccessful log on occurred (I=invalid user ID/password, and S = insufficient security access).
paswrđ	varchar2(128)	varchar(128)	yes		User Password. Deprecated.
prdt_run	varchar2(1)	varchar(1)	yes		Product Being Run. This column identifies what product is being accessed. C= I/CAD, D= CADDDBM, I= I/Informer.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies rows
usr_id	varchar2(20)	varchar(20)	yes		User Identification. This column holds the user ID of the employee logging on or off. If the user attempts to log on unsuccessfully more than a predefined number of times, what s/he tried to key in is placed in the database
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
ushis_cdts	cdts		no	yes	
ushis_empid	empid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered

ushis_pk	unique_id	primaryKey	no
----------	-----------	------------	----

 [Top](#)

Table Name - usrgrp					
Description	This table is used to store the user groups that have been defined for access to scratch pad data.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
descr	varchar2(50)	varchar(50)	yes		Description. This column contains the text description of the group.
 empid	number(10,0)	int	no		Employee Identifier. This column contains the unique employee ID that defines this person as a member of this group.
 grpId	varchar2(4)	varchar(4)	no		Group Identifier. This column contains the unique group ID that is used to control access to scratch pad information.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
usrgrp_primary_key	grpId, empid			primaryKey	yes

 [Top](#)

Table Name - valid_device					
Description	Stores all the valid device ids in the system. This table is populated via triggers on device-related tables. This table is needed for the conceptual model, so that all devices are guaranteed to have a parent record. CR 1-6PGD42: PLT				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 device_id	varchar2(40)	varchar(40)	no		Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
 device_sub_type	number(5,0)	smallint	no	nonNegativeNumber	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 device_type	number(5,0)	smallint	no	device_type between 0 and 6	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
valid_device_pk	device_id, device_type, device_sub_type			primaryKey	yes
Check Constraints					
Constraint Name	Required	Oracle Definition		Sql Server Definition	
valid_device_mdt_smt_id_ck	Yes	(device_type not in (5,6)) or (regexp_like(device_id, ''[0-9A-Fa-f]{1,10}\$'))		(device_type not in (5,6)) or (\$var{mss_default_schema}.is_hex_number(device_id,10) = 1)	

 [Top](#)

Table Name - valid_unit					
Description	Defines all of the valid unit ids for the system. This table is populated via triggers on unit-related tables.				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
 unid	varchar2(10)	varchar(10)	no		Unit ID
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
valid_unit_pk	unid			primaryKey	yes

 [Top](#)

Table Name - vehic					
Description	This table contains vehicle information which is related to the event and is displayed, added, and updated on the Supplemental Information Form in I/CAD.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.
cdts2 [SQL Server only]	timestamp with time zone	datetimeoffset	no		Creation Date/Time Stamp. Stores the date/time stamp at which the record was created.
cpers	number(10,0)	int	no	nonNegativeNumber	Creating Person. This column stores the identification number of the person who created the event.
cterm	varchar2(15)	varchar(15)	no		Creating Terminal. This column contains the nodename of the terminal from which this record was created.
curent	varchar2(1)	varchar(1)	no	booleanTOrF	Current Flag. This column contains either a (T) or an (F) to indicate whether the record is the most current version of the event. Only one record for any given event in the event table should have flag = (T).
disableautoquery	varchar2(1)	varchar(1)	yes	booleanTOrF	T= Do not run auto query against this record. Used by Informer.
 eid	number(10,0)	int	no	positiveNumber	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id=0.
info_scope	varchar2(12)	varchar(12)	yes		Information Scope. This column contains the scope of the supplemental information.
license	varchar2(8)	varchar(8)	yes		License Plate Number.
license_type	varchar2(10)	varchar(10)	yes		License Type. This column contains the type of vehicle license.
license_yr	varchar2(4)	varchar(4)	yes		License Year. This column contains the year of the license.
make	varchar2(5)	varchar(5)	yes		Make of the Vehicle.
model	varchar2(5)	varchar(5)	yes		Model of the Vehicle.
model_year	number(10,0)	int	yes		Year of the Vehicle.
remarks	varchar2(20)	varchar(20)	yes		This column stores the remarks about the vehicle.
 rev_num	number(10,0)	int	no	positiveNumber	Revision Number. This column contains the revision number of the record. Since no data is ever deleted from the database, it is used to provide an audit trail to trace the evolution of the event.
 row_num	number(10,0)	int	no		Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.
state	varchar2(4)	varchar(4)	yes		State Register of the Vehicle.
supp_avail_dts	varchar2(16)	varchar(16)	no	ipsTimestamp	After this date, the supplemental record will not be returned by LOI searches.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which this record was last updated.
udts2 [SQL Server only]	timestamp with time zone	datetimeoffset	yes		Update Date/Time Stamp
unid	varchar2(10)	varchar(10)	yes		The unit related to the event
updt_flag	varchar2(15)	varchar(15)	no		Update Flag. This column contains the nodename of the terminal initiating an update.
upers	number(10,0)	int	yes	nonNegativeNumber	Updating Person. This column contains the employee id of the person who is updating the event.
uterm	varchar2(15)	varchar(15)	yes		Updating Terminal. This column contains the nodename of the terminal from which the record was updated.
vehic_color	varchar2(7)	varchar(7)	yes		Vehicle Color. This column contains the color of the vehicle.
vin	varchar2(25)	varchar(25)	yes		Vehicle Identification Number
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause

vehic_cds2udts2	Oracle: string_to_datetimeoffset(cds), string_to_datetimeoffset(udts) SQL Server: cds2, uds2	no	no	
vehic_cdsudts	cdts, uds	no	no	
Key Constraints				
Constraint Name	Columns	Constraint Type		Sql Server Clustered
vehic_primary_key	cid, row_num, rev_num	primaryKey		yes

 [Top](#)

Table Name - vivistanodes					
Description	Specifies the map between the operator IDs of Vivista DCCI System and the one of CAD, including Local Site ID and Local Operator ID, and the mux_ids. The line_id and the DPNSS_Extn are also provided in this table to support the MakeCall feature.				
Copy Type	ALL_WITH_CHECK				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
dpnss_extn	number(10,0)	int	yes		DPNSS Extension to use to make the call. 9999 is used if the DPNSS Extension is not defined.
line_id	number(10,0)	int	yes		Defines the line used for making call. 9999 is used if the line is not defined.
 local_op_id	number(10,0)	int	no		Defines the terminal the operator is physically located at in Vivista DCCI System.
 local_site_id	number(10,0)	int	no		Defines the site the operator is physically located at in Vivista DCCI System.
 mux_id	number(10,0)	int	no		Position id in CAD system.
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
vivistanodes_pk	local_site_id, local_op_id, mux_id			primaryKey	yes

 [Top](#)

Table Name - xref					
Description	This table is used to store information for cross referencing events and case numbers.				
Copy Type	UPDATE				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
cdts	varchar2(16)	varchar(16)	no	ipsTimestamp	Create Date/Time Stamp. This column contains the current date/time stamp that is set to the date and time when the record was created.
curent	varchar2(1)	varchar(1)	no	curent in ('T','F','O')	Current Record Indicator Flag. This column contains the current record indicator flag. (T) denotes current record whereas (F) indicates an older record. (O) is used to temporarily lock the record.
delete_id [default = '0']	raw(16)	varbinary(16)	no		A value that uniquely identifies deleted rows
p_eid	number(10,0)	int	no		Primary Event Number.
p_type	varchar2(1)	varchar(1)	yes	p_type in ('A','C','R')	Primary Event Type. A=Active, C=Cancelled, R is used for round-trip scheduled events to cross-reference origin and return trip events
pers	number(10,0)	int	no	nonNegativeNumber	Operator Identifier. This column contains the unique ID of the operator who last updated the case number record.
recovery_unique_id	raw(16)	varbinary(16)	yes		This column is used by DBCopy to temporarily disable the unique constraints on the table. This column is included in the unique constraint definition.
s_eid	number(10,0)	int	no		Secondary Event Number.
s_type	varchar2(1)	varchar(1)	yes	s_type in ('A','C','R')	Secondary Event Type. A=Active, C=Cancelled, R is used for round-trip scheduled events to cross-reference origin and return trip events
term	varchar2(15)	varchar(15)	no		Terminal Node Identifier. This column contains the name of the terminal node where the case number record is created.
udts	varchar2(16)	varchar(16)	yes	ipsTimestamp	Update Date/Time Stamp. This column contains the update date/time stamp that records the date and time when this record was created.
 unique_id	raw(16)	varbinary(16)	no		Uniquely identifies a row
x_type	varchar2(1)	varchar(1)	no	x_type in ('D','M','O','P','X')	Type of Cross Reference Row. X = Cross reference, P = Primary, D = Duplicate, M = Master, O = Outage (InService TA sets x_type to O for events that are cancelled and rolled up into another event)
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
xref_cdsudts	cdts, udts		no	no	
xref_rcvr_unique_id	recovery_unique_id		no	no	
xref_s_eid	s_eid		no	no	
Key Constraints					
Constraint Name	Columns			Constraint Type	Sql Server Clustered
xref_primary_key	unique_id			primaryKey	no
xref_unique	p_eid, s_eid, delete_id, recovery_unique_id			uniqueKey	yes

 [Top](#)

Table Name - update_status					
Description	This table is used to record the timestamp of the last insert/update/delete made to ALL_WITH_CHECK tables. This is used to optimize DBCopy for tables that must be entirely copied each time.				
Copy Type	NO_ACTION				
Columns					
Column Name	Oracle Type	Sql Server Type	NULL	Constraint	Description
change_timestamp	varchar2(16)	varchar(16)	no	ipsTimestamp	The timestamp of the last insert, update, or delete made to a table.
table_name	varchar2(30)	varchar(30)	no		The name of a table.
 unique_id [default = sys_guid()]	raw(16)	varbinary(16)	no		Unique identifier for rows. Used by ALL_WITH_CHECK triggers to remove old rows.
Indexes					
Index Name	Columns		Is Unique	Sql Server Clustered	Sql Server Where Clause
update_status_table_name	table_name		no	yes	
Key Constraints					
Constraint Name	Columns		Constraint Type		Sql Server Clustered
update_status_pk	unique_id		primaryKey		no

 [Top](#)

View Name - ev_ty	
Description	Compatibility view that allows queries to continue to work against ev_ty
View Definition	
Oracle Definition	Sql Server Definition
create or replace view ev_ty (ag_id, alarm_leve, assign_case_state, auto_response, can_dispatch, case_num_id, cbtime1, cbtime2, days_avail, disp_req, e_u_type, eng, loi_dist, majevt_id, msg, near_dist, page_id, priority,	create view ev_ty (ag_id, alarm_leve, assign_case_state, auto_response, can_dispatch, case_num_id, cbtime1, cbtime2, days_avail, disp_req, e_u_type, eng, loi_dist, majevt_id, msg, near_dist, page_id, priority,

<pre>resp_plan_name, sub_eng, sub_tycod, time1, time1_def, time2, time3, time4, time5, tycod, fs_icode, fs_icodemessage, fs_rcode, fs_rcodemessage, intercadsend,additional_events) as select et.ag_id, etal.alarm_lev, assign_case_state, auto_response, 'F', -- can_dispatch case_num_id, initial_callback_timer, --cbtime1 repeat_callback_timer, --cbtime2 days_avail, disp_req, 'E', eng, loi_dist, majevt_id, etal.msg, near_dist, page_id, priority, etal.resp_plan_name, sub_eng, case when et.sub_tycod = 'default' then NULL else et.sub_tycod end, pending_timer, -- time1 pending_timer_default, -- time1_def dispatch_timer, -- time2 enroute_timer, -- time3 arrive_timer, -- time4 acknowledge_timer, -- time5 et.tycod, fs_icode, fs_icodemessage, fs_rcode, fs_rcodemessage, intercadsend, additional_events from event_type et join event_type_alarm_level etal on et.tycod = etal.tycod and et.sub_tycod = etal.sub_tycod and et.ag_id = etal.ag_id UNION ALL select ag_id, 0, -- alarm_lev 0, -- assign_case_state 'T', -- auto_response can_dispatch, NULL, -- case_num_id 0, -- cbtime1 0, -- cbtime2 0, -- days_avail 'N', -- disp_req 'U', -- e_u_type eng, NULL, -- loi_dist NULL, -- majevt_id NULL, -- msg NULL, -- near_dist NULL, -- page_id 9, -- priority NULL, -- resp_plan_name NULL, -- sub_eng NULL, -- sub_tycod alert_timer, -- time1 0, -- time1_def 0, -- time2 0, -- time3 0, -- time4 0, -- time5 oos.tycod, NULL, -- fs_icode NULL, -- fs_icodemessage NULL, -- fs_rcode NULL, -- fs_rcodemessage NULL, -- intercadsend, NULL -- additional_events from out_of_service_type oos join out_of_service_type_agency oos_ag</pre>	<pre>resp_plan_name, sub_eng, sub_tycod, time1, time1_def, time2, time3, time4, time5, tycod, fs_icode, fs_icodemessage, fs_rcode, fs_rcodemessage, intercadsend,additional_events) as select et.ag_id, etal.alarm_lev, assign_case_state, auto_response, 'F', -- can_dispatch case_num_id, initial_callback_timer, --cbtime1 repeat_callback_timer, --cbtime2 days_avail, disp_req, 'E', eng, loi_dist, majevt_id, etal.msg, near_dist, page_id, priority, etal.resp_plan_name, sub_eng, case when et.sub_tycod = 'default' then NULL else et.sub_tycod end, pending_timer, -- time1 pending_timer_default, -- time1_def dispatch_timer, -- time2 enroute_timer, -- time3 arrive_timer, -- time4 acknowledge_timer, -- time5 et.tycod, fs_icode, fs_icodemessage, fs_rcode, fs_rcodemessage, intercadsend, additional_events from event_type et join event_type_alarm_level etal on et.tycod = etal.tycod and et.sub_tycod = etal.sub_tycod and et.ag_id = etal.ag_id UNION ALL select ag_id, 0, -- alarm_lev 0, -- assign_case_state 'T', -- auto_response can_dispatch, NULL, -- case_num_id 0, -- cbtime1 0, -- cbtime2 0, -- days_avail 'N', -- disp_req 'U', -- e_u_type eng, NULL, -- loi_dist NULL, -- majevt_id NULL, -- msg NULL, -- near_dist NULL, -- page_id 9, -- priority NULL, -- resp_plan_name NULL, -- sub_eng NULL, -- sub_tycod alert_timer, -- time1 0, -- time1_def 0, -- time2 0, -- time3 0, -- time4 0, -- time5 oos.tycod, NULL, -- fs_icode NULL, -- fs_icodemessage NULL, -- fs_rcode NULL, -- fs_rcodemessage NULL, -- intercadsend, NULL -- additional_events from out_of_service_type oos join out_of_service_type_agency oos_ag</pre>
--	--

on oos.tycod = oos_ag.tycod	on oos.tycod = oos_ag.tycod
UNION ALL	UNION ALL
select	select
ag_id,	ag_id,
0, -- alarm_lev	0, -- alarm_lev
0, -- assign_case_state	0, -- assign_case_state
'T', -- auto_response	'T', -- auto_response
'F', -- can_dispatch	'F', -- can_dispatch
case_num_id,	case_num_id,
0, -- cbtime1	0, -- cbtime1
0, -- cbtime2	0, -- cbtime2
0, -- days_avail	0, -- days_avail
'N', -- disp_req	'N', -- disp_req
'D', -- e_u_type	'D', -- e_u_type
eng,	eng,
NULL, -- loi_dist	NULL, -- loi_dist
NULL, -- majevt_id	NULL, -- majevt_id
NULL, -- msg	NULL, -- msg
NULL, -- near_dist	NULL, -- near_dist
NULL, -- page_id	NULL, -- page_id
9, -- priority	9, -- priority
NULL, -- resp_plan_name	NULL, -- resp_plan_name
NULL, -- sub_eng	NULL, -- sub_eng
NULL, -- sub_tycod	NULL, -- sub_tycod
0, -- time1	0, -- time1
0, -- time1_def	0, -- time1_def
0, -- time2	0, -- time2
0, -- time3	0, -- time3
0, -- time4	0, -- time4
0, -- time5	0, -- time5
tycod,	tycod,
NULL, -- fs_icode	NULL, -- fs_icode
NULL, -- fs_icodemessage	NULL, -- fs_icodemessage
NULL, -- fs_rcode	NULL, -- fs_rcode
NULL, -- fs_rcodemessage	NULL, -- fs_rcodemessage
NULL, -- intercadsend	NULL, -- intercadsend
NULL -- additional_events	NULL -- additional_events
from disposition_type	from disposition_type

 [Top](#)

View Name - multi_response_view	
Description	This view is used to provide additional data to the MFC monitors in the form of custom columns pulled from a config id. Customers may choose to use a different view or they may alter this view if they need additional columns in the monitors. Note that this view is not used by the WPF monitors.
View Definition	
Oracle Definition	Sql Server Definition
create or replace view multi_response_view as (select agency_event.num_1, agency_event.multi_event_id, agency_event.is_open, trans_des.origin_location as origin, trans_des.location as destination from agency_event left outer join trans_des on agency_event.num_1= trans_des.num_1 where agency_event.eid != 0)	create view multi_response_view as (select agency_event.num_1, agency_event.multi_event_id, agency_event.is_open, trans_des.origin_location as origin, trans_des.location as destination from agency_event left outer join trans_des on agency_event.num_1= trans_des.num_1 where agency_event.eid != 0)

 [Top](#)

View Name - nodeassign	
Description	Compatibility view
View Definition	
Oracle Definition	Sql Server Definition
create or replace view nodeassign (ag_id, app_type, current, currassign, defaultassign, dgroup, lflag, max_readwrite, mux_id, readwrite, term, udts) as select ag_id, app_type, 'T', current_visibility, default_visibility, dgroup, current_access, max_access, NULL, default_access, id, udts from app_access union all select NULL, NULL, 'T', NULL, NULL, NULL, 'N', 'W', mux_id, 'W', term, NULL from term union all	create view nodeassign (ag_id, app_type, current, currassign, defaultassign, dgroup, lflag, max_readwrite, mux_id, readwrite, term, udts) as select ag_id, app_type, 'T', current_visibility, default_visibility, dgroup, current_access, max_access, NULL, default_access, id, udts from app_access union all select NULL, NULL, 'T', NULL, NULL, NULL, 'N', 'W', mux_id, 'W', term, NULL from term union all

select NULL, special_app, 'T', NULL, NULL, NULL, 'N', 'W', NULL, 'W', term, NULL from term_special_app	select NULL, special_app, 'T', NULL, NULL, NULL, 'N', 'W', NULL, 'W', term, NULL from term_special_app
--	--

 [Top](#)

View Name - time_zone_info	
Description	Compatibility view for time_zone_info
View Definition	
Oracle Definition	Sql Server Definition
create or replace view time_zone_info(dst_day_instance, dst_day_of_week, dst_hour, dst_minute, dst_month, dst_name, dst_offset, is_dst_used, offset_from_utc, std_day_instance, std_day_of_week, std_hour, std_minute, std_month, std_name, use_utc, time_skew_tolerance, current_dts) as select get_dst_day_instance, get_dst_day_of_week, get_dst_hour, get_dst_minute, get_dst_month, substr(get_dst_name,1,2), get_dst_offset, case is_dst_used when 1 then 'T' else 'F' end, get_offset_from_utc, get_std_day_instance, get_std_day_of_week, get_std_hour, get_std_minute, get_std_month, substr(get_std_name,1,2), case is_utc_used when 1 then 'T' else 'F' end, get_time_skew_tolerance, substr(get_dts,1,16) from dual	create view time_zone_info(dst_day_instance, dst_day_of_week, dst_hour, dst_minute, dst_month, dst_name, dst_offset, is_dst_used, offset_from_utc, std_day_instance, std_day_of_week, std_hour, std_minute, std_month, std_name, use_utc, time_skew_tolerance, current_dts) as select \$var(mss_default_schema).get_dst_day_instance(), \$var(mss_default_schema).get_dst_day_of_week(), \$var(mss_default_schema).get_dst_hour(), \$var(mss_default_schema).get_dst_minute(), \$var(mss_default_schema).get_dst_month(), \$var(mss_default_schema).get_dst_name(), \$var(mss_default_schema).get_dst_offset(), case \$var(mss_default_schema).is_dst_used() when 1 then 'T' else 'F' end, \$var(mss_default_schema).get_offset_from_utc(), \$var(mss_default_schema).get_std_day_instance(), \$var(mss_default_schema).get_std_day_of_week(), \$var(mss_default_schema).get_std_hour(), \$var(mss_default_schema).get_std_minute(), \$var(mss_default_schema).get_std_month(), \$var(mss_default_schema).get_std_name(), case \$var(mss_default_schema).is_utc_used() when 1 then 'T' else 'F' end, \$var(mss_default_schema).get_time_skew_tolerance(), \$var(mss_default_schema).get_dts()

 [Top](#)

Structured View Name - aeven				
Description	Aeven is a compatibility view that combines the data in agency_event and agency_event_history in a format similar to the old aeven table. If you add custom columns to agency_event and agency_event_history, run the stored procedure CreateAevenViewWithCustomCols to update this view with your custom columns.			
Table Name	agency_event			
Where Clause				
Set Operator	unionAll			
Second Table Name	agency_event_history			
Second Where Clause				
Columns				
Column Alias	Oracle Expression	SQL Server Expression	Second Oracle Expression	Second SQL Server Expression
acknowledge_timer	acknowledge_timer	acknowledge_timer	acknowledge_timer	acknowledge_timer
ad_sec	ad_sec	ad_sec	ad_sec	ad_sec
ad_ts	ad_ts	ad_ts	ad_ts	ad_ts
aecust1	aecust1	aecust1	aecust1	aecust1
aecust2	aecust2	aecust2	aecust2	aecust2
aecust3	aecust3	aecust3	aecust3	aecust3
aecust4	aecust4	aecust4	aecust4	aecust4
ag_id	ag_id	ag_id	ag_id	ag_id
alarm_lev	alarm_lev	alarm_lev	alarm_lev	alarm_lev
appt_alarm_until	appt_alarm_until	appt_alarm_until	appt_alarm_until	appt_alarm_until
appt_end_ts	appt_end_ts	appt_end_ts	appt_end_ts	appt_end_ts
appt_start_dts	appt_start_dts	appt_start_dts	appt_start_dts	appt_start_dts
ar_sec	ar_sec	ar_sec	ar_sec	ar_sec
ar_ts	ar_ts	ar_ts	ar_ts	ar_ts
arrive_timer	arrive_timer	arrive_timer	arrive_timer	arrive_timer
assigned_units	assigned_units	assigned_units	assigned_units	assigned_units
callback_dts	callback_dts	callback_dts	callback_dts	callback_dts
cbtime2	cbtime2	cbtime2	cbtime2	cbtime2

cdts	rev_dts	rev_dts	rev_dts	rev_dts
closing_allowed	closing_allowed	closing_allowed	closing_allowed	closing_allowed
cpers	rev_pers	rev_pers	rev_pers	rev_pers
create_pers	cpers	cpers	original_cpers	original_cpers
create_term	cterm	cterm	original_cterm	original_cterm
csec	rev_sec	rev_sec	rev_sec	rev_sec
cterm	rev_term	rev_term	rev_term	rev_term
curent	'T'	'T'	'F'	'F'
dest_cid	dest_cid	dest_cid	dest_cid	dest_cid
dgroup	dgroup	dgroup	dgroup	dgroup
dispass_unit	dispass_unit	dispass_unit	dispass_unit	dispass_unit
dispatch_timer	dispatch_timer	dispatch_timer	dispatch_timer	dispatch_timer
ds_sec	ds_sec	ds_sec	ds_sec	ds_sec
ds_ts	ds_ts	ds_ts	ds_ts	ds_ts
due_dts	due_dts	due_dts	due_dts	due_dts
eid	eid	eid	eid	eid
en_sec	en_sec	en_sec	en_sec	en_sec
en_ts	en_ts	en_ts	en_ts	en_ts
enroute_timer	enroute_timer	enroute_timer	enroute_timer	enroute_timer
esz	esz	esz	esz	esz
eta	eta	eta	eta	eta
evt_rev_num	evt_rev_num	evt_rev_num	evt_rev_num	evt_rev_num
ex_evt	case when ex_evt = 'F' then NULL else ex_evt end	case when ex_evt = 'F' then NULL else ex_evt end	case when ex_evt = 'F' then NULL else ex_evt end	case when ex_evt = 'F' then NULL else ex_evt end
external_event_id	external_event_id	external_event_id	external_event_id	external_event_id
flags	flags	flags	flags	flags
group_id	group_id	group_id	group_id	group_id
group_order	group_order	group_order	group_order	group_order
hold_dts	hold_dts	hold_dts	hold_dts	hold_dts
hold_type	hold_type	hold_type	hold_type	hold_type
hold_unit	hold_unit	hold_unit	hold_unit	hold_unit
is_open	is_open	is_open	is_open	is_open
is_rec_enabled	is_rec_enabled	is_rec_enabled	is_rec_enabled	is_rec_enabled
is_rec_preempt_enabled	is_rec_preempt_enabled	is_rec_preempt_enabled	is_rec_preempt_enabled	is_rec_preempt_enabled
late_run	case late_run when 'F' then NULL else late_run end	case late_run when 'F' then NULL else late_run end	case late_run when 'F' then NULL else late_run end	case late_run when 'F' then NULL else late_run end
lev2	lev2	lev2	lev2	lev2
lev3	lev3	lev3	lev3	lev3
lev4	lev4	lev4	lev4	lev4
lev5	lev5	lev5	lev5	lev5
loi_avail_dts	loi_avail_dts	loi_avail_dts	loi_avail_dts	loi_avail_dts
majevt_evty	majevt_evty	majevt_evty	majevt_evty	majevt_evty
majevt_loc	majevt_loc	majevt_loc	majevt_loc	majevt_loc
multi_event_id	multi_event_id	multi_event_id	multi_event_id	multi_event_id
multi_event_response	multi_event_response	multi_event_response	multi_event_response	multi_event_response
mun	mun	mun	mun	mun
num_1	num_1	num_1	num_1	num_1
open_and_curent	is_open	is_open	'F'	'F'
pend_dts	pend_dts	pend_dts	pend_dts	pend_dts
pending_timer	pending_timer	pending_timer	pending_timer	pending_timer
planned_task_end_dts	planned_task_end_dts	planned_task_end_dts	planned_task_end_dts	planned_task_end_dts
planned_task_start_dts	planned_task_start_dts	planned_task_start_dts	planned_task_start_dts	planned_task_start_dts
prim_member	prim_member	prim_member	prim_member	prim_member
prim_unit	prim_unit	prim_unit	prim_unit	prim_unit
priority	priority	priority	priority	priority
priority_changed_dts	priority_changed_dts	priority_changed_dts	priority_changed_dts	priority_changed_dts
probe_flag	probe_flag	probe_flag	probe_flag	probe_flag
proqa_case_num	proqa_case_num	proqa_case_num	proqa_case_num	proqa_case_num
proqa_case_type	proqa_case_type	proqa_case_type	proqa_case_type	proqa_case_type
rec_fea_mslink	rec_fea_mslink	rec_fea_mslink	rec_fea_mslink	rec_fea_mslink
rec_select_mode	rec_select_mode	rec_select_mode	rec_select_mode	rec_select_mode
rec_x_cord	rec_x_cord	rec_x_cord	rec_x_cord	rec_x_cord
rec_y_cord	rec_y_cord	rec_y_cord	rec_y_cord	rec_y_cord
recom_incomplete	recom_incomplete	recom_incomplete	recom_incomplete	recom_incomplete
recommend_mode	recommend_mode	recommend_mode	recommend_mode	recommend_mode
reopen	reopen	reopen	reopen	reopen
resp_down	case when resp_down = 'F' then NULL else resp_down end	case when resp_down = 'F' then NULL else resp_down end	case when resp_down = 'F' then NULL else resp_down end	case when resp_down = 'F' then NULL else resp_down end
response_order	response_order	response_order	response_order	response_order
rev_num	rev_num	rev_num	rev_num	rev_num
scdts	scdts	scdts	scdts	scdts
sdts	sdts	sdts	sdts	sdts
sitfnd	sitfnd	sitfnd	sitfnd	sitfnd
ssec	ssec	ssec	ssec	ssec
status_code	status_code	status_code	status_code	status_code
sub_eng	sub_eng	sub_eng	sub_eng	sub_eng
sub_sitfnd	sub_sitfnd	sub_sitfnd	sub_sitfnd	sub_sitfnd
sub_tycod	case when sub_tycod = 'default' then null else sub_tycod end	case when sub_tycod = 'default' then null else sub_tycod end	case when sub_tycod = 'default' then null else sub_tycod end	case when sub_tycod = 'default' then null else sub_tycod end
suggested_unit	suggested_unit	suggested_unit	suggested_unit	suggested_unit
supp_info	supp_info	supp_info	supp_info	supp_info
ta_sec	ta_sec	ta_sec	ta_sec	ta_sec
ta_ts	ta_ts	ta_ts	ta_ts	ta_ts
talk_group_label	talk_group_label	talk_group_label	talk_group_label	talk_group_label
tr_sec	tr_sec	tr_sec	tr_sec	tr_sec
tr_ts	tr_ts	tr_ts	tr_ts	tr_ts
tycod	tycod	tycod	tycod	tycod
typ_eng	typ_eng	typ_eng	typ_eng	typ_eng
udts	case when udts = rev_dts then null else udts end	case when udts = rev_dts then null else udts end	cdts	cdts
upers	case when udts = rev_dts then null else upers end	case when udts = rev_dts then null else upers end	cpers	cpers
uterm	case when udts = rev_dts then null else uterm end	case when udts = rev_dts then null else uterm end	cterm	cterm
vdts	vdts	vdts	vdts	vdts
vsec	vsec	vsec	vsec	vsec
xcmt	xcmt	xcmt	xcmt	xcmt
xdow	xdow	xdow	xdow	xdow
xdts	xdts	xdts	xdts	xdts

xpers	xpers	xpers	xpers	xpers
xsec	xsec	xsec	xsec	xsec
xterm	xterm	xterm	xterm	xterm

 [Top](#)

Structured View Name - event				
Description	Event is a compatibility view that combines the data in common_event and common_event_history in a format similar to the old event table.			
Table Name	common_event			
Where Clause				
Set Operator	unionAll			
Second Table Name	common_event_history			
Second Where Clause				
Columns				
Column Alias	Oracle Expression	SQL Server Expression	Second Oracle Expression	Second SQL Server Expression
cdts	rev_dts	rev_dts	rev_dts	rev_dts
cecust1	cecust1	cecust1	cecust1	cecust1
cecust2	cecust2	cecust2	cecust2	cecust2
cecust3	cecust3	cecust3	cecust3	cecust3
cecust4	cecust4	cecust4	cecust4	cecust4
cpers	rev_pers	rev_pers	rev_pers	rev_pers
csec	rev_sec	rev_sec	rev_sec	rev_sec
cterm	rev_term	rev_term	rev_term	rev_term
curent	'T'	'T'	'F'	'F'
dow	dow	dow	dow	dow
capt	capt	capt	capt	capt
earea	earea	earea	earea	earea
ecompl	ecompl	ecompl	ecompl	ecompl
edirpre	edirpre	edirpre	edirpre	edirpre
edirsuf	edirsuf	edirsuf	edirsuf	edirsuf
efeanme	efeanme	efeanme	efeanme	efeanme
efeatyp	efeatyp	efeatyp	efeatyp	efeatyp
eid	eid	eid	eid	eid
eloc_fld1	eloc_fld1	eloc_fld1	eloc_fld1	eloc_fld1
eloc_fld2	eloc_fld2	eloc_fld2	eloc_fld2	eloc_fld2
eloc_fld3	eloc_fld3	eloc_fld3	eloc_fld3	eloc_fld3
eloc_fld4	eloc_fld4	eloc_fld4	eloc_fld4	eloc_fld4
elocation	elocation	elocation	elocation	elocation
emun	emun	emun	emun	emun
estnum	estnum	estnum	estnum	estnum
fea_mslink	fea_mslink	fea_mslink	fea_mslink	fea_mslink
hash	hash	hash	hash	hash
loc_com	loc_com	loc_com	loc_com	loc_com
loc_ver	loc_ver	loc_ver	loc_ver	loc_ver
loi_event	loi_event	loi_event	loi_event	loi_event
loi_inf	loi_inf	loi_inf	loi_inf	loi_inf
loi_specsit	loi_specsit	loi_specsit	loi_specsit	loi_specsit
maplevs	maplevs	maplevs	maplevs	maplevs
parse_type	parse_type	parse_type	parse_type	parse_type
patient	patient	patient	patient	patient
pcad_case_num	pcad_case_num	pcad_case_num	pcad_case_num	pcad_case_num
rev_num	rev_num	rev_num	rev_num	rev_num
s_esz	s_esz	s_esz	s_esz	s_esz
udts	case when udts = rev_dts then null else udts end	case when udts = rev_dts then null else udts end	cdts	cdts
updt_flag	updt_flag	updt_flag	'NULLTERM'	'NULLTERM'
upers	case when udts = rev_dts then null else upers end	case when udts = rev_dts then null else upers end	cpers	cpers
uterm	case when udts = rev_dts then null else uterm end	case when udts = rev_dts then null else uterm end	cterm	cterm
x_cord	x_cord	x_cord	x_cord	x_cord
xstreet1	xstreet1	xstreet1	xstreet1	xstreet1
xstreet2	xstreet2	xstreet2	xstreet2	xstreet2
y_cord	y_cord	y_cord	y_cord	y_cord
zip	zip	zip	zip	zip

 [Top](#)

Structured View Name - map_switch	
Description	Used to select which set of map tables is active.
Query Type	Select all columns (select *)
Table Name	map_switch_table
Where Clause	rev_num = (select max(rev_num) from map_switch_table)

 [Top](#)

Entity Type Name - AbandonedCall						
Description	This table stores abandoned calls. An abandoned call is an incoming call that is terminated before an operator has the chance to answer it.					
Base Table Name	abandoned_calls					
View Name	cmvAbandonedCall					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AbandonedTime	abandoned_dts	dateTimeOffset	no	readOnly	Abandoned time - when abandoned call record is created in database.	
Abandonments	abandonments	int32	no	readOnly	Number of calls from this phone number that have been abandoned.	
CallId	call_id	string(20)	no	readOnly	Call id for the current abandoned call	
CallReceivedTime	received_dts	dateTimeOffset	no	readOnly	Date and Time of when the call appeared on the system	
CallbackAttemptTime	callback_attempt_dts	dateTimeOffset	yes	readOnly	Date and time of last callback attempt	
CallbackAttempts [default = 0]	callback_attempts	int32	no	readOnly	Number of callback attempts	
CallerPhoneNumber	caller_phone	string(20)	no	readOnly	Caller's number	
FirstAbandonedTime	first_abandoned_dts	dateTimeOffset	no	readOnly	When first abandoned call arrived in the system	
 FirstCallId	first_call_id	string(20)	no	readOnly	Unique Call ID in CAD system for the first call from this number. Serves as a unique id for a set of abandoned calls	
Location	location	string(512)	yes	readOnly	Location (address or X_Uors/Y_Uors) of caller.	
PsapId	psap_id	string(10)	no	readOnly	Id of the PSAP the call came in on.	
RevisionNumber	rev_num	int32	no	readOnly	Revision number for this record	
Vendor	vendor	string(20)	no	readOnly	The telephone vendor of the call.	



[Top](#)

Entity Type Name - AbandonedCallHistory					
Description	This table stores the history of abandoned calls.				
Base Table Name	abandoned_calls_history				
View Name	cmvAbandonedCallHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AbandonedTime	abandoned_dts	dateTimeOffset	no	readOnly	Abandoned time - when abandoned call record is created in database.
Abandonments	abandonments	int32	no	readOnly	Number of calls from this phone number that have been abandoned.
CallId	call_id	string(20)	no	readOnly	Call id for the current abandoned call
CallReceivedTime	received_dts	dateTimeOffset	no	readOnly	Date and Time of when the call appeared on the system
CallbackAttemptTime	callback_attempt_dts	dateTimeOffset	yes	readOnly	Date and time of last callback attempt
CallbackAttempts [default = 0]	callback_attempts	int32	no	readOnly	Number of callback attempts
CallerPhoneNumber	caller_phone	string(20)	no	readOnly	Caller's number
Comments	comments	string(256)	yes	readOnly	Comments
ConnectTerminal	connect_terminal	string(15)	yes	readOnly	If not null, the terminal that successfully called back or answered a call from the number.
ConnectType [default = 0]	connect_type	int16	no	readOnly	Connection type. Values may include: 0 = This number never connected; 1 = Successfully called back; 2 = Successfully answered via voice; 3 = Successfully answered via SMS -
CreatedTime	cdts	dateTimeOffset	no	readOnly	Time row was created
FirstAbandonedTime	first_abandoned_dts	dateTimeOffset	no	readOnly	When first abandoned call arrived in the system
 FirstCallId	first_call_id	string(20)	no	readOnly	Unique Call ID in CAD system for the first call from this number. Serves as a unique id for a set of abandoned calls.
Location	location	string(512)	yes	readOnly	Location (address or X_Uors/Y_Uors) of caller.
PsapId	psap_id	string(10)	no	readOnly	ID of the PSAP the call came in on
 RevisionNumber	rev_num	int32	no	readOnly	Revision number for this record
Vendor	vendor	string(20)	no	readOnly	The telephone vendor of the call.



[Top](#)

Entity Type Name - AbandonedEvent						
Description	Abandoned event data. When a user chooses to abandon an event in Dispatcher, and the SaveAbandonInfo parameter in the cad GeneralDetails parameter list is on, Dispatcher will write data from the Event Information form to the save_abandon table.					
Base Table Name	save_abandon					
View Name	cmvAbandonedEvent					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
 AbandonId	abandon_id	int32	no	readOnly	Uniquely identifies an abandoned event	
CreatedEmployeeId	cpers	int32	no	readOnly	Creating operator employee id	
CreatedTerminal	cterm	string(15)	no	readOnly	Creating terminal node	
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/time stamp	
FormId	s_form	string(40)	yes	readOnly	This column contains the form id or name	
GadgetColumn	g_col	int32	no	readOnly	Gadget column number	
GadgetId	gadget	int32	no	readOnly	Gadget id number	
GadgetRow	g_row	int32	no	readOnly	Gadget row number	
GadgetText	g_text	string(4000)	yes	readOnly	Gadget text	
GuiType	gui_type	int16	no	readOnly	Indicates the type of GUI associated with the data, 1 = MFC, 2 = WPF	
 ItemNumber	row_num	int32	no	readOnly	Enumerates the rows for a given abandon_id	



[Top](#)

Entity Type Name - ActiveBrokerCall					
Description	Internal table used by Intergraph Communications Controller to persist internal caches in support of failovers				
Base Table Name	active_broker_calls				
View Name	cmvActiveBrokerCall				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 ActiveBrokerCallId	unique_id	guid	no	readOnly	Unique ID for a row in the table
BrokerMessage	broker_message	string(Max)	no	readOnly	Message sent from client to broker persisted to database, used to restore BrokerCore caches in the case of failover.
CallId	call_id	string(20)	yes	readOnly	Unique Call ID in CAD for the call from this number.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Time message is received by the BrokerCore.
Terminal	term	string(15)	no	readOnly	The terminal of the client that the message came from
Vendor	vendor	string(20)	no	readOnly	The telephone vendor name from the message received by the BrokerCore.
VendorLocalCallId	vendor_local_call_id	string(64)	no	readOnly	Vendor specific local call id from the client terminal from the message received by the BrokerCore.



[Top](#)

Entity Type Name - ActiveCrew					
Description	This table describes crews within the CAD system. There is one record for every crew that is currently logged on.				
Base Table Name	cd_crews				
View Name	cmvActiveCrew				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyId [Monitored]	ag_id	string(9)	no	readOnly	Agency ID for which the crew is defined. This column links to the ag_id column in the def_station_crew table.
AvailableAtStationTime	avail_stn_dts	dateTimeOffset	no	readOnly	Available Station Date Time. Date and time when crew last became available at station headquarters.
CrewId [Monitored]	crew_id	string(30)	no	readOnly	Crew ID. This column links to the crew_id column in the def_station_crew table.
CrewStatus [default = UNASSGN] [Monitored]	crew_status	string(10)	no	readOnly	Crew Status. Values are ASSGN, UNASSGN.
DispatchGroup [Monitored]	dgroup	string(5)	yes	readOnly	Dispatch Group for which the crew is defined. This column links to the dgroup column in the def_station_crew table.
IsLoggedOffOnClear [default = false]	log_off	boolean	no	readOnly	Tor F. If this column is T, then the crew will be logged off when it is cleared from the unit to which it is assigned.
LineupName	lineup_name	string(30)	yes	readOnly	Lineup Name. Crew was logged on with this lineup.
LogonTime	lon_dts	dateTimeOffset	no	readOnly	Date Time Stamp when the crew was logged on.
RestrictionType	restriction_type	string(5)	yes	readOnly	Restriction Type. This column links to the restriction_type column in the def_station_crew table.
StationId	station	string(10)	no	readOnly	Station ID.

UnitId [Monitored]	unid	string(10)	yes	readOnly	Unit ID of assigned unit.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedCrew	ActiveCrew	1	0..1	DefinedCrew	ActiveCrew	CrewId	CrewId
DefinedStation	ActiveCrew	1	*	DefinedStation	ActiveCrews	StationId	StationId
ActiveCrew	ActiveCrewRestriction	1	*	ActiveCrew	ActiveCrewRestrictions	CrewId	CrewId
ActiveCrew	ActiveUnit	0..1	*	ActiveCrew	ActiveUnits	CrewId	CrewId
ActiveCrew	ActiveUnit	0..1	*	RelocatedCrew	RelocatedUnits	CrewId	RelocatedCrewId

 [Top](#)

Entity Type Name - ActiveCrewRestriction							
Description	This table contains the restrictions on all the currently active crews. It is managed in exactly the same manner as the cd_crews table and works in conjunction with that table.						
Base Table Name	act_restriction						
View Name	cmvActiveCrewRestriction						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 CrewId	crew_id	string(30)	no	readOnly	Crew ID. This column links to the crew_id column in the cd_crews table.		
 Restriction	restriction	string(10)	no	readOnly	Crew Restriction when crew is logged on. This may be a unit id or a unit type based on the crew's restriction_type attribute.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveCrew	ActiveCrewRestriction	1	*	ActiveCrew	ActiveCrewRestrictions	CrewId	CrewId

 [Top](#)

Entity Type Name - ActiveStationEmployee							
Description	Personnel who are currently logged on to a station. Station personnel can be explicitly logged on via the logon station personnel command, or implicitly logged on when personnel are assigned to a unit via logon unit or unit properties, and that unit is associated with a station. When a station person is assigned to a unit, the unit id can be found in the act_persl table. Added for CR 1-4UUSDH						
Base Table Name	act_station_persl						
View Name	cmvActiveStationEmployee						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
DelayValue [default = 0]	delay_value	int32	no	readOnly	Delay, in minutes. Amount of time it would take this person to get to the station.		
Description	description	string(200)	yes	readWrite	Description or comment		
 EmployeeId [Monitored]	empid	int32	no	readOnly	Employee id		
LogonMethod	logon_method	int32	no	readOnly	The method by which the person was logged on to the station. 0= Logged on implicitly by Logon Unit or Unit Properties. 1= Logged on explicitly by dispatcher using Logon Station Personnel command.		
LogonTime	logon_dts	dateTimeOffset	no	readOnly	Logged on timestamp		
RecommendedUnitId	recommended_unid	string(10)	yes	readOnly	Unit for which the employee has been recommended. Recommend Unit will set this column.		
StationId [Monitored]	station	string(10)	no	readOnly	Station id		
Status [Monitored]	status	int32	no	readOnly	Current status. 0= available, 1= unavailable (due to a break or other temporary reason), 2= unavailable because the person is currently assigned to a unit, 3 = unavailable because Recommend Unit has recommended this person for a unit (recommended_unid contains the recommended_unit id).		
StatusTime	status_dts	dateTimeOffset	no	readOnly	Time when person changed to current status.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	ActiveStationEmployee	1	0..1	DefinedEmployee	ActiveStationEmployee	EmployeeId	EmployeeId
DefinedStation	ActiveStationEmployee	1	*	DefinedStation	ActiveStationEmployees	StationId	StationId

 [Top](#)

Entity Type Name - ActiveStationEmployeeHistory							
Description	Records the history for logged on station personnel. CAD inserts a history record whenever an active station personnel record in act_station_persl is inserted, updated or deleted. Added for CR 1-4UUSDH						
Base Table Name	station_persl_history						
View Name	cmvActiveStationEmployeeHistor						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ChangeCode	change_code	int32	no	readOnly	Code that describes what action on the active station person caused this history record to be written. 0= logon, 1= modify, 2= logoff		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee id of person creating this history record		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal creating this history record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Timestamp when record was inserted into table.		
DelayValue [default = 0]	delay_value	int32	no	readOnly	Delay, in minutes. Amount of time it would take this person to get to the station.		
Description	description	string(200)	yes	readWrite	Description or comment		
EmployeeId	empid	int32	no	readOnly	Employee id		
LogoffTime	logoff_dts	dateTimeOffset	yes	readOnly	Timestamp for when person logged off.		
LogonMethod	logon_method	int32	no	readOnly	The method by which the person was logged on to the station. 0= Logged on implicitly by Logon Unit or Unit Properties. 1= Logged on explicitly by dispatcher using Logon Station Personnel command.		
LogonTime	logon_dts	dateTimeOffset	no	readOnly	Logged on timestamp		
RecommendedUnitId	recommended_unid	string(10)	yes	readOnly	Unit for which the employee has been recommended. Recommend Unit will set this column.		
StationId	station	string(10)	no	readOnly	Station id		
Status	status	int32	no	readOnly	Current status. 0= available, 1= unavailable (due to a break or other temporary reason), 2= unavailable because the person is currently assigned to a unit, 3= unavailable because Recommend Unit has recommended this person for a unit (recommended_unid contains the recommended unit id).		
StatusTime	status_dts	dateTimeOffset	no	readOnly	Time when person changed to current status.		
 UniqueId	unique_id	guid	no	readOnly	Unique identifier for this record.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	ActiveStationEmployeeHistory	1	*	DefinedEmployee	ActiveStationEmployeeHistories	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - ActiveUnit	
Description	This table describes units within the CAD system. There is one record for every unit that is currently logged on.

Base Table Name	cd_units				
View Name	cmvActiveUnit				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
ActiveUnitChildChangeHistId	un_hi_child_change_id	guid	no	readOnly	Unit history child change ID. Links to child change id column in un_hi_device and un_hi_persl. This column will always have a value, even if the unit has no devices or personnel
ActiveUnitHistoryId	un_hi_rec_id	guid	no	readOnly	Latest un_hi row for this unit. Used when writing un_hi_device_loc records, and when joining un_hi with un_hi_device_loc
AgencyEventId	num_1	string(12)	yes	readOnly	Agency event number that the unit is currently assigned to.
AgencyEventSubtypeCode	sub_tycod	string(16)	yes	readOnly	The sub-type of the event type.
AgencyEventTypeCode	tycod	string(16)	yes	readOnly	When the unit is on an event, this column contains the event type code.
AgencyId [Monitored]	ag_id	string(9)	no	readOnly	Agency ID to which the unit is assigned.
AlarmTime [default = 0]	alarm_time	int32	no	readOnly	Time (in minutes) after a unit status change occurs that the alarm will go off.
AreEmployeesTracked [default = false]	track_personnel	boolean	no	readOnly	Are the unit's personnel being tracked separately from the unit? Y= Yes, N= No
AttributesOrEquipmentChanged	attr_equip_chng	string(1)	yes	readOnly	Flag indicating if unit has the same or different attributes and equipment as the logon defaults. The actual character in the column depends on the EquipAttrChanged and EquipAttrSame parameters in the StatusDisplay parameter table.
Bay	bay	string(3)	yes	readOnly	Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table.
Beat	lev3	string(7)	yes	readOnly	Current post lev_3 unit is geographically assigned to. Often referred to as a beat.
ChangeComment	uhiscm	string(40)	yes	readOnly	The latest unit history comment.
CommonEventId	eid	int32	yes	readOnly	Event number to which the unit is dispatched
CoveringUnitId	cover_unit	string(10)	yes	readOnly	Unit id (unid) of the unit that is covering this unit.
CrewId [Monitored]	crew_id	string(30)	yes	readOnly	ID of crew assigned to unit.
DefaultAvailableStatus	type_avail	int16	no	readOnly	This will be the unit's default available status. The possible values for this column come from the cad UnitStatus parameter table.
DelayTime [default = 0]	delay_value	int32	no	readOnly	Delay value, in seconds. This value will be added to the unit's time/distance when recommending units by the road network
DispatchAlarmLevel	disp_alarm_lev	int32	yes	readOnly	Alarm Level of the event when the unit was dispatched
DispatchGroup [Monitored]	dgroup	string(5)	no	readOnly	Dispatch Group. This column links to the dgroup column in the def_unit, lineup, app_access, roster, esz, agency_event, and un_hi tables.
DispatchNumber	disp_num	string(12)	yes	readOnly	A unique dispatch number is assigned per agency when the unit is dispatched. This number is unique per unit per event.
ExtendedUnitAttributes	ext_unitattr	string(64)	no	readOnly	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).
GroupLeaderUnitId	group_id	string(10)	yes	readOnly	This column represents the unit id (group leader) of the unit for which this unit is a member of. If this unit is a group leader, this column will contain its own unit id.
HasAlarmSounded [default = false]	alarm_rung	boolean	no	readOnly	Is set to N or Y based upon whether the alarm has been sounded for the unit.
HasAmCourtAppearance	court_am	boolean	no	readOnly	T' if the unit has a court apperance in the morning. This field applies to MDT units only.
HasBeenTemporarilyTransferred	transferred	boolean	no	readOnly	If T', then the unit has been temporarily transferred.
HasFailedToRespond	fail_resp	boolean	no	readOnly	Failure to Respond. Flags whether unit failed to respond to last transmission.
HasLocationChanged	loc_changed	boolean	no	readOnly	T' indicates that a change location has been executed on this unit.
HasNameChanged	name_chng	boolean	no	readOnly	Indicates if the name of the unit has changed.
HasPmCourtAppearance	court_pm	boolean	no	readOnly	T' if the unit has a court appearance in the PM. This field applies only to MDT units.
IsAvailableForRecommend	avail_rec	boolean	no	readOnly	Defines whether unit is available for recommendation. AVAIL_REC only applies to units assigned to an event. T' indicates that the unit is still available for recommendation even though it is on another event.
IsInEmergency	emergency	boolean	no	readOnly	Flag indicating if unit is in an emergency situation. If field is T', then this is a unit emergency.
IsLateRun [default = false]	resp_stop	boolean	no	readOnly	If Y then the unit is associated with late run functionality.
IsLocked	locked	boolean	no	readOnly	Locked Flag, used to lock a unit record for update. The updt_term column will allow locking a unit record and updating it while locked.
IsLoggedOffOnClear	log_off	boolean	no	readOnly	If this column is T', then the unit will be logged off when it is cleared from the event it is assigned to.
IsMdtVoiceAvailable [default = true]	vflag	boolean	no	readOnly	MDT Voice Flag. This field defines whether the MDT unit is available on voice (radio). Y = Yes, N = No.
IsOutOfComplianceIfDispatched [default = false]	post_status	boolean	no	readOnly	Set value to 1 if dispatching this unit will cause the system to be out of compliance with the system status plan, otherwise set to 0.
IsSharedCrew [default = false]	shared_crew	boolean	no	readOnly	Indicates that this is a shared crew unit. If shared crew = Y, then the unit's employees can be assigned to other shared crew units.
IsUnavailable	unavail_rec	boolean	no	readOnly	T' if unit unavailable for recommendation, NULL if available. UNAVAIL_REC only applies to available units. T' indicates that the unit is NOT available for recommendation even though it's not assigned to an event.
Latitude [default = 0.0]	latitude	double	no	readOnly	Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
LineupName	lineup_name	string(30)	yes	readOnly	Populated at unit log on to indicate the lineup the, unit was associated with.
Location	location	string(80)	yes	readOnly	Last known location of unit.
LockingTerminal	updt_term	string(15)	yes	readOnly	If not NULL, then the record is locked by the terminal id that is in this column.
LogonTime	lon_dts	dateTimeOffset	no	readOnly	Date-time stamp of when the unit was logged on.
Longitude [default = 0.0]	longitude	double	no	readOnly	Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
MaxAcknowledgeTime [default = 0]	ack_timer	int32	no	readOnly	The maximum time this unit should be in acknowledge status
MaxArriveTime [default = 0]	arrive_timer	int32	no	readOnly	The maximum time a unit at this station should be in arrive status
MaxDispatchTime [default = 0]	disp_timer	int32	no	readOnly	The maximum time this unit should be in dispatch status
MaxEnrouteTime [default = 0]	enroute_timer	int32	no	readOnly	The maximum time this unit should be in enroute status
MaxHeight	max_ht	int32	yes	readOnly	Maximum height of unit.
MaxWeight	max_wt	int32	yes	readOnly	Maximum weight of unit.
MaxWidth	max_wd	int32	yes	readOnly	Maximum width of unit.
MdtHostName	mdthostname	string(24)	yes	readOnly	System name of the mobile terminal. Used by I/MDT and Informer to route Informer responses when "node-locked" ORI authorization is necessary.
MdtStatus	mdt_status_ind	string(1)	yes	readOnly	The status of the MDT.
Mileage	mileage	string(8)	yes	readOnly	Indicates initial mileage of the unit at log on. This value can also indicate the mileage of the unit at the time of a status change.
OldAgencyId	oag_id	string(9)	yes	readOnly	The old agency id for a transferred unit.
OldDispatchGroup	odgroup	string(5)	yes	readOnly	Original dispatch group that the unit was assigned to - in case of transfer event/unit.
OutOfServiceTypeCode	outtype	string(16)	yes	readOnly	Out of service type code.
PageDestination	page_unit_person	int16	no	readOnly	0 - Page unit only, 1 - Page Employee only, 2 - Page both unit and Employee
PagerId	page_id	string(12)	yes	readOnly	Pager ID or Pager Group ID from def_page.
PermanentLocation	loc_comm	string(40)	yes	readOnly	Location comment. Defines permanent deployment location
PermanentStationId	perm_station	string(10)	yes	readOnly	Permanent station id.
RelocatedCrewId	reloc_crew_id	string(30)	yes	readOnly	Contains the crew_id when the unit is relocated and sharing is allowed at a relocated station.
ShiftDuration	shift_duration	int32	yes	readOnly	Shift duration stored in seconds.
ShiftStart	shift_start	dateTimeOffset	yes	readOnly	Scheduled shift start date/time stamp.
ShiftStartDelta	shift_delta	int32	yes	readOnly	Difference in time of true start of shift from scheduled start of shift.
SpecialContact	spec_contact	string(40)	yes	readOnly	Special contact message.
StationId	station	string(10)	yes	readOnly	Current station/post id.
Status	unit_status	int16	no	readOnly	The current status of the unit.

StatusChangeTime	status_dts	dateTimeOffset	yes	readOnly	Time/date stamp when unit status changed to the current status.		
SymbolNumber	symnum	int32	no	readOnly	Symbol number. The symbol number is used to select a bitmap from the resource file. The bitmap is displayed on the map as the unit's symbol.		
TotalAvailableStationTime	avail_stn_tm	int32	yes	readOnly	Available Station Time. Time (in seconds) that a unit was available at station headquarters.		
TotalEmergencyEventCount	emg_evt_cnt	int16	no	readOnly	Number of emergency events worked since unit logged on.		
TotalEventCount	tot_evt_cnt	int16	yes	readOnly	Number of events worked.		
TotalEventTime	evnt_wk_tm	int32	yes	readOnly	Total amount of time (in seconds) that the unit has spent on events since log on		
TotalStationMoves	stn_move_cnt	int16	yes	readOnly	Total number of station/post moves.		
TotalTransports	transp_cnt	int16	yes	readOnly	Total number of transports that a unit has worked since logon.		
TotalUnavailableTime	unavail_tm	int32	yes	readOnly	Total time (in seconds) that the unit has been unavailable, not including out of service time, since logon.		
TransportXCoordinate	transxor	int32	yes	readOnly	This column holds the x coordinate of a unit's transport destination. It is set when a unit is transported with a verified location. It is then used by the Transport Arrive command to set a unit's x coordinate.		
TransportYCoordinate	transyor	int32	yes	readOnly	This column holds the y coordinate of a unit's transport destination. It is set when a unit is transported to a verified destination. It is then used by the Transport Arrive command to set the unit's y coordinate.		
UnitCustom1	ucust1	string(50)	yes	readWrite	Unit custom column 1		
UnitCustom2	ucust2	string(50)	yes	readWrite	Unit custom column 2		
UnitCustom3	ucust3	string(50)	yes	readWrite	Unit custom column 3		
UnitCustom4	ucust4	string(50)	yes	readWrite	Unit custom column 4		
 UnitId [Monitored]	unid	string(10)	no	readOnly	Unit id.		
UnitType	unityp	string(6)	yes	readOnly	Unit type (patrol, pumper, etc).		
UpdateCount	proc_count	int32	no	readOnly	Process counter incremented when this row is updated.		
VehicleId	carid	string(12)	yes	readOnly	Agency vehicle id number.		
Warning	warning	string(40)	yes	readOnly	Dispatch warning message.		
XCoordinate [default = 0]	lastxor	int32	no	readOnly	Last known x-coordinate of the unit.		
YCoordinate [default = 0]	lastyor	int32	no	readOnly	Last known y-coordinate of the unit.		
Zone	lev4	string(5)	yes	readOnly	Current post lev_4 unit is geographically assigned to. Often referred to as a zone.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveCrew	ActiveUnit	0..1	*	ActiveCrew	ActiveUnits	CrewId	CrewId
ActiveCrew	ActiveUnit	0..1	*	RelocatedCrew	RelocatedUnits	CrewId	RelocatedCrewId
ActiveUnit	ActiveUnit	0..1	*	CoveredByUnit	CoveringUnits	UnitId	CoveringUnitId
AgencyDispatchGroup	ActiveUnit	1	*	AgencyDispatchGroup	ActiveUnits	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyEvent	ActiveUnit	0..1	*	AgencyEvent	ActiveUnits	AgencyEventId	AgencyEventId
CommonEvent	ActiveUnit	0..1	*	CommonEvent	ActiveUnits	CommonEventId	CommonEventId
DefinedStation	ActiveUnit	0..1	*	DefinedStation	ActiveUnits	StationId	StationId
ActiveUnit	ActiveUnitDevice	1	*	ActiveUnit	ActiveUnitDevices	UnitId	UnitId
ActiveUnit	ActiveUnitEmployee	1	*	ActiveUnit	ActiveUnitEmployees	UnitId	UnitId
ActiveUnit	ActiveUnitEquipment	1	*	ActiveUnit	ActiveUnitEquipment	UnitId	UnitId
OutOfServiceType	ActiveUnit	0..1	*	OutOfServiceType	ActiveUnits	OutOfServiceTypeCode	OutOfServiceTypeCode
ValidUnit	ActiveUnit	1	0..1	ValidUnit	ActiveUnit	UnitId	UnitId
ActiveUnit	DispatchAssignedEvent	1	*	ActiveUnit	DispatchAssignedEvents	UnitId	UnitId
ActiveUnit	MdtLoggedOnEmployee	1	*	ActiveUnit	MdtLoggedOnEmployees	UnitId	UnitId

 [Top](#)

Entity Type Name - ActiveUnitChildChangeHistory							
Description	Records the unit history child change IDs. CR 1-6PGD42: PLT						
Base Table Name	un_hi_child_change						
View Name	cmvActiveUnitChildChangeHisor						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 ActiveUnitChildChangeHistId	un_hi_child_change_id	guid	no	readOnly	Unit history child change id. A new ID is written when unit's personnel and/or unit's devices are modified, and new un_hi_persl and un_hi_device records are written		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation timestamp		
UnitId	unid	string(10)	no	readOnly	Unit ID		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnitChildChangeHistory	ActiveUnitDeviceHistory	1	*	ActiveUnitChildChangeHistory	ActiveUnitDeviceHistories	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId
ActiveUnitChildChangeHistory	ActiveUnitEmployeeDeviceHist	1	*	ActiveUnitChildChangeHistory	ActiveUnitEmployeeDeviceHists	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId
ActiveUnitChildChangeHistory	ActiveUnitEmployeeHistory	1	*	ActiveUnitChildChangeHistory	ActiveUnitEmployeeHistories	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId
ActiveUnitChildChangeHistory	ActiveUnitHistory	1	*	ActiveUnitChildChangeHistory	ActiveUnitHistories	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId

 [Top](#)

Entity Type Name - ActiveUnitDevice					
Description	Act_device stores devices associated with logged on units, unit personnel, and unit vehicles. When units are logged on, the devices such as GPS Device, and radio alias may be pulled from def_device (or lineup_device if logging on units from a lineup), or the user can manually override the device information. MDT Server should be the only application that inserts, updates or deletes MDT ID rows. When signing on people to units, the person's defined devices, such as HT Radio, can be pulled from def_device/ lineup_device or manually overridden by the user. I/Tracker updates the location fields in this table, and CAD can update the other fields. The history information for the location fields is in un_hi_device_loc and the history of changes to the other device columns is in un_hi_device. CR 1-6PGD42: PLT				
Base Table Name	act_device				
View Name	cmvActiveUnitDevice				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
Altitude	altitude	double	yes	readOnly	Distance above mean sea level (+ above)
Bearing	bearing	double	yes	readOnly	Clockwise angle from true North range [0, 360.0]
Description	description	string(50)	yes	readWrite	Description
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device
 DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
 DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
FixAge	fix_age	int16	yes	readOnly	Code for age of fix when this location was recorded (not the current age of the data). 0=unknown, 1=10 seconds or greater, 2=less than 10 seconds
FixType	fix_type	int16	yes	readOnly	GPS source (fix type) indicator. 0=2D, 1=3D, 2=2D-differential, 3=3D-differential, 6=dead reckoning, 8=degraded, 9=unknown/invalid
GpsDate	gps_date	string(8)	yes	readOnly	Date of last GPS data from the device, in YYYYMMDD format

GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
GpsTime	gps_time	int32	yes	readOnly	Time of last GPS data from the device, stored in seconds since midnight UTC		
HorizontalPrecision	horizontal_precision	int16	yes	readOnly	Horizontal dilution of precision: 1=ideal, 2-3=excellent, 4-6=good, 7-8=moderate, 9-20=fair, 21-50=poor		
IpAddressAndPort	apcdata	string(64)	yes	readWrite	IP Address and port last received by the MDT Server from the Client		
IsMasterMdt [default = false]	is_master_mdt	boolean	no	readOnly	From MDT Server's perspective, is this the master device for this unit? 1= Master device, 0= Not master device.		
IsTrackable [default = false]	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForUnit	tdevice_for_unit	boolean	no	readOnly	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False		
Latitude	latitude	double	yes	readOnly	Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)		
Location	location	string(80)	yes	readOnly	Location, derived from reverse geocoding the device's coordinates.		
LocationUpdatedTime	loc_updated_dts	dateTimeOffset	yes	readOnly	Datetime when location was last updated		
Longitude	longitude	double	yes	readOnly	Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)		
MpsClientId	clientid	string(64)	yes	readWrite	Contains the unique ID provided by the MPS Client		
Owner {hidden}	owner				Device's owner. 0 = unit, 1 = employee		
SatelliteCount	sat_count	int32	yes	readOnly	Number of satellites used in fix		
Sensor	sensor	string(150)	yes	readOnly	Sensor data. Previously called device in old avl_log table		
SmartphoneDeviceId	smartphone_device_id	string(64)	yes	readOnly	Physical device id of the Apple iOS, Android, Windows Phone, etc. device		
SmartphoneOs	smartphone_os	int32	yes	readOnly	Type of smartphone. 0= Apple iOS, 1= Android, 2= Blackberry, 3= Windows		
SmartphonePushToken	smartphone_push_token	string(256)	yes	readOnly	Token used to push data back to the device		
SpeedBearing	speed_bearing	double	yes	readOnly	Speed along the bearing (+ forward, - reverse).		
SpeedVertical	speed_vertical	double	yes	readOnly	Speed vertical (+ up, - down)		
TdeviceForEmp {hidden}	tdevice_for_emp				Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False		
 UnitId	unid	string(10)	no	 readOnly	Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.		
UnitsOfMeasurement [default = 0]	units_of_measurement	int16	no	readOnly	Units of measurement. 0=unknown, 1=metric (meters/KPH), 2=imperial (feet/MPH)		
XCoordinate	loc_x	int32	yes	readOnly	Last known x-coordinate of the device		
YCoordinate	loc_y	int32	yes	readOnly	Last known y-coordinate of the device		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnit	ActiveUnitDevice	1	*	ActiveUnit	ActiveUnitDevices	UnitId	UnitId
ValidDevice	ActiveUnitDevice	1	*	ValidDevice	ActiveUnitDevices	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode

[Top](#)

Entity Type Name - ActiveUnitDeviceHistory							
Description	This table contains history information, aside from location updates, for the unit's devices and the unit personnel's devices. The history of location changes is stored in un_hi_device_loc. CR 1-6PGD42: PLT						
Base Table Name	un_hi_device						
View Name	cmvActiveUnitDeviceHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ActiveUnitChildChangeHistId	un_hi_child_change_id	guid	no	readOnly	Unit history child change id.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Insert datetime		
Description	description	string(50)	yes	readWrite	Description		
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device		
DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system		
DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name		
GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
IpAddressAndPort	apcdata	string(64)	yes	readWrite	IP Address and port last received by the MDT Server from the Client		
IsMasterMdt [default = false]	is_master_mdt	boolean	no	readOnly	From MDT Server's perspective, is this the master device for this unit? 1= Master device, 0= Not master device.		
IsTrackable [default = false]	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForUnit	tdevice_for_unit	boolean	no	readOnly	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False		
MpsClientId	clientid	string(64)	yes	readWrite	Contains the unique ID provided by the MPS Client		
Owner {hidden}	owner				Device's owner. 0 = unit, 1 = employee		
SmartphoneDeviceId	smartphone_device_id	string(64)	yes	readOnly	Physical device id of the Apple iOS, Android, Windows Phone, etc. device		
SmartphoneOs	smartphone_os	int32	yes	readOnly	Type of smartphone. 0= Apple iOS, 1= Android, 2= Blackberry, 3= Windows		
TdeviceForEmp {hidden}	tdevice_for_emp				Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False		
UnitId	unid	string(10)	no	readOnly	Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnitChildChangeHistory	ActiveUnitDeviceHistory	1	*	ActiveUnitChildChangeHistory	ActiveUnitDeviceHistories	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId
ValidDevice	ActiveUnitDeviceHistory	1	*	ValidDevice	ActiveUnitDeviceHistories	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode

[Top](#)

Entity Type Name - ActiveUnitEmployee					
Description	The employees assigned to this unit. There must be at least one per unit.				
Base Table Name	act_persl				
View Name	cmvActiveUnitEmployee				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 EmployeeId	empid	int32	no	readOnly	Employee assigned to this unit.
IsPrimary [default = false]	primary_empid	boolean	no	readOnly	Primary employee. T = True, F = False
PreviousUnitId	prev_unid	string(10)	yes	readOnly	The previous unit id that the employee was in prior to the current unit. This information is set to NULL during each log on.
 UnitId	unid	string(10)	no	readOnly	Unit id
Associations					

Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnit	ActiveUnitEmployee	1	*	ActiveUnit	ActiveUnitEmployees	UnitId	UnitId
DefinedEmployee	ActiveUnitEmployee	1	*	DefinedEmployee	ActiveUnitEmployees	EmployeeId	EmployeeId
ActiveUnitEmployee	ActiveUnitEmployeeDevice	1	*	ActiveUnitEmployee	ActiveUnitEmployeeDevices	UnitId, EmployeeId	UnitId, EmployeeId

[Top](#)

Entity Type Name - ActiveUnitEmployeeDevice							
Description	Act_device stores devices associated with logged on units, unit personnel, and unit vehicles. When units are logged on, the devices such as GPS Device, and radio alias may be pulled from def_device (or lineup_device if logging on units from a lineup), or the user can manually override the device information. MDT Server should be the only application that inserts, updates or deletes MDT ID rows. When signing on people to units, the person's defined devices, such as HT Radio, can be pulled from def_device/ lineup_device or manually overridden by the user. I/Tracker updates the location fields in this table, and CAD can update the other fields. The history information for the location fields is in un_hi_device_loc and the history of changes to the other device columns is in un_hi_device. CR 1-6PGD42: PLT						
Base Table Name	act_device						
View Name	cmvActiveUnitEmployeeDevice						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Altitude	altitude	double	yes	readOnly	Distance above mean sea level (+ above)		
Bearing	bearing	double	yes	readOnly	Clockwise angle from true North range [0, 360.0]		
Description	description	string(50)	yes	readWrite	Description		
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device		
 DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system		
 DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
 DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name		
EmployeeId	empid	int32	no	readOnly	If owner =1, employee that owns this device. Links to act_persl.empid		
FixAge	fix_age	int16	yes	readOnly	Code for age of fix when this location was recorded (not the current age of the data). 0=unknown, 1=10 seconds or greater, 2=less than 10 seconds		
FixType	fix_type	int16	yes	readOnly	GPS source (fix type) indicator. 0=2D, 1=3D, 2=2D-differential, 3=3D-differential, 6=dead reckoning, 8=degraded, 9=unknown/invalid		
GpsDate	gps_date	string(8)	yes	readOnly	Date of last GPS data from the device, in YYYYMMDD format		
GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
GpsTime	gps_time	int32	yes	readOnly	Time of last GPS data from the device, stored in seconds since midnight UTC		
HorizontalPrecision	horizontal_precision	int16	yes	readOnly	Horizontal dilution of precision: 1=ideal, 2-3=excellent, 4-6=good, 7-8=moderate, 9-20=fair, 21-50=poor		
IpAddressAndPort	apcdata	string(64)	yes	readWrite	IP Address and port last received by the MDT Server from the Client		
IsMasterMdt [default = false]	is_master_mdt	boolean	no	readOnly	From MDT Server's perspective, is this the master device for this unit? 1= Master device, 0= Not master device.		
IsTrackable [default = false]	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForEmployee	tdevice_for_emp	boolean	no	readOnly	Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False		
IsTrackingDeviceForUnit	tdevice_for_unit	boolean	no	readOnly	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False		
Latitude	latitude	double	yes	readOnly	Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)		
Location	location	string(80)	yes	readOnly	Location, derived from reverse geocoding the device's coordinates.		
LocationUpdatedTime	loc_updated_dts	dateTimeOffset	yes	readOnly	Datetime when location was last updated		
Longitude	longitude	double	yes	readOnly	Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)		
MpsClientId	clientid	string(64)	yes	readWrite	Contains the unique ID provided by the MPS Client		
Owner {hidden}	owner				Device's owner. 0 = unit, 1 = employee		
SatelliteCount	sat_count	int32	yes	readOnly	Number of satellites used in fix		
Sensor	sensor	string(150)	yes	readOnly	Sensor data. Previously called device in old av1_log table		
SmartphoneDeviceId	smartphone_device_id	string(64)	yes	readOnly	Physical device id of the Apple iOS, Android, Windows Phone, etc. device		
SmartphoneOs	smartphone_os	int32	yes	readOnly	Type of smartphone. 0= Apple iOS, 1= Android, 2= Blackberry, 3= Windows		
SmartphonePushToken	smartphone_push_token	string(256)	yes	readOnly	Token used to push data back to the device		
SpeedBearing	speed_bearing	double	yes	readOnly	Speed along the bearing (+ forward, - reverse).		
SpeedVertical	speed_vertical	double	yes	readOnly	Speed vertical (+ up, - down)		
 UnitId	unid	string(10)	no	readOnly	Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.		
UnitsOfMeasurement [default = 0]	units_of_measurement	int16	no	readOnly	Units of measurement. 0=unknown, 1=metric (meters/KPH), 2=imperial (feet/MPH)		
XCoordinate	loc_x	int32	yes	readOnly	Last known x-coordinate of the device		
YCoordinate	loc_y	int32	yes	readOnly	Last known y-coordinate of the device		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnitEmployee	ActiveUnitEmployeeDevice	1	*	ActiveUnitEmployee	ActiveUnitEmployeeDevices	UnitId, EmployeeId	UnitId, EmployeeId
ValidDevice	ActiveUnitEmployeeDevice	1	*	ValidDevice	ActiveUnitEmployeeDevices	DeviceTypeCode, DeviceSubtypeCode, DeviceId	DeviceTypeCode, DeviceSubtypeCode, DeviceId

[Top](#)

Entity Type Name - ActiveUnitEmployeeDeviceHist					
Description	This table contains history information, aside from location updates, for the unit's devices and the unit personnel's devices. The history of location changes is stored in un_hi_device_loc. CR 1-6PGD42: PLT				
Base Table Name	un_hi_device				
View Name	cmvActiveUnitEmployeeDeviceHis				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 ActiveUnitChildChangeHistId	un_hi_child_change_id	guid	no	readOnly	Unit history child change id.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Insert datetime
Description	description	string(50)	yes	readWrite	Description
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device
 DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system
 DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.
 DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name
EmployeeId	empid	int32	no	readOnly	If owner = 1, this column has the employee that owns the device.

GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
IpAddressAndPort	apcdata	string(64)	yes	readWrite	IP Address and port last received by the MDT Server from the Client		
IsMasterMdt [default = false]	is_master_mdt	boolean	no	readOnly	From MDT Server's perspective, is this the master device for this unit? 1= Master device, 0= Not master device.		
IsTrackable [default = false]	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForEmployee	tdevice_for_emp	boolean	no	readOnly	Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False		
IsTrackingDeviceForUnit	tdevice_for_unit	boolean	no	readOnly	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False		
MpsClientId	clientid	string(64)	yes	readWrite	Contains the unique ID provided by the MPS Client		
Owner {hidden}	owner				Device's owner. 0 = unit, 1 = employee		
SmartphoneDeviceId	smartphone_device_id	string(64)	yes	readOnly	Physical device id of the Apple iOS, Android, Windows Phone, etc. device		
SmartphoneOs	smartphone_os	int32	yes	readOnly	Type of smartphone. 0= Apple iOS, 1= Android, 2= Blackberry, 3= Windows		
UnitId	unid	string(10)	no	readOnly	Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnitChildChangeHistory	ActiveUnitEmployeeDeviceHist	1	*	ActiveUnitChildChangeHistory	ActiveUnitEmployeeDeviceHists	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId
ValidDevice	ActiveUnitEmployeeDeviceHist	1	*	ValidDevice	ActiveUnitEmployeeDeviceHists	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode

 [Top](#)

Entity Type Name - ActiveUnitEmployeeHistory								
Description	History information for the employees assigned to the unit.							
Base Table Name	un_hi_persl							
View Name	cmvActiveUnitEmployeeHistory							
Monitored	No							
Properties								
Property Name	Base Column	Data Type	NULL	Access Type	Description			
 ActiveUnitChildChangeHistId	un_hi_child_change_id	guid	no	readOnly	Unit history child change ID. Links row back to un_hi. To reduce database writes, we are only writing child data if some child data changes.			
ActualCreatedTime	recovery_cdt	dateTimeOffset	yes	readOnly	Note: This column is server-generated. Essentially, the column is read only to applications.			
CreatedTime	cdts	dateTimeOffset	no	readOnly	The create datetime stamp			
 EmployeeId	empid	int32	no	readOnly	This column stores the employee id of a person currently assigned to a unit.			
IsPrimary	primary_empid	boolean	no	readOnly	Primary Employee. T = True, F = False			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnitChildChangeHistory	ActiveUnitEmployeeHistory		1	*	ActiveUnitChildChangeHistory	ActiveUnitEmployeeHistories	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId

 [Top](#)

Entity Type Name - ActiveUnitEquipment							
Description	This table holds the equipment present on the all the currently active units in the system. It is managed in exactly the same manner as the cd_units table and works in conjunction with that table						
Base Table Name	act equip						
View Name	cmvActiveUnitEquipment						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
EquipmentCount	num equip	int32	no	readOnly	Number of pieces of this equipment		
 EquipmentName	equip	string(10)	no	readOnly	Equipment present on this unit		
 UnitId	unid	string(10)	no	readOnly	Unit identification - this column provides a link to the cd_units table record		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnit	ActiveUnitEquipment	1	*	ActiveUnit	ActiveUnitEquipment	UnitId	UnitId

 [Top](#)

Entity Type Name - ActiveUnitHistory					
Description	This table contains a history of everything that has happened to all the units in the system. When data in the active unit's child tables act_persl or act_device is modified (other than location data), CAD records a new change id, and writes the latest personnel and device history, as well as unit history. The un_hi_child_change_id identifies a set of un_hi_persl and un_hi_device records, that are valid for one or more un_hi records.				
Base Table Name	un_hi				
View Name	cmvActiveUnitHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
ActiveUnitChildChangeHistId	un_hi_child_change_id	guid	no	readOnly	Child change ID. Links to child change id column in un_hi_device and un_hi_persl. To reduce database writes, CAD only writes child records if some child data changes.
 ActiveUnitHistoryId	unique_id	guid	no	readOnly	Uniquely identifies a unit history row.
ActualCreatedTime	recovery_cdt	dateTimeOffset	yes	readOnly	Note: This column is server-generated. Essentially, the column is read only to applications.
AgencyEventId	num_1	string(12)	yes	readOnly	Agency "event" number that this unit history is associated with. It is linked to the num_1 column in the agency_event table.
AgencyEventRevisionNumber	agency_event_rev_num	int32	yes	readOnly	The revision number of the agency event. When the unit is assigned to an event, this column contains the revision number of the event at the time the unit history record is written.
AgencyEventSubTypeCode	sub_tycode	string(16)	yes	readOnly	The sub-type of the event type.
AgencyEventTypeCode	tycode	string(16)	yes	readOnly	Event Type Code. The type of the event if the current record was generated while the unit was assigned to an event. When the unit is out of service, this column contains the out of service code. May contain the disposition code in certain situations
AgencyId	ag_id	string(9)	no	readOnly	Agency id (from agenc table) that the unit is associated with.
AreEmployeesTracked [default = false]	track_personnel	boolean	no	readOnly	Are the unit's personnel being tracked separately from the unit? Y= Yes, N= No
ChangeComment	uhiscm	string(200)	yes	readOnly	Unit History Comment. Any comment associated with this unit's history record.
CommonEventId	eid	int32	yes	readOnly	Event Identification Number. The system event number if the current record was generated while the unit was assigned to an event. It links to the eid column in the common_event, agency_event, evcom, vehic, perso, and propt tables.
CreatedEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification number of the person who created the event.
CreatedSeconds {hidden}	csec				Cdts time stamp stored in epoch seconds
CreatedTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal from which the record was created.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.
CrewId	crew_id	string(30)	yes	readOnly	ID of crew assigned to unit.
DispatchAlarmLevel	disp_alarm_lev	int32	yes	readOnly	Alarm Level of the event when the unit was dispatched
DispatchGroup	dgroup	string(5)	no	readOnly	Dispatch Group. The dispatch group to which the unit is assigned. It links to the dgroup columns in the app_access, agency_dgroup, ed_units, roster, esz, and agency_event tables.

DispatchNumber	disp_num	string(12)	yes	readOnly	Dispatch Number. This column contains the unique dispatch number for the unit for an event.		
IsIgnoreOnLoad	act_check	boolean	no	readOnly	Load Flag. If this value is not NULL, the record is to be ignored at load time. For example, if values were loaded in using Manual Times in I/CAD, this value would be set to (F).		
Latitude	latitude	double	no	readOnly	Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)		
Location	location	string(80)	yes	readOnly	Unit Location. This column contains the last known location of the unit. This value is displayed on the status monitor.		
Longitude	longitude	double	no	readOnly	Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)		
MdtHostName	mdthostname	string(24)	yes	readOnly	System name of the mobile terminal. Used by I/MDT and Informer to route Informer responses when "node-locked" ORI authorization is necessary.		
Mileage	mileage	string(8)	yes	readOnly	Indicates initial mileage of the unit at log on. This value can also indicate the mileage of the unit at the time of a status change.		
OldAgencyId	oag_id	string(9)	yes	readOnly	The old agency id for a transferred unit.		
OldDispatchGroup	odgroup	string(5)	yes	readOnly	Original dispatch group that the unit was assigned to - in case of transfer event/unit.		
PagerId	page_id	string(12)	yes	readOnly	The page id used to link tables such as def_page and cd_units. Used to look up pager codes and system types and other specific paging info.		
StationId	station	string(10)	yes	readOnly	Current station/post id.		
Status	unit_status	string(2)	no	readOnly	Unit's Status. The current status of the unit as it is defined in the cad UnitStatus parameter table and StatusDisplay parameter list. For example, "AV" for "available on radio", "ER" for "enroute", and so on. This column may contain why the history record was written, such as UE for "Unit employee update."		
UnitCustom1	ucust1	string(50)	yes	readWrite	Unit custom column 1		
UnitCustom2	ucust2	string(50)	yes	readWrite	Unit custom column 2		
UnitCustom3	ucust3	string(50)	yes	readWrite	Unit custom column 3		
UnitCustom4	ucust4	string(50)	yes	readWrite	Unit custom column 4		
UnitId	unid	string(10)	no	readOnly	Unit ID. The unit name that is associated with this history record. It links to the unid column in the cd_units and roster tables.		
UnitType	unityp	string(6)	yes	readOnly	Unit type (patrol, pumper, etc).		
VehicleId	carid	string(12)	yes	readOnly	Car ID. The vehicle identification number. This could be the actual number painted on the car, or any other identification information about the unit.		
XCoordinate	lastxor	int32	no	readOnly	Last known X-coordinate of the unit in "uors" (the Map design files coordinate system -- units of resolution). This is used for placing the unit symbol on the map screen.		
YCoordinate	lastyor	int32	no	readOnly	Last known Y-coordinate of the unit in "uors" (the Map design files coordinate system -- units of resolution). This is used for placing the unit symbol on the map screen.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnitChildChangeHistory	ActiveUnitHistory	1	*	ActiveUnitChildChangeHistory	ActiveUnitHistories	ActiveUnitChildChangeHistId	ActiveUnitChildChangeHistId
AgencyDispatchGroup	ActiveUnitHistory	1	*	AgencyDispatchGroup	ActiveUnitHistories	AgencyId, DispatchGroup	AgencyId, DispatchGroup
ValidUnit	ActiveUnitHistory	1	*	ValidUnit	ActiveUnitHistories	UnitId	UnitId

 [Top](#)

Entity Type Name - Agency							
Description	This table contains a record for each agency defined in the I/CAD system. The active deployment plan and active lineup columns are modified to reflect active plans.						
Base Table Name	agenc						
View Name	cmvAgency						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId	ag_id	string(9)	no	readOnly	Unique Agency ID number used throughout I/CAD		
AgencyName	ag_nme	string(50)	yes	readOnly	Agency's full name		
AgencyType	ag_typ	string(8)	yes	readOnly	Agency type. Police, fire, etc. This value is used in the agency list gadget on the calltaker/dispatcher form and other forms commands as necessary.		
City	ag_city	string(20)	yes	readOnly	Agency city.		
ContactName	contact	string(20)	yes	readOnly	Agency contact person.		
DeploymentPlanName	act_pln	string(30)	no	readOnly	Active deployment plan. Defines the deployment plan that is currently used for this agency.		
IsTransferPermanent [default = false]	permxfer	boolean	no	readOnly	Permanent Transfer Flag. (T) = permanent unit transfer to another dispatch group, (F) = temporary transfer		
LineupName	lineup_name	string(30)	yes	readOnly	Active line-up for agency		
NextCaseIdSlot	num_2	int32	yes	readOnly	Identifies row in numbr table containing Dispatch Number Table ID for this agency		
NextEventIdSlot	num_1	int32	no	readOnly	Identifies row in numbr table containing next available event number for agency. Written to num_1 column in agency_event table for all events created for agency		
Phone	phone	string(14)	yes	readOnly	Agency telephone number.		
State	ag_st	string(4)	yes	readOnly	Agency state.		
StreetAddress	ag_add	string(30)	yes	readOnly	Agency address		
ZipCode	ag_zip	string(10)	yes	readOnly	Agency zip code.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyCaseNumber	1	*	Agency	AgencyCaseNumbers	AgencyId	AgencyId
Agency	AgencyDeploymentPlan	1	*	Agency	AgencyDeploymentPlans	AgencyId	AgencyId
Agency	AgencyDispatchGroup	1	*	Agency	AgencyDispatchGroups	AgencyId	AgencyId
Agency	AgencyEventDetailedEventType	1	*	Agency	AgencyEventDetailedEventTypes	AgencyId	AgencyId
Agency	AgencyEventDispositionType	1	*	Agency	AgencyEventDispositionTypes	AgencyId	AgencyId
Agency	AgencyEventPriorityTimeDefault	1	*	Agency	AgencyEventPriorityTimeDefaults	AgencyId	AgencyId
Agency	AgencyEventType	1	*	Agency	AgencyEventTypes	AgencyId	AgencyId
Agency	AgencyRosterUnitEmployee	1	*	Agency	AgencyRosterUnitEmployees	AgencyId	AgencyId
Agency	Broadcast	1	*	Agency	Broadcasts	AgencyId	AgencyId
Agency	CommonEventCommentLine	0..1	*	Agency	CommonEventCommentLines	AgencyId	AgencyId
Agency	DefinedDevice	0..1	*	Agency	DefinedDevices	AgencyId	AgencyId
Agency	DefinedEmployee	1	*	Agency	DefinedEmployees	AgencyId	AgencyId
Agency	DefinedUnitType	1	*	Agency	DefinedUnitTypes	AgencyId	AgencyId
Agency	DefinedVehicle	1	*	Agency	DefinedVehicles	AgencyId	AgencyId
Agency	OutOfServiceTypeAgency	1	*	Agency	OutOfServiceTypeAgencies	AgencyId	AgencyId
Agency	ScheduledItem	0..1	*	Agency	ScheduledItems	AgencyId	AgencyId
Agency	SpecialSituationAgency	1	*	Agency	SpecialSituationAgencies	AgencyId	AgencyId
Agency	UnitAgencyRestriction	1	*	Agency	UnitAgencyRestrictions	AgencyId	AgencyId

 [Top](#)

Entity Type Name - AgencyCaseNumber					
Description	The agency_case_number table is used to allow any number of case types to be defined for an agency.				
Base Table Name	agency_case_number				
View Name	cmvAgencyCaseNumber				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AgencyId	ag_id	string(9)	no	readOnly	The ag_id column specifies the agency identifier the case number specification is to be associated with.
CreatedTime	cdts	dateTimeOffset	no	readOnly	The cdts column specifies the creation date, time stamp of the record.

 NumberType	num	int32	no	readOnly	The num column specifies the numbr table that will be used to retrieve case numbers.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyCaseNumber	1	*	Agency	AgencyCaseNumbers	AgencyId	AgencyId

 [Top](#)

Entity Type Name - AgencyDeploymentPlan							
Description	Defines what deployment plans are valid for each agency.						
Base Table Name	agency_deplo_plan						
View Name	cmvAgencyDeploymentPlan						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId	ag_id	string(9)	no	readOnly	Agency ID		
 DeploymentPlanName	deplo_plan_name	string(30)	no	readOnly	Deployment plan name		
Description	description	string(50)	yes	readOnly	User-defined comment or description. For example, this column might explain when the agency uses this deployment plan.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyDeploymentPlan	1	*	Agency	AgencyDeploymentPlans	AgencyId	AgencyId
DeploymentPlan	AgencyDeploymentPlan	1	*	DeploymentPlan	AgencyDeploymentPlans	DeploymentPlanName	DeploymentPlanName

 [Top](#)

Entity Type Name - AgencyDispatchGroup							
Description	Stores information about the valid dispatch groups for each agency. CADDDBM uses this table to ensure that users enter valid dispatch groups.						
Base Table Name	agency_dgroup						
View Name	cmvAgencyDispatchGroup						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId [Monitored]	ag_id	string(9)	no	readOnly	Agency ID		
 DispatchGroup [Monitored]	dgroup	string(5)	no	readOnly	Dispatch Group		
DispatchGroupDescription	description	string(50)	yes	readOnly	Description for dispatch group		
PagerId	page_id	string(12)	yes	readOnly	Pager ID or Pager Group ID from def_page. If the page_id is not specified in the page_notify_priority table, I/Page will look for the page_id in this table. I/Page sends notifications to this page identifier when new events are created with the specified agency and dispatch group.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyDispatchGroup	ActiveUnit	1	*	AgencyDispatchGroup	ActiveUnits	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	ActiveUnitHistory	1	*	AgencyDispatchGroup	ActiveUnitHistories	AgencyId, DispatchGroup	AgencyId, DispatchGroup
Agency	AgencyDispatchGroup	1	*	Agency	AgencyDispatchGroups	AgencyId	AgencyId
AgencyDispatchGroup	AgencyEvent	1	*	AgencyDispatchGroup	AgencyEvents	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	ApplicationDispatchGroupAccess	1	*	AgencyDispatchGroup	ApplicationDispatchGroupAccess	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	ChangeSubscriber	0..1	*	AgencyDispatchGroup	ChangeSubscribers	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	DefinedCrew	0..1	*	AgencyDispatchGroup	DefinedCrews	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	DefinedStation	1	*	AgencyDispatchGroup	DefinedStations	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	DefinedUnit	1	*	AgencyDispatchGroup	DefinedUnits	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	DispatchGroupResponseTime	1	*	AgencyDispatchGroup	DispatchGroupResponseTimes	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyDispatchGroup	LineupUnit	1	*	AgencyDispatchGroup	LineupUnits	AgencyId, DispatchGroup	AgencyId, DispatchGroup

 [Top](#)

Entity Type Name - AgencyEvent					
Description	This table holds event information specific to agencies assigned to events. The records are created by I/CAD only.				
Base Table Name	agency_event				
View Name	cmvAgencyEvent				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AddedSeconds {hidden}	ad_sec				Ad_ts time stamp stored in epoch seconds
AddedTime	ad_ts	dateTimeOffset	no	readOnly	Time event was actually added into system
AgencyEventCustom1	aecust1	string(50)	yes	readWrite	Agency event custom column 1
AgencyEventCustom2	aecust2	string(50)	yes	readWrite	Agency event custom column 2
AgencyEventCustom3	aecust3	string(50)	yes	readWrite	Agency event custom column 3
AgencyEventCustom4	aecust4	string(50)	yes	readWrite	Agency event custom column 4
 AgencyEventId [Monitored]	num_1	string(12)	no	readOnly	Agency "event" number
AgencyEventSubtypeCode [default = default] [Monitored]	sub_tycod	string(16)	no	readOnly	The sub-type of the event type.
AgencyEventSubtypeCodeDesc	sub_eng	string(80)	yes	readOnly	The textual description of the sub_type
AgencyEventTypeCode [Monitored]	tycod	string(16)	no	readOnly	Agency specified event type used to describe the event which has occurred
AgencyEventTypeCodeDesc	typ_eng	string(80)	yes	readOnly	Verbose description of the event type
AgencyId	ag_id	string(9)	no	readOnly	Agency ID for the agency associated with the event
AlarmLevel	alarm_lev	int32	no	readOnly	Alarm Level for the event
AppointmentAlarmSnooze	appt_alarm_until	dateTimeOffset	yes	readOnly	Datetime stamp for next appointment alarm time
AppointmentEndTime	appt_end_ts	dateTimeOffset	yes	readOnly	Appointment end date/time stamp. Appointment is to be completed by this date/time.
AppointmentStartTime	appt_start_dts	dateTimeOffset	yes	readOnly	Appointment start date/time stamp. The earlier time in an appointment window. For an appointment this will be a fixed, default time, typically at the beginning of the work day.
Area	lev2	string(6)	yes	readOnly	Level 2 area code from the deployment table
Attributes [default = 0]	flags	int32	no	readOnly	Flags column contains 6 bits that were previously stored in supp_info column: 1 = Secure access (old SecureAccSuppMask) 2 = Event has graphics (old GraphicsSuppMask) 4 = Event has common graphics (old GraphicsCmnSuppMask) 8 = Units have been dispatched to event (old UnitInfoSuppMask) 16 = Event has SOP (old SOPSuppMask) 32 = Event's location is a special address using specific map levels (old MapLevelsSuppMask)
Beat	lev3	string(7)	yes	readOnly	Beat (Level 3 area code from the deployment table)
CallbackRepeatInterval [default = 0]	cbtime2	int32	no	readOnly	Event repeat call back timer value. Zero if no timer.

CallbackTime	callback_dts	dateTimeOffset	yes	readOnly	Event call back timer expiration date time stamp. Null if no timer.
ClosingComment	xcmnt	string(80)	yes	readOnly	Closing Comments
ClosingDayOfWeek {hidden}	xdow				Closing Day of the week, Sunday - Saturday (1-7), where Sunday = 1 and Saturday = 7
ClosingEmployeeId	xpers	int32	yes	readOnly	ID of person who closed the event.
ClosingSeconds {hidden}	xsec				Xdts time stamp stored in epoch seconds.
ClosingTerminal	xterm	string(15)	yes	readOnly	Terminal which closed the event.
ClosingTime	xdts	dateTimeOffset	yes	readOnly	Closing Date/Time Stamp.
CommonEventId	eid	int32	no	readOnly	Unique Event Id Number generated by the system
CommonEventRevisionNumber	evt_rev_num	int32	no	readOnly	Common event revision number corresponding to this agency event revision.
CreatedEmployeeId	cpers	int32	no	readOnly	Creating person empid number
CreatedTerminal	cterm	string(15)	no	readOnly	Creating Terminal
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp.
DestinationId	dest_cid	int32	yes	readOnly	Scheduled Event destination. This is a secondary event record for a scheduled event which holds its final destination. The starting point is in the first event record.
DispatchAssignedUnitId	dispass_unit	string(10)	yes	readOnly	ID of Unit event is dispatch assigned to (NULL if event is not dispatch assigned)
DispatchGroup	dgroup	string(5)	no	readOnly	Dispatch Group handling event
District	lev_5	string(5)	yes	readOnly	District (Level 5 area code from the deployment table)
DueTime	due_dts	dateTimeOffset	yes	readOnly	Due date/time stamp. The latest time that an event can be scheduled, typically an internal constraint. Typically not used to record an agreement between two
Esz {default = -1}	esz	int32	no	readOnly	Emergency Service Zone for verified location. Level 1 area code from deployment table.
Eta	eta	int32	yes	readOnly	Estimated Time of Arrival. For AutoDispatch events, the ETA is the estimated time in minutes from the current time that it will take for a unit to arrive at the event.
FirstUnitArrivedSeconds {hidden}	ar_sec				Ar_ts time stamp stored in epoch secs
FirstUnitArrivedTime	ar_ts	dateTimeOffset	yes	readOnly	Time that the first unit arrived on the scene
FirstUnitDispatchedSeconds {hidden}	ds_sec				Ds_ts time stamp stored in epoch seconds
FirstUnitDispatchedTime	ds_ts	dateTimeOffset	yes	readOnly	Dispatched Time Stamp. Time that the first unit was dispatched to the event.
FirstUnitEnroutedSeconds {hidden}	en_sec				En_ts time stamp stored in epoch seconds
FirstUnitEnroutedTime	en_ts	dateTimeOffset	yes	readOnly	Time first unit was enroute to event
FirstUnitTransportArrivedSecs {hidden}	ta_sec				Ta_ts time stamp stored in epoch seconds
FirstUnitTransportArrivedTime	ta_ts	dateTimeOffset	yes	readOnly	Transport Arrived Time Stamp. Time that the first unit transport arrived for the event.
FirstUnitTransportedSeconds {hidden}	tr_sec				Tr_ts time stamp stored in epoch seconds
FirstUnitTransportedTime	tr_ts	dateTimeOffset	yes	readOnly	Transport Time Stamp. Time that the first unit transported for the event.
FirstViewedSeconds {hidden}	vsec				Vdts time stamp stored in epoch seconds.
FirstViewedTime	vdts	dateTimeOffset	yes	readOnly	First view Date/time stamp.
GroupId	group_id	string(12)	yes	readOnly	The id of the group that this event belongs to
GroupOrder	group_order	int32	yes	readOnly	Order of event in group.
HasTemporaryLock {default = false}	temp_lock	boolean	no	readOnly	Used to temporarily lock a record. T= row is locked. F = row is not locked. The committed value in the database should always be F
HeldForUnitId	hold_unit	string(10)	yes	readOnly	ID of unit event is held for
HoldTime	hold_dts	dateTimeOffset	yes	readOnly	Date/Time when held/agreed response event will become a pending event
HoldType {default = 0}	hold_type	int32	no	readOnly	Held Event Type Code indicates hold status of the event: 0 = not held, 1 = held , 2 = agreed response, 3 = broadcast held
InterCadExternalEventId	external_event_id	string(30)	yes	readOnly	InterCAD column, event id from a foreign system
IsClosingAllowed {default = true}	closing_allowed	boolean	no	readOnly	Indicates that there are no items pending that would prevent the event from being closed.T or F
IsExemptEvent {default = false}	ex_evt	boolean	no	readOnly	Exempt event flag, identifies events exempt from contracted time limits for response. (T) if exempt, (F) otherwise.
IsLateRun {default = false}	late_run	boolean	no	readOnly	Late run event. (T) indicates response time requirement for event was not met and late run information is present in the evcom table. F otherwise
IsOpen {default = true} [Monitored]	is_open	boolean	no	readOnly	T if the event is open, F otherwise
IsRecPreemptEnabled {default = true}	is_rec_preempt_enabled	boolean	no	readOnly	Controls whether unit recommendations for the event can suggest units to be preempted. T - preempts are allowed, F - preempts are disabled
IsRecommendEnabled {default = true}	is_rec_enabled	boolean	no	readOnly	Controls whether additional unit recommendations are performed for the event. T - recommendations are generated, F - further recommendations are disabled
IsRecommendIncomplete {default = false}	recom_incomplete	boolean	no	readOnly	'T' when last unit recommendation was incomplete for event, 'F' otherwise
IsReopened {default = false}	reopen	boolean	no	readOnly	This column will be used to indicate that an agency event has been reopened. The column will have a value of 'F' to indicate that the event has not been reopened. The column will have a value of 'T' to indicate that the event has been reopened.
IsResponseTimeDown {default = false}	resp_down	boolean	no	readOnly	Response Time Down Flag. (T) indicates this condition was in effect during lifetime of event due to exempting coditions for late run time. Set using Response Time Down command in I/CAD. (F) otherwise
LastStatusChangeTime	scdts	dateTimeOffset	no	readOnly	This column represents the "status change" date time stamp. It contains the time at which an event changes status. This should correspond to the re-setting of an event's timer.
LoiAvailableTime	loi_avail_dts	dateTimeOffset	no	readOnly	After this date, the agency event record will no longer be retrieved by LOI searches.
MajorEventId	majevt_evty	string(10)	yes	readOnly	Major event type. Identifies this event as a major event. It is set based on the major event id from the event table and points to a major event plan. Major event software must be running for this to work.
MajorEventLocation	majevt_loc	string(10)	yes	readOnly	Major Event Location. It is set based on the major event id from the alarm or sp_ad table (retrieved by Location Verify) and points to a major event plan. Major event software must be running for this to function.
MaxAcknowledgeTime	acknowledge_timer	int32	no	readOnly	Acknowledge Alarm Timer. How long a unit on this event can be in the acknowledgement status before an alarm sounds.
MaxArriveTime	arrive_timer	int32	no	readOnly	Arrive alarm timer. How long a unit on this event can be in the arrive status before an alarm sounds.
MaxDispatchTime	dispatch_timer	int32	no	readOnly	Dispatch Alarm Timer. How long a unit on this event can be in the dispatched status before an alarm sounds.
MaxEnrouteTime	enroute_timer	int32	no	readOnly	Enroute Alarm Timer. How long a unit on this type of event can be in the enroute status before an alarm sounds
MaxPendingTime	pending_timer	int32	no	readOnly	Pending Alarm Timer. How long this event can stay pending before an alarm sounds.
MultiEventId {default = 0}	multi_event_id	string(12)	no	readOnly	For Multi-Response events, this column contains the agency event ID (num_1) from the master event, which ties together all rows that belong to a particular multi-response event. If the row is not part of a multi-response event, the multi_event_id is set to 0.
MultiEventResponse	multi_event_response	string(1)	yes	readOnly	Multi-Event Response (MRE) flag: 'O' = Starting Origin- the trans_des.origin_location of this row defines the starting origin of the MRE. 'D' = Final Destination - the trans_des.location of this row defines the final destination of the MRE. 'B' = Both - the trans_des row represents both the origin and the destination of the entire MRE. 'M' = Master Event record. NULL = Intermediate response, or event is not part of a MRE.
MultiEventResponseOrder {default = 0}	response_order	int32	no	readOnly	The order of the responses of a multi-response event
MultiEventSuggestedUnit	suggested_unit	string(30)	yes	readOnly	The unit preferred to service this response of the multi-response event. If this row is not part of a multi-response event, or it is the master event for a multi-response event, the suggested_unit will be null.
Municipality	mun	string(40)	yes	readOnly	Municipality (Level 6 area code from the deployment table)
PendingAlarmTime	pend_dts	dateTimeOffset	yes	readOnly	Pending Event Date/Time Stamp is the time at which the pending events alarm will go off.
PlannedTaskEndTime [Monitored]	planned_task_end_dts	dateTimeOffset	yes	readOnly	Planned task end time. Used by the Resource Scheduler
PlannedTaskStartTime [Monitored]	planned_task_start_dts	dateTimeOffset	yes	readOnly	Planned task start time. Used by Resource Scheduler
PrimaryEmployeeId	prim_member	int32	yes	readOnly	Employee id number of primary unit member (if a primary unit is assigned) or the operator id (if a primary unit is not assigned)
PrimaryUnitId	prim_unit	string(10)	yes	readOnly	Primary Unit. ID of unit that reported disposition code, requested case number via Assign Case Number, or arrived on the scene with the case number.

Priority [Monitored]	priority	int32	no	readOnly	Event Priority (0-9) for agency from event_type table.
PriorityChangedTime	priority_changed_dts	dateTimeOffset	yes	readOnly	The last time that the priority changed.
ProQACaseld	proqa_case_num	string(12)	yes	readOnly	ProQA case number received from ProQA Paramount
ProQACaseType	proqa_case_type	string(10)	yes	readOnly	ProQA case type
RecMapSegmentId [default = 0]	rec_fea_mslink	int32	no	readOnly	Special feature ID to use when recommending units for the event
RecXCoordinate [default = 0]	rec_x_cord	int32	no	readOnly	Special X coordinate to use when recommending units for the event
RecYCoordinate [default = 0]	rec_y_cord	int32	no	readOnly	Special Y coordinate to use when recommending units for the event
RecommendMode [default = 3]	recommend_mode	int32	no	readOnly	Recommendation mode for event. 0 - beats, 1 - street network, 2 - closest, 3 - use default
RecommendSelectMode [default = 3]	rec_select_mode	int32	no	readOnly	Unit selection mode for recommendations. 0 - use available only, 1 - use assigned units to fill missing requirements, 2 - use any unit, 3 - use default
RevisionEmployeeId	rev_pers	int32	no	readOnly	Employee ID of person who created this revision
RevisionNumber	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail to trace the evolution of an event.
RevisionSecs {hidden}	rev_sec				Rev_dts time stamp stored in epoch seconds
RevisionTerminal	rev_term	string(15)	no	readOnly	Terminal that created this revision
RevisionTime	rev_dts	dateTimeOffset	no	readOnly	Date timestamp when this revision was created. Note that some updates to agency_event do not create a new revision.
RmsTransferTime	probe_flag	dateTimeOffset	yes	readOnly	Probe Data Indicator Flag. Timestamp used to indicate when event data was transferred to RMS. May be used by I/LEADS-Link, FireLink or CADLink.
SituationFoundSubtype	sub_sitfnd	string(16)	yes	readOnly	The sub-type of the sitfnd event type.
SituationFoundType	sitfnd	string(16)	yes	readOnly	Situation Found. Event type (from event_type table) that is found at the scene if it differs from the event type that was initially reported.
StartedSeconds {hidden}	ssec				Sdts time stamp stored in epoch seconds
StartedTime	sdts	dateTimeOffset	yes	readOnly	Time stamp when the user enters the initial location or event type for a new event to indicate the beginning of event data entry
StatusCode [Monitored]	status_code	int32	no	readOnly	Current event status. 7 = Pending, 8 = Assigned, 9 = Held, 10 = Broadcast and Held, 11 = Broadcast and Cancel, 12 = Cancel, 13 = Station Alert, 15 = Agreed Response, 16 = Closed, 17 = Awaiting Closure, 18 = Dispatch Assigned, 20 = Dependent Status, 21 = Scheduled. The mnemonic values are defined in the cad>StatusDisplay parameter list.
SupplementalInfoTables [default = 0]	supp_info	int32	no	readOnly	Supplemental Information Identifier. This mask identifies the supplemental tables that have records tied to this event. This is configurable and is defined in the parameter file.
TalkGroupLabel	talk_group_label	string(15)	yes	readOnly	MCGE talkchannel associated to this event. Used by I/Radio.
TotalAssignedUnits	assigned_units	int16	no	readOnly	This column is used to keep track of the number of units assigned to the event.
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of person updating event.
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal which updated event.
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp.
Zone	lev4	string(5)	yes	readOnly	Zone (Level 4 area code from the deployment table)

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	ActiveUnit	0..1	*	AgencyEvent	ActiveUnits	AgencyEventId	AgencyEventId
AgencyEvent	AgencyEventAccess	1	*	AgencyEvent	AgencyEventAccess	AgencyEventId	AgencyEventId
AgencyEvent	AgencyEventAddedRequirement	1	*	AgencyEvent	AgencyEventAddedRequirements	AgencyEventId	AgencyEventId
AgencyDispatchGroup	AgencyEvent	1	*	AgencyDispatchGroup	AgencyEvents	AgencyId, DispatchGroup	AgencyId, DispatchGroup
AgencyEventGroup	AgencyEvent	0..1	*	AgencyEventGroup	AgencyEvents	GroupId	GroupId
AgencyEvent	AgencyEventCaseld	1	*	AgencyEvent	AgencyEventCaselds	AgencyEventId	AgencyEventId
CommonEvent	AgencyEvent	1	*	CommonEvent	AgencyEvents	CommonEventId	CommonEventId
AgencyEvent	AgencyEventDisposition	1	*	AgencyEvent	AgencyEventDispositions	AgencyEventId	AgencyEventId
AgencyEvent	AgencyEventHistory	1	*	AgencyEvent	AgencyEventHistories	AgencyEventId	AgencyEventId
AgencyEvent	AgencyEventResponsePlan	1	*	AgencyEvent	AgencyEventResponsePlans	AgencyEventId	AgencyEventId
AgencyEvent	AgencyEventSchedule	0..1	*	AgencyEvent	AgencyEventSchedules	AgencyEventId	AgencyEventId
AgencyEvent	AgencyEventTimer	1	*	AgencyEvent	AgencyEventTimers	AgencyEventId	AgencyEventId
AgencyEvent	BroadcastReference	0..1	*	AgencyEvent	BroadcastReferences	AgencyEventId	AgencyEventId
AgencyEvent	DispatchAssignedEvent	1	0..1	AgencyEvent	DispatchAssignedEvent	AgencyEventId	AgencyEventId
AgencyEvent	ExternalRequestForResources	1	0..1	AgencyEvent	ExternalRequestForResources	AgencyEventId	LocalAgencyEventId
AgencyEvent	Message	0..1	*	AgencyEvent	Messages	AgencyEventId	AgencyEventId
AgencyEvent	MultiEventTransportLocation	0..1	*	AgencyEvent	MultiEventTransportLocations	AgencyEventId	AgencyEventId
AgencyEvent	RecommendHistory	1	*	AgencyEvent	RecommendHistories	AgencyEventId	AgencyEventId
AgencyEvent	ScheduledDispatchAssignedEvent	1	0..1	AgencyEvent	ScheduledDispatchAssignedEvent	AgencyEventId	AgencyEventId
AgencyEvent	TowRequest	1	*	AgencyEvent	TowRequests	AgencyEventId	AgencyEventId
AgencyEvent	TransportLocation	0..1	*	AgencyEvent	TransportLocations	AgencyEventId	AgencyEventId

 [Top](#)

Entity Type Name - AgencyEventAccess							
Description	This table is used to identify specific events that have a higher level of security access, than normal events in the agency/dispatch group, and the users that have access to that event.						
Base Table Name	secure_acc						
View Name	cmvAgencyEventAccess						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyEventId [Monitored]	num_1	string(12)	no	readOnly	Event number for which security access has been limited to a user or group of users.		
 EmployeeId [Monitored]	empid	int32	no	readOnly	Employee id of user that has been granted access to the event.		
 GroupId [Monitored]	grpId	string(31)	no	readOnly	Group identifier of a group of users that have been granted access to the event.		
IsActive [Monitored]	curent	boolean	no	readOnly	Used to determine if this is the active record (set to "T"), or if it is a history record (set to "F")		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp		
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventAccess	1	*	AgencyEvent	AgencyEventAccess	AgencyEventId	AgencyEventId
DefinedEmployee	AgencyEventAccess	1	*	DefinedEmployee	AgencyEventAccess	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - AgencyEventAccessHistory	
Description	This table is used to identify specific events that have a higher level of security access, than normal events in the agency/dispatch group, and the users that have access to that event.
Base Table Name	secure_acc

View Name	cmvAgencyEventAccessHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	num_1	string(12)	no	readOnly	Event number for which security access has been limited to a user or group of users.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update date/time stamp
EmployeeId	empid	int32	no	readOnly	Employee id of user that has been granted access to the event.
GroupId	grpId	string(31)	no	readOnly	Group identifier of a group of users that have been granted access to the event.
IsActive [default = false]	curent	boolean	no	readOnly	Used to determine if this is the active record (set to "T"), or if it is a history record (set to "F")
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp

[Top](#)

Entity Type Name - AgencyEventAddedRequirement							
Description	Defines additional response plan requirements added to a specific agency event and alarm level. Added for CAD 9.1 Recommend Unit CRs.						
Base Table Name	agency_event_added_req						
View Name	cmvAgencyEventAddedRequirement						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	no	readOnly	Agency event number		
AlarmLevel	alarm_lev	int32	no	readOnly	Alarm level for the event		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation timestamp		
IsDeleted [default = false]	is_deleted	boolean	no	readOnly	T if requirement has been deleted, F otherwise		
RequirementId	unique_id	guid	no	readOnly	Unique ID of added requirement. This value is used when writing results to the recom_hist table.		
RequirementName	req_name	string(50)	no	readOnly	Name of unit ID or nested response plan added to default requirements		
RequirementNumber	req_number	int32	no	readOnly	Sequential order of requirement beginning with zero		
RequirementType	req_type	int32	no	readOnly	Type of requirement. 0 for unit ID, 1 for nested response plan		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update timestamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventAddedRequirement	1	*	AgencyEvent	AgencyEventAddedRequirements	AgencyEventId	AgencyEventId

[Top](#)

Entity Type Name - AgencyEventCaseId							
Description	The case_num table holds records which document events which occurred and were handled by a particular agency.						
Base Table Name	case_num						
View Name	cmvAgencyEventCaseId						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	no	readOnly	Corresponds to num_1 column in agency_event table and uniquely IDs the event as defined by the responsible agency		
AgencyId	ag_id	string(9)	yes	readOnly	ID of agency (from agenc table) handling the event associated with this record.		
CaseId	case_num	string(12)	no	readOnly	Unique id number for case		
CommonEventId	eid	int32	no	readOnly	Unique id (system-generated) for the associated event		
CreatedEmployeeId	cpers	int32	no	readOnly	ID of person creating record		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal creating record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp		
DispatchGroup	dgroup	string(5)	yes	readOnly	Dispatch Group. Queried by Firelink Interface application. Populated using Svrcmds.		
IsActive	curent	boolean	no	readOnly	Current Record Indicator Flag		
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of person updating record		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventCaseId	1	*	AgencyEvent	AgencyEventCaseIds	AgencyEventId	AgencyEventId

[Top](#)

Entity Type Name - AgencyEventDetailedEventType							
Description	This table contains information used for assigning results codes to events using the assign result code command in CAD. This data is created using the Detailed Event Types command in CADDBM.						
Base Table Name	det_ev_ty						
View Name	cmvAgencyEventDetailedEventTyp						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventTypeCode	tycod	string(16)	no	readOnly	Type code. Joins to the event_type table tycod column. Used by the Assign Result Code command to select the valid records based on the ag_id and tycod of the selected event.		
AgencyId	ag_id	string(9)	no	readOnly	Unique id (from agenc table) for the agency associated with the event. This allows agencies to have different detailed event type information for the same event type.		
DetailedEventTypeCode	det_code	string(8)	no	readOnly	Defines valid detailed type codes to be used by the Assign Result Code command.		
DetailedEventTypeCodeDesc	det_literal	string(40)	yes	readOnly	This column contains the literal description of the detailed event type.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyEventDetailedEventTyp	1	*	Agency	AgencyEventDetailedEventTypes	AgencyId	AgencyId

[Top](#)

Entity Type Name - AgencyEventDisposition						
Description	Event dispositions and result codes associated with events in agency_event					
Base Table Name	ev_dispo					
View Name	cmvAgencyEventDisposition					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	

 AgencyEventId	num_1	string(12)	no	readOnly	Agency "event" number		
CaseId	case_num	string(12)	yes	readOnly	Unique id number for case		
CommonEventId	eid	int32	no	readOnly	Unique Event Id Number generated by the system		
DetailedEventTypeCode	qual1	string(8)	yes	readOnly	Assign Result Code qualifier		
 DispositionNumber	row_num	int32	no	readOnly	Row Number. This column identifies which disposition this row is associated with. The first row is the primary disposition.		
DispositionTypeCode [default = default]	dispo	string(16)	yes	readOnly	Closing Disposition or result code.		
IsActive	curent	boolean	no	readOnly	Flag to indicate whether or not this record is the most current revision for this disposition code for a given event		
Qualifier1	qual2	string(3)	yes	readOnly	Assign Result Code qualifier		
Qualifier2	qual3	string(3)	yes	readOnly	Assign Result Code qualifier		
RevisionEmployeeId	cpers	int32	no	readOnly	Empid of the person who created the event disposition.		
RevisionNumber	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail.		
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal name on which an event disposition was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Date/time this record was inserted		
UnitEmployeeId	member_id	int32	yes	readOnly	This column stores the employee id of a person assigned to the associated unit.		
UnitId	unit_id	string(10)	yes	readOnly	ID of unit that reported disposition code		
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of person updating event disposition		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal which updated event disposition		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date/time of when this record was last updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventDisposition	1	*	AgencyEvent	AgencyEventDispositions	AgencyEventId	AgencyEventId
DefinedEmployee	AgencyEventDisposition	0..1	*	DefinedEmployee	AgencyEventDispositions	EmployeeId	UnitEmployeeId
ValidUnit	AgencyEventDisposition	0..1	*	ValidUnit	AgencyEventDispositions	UnitId	UnitId

 [Top](#)

Entity Type Name - AgencyEventDispositionHistory					
Description	Event dispositions and result codes associated with events in agency_event				
Base Table Name	ev_dispo				
View Name	cmvAgencyEventDispositionHisto				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AgencyEventId	num_1	string(12)	no	readOnly	Agency "event" number
CaseId	case_num	string(12)	yes	readOnly	Unique id number for case
CommonEventId	eid	int32	no	readOnly	Unique Event Id Number generated by the system
CreatedEmployeeId	upers	int32	no	readOnly	ID of person updating event disposition
CreatedTerminal	uterm	string(15)	no	readOnly	Terminal which updated event disposition
CreatedTime	udts	dateTimeOffset	no	readOnly	Date/time of when this record was last updated
DetailedEventTypeCode	qual1	string(8)	yes	readOnly	Assign Result Code qualifier
 DispositionNumber	row_num	int32	no	readOnly	Row Number. This column identifies which disposition this row is associated with. The first row is the primary disposition.
DispositionTypeCode [default = default]	dispo	string(16)	yes	readOnly	Closing Disposition or result code.
IsActive [default = false]	curent	boolean	no	readOnly	Flag to indicate whether or not this record is the most current revision for this disposition code for a given event
Qualifier1	qual2	string(3)	yes	readOnly	Assign Result Code qualifier
Qualifier2	qual3	string(3)	yes	readOnly	Assign Result Code qualifier
RevisionEmployeeId	cpers	int32	no	readOnly	Empid of the person who created the event disposition.
 RevisionNumber	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail.
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal name on which an event disposition was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Date/time this record was inserted
UnitEmployeeId	member_id	int32	yes	readOnly	This column stores the employee id of a person assigned to the associated unit.
UnitId	unit_id	string(10)	yes	readOnly	ID of unit that reported disposition code

 [Top](#)

Entity Type Name - AgencyEventDispositionType							
Description	This table contains disposition type codes. Previously, this data was stored in ev_ty where e_u_type = 'D'						
Base Table Name	disposition_type						
View Name	cmvAgencyEventDispositionType						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId	ag_id	string(9)	no	readOnly	Agency Id		
CaseIdLocation	case_num_id	int32	yes	readOnly	Case Number Identifier. This column defines where to receive the case number for this disposition. This column links to the num_id column in the numbr table.		
 DispositionTypeCode	tycod	string(16)	no	readOnly	The disposition type code.		
DispositionTypeCodeDesc	eng	string(80)	yes	readOnly	English Description. This column contains the textual description of the disposition type.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyEventDispositionType	1	*	Agency	AgencyEventDispositionTypes	AgencyId	AgencyId

 [Top](#)

Entity Type Name - AgencyEventGroup					
Description	The event_group table is used to store overall information about event groups. CR 1-4UUAAM 1-4UUDT8 - Event Groups				
Base Table Name	event_group				
View Name	cmvAgencyEventGroup				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
ClosingEmployeeId	xpers	int32	yes	readOnly	ID of person who closed the event group.
ClosingTerminal	xterm	string(15)	yes	readOnly	Terminal which closed the event group.
ClosingTime	xdts	dateTimeOffset	yes	readOnly	Closing Date/Time Stamp.
CreatedEmployeeId	cpers	int32	no	readOnly	Creation employee id.
CreatedTerminal	cterm	string(15)	no	readOnly	Creation terminal.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp.
Description [Monitored]	description	string(50)	yes	readWrite	Group description.

 GroupId [Monitored]	group_id	string(12)	no	readOnly	Unique group id.		
GroupStatus [default = A]	group_status	string(1)	no	readOnly	Status of event group - values are 'A' - Active (default), 'C' - Closed		
GroupType [Monitored]	group_type	int16	no	readOnly	Group type.		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update employee id.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Update terminal.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEventGroup	AgencyEvent	0..1	*	AgencyEventGroup	AgencyEvents	GroupId	GroupId

 [Top](#)

Entity Type Name - AgencyEventHistory					
Description	This table contains historical agency event records. When an agency_event record is updated, a snapshot of its previous contents are recorded in this table.				
Base Table Name	agency_event_history				
View Name	cmvAgencyEventHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AddedSeconds {hidden}	ad_sec				Ad_ts time stamp stored in epoch seconds
AddedTime	ad_ts	dateTimeOffset	no	readOnly	Time event was actually added into system
AgencyEventCustom1	aecust1	string(50)	yes	readWrite	Agency event custom column 1
AgencyEventCustom2	aecust2	string(50)	yes	readWrite	Agency event custom column 2
AgencyEventCustom3	aecust3	string(50)	yes	readWrite	Agency event custom column 3
AgencyEventCustom4	aecust4	string(50)	yes	readWrite	Agency event custom column 4
 AgencyEventId	num_1	string(12)	no	readOnly	Agency "event" number
AgencyEventSubtypeCode [default = default]	sub_tycod	string(16)	no	readOnly	The sub-type of the event type.
AgencyEventSubtypeCodeDesc	sub_eng	string(80)	yes	readOnly	The textual description of the sub_type
AgencyEventTypeCode	tycod	string(16)	no	readOnly	Agency specified event type used to describe the event which has occurred
AgencyEventTypeCodeDesc	typ_eng	string(80)	yes	readOnly	Verbose description of the event type
AgencyId	ag_id	string(9)	no	readOnly	Agency ID for the agency associated with the event
AlarmLevel	alarm_lev	int32	no	readOnly	Alarm Level for the event
AppointmentAlarmSnooze	appt_alarm_until	dateTimeOffset	yes	readOnly	Datetime stamp for next appointment alarm time
AppointmentEndTime	appt_end_ts	dateTimeOffset	yes	readOnly	Appointment end date/time stamp. Appointment is to be completed by this date/time.
AppointmentStartTime	appt_start_dts	dateTimeOffset	yes	readOnly	Appointment start date/time stamp. The earlier time in an appointment window. For an appointment this will be a fixed, default time, typically at the beginning of the work day.
Area	lev2	string(6)	yes	readOnly	Level 2 area code from the deployment table
Attributes [default = 0]	flags	int32	no	readOnly	Flags column contains 6 bits that were previously stored in supp_info column: 1 = Secure access (old SecureAccSuppMask) 2 = Event has graphics (old GraphicsSuppMask) 4 = Event has common graphics (old GraphicsCmnSuppMask) 8 = Units have been dispatched to event (old UnitInfoSuppMask) 16 = Event has SOP (old SOPSuppMask) 32 = Event's location is a special address using specific map levels (old MapLevelsSuppMask)
Beat	lev3	string(7)	yes	readOnly	Beat (Level 3 area code from the deployment table)
CallbackRepeatInterval [default = 0]	cbtime2	int32	no	readOnly	Event repeat call back timer value. Zero if no timer.
CallbackTime	callback_dts	dateTimeOffset	yes	readOnly	Event call back timer expiration date time stamp. Null if no timer.
ClosingComment	xcmt	string(80)	yes	readOnly	Closing Comments
ClosingDayOfWeek {hidden}	xdow				Closing Day of the week, Sunday - Saturday (1-7), where Sunday = 1 and Saturday = 7
ClosingEmployeeId	xpers	int32	yes	readOnly	ID of person closing event
ClosingSeconds {hidden}	xsec				Xdts time stamp stored in epoch seconds.
ClosingTerminal	xterm	string(15)	yes	readOnly	Terminal which closed event
ClosingTime	xdts	dateTimeOffset	yes	readOnly	Closing Date/Time Stamp
CommonEventId	eid	int32	no	readOnly	Unique Event Id Number generated by the system
CommonEventRevisionNumber	evt_rev_num	int32	no	readOnly	Common event revision number corresponding to this agency event revision.
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of person creating this history row. The CPERS column shows up as UPERS in the aeven compatibility view.
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal creating this history row. The CTERM column shows up as UTERM in the aeven compatibility view.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp of this history row. The CDTS column shows up as UDTS in the aeven compatibility view.
DestinationId	dest_eid	int32	yes	readOnly	Scheduled Event destination. This is a secondary event record for a scheduled event which holds its final destination. The starting point is in the first event record.
DispatchAssignedUnitId	dispass_unit	string(10)	yes	readOnly	ID of Unit event is dispatch assigned to (NULL if event is not dispatch assigned)
DispatchGroup	dgroup	string(5)	no	readOnly	Dispatch Group handling event
District	lev5	string(5)	yes	readOnly	District (Level 5 area code from the deployment table)
DueTime	due_dts	dateTimeOffset	yes	readOnly	Due date/time stamp. The latest time that an event can be scheduled, typically an internal constraint. Typically not used to record an agreement between two
Esz [default = -1]	esz	int32	no	readOnly	Emergency Service Zone for verified location. Level 1 area code from deployment table.
Eta	eta	int32	yes	readOnly	Estimated Time of Arrival. For AutoDispatch events, the ETA is the estimated time in minutes from the current time that it will take for a unit to arrive at the event.
FirstUnitArriveSeconds {hidden}	ar_sec				Ar_ts time stamp stored in epoch secs
FirstUnitArrivedTime	ar_ts	dateTimeOffset	yes	readOnly	Time that the first unit arrived on the scene
FirstUnitDispatchedSeconds {hidden}	ds_sec				Ds_ts time stamp stored in epoch seconds
FirstUnitDispatchedTime	ds_ts	dateTimeOffset	yes	readOnly	Dispatched Time Stamp. Time that the first unit was dispatched to the event.
FirstUnitEnroutedSeconds {hidden}	en_sec				En_ts time stamp stored in epoch seconds
FirstUnitEnroutedTime	en_ts	dateTimeOffset	yes	readOnly	Time first unit was enroutre to event
FirstUnitTransportArrivedSecs {hidden}	ta_sec				Ta_ts time stamp stored in epoch seconds
FirstUnitTransportArrivedTime	ta_ts	dateTimeOffset	yes	readOnly	Transport Arrived Time Stamp. Time that the first unit transport arrived for the event.
FirstUnitTransportedSeconds {hidden}	tr_sec				Tr_ts time stamp stored in epoch seconds
FirstUnitTransportedTime	tr_ts	dateTimeOffset	yes	readOnly	Transport Time Stamp. Time that the first unit transported for the event.
FirstViewedSeconds {hidden}	vsec				Vdts time stamp stored in epoch seconds.
FirstViewedTime	vdts	dateTimeOffset	yes	readOnly	First view Date/time stamp.
GroupId	group_id	string(12)	yes	readOnly	The id of the group that this event belongs to
GroupOrder	group_order	int32	yes	readOnly	Order of event in group.
HeldForUnitId	hold_unit	string(10)	yes	readOnly	ID of unit event is held for
HoldTime	hold_dts	dateTimeOffset	yes	readOnly	Date/Time when held/agreed response event will become a pending event
HoldType [default = 0]	hold_type	int32	no	readOnly	Held Event Type Code indicates hold status of the event: 0 = not held, 1 = held , 2 = agreed response, 3 = broadcast held

InterCadExternalEventId	external_event_id	string(30)	yes	readOnly	InterCAD column, event id from a foreign system
IsClosingAllowed [default = true]	closing_allowed	boolean	no	readOnly	Indicates that there are no items pending that would prevent the event from being closed.T or F
IsExemptEvent [default = false]	ex_evt	boolean	no	readOnly	Exempt event flag, identifies events exempt from contracted time limits for response. (T) if exempt, (F) otherwise.
IsLateRun [default = false]	late_run	boolean	no	readOnly	Late run event. (T) indicates response time requirement for event was not met and late run information is present in the evcom table. (F) otherwise
IsOpen	is_open	boolean	no	readOnly	T if the event is open, F otherwise
IsRecPreemptEnabled [default = true]	is_rec_preempt_enabled	boolean	no	readOnly	Controls whether unit recommendations for the event can suggest units to be preempted. T - preempts are allowed, F - preempts are disabled
IsRecommendEnabled [default = true]	is_rec_enabled	boolean	no	readOnly	Controls whether additional unit recommendations are performed for the event. T - recommendations are generated, F - further recommendations are disabled
IsRecommendIncomplete [default = false]	recom_incomplete	boolean	no	readOnly	'T' when last unit recommendation was incomplete for event, 'F' otherwise
IsReopened	reopen	boolean	no	readOnly	This column will be used to indicate that an agency event has been reopened. The column will have a value of 'F' to indicate that the event has not been reopened. The column will have a value of 'T' to indicate that the event has been reopened.
IsResponseTimeDown [default = false]	resp_down	boolean	no	readOnly	Response Time Down Flag. (T) indicates this condition was in effect during lifetime of event due to exempting coditions for late run time. Set using Response Time Down command in I/CAD. (F) otherwise
LastStatusChangeTime	scdts	dateTimeOffset	no	readOnly	This column represents the "status change" date time stamp. It contains the time at which an event changes status. This should correspond to the re-setting of an event's timer.
LoiAvailableTime	loi_avail_dts	dateTimeOffset	no	readOnly	After this date, the agency_event record will no longer be retrieved by LOI searches.
MajorEventLocation	majevt_loc	string(10)	yes	readOnly	Major Event Location. It is set based on the major event id from the alarm or sp_ad table (retrieved by Location Verify) and points to a major event plan. Major event software must be running for this to function.
MajorEventType	majevt_evty	string(10)	yes	readOnly	Major event type. Identifies this event as a major event. It is set based on the major event id from the event table and points to a major event plan. Major event software must be running for this to work.
MaxAcknowledgeTime	acknowledge_timer	int32	no	readOnly	Acknowledge Alarm Timer. How long a unit on this event can be in the acknowledgement status before an alarm sounds.
MaxArriveTime	arrive_timer	int32	no	readOnly	Arrive alarm timer. How long a unit on this event can be in the arrive status before an alarm sounds.
MaxDispatchTime	dispatch_timer	int32	no	readOnly	Dispatch Alarm Timer. How long a unit on this event can be in the dispatched status before an alarm sounds.
MaxEnrouteTime	enroute_timer	int32	no	readOnly	Enroute Alarm Timer. How long a unit on this event can be in the enroute status before an alarm sounds
MaxPendingTime	pending_timer	int32	no	readOnly	Pending Alarm Timer. How long this event can stay pending before an alarm sounds.
MultiEventId [default = 0]	multi_event_id	string(1)	no	readOnly	For Multi-Response events, this column contains the agency event ID (num. 1) from the master event, which ties together all rows that belong to a particular multi-response event. If the row is not part of a multi-response event, the multi_event_id is set to 0.
MultiEventResponse	multi_event_response	string(1)	yes	readOnly	Multi-Event Response (MRE) flag: 'O' = Starting Origin- the trans_des.origin_location of this row defines the starting origin of the MRE. 'D' = Final Destination - the trans_des.location of this row defines the final destination of the MRE. 'B' = Both - the trans_des row represents both the origin and the destination of the entire MRE. 'M' = Master Event record. NULL = Intermediate response, or event is not part of a MRE.
MultiEventResponseOrder [default = 0]	response_order	int32	no	readOnly	The order of the responses of a multi-response event
MultiEventSuggestedUnit	suggested_unit	string(30)	yes	readOnly	The unit preferred to service this response of the multi-response event. If this row is not part of a multi-response event, or it is the master event for a multi-response event, the suggested_unit will be null.
Municipality	mun	string(40)	yes	readOnly	Municipality (Level 6 area code from the deployment table)
OriginalEmployeeId	original_cpers	int32	no	readOnly	Empid of the person who originally created the event. After event creation, this value should never be changed. Maps to create_pers in the aeven compatibility view
OriginalTerminal	original_cterm	string(15)	no	readOnly	Terminal which originally created this event. After event creation, this value should never be changed. Maps to create_term in aeven view.
PendingAlarmTime	pend_dts	dateTimeOffset	yes	readOnly	Pending Event Date/Time Stamp is the time at which the pending events alarm will go off.
PlannedTaskEndTime	planned_task_end_dts	dateTimeOffset	yes	readOnly	Planned task end time. Used by the Resource Scheduler
PlannedTaskStartTime	planned_task_start_dts	dateTimeOffset	yes	readOnly	Planned task start time. Used by the Resource Scheduler
PrimaryEmployeeId	prim_member	int32	yes	readOnly	Employee id number of primary unit member (if a primary unit is assigned) or the operator id (if a primary unit is not assigned)
PrimaryUnitId	prim_unit	string(10)	yes	readOnly	Primary Unit. ID of unit that reported disposition code, requested case number via Assign Case Number, or arrived on the scene with the case number.
Priority	priority	int32	no	readOnly	Event Priority (0-9) for agency from event_type table.
PriorityChangedTime	priority_changed_dts	dateTimeOffset	yes	readOnly	The last time the priority changed.
ProQACaseId	proqa_case_num	string(12)	yes	readOnly	ProQA case number received from ProQA Paramount
ProQACaseType	proqa_case_type	string(10)	yes	readOnly	ProQA case type
RecMapSegmentId [default = 0]	rec_fea_mslink	int32	no	readOnly	Special feature ID to use when recommending units for the event
RecXCoordinate [default = 0]	rec_x_cord	int32	no	readOnly	Special X coordinate to use when recommending units for the event
RecYCoordinate [default = 0]	rec_y_cord	int32	no	readOnly	Special Y coordinate to use when recommending units for the event
RecommendMode [default = 3]	recommend_mode	int32	no	readOnly	Recommendation mode for event. 0 - beats, 1 - street network, 2 - closest, 3 - use default
RecommendSelectMode [default = 3]	rec_select_mode	int32	no	readOnly	Unit selection mode for recommendations. 0 - use available only, 1 - use assigned units to fill missing requirements, 2 - use any unit, 3 - use default
RevisionEmployeeId	rev_pers	int32	no	readOnly	The person who created this revision. The rev_pers column is copied from the agency_event upers column. This column is shown as cpers in the aeven view.
 RevisionNumber	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail to trace the evolution of an event.
RevisionSecs {hidden}	rev_sec				The creation timestamp, in epoch seconds, for this revision. The rev_sec column is copied from the agency_event usec column. This column is shown as csec in the aeven view.
RevisionTerminal	rev_term	string(15)	no	readOnly	The rev_term column is copied from the agency_event uterm column. This column is shown as cterm in the aeven view.
RevisionTime	rev_dts	dateTimeOffset	no	readOnly	The creation timestamp for this revision. The rev_dts column is copied from the agency_event udtis column. This column is shown as cdts in the aeven view.
RmsTransferTime	probe_flag	dateTimeOffset	yes	readOnly	Probe Data Indicator Flag. Timestamp used to indicate when event data was transferred to RMS. May be used by I/LEADS-Link, FireLink or CADLink.
SituationFoundSubtype	sub_sitfnd	string(16)	yes	readOnly	The sub-type of the sitfnd event type.
SituationFoundType	sitfnd	string(16)	yes	readOnly	Situation Found. Event type (from event_type table) that is found at the scene if it differs from the event type that was initially reported.
StartedSeconds {hidden}	ssec				Sdts time stamp stored in epoch seconds
StartedTime	sdts	dateTimeOffset	yes	readOnly	Time stamp when the user enters the initial location or event type for a new event to indicate the beginning of event data entry
StatusCode	status_code	int32	no	readOnly	Current event status. 7 = Pending, 8 = Assigned, 9 = Held, 10 = Broadcast and Held, 11 = Broadcast and Cancel, 12 = Cancel, 13 = Station Alert, 15 = Agreed Response, 16 = Closed, 17 = Awaiting Closure, 18 = Dispatch Assigned, 20 = Dependent Status, 21 = Scheduled The mnemonic values are defined in the cad StatusDisplay parameter list.
SupplementalInfoTables [default = 0]	supp_info	int32	no	readOnly	Supplemental Information Identifier. This mask identifies the supplemental tables that have records tied to this event. This is configurable and is defined in the parameter file.
TalkGroupLabel	talk_group_label	string(15)	yes	readOnly	MCGE talkchannel associated to this event. Used by I/Radio.
TotalAssignedUnits	assigned_units	int16	no	readOnly	This column is used to keep track of the number of units assigned to the event.
Zone	lev4	string(5)	yes	readOnly	Zone (Level 4 area code from the deployment table)

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventHistory	1	*	AgencyEvent	AgencyEventHistories	AgencyEventId	AgencyEventId

Entity Type Name - AgencyEventPriorityTimeDefault	
Description	Contains timer values set on events in memory. These timer values are applied when timer values are not defined in the event_type table. Timer values are defined for one to ten priority codes for an agency.
Base Table Name	priority_times
View Name	cmvAgencyEventPriorityTimeDefa
Monitored	No

Properties								
Property Name	Base Column	Data Type	NULL	Access Type	Description			
 AgencyId	ag_id	string(9)	no	readOnly	Agency identifier. An agency can have 1 to 10 records (priorities "0" to "9").			
MaxAcknowledgeTime [default = 0]	time5	int32	no	readOnly	Timer 5, same as in event_type.acknowledge_timer			
MaxArriveTime [default = 0]	time4	int32	no	readOnly	Timer 4, same as in event_type.arrive_timer			
MaxDispatchTime [default = 0]	time2	int32	no	readOnly	Timer 2, same as in event_type.dispatch_timer			
MaxEnrouteTime [default = 0]	time3	int32	no	readOnly	Timer 3, same as in event_type.enroute_timer			
MaxPendingTime [default = 0]	time1	int32	no	readOnly	Timer 1, same as in event_type.pending_timer			
 Priority	priority	int32	no	readOnly	Priority Number. The event priority code for which the timer values in the record will be applied.			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyEventPriorityTimeDefault		1	*	Agency	AgencyEventPriorityTimeDefaults	AgencyId	AgencyId

 [Top](#)

Entity Type Name - AgencyEventResponsePlan							
Description	Explicitly defines response plans to use for unit recommendation for specific agency events and alarm levels, overriding normal response plan selection. Added for CAD 9.1 Recommend Unit CRs.						
Base Table Name	agency_event_resp_plan						
View Name	cmvAgencyEventResponsePlan						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AlarmLevel	alarm_lev	int32	no	readOnly	Alarm level for the event		
 AgencyEventId	num_1	string(12)	no	readOnly	Agency event number		
ResponsePlanName	resp_plan_name	string(50)	no	readOnly	Response plan to use		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventResponsePlan	1	*	AgencyEvent	AgencyEventResponsePlans	AgencyEventId	AgencyEventId

 [Top](#)

Entity Type Name - AgencyEventSchedule							
Description	This table holds the scheduling information for CAD events created as scheduled.						
Base Table Name	s_calendar						
View Name	cmvAgencyEventSchedule						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	event_no	string(12)	yes	readOnly	The active CAD event (num_1 in the agency_event table) that corresponds to this schedule		
 AgencyEventScheduleId	sched_id	string(12)	no	readOnly	The unique scheduled i.d. of the scheduled event that this specific record is associated with		
AppointmentTime	appt_dts	dateTimeOffset	no	readOnly	The date-time stamp for the scheduled event appointment (this is an informational field only - not used in functionality)		
CancelledComment	xcmt	string(20)	yes	readOnly	The closing comment when the given scheduled event has been cancelled		
CancelledEmployeeId	xpers	int32	yes	readOnly	The i.d. of the operator that was responsible for cancelling the given scheduled event (cf. column "empid" of "persl" table)		
CancelledTerminal	xterm	string(15)	yes	readOnly	The name of the terminal that cancelled the given scheduled event		
CancelledTime	xdts	dateTimeOffset	yes	readOnly	The date-time stamp of the time when the given scheduled event had been cancelled (in format YYYYMMDDHHMMSSZZ)		
CreatedEmployeeId	create_pers	int32	no	readOnly	The employee id of the person who originally created scheduled event - will not change when row is updated		
CreatedTerminal	create_term	string(15)	no	readOnly	The terminal where scheduled event was originally created - will not change when row is updated		
EventComment	comm	string(256)	yes	readOnly	Stores a comment for recurring events.		
HeldForUnitId	umid	string(10)	yes	readOnly	The unit i.d. of the unit that the event (when generated into a CAD event) will be held for		
IsActive [default = true]	curent	boolean	no	readOnly	Active record flag. Flag is set to "T" if this is the active record, and to "F" if this is a history record. "O" is used to temporarily lock the record.		
IsCancelled [default = false]	is_cancelled	boolean	no	readOnly	Is Cancelled. When T, scheduled event has been cancelled. When F, scheduled event is active.		
NextScheduleId	next_schedid	string(12)	yes	readOnly	Scheduled event id of next event for recurring event.		
PreviousScheduleId	prev_schedid	string(12)	yes	readOnly	Scheduled event id of previous event for recurring event.		
RequestedTime	rqst_dts	dateTimeOffset	no	readOnly	The date-time stamp for the time requested for pick-up of the patient (what the caller requested) - the actual scheduled pick-up time will be found in the "sched_dts" column		
ReturnScheduleId	return_schedid	string(12)	yes	readOnly	Scheduled event id of the related event for round-trip event		
RevisionEmployeeId	cpers	int32	no	readOnly	The employee ID of the operator who created the given record (cf. column "empid" of "persl" table)		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	The terminal i.d. of the terminal that created the given record		
RevisionTime	cdts	dateTimeOffset	no	readOnly	The date-time stamp when the given record was created (in format YYYYMMDDHHMMSSZZ)		
ScheduledTime	sched_dts	dateTimeOffset	no	readOnly	The date-time stamp of the time that the patient pick-up is scheduled for (which may be different than the time that had been requested by the patient - see "rqst_dts" column)		
UpdatedEmployeeId	upers	int32	yes	readOnly	The i.d. of the operator who last updated the given record (cf. column "empid" of "persl" table)		
UpdatedTerminal	uterm	string(15)	yes	readOnly	The terminal i.d. of the terminal that last updated the given record		
UpdateTime	udts	dateTimeOffset	yes	readOnly	The date-time stamp of the last time the given record had been updated (in format YYYYMMDDHHMMSSZZ)		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventSchedule	0..1	*	AgencyEvent	AgencyEventSchedules	AgencyEventId	AgencyEventId
AgencyEventSchedule	AgencyEventSchedule	0..1	*	NextSchedule	ReverseNextSchedules	AgencyEventScheduleId	NextScheduleId
AgencyEventSchedule	AgencyEventSchedule	0..1	*	PreviousSchedule	ReversePreviousSchedules	AgencyEventScheduleId	PreviousScheduleId
AgencyEventSchedule	AgencyEventSchedule	0..1	*	ReturnSchedule	ReverseReturnSchedules	AgencyEventScheduleId	ReturnScheduleId

 [Top](#)

Entity Type Name - AgencyEventScheduleHistory					
Description	This table holds the scheduling information for CAD events created as scheduled.				
Base Table Name	s_calendar				
View Name	cmvAgencyEventScheduleHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	event_no	string(12)	yes	readOnly	The active CAD event (num_1 in the agency_event table) that corresponds to this schedule
 AgencyEventScheduleId	sched_id	string(12)	no	readOnly	The unique scheduled i.d. of the scheduled event that this specific record is associated with

AppointmentTime	appt_dts	dateTimeOffset	no	readOnly	The date-time stamp for the scheduled event appointment (this is an informational field only - not used in functionality)
CancelledComment	xcmt	string(20)	yes	readOnly	The closing comment when the given scheduled event has been cancelled
CancelledEmployeeId	xpers	int32	yes	readOnly	The i.d. of the operator that was responsible for cancelling the given scheduled event (cf. column "empid" of "persl" table)
CancelledTerminal	xterm	string(15)	yes	readOnly	The name of the terminal that cancelled the given scheduled event
CancelledTime	xdts	dateTimeOffset	yes	readOnly	The date-time stamp of the time when the given scheduled event had been cancelled (in format YYYYMMDDHHMMSSZZ)
CreatedEmployeeId	upers	int32	no	readOnly	The i.d. of the operator who last updated the given record (cf. column "empid" of "persl" table)
CreatedTerminal	uterm	string(15)	no	readOnly	The terminal i.d. of the terminal that last updated the given record
CreatedTime	udts	dateTimeOffset	no	readOnly	The date-time stamp of the last time the given record had been updated (in format YYYYMMDDHHMMSSZZ)
EventComment	comm	string(256)	yes	readOnly	Stores a comment for recurring events.
IsActive (default = false)	curent	boolean	no	readOnly	Active record flag. Flag is set to "T" if this is the active record, and to "F" if this is a history record. "O" is used to temporarily lock the record.
IsCancelled (default = false)	is_cancelled	boolean	no	readOnly	Is Cancelled. When T, scheduled event has been cancelled. When F, scheduled event is active.
NextScheduleId	next_schedid	string(12)	yes	readOnly	Scheduled event id of next event for recurring event.
OriginalEmployeeId	create_pers	int32	no	readOnly	The employee id of the person who originally created scheduled event - will not change when row is updated
OriginalTerminal	create_term	string(15)	no	readOnly	The terminal where scheduled event was originally created - will not change when row is updated
PreviousScheduleId	prev_schedid	string(12)	yes	readOnly	Scheduled event id of previous event for recurring event.
RequestedTime	rqst_dts	dateTimeOffset	no	readOnly	The date-time stamp for the time requested for pick-up of the patient (what the caller requested) - the actual scheduled pick-up time will be found in the "sched_dts" column
ReturnScheduleId	return_schedid	string(12)	yes	readOnly	Scheduled event id of the related event for round-trip event
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	The terminal i.d. of the terminal that created the given record
RevisionTime	cdts	dateTimeOffset	no	readOnly	The date-time stamp when the given record was created (in format YYYYMMDDHHMMSSZZ)
RevisionEmployeeId	cpers	int32	no	readOnly	The employee ID of the operator who created the given record (cf. column "empid" of "persl" table)
ScheduledTime	sched_dts	dateTimeOffset	no	readOnly	The date-time stamp of the time that the patient pick-up is scheduled for (which may be different than the time that had been requested by the patient - see "rqst_dts" column)
UnitId	unid	string(10)	yes	readOnly	The unit i.d. of the unit that the event (when generated into a CAD event) will be held for

 [Top](#)

Entity Type Name - AgencyEventTimer							
Description	Used to maintain data about individual timers						
Base Table Name	timer						
View Name	cmvAgencyEventTimer						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId [Monitored]	object_id	string(30)	no	readOnly	For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name		
AgencyId [Monitored]	ag_id	string(9)	yes	readOnly	Agency timer is associated with		
Category {hidden}	category				EV = event, UN = unit, GE = general, not associated with event or unit		
ClosingText [Monitored]	closing_text	string(160)	yes	readOnly	Text string associated with closing of the timer.		
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee id of creator		
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	Terminal node identifier of creator.		
CreatedTime [Monitored]	cdts	dateTimeOffset	no	readOnly	Date, time stamp of when timer is created.		
DispatchGroup [Monitored]	dgroup	string(5)	yes	readOnly	Dispatch group timer is associated with		
IsRepeating [Monitored]	repeat	boolean	no	readOnly	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of unique timer		
SetName [Monitored]	set_name	string(15)	yes	readOnly	Name of set that timer is associated.		
StartedTime [Monitored]	start_dts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer begins excxcuting.		
StatusCode [Monitored]	status_code	int32	no	readOnly	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled		
Timeout [Monitored]	timeout	int32	no	readOnly	timer expiration in seconds. Range can be 1 to max int.		
TimeoutText [Monitored]	timeout_text	string(160)	yes	readOnly	Text string associated with expiration of timer.		
 TimerId [Monitored]	timer_id	guid	no	readOnly	Uniquely identifies the row		
TimerType [Monitored]	type	int32	no	readOnly	The type of timer		
UpdatedEmployeeId [Monitored]	upers	int32	yes	readOnly	Employee id of updating person		
UpdatedTerminal [Monitored]	uterm	string(15)	yes	readOnly	Terminal node identifier of updater		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer is updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	AgencyEventTimer	1	*	AgencyEvent	AgencyEventTimers	AgencyEventId	AgencyEventId
AgencyEventTimer	AgencyEventTimerHistory	1	*	AgencyEventTimer	AgencyEventTimerHistories	TimerId	TimerId

 [Top](#)

Entity Type Name - AgencyEventTimerHistory					
Description	Used to maintain data about individual timer history				
Base Table Name	timer_history				
View Name	cmvAgencyEventTimerHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	object_id	string(30)	no	readOnly	For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name
AgencyId	ag_id	string(9)	yes	readOnly	Agency timer is associated with
Category {hidden}	category				EV = event, UN = unit, GE = general, not associated with event or unit
ClosingText	closing_text	string(160)	yes	readOnly	Text string associated with closing of the timer.
CreatedEmployeeId	cpers	int32	no	readOnly	Employee id of creator
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal node identifier of creator.

CreatedTime	cdts	dateTimeOffset	no	readOnly	Date, time stamp of when timer is created.		
DispatchGroup	dgroup	string(5)	yes	readOnly	Dispatch group timer is associated with		
IsRepeating	repeat	boolean	no	readOnly	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.		
 RevisionNumber	rev_num	int32	no	readOnly	Revision number of unique timer		
SetName	set_name	string(15)	yes	readOnly	Name of set that timer is associated.		
StartedTime	start_dts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer begins executing.		
StatusCode	status_code	int32	no	readOnly	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled		
Timeout	timeout	int32	no	readOnly	timer expiration in seconds. Range can be 1 to max int.		
TimeoutText	timeout_text	string(160)	yes	readOnly	Text string associated with expiration of timer.		
 TimerId	timer_id	guid	no	readOnly	Uniquely identifies the row		
TimerType	type	int32	no	readOnly	The type of timer		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEventTimer	AgencyEventTimerHistory	1	*	AgencyEventTimer	AgencyEventTimerHistories	TimerId	TimerId

 [Top](#)

Entity Type Name - AgencyEventType							
Description	This table contains event type codes. This info is used at I/CAD startup to build various associated lists such as the Event Type field on the main dispatcher form. Previously, this data was stored in ev_ty where e_u_type = 'E'						
Base Table Name	event_type						
View Name	cmvAgencyEventType						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyEventSubtypeCode [default = default]	sub_tycod	string(16)	no	readOnly	The sub-type of the event type. 'default' if not specified		
AgencyEventSubtypeCodeDesc	sub_eng	string(80)	yes	readOnly	The textual description of the sub-type.		
 AgencyEventTypeCode	tycod	string(16)	no	readOnly	Event type code		
AgencyEventTypeCodeDesc	eng	string(80)	yes	readOnly	English Description. This column contains the textual description of the event type.		
 AgencyId	ag_id	string(9)	no	readOnly	Agency Id. Different agencies may have different type information for the same event type. For example, police might respond to a murder with priority 1, but EMS may respond with a priority of 3		
AssignCaseStates [default = 0]	assign_case_state	int32	no	readOnly	Bitmap for states that automatically assign case numbers to an event. 0 = Undefined, 2 = Dispatch, 4 = Arrive, 8 = Transport, 16 = Transport arrive, 32 = Available, 64 = Assign Case		
CallbackRepeatIntervalDefault [default = 0]	repeat_callback_timer	int32	no	readOnly	Event type default repeat call back timer value. Initialized to 0. Previously called ev_ty.cbtime2		
CallbackTimeDefault [default = 0]	initial_callback_timer	int32	no	readOnly	Event type default initial call back timer value. Initialized to 0. Previously called ev_ty.cbtime1		
CaseIdLocation	case_num_id	int32	yes	readOnly	Case Number Identifier. This column defines where to receive the case number for this disposition. This column links to the num_id column in the numbr table.		
IsAdvisedEvent [default = false]	advised_event	boolean	no	readOnly	Create events of this type as advised events.		
IsAutoRespond [default = true]	auto_response	boolean	no	readOnly	When an event of this type is created, should this agency automatically be configured to respond. T= Automatically respond. F = do not automatically respond.		
IsDispositionRequired [default = false]	disp_req	boolean	no	readOnly	Required Disposition Code. This column is used to determine if a disposition is required for the event type. This code is set to (Y) if a disposition is required, else N.		
LoiAvailableTime [default = 0]	days_avail	int32	no	readOnly	Days Available. This column contains the number of days available for LOI searches.		
LoiDistance	loi_dist	single	yes	readOnly	The distance that DBserver uses for Area Location of Interest searches		
MajorEventId	majevt_id	string(10)	yes	readOnly	Major Event Identifier. This column contains the ID pointer to a major incident plan.		
MaxAcknowledgeTime [default = 0]	acknowledge_timer	int32	no	readOnly	Acknowledge Alarm Timer. How long a unit on this type of event can be in the acknowledgement status before an alarm sounds. Previously called ev_ty.time5		
MaxArriveTime [default = 0]	arrive_timer	int32	no	readOnly	Arrive alarm timer. How long a unit on this type of event can be in the arrive status before an alarm sounds. Previously called ev_ty.time4		
MaxDispatchTime [default = 0]	dispatch_timer	int32	no	readOnly	Dispatch Alarm Timer. How long a unit on this type of event can be in the dispatched status before an alarm sounds. Previously called ev_ty.time2		
MaxEnrouteTime [default = 0]	enroute_timer	int32	no	readOnly	Enroute Alarm Timer. How long a unit on this type of event can be in the enroute status before an alarm sounds. Previously called ev_ty.time3		
MaxPendingTime [default = 0]	pending_timer	int32	no	readOnly	Pending Alarm Timer. How long an event of this type can stay pending before an alarm sounds. Previously called ev_ty.time1		
NearbyEventDistance	near_dist	single	yes	readOnly	The distance that the Nearby Event(Duplicate Event) command uses for nearby event searches		
PendingTimeDefault [default = 0]	pending_timer_default	int32	no	readOnly	Default value for pending_timer. Previously called ev_ty.time1_def		
Priority [default = 9]	priority	int32	no	readOnly	Priority Number. This column contains the priority code to use with the event types only. Valid values are 0 to 9		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyEventType	1	*	Agency	AgencyEventTypes	AgencyId	AgencyId
AgencyEventType	AgencyEventTypeAlias	1	*	AgencyEventType	AgencyEventTypeAliases	AgencyId, AgencyEventTypeCode, AgencyEventSubtypeCode	AliasAgencyId, AgencyEventTypeAlias, AgencyEventSubtypeAlias
AgencyEventType	AgencyEventTypeResponse	1	*	AgencyEventType	AgencyEventTypeResponses	AgencyId, AgencyEventTypeCode, AgencyEventSubtypeCode	AgencyId, AgencyEventTypeCode, AgencyEventSubtypeCode

 [Top](#)

Entity Type Name - AgencyEventTypeAlias						
Description	Contains agency-specific aliases for event types.					
Base Table Name	ev_ty_alias					
View Name	cmvAgencyEventTypeAlias					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AgencyEventSubtypeAlias [default = default]	alias_sub_tycod	string(16)	no	readOnly	Sub-type of aliased event type. Will contain 'default' if there is no sub-type.	
 AgencyEventSubtypeCode [default = default]	sub_tycod	string(16)	no	readOnly	Sub-type of event type. Will contain 'default' if there is no sub-type.	
AgencyEventTypeAlias	alias_tycod	string(16)	no	readOnly	Aliased event type	
 AgencyEventTypeCode	tycod	string(16)	no	readOnly	Event type	
 AliasAgencyId	alias_ag_id	string(9)	no	readOnly	Agency id of aliased event type	

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEventType	AgencyEventTypeAlias	1	*	AgencyEventType	AgencyEventTypeAliases	AgencyId, AgencyEventTypeCode, AgencyEventSubtypeCode	AliasAgencyId, AgencyEventTypeAlias, AgencyEventSubtypeAlias

 [Top](#)

Entity Type Name - AgencyEventTypeResponse							
Description	This table contains the alarm level and response plan information for event type codes. This table links back to the event_type table.						
Base Table Name	event_type_alarm_level						
View Name	cmvAgencyEventTypeResponse						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyEventSubtypeCode [default = default]	sub_tycode	string(16)	no	readOnly	The sub-type of the event type. 'default' if not specified		
 AgencyEventTypeCode	tycod	string(16)	no	readOnly	Event type code		
 AgencyId	ag_id	string(9)	no	readOnly	Agency Id. Different agencies may have different type information for the same event type. For example, police might respond to a murder with priority 1, but EMS may respond with a priority of 3		
 AlarmLevel [default = 0]	alarm_lev	int32	no	readOnly	Alarm Level. This defines the alarm level for the event type. The value must be greater than or equal to 0.		
IncidentCode	fs_icode	string(4)	yes	readOnly	The incident code that will be added to the ZIR protocol packet. If the ZIR protocol version is Westnet Firstin 11, this string must be exactly four characters long Examples: 1001, 1004, 1250, etc. Or if the ZIR protocol version is Westnet Firstin 8, this string must be exactly three characters long Examples: 101, 104, or 199, and the 'I' must be capitalized. Each I- code maps directly to a specific type code (tycod)		
IncidentCodeDesc	fs_icodemessage	string(50)	yes	readOnly	A description of the incident code. Examples: structure fire, animal bite, toxic waste spill, etc. This field cannot be longer than 50 characters		
InterCadAdditionalEvents	additional_events	string(80)	yes	readOnly	InterCAD column, a coded ASCII string with event type and sub type		
IsInterCadSendEvent	intercadsend	boolean	no	readOnly	InterCAD column, indicates if InterCAD sends events out to a third party		
PagerId	page_id	string(12)	yes	readOnly	Pager ID or Pager Group ID. If the page_id is not specified in the esz table, I/Page will look for the page_id in this table. I/Page sends notifications to this page identifier when new events are created with the specified agency, event type, sub-type and alarm level.		
ResponseCode	fs_rcode	string(4)	yes	readOnly	The response code that will be added to the ZIR protocol packet. Each R-code corresponds to a specific severity level. If the ZIR protocol is Westnet Firstin 11, this string must be exactly four characters long. Examples: R001, R004, R250, etc. Or if the ZIR protocol is Westnet Firstin 8, this string must be exactly two characters long. Examples: R1, R4, or R8, and the 'R' must be capitalized. R-codes are mapped to a valid alarm level and tycod combination. If there are identical fs_icode entries, they will have different R-Code combinations.		
ResponseCodeDesc	fs_rcodemessage	string(60)	yes	readOnly	A description of the R-Code. This field cannot be longer than 60 characters		
ResponsePlanName	resp_plan_name	string(50)	yes	readOnly	Response plan which will be used when an event of this type is created.		
UnitRecommendMessage	msg	string(80)	yes	readOnly	Message. This column is information specific of the event type to be displayed at time of unit recommendation.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEventType	AgencyEventTypeResponse	1	*	AgencyEventType	AgencyEventTypeResponses	AgencyId, AgencyEventTypeCode, AgencyEventSubtypeCode	AgencyId, AgencyEventTypeCode, AgencyEventSubtypeCode

 [Top](#)

Entity Type Name - AgencyRosterUnitEmployee							
Description	The roster table defines for each agency its employees, their work schedule and days off, their workshift, and the unit each is assigned to. This table provides the information from which the lineups are created.						
Base Table Name	roster						
View Name	cmvAgencyRosterUnitEmployee						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Agency Identification. This column defines the name of the agency.		
DaysOff	daysoff	string(7)	yes	readOnly	Days Off. This column defines the days off for each employee, where 1 = Sunday and 7 = Saturday.		
 EmployeeId	empid	int32	no	readOnly	Employee ID. This column contains the personnel identification number for the employee.		
RosterDesc	descript	string(80)	yes	readOnly	Description. This column contains descriptive information about the roster		
 RosterName	roster_name	string(30)	no	readOnly	Roster Name. This column contains the name of the roster.		
 UnitId	unid	string(10)	no	readOnly	Unit ID. This column contains the unit identification, usually the call letters.		
VehicleId	carid	string(12)	yes	readOnly	Vehicle ID		
WorkShift	work_shift	string(5)	yes	readOnly	Work Shift. This column defines the workshift for each employee assignment.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	AgencyRosterUnitEmployee	1	*	Agency	AgencyRosterUnitEmployees	AgencyId	AgencyId
DefinedEmployee	AgencyRosterUnitEmployee	1	*	DefinedEmployee	AgencyRosterUnitEmployees	EmployeeId	EmployeeId
DefinedVehicle	AgencyRosterUnitEmployee	0..1	*	DefinedVehicle	AgencyRosterUnitEmployees	VehicleId	VehicleId
ValidUnit	AgencyRosterUnitEmployee	1	*	ValidUnit	AgencyRosterUnitEmployees	UnitId	UnitId

 [Top](#)

Entity Type Name - AniAliCallInfo					
Description	This table contains all ANI/ALI information that was ever viewed through the ANI/ALI interface. The data is stored here automatically by the ANI/ALI process as soon as a calltaker picks up on an ANI/ALI line (E911 call).				
Base Table Name	an_al				
View Name	cmvAniAliCallInfo				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AlternateCallerPhone	lnp_alt	string(14)	yes	readOnly	Local number portability alternate number: This column is configured through the parameter file.
 AniAliNumber	ani_num	int32	no	readOnly	Unique ANI/ALI Number to identify each entry (system- generated).
CallDate	date_stamp	string(10)	yes	readOnly	Date of call. This column is configured through the parameter file.
CallId	call_num	string(20)	no	readOnly	A unique identifying number assigned from the numbr table for a call. Links to call_data.call_num or common_event_call.call_id. If there are multiple ANI/ALI spills for a call, the call_num may be the same for multiple an_al records.
CallTime	time_stamp	string(8)	yes	readOnly	Time of the call. This column is configured through the parameter file.
CallerCellId	cell_id	string(8)	yes	readOnly	Cell ID of the cell phone - Only available from specific carriers. This column is configured through the parameter file.
CallerCity	ccity	string(32)	yes	readOnly	City of caller. This column is configured through the parameter file.
CallerCounty	county	string(5)	yes	readOnly	County - if available . This column is configured through the parameter file.
CallerName	clname	string(32)	yes	readOnly	Caller name. This column is configured through the parameter file.
CallerPhone	clnum	string(14)	yes	readOnly	Phone number of caller. This column is configured through the parameter file.
CallerState	state	string(4)	yes	readOnly	State. This column is configured through the parameter file.

ConsolePosition	position_id	string(10)	yes	readOnly	Id of position where the ANI/ALI packet was sent. Links to term.mux_id
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation data/time stamp
DirectionPrefix	edirpre	string(2)	yes	readOnly	Street Prefix or Number Suffix
DirectionSuffix	edirsuf	string(4)	yes	readOnly	Direction suffix. This column is configured through the parameter file.
EmergencyServiceAgencies	esn_text	string(175)	yes	readOnly	ESN text. Lists Agencies responsible for this area. This column is configured through the parameter file.
EmergencyServiceNumber	esn	string(5)	yes	readOnly	Emergency service number. This column is configured through the parameter file.
LocationId	loc_id	string(20)	yes	readOnly	Location information. This column is configured through the parameter file.
MobileCallbackPhone	callback	string(14)	yes	readOnly	The callback number for cell calls: This column is configured through the parameter file.
OperatingTelephoneCompany	otc	string(70)	yes	readOnly	Operating Telephone Company - Obsolete? This column is configured through the parameter file.
PickUpTerminal	term	string(15)	no	readOnly	ID of Terminal which picked up the call.
PilotPhone	pilot_nnx	string(14)	yes	readOnly	Pilot telephone number. This column is configured through the parameter file.
ServiceClass	service	string(35)	yes	readOnly	Class of service. This column is configured through the parameter file.
StreetName	efeanme	string(60)	yes	readOnly	Feature name. This column is configured through the parameter file.
StreetNumber	estnum	string(15)	yes	readOnly	House number. This column is configured through the parameter file.
StreetNumberSuffix	house_num_suf	string(5)	yes	readOnly	House number suffix. This column is configured through the parameter file.
StreetType	efeatyp	string(4)	yes	readOnly	Feature type This column is configured through the parameter file.
TowerSectorId	sector_id	string(2)	yes	readOnly	Sector ID - Tower Sector for Phase 1 information. This column is configured through the parameter file.
XCoordinateOrLongitude	x_long	string(15)	yes	readOnly	Longitude value from AniAli packet
XYCoordinate	xy_uors	string(30)	yes	readOnly	UOR data generated from Lat/Long and map by the I/AniAli process in the form "XY=(-<x-uor>,<y-uor>)"
YCoordinateOrLatitude	y_lat	string(15)	yes	readOnly	Latitude value form AniAli packet


[Top](#)

Entity Type Name - ApplicationDispatchGroupAccess							
Description	This table stores information about application access to agency/ dispatch groups. Dispatcher, Calltaker, CADDDBM and the Recommend Unit Service restrict access based on the terminal node running the application. NetViewer, NetDispatcher and NetCommander restrict access based on the employee running the application.						
Base Table Name	app_access						
View Name	cmvApplicationDispatchGroupAcc						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId	ag_id	string(9)	no	readOnly	Agency ID. Contains the agency id of the dispatch group.		
 ApplicationType	app_type	string(15)	no	readOnly	Application type: call (Calltaker), disp (Dispatcher), caddbm, mdt_server (MDT Server), NetCommander, NetViewer (NetViewer or NetDispatcher), recunitsvc% (Recommend Unit Service)		
CurrentAccess [default = N]	current_access	string(1)	no	readOnly	Current Access: Contains a C (cover), R (read), W (Write) if this application type and access are signed on for the user. N means no access. L means terminal is 'locked' by the Change Operator command. Old lflag column		
CurrentAccessSaved	current_access_saved	string(1)	yes	readOnly	Saved value of current_access column. The Change Operator command in CAD sets current_access_saved to current_access, and then sets current_access to L to indicate terminal is locked. Value is NULL when app is not in Change Operator mode.		
CurrentVisibility [default = N]	current_visibility	string(1)	no	readOnly	Current Visibility. Column is set to 'L' for loaded but not visible, 'Y' for loaded and visible or 'N' for not loaded. Old currassign column		
DefaultAccess [default = R]	default_access	string(1)	no	readOnly	Default access. Defines whether the user may monitor (R) events and units of an agency/ dispatch group or update (W) them or (C) cover them. For the Recommend Unit Service, (R) is not used, (W) means units in agency/dgroups with this access level will be considered for recommendations, but events will be ignored and (C) means events in agency/dgroups with this access level will have recommendations generated, and units in agency/dgroups with this access level will be considered for recommendations. This value is set by CADDDBM. Old readwrite column		
DefaultVisibility [default = Y]	default_visibility	string(1)	no	readOnly	Default visibility. Contains a Y if agency dispatch group is to be visible at signon. Contains an L for Loaded but not visible. When this is set to N, state can still be modified through the Define Node command. Old defaultassign column		
 DispatchGroup	dgroup	string(5)	no	readOnly	Dispatch group		
 EmployeeId [default = 0]	empid	int32	no	readOnly	This column contains the numeric representation of the employee id in the id column if id_type is E or zero if id type is T.		
 Id	id	string(15)	no	readOnly	This column contains either the terminal node name or the employee id		
IdType	id_type	string(1)	no	readOnly	ID Type. E = employee id. T = terminal node.		
MaxAccess [default = R]	max_access	string(1)	no	readOnly	Maximum access allowed to agency / dispatch group, as defined in CADDDBM. Defines the allowed access transitions through the "Define Node" command. Values are R (Read), W (Write), and C (Cover). Old max_readwrite column		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyDispatchGroup	ApplicationDispatchGroupAccess	1	*	AgencyDispatchGroup	ApplicationDispatchGroupAccess	AgencyId, DispatchGroup	AgencyId, DispatchGroup


[Top](#)

Entity Type Name - ApplicationDisplay					
Description	Used to store window locations when a user signs off so that the locations can be restored when the user logs in on a different machine.				
Base Table Name	app_display				
View Name	cmvApplicationDisplay				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 ApplicationType	app_type	string(20)	no	readOnly	Executable name, such as IDISP or ICALL
 DisplaySetName	display_set	string(20)	no	readOnly	User application set name, such as arrange or startup
ItemData	item_data	string(4000)	no	readOnly	Xy locations, num maps, etc.
 ItemName	item_name	string(80)	no	readOnly	Item Name, such as mainframe, ssm, num_maps, etc.
 UserName	usr_id	string(20)	no	readOnly	User's id from persl.usr_id


[Top](#)

Entity Type Name - AttachmentContent					
Description	This table stores attachment contents for items such as calls, events, and messages				
Base Table Name	attachment_content				
View Name	cmvAttachmentContent				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AttachmentId	attachment_id	guid	no	readOnly	Uniquely identifies an attachment
Content	content	binary(Max)	no	readOnly	The binary data that represents the attachment
CreatedEmployeeId	cpers	int32	no	readOnly	The employee id of the person that created this record
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that was used to create this record
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time when the attachment record was created


[Top](#)

Entity Type Name - AttachmentInfo	
Description	This table stores metadata associated with the content data stored in the attachment_content table
Base Table Name	attachment_info

View Name	cmvAttachmentInfo						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AttachmentId	attachment_id	guid	no	readOnly	Uniquely identifies an attachment		
ContentSize	content_size	int32	no	readOnly	The number of bytes contained in the attachment. The absolute maximum of an attachment is 50 MB, but it may be limited in support of other requirements		
ContentType	content_type	string(255)	no	readOnly	The mime-type of the file attachment. The size comes from RFC 4288		
CreatedEmployeeId	cpers	int32	no	readOnly	The employee id of the person that created this record		
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that was used to create this record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time when the attachment record was created		
Name	name	string(260)	no	readOnly	A user provided name for the attachment that may default to the file name. The size is MAX_PATH		
OriginalFileName	original_file_name	string(260)	yes	readOnly	The original file name if the attachment originated as a file		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AttachmentInfo	CallAttachment	1	*	AttachmentInfo	CallAttachments	AttachmentId	AttachmentId
AttachmentInfo	CommonEventAttachment	1	*	AttachmentInfo	CommonEventAttachments	AttachmentId	AttachmentId
AttachmentInfo	MessageAttachment	1	*	AttachmentInfo	MessageAttachments	AttachmentId	AttachmentId

 [Top](#)

Entity Type Name - Broadcast							
Description	The broadcast table contains the common data associated with each broadcast message issued. This information is tied to specific information in cast_nar, cast_subject, broad_xref, and cast_vehicle via the broadcast_num column.						
Base Table Name	broadcast						
View Name	cmvBroadcast						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Agency ID (from agenc table) for the dispatch group authorizing broadcast		
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID for the broadcast		
CancelledComment	xcmt	string(40)	yes	readOnly	Closing Comments		
CancelledEmployeeId	xpers	int32	yes	readOnly	Cancelling Person		
CancelledTerminal	xterm	string(15)	yes	readOnly	Cancelling Terminal		
CancelledTime	xdts	dateTimeOffset	yes	readOnly	Cancel Date/Time Stamp		
IsActive	curent	boolean	no	readOnly	Current Record Indicator		
Location	location	string(150)	yes	readOnly	Location associated to a broadcast		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag, contains the nodename of the terminal which has locked the record for updating, or NULLTERM if it is not locked		
LookupType	lookout_type	string(8)	no	readOnly	Lookupout Type.		
RevisionEmployeeId	cpers	int32	no	readOnly	Person creating broadcast		
RevisionNumber [default = 1]	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail to trace the evolution of a broadcast.		
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal creating broadcast		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp.		
SenderEmployeeId	reg_num	int32	yes	readOnly	Employee Id number of person on whose authority broadcast is being issued.		
SenderFirstName	reg_fname	string(50)	yes	readOnly	First Name of person on whose authority broadcast is sent		
SenderLastName	reg_lname	string(50)	yes	readOnly	Last Name of person on whose authority broadcast is sent		
SenderMiddleInitial	reg_mi	string(1)	yes	readOnly	Middle Initial of person on whose authority this broadcast is being sent		
SenderOther	reg_other	string(20)	yes	readOnly	Other Authority authorizing broadcast to be sent		
SenderUnitId	reg_unit	string(10)	yes	readOnly	Registering Unit on whose authority broadcast is sent		
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of person updating broadcast		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating broadcast		
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	Broadcast	1	*	Agency	Broadcasts	AgencyId	AgencyId
Broadcast	BroadcastCommentLine	1	*	Broadcast	BroadcastCommentLines	BroadcastId	BroadcastId
Broadcast	BroadcastDestination	1	*	Broadcast	BroadcastDestinations	BroadcastId	BroadcastId
Broadcast	BroadcastPerson	1	*	Broadcast	BroadcastPeople	BroadcastId	BroadcastId
Broadcast	BroadcastReference	1	0..1	Broadcast	BroadcastReference	BroadcastId	BroadcastId
Broadcast	BroadcastVehicle	1	*	Broadcast	BroadcastVehicles	BroadcastId	BroadcastId
Broadcast	BroadcastViewingTerminal	1	*	Broadcast	BroadcastViewingTerminals	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - BroadcastCommentLine							
Description	This table contains the narration, or comments, pertaining to individual broadcasts.						
Base Table Name	cast_nar						
View Name	cmvBroadcastCommentLine						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID of broadcast to which the information in this record pertains		
CommentText	comm	string(80)	no	readOnly	One line of the text entered in the narrative gadget on any of the broadcast forms		
CreatedEmployeeId	cpers	int32	no	readOnly	Creation Person		
CreatedTerminal	cterm	string(15)	no	readOnly	Creation Terminal		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp		
 LinearOrder	lin_ord	int32	no	readOnly	Line Order used to assemble entries from the comm column into a complete description.		
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update date time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Broadcast	BroadcastCommentLine	1	*	Broadcast	BroadcastCommentLines	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - BroadcastDestination	
Description	This table stores the destinations for a specified command type and instance. Used by broadcast.
Base Table Name	destinations
View Name	cmvBroadcastDestination
Monitored	No
Properties	

Property Name	Base Column	Data Type	NULL	Access Type	Description		
 BroadcastId	item_number	int32	no	readOnly	Unique item number for the command which stores its information in this table.		
CommandCode {hidden}	command_code				Integer value indicating for which command this destination is relevant. 1=Broadcast, 3=Scratch Pad		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The creation date time stamp.		
DeletedId {hidden}	delete_id				An arbitrary value that uniquely identifies a deleted row		
 Destination	destination	string(80)	no	readOnly	A destination such as a nodename, mdt-id, page-id, email address, etc.		
DestinationId	unique_id	guid	no	readOnly	Uniquely identifies a row		
DestinationSubtype	sub_type	string(15)	yes	readOnly	CAD, MDT, PAGER, or other application.		
 DestinationType	main_type	string(8)	no	readOnly	TERM, PERSON, PAGER, STATION, GROUP, EMPID, or FILTER.		
IsActive {hidden}	curent				T/F, indicates if row is active or deleted		
MessageStatus	msg_status	string(1)	no	readOnly	B/H/R/N/S, Indicating broadcast, scheduled, read, not read, or saved.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The update date time stamp.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Broadcast	BroadcastDestination	1	*	Broadcast	BroadcastDestinations	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - BroadcastHistory					
Description	The broadcast table contains the common data associated with each broadcast message issued. This information is tied to specific information in cast_nar, cast_subject, broad_xref, and cast_vehicle via the broadcast_num column.				
Base Table Name	broadcast				
View Name	cmvBroadcastHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyId	ag_id	string(9)	no	readOnly	Agency ID (from agenc table) for the dispatch group authorizing broadcast
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID for the broadcast
CancelledComment	xcmt	string(40)	yes	readOnly	Closing Comments
CancelledEmployeeId	xpers	int32	yes	readOnly	Cancelling Person
CancelledTerminal	xterm	string(15)	yes	readOnly	Cancelling Terminal
CancelledTime	xdts	dateTimeOffset	yes	readOnly	Cancel Date/Time Stamp
CreatedEmployeeId	upers	int32	no	readOnly	ID of person updating broadcast
CreatedTerminal	uterm	string(15)	no	readOnly	Terminal updating broadcast
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator
Location	location	string(150)	yes	readOnly	Location associated to a broadcast
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag, contains the nodename of the terminal which has locked the record for updating, or NULLTERM if it is not locked
LookoutType	lookout_typ	string(8)	no	readOnly	Lookout Type.
RevisionEmployeeId	cpers	int32	no	readOnly	Person creating broadcast
 RevisionNumber [default = 1]	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail to trace the evolution of a broadcast.
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal creating broadcast
RevisionTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp.
SenderEmployeeId	reg_num	int32	yes	readOnly	Employee Id number of person on whose authority broadcast is being issued.
SenderFirstName	reg_fname	string(50)	yes	readOnly	First Name of person on whose authority broadcast is sent
SenderLastName	reg_lname	string(50)	yes	readOnly	Last Name of person on whose authority broadcast is sent
SenderMiddleInitial	reg_mi	string(1)	yes	readOnly	Middle Initial of person on whose authority this broadcast is being sent
SenderOther	reg_other	string(20)	yes	readOnly	Other Authority authorizing broadcast to be sent
SenderUnitId	reg_unit	string(10)	yes	readOnly	Registering Unit on whose authority broadcast is sent

 [Top](#)

Entity Type Name - BroadcastPerson							
Description	The cast_subject table contains records which are descriptive of the persons who were the subjects of the individual broadcasts.						
Base Table Name	cast_subject						
View Name	cmvBroadcastPerson						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AdditionalInfo	additional	string(80)	yes	readOnly	Additional Subject Info not found in other columns		
Age	age	int32	yes	readOnly	Age of broadcast subject		
BirthDate	date_ob	string(10)	yes	readOnly	Date of Birth of subject		
 BroadcastId	broadcast_num	int32	no	readOnly	Unique broadcast ID to which the information in this record pertains		
Clothing	clothing	string(80)	yes	readOnly	Subject clothing		
EyeColor	eye	string(3)	yes	readOnly	Eye color of subject		
FirstName	fname	string(50)	yes	readOnly	First Name of subject		
HairColor	hair	string(3)	yes	readOnly	Hair Color of subject		
Height	height	int32	yes	readOnly	Height of broadcast subject.		
IsActive	curent	boolean	no	readOnly	Current Record Indicator		
LastName	lname	string(50)	yes	readOnly	Last Name of the subject		
 PersonNumber	row_num	int32	no	readOnly	Row number of the form gadget which contains the subject information		
PhysicalDesc	physical	string(80)	yes	readOnly	Physical description of the subject		
Race	race	string(1)	yes	readOnly	Racial group of subject		
RevisionEmployeeId	cpers	int32	no	readOnly	Creation Person		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creation Terminal		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp		
Sex	sex	string(1)	yes	readOnly	Sex of the broadcast subject		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp		
Weight	weight	int32	yes	readOnly	Physical weight of subject		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Broadcast	BroadcastPerson	1	*	Broadcast	BroadcastPeople	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - BroadcastPersonHistory					
Description	The cast_subject table contains records which are descriptive of the persons who were the subjects of the individual broadcasts.				
Base Table Name	cast_subject				
View Name	cmvBroadcastPersonHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AdditionalInfo	additional	string(80)	yes	readOnly	Additional Subject Info not found in other columns
Age	age	int32	yes	readOnly	Age of broadcast subject
BirthDate	date_ob	string(10)	yes	readOnly	Date of Birth of subject
 BroadcastId	broadcast_num	int32	no	readOnly	Unique broadcast ID to which the information in this record pertains
Clothing	clothing	string(80)	yes	readOnly	Subject clothing
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp
EyeColor	eye	string(3)	yes	readOnly	Eye color of subject
FirstName	fname	string(50)	yes	readOnly	First Name of subject
HairColor	hair	string(3)	yes	readOnly	Hair Color of subject
Height	height	int32	yes	readOnly	Height of broadcast subject.
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator
LastName	lname	string(50)	yes	readOnly	Last Name of the subject
 PersonNumber	row_num	int32	no	readOnly	Row number of the form gadget which contains the subject information
PhysicalDesc	physical	string(80)	yes	readOnly	Physical description of the subject
Race	race	string(1)	yes	readOnly	Racial group of subject
RevisionEmployeeId	cpers	int32	no	readOnly	Creation Person
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creation Terminal
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp
Sex	sex	string(1)	yes	readOnly	Sex of the broadcast subject
Weight	weight	int32	yes	readOnly	Physical weight of subject

 [Top](#)

Entity Type Name - BroadcastReference							
Description	This table contains information about case and event numbers cross- referenced to a broadcast.						
Base Table Name	broad_xref						
View Name	cmvBroadcastReference						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	yes	readOnly	Unique ID for the event cross- referenced to this broadcast		
AgencyEventSubtypeCode	sub_tycode	string(16)	yes	readOnly	The sub-type of the event type.		
AgencyEventTypeCode	tycode	string(16)	yes	readOnly	Type of event cross-referenced to this broadcast		
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID for the broadcast		
CaseId	case_num	string(12)	yes	readOnly	Unique ID for the case number which is cross-referenced to this broadcast		
IsActive [default = true]	current	boolean	no	readOnly	Current Flag.		
RevisionEmployeeId	cpers	int32	no	readOnly	Employee ID of person who created this record		
RevisionNumber [default = 1]	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail to trace the evolution of a broadcast.		
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal from which this record was created		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date-Time stamp for this record		
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of person updating broadcast cross reference		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating broadcast cross reference		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date-time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	BroadcastReference	0..1	*	AgencyEvent	BroadcastReferences	AgencyEventId	AgencyEventId
Broadcast	BroadcastReference	1	0..1	Broadcast	BroadcastReference	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - BroadcastReferenceHistory					
Description	This table contains information about case and event numbers cross- referenced to a broadcast.				
Base Table Name	broad_xref				
View Name	cmvBroadcastReferenceHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	num_1	string(12)	yes	readOnly	Unique ID for the event cross- referenced to this broadcast
AgencyEventSubtypeCode	sub_tycode	string(16)	yes	readOnly	The sub-type of the event type.
AgencyEventTypeCode	tycode	string(16)	yes	readOnly	Type of event cross-referenced to this broadcast
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID for the broadcast
CaseId	case_num	string(12)	yes	readOnly	Unique ID for the case number which is cross-referenced to this broadcast
CreatedEmployeeId	upers	int32	no	readOnly	ID of person updating broadcast cross reference
CreatedTerminal	uterm	string(15)	no	readOnly	Terminal updating broadcast cross reference
CreatedTime	udts	dateTimeOffset	no	readOnly	Update date-time stamp
IsActive [default = false]	current	boolean	no	readOnly	Current Flag.
RevisionEmployeeId	cpers	int32	no	readOnly	Employee ID of person who created this record
 RevisionNumber	rev_num	int32	no	readOnly	Revision Number of Record. Used to provide an audit trail to trace the evolution of a broadcast.
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal from which this record was created
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date-Time stamp for this record

 [Top](#)

Entity Type Name - BroadcastVehicle	
Description	The cast_vehicle table contains records which describe the vehicles involved within the individual broadcasts.
Base Table Name	cast_vehicle
View Name	cmvBroadcastVehicle
Monitored	No

Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AdditionalInfo	additional	string(45)	yes	readOnly	Additional vehicle info not found in other columns		
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID of broadcast to which information in this record pertains		
IsActive	current	boolean	no	readOnly	Current Record Indicator		
LicensePlateNumber	license	string(9)	yes	readOnly	License number of vehicle		
LicenseYear	year_lic	int32	yes	readOnly	Year of the vehicle license		
MainColor	color_1	string(7)	yes	readOnly	Main color of the vehicle		
Make	make	string(4)	yes	readOnly	Abbreviated vehicle make info		
Model	model	string(3)	yes	readOnly	Abreviated vehicle model info		
ModelYear	year_vch	int32	yes	readOnly	Model year of the vehicle		
RevisionEmployeeId	cpers	int32	no	readOnly	Creation Person		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creation Terminal		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp		
SecondaryColor	color_2	string(7)	yes	readOnly	Secondary vehicle color		
State	state	string(4)	yes	readOnly	State where vehicle licensed		
Style	style	string(3)	yes	readOnly	Vehicle Style (4dr, 2dr,etc)		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp		
 VehicleNumber	row_num	int32	no	readOnly	Row number of form gadget containing vehicle info		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Broadcast	BroadcastVehicle	1	*	Broadcast	BroadcastVehicles	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - BroadcastVehicleHistory					
Description	The cast_vehicle table contains records which describe the vehicles involved within the individual broadcasts.				
Base Table Name	cast_vehicle				
View Name	cmvBroadcastVehicleHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AdditionalInfo	additional	string(45)	yes	readOnly	Additional vehicle info not found in other columns
 BroadcastId	broadcast_num	int32	no	readOnly	Unique ID of broadcast to which information in this record pertains
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator
LicensePlateNumber	license	string(9)	yes	readOnly	License number of vehicle
LicenseYear	year_lic	int32	yes	readOnly	Year of the vehicle license
MainColor	color_1	string(7)	yes	readOnly	Main color of the vehicle
Make	make	string(4)	yes	readOnly	Abbreviated vehicle make info
Model	model	string(3)	yes	readOnly	Abreviated vehicle model info
ModelYear	year_vch	int32	yes	readOnly	Model year of the vehicle
RevisionEmployeeId	cpers	int32	no	readOnly	Creation Person
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creation Terminal
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp
SecondaryColor	color_2	string(7)	yes	readOnly	Secondary vehicle color
State	state	string(4)	yes	readOnly	State where vehicle licensed
Style	style	string(3)	yes	readOnly	Vehicle Style (4dr, 2dr,etc)
 VehicleNumber	row_num	int32	no	readOnly	Row number of form gadget containing vehicle info

 [Top](#)

Entity Type Name - BroadcastViewingTerminal							
Description	A table that is used for saving the broadcast's last viewing time for terminals. The table will keep one record for each terminal and broadcast number.						
Base Table Name	broadcast_last_viewed						
View Name	cmvBroadcastViewingTerminal						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 BroadcastId	broadcast_num	int32	no	readOnly	The broadcast number		
 CreatedTerminal	cterm	string(15)	no	readOnly	The terminal		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The date and time when the record was created.		
LastViewedTime	last_viewed_dts	dateTimeOffset	yes	readOnly	The last time a terminal viewed a certain broadcast		
UpdateTime	udts	dateTimeOffset	yes	readOnly	The date and time when the record was updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Broadcast	BroadcastViewingTerminal	1	*	Broadcast	BroadcastViewingTerminals	BroadcastId	BroadcastId

 [Top](#)

Entity Type Name - CallAttachment					
Description	Association between a call and its attachments.				
Base Table Name	call_attachment				
View Name	cmvCallAttachment				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AttachmentId	attachment_id	guid	no	readOnly	The key for the attachment
 CallId	call_id	string(20)	no	readOnly	The key for the call
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person adding the attachment to the call
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where the attachment was added to the call
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time the attachment was associated with the call
Associations					

Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AttachmentInfo	CallAttachment	1	*	AttachmentInfo	CallAttachments	AttachmentId	AttachmentId
CallInfo	CallAttachment	1	*	CallInfo	CallAttachments	CallId	CallId

 [Top](#)

Entity Type Name - CallInfo							
Description	This table holds the information regarding calls that came in via the phone system.						
Base Table Name	call_info						
View Name	cmvCallInfo						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CallDirection	call_direction	int16	no	readWrite	The direction of the call. 0 - "U" Don't know. Data not available, 1 - "I" Incoming Internal call, 2 - "E" Incoming External call, 3 - "O" Outgoing call		
 CallId	call_id	string(20)	no	readOnly	The key for the call		
CallLink	call_link	string(20)	yes	readWrite	This will usually be NULL. If a call is queued and a client answers it before the server is able to assign a number to it, the client will create a call_data record. If it then gets notification from the server that the server has assigned a number, it puts the server assigned number in the call_link field. In this case, the call will have two call_data records and the second one will be linked to the first one.		
CallType	call_type	int16	no	readWrite	The type of the call. Valid values are: Text - 0, Voice - 1, Alarm - 2, RadioTalk - 3		
CalledPhoneNumber	called_phone	string(20)	yes	readWrite	Called number		
CallerPhoneNumber	caller_phone	string(20)	yes	readWrite	Caller's number		
ConversationExpireTime	conversation_expire_dts	dateTimeOffset	yes	readWrite	Time after which the conversation is no longer available from the vendor		
ConversationId	conversation_id	string(40)	yes	readWrite	Refers to a conversation file.		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person adding the call to the system		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where the call was added to the system		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation time		
IsEmergency	is_emergency	boolean	no	readWrite	1 if this call is an emergency call, else 0		
IsWireless	is_wireless	boolean	no	readWrite	1 if this call is a wireless call, else 0		
LineName	line_name	string(20)	yes	readWrite	The name of the line the call was received on		
LineType	line_type	string(10)	yes	readWrite	The line type the call was received from		
ReceivedTime	received_dts	dateTimeOffset	no	readOnly	Date and time that the call appeared on the Call Control system.		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of the record		
Terminal	term	string(15)	yes	readWrite	The terminal that owns the line that the call appears on or is dialed from. For queues, this will be the server. For an operator dialing out, it will be the workstation's name.		
TextCallType	text_type	int16	yes	readWrite	The type of the text call. Valid values are: TTY - 0, SMS - 1, RTT - 2, IM - 3. If the call is not a text call, the value is null.		
UpdatedEmployeeId	upers	int32	yes	readOnly	Employee Id of user updating record		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal name at which update made		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date/Time stamp of when record updated		
Vendor	vendor	string(20)	yes	readWrite	The telephone vendor of the call.		
VendorLocalCallId	vendor_local_call_id	string(64)	yes	readWrite	Local Call ID from the vendor.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CallInfo	CallAttachment	1	*	CallInfo	CallAttachments	CallId	CallId
CallInfo	CallInfoHistory	1	*	CallInfo	CallInfoHistories	CallId	CallId
CallInfo	CallText	1	*	CallInfo	CallTexts	CallId	CallId
CallInfo	CallTransition	1	*	CallInfo	CallTransitions	CallId	CallId
CallInfo	CommonEventCall	0..1	*	CallInfo	CommonEventCalls	CallId	CallId
CallInfo	CommonEventCallHistory	0..1	*	CallInfo	CommonEventCallHistories	CallId	CallId

 [Top](#)

Entity Type Name - CallInfoHistory							
Description	This table holds the complete history of information regarding calls that came in via the phone system						
Base Table Name	call_info_history						
View Name	cmvCallInfoHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CallDirection	call_direction	int16	no	readOnly	The direction of the call. 0 - "U" Don't know. Data not available, 1 - "I" Incoming Internal call, 2 - "E" Incoming External call, 3 - "O" Outgoing call		
 CallId	call_id	string(20)	no	readOnly	The key for the call		
CallLink	call_link	string(20)	yes	readOnly	This will usually be NULL. If a call is queued and a client answers it before the server is able to assign a number to it, the client will create a call_data record. If it then gets notification from the server that the server has assigned a number, it puts the server assigned number in the call_link field. In this case, the call will have two call_data records and the second one will be linked to the first one.		
CallType	call_type	int16	no	readOnly	The type of the call. Valid values are: Text - 0, Voice - 1, Alarm - 2, RadioTalk - 3		
CalledPhoneNumber	called_phone	string(20)	yes	readOnly	Called number		
CallerPhoneNumber	caller_phone	string(20)	yes	readOnly	Caller's number		
ConversationExpireTime	conversation_expire_dts	dateTimeOffset	yes	readOnly	Time after which the conversation is no longer available from the vendor		
ConversationId	conversation_id	string(40)	yes	readOnly	Refers to a conversation file.		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person adding the call to the system		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where the call was added to the system		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation time		
IsEmergency	is_emergency	boolean	no	readOnly	1 if this call is an emergency call, else 0		
IsWireless	is_wireless	boolean	no	readOnly	1 if this call is a wireless call, else 0		
LineName	line_name	string(20)	yes	readOnly	The name of the line the call was received on		
LineType	line_type	string(10)	yes	readOnly	The line type the call was received from		
ReceivedTime	received_dts	dateTimeOffset	no	readOnly	Date and time that the call appeared on the Call Control system.		
 RevisionNumber	rev_num	int32	no	readOnly	Revision number of the record		
Terminal	term	string(15)	yes	readOnly	The terminal that owns the line that the call appears on or is dialed from. For queues this will be the server. For an operator dialing out it will be the workstation's name.		
TextCallType	text_type	int16	yes	readOnly	The type of the text call. Valid values are: TTY - 0, SMS - 1, RTT - 2, IM - 3. If the call is not a text call, the value is null.		
Vendor	vendor	string(20)	yes	readOnly	The telephone vendor of the call.		
VendorLocalCallId	vendor_local_call_id	string(64)	yes	readOnly	Local Call ID from the vendor.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CallInfo	CallInfoHistory	1	*	CallInfo	CallInfoHistories	CallId	CallId

 [Top](#)

Entity Type Name - CallText	
Description	Contains text conversations for text or TTY calls
Base Table Name	call_text

View Name	cmvCallText						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 CallId	call_id	string(20)	no	readOnly	Unique Call ID in CAD system.		
 ConversationOrder	conversation_order	int32	no	readOnly	The sequence of the text in the conversation for the same call.		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person adding the text to the call		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where the text was added to the call		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation time		
Source	source	int16	no	readOnly	The source of the text. Valid values are: caller - 0, receiver - 1		
Text	text	string(256)	no	readOnly	The text string from one transmission		
TransmissionTime	transmission_dts	dateTimeOffset	no	readOnly	Transmission Time. Date and time that the text was sent or received by the Call Control system.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CallInfo	CallText	1	*	CallInfo	CallTexts	CallId	CallId

 [Top](#)

Entity Type Name - CallTransition							
Description	Contains the history of the transitions that a call goes through.						
Base Table Name	call_transition						
View Name	cmvCallTransition						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CallId	call_id	string(20)	no	readOnly	Unique Call ID in CAD system.		
 CallTransitionId	unique_id	guid	no	readOnly	Primary key		
ConferencePhoneNumber	conference_phone	string(20)	yes	readOnly	Conference phone number		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person making the transition on the call		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where the transition on the call was made		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation time		
IsConsult	is_consult	boolean	no	readOnly	1 - consult call, 0 - Not a consult call.		
ReceivedTime	received_dts	dateTimeOffset	no	readOnly	Date and time of the call transition received on the Call Control system.		
TransferPhoneNumber	transfer_phone	string(20)	yes	readOnly	Transfer phone number		
Transition	transition	int16	no	readOnly	Unkn: Unknown - 0, Conn: Call Connected - 1, Discon: Call Disconnect (hangup) - 2, Busy: Call Busy - 3, Hold: Call Hold - 4, Recall: Call Callback - 5, Ans: Call Answer - 6, Aband: Call Abandoned - 7, Conf: Call Conference - 8, Trans: Call Transfer - 9, RingIn: Call Offering (Incoming call ringing) - 10, RingOut: Call Ringback (Outgoing call ringing) - 11, ConfIdl: Conference call itself goes idle - 2 part call may still exist - 12, Idle: Call went idle (one or both parties hung-up or call was transferred) - 13, Park: Call Park - 14, Mon: Call Monitor - 15, QAns - 16		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CallInfo	CallTransition	1	*	CallInfo	CallTransitions	CallId	CallId

 [Top](#)

Entity Type Name - CatalogedAlarm							
Description	This table contains alarm- related data used along with information from the segme table for the location verification of a cataloged alarm. A cataloged alarm can be created through CADDDBM.						
Base Table Name	alarm						
View Name	cmvCatalogedAlarm						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Address	address	string(80)	yes	readOnly	Address		
AgencyEventSubType	sub_tycode	string(16)	yes	readOnly	The sub-type of the event type.		
AgencyEventType	tycode	string(16)	yes	readOnly	Event Type Code for alarm from the event_type table		
AlConst {hidden}	al_const				Used by IABL during alarm data bulk load.		
AlarmId	mslink	int32	yes	readOnly	Map Linkage. Links graphics cell for the alarm to a specific location.		
 AlarmName	alarm_id	string(80)	no	readOnly	Unique ID number of alarm		
AlarmStatus	al_status	string(10)	yes	readOnly	Alarm Status		
Apartment	aptnum	string(5)	yes	readOnly	Apartment Number		
CallSource	call_sour	string(8)	yes	readOnly	Call Source.		
Company	company	string(21)	yes	readOnly	Name of company where the alarm is located		
DataSource	data_source	string(5)	yes	readOnly	Source		
MajorEventId	majevt_id	string(10)	yes	readOnly	Major Event Identifier. Pointer to major event plan if this alarm is a major event. NULL otherwise		
MapSegmentId	fea_mslink	int32	yes	readOnly	Segment containing street address of the alarm location		
MapSpecialAddressId	spad_mslink	int32	no	readOnly	Special Address Map Link.		
Pname {hidden}	pname				Premise Name if provided by the input system. Only populated by IABL.		
Priority	priority	int32	yes	readOnly	Alarm priority code.		
Soundex	soundex	string(4)	yes	readOnly	The soundex code for the cataloged alarm name		
StreetNumber	str_num	string(15)	yes	readOnly	Street number of alarm address		
UpdateAction	update_action	string(3)	yes	readOnly	Update action		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CatalogedAlarm	CatalogedAlarmCommentLine	1	*	CatalogedAlarm	CatalogedAlarmCommentLines	AlarmName	AlarmName
CatalogedAlarm	CatalogedAlarmContact	1	*	CatalogedAlarm	CatalogedAlarmContacts	AlarmName	AlarmName
MapSegment	CatalogedAlarm	0..1	*	MapSegment	CatalogedAlarms	MapSegmentId	MapSegmentId
MapSpecialAddress	CatalogedAlarm	1	*	MapSpecialAddress	CatalogedAlarms	MapSpecialAddressId	MapSpecialAddressId
CatalogedAlarm	CatalogedAlarmPerson	1	*	CatalogedAlarm	CatalogedAlarmPeople	AlarmName	AlarmName
CatalogedAlarm	CatalogedAlarmProperty	1	*	CatalogedAlarm	CatalogedAlarmProperties	AlarmName	AlarmName
CatalogedAlarm	CatalogedAlarmVehicle	1	*	CatalogedAlarm	CatalogedAlarmVehicles	AlarmName	AlarmName

 [Top](#)

Entity Type Name - CatalogedAlarmCommentLine						
Description	This table contains the comments associated with an alarm that was processed by I/CAD.					
Base Table Name	alarmcom					
View Name	cmvCatalogedAlarmCommentLine					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	

 AlarmName	alarm_id	string(80)	no	readOnly	Unique Alarm id number		
CommentText	comm	string(80)	no	readOnly	Comments text.		
 LinearOrder	lin_ord	int32	no	readOnly	Line Order Number assigned to comments records to maintain the order in which they were entered on the form		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CatalogedAlarm	CatalogedAlarmCommentLine	1	*	CatalogedAlarm	CatalogedAlarmCommentLines	AlarmName	AlarmName

 [Top](#)

Entity Type Name - CatalogedAlarmContact							
Description	The CADDBM spad_cont_name table contains information describing the person to contact with respect to a special address, commonplace name, or alarm.						
Base Table Name	spad_cont_name						
View Name	cmvCatalogedAlarmContact						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AlarmName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
ContactDate	co_date	string(10)	yes	readOnly	Records date the individual named in the clname column was contacted about the alarm.		
ContactName	clname	string(45)	yes	readOnly	Name of the individual to contact		
ContactPhone	clnum	string(14)	yes	readOnly	Telephone number of the individual to contact		
ContactPriority	priority	int32	yes	readOnly	Indicates priority order in which individual named within this record is to be contacted		
ContactStreetAddress	cstr_add	string(36)	yes	readOnly	Full street address of the individual to contact		
ContactTime	co_time	string(5)	yes	readOnly	Records time the individual named in clname column was contacted about the alarm.		
DataSource	data_source	string(5)	yes	readOnly	Data source		
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for the individual to contact		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
OriginTable {hidden}	origin_table				Table name associated with this contact		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CatalogedAlarm	CatalogedAlarmContact	1	*	CatalogedAlarm	CatalogedAlarmContacts	AlarmName	AlarmName

 [Top](#)

Entity Type Name - CatalogedAlarmPerson							
Description	The CADDBM perso table contains person information which is related to the special address, commonplace name, or alarm.						
Base Table Name	spad_perso						
View Name	cmvCatalogedAlarmPerson						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Age	age	int32	yes	readOnly	Age of the person related to the special address		
 AlarmName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
DateOfBirth	dob	string(10)	yes	readOnly	Date of birth of the person related to the special address		
EyeColor	eye	string(3)	yes	readOnly	Eye color of the person related to the special address		
HairColor	hair	string(3)	yes	readOnly	Hair color of the person related to the special address		
Height	height	int32	yes	readOnly	Height of the person related to the special address		
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for this person		
LicenseNumber	oln	string(20)	yes	readOnly	Operator license number related to the special address		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
Name	nme	string(50)	yes	readOnly	Name of the person related to the special address		
OriginTable {hidden}	origin_table				Table name associated with this person		
Race	race	string(1)	yes	readOnly	Race of the person related to the special address		
Remarks	remarks	string(20)	yes	readOnly	Descriptive remarks about the person related to the special address		
Sex	sex	string(1)	yes	readOnly	Sex of the person related to the special address		
State	state	string(2)	yes	readOnly	State of the operator license number		
Weight	weight	int32	yes	readOnly	Weight of the person related to the special address		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CatalogedAlarm	CatalogedAlarmPerson	1	*	CatalogedAlarm	CatalogedAlarmPeople	AlarmName	AlarmName

 [Top](#)

Entity Type Name - CatalogedAlarmProperty					
Description	This table contains property information related to special address, commonplace name, or alarm.				
Base Table Name	spad_propt				
View Name	cmvCatalogedAlarmProperty				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AlarmName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for the property
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value
MonetaryValue	value	string(10)	yes	readOnly	Monetary value of the property item
OriginTable {hidden}	origin_table				Table name associated with the item
PropertyDesc	item	string(10)	yes	readOnly	Description of the item

Remarks	remarks	string(20)	yes	readOnly	Remarks about the property item		
SerialNumber	serialnum	string(20)	yes	readOnly	Serial number of the item		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CatalogedAlarm	CatalogedAlarmProperty	1	*	CatalogedAlarm	CatalogedAlarmProperties	AlarmName	AlarmName

 [Top](#)

Entity Type Name - CatalogedAlarmVehicle							
Description	This table contains vehicle information which is related to the special address, commonplace name, or alarm.						
Base Table Name	spad_vehic						
View Name	cmvCatalogedAlarmVehicle						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AlarmName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
Color	vehic_color	string(7)	yes	readOnly	Vehicle Color. This column contains the color of the vehicle.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.		
LicensePlateNumber	license	string(8)	yes	readOnly	License Plate Number.		
LicenseType	license_type	string(10)	yes	readOnly	License Type. This column contains the type of vehicle license.		
LicenseYear	license_yr	string(4)	yes	readOnly	License Year. This column contains the year of the license.		
Make	make	string(5)	yes	readOnly	Make of the Vehicle.		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
Model	model	string(5)	yes	readOnly	Model of the Vehicle.		
ModelYear	model_year	int32	yes	readOnly	Year of the Vehicle.		
OriginTable {hidden}	origin_table				Table name associated with this vehicle		
Remarks	remarks	string(20)	yes	readOnly	This column stores the remarks about the vehicle.		
State	state	string(4)	yes	readOnly	State Register of the Vehicle.		
Vin	vin	string(25)	yes	readOnly	Vehicle Identification Number		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CatalogedAlarm	CatalogedAlarmVehicle	1	*	CatalogedAlarm	CatalogedAlarmVehicles	AlarmName	AlarmName

 [Top](#)

Entity Type Name - ChangeItem							
Description	Identifies the entities and properties in which subscriptions are interested. This table is used by the Change Publisher Service.						
Base Table Name	change_item						
View Name	cmvChangeItem						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 ChangeItemId	id	guid	no	readWrite	Uniquely identifies the change item		
EntityTypeName	entity_type_name	string(45)	no	readWrite	The entity type name of interest		
NavigationPropertyName	navigation_property_name	string(35)	yes	readOnly	The name of the navigation property that must be used to access the property if it is hidden		
PrincipalEntityTypeName	principal_entity_type_name	string(45)	yes	readOnly	The principal entity type name associated with the navigation property		
PrincipalPropertyName	principal_property_name	string(30)	yes	readOnly	The principal property name associated with the navigation property		
PropertyName	property_name	string(30)	no	readWrite	The property name of interest		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ChangeSubscription	ChangeItem	*	*	ChangeSubscriptions	ChangeItems	Storage Entity Type: ChangeSubscriptionChangeItem	
ChangeItem	ChangeSubscriptionChangeItem	1	*	ChangeItem	ChangeSubscriptionChangeItems	ChangeItemId	ChangeItemId

 [Top](#)

Entity Type Name - ChangeSubscriber							
Description	A client that is interested in a subscription. This table is used by the Change Publisher Service.						
Base Table Name	subscriber						
View Name	cmvChangeSubscriber						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	agency_id	string(9)	yes	readWrite	An agency identifier		
Application	application	string(15)	yes	readOnly	Application that will receive the change information packets. The Change Subscription Publisher Service specifies the application when it sends Listener packets to the clients. So, the value in this column is actually the string that the application uses when it logs on to Listener.		
DispatchGroup	dispatch_group	string(6)	yes	readWrite	A dispatch group		
 SubscriberId	id	guid	no	readWrite	Uniquely identifies a subscriber		
 SubscriptionId	subscription_id	guid	no	readWrite	Identifies the subscription of interest		
TerminalName	terminal	string(15)	yes	readWrite	The name of a terminal		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyDispatchGroup	ChangeSubscriber	0..1	*	AgencyDispatchGroup	ChangeSubscribers	AgencyId, DispatchGroup	AgencyId, DispatchGroup
ChangeSubscription	ChangeSubscriber	1	*	ChangeSubscription	ChangeSubscribers	SubscriptionId	SubscriptionId
Terminal	ChangeSubscriber	0..1	*	Terminal	ChangeSubscribers	TerminalName	TerminalName

 [Top](#)

Entity Type Name - ChangeSubscription							
Description	Allows users to subscribe to database change notifications. This table is used by the Change Publisher Service.						
Base Table Name	subscription						
View Name	cmvChangeSubscription						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
IsActive	is_active	boolean	no	readWrite	Indicates if subscription is active (T/F)		
 SubscriptionId	id	guid	no	readWrite	Uniquely identifies a subscription		
SubscriptionName	name	string(50)	no	readWrite	User friendly name that uniquely identifies a subscription		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ChangeSubscription	ChangeItem	*	*	ChangeSubscriptions	ChangeItems	Storage Entity Type: ChangeSubscriptionChangeItem	
ChangeSubscription	ChangeSubscriber	1	*	ChangeSubscription	ChangeSubscribers	SubscriptionId	SubscriptionId
ChangeSubscription	ChangeSubscriptionChangeItem	1	*	ChangeSubscription	ChangeSubscriptionChangeItems	SubscriptionId	SubscriptionId

 [Top](#)

Entity Type Name - ChangeSubscriptionChangeItem							
Description	Ties a subscription to a change item. This table is used by the Change Publisher Service.						
Base Table Name	subscription_change_item						
View Name	cmvChangeSubscriptionChangeIte						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 ChangeItemId	change_item_id	guid	no	readWrite	Identifies the associated change item		
 SubscriptionId	subscription_id	guid	no	readWrite	Identifies the subscription that is associated with this item		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ChangeItem	ChangeSubscriptionChangeItem	1	*	ChangeItem	ChangeSubscriptionChangeItems	ChangeItemId	ChangeItemId
ChangeSubscription	ChangeSubscriptionChangeItem	1	*	ChangeSubscription	ChangeSubscriptionChangeItems	SubscriptionId	SubscriptionId

 [Top](#)

Entity Type Name - CommandHistory					
Description	This table is used to track the system history of certain commands executed by I/CAD. These are: Define Node, Define Remote Node, Stack Event, Stack Event Alarm, Change Deployment Table, Change Password, Global Time, ETA Off, ETA On, Change Unit Number, Reset Password, Response Time Down, Response Time Clear, Transfer Unit, Unit Properties, and Logoff Unit.				
Base Table Name	sys_hist				
View Name	cmvCommandHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 CommandHistoryId	unique_id	guid	no	readOnly	Unique id. Used to uniquely identify each row in the table.
CommandInfo	comments	string(240)	yes	readOnly	Comments. This column contains the textual comments.
CommandName	cmd_name	string(40)	no	readOnly	Command Name. Name of the command that was executed in I/CAD.
CreatedEmployeeId	cpers	int32	no	readOnly	Creating Person. This column contains the unique ID of the operator creating the record.
CreatedSecs {hidden}	csec				Cdts time stamp stored in epoch seconds
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal Node Identifier. This column contains the name of the terminal node that created the record.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Current Date/Time Stamp. This column contains the date/time stamp that represents the date and time this record was created.

 [Top](#)

Entity Type Name - CommonEvent					
Description	The common_event table contains information common to all agencies that may be assigned to an event. The records in this table are created by I/CAD only.				
Base Table Name	common_event				
View Name	cmvCommonEvent				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
Apartment [Monitored]	eapt	string(5)	yes	readOnly	Apartment number component of event's location
Area [Monitored]	eara	string(40)	yes	readOnly	Area component of the event's location
CommonEventCustom1	cecust1	string(50)	yes	readWrite	Common event custom column 1
CommonEventCustom2	cecust2	string(50)	yes	readWrite	Common event custom column 2
CommonEventCustom3	cecust3	string(50)	yes	readWrite	Common event custom column 3
CommonEventCustom4	cecust4	string(50)	yes	readWrite	Common event custom column 4
 CommonEventId [Monitored]	eid	int32	no	readOnly	System event number for the event.
CommonplaceName	ecompl	string(80)	yes	readOnly	Commonplace name associated with the event's location
CreatedDayOfWeek {hidden}	dow				Day of week on which the event was reported
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee ID of the person responsible for creating the record
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	Terminal on which the record was created
CreatedTime	cdts	dateTimeOffset	no	readOnly	Date/time this record was inserted
CrossStreet1	xstreet1	string(34)	yes	readOnly	Feature name and type of one street which intersects the event's location
CrossStreet2	xstreet2	string(34)	yes	readOnly	Feature name and type of one street which intersects the event's location
DirectionPrefix [Monitored]	edirpre	string(2)	yes	readOnly	Direction prefix component of the event's location
DirectionSuffix [Monitored]	edirsuf	string(2)	yes	readOnly	Direction suffix component of the event's location
HasInformerLoiData [default = false]	loi_inf	boolean	no	readOnly	Loi_inf is used to identify if the selected event has related Informer information found via Informer searches. It is used to light the Location button or the Inf button on the Event dialogs in CAD.
HasLoiData [default = false]	loi_event	boolean	no	readOnly	Loi_event is used to identify if the selected event has related events found via a DBServer search of the event tables. It is used to light the Location button or the Ev button on the Event dialogs in CAD.
HasSpecialSituationLoiData [default = false]	loi_specsit	boolean	no	readOnly	Loi_specsit is used to identify if the selected event has related special situation data found via a DBServer search of the special situation table. It is used to light the Location button or the SS button on the Event dialogs in CAD.
HasTemporaryLock [default = false]	temp_lock	boolean	no	readOnly	Used to temporarily lock the row. T= row is locked. F = row is not locked. The committed value in the database should always be F
IsLocationVerified	loc_ver	boolean	no	readOnly	The location verified status for the event. T means the location was successfully verified. F means the location was not verified.
Latitude	latitude	double	no	readOnly	Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)

Location	elocation	string(450)	no	readOnly	Event location string
Location1	eloc_fld1	string(5)	yes	readOnly	Generic location field
Location2	eloc_fld2	string(5)	yes	readOnly	Generic location field
Location3	eloc_fld3	string(5)	yes	readOnly	Generic location field
Location4	eloc_fld4	string(5)	yes	readOnly	Generic location field
LocationComment	loc_com	string(80)	yes	readOnly	Location comments.
LockingTerminal	updt_flag	string(15)	no	readOnly	Mutual exclusion column for event updating. If event is not being updated, value is set to NULLTERM.
Longitude	longitude	double	no	readOnly	Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
MapLevels	maplevs	string(200)	yes	readOnly	Map level(s) assigned to the event due to special address as location
MapSegmentId	fea_mslink	int32	yes	readOnly	Source feature map link
Municipality [Monitored]	emun	string(40)	yes	readOnly	Municipality component of the event's location
ParseType [default = -1]	parse_type	int32	no	readOnly	Parse type. Indicates how the location was parsed. -1= unknown, 0= street, 1= intersection, 2= commonplace, 3= alarm, 4= X,Y location.
PatientName	patient	string(45)	yes	readOnly	Patient's name if this event is a scheduled event
ProQACadCaseId	pcad_case_num	string(12)	yes	readOnly	CAD case number generated for ProQA case
RevisionEmployeeId	rev_pers	int32	no	readOnly	Employee ID of person who created this revision.
RevisionNumber	rev_num	int32	no	readOnly	Record revision number.
RevisionSeconds [hidden]	rev_sec				Rev_dts time stamp stored in epoch seconds.
RevisionTerminal	rev_term	string(15)	no	readOnly	Terminal on which this revision was created.
RevisionTime	rev_dts	dateTimeOffset	no	readOnly	Date timestamp when this revision was created. Note that not all updates generate a new revision.
StreetName [Monitored]	efeanme	string(30)	yes	readOnly	Feature name component (street name) of the event's location
StreetNameHash	hash	int32	yes	readOnly	The hash value of the address. The hash uses the direction prefix, street name, street type, and direction suffix for street addresses. For intersections, it uses those values from both streets.
StreetNumber [Monitored]	estnum	string(15)	yes	readOnly	Street number (house number) component of the event's location
StreetType [Monitored]	efeatyp	string(4)	yes	readOnly	Feature type component of the event's location
SystemEsz [default = -1]	s_esz	int32	yes	readOnly	Stores the system esz value from the verified event location.
UpdatedEmployeeId [Monitored]	upers	int32	yes	readOnly	Employee ID of the person responsible for updating the record.
UpdatedTerminal [Monitored]	uterm	string(15)	yes	readOnly	Terminal on which the record was updated.
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date/time of when this record was last updated.
XCoordinate	x_cord	int32	no	readOnly	X map coordinate for the event's location
YCoordinate	y_cord	int32	no	readOnly	Y map coordinate for the event's location
ZipCode	zip	string(10)	yes	readOnly	Zip Code. Queried by Firelink Interface application.

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	ActiveUnit	0..1	*	CommonEvent	ActiveUnits	CommonEventId	CommonEventId
CommonEvent	AgencyEvent	1	*	CommonEvent	AgencyEvents	CommonEventId	CommonEventId
CommonEvent	CommonEventAttachment	1	*	CommonEvent	CommonEventAttachments	CommonEventId	CommonEventId
CommonEvent	CommonEventBoat	1	*	CommonEvent	CommonEventBoats	CommonEventId	CommonEventId
CommonEvent	CommonEventCall	1	*	CommonEvent	CommonEventCalls	CommonEventId	CommonEventId
CommonEvent	CommonEventCommentLine	1	*	CommonEvent	CommonEventCommentLines	CommonEventId	CommonEventId
CommonEvent	CommonEventContact	1	*	CommonEvent	CommonEventContacts	CommonEventId	CommonEventId
CommonEvent	CommonEventGun	1	*	CommonEvent	CommonEventGuns	CommonEventId	CommonEventId
CommonEvent	CommonEventHistory	1	*	CommonEvent	CommonEventHistories	CommonEventId	CommonEventId
CommonEvent	CommonEventIncidentState	1	*	CommonEvent	CommonEventIncidentStates	CommonEventId	CommonEventId
CommonEvent	CommonEventIqaStep	1	*	CommonEvent	CommonEventIqaSteps	CommonEventId	CommonEventId
CommonEvent	CommonEventLvSession	1	*	CommonEvent	CommonEventLvSessions	CommonEventId	CommonEventId
CommonEvent	CommonEventPerson	1	*	CommonEvent	CommonEventPeople	CommonEventId	CommonEventId
CommonEvent	CommonEventProperty	1	*	CommonEvent	CommonEventProperties	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement13	1	*	CommonEvent	CommonEventSupplement1s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement10	1	*	CommonEvent	CommonEventSupplement10s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement11	1	*	CommonEvent	CommonEventSupplement11s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement12	1	*	CommonEvent	CommonEventSupplement12s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement14	1	*	CommonEvent	CommonEventSupplement2s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement15	1	*	CommonEvent	CommonEventSupplement3s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement16	1	*	CommonEvent	CommonEventSupplement4s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement17	1	*	CommonEvent	CommonEventSupplement5s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement18	1	*	CommonEvent	CommonEventSupplement6s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement19	1	*	CommonEvent	CommonEventSupplement7s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement20	1	*	CommonEvent	CommonEventSupplement8s	CommonEventId	CommonEventId
CommonEvent	CommonEventSupplement9	1	*	CommonEvent	CommonEventSupplement9s	CommonEventId	CommonEventId
CommonEvent	CommonEventVehicle	1	*	CommonEvent	CommonEventVehicles	CommonEventId	CommonEventId
CommonEvent	CrossReference	1	*	PrimaryCommonEvent	PrimaryCrossReferences	CommonEventId	PrimaryCommonEventId
CommonEvent	CrossReference	1	*	SecondaryCommonEvent	SecondaryCrossReferences	CommonEventId	SecondaryCommonEventId
CommonEvent	MultiEventTransportLocation	1	*	CommonEvent	MultiEventTransportLocations	CommonEventId	CommonEventId
CommonEvent	RotationalServiceInstance	1	*	CommonEvent	RotationalServiceInstances	CommonEventId	CommonEventId
CommonEvent	TowRequest	1	*	CommonEvent	TowRequests	CommonEventId	CommonEventId
CommonEvent	TransportLocation	1	*	CommonEvent	TransportLocations	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventAttachment					
Description	Associates an event with an attachment				
Base Table Name	event_attachment				
View Name	cmvCommonEventAttachment				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AttachmentId	attachment_id	guid	no	readOnly	Uniquely identifies an attachment
 CommonEventId	eid	int32	no	readOnly	Event Identification Number
CreatedEmployeeId	cpers	int32	no	readOnly	The employee id of the person that created this record
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that was used to create this record
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time when this record was created
InformationScope	info_scope	string(12)	yes	readOnly	The agency this attachment is visible to, or null if visible to agencies that see the event
IsActive	current	boolean	no	readOnly	Flag to indicate if the attachment is to be considered attached to the event
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated
UpdatedEmployeeId	upers	int32	yes	readOnly	The employee id of the person that updated this record
UpdatedTerminal	uterm	string(15)	yes	readOnly	The terminal that was used to update this record

UpdatedTime	udts	dateTimeOffset	yes	readOnly	The time when this record was updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AttachmentInfo	CommonEventAttachment	1	*	AttachmentInfo	CommonEventAttachments	AttachmentId	AttachmentId
CommonEvent	CommonEventAttachment	1	*	CommonEvent	CommonEventAttachments	CommonEventId	CommonEventId
CommonEventAttachment	CommonEventAttachmentHistory	1	*	CommonEventAttachment	CommonEventAttachmentHistories	CommonEventId, AttachmentId	CommonEventId, AttachmentId

 [Top](#)

Entity Type Name - CommonEventAttachmentHistory							
Description	Represents the addition or removal of an attachment to an event						
Base Table Name	event_attachment_history						
View Name	cmvCommonEventAttachmentHisor						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AttachmentId	attachment_id	guid	no	readOnly	Uniquely identifies an attachment		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number		
CreatedEmployeeId	cpers	int32	no	readOnly	The employee id of the person that created this record		
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that was used to create this record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time when this record was created		
InformationScope	info_scope	string(12)	yes	readOnly	The agency this attachment is visible to, or null if visible to agencies that see the event		
IsActive	curent	boolean	no	readOnly	Flag to indicate if the attachment is to be considered attached to the event		
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEventAttachment	CommonEventAttachmentHistory	1	*	CommonEventAttachment	CommonEventAttachmentHistories	CommonEventId, AttachmentId	CommonEventId, AttachmentId

 [Top](#)

Entity Type Name - CommonEventBoat							
Description	Supplemental boat table that can be used by informer						
Base Table Name	boat						
View Name	cmvCommonEventBoat						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	DTS when record expires		
 CommonEventId	eid	int32	no	readOnly	Eid of event		
HullNumber	hull_num	string(50)	yes	readWrite	Hull number of boat		
IdNumber	id_num	string(50)	yes	readWrite	Id number of boat		
InformationScope	info_scope	string(12)	yes	readOnly	If not null, it is the creating agency		
IsActive [default = true]	curent	boolean	no	readOnly	T=record is current, F=earlier record		
IsAutoQueryDisabled	disableautoquery	boolean	yes	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row number		
Jurisdiction	juris	string(10)	yes	readWrite	Jurisdiction		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update flag		
Make	make	string(50)	yes	readWrite	Make of boat		
RegistrationNumber	reg_num	string(50)	yes	readWrite	Registration number of boat		
Remarks	remarks	string(20)	yes	readWrite	Remarks		
Reserved	res	string(2)	yes	readWrite	Unknown		
RevisionEmployeeId	cpers	int32	no	readOnly	Empid of person creating record		
RevisionNumber	rev_num	int32	no	readOnly	Revision number		
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal creating record		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Dts when record was created		
UnitId	unid	string(10)	yes	readWrite	Unit id of MDT creating supp record		
UpdatedEmployeeId	upers	int32	yes	readOnly	Empid of person updating record		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Dts when record was updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventBoat	1	*	CommonEvent	CommonEventBoats	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventBoatHistory					
Description	Supplemental boat table that can be used by informer				
Base Table Name	boat				
View Name	cmvCommonEventBoatHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	DTS when record expires
 CommonEventId	eid	int32	no	readOnly	Eid of event
CreatedEmployeeId	upers	int32	yes	readOnly	Empid of person updating record
CreatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record
CreatedTime	udts	dateTimeOffset	yes	readOnly	Dts when record was updated
HullNumber	hull_num	string(50)	yes	readOnly	Hull number of boat
IdNumber	id_num	string(50)	yes	readOnly	Id number of boat
InformationScope	info_scope	string(12)	yes	readOnly	If not null, it is the creating agency
IsActive [default = false]	curent	boolean	no	readOnly	T=record is current, F=earlier record
IsAutoQueryDisabled	disableautoquery	boolean	yes	readOnly	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row number
Jurisdiction	juris	string(10)	yes	readOnly	Jurisdiction
LockingTerminal	updt_flag	string(15)	no	readOnly	Update flag
Make	make	string(50)	yes	readOnly	Make of boat
RegistrationNumber	reg_num	string(50)	yes	readOnly	Registration number of boat

Remarks	remarks	string(20)	yes	readOnly	Remarks
Reserved	res	string(2)	yes	readOnly	Unknown
RevisionEmployeeId	cpers	int32	no	readOnly	Empid of person creating record
 RevisionNumber	rev_num	int32	no	readOnly	Revision number
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal creating record
RevisionTime	cdts	dateTimeOffset	no	readOnly	Dts when record was created
UnitId	unid	string(10)	yes	readOnly	Unit id of MDT creating supp record

 [Top](#)

Entity Type Name - CommonEventCall							
Description	This table holds a record for every call that comes in about an event. Calls can come in via multiple sources, and regardless of the source they will have a call record in this table.						
Base Table Name	common_event_call						
View Name	cmvCommonEventCall						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CallId	call_id	string(20)	yes	readWrite	Unique Call ID in CAD system. Links to an_al.call_num		
CallSource	call_sour	string(8)	yes	readWrite	Call source. Ani/AlI, Radio, Walk-in,etc.		
CallerCityStateZipCode	ccity	string(25)	yes	readWrite	Caller city. May also contain caller state and zip code. (From ANI/ALI or operator entered)		
CallerName [Monitored]	clname	string(50)	yes	readWrite	Actual caller name (From ANI/ALI or operator entered)		
CallerPhoneNumber	clnum	string(20)	yes	readWrite	Phone number (From ANI/ALI or operator entered)		
CallerStreetAddress	estr_add	string(80)	yes	readWrite	Caller location (From ANI/ALI or operator entered)		
 CommonEventCallId [Monitored]	event_call_id	int32	no	readOnly	Unique id for this call. Generated via numbr table entry		
CommonEventId [Monitored]	eid	int32	no	readWrite	Event Identification Number		
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee ID of the person adding the call to the event		
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	Terminal where the call was added to the event		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time the event was associated with the call		
IsFirstCaller	first_call	boolean	no	readOnly	1 if First Caller, else 0		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of the record		
UpdatedEmployeeId [Monitored]	upers	int32	yes	readOnly	Employee Id of user updating record		
UpdatedTerminal [Monitored]	uterm	string(15)	yes	readOnly	Terminal name at which update made		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date/Time stamp of when record updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CallInfo	CommonEventCall	0..1	*	CallInfo	CommonEventCalls	CallId	CallId
CommonEvent	CommonEventCall	1	*	CommonEvent	CommonEventCalls	CommonEventId	CommonEventId
CommonEventCall	CommonEventCallHistory	1	*	CommonEventCall	CommonEventCallHistories	CommonEventCallId	CommonEventCallId
CommonEventCall	Message	0..1	*	CommonEventCall	Messages	CommonEventCallId	CommonEventCallId

 [Top](#)

Entity Type Name - CommonEventCallHistory							
Description	This table holds a record for every change to every call that comes in about an event. Calls can come in via multiple sources, and regardless of the source they will have a call record in this table. This table contains the current record, as well as all the history records.						
Base Table Name	common_event_call_history						
View Name	cmvCommonEventCallHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CallId	call_id	string(20)	yes	readOnly	Unique Call ID in CAD system. Optional. Links to an_al.call_num		
CallSource	call_sour	string(8)	yes	readOnly	Call source. Ani/AlI, Radio, Walk-in,etc.		
CallerCityStateZipCode	ccity	string(25)	yes	readOnly	Caller city. May also contain caller state and zip code. (From ANI/ALI or operator entered)		
CallerName	clname	string(50)	yes	readOnly	Actual caller name (From ANI/ALI or operator entered)		
CallerPhoneNumber	clnum	string(20)	yes	readOnly	Phone number (From ANI/ALI or operator entered)		
CallerStreetAddress	cstr_add	string(80)	yes	readOnly	Caller location (From ANI/ALI or operator entered)		
 CommonEventCallId	event_call_id	int32	no	readOnly	Unique id for this call. Generated via numbr table entry		
CommonEventId	eid	int32	no	readOnly	Event Identification Number		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person adding the call to the event		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where the call was added to the event		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time the event was associated with the call		
IsFirstCaller	first_call	boolean	no	readOnly	1 if First Caller, else 0		
 RevisionNumber	rev_num	int32	no	readOnly	Revision number of the record		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CallInfo	CommonEventCallHistory	0..1	*	CallInfo	CommonEventCallHistories	CallId	CallId
CommonEventCall	CommonEventCallHistory	1	*	CommonEventCall	CommonEventCallHistories	CommonEventCallId	CommonEventCallId

 [Top](#)

Entity Type Name - CommonEventCommentLine					
Description	This table contains comments entered when the event was created/updated in I/CAD. They can be seen by all agencies or marked as agency specific, making them visible only to the agency responding to the event.				
Base Table Name	evcom				
View Name	cmvCommonEventCommentLine				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
CreatedSecs {hidden}	csec				Cdts time stamp stored in epoch seconds
AgencyId [Monitored]	comm_scope	string(12)	yes	readOnly	Readership scope for the comment. This column is NULL when the information is common, or the ID of the agency for which the information is specific to.
CommentText [Monitored]	comm	string(4000)	no	readOnly	Segment of the comment entered by the user

CommonEventCommentId [Monitored]	unique_id	guid	no	readOnly	Unique identifier		
CommonEventId [Monitored]	eid	int32	no	readOnly	Event Identification Number. Internal system event number to which this comment belongs. This column links to the eid column in the event, agency_event, vehic, perso, un_hi, and propt tables.		
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee ID of the person responsible for creating the record.		
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal on which the record was created.		
CreatedTime [Monitored]	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmsszz) at which this record was inserted into the database.		
IsSystemComment [Monitored]	comm_key	boolean	no	readOnly	Indicates if this is a system comment (comm_key > 0)		
LineGroupId [Monitored]	lin_grp	int32	no	readOnly	Unique identifier for a group of lines of event comments. An individual line of comment will have a value of zero. A group of lines of the same comment will have an integer value generated from the numbr table.		
LinearOrder [Monitored]	lin_ord	int32	no	readOnly	Linear order for this comment segment. This value is used in the reconstruction of the comment by selecting all records with the same eid, cterm and cdts.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	CommonEventCommentLine	0..1	*	Agency	CommonEventCommentLines	AgencyId	AgencyId
CommonEvent	CommonEventCommentLine	1	*	CommonEvent	CommonEventCommentLines	CommonEventId	CommonEventId

[Top](#)

Entity Type Name - CommonEventContact							
Description	The cont_name table contains information describing the contact of persons due to the occurrence of various alarms.						
Base Table Name	cont_name						
View Name	cmvCommonEventContact						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
CommonEventId	eid	int32	no	readOnly	Unique integer value which identifies this record.		
ContactDate	co_date	string(10)	yes	readWrite	Records date the individual named in the clname column was contacted about alarm.		
ContactName	clname	string(45)	yes	readWrite	Full name of the contacted individual.		
ContactPhone	clnum	string(14)	yes	readWrite	Telephone number of the contacted individual.		
ContactPriority	priority	int32	yes	readWrite	Indicates priority order in which person named within this record was to be contacted in the event of an alarm.		
ContactStreetAddress	cstr_add	string(36)	yes	readWrite	Full street address of the contacted individual.		
ContactTime	co_time	string(5)	yes	readWrite	Records time the individual named in clname column was contacted about the alarm.		
InformationScope	info_scope	string(12)	yes	readOnly	Indicates/limits availability of record contents to particular agencies.		
IsActive [default = true]	curent	boolean	no	readOnly	Status of this record. When T = current record, F = old record		
ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for this contacted individual and alarm.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Used by CAD to temporarily lock this record for update.		
RevisionEmployeeId	cpers	int32	no	readOnly	ID number creating person.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creation terminal		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp.		
UpdatedEmployeeId	upers	int32	yes	readOnly	Updating person		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating terminal		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventContact	1	*	CommonEvent	CommonEventContacts	CommonEventId	CommonEventId

[Top](#)

Entity Type Name - CommonEventContactHistory						
Description	The cont_name table contains information describing the contact of persons due to the occurrence of various alarms.					
Base Table Name	cont_name					
View Name	cmvCommonEventContactHistory					
Monitored	No					
				Properties		
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
CommonEventId	eid	int32	no	readOnly	Unique integer value which identifies this record.	
ContactDate	co_date	string(10)	yes	readOnly	Records date the individual named in the clname column was contacted about alarm.	
ContactName	clname	string(45)	yes	readOnly	Full name of the contacted individual.	
ContactPhone	clnum	string(14)	yes	readOnly	Telephone number of the contacted individual.	
ContactPriority	priority	int32	yes	readOnly	Indicates priority order in which person named within this record was to be contacted in the event of an alarm.	
ContactStreetAddress	cstr_add	string(36)	yes	readOnly	Full street address of the contacted individual.	
ContactTime	co_time	string(5)	yes	readOnly	Records time the individual named in clname column was contacted about the alarm.	
CreatedEmployeeId	upers	int32	yes	readOnly	Updating person	
CreatedTerminal	uterm	string(15)	yes	readOnly	Updating terminal	
CreatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp	
InformationScope	info_scope	string(12)	yes	readOnly	Indicates/limits availability of record contents to particular agencies.	
IsActive [default = false]	curent	boolean	no	readOnly	Status of this record. When T = current record, F = old record	
ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for this contacted individual and alarm.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Used by CAD to temporarily lock this record for update.	
RevisionEmployeeId	cpers	int32	no	readOnly	ID number creating person.	
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creation terminal	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp.	

[Top](#)

Entity Type Name - CommonEventGun						
Description	Supplemental table for guns that Informer will use to generate queries.					
Base Table Name	gun					
View Name	cmvCommonEventGun					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	

AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	DTS when record expires
Caliber	caliber	string(5)	yes	readWrite	Caliber of gun
 CommonEventId	eid	int32	no	readOnly	Eid of event
InformationScope	info_scope	string(12)	yes	readOnly	If not null, creating agency
IsActive [default = true]	curent	boolean	no	readOnly	T=record is curent, F=earlier record
IsAutoQueryDisabled	disableautoquery	boolean	yes	readWrite	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row number
Jurisdiction	juris	string(10)	yes	readWrite	Jurisdiction
LockingTerminal	updt_flag	string(15)	no	readOnly	Update flag
Make	make	string(50)	yes	readWrite	Make of gun
Model	model	string(50)	yes	readWrite	Model of gun
OperatorLicenseNumber	oln	string(50)	yes	readWrite	Operator license number of gun owner
OwnerDateOfBirth	dob	string(8)	yes	readWrite	Date of birth of gun owner
OwnerName	nme	string(100)	yes	readWrite	Name of gun owner
Remarks	remarks	string(20)	yes	readWrite	Remarks
RevisionEmployeeId	cpers	int32	no	readOnly	Empid of person creating record
RevisionNumber	rev_num	int32	no	readOnly	Revision number
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal creating record
RevisionTime	cdts	dateTimeOffset	no	readOnly	Dts when record was created
SerialNumber	serialnum	string(50)	yes	readWrite	Serial number of gun
UnitId	unid	string(10)	yes	readWrite	Unit id of officer creating supp info record
UpdatedEmployeeId	upers	int32	yes	readOnly	Empid of person updating record
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Dts of when record was updated

Associations

Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventGun	1	*	CommonEvent	CommonEventGuns	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventGunHistory						
Description	Supplemental table for guns that Informer will use to generate queries.					
Base Table Name	gun					
View Name	cmvCommonEventGunHistory					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	DTS when record expires	
Caliber	caliber	string(5)	yes	readOnly	Caliber of gun	
 CommonEventId	eid	int32	no	readOnly	Eid of event	
CreatedEmployeeId	upers	int32	yes	readOnly	Empid of person updating record	
CreatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record	
CreatedTime	udts	dateTimeOffset	yes	readOnly	Dts of when record was updated	
InformationScope	info_scope	string(12)	yes	readOnly	If not null, creating agency	
IsActive [default = false]	curent	boolean	no	readOnly	T=record is curent, F=earlier record	
IsAutoQueryDisabled	disableautoquery	boolean	yes	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row number	
Jurisdiction	juris	string(10)	yes	readOnly	Jurisdiction	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update flag	
Make	make	string(50)	yes	readOnly	Make of gun	
Model	model	string(50)	yes	readOnly	Model of gun	
OperatorLicenseNumber	oln	string(50)	yes	readOnly	Operator license number of gun owner	
OwnerDateOfBirth	dob	string(8)	yes	readOnly	Date of birth of gun owner	
OwnerName	nme	string(100)	yes	readOnly	Name of gun owner	
Remarks	remarks	string(20)	yes	readOnly	Remarks	
RevisionEmployeeId	cpers	int32	no	readOnly	Empid of person creating record	
 RevisionNumber	rev_num	int32	no	readOnly	Revision number	
RevisionTerminal	cterm	string(15)	no	readOnly	Terminal creating record	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Dts when record was created	
SerialNumber	serialnum	string(50)	yes	readOnly	Serial number of gun	
UnitId	unid	string(10)	yes	readOnly	Unit id of officer creating supp info record	

 [Top](#)

Entity Type Name - CommonEventHistory						
Description	The event table contains historical common event records. When a common_event record is updated, a snapshot of its previous contents are recorded in this table.					
Base Table Name	common_event_history					
View Name	cmvCommonEventHistory					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
Apartment	eapt	string(5)	yes	readOnly	Apartment number component of event's location	
Area	earea	string(40)	yes	readOnly	Area component of the event's location	
CommonEventCustom1	eccust1	string(50)	yes	readWrite	Common event custom column 1	
CommonEventCustom2	eccust2	string(50)	yes	readWrite	Common event custom column 2	
CommonEventCustom3	eccust3	string(50)	yes	readWrite	Common event custom column 3	
CommonEventCustom4	eccust4	string(50)	yes	readWrite	Common event custom column 4	
 CommonEventId	eid	int32	no	readOnly	System event number for the event.	
CommonplaceName	ecompl	string(80)	yes	readOnly	Commonplace name associated with the event's location	
CreatedDayOfWeek {hidden}	dow				Day of week on which the event was reported	
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of the person responsible for creating this history record	
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal on which this history record was created	
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp of this history row.	
CrossStreet1	xstreet1	string(34)	yes	readOnly	Feature name and type of one street which intersects the event's location	
CrossStreet2	xstreet2	string(34)	yes	readOnly	Feature name and type of one street which intersects the event's location	
DirectionPrefix	edirpre	string(2)	yes	readOnly	Direction prefix component of the event's location	
DirectionSuffix	edirsuf	string(2)	yes	readOnly	Direction suffix component of the event's location	
HasInformerLoiData [default = false]	loi_inf	boolean	no	readOnly	Loi_inf is used to identify if the selected event has related Informer information found via Informer searches. It is used to light the Location button or the Inf button on the Event dialogs in CAD.	

HasLoiData [default = false]	loi_event	boolean	no	readOnly	Loi_event is used to identify if the selected event has related events found via a DBServer search of the event tables. It is used to light the Location button or the Ev button on the Event dialogs in CAD.
HasSpecialSituationLoiData [default = false]	loi_specsit	boolean	no	readOnly	Loi_specsit is used to identify if the selected event has related special situation data found via a DBServer search of the special situation table. It is used to light the Location button or the SS button on the Event dialogs in CAD.
IsLocationVerified	loc_ver	boolean	no	readOnly	The location verified status for the event. T means the location was successfully verified. F means the location was not verified.
Latitude	latitude	double	no	readOnly	Latitude. Decimal degrees range [-90.0, 90.0] (+ North, -South)
Location	elocation	string(450)	no	readOnly	Event location string
Location1	eloc_fld1	string(5)	yes	readOnly	Generic location field
Location2	eloc_fld2	string(5)	yes	readOnly	Generic location field
Location3	eloc_fld3	string(5)	yes	readOnly	Generic location field
Location4	eloc_fld4	string(5)	yes	readOnly	Generic location field
LocationComment	loc_com	string(80)	yes	readOnly	Location comments.
Longitude	longitude	double	no	readOnly	Longitude. Decimal degrees range [-180.0, 180.0] (+ East, -West)
MapLevels	maplevs	string(200)	yes	readOnly	Map level(s) assigned to the event due to special address as location
MapSegmentId	fea_mslink	int32	yes	readOnly	Source feature map link
Municipality	emun	string(40)	yes	readOnly	Municipality component of the event's location
ParseType [default = -1]	parse_type	int32	no	readOnly	Parse type. Indicates how the location was parsed. -1= unknown, 0= street, 1= intersection, 2= commonplace, 3= alarm, 4= X,Y location.
PatientName	patient	string(45)	yes	readOnly	Patient's name if this event is a scheduled event
ProQACadCaseId	pcad_case_num	string(12)	yes	readOnly	CAD case number generated for ProQA case
RevisionEmployeeId	rev_pers	int32	no	readOnly	The person who created this revision. The rev_pers column is copied from the common_event upers column. This column is shown as opers in the event view.
 RevisionNumber	rev_num	int32	no	readOnly	Record revision number.
RevisionSeconds {hidden}	rev_sec				The creation timestamp, in epoch seconds, for this revision. The rev_sec column is copied from the common_event usec column. This column is shown as csec in the event view.
RevisionTerminal	rev_term	string(15)	no	readOnly	The terminal that created this revision. The rev_term column is copied from the common_event uterm column. This column is shown as cterm in the event view.
RevisionTime	rev_dts	dateTimeOffset	no	readOnly	The creation timestamp for this revision. The rev_dts column is copied from the common_event udtls column. This column is shown as cdtls in the event view.
StreetName	efeanme	string(30)	yes	readOnly	Feature name component (street name) of the event's location
StreetNameHash	hash	int32	yes	readOnly	The hash value of the address. The hash uses the direction prefix, street name, street type, and direction suffix for street addresses. For intersections, it uses those values from both streets.
StreetNumber	estnum	string(15)	yes	readOnly	Street number (house number) component of the event's location
StreetType	efeatyp	string(4)	yes	readOnly	Feature type component of the event's location
SystemEsz [default = -1]	s_esz	int32	yes	readOnly	Stores the system esz value from the verified event location.
XCoordinate	x_cord	int32	no	readOnly	X map coordinate for the event's location
YCoordinate	y_cord	int32	no	readOnly	Y map coordinate for the event's location
ZipCode	zip	string(10)	yes	readOnly	Zip Code. Queried by Firelink Interface application.

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventHistory	1	*	CommonEvent	CommonEventHistories	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventIncidentState							
Description	The incident_tracking table contains incident command state information which is related to the event and is added using the Incident Command Tracking form and is displayed on the Event Supplement Form in I/CAD.						
Base Table Name	incident_tracking						
View Name	cmvCommonEventIncidentState						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most recent version of the record, an (F) if it is an older version.		
IsUserGenerated	user_gen	boolean	no	readWrite	Indicates if the record was generated by the user or the system. (T) if this record was generated by the user (state button click), or an (F) if it was generated by the system (timer expired or dialog closed with active timer).		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the property information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated the record.		
MaxStateTime	timer_value	double	yes	readWrite	Timer Value. This column stores the value of the timer in minutes.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the incident state.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the personnel identification number of the person who created the record.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal from which the record was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) at which the record was created.		
StateAchievedSeconds {hidden}	state_sec				Time stamp at which state was achieved, stored in epoch seconds		
StateAchievedTime	state_dts	dateTimeOffset	yes	readWrite	Date/Time Stamp. This column contains the date/time (yyyymmddhhmmss) at which state was achieved.		
StateDesc	state_desc	string(200)	yes	readWrite	State Description. This column contains a description of the incident state.		
StateSetName	set_name	string(50)	yes	readWrite	Set Name. This column contains the name that describes the set of incident states.		
UpdatedEmployeeId	upers	int32	yes	readOnly	Updating Person. The ID of the person updating the event.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. The terminal from which the record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventIncidentState	1	*	CommonEvent	CommonEventIncidentStates	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventIncidentStateHist						
Description	The incident_tracking table contains incident command state information which is related to the event and is added using the Incident Command Tracking form and is displayed on the Event Supplement Form in I/CAD.					
Base Table Name	incident_tracking					
View Name	cmvCommonEventIncidentStateHis					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	yes	readOnly	Updating Person. The ID of the person updating the event.	
CreatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. The terminal from which the record was updated.	

CreatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time (yyyymmddhhmmss) at which the record was last updated.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most recent version of the record, an (F) if it is an older version.
IsUserGenerated	user_gen	boolean	no	readOnly	Indicates if the record was generated by the user or the system. (T) if this record was generated by the user (state button click), or an (F) if it was generated by the system (timer expired or dialog closed with active timer).
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the property information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated the record.
MaxStateTime	timer_value	double	yes	readOnly	Timer Value. This column stores the value of the timer in minutes.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the incident state.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the personnel identification number of the person who created the record.
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal from which the record was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) at which the record was created.
StateAchievedSeconds {hidden}	state_sec				Time stamp at which state was achieved, stored in epoch seconds
StateAchievedTime	state_dts	dateTimeOffset	yes	readOnly	Date/Time Stamp. This column contains the date/time (yyyymmddhhmmss) at which state was achieved.
StateDesc	state_desc	string(20)	yes	readOnly	State Description. This column contains a description of the incident state.
StateSetName	set_name	string(50)	yes	readOnly	Set Name. This column contains the name that describes the set of incident states.

 [Top](#)

Entity Type Name - CommonEventIqaStep							
Description	The iqa_log table contains audit logs of I/QA protocol sessions.						
Base Table Name	iqa_log						
View Name	cmvCommonEventIqaStep						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	ID of event with which this record is associated		
InformationScope	info_scope	string(12)	yes	readOnly	Indicates/limits availability of record contents to particular agencies.		
IsActive [default = true]	curent	boolean	no	readOnly	Status of this record. T when current, F when old.		
 ItemNumber	row_num	int32	no	readOnly	Sequence number of this step of the protocol for this event.		
LockingTerminal [default = NULLTERM]	updt_flag	string(15)	no	readOnly	Used by CAD to temporarily lock this record for update.		
RevisionEmployeeId	cpers	int32	no	readOnly	ID number of creating person		
RevisionNumber	rev_num	int32	no	readOnly	The revision number for the row.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creation terminal		
RevisionTime	cdts	dateTimeOffset	no	readOnly	The date-time stamp of when the record was added to the database		
StepAction	action	string(20)	no	readWrite	The type of action taken at this step.		
StepPerformedTime	ats	string(16)	yes	readWrite	The time at which the step was performed.		
StepResult	rslt	string(50)	yes	readWrite	The result of the step - may be the answer to the question, or DONE or SKIPPED, etc.		
StepText	text	string(240)	yes	readWrite	The text of the step. Either the text of the question, instructions, or command.		
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of updating person.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating terminal.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventIqaStep	1	*	CommonEvent	CommonEventIqaSteps	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventIqaStepHistory					
Description	The iqa_log table contains audit logs of I/QA protocol sessions.				
Base Table Name	iqa_log				
View Name	cmvCommonEventIqaStepHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 CommonEventId	eid	int32	no	readOnly	ID of event with which this record is associated
CreatedEmployeeId	upers	int32	no	readOnly	ID of updating person.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating terminal.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update date/time stamp
InformationScope	info_scope	string(12)	yes	readOnly	Indicates/limits availability of record contents to particular agencies.
IsActive [default = false]	curent	boolean	no	readOnly	Status of this record. T when current, F when old.
 ItemNumber	row_num	int32	no	readOnly	Sequence number of this step of the protocol for this event.
LockingTerminal [default = NULLTERM]	updt_flag	string(15)	no	readOnly	Used by CAD to temporarily lock this record for update.
RevisionEmployeeId	cpers	int32	no	readOnly	ID number of creating person
 RevisionNumber	rev_num	int32	no	readOnly	The revision number for the row.
RevisionTerminal	cterm	string(15)	no	readOnly	Creation terminal
RevisionTime	cdts	dateTimeOffset	no	readOnly	The date-time stamp of when the record was added to the database
StepAction	action	string(20)	no	readOnly	The type of action taken at this step.
StepPerformedTime	ats	string(16)	yes	readOnly	The time at which the step was performed.
StepResult	rslt	string(50)	yes	readOnly	The result of the step - may be the answer to the question, or DONE or SKIPPED, etc.
StepText	text	string(240)	yes	readOnly	The text of the step. Either the text of the question, instructions, or command.

 [Top](#)

Entity Type Name - CommonEventLvSession					
Description	This table stores location verify (LV) choices presented to the user during event creation. When the user enters an address in CAD, CAD may display location verify dialogs, asking the user for more information. CAD stores the address originally submitted by the user, plus the list of location verify addresses offered by CAD. If a user modifies an event's location on the main event information dialog, CAD will record the subsequent LV exchanges as a separate LV session. This table is only populated if you turn on the EnableLVSessionLog parameter in the cad GeneralDetails parameter list. Added for CR1-4HLEEQ.				
Base Table Name	lv_session				
View Name	cmvCommonEventLvSession				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation timestamp
CreatedEmployeeId	cpers	int32	no	readOnly	Employee id of the person in this location verify session.

CreatedTerminal	cterm	string(15)	no	readOnly	Creation terminal		
CommonEventId	eid	int32	no	readOnly	Event id		
SessionData	session_data	string(Max)	no	readOnly	Location verify session data. For Intergraph Development use only.		
 SessionId	session_id	guid	no	readOnly	Unique session id		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventLvSession	1	*	CommonEvent	CommonEventLvSessions	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventPerson							
Description	The perso table contains person information which is related to the event and is displayed, added, and updated on the Event Supplement Form in I/CAD. Column 2 is user- configurable and may be added to or removed as necessary.						
Base Table Name	perso						
View Name	cmvCommonEventPerson						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Age	age	int32	yes	readWrite	This column contains the age of the person related to the event.		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	cid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
DateOfBirth	dob	string(10)	yes	readWrite	Date Of Birth. The date that the person related to the event was born.		
EyeColor	eye	string(3)	yes	readWrite	Eye color of the person related the event.		
HairColor	hair	string(3)	yes	readWrite	Hair color of the person related to the event.		
Height	height	int32	yes	readWrite	Height of the person related to the event.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LicenseNumber	oln	string(20)	yes	readWrite	Operator License Number		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Name	nme	string(50)	yes	readWrite	Name of the person related to the event.		
Race	race	string(1)	yes	readWrite	Race of the person related to the event.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyymmddhhmmss) at which the record was created.		
Sex	sex	string(1)	yes	readWrite	Sex of the person related to the event.		
SocialSecurityNumber	soc	string(9)	yes	readWrite	Social security number		
State	state	string(2)	yes	readWrite	State of the Operator License Number		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyymmddhhmmss) at which the record was last updated.		
Weight	weight	int32	yes	readWrite	Weight of the person related to the event.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventPerson	1	*	CommonEvent	CommonEventPeople	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventPersonHistory					
Description	The perso table contains person information which is related to the event and is displayed, added, and updated on the Event Supplement Form in I/CAD. Column 2 is user- configurable and may be added to or removed as necessary.				
Base Table Name	perso				
View Name	cmvCommonEventPersonHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
Age	age	int32	yes	readOnly	This column contains the age of the person related to the event.
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyymmddhhmmss) at which the record was last updated.
DateOfBirth	dob	string(10)	yes	readOnly	Date Of Birth. The date that the person related to the event was born.
EyeColor	eye	string(3)	yes	readOnly	Eye color of the person related the event.
HairColor	hair	string(3)	yes	readOnly	Hair color of the person related to the event.
Height	height	int32	yes	readOnly	Height of the person related to the event.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LicenseNumber	oln	string(20)	yes	readOnly	Operator License Number
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Name	nme	string(50)	yes	readOnly	Name of the person related to the event.
Race	race	string(1)	yes	readOnly	Race of the person related to the event.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyymmddhhmmss) at which the record was created.
Sex	sex	string(1)	yes	readOnly	Sex of the person related to the event.
SocialSecurityNumber	soc	string(9)	yes	readOnly	Social security number
State	state	string(2)	yes	readOnly	State of the Operator License Number
UnitId	unid	string(10)	yes	readOnly	The unit related to the event
Weight	weight	int32	yes	readOnly	Weight of the person related to the event.

[Top](#)

Entity Type Name - CommonEventProperty							
Description	This table contains property info related to the event and is displayed, added, and updated on the Supplemental Information Form in I/CAD. Col 2 is user-configurable an may be added to or removed as necessary.						
Base Table Name	prop						
View Name	cmvCommonEventProperty						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most recent version of the record, an (F) if it is an older version.		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the property information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated the record.		
MonetaryValue	value	string(10)	yes	readWrite	Monetary value of the property item.		
PropertyDesc	item	string(10)	yes	readWrite	Item Description. This column contains a description of the item not covered by other columns.		
Remarks	remarks	string(20)	yes	readWrite	Remarks about the Property. This column stores remarks regarding items of property.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the the personnel identification number of the person who created the record.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal from which the record was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) at which the record was created.		
SerialNumber	serialnum	string(20)	yes	readWrite	Serial Number of the Item.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Updating Person. The ID of the person updating the event.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. The terminal from which the record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventProperty	1	*	CommonEvent	CommonEventProperties	CommonEventId	CommonEventId

[Top](#)

Entity Type Name - CommonEventPropertyHistory						
Description	This table contains property info related to the event and is displayed, added, and updated on the Supplemental Information Form in I/CAD. Col 2 is user-configurable an may be added to or removed as necessary.					
Base Table Name	prop					
View Name	cmvCommonEventPropertyHistory					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Updating Person. The ID of the person updating the event.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. The terminal from which the record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most recent version of the record, an (F) if it is an older version.	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the property information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated the record.	
MonetaryValue	value	string(10)	yes	readOnly	Monetary value of the property item.	
PropertyDesc	item	string(10)	yes	readOnly	Item Description. This column contains a description of the item not covered by other columns.	
Remarks	remarks	string(20)	yes	readOnly	Remarks about the Property. This column stores remarks regarding items of property.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the the personnel identification number of the person who created the record.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal from which the record was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) at which the record was created.	
SerialNumber	serialnum	string(20)	yes	readOnly	Serial Number of the Item.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

[Top](#)

Entity Type Name - CommonEventSupplement10					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Base Table Name	supp_table10				
View Name	cmvCommonEventSupplement10				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
UnitId	unid	string(10)	yes	readWrite	The unit related to the event
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
Associations					

Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement10	1	*	CommonEvent	CommonEventSupplement10s	CommonEventId	CommonEventId

[Top](#)

Entity Type Name - CommonEventSupplement10History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS					
Base Table Name	supp_table10					
View Name	cmvCommonEventSupplement10Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

[Top](#)

Entity Type Name - CommonEventSupplement11							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS						
Base Table Name	supp_table11						
View Name	cmvCommonEventSupplement11						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement11	1	*	CommonEvent	CommonEventSupplement11s	CommonEventId	CommonEventId

[Top](#)

Entity Type Name - CommonEventSupplement11History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table11					
View Name	cmvCommonEventSupplement11Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

[Top](#)

Entity Type Name - CommonEventSupplement12						
--	--	--	--	--	--	--

Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS						
Base Table Name	supp_table12						
View Name	cmvCommonEventSupplement12						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement12	1	*	CommonEvent	CommonEventSupplement12s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement12History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table12					
View Name	cmvCommonEventSupplement12Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

 [Top](#)

Entity Type Name - CommonEventSupplement13								
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS							
Base Table Name	supp_table13							
View Name	cmvCommonEventSupplement13							
Monitored	No							
Properties								
Property Name	Base Column	Data Type	NULL	Access Type	Description			
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.			
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.			
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information			
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).			
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.			
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.			
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.			
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.			
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.			
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.			
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.			
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyyymmddhhmmss) at which the record was created.			
UnitId	unid	string(10)	yes	readWrite	The unit related to the event			
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.			
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.			
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyyymmddhhmmss) at which the record was last updated.			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement13		1	*	CommonEvent	CommonEventSupplement1s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement13History							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NWIAS						
Base Table Name	supp_table13						
View Name	cmvCommonEventSupplement13Hist						
Monitored	No						

Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
UnitId	unid	string(10)	yes	readOnly	The unit related to the event

 [Top](#)

Entity Type Name - CommonEventSupplement14							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS						
Base Table Name	supp_table14						
View Name	cmvCommonEventSupplement14						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement14	1	*	CommonEvent	CommonEventSupplement2s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement14History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table14					
View Name	cmvCommonEventSupplement14Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

 [Top](#)

Entity Type Name - CommonEventSupplement15						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table15					
View Name	cmvCommonEventSupplement15					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	

IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).			
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.			
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.			
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.			
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.			
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.			
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.			
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.			
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.			
UnitId	unid	string(10)	yes	readWrite	The unit related to the event			
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.			
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.			
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement15		1	*	CommonEvent	CommonEventSupplement3s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement15History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table15					
View Name	cmvCommonEventSupplement15Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

 [Top](#)

Entity Type Name - CommonEventSupplement16							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS						
Base Table Name	supp_table16						
View Name	cmvCommonEventSupplement16						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement16	1	*	CommonEvent	CommonEventSupplement4s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement16History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table16					
View Name	cmvCommonEventSupplement16Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	

IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
UnitId	unid	string(10)	yes	readOnly	The unit related to the event

 [Top](#)

Entity Type Name - CommonEventSupplement17							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS						
Base Table Name	supp_table17						
View Name	cmvCommonEventSupplement17						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement17	1	*	CommonEvent	CommonEventSupplement5s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement17History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table17					
View Name	cmvCommonEventSupplement17Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

 [Top](#)

Entity Type Name - CommonEventSupplement18						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table18					
View Name	cmvCommonEventSupplement18					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = true]	curent	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	

UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement18	1	*	CommonEvent	CommonEventSupplements6s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement18History					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Base Table Name	supp_table18				
View Name	cmvCommonEventSupplement18Hist				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
UnitId	unid	string(10)	yes	readOnly	The unit related to the event

 [Top](#)

Entity Type Name - CommonEventSupplement19							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS						
Base Table Name	supp_table19						
View Name	cmvCommonEventSupplement19						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement19	1	*	CommonEvent	CommonEventSupplement7s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement19History					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Base Table Name	supp_table19				
View Name	cmvCommonEventSupplement19Hist				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.

UnitId	unid	string(10)	yes	readOnly	The unit related to the event
--------	------	------------	-----	----------	-------------------------------

 [Top](#)

Entity Type Name - CommonEventSupplement20							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS						
Base Table Name	supp_table20						
View Name	cmvCommonEventSupplement20						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement20	1	*	CommonEvent	CommonEventSupplements	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement20History						
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS					
Base Table Name	supp_table20					
View Name	cmvCommonEventSupplement20Hist					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.	
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.	
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.	
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.	
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.	
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information	
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).	
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.	
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.	
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.	
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.	
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.	
 RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.	
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.	
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.	
UnitId	unid	string(10)	yes	readOnly	The unit related to the event	

 [Top](#)

Entity Type Name - CommonEventSupplement9							
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS						
Base Table Name	supp_table9						
View Name	cmvCommonEventSupplement9						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
 CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information		
IsActive [default = true]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.		
Remarks	remarks	string(20)	yes	readWrite	Remarks. This column contains descriptive remarks about the person related to the event.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update Person. ID of the person updating this record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. Terminal from which this record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventSupplement9	1	*	CommonEvent	CommonEventSupplement9s	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - CommonEventSupplement9History					
Description	This is a generic pre-defined supplemental table. You can add any additional columns that are needed. CR 1-5NW1AS				
Base Table Name	supp_table9				
View Name	cmvCommonEventSupplement9Histo				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for CAD use only. It is generated by using the numbr table row with num_id = 0.
CreatedEmployeeId	upers	int32	no	readOnly	Update Person. ID of the person updating this record.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. Terminal from which this record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which the record was last updated.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information
IsActive [default = false]	current	boolean	no	readOnly	Current Record Indicator. The current flag contains a (T) if this is the most current version of the record, or an (F) if it is an older record. Only one record for any row number should be set to (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the person information will be displayed.
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column stores the nodename of the terminal which updated this record.
Remarks	remarks	string(20)	yes	readOnly	Remarks. This column contains descriptive remarks about the person related to the event.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification of the person who created the event.
RevisionNumber	rev_num	int32	no	readOnly	The revision number that is incremented when a row is updated.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The node- name of the terminal from which the event was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) at which the record was created.
UnitId	unid	string(10)	yes	readOnly	The unit related to the event

[Top](#)

Entity Type Name - CommonEventVehicle							
Description	This table contains vehicle information which is related to the event and is displayed, added, and updated on the Supplemental Information Form in I/CAD.						
Base Table Name	vehic						
View Name	cmvCommonEventVehicle						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.		
Color	vehic_color	string(7)	yes	readWrite	Vehicle Color. This column contains the color of the vehicle.		
CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id=0.		
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information.		
IsActive [default = true]	current	boolean	no	readOnly	Current Flag. This column contains either a (T) or an (F) to indicate whether the record is the most current version of the event. Only one record for any given event in the event table should have flag = (T).		
IsAutoQueryDisabled	disableautoquery	boolean	no	readWrite	T= Do not run auto query against this record. Used by Informer.		
ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.		
LicensePlateNumber	license	string(8)	yes	readWrite	License Plate Number.		
LicenseType	license_type	string(10)	yes	readWrite	License Type. This column contains the type of vehicle license.		
LicenseYear	license_yr	string(4)	yes	readWrite	License Year. This column contains the year of the license.		
LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column contains the nodename of the terminal initiating an update.		
Make	make	string(5)	yes	readWrite	Make of the Vehicle.		
Model	model	string(5)	yes	readWrite	Model of the Vehicle.		
ModelYear	model_year	int32	yes	readWrite	Year of the Vehicle.		
Remarks	remarks	string(20)	yes	readWrite	This column stores the remarks about the vehicle.		
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification number of the person who created the event.		
RevisionNumber	rev_num	int32	no	readOnly	Revision Number. This column contains the revision number of the record. Since no data is ever deleted from the database, it is used to provide an audit trail to trace the evolution of the event.		
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. This column contains the nodename of the terminal from which this record was created.		
RevisionTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.		
State	state	string(4)	yes	readWrite	State Register of the Vehicle.		
UnitId	unid	string(10)	yes	readWrite	The unit related to the event		
UpdatedEmployeeId	upers	int32	yes	readOnly	Updating Person. This column contains the employee id of the person who is updating the event.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating Terminal. This column contains the nodename of the terminal from which the record was updated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which this record was last updated.		
Vin	vin	string(25)	yes	readWrite	Vehicle Identification Number		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CommonEventVehicle	1	*	CommonEvent	CommonEventVehicles	CommonEventId	CommonEventId
CommonEventVehicle	TowRequestVehicle	1	*	CommonEventVehicle	TowRequestVehicles	CommonEventId, ItemNumber	CommonEventId, CommonEventVehicleItemNumber

[Top](#)

Entity Type Name - CommonEventVehicleHistory					
Description	This table contains vehicle information which is related to the event and is displayed, added, and updated on the Supplemental Information Form in I/CAD.				
Base Table Name	vehic				
View Name	cmvCommonEventVehicleHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AvailabilityTime	supp_avail_dts	dateTimeOffset	no	readOnly	After this date, the supplemental record will not be returned by LOI searches.
Color	vehic_color	string(7)	yes	readOnly	Vehicle Color. This column contains the color of the vehicle.
CommonEventId	eid	int32	no	readOnly	Event Identification Number. This is a unique number for I/CAD use only. It is generated by using the numbr table row with num_id=0.
CreatedEmployeeId	upers	int32	no	readOnly	Updating Person. This column contains the employee id of the person who is updating the event.
CreatedTerminal	uterm	string(15)	no	readOnly	Updating Terminal. This column contains the nodename of the terminal from which the record was updated.
CreatedTime	udts	dateTimeOffset	no	readOnly	Update Date/Time Stamp. This column contains the date/ time stamp (yyyymmddhhmmss) at which this record was last updated.
InformationScope	info_scope	string(12)	yes	readOnly	Information Scope. This column contains the scope of the supplemental information.
IsActive [default = false]	current	boolean	no	readOnly	Current Flag. This column contains either a (T) or an (F) to indicate whether the record is the most current version of the event. Only one record for any given event in the event table should have flag = (T).
IsAutoQueryDisabled	disableautoquery	boolean	no	readOnly	T= Do not run auto query against this record. Used by Informer.
ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.
LicensePlateNumber	license	string(8)	yes	readOnly	License Plate Number.
LicenseType	license_type	string(10)	yes	readOnly	License Type. This column contains the type of vehicle license.
LicenseYear	license_yr	string(4)	yes	readOnly	License Year. This column contains the year of the license.

LockingTerminal	updt_flag	string(15)	no	readOnly	Update Flag. This column contains the nodename of the terminal initiating an update.
Make	make	string(5)	yes	readOnly	Make of the Vehicle.
Model	model	string(5)	yes	readOnly	Model of the Vehicle.
ModelYear	model_year	int32	yes	readOnly	Year of the Vehicle.
Remarks	remarks	string(20)	yes	readOnly	This column stores the remarks about the vehicle.
RevisionEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification number of the person who created the event.
 RevisionNumber	rev_num	int32	no	readOnly	Revision Number. This column contains the revision number of the record. Since no data is ever deleted from the database, it is used to provide an audit trail to trace the evolution of the event.
RevisionTerminal	cterm	string(15)	no	readOnly	Creating Terminal. This column contains the nodename of the terminal from which this record was created.
RevisionTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.
State	state	string(4)	yes	readOnly	State Register of the Vehicle.
UnitId	unid	string(10)	yes	readOnly	The unit related to the event
Vin	vin	string(25)	yes	readOnly	Vehicle Identification Number

 [Top](#)

Entity Type Name - CommonPlaceContact							
Description	The CADDDB spad_cont_name table contains information describing the person to contact with respect to a special address, commonplace name, or alarm.						
Base Table Name	spad_cont_name						
View Name	cmvCommonPlaceContact						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ContactDate	co_date	string(10)	yes	readOnly	Records date the individual named in the clname column was contacted about the alarm.		
ContactName	clname	string(45)	yes	readOnly	Name of the individual to contact		
ContactPhone	clrnum	string(14)	yes	readOnly	Telephone number of the individual to contact		
ContactPriority	priority	int32	yes	readOnly	Indicates priority order in which individual named within this record is to be contacted		
ContactStreetAddress	cstr_add	string(36)	yes	readOnly	Full street address of the individual to contact		
ContactTime	co_time	string(5)	yes	readOnly	Records time the individual named in clname column was contacted about the alarm.		
DataSource	data_source	string(5)	yes	readOnly	Data source		
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for the individual to contact		
 MapCommonPlaceName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
OriginTable {hidden}	origin_table				Table name associated with this contact		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapCommonPlace	CommonPlaceContact	1	*	MapCommonPlace	CommonPlaceContacts	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName

 [Top](#)

Entity Type Name - CommonPlacePerson							
Description	The CADDDB perso table contains person information which is related to the special address, commonplace name, or alarm.						
Base Table Name	spad_perso						
View Name	cmvCommonPlacePerson						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Age	age	int32	yes	readOnly	Age of the person related to the special address		
DateOfBirth	dob	string(10)	yes	readOnly	Date of birth of the person related to the special address		
EyeColor	eye	string(3)	yes	readOnly	Eye color of the person related to the special address		
HairColor	hair	string(3)	yes	readOnly	Hair color of the person related to the special address		
Height	height	int32	yes	readOnly	Height of the person related to the special address		
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for this person		
LicenseNumber	oln	string(20)	yes	readOnly	Operator license number related to the special address		
 MapCommonPlaceName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
Name	nme	string(50)	yes	readOnly	Name of the person related to the special address		
OriginTable {hidden}	origin_table				Table name associated with this person		
Race	race	string(1)	yes	readOnly	Race of the person related to the special address		
Remarks	remarks	string(20)	yes	readOnly	Descriptive remarks about the person related to the special address		
Sex	sex	string(1)	yes	readOnly	Sex of the person related to the special address		
State	state	string(2)	yes	readOnly	State of the operator license number		
Weight	weight	int32	yes	readOnly	Weight of the person related to the special address		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapCommonPlace	CommonPlacePerson	1	*	MapCommonPlace	CommonPlacePeople	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName

 [Top](#)

Entity Type Name - CommonPlaceProperty					
Description	This table contains property information related to special address, commonplace name, or alarm.				
Base Table Name	spad_propt				
View Name	cmvCommonPlaceProperty				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for the property

 MapCommonPlaceName	origin_id	string(80)	no		readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.	
 MapSpecialAddressId	spad_mslink	int32	no		readOnly	The associated special address mslink value	
MonetaryValue	value	string(10)	yes		readOnly	Monetary value of the property item	
OriginTable {hidden}	origin_table					Table name associated with the item	
PropertyDesc	item	string(10)	yes		readOnly	Description of the item	
Remarks	remarks	string(20)	yes		readOnly	Remarks about the property item	
SerialNumber	serialnum	string(20)	yes		readOnly	Serial number of the item	
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapCommonPlace	CommonPlaceProperty	1	*	MapCommonPlace	CommonPlaceProperties	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName

 [Top](#)

Entity Type Name - CommonPlaceVehicle							
Description	This table contains vehicle information which is related to the special address, commonplace name, or alarm.						
Base Table Name	spad_vehic						
View Name	cmvCommonPlaceVehicle						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Color	vehic_color	string(7)	yes	readOnly	Vehicle Color. This column contains the color of the vehicle.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.		
LicensePlateNumber	license	string(8)	yes	readOnly	License Plate Number.		
LicenseType	license_type	string(10)	yes	readOnly	License Type. This column contains the type of vehicle license.		
LicenseYear	license_yr	string(4)	yes	readOnly	License Year. This column contains the year of the license.		
Make	make	string(5)	yes	readOnly	Make of the Vehicle.		
 MapCommonPlaceName	origin_id	string(80)	no	readOnly	For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
Model	model	string(5)	yes	readOnly	Model of the Vehicle.		
ModelYear	model_year	int32	yes	readOnly	Year of the Vehicle.		
OriginTable {hidden}	origin_table				Table name associated with this vehicle		
Remarks	remarks	string(20)	yes	readOnly	This column stores the remarks about the vehicle.		
State	state	string(4)	yes	readOnly	State Register of the Vehicle.		
Vin	vin	string(25)	yes	readOnly	Vehicle Identification Number		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapCommonPlace	CommonPlaceVehicle	1	*	MapCommonPlace	CommonPlaceVehicles	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName

 [Top](#)

Entity Type Name - CrossReference							
Description	This table is used to store information for cross referencing events and case numbers.						
Base Table Name	xref						
View Name	cmvCrossReference						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedTerminal	term	string(15)	no	readOnly	Terminal Node Identifier. This column contains the name of the terminal node where the case number record is created.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp. This column contains the current date/time stamp that is set to the date and time when the record was created.		
 CrossReferenceId	unique_id	guid	no	readOnly	Uniquely identifies a row		
CrossReferenceType	x_type	string(1)	no	readOnly	Type of Cross Reference Row. X = Cross reference, P = Primary, D = Duplicate, M = Master, O = Outage (InService TA sets x_type to O for events that are cancelled and rolled up into another event)		
DeletedId {hidden}	delete_id				A value that uniquely identifies deleted rows		
IsActive {hidden}	curent				Current Record Indicator Flag. This column contains the current record indicator flag. (T) denotes current record whereas (F) indicates an older record. (O) is used to temporarily lock the record.		
PrimaryCommonEventId	p_eid	int32	no	readOnly	Primary Event Number.		
PrimaryCommonEventStatus	p_type	string(1)	yes	readOnly	Primary Event Type. A=Active, C=Cancelled, R is used for round-trip scheduled events to cross-reference origin and return trip events		
SecondaryCommonEventId	s_eid	int32	no	readOnly	Secondary Event Number.		
SecondaryCommonEventStatus	s_type	string(1)	yes	readOnly	Secondary Event Type. A=Active, C=Cancelled, R is used for round-trip scheduled events to cross-reference origin and return trip events		
UpdatedEmployeeId	pers	int32	no	readOnly	Operator Identifier. This column contains the unique ID of the operator who last updated the case number record.		
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp. This column contains the update date/time stamp that records the date and time when this record was created.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	CrossReference	1	*	PrimaryCommonEvent	PrimaryCrossReferences	CommonEventId	PrimaryCommonEventId
CommonEvent	CrossReference	1	*	SecondaryCommonEvent	SecondaryCrossReferences	CommonEventId	SecondaryCommonEventId

 [Top](#)

Entity Type Name - DefinedCrew					
Description	This table contains crew definitions.				
Base Table Name	def_station_crew				
View Name	cmvDefinedCrew				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyId	ag_id	string(9)	no	readOnly	Agency ID for which the crew is defined.
 CrewId	crew_id	string(30)	no	readOnly	Crew ID.

DispatchGroup	dgroup	string(5)	yes	readOnly	Dispatch Group for which the crew is defined.		
RestrictionType	restriction_type	string(5)	yes	readOnly	Restriction Type. Values are <NULL>, ID, TYPE.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedCrew	ActiveCrew	1	0..1	DefinedCrew	ActiveCrew	CrewId	CrewId
AgencyDispatchGroup	DefinedCrew	0..1	*	AgencyDispatchGroup	DefinedCrews	AgencyId, DispatchGroup	AgencyId, DispatchGroup
DefinedCrew	DefinedCrewRestriction	1	*	DefinedCrew	DefinedCrewRestrictions	CrewId	CrewId
DefinedCrew	LineupCrew	1	*	DefinedCrew	LineupCrews	CrewId	CrewId

[Top](#)

Entity Type Name - DefinedCrewRestriction							
Description	This table contains crew restrictions. It is managed in exactly the same manner as the def_station_crew table and works in conjunction with that table.						
Base Table Name	def_station_crew_restriction						
View Name	cmvDefinedCrewRestriction						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 CrewId	crew_id	string(30)	no	readOnly	Crew ID. This column links back to the crew_id column in the def_station_crew table.		
 Restriction	restriction	string(10)	no	readOnly	Crew Restriction. This may be a unit id or a unit type based on the crew's restriction_type attribute.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedCrew	DefinedCrewRestriction	1	*	DefinedCrew	DefinedCrewRestrictions	CrewId	CrewId

[Top](#)

Entity Type Name - DefinedDevice							
Description	Def_device stores the defined devices for units, vehicles and people. Defined devices may include MDTs, GPS devices such as AVLs, vehicle-mounted radios (radio aliases), and HT radios. CR 1-6PGD42: PLT						
Base Table Name	def_device						
View Name	cmvDefinedDevice						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	yes	readOnly	Agency ID. If owner = 3, the agency that owns this device, else null.		
Description	description	string(50)	yes	readOnly	Device description		
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device		
 DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For HT radios, this may be the radio id. This may also be a GUID or UUID received from an external system		
 DeviceSubtypeCode	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
 DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name		
EmployeeId	empid	int32	yes	readOnly	If owner = 1, employee that owns this device, else null		
GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
IsTrackable	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForOwner	tdevice_for_owner	boolean	no	readOnly	Specifies if this device is used as the tracking device for the owner. 1= True, 0 = False		
Owner	owner	int16	no	readOnly	Owner. 0 = unit, 1 = employee, 2 = Vehicle, 3 = Agency		
UnitId	unid	string(10)	yes	readOnly	If owner = 0, the unit that owns this device, else null		
VehicleId	carid	string(12)	yes	readOnly	If owner = 2, vehicle that owns this device, else null		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	DefinedDevice	0..1	*	Agency	DefinedDevices	AgencyId	AgencyId
DefinedEmployee	DefinedDevice	0..1	*	DefinedEmployee	DefinedDevices	EmployeeId	EmployeeId
DefinedUnit	DefinedDevice	0..1	*	DefinedUnit	DefinedDevices	UnitId	UnitId
DefinedVehicle	DefinedDevice	0..1	*	DefinedVehicle	DefinedDevices	VehicleId	VehicleId
ValidDevice	DefinedDevice	1	0..1	ValidDevice	DefinedDevice	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode

[Top](#)

Entity Type Name - DefinedEmployee					
Description	The persl table holds a record for each employee who requires access to the I/CAD product or is listed as an employee of a unit. Most of this information is set in CADDDBM. I/CAD updates the app_type, logged_on, ldts, lodts and term columns when the user logs on. The psrwd and pass_date columns are updated when the user changes his/her password.				
Base Table Name	persl				
View Name	cmvDefinedEmployee				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyId	ag_id	string(9)	no	readOnly	Agency ID. The agency ID in the personel table shows the agency for which the employee works (Police, Fire). The info pertaining to the agency is stored in the agenc table. The persl and agenc tables are linked together by the agency ID.
AlternateId	emp_num	string(16)	yes	readOnly	This is an optional employee identifier that can contain letters as well as numbers. The empid column is still used to uniquely identify a person.
ApplicationType	app_type	string(30)	yes	readOnly	Application type. This field is set when a person logs on to an application.
BloodType	bl_type	string(5)	yes	readOnly	Blood Type. The blood type of the employee is stored in this column in case of an emergency.
CadCommandAccess	cad_cmd_mask	int32	no	readOnly	CAD Command Mask. This column contains the key that limits access to I/CAD commands.
CaddbmCommandAccess	dbm_cmd_mask	int32	no	readOnly	CADDDBM Command Mask. This column contains the key that limits access to the CADDDBM commands.
ChatGroup	chatid	int32	yes	readOnly	Contains the CHAT GROUP the user is currently in
DefaultUnitId	default_unid	string(10)	yes	readOnly	The default unit id for the employee to use when the employee transfers from one unit to another. The primary purpose of this is to give each employee a unit id if they are acting as a single employee unit.
Domain	domain	string(64)	yes	readOnly	User's domain. Used for single sign on domain verification.
Email	email	string(80)	yes	readOnly	An email address for this person.
EmergencyCity	not_city	string(20)	yes	readOnly	City of the person to notify in case of an emergency involving the employee.
EmergencyName	not_nme	string(25)	yes	readOnly	Name of the person to Notify in case of an emergency involving the employee.
EmergencyPhone	not_ph	string(14)	yes	readOnly	Phone number of the person to notify in case of an emergency involving the employee.
EmergencyState	not_st	string(4)	yes	readOnly	State of the person to notify in case of an emergency involving the employee.

EmergencyStreetAddress	not_add	string(30)	yes	readOnly	Address of Person to Notify in case of an emergency involving the employee.
EmployeeCustom1	pcust1	string(50)	yes	readWrite	Person custom column 1
EmployeeCustom2	pcust2	string(50)	yes	readWrite	Person custom column 2
EmployeeCustom3	pcust3	string(50)	yes	readWrite	Person custom column 3
EmployeeCustom4	pcust4	string(50)	yes	readWrite	Person custom column 4
 EmployeeId	empid	int32	no	readOnly	Employee ID. This is the unique identifier of the persl table. It is stored in several tables when the identity of the person who created the record is needed for further information or S/he is assoc with a unit.
FirstName	fname	string(50)	yes	readOnly	First name of the employee.
HomeCity	emp_city	string(20)	yes	readOnly	City in which the employee resides.
HomePhone	phone	string(14)	yes	readOnly	Home Telephone Number. This column contains the home phone number in case the employee needs to be contacted when off duty, for example, if s/he is the only one in the department with a certain needed skill.
HomeState	emp_st	string(4)	yes	readOnly	State in which the employee resides.
HomeStreetAddress	emp_add	string(30)	yes	readOnly	Employee's street address.
IsActive [default = true]	curent	boolean	no	readOnly	This column reflects whether the personnel record is active. (T) represents an active employee, (F) resrepresents an inactive employee
LastName	lname	string(50)	yes	readOnly	Last name of the employee.
MiddleInitial	mi	string(1)	yes	readOnly	Middle Initial of the employee.
NameSoundex	soundex	string(4)	yes	readOnly	This column contains the soundex value of the employee name.
PagerId	page_id	string(12)	yes	readOnly	The Pager ID or Pager Group ID associated with this person.
Password	pswrd	string(128)	yes	readOnly	Password. For the employee to be able to log on to the I/CAD system, s/he must first enter the right combination of user id and password. If it is incorrect, the employee will not gain access to I/CAD.
PasswordExpiration	delex	int32	no	readOnly	Expiration of Password. The delex column contains the number of days until the expiration of the password.
PasswordHashId	pswrd_hash_id	int32	yes	readOnly	Password hash algorithm ID. 0 = Legacy CDencrypt, 1 = MD5, 2 = SHA512
PasswordNotification	dclno	int32	no	readOnly	Notification of Password. This column is the number of days from the creation time when the employee is to be notified of the expiration date of the current password.
PasswordTime	pass_date	dateTimeOffset	no	readOnly	Date of Password Creation or Password Update. This date is important in finding out when a password will expire or when the employee needs to be notified of the expiration date. The date is stored in epoch seconds.
RmsId	rms_id	int32	yes	readOnly	RMS employee ID. Used by CAD-inPURSUIT integration and Business Intelligence to link employee records in the CAD and RMS systems.
UserName	usr_id	string(20)	no	readOnly	Users ID.

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	ActiveStationEmployee	1	0..1	DefinedEmployee	ActiveStationEmployee	EmployeeId	EmployeeId
DefinedEmployee	ActiveStationEmployeeHistory	1	*	DefinedEmployee	ActiveStationEmployeeHistories	EmployeeId	EmployeeId
DefinedEmployee	ActiveUnitEmployee	1	*	DefinedEmployee	ActiveUnitEmployees	EmployeeId	EmployeeId
DefinedEmployee	AgencyEventAccess	1	*	DefinedEmployee	AgencyEventAccess	EmployeeId	EmployeeId
DefinedEmployee	AgencyEventDisposition	0..1	*	DefinedEmployee	AgencyEventDispositions	EmployeeId	UnitEmployeeId
DefinedEmployee	AgencyRosterUnitEmployee	1	*	DefinedEmployee	AgencyRosterUnitEmployees	EmployeeId	EmployeeId
DefinedEmployee	DefinedDevice	0..1	*	DefinedEmployee	DefinedDevices	EmployeeId	EmployeeId
DefinedEmployee	DefinedEmployeeAccessHistory	0..1	*	DefinedEmployee	DefinedEmployeeAccessHistories	EmployeeId	EmployeeId
Agency	DefinedEmployee	1	*	Agency	DefinedEmployees	AgencyId	AgencyId
DefinedEmployee	DefinedEmployeePasswordHistory	1	*	DefinedEmployee	DefinedEmployeePasswordHistories	EmployeeId	EmployeeId
DefinedEmployee	DefinedEmployeeSkill	1	*	DefinedEmployee	DefinedEmployeeSkills	EmployeeId	EmployeeId
DefinedEmployee	DefinedEmployeeStatus	1	0..1	DefinedEmployee	DefinedEmployeeStatus	EmployeeId	EmployeeId
DefinedEmployee	DefinedEmployeeTerminalAccess	1	*	DefinedEmployee	DefinedEmployeeTerminalAccess	EmployeeId	EmployeeId
DefinedEmployee	DefinedGroupEmployee	1	*	DefinedEmployee	DefinedGroupEmployees	EmployeeId	EmployeeId
DefinedEmployee	DefinedStationEmployee	1	*	DefinedEmployee	DefinedStationEmployees	EmployeeId	EmployeeId
DefinedEmployee	LineupUnitEmployee	1	*	DefinedEmployee	LineupUnitEmployees	EmployeeId	EmployeeId
DefinedEmployee	MessageGroupMember	0..1	*	DefinedEmployee	MessageGroupMembers	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - DefinedEmployeeAccessHistory							
Description	This table holds a history record for each employee who tries to access I/CAD. A record is written whenever an employee (attempts to) logs on or off. This table is used for inquiries on the employee.						
Base Table Name	ushis						
View Name	cmvDefinedEmployeeAccessHisor						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ApplicationType	prdt_run	string(1)	yes	readOnly	Product Being Run. This column identifies what product is being accessed. C= I/CAD, D= CADDBM, I= I/Informer.		
CreatedDayOfWeek {hidden}	dow				Day of week. This column contains the numeric equivalent for the day of the week, with 1 = Sunday and 7 = Saturday.		
CreatedSeconds {hidden}	csec				Cdts time stamp stored in epoch seconds		
CreatedTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal from which the record was created.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp. Stores the date/time stamp (yyyymmddhhmmss) of when the record was created.		
 EmployeeAccessHistoryId	unique_id	guid	no	readOnly	Uniquely identifies rows		
EmployeeId	empid	int32	yes	readOnly	Employee ID. This column contains the unique identifier for the employee which traces back to the persl (personnel) table.		
LogonStatus	lolflag	string(1)	no	readOnly	Logon/Logoff Transaction. This field indicates if the employee is logged on (N), logged off (F), logged off by the Free Person command (M), or an unsuccessful log on occurred (I=invalid user ID/password, and S = insufficient security access).		
Password	pswrd	string(128)	yes	readOnly	User Password. Deprecated.		
UserName	usr_id	string(20)	yes	readOnly	User Identification. This column holds the user ID of the employee logging on or off. If the user attempts to log on unsuccessfully more than a predefined number of times, what s/he tried to key in is placed in the database		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	DefinedEmployeeAccessHistory	0..1	*	DefinedEmployee	DefinedEmployeeAccessHistories	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - DefinedEmployeePasswordHistory								
Description	Contains password history information							
Base Table Name	pswrd_hist							
View Name	cmvDefinedEmployeePasswordHist							
Monitored	No							
Properties								
Property Name	Base Column	Data Type	NULL	Access Type	Description			
CreatedTime	cdts	dateTimeOffset	no	readOnly	Change date/time stamp			
 EmployeeId	empid	int32	no	readOnly	Employee id from persl.empid			
Password	pswrd	string(128)	yes	readOnly	New password			
 RevisionNumber	rev_num	int32	no	readOnly	Password revision number			
UserName	usr_id	string(20)	no	readOnly	User's id from persLusr_id			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References

DefinedEmployee	DefinedEmployeePasswordHistory	1	*	DefinedEmployee	DefinedEmployeePasswordHistories	EmployeeId	EmployeeId
---------------------------------	--------------------------------	---	---	-----------------	----------------------------------	------------	------------

 [Top](#)

Entity Type Name - DefinedEmployeeSkill							
Description	The skills that an employee has.						
Base Table Name	persl_skill						
View Name	cmvDefinedEmployeeSkill						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Description	description	string(80)	yes	readOnly	Description or comment regarding this employee's skill.		
 EmployeeId	empid	int32	no	readOnly	The employee identifier		
 SkillName	skill	string(8)	no	readOnly	A skill that the employee possesses		
SkillPriority (default = 3)	skill_priority	int32	no	readOnly	A relative priority used during unit recommendation to rank skills assigned to a person. Valid values are from 1 to 5, with 1 being the highest priority.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	DefinedEmployeeSkill	1	*	DefinedEmployee	DefinedEmployeeSkills	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - DefinedEmployeeStatus							
Description	The persl table holds a record for each employee who requires access to the I/CAD product or is listed as an employee of a unit. Most of this information is set in CADDDBM. I/CAD updates the app_type, logged_on, ldis, lodts and term columns when the user logs on. The pswrd and pass_date columns are updated when the user changes his/her password.						
Base Table Name	persl						
View Name	cmvDefinedEmployeeStatus						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ApplicationInUse	app_type	string(30)	yes	readOnly	Application type. This field is set when a person logs on to an application.		
 EmployeeId	empid	int32	no	readOnly	Employee ID. This is the unique identifier of the persl table. It is stored in several tables when the identity of the person who created the record is needed for further information or S/he is assoc with a unit.		
IsLoggedIn [default = false]	logged_on	boolean	no	readOnly	T indicates the employee is logged on, F indicates the employee is logged off		
LogoffTime	lodts	dateTimeOffset	yes	readOnly	Logoff Date/Time Stamp. This column contains the date/ time at which the employee successfully logged out of I/CAD.		
LagonTime	ldts	dateTimeOffset	yes	readOnly	Login Date/Time Stamp. When the employee successfully logs on to I/CAD, the date/ time stamp will be updated in that employee's record. This stamp is formatted for easier reading when the user sees it.		
RemoteProcessInUse	pid	int32	yes	readOnly	Process ID, when logged into a remote session. NULL otherwise.		
RemoteTerminalInUse	host_term	string(15)	yes	readOnly	Terminal name of host computer for remote session. This is NULL if CAD is running as a normal local process.		
TerminalInUse	term	string(15)	yes	readOnly	Terminal Node Name. This column contains the terminal node where the employee is currently logged on.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	DefinedEmployeeStatus	1	0..1	DefinedEmployee	DefinedEmployeeStatus	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - DefinedEmployeeTerminalAccess							
Description	This table holds records for all employees who require access to the I/CAD product. No columns here may be changed within I/CAD. CADDDBM modifies data in this table						
Base Table Name	noden						
View Name	cmvDefinedEmployeeTerminalAcce						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 EmployeeId	empid	int32	no	readOnly	Employee ID. The employee identification number is the unique identifier which links back to the persl record.		
 TerminalName	term	string(15)	no	readOnly	Terminal Node Name. The terminal(s) at which the employee may run applications. If the employee may run applications on any terminal, an (A) is put in this column.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	DefinedEmployeeTerminalAccess	1	*	DefinedEmployee	DefinedEmployeeTerminalAccess	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - DefinedGroupEmployee							
Description	This table is used to store the user groups that have been defined for access to scratch pad data.						
Base Table Name	usrgrp						
View Name	cmvDefinedGroupEmployee						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
DefinedGroupDesc	descr	string(50)	yes	readOnly	Description. This column contains the text description of the group.		
 DefinedGroupId	grpid	string(4)	no	readOnly	Group Identifier. This column contains the unique group ID that is used to control access to scratch pad information.		
 EmployeeId	empid	int32	no	readOnly	Employee Identifier. This column contains the unique employee ID that defines this person as a member of this group.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	DefinedGroupEmployee	1	*	DefinedEmployee	DefinedGroupEmployees	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - DefinedPager						
Description	This is the paging definition table. Def_page defines the individual pagers and pager groups. The page_id value (which may be an individual pager id or goup id) is used in other tables such as cd_units, agency_dgroup, and esz. The pager group members are defined in def_pgroup.					
Base Table Name	def_page					
View Name	cmvDefinedPager					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	

Description	description	string(30)	yes	readOnly	Description. The page_id may be cryptic. This column can provide a more user-friendly description of the pager or pager group.		
PageCode	page_code	string(80)	yes	readOnly	The actual page code to be sent to the controlling device. Must be specified for individual pagers (id_type = 'P')		
PageConditionId	cond_id	string(12)	yes	readOnly	An id for a conditional expression in the page_cond table. Can only be specified for individual pagers (id_type = 'P')		
PageOrder [default = 9999]	page_order	int32	no	readOnly	Paging order. When a CAD command lists multiple pager ids, then this column determines the order in which the pages are sent. Pagers and pager groups with smaller page_order values will get sent pages first.		
PageType	page_type	string(120)	yes	readOnly	The page interface/controller type such as zetron or tap. Tap is a protocol supported by many controllers such as Glenayre. Use caddbm to populate. Must be specified for individual pagers (id_type = 'P')		
 PagerId	page_id	string(12)	no	readOnly	Pager ID or pager group ID. The id_type column specifies whether this value is a pager ID or pager group ID.		
PagerIdType	id_type	string(1)	no	readOnly	Defines whether the page_id refers to an individual pager (P) or a pager group (G).		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedPager	DefinedPagerGroupMember	1	*	DefinedPager	DefinedPagerGroupMembers	PagerId	PagerId

 [Top](#)

Entity Type Name - DefinedPagerGroupMember							
Description	This table defines pager group members. A group can contain individual pagers as well as groups of pagers, so the page_id column can contain either a page_id or a group_id. The def_page table contains the definitions of the pager groups as well as the individual pager ids.						
Base Table Name	def_pgroup						
View Name	cmvDefinedPagerGroupMember						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
MemberOrder [default = 9999]	member_order	int32	no	readOnly	Member order. Determines the order in which pages are sent. Members with a smaller value will be sent pages first.		
 PagerGroupId	group_id	string(12)	no	readOnly	The group id defines a group of pager ids.		
 PagerId	page_id	string(12)	no	readOnly	Pager ID or Group ID. This column can contain a page_id or a group_id.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedPager	DefinedPagerGroupMember	1	*	DefinedPager	DefinedPagerGroupMembers	PagerId	PagerId

 [Top](#)

Entity Type Name - DefinedStation							
Description	The def_station table defines stations and/or posts that are used within CAD. Stations and Posts are usually locations or places associated with Fire and EMS agencies.						
Base Table Name	def_station						
View Name	cmvDefinedStation						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Identification for agency to which a station is assigned		
Beat	lev3	string(7)	yes	readOnly	This column contains an identifier for beat or service area to which this station is assigned.		
CreatedEmployeeId	cpers	int32	no	readOnly	Creating Person		
CreatedTerminal	cterm	string(15)	no	readOnly	Creating Terminal		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Create Date/Time Stamp		
DispatchGroup	dgroup	string(5)	no	readOnly	Station's dispatch group		
MaxAcknowledgeTime [default = 0]	ack_timer	int32	no	readOnly	The maximum time a unit at this station should be in acknowledge status		
MaxArriveTime [default = 0]	arrive_timer	int32	no	readOnly	The maximum time a unit at this station should be in arrive status		
MaxDispatchTime [default = 0]	disp_timer	int32	no	readOnly	The maximum time a unit at this station should be in dispatch status		
MaxEnrouteTime [default = 0]	enroute_timer	int32	no	readOnly	The maximum time a unit at this station should be in enroute status		
PagerId	page_id	string(12)	yes	readOnly	Pager ID or Pager Group ID from def_page.		
Phone	phone_no	string(14)	yes	readOnly	Phone number for this station		
PrintOutputType	prt_type	string(1)	yes	readOnly	Indicates to Fire Station Printing what type of output prt_addr references. Legal values are: A-ASCII text, B-FSA print packet, C-RTF, D-Email address, E-Windows executable F- Motorola's PMDC interface.		
PrintQueueAddress	prt_addr	string(80)	yes	readOnly	Print queue address of this station.		
 StationId [Monitored]	station	string(10)	no	readOnly	Unique id for this station. It is the key for this table.		
StationName	s_name	string(30)	yes	readOnly	Name of this station		
XCoordinate [default = 0.0]	loc_x	double	no	readOnly	X coordinate of station's physical location (in Master Units)		
YCoordinate [default = 0.0]	loc_y	double	no	readOnly	Y coordinate of station's physical location (in Master Units)		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedStation	ActiveCrew	1	*	DefinedStation	ActiveCrews	StationId	StationId
DefinedStation	ActiveStationEmployee	1	*	DefinedStation	ActiveStationEmployees	StationId	StationId
DefinedStation	ActiveUnit	0..1	*	DefinedStation	ActiveUnits	StationId	StationId
AgencyDispatchGroup	DefinedStation	1	*	AgencyDispatchGroup	DefinedStations	AgencyId, DispatchGroup	AgencyId, DispatchGroup
DefinedStation	DefinedStationEmployee	1	*	DefinedStation	DefinedStationEmployees	StationId	StationId
DefinedStation	DefinedUnit	0..1	*	DefinedStation	DefinedUnits	StationId	StationId
DefinedStation	LineupUnit	0..1	*	DefinedStation	LineupUnits	StationId	StationId
DefinedStation	ResponseRequirementCriterion	0..1	*	DefinedStation	ResponseRequirementCriteria	StationId	StationId

 [Top](#)

Entity Type Name - DefinedStationEmployee					
Description	Defines the personnel associated with each station. When a person is logged onto to a station, the data from this table is typically copied to act_station_persl. Note that you can define associations between a person and multiple stations. However, a person can only log onto to a single station. Added for CR 1-4UUSDH				
Base Table Name	def_station_persl				
View Name	cmvDefinedStationEmployee				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
DefaultStatus [default = 0]	default_status	int32	no	readOnly	Default status. When a person is logged on to a station, the person will be put in this status. 0= available, 1= unavailable
DelayValue [default = 0]	delay_value	int32	no	readOnly	Delay, in minutes. Amount of time it would take this person to get to the station.
Description	description	string(200)	yes	readWrite	Description or comment. When a station person is logged on, this description is copied to act_station_persl, unless the dispatcher specifies a new comment.
 EmployeeId	empid	int32	no	readOnly	Employee id

	StationId	station	string(10)	no	readOnly	Station id.	
Associations							
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References
DefinedEmployee	DefinedStationEmployee		1	*	DefinedEmployee	DefinedStationEmployees	EmployeeId
DefinedStation	DefinedStationEmployee		1	*	DefinedStation	DefinedStationEmployees	StationId

 [Top](#)

Entity Type Name - DefinedUnit							
Description	This table contains unit definitions.						
Base Table Name	def_unit						
View Name	cmvDefinedUnit						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Unit's agency ID. This column links to the ag_id column of the agenc table.		
Bay	bay	string(3)	yes	readOnly	Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table		
Beat	lev3	string(7)	yes	readOnly	Beat to which this unit is assigned		
DefaultAvailableStatus [default = 0]	type_avail	int16	no	readOnly	Default availability status. This will be the unit's status when it is cleared from an event, returned to service, or another change occurs that makes it available. The possible values for this column come from the cad UnitStatus parameter list.		
DeploymentLocation	loc_comm	string(40)	yes	readOnly	Permanent deployment location for the unit.		
DispatchGroup	dgroup	string(5)	no	readOnly	Unit's dispatch group.		
ExtendedUnitAttributes	ext_unitattr	string(64)	no	readOnly	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).		
IsClearReportEnabled [default = false]	require_cor	boolean	no	readOnly	This column supports fire station clear reports per unit. The value '1' means enable report for that unit, '0' will not print clear report for the unit.		
IsLateRun [default = false]	resp_stop	boolean	no	readOnly	Response Stop Flag. Flag used to indicate if the unit is associated with a late run. (Y = late run).		
IsSharedCrew [default = false]	shared_crew	boolean	no	readOnly	Indicates whether or not this unit is a shared crew unit. Y = the unit is a shared crew unit. N = the unit is not a shared crew unit.		
MdtGroup	mdtgroup	string(16)	yes	readOnly	The mdtgroup column defines an override of the MDT GROUP to which that unit is assigned.		
StationId	station	string(10)	yes	readOnly	Where applicable, this column contains the id of station in which unit is located. Station must be defined in def_station table before it is referenced here		
Status [default = 0]	unit_status	int16	no	readOnly	The unit's status when it is first logged on. The possible values for this column come from the cad UnitStatus parameter list.		
SymbolNumber [default = 0]	symnum	int32	no	readOnly	Symbol number. The symbol number is used to select a bitmap from the resource file. The bitmap is displayed on the map as the unit's symbol.		
UnitCustom1	ucust1	string(50)	yes	readWrite	Unit custom column 1		
UnitCustom2	ucust2	string(50)	yes	readWrite	Unit custom column 2		
UnitCustom3	ucust3	string(50)	yes	readWrite	Unit custom column 3		
UnitCustom4	ucust4	string(50)	yes	readWrite	Unit custom column 4		
 UnitId	unid	string(10)	no	readOnly	Unique Unit ID for this unit. This is a key to this table. Links to unid column in the lineup, cd_units and roster tables.		
UnitType	unityp	string(6)	yes	readOnly	Type of unit. (PATROL, TRUCK, etc.)		
XCoordinate [default = 0.0]	loc_x	double	no	readOnly	X coordinate of this unit's permanent deployment location (default location) in Master Units.		
YCoordinate [default = 0.0]	loc_y	double	no	readOnly	Y coordinate of this unit's permanent deployment location (default location) in Master Units.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedUnit	DefinedDevice	0..1	*	DefinedUnit	DefinedDevices	UnitId	UnitId
AgencyDispatchGroup	DefinedUnit	1	*	AgencyDispatchGroup	DefinedUnits	AgencyId, DispatchGroup	AgencyId, DispatchGroup
DefinedStation	DefinedUnit	0..1	*	DefinedStation	DefinedUnits	StationId	StationId
ValidUnit	DefinedUnit	1	0..1	ValidUnit	DefinedUnit	UnitId	UnitId

 [Top](#)

Entity Type Name - DefinedUnitType							
Description	This table defines the valid unit types and their associated properties. A unit type can be defined differently for different agencies.						
Base Table Name	def_unit_type						
View Name	cmvDefinedUnitType						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId	ag_id	string(9)	no	readOnly	Agency id		
Category [default = 0]	category	int32	no	readOnly	Configurable category, e.g. normal, supervisor. The only value which is hardcoded is 0, which means normal or default. The other values come from the unit_type_category pick list in the cad->PickLists parameter table. By default, the picklist contains 0 for default and 1 for supervisor, but customers can change that.		
Description	description	string(30)	yes	readOnly	Description or comment for this unit type.		
MaxRecommendDistance [default = 0]	max_rec_dist	double	no	readOnly	Maximum radius around event in which to look for units of this type to recommend, or 0 for no limit		
SpeedFactor [default = 1]	speed_factor	double	no	readOnly	Multiplier applied to unit routes for recommendation		
 UnitType	unityp	string(6)	no	readOnly	Unit type.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	DefinedUnitType	1	*	Agency	DefinedUnitTypes	AgencyId	AgencyId

 [Top](#)

Entity Type Name - DefinedVehicle						
Description	This table defines any physical vehicles used in CAD. All police cars, fire trucks, etc. are defined here.					
Base Table Name	def_vhic					
View Name	cmvDefinedVehicle					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	

AgencyId	ag_id	string(9)	no	readOnly	Agency to which vehicle belongs
DelayTime [default = 0]	delay_value	int32	no	readOnly	This value will be added to the unit's time/distance when recommending units by the road network
IsMdtVoiceAvailable [default = true]	vflag	boolean	no	readOnly	MDT Voice Flag. This field defines whether the MDT unit is available on voice (radio). Y = Yes, N = No.
MaxAcknowledgeTime [default = 0]	ack_timer	int32	no	readOnly	The time in minutes that a vehicle can be in acknowledge status.
MaxArriveTime [default = 0]	arrive_timer	int32	no	readOnly	The maximum time a unit with this vehicle should be in arrive status
MaxDispatchTime [default = 0]	disp_timer	int32	no	readOnly	The maximum time a unit with this vehicle should be in dispatch status.
MaxEnrouteTime [default = 0]	enroute_timer	int32	no	readOnly	The maximum time a unit with this vehicle should be in enroute status
MaxHeight [default = 0]	max_ht	int32	no	readOnly	Maximum height for vehicle
MaxWeight [default = 0]	max_wt	int32	no	readOnly	Maximum weight of vehicle.
MaxWidth [default = 0]	max_wd	int32	no	readOnly	Maximum width for vehicle
PageDestination [default = 0]	page_unit_person	int16	no	readOnly	0 - Page unit only 1 - Page Employee only 2 - Page both unit & Employee
PagerId	page_id	string(12)	yes	readOnly	The pager id or pager group id associated with the vehicle. This value is carried forward into the unit at log on.
VehicleId	carid	string(12)	no	readOnly	Unique id for this vehicle.

Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedVehicle	AgencyRosterUnitEmployee	0..1	*	DefinedVehicle	AgencyRosterUnitEmployees	VehicleId	VehicleId
DefinedVehicle	DefinedDevice	0..1	*	DefinedVehicle	DefinedDevices	VehicleId	VehicleId
Agency	DefinedVehicle	1	*	Agency	DefinedVehicles	AgencyId	AgencyId
DefinedVehicle	DefinedVehicleEquipment	1	*	DefinedVehicle	DefinedVehicleEquipment	VehicleId	VehicleId
DefinedVehicle	LineupUnit	0..1	*	DefinedVehicle	LineupUnits	VehicleId	VehicleId

[Top](#)

Entity Type Name - DefinedVehicleEquipment							
Description	The equipment associated with vehicles.						
Base Table Name	def equip						
View Name	cmvDefinedVehicleEquipment						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
EquipmentCount	num equip	int32	no	readOnly	Number of pieces of this equipment		
EquipmentName	equip	string(10)	no	readOnly	This column contains a piece of equipment in this vehicle.		
VehicleId	carid	string(12)	no	readOnly	The id for a vehicle		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedVehicle	DefinedVehicleEquipment	1	*	DefinedVehicle	DefinedVehicleEquipment	VehicleId	VehicleId

[Top](#)

Entity Type Name - DeploymentBeat							
Description	The beats for a deployment plan						
Base Table Name	beat						
View Name	cmvDeploymentBeat						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Beat	lev3	string(7)	no	readOnly	Beat		
CommentText	comm	string(80)	yes	readOnly	Comments about this record.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The create datetime stamp		
DeletedId {hidden}	delete_id				A unique id that is set when the row is deleted.		
DeploymentBeatId	unique_id	guid	no	readOnly	Uniquely identifies a row		
DeploymentPlanName	depo_plan_name	string(30)	no	readOnly	The deployment plan name		
District	lev5	string(5)	yes	readOnly	Jurisdiction (command level) that encompasses the beat.		
IsActive {hidden}	curent				T = Current, F = Deleted		
MapNumber	map_no	string(8)	yes	readOnly	This column contains a deployment plan design file name that will be displayed if this deployment is used.		
Municipality	mun	string(40)	yes	readOnly	Municipality (level 6 area) in which this beat is loacted.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The update datetime stamp		
Zone	lev4	string(5)	yes	readOnly	Division (zone level) that encompasses the beat.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DeploymentPlan	DeploymentBeat	1	*	DeploymentPlan	DeploymentBeats	DeploymentPlanName	DeploymentPlanName
DeploymentBeat	DeploymentResponseBackupBeat	1	*	DeploymentBeat	DeploymentResponseBackupBeats	DeploymentPlanName, Beat	DeploymentPlanName, Beat
DeploymentBeat	DeploymentResponse	1	*	DeploymentBeat	DeploymentResponses	DeploymentPlanName, Beat	DeploymentPlanName, Beat
DeploymentBeat	DeploymentRunCardUnit	1	*	DeploymentBeat	DeploymentRunCardUnits	DeploymentPlanName, Beat	DeploymentPlanName, Beat

[Top](#)

Entity Type Name - DeploymentPlan					
Description	Defines all the valid deployment plans in the system.				
Base Table Name	depo_plan				
View Name	cmvDeploymentPlan				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
DeploymentPlanDescription	description	string(50)	yes	readOnly	Description
 DeploymentPlanName	depo_plan_name	string(30)	no	readOnly	Deployment plan name
Associations					

Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DeploymentPlan	AgencyDeploymentPlan	1	*	DeploymentPlan	AgencyDeploymentPlans	DeploymentPlanName	DeploymentPlanName
DeploymentPlan	DeploymentBeat	1	*	DeploymentPlan	DeploymentBeats	DeploymentPlanName	DeploymentPlanName
DeploymentPlan	DeploymentRunCardUnit	1	*	DeploymentPlan	DeploymentRunCardUnits	DeploymentPlanName	DeploymentPlanName

 [Top](#)

Entity Type Name - DeploymentResponse							
Description	The esz table is used to store information about what type of equipment must be deployed when certain events happen in certain areas. There will be a record for each deployment plan and esz combination. There may also be overrides for certain event types.						
Base Table Name	esz						
View Name	cmvDeploymentResponse						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventSubtypeCode [default = default]	sub_tycod	string(16)	no	readOnly	The sub-type of the event type. If no event sub-type is specified this will be set to default.		
AgencyEventTypeCode [default = default]	tycod	string(16)	no	readOnly	Event type code for which this record is written. If no event type is specified this will be set to default.		
AlarmLevel [default = -1]	alarm_lev	int32	no	readOnly	Alarm level for a specified Event Type within an Emergency Service Zone. If no alarm level is specified this will be set to -1.		
Area	lev2	string(6)	yes	readOnly	Reporting area/ census track/ grid in which this ESZ is located.		
Beat	lev3	string(7)	no	readOnly	Beat/district in which the esz is located.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The create datetime stamp		
DeleteId {hidden}	delete_id				A unique id that is set when the row is deleted		
DeploymentPlanName	deplo_plan_name	string(30)	no	readOnly	The deployment plan name		
 DeploymentResponseId	unique_id	guid	no	readOnly	Uniquely identifies a row		
DispatchGroup	dgroup	string(5)	yes	readOnly	Unique id for dispatch group of the ESZ of this record.		
Esz	esz	int32	no	readOnly	Emergency Service Zone. (level one area)		
IsActive {hidden}	current				T = Current, F = Deleted		
PagerId	page_id	string(12)	yes	readOnly	Associated Pager ID or Pager Group ID		
ResponsePlanName	resp_plan_name	string(50)	yes	readOnly	Response plan which will be used when an event happens in this ESZ.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The update datetime stamp.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DeploymentResponse	DeploymentResponseBackupBeat	1	*	DeploymentResponse	DeploymentResponseBackupBeats	DeploymentResponseId	DeploymentResponseId
DeploymentBeat	DeploymentResponse	1	*	DeploymentBeat	DeploymentResponses	DeploymentPlanName, Beat	DeploymentPlanName, Beat

 [Top](#)

Entity Type Name - DeploymentResponseBackupBeat							
Description	The ordered list of backup beats associated with a row in the esz table.						
Base Table Name	backup_beat_list						
View Name	cmvDeploymentResponseBackupBea						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
BackupOrder	backup_order	int16	no	readOnly	The order in which the backup beats are used.		
Beat	backup_beat	string(7)	no	readOnly	Backup beat from which units may be dispatched if none are available from the primary beat.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The create datetime stamp		
DeleteId {hidden}	delete_id				A unique id that is set that when the row is deleted.		
DeploymentPlanName	deplo_plan_name	string(30)	no	readOnly	The deployment plan name		
 DeploymentRespBackupBeatId	unique_id	guid	no	readOnly	Uniquely identifies a row		
DeploymentResponseId	esz_rec_id	guid	no	readOnly	Unique record id (unique_id) from the esz table.		
IsActive {hidden}	current				T= Current, F = Deleted		
MinUnits {default = 0}	min_units	int32	no	readOnly	The minimum number of available units a beat must contain.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The update datetime stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DeploymentBeat	DeploymentResponseBackupBeat	1	*	DeploymentBeat	DeploymentResponseBackupBeats	DeploymentPlanName, Beat	DeploymentPlanName, Beat
DeploymentResponse	DeploymentResponseBackupBeat	1	*	DeploymentResponse	DeploymentResponseBackupBeats	DeploymentResponseId	DeploymentResponseId

 [Top](#)

Entity Type Name - DeploymentRunCardUnit					
Description	Contains run card definitions tied to deployment table, event type and beat/ESZ				
Base Table Name	run_card				
View Name	cmvDeploymentRunCardUnit				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AgencyEventSubtypeCode	sub_tycod	string(16)	no	readOnly	Event subtype, or "default" if none
 AgencyEventTypeCode	tycod	string(16)	no	readOnly	Event type for run card, or "default" if none
 AlarmLevel	alarm_lev	int32	no	readOnly	Alarm level for unit
 Beat	lev3	string(7)	no	readOnly	Beat name, or "" if record associated with an ESZ (ESZ column cannot be -1)
CardComment	card_comment	string(50)	yes	readOnly	User-supplied comment associated with run card definition (will be NULL except in the first row of run card definition)
 DeploymentPlanName	deplo_plan_name	string(30)	no	readOnly	Deployment plan name that this run card is associated with
 Esz	esz	int32	no	readOnly	ESZ, or -1 if record associated with a beat (LEV3 column cannot be "")
UnitId	unid	string(10)	no	readOnly	ID of unit assigned to run card
 UnitOrder	unit_order	int32	no	readOnly	Unit's order within alarm, beginning with zero
Associations					

Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DeploymentBeat	DeploymentRunCardUnit	1	*	DeploymentBeat	DeploymentRunCardUnits	DeploymentPlanName, Beat	DeploymentPlanName, Beat
DeploymentPlan	DeploymentRunCardUnit	1	*	DeploymentPlan	DeploymentRunCardUnits	DeploymentPlanName	DeploymentPlanName
ValidUnit	DeploymentRunCardUnit	1	*	ValidUnit	DeploymentRunCardUnits	UnitId	UnitId

[Top](#)

Entity Type Name - Destination						
Description	This table stores the destinations for a specified command type and instance. Used by broadcast.					
Base Table Name	destinations					
View Name	cmvDestination					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
CommandCode	command_code	int32	no	readOnly	Integer value indicating for which command this destination is relevant. 1=Broadcast, 3=Scratch Pad	
CreatedTime	cdts	dateTimeOffset	no	readOnly	The creation date time stamp.	
DeletedId {hidden}	delete_id				An arbitrary value that uniquely identifies a deleted row	
Destination	destination	string(80)	no	readOnly	A destination such as a nodename, mdt-id, page-id, email address, etc.	
DestinationId	unique_id	guid	no	readOnly	Uniquely identifies a row	
DestinationSubtype	sub_type	string(15)	yes	readOnly	CAD, MDT, PAGER, or other application.	
DestinationType	main_type	string(8)	no	readOnly	TERM, PERSON, PAGER, STATION, GROUP, EMPID, or FILTER.	
IsActive {hidden}	current				T/F, indicates if row is active or deleted	
ItemNumber	item_number	int32	no	readOnly	Unique item number for the command which stores its information in this table.	
MessageStatus	msg_status	string(1)	no	readOnly	B/H/R/N/S, Indicating broadcast, scheduled, read, not read, or saved.	
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The update date time stamp.	

[Top](#)

Entity Type Name - DispatchAssignedEvent							
Description	This table is used by the Dispatch Assigned (DAed) functionality to maintain the order in which events are dispatch assigned to units. This table is not for historical use. Records are removed as DA events are dispatched (DPed)						
Base Table Name	dispass_event						
View Name	cmvDispatchAssignedEvent						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	no	readOnly	This field represents the agency event number for any event that is Dispatch Assigned to a unit.		
AlarmTime [default = 0]	alarm_time	int32	no	readOnly	Minutes after last status change when unit goes into an alarm state		
DispatchNumber	disp_num	string(12)	yes	readOnly	Unique dispatch number assigned to dispatch assigned event		
ListPosition	list_pos	int32	no	readOnly	This column represents the position in which an event was Dispatch Assigned to a unit in relation to other DA events for that unit. Ordering starts at 0 but may go negative if DA events are moved to the top of the list		
StatusChangeTime	status_dts	dateTimeOffset	no	readOnly	Date/time of last status change		
TransportLocation	trans_location	string(80)	yes	readOnly	Transport location text		
TransportXCoordinate [default = 0]	transxor	int32	no	readOnly	Verified X coordinate of transport location		
TransportYCoordinate [default = 0]	transyor	int32	no	readOnly	Verified Y coordinate of transport location		
UnitId	unid	string(10)	no	readOnly	This field represents the unit number for a unit that has an event dispatch assigned to it.		
UnitStatus	unit_status	int32	no	readOnly	This column will allow a unit status to be assigned for each dispatch assigned event.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnit	DispatchAssignedEvent	1	*	ActiveUnit	DispatchAssignedEvents	UnitId	UnitId
AgencyEvent	DispatchAssignedEvent	1	0..1	AgencyEvent	DispatchAssignedEvent	AgencyEventId	AgencyEventId

[Top](#)

Entity Type Name - DispatchGroupResponseTime							
Description	The resp_time table defines the estimated time of arrival for an agency and dispatch group based on the day of the week and the hour of the day. The data in this table can be managed using the Deployment-> ETA Table command in CADDBM.						
Base Table Name	resp_time						
View Name	cmvDispatchGroupResponseTime						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Agency Identification. This column stores the name of the agency.		
DayOfWeek	dow	string(1)	no	readOnly	Day of the Week. This column defines the day of the week, where 1 = Sunday and 7 = Saturday.		
DispatchGroup	dgroup	string(5)	no	readOnly	Dispatch Group. This column defines the dispatch group.		
EstimatedArrivalTime	eta	int32	no	readOnly	Estimated Time of Arrival. This column defines the estimated time of arrival for a given time on a given day of the week.		
HourOfDay	hod	string(2)	no	readOnly	Hour of the Day. This column defines the hour of the day in military time.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyDispatchGroup	DispatchGroupResponseTime	1	*	AgencyDispatchGroup	DispatchGroupResponseTimes	AgencyId, DispatchGroup	AgencyId, DispatchGroup

[Top](#)

Entity Type Name - ExternalRequestedResource					
Description	This table contains the resources (units) that were requested by the external system, as well as the status of that request. Added for CR 1-5ZJQK4				
Base Table Name	external_requested_resource				
View Name	cmvExternalRequestedResource				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
CreatedEmployeeId	cpers	int32	no	readOnly	Person that created this record
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal that created this record
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date timestamp
LocalAgencyEventId [Monitored]	local_event_id	string(12)	no	readOnly	Agency event ID (num_1) on local system, that corresponds to the external event.

RequestStatus [Monitored]	request_status	string(1)	no	readOnly	Status of the request. "A" = Accepted, "O" = Overridden (the external system's ability to change the unit's status has been overridden), "R" = Rejected, "T" = Timed Out, "U" = Unreachable, "W" = Waiting		
StatusTime [Monitored]	status_dts	dateTimeOffset	no	readOnly	Status Time. Contains the time that this request was created or last updated.		
 UnitId [Monitored]	unit_id	string(10)	no	readOnly	Unit requested by external system		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update person		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Update terminal		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update timestamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ExternalRequestForResources	ExternalRequestedResource	1	*	ExternalRequestForResources	ExternalRequestedResources	LocalAgencyEventId	LocalAgencyEventId
ValidUnit	ExternalRequestedResource	1	*	ValidUnit	ExternalRequestedResources	UnitId	UnitId

 [Top](#)

Entity Type Name - ExternalRequestForResources							
Description	This table records requests for resources (units) that are made by external systems via BizTalk and IFCAD. For example, if a nearby agency, running a different CAD system, requests units for mutual aid, this table records that request. The external_requested_resource table has the list of resources that were requested. Added for CR 1-5ZJQK4						
Base Table Name	external_request_for_resources						
View Name	cmvExternalRequestForResources						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedEmployeeId	cpers	int32	no	readOnly	Person that created this record		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal that created the record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date timestamp		
ExternalEventId [Monitored]	external_event_id	string(64)	no	readOnly	External event ID		
ExternalSystemId [default = default] [Monitored]	external_system_id	string(64)	no	readOnly	External system ID		
IsRequestClosed [default = false] [Monitored]	request_closed	boolean	no	readOnly	Is request closed (T) or open (F)		
 LocalAgencyEventId [Monitored]	local_event_id	string(12)	no	readOnly	Agency event ID (num_1) on local system, that corresponds to the external event.		
UpdatedEmployeeId	upers	int32	yes	readOnly	Update person		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Update terminal		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update timestamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ExternalRequestForResources	ExternalRequestedResource	1	*	ExternalRequestForResources	ExternalRequestedResources	LocalAgencyEventId	LocalAgencyEventId
AgencyEvent	ExternalRequestForResources	1	0..1	AgencyEvent	ExternalRequestForResources	AgencyEventId	LocalAgencyEventId

 [Top](#)

Entity Type Name - FireStationAlert					
Description	The fs_alert table contains the alert address, station, bay and alert order information for all alertable units. Each row represents an individual unit at a fire station, at a particular alert order. Each unit id (unid) in cd_units to be alerted should correspond to a station and bay in fs_alert. If the primary address is unreachable, an alert will be sent to the alternate address				
Base Table Name	fs_alert				
View Name	cmvFireStationAlert				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AlertAddress	alert_address	string(24)	no	readOnly	Contains the address for alertable units. Unique for each station/bay/type/alert_order combination. Format varies for each controller.
 AlertOrder [default = 1]	alert_order	int32	no	readOnly	Order in which to alert this address. 1 = Primary, 2 = Alternate
 Bay	bay	string(3)	no	readOnly	Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table
 ControllerType	type	string(10)	no	readOnly	Type of controller. Current possible values include: CENTRACOM, FRAP, LOCUTION, MODBUS, MOSCAD, PAGER, WESTNET, ZETRON, and ZETRONXML. If type = PAGER, then this must be an alternate alert address (alert_order = 2)
 StationId	station	string(10)	no	readOnly	Unit's station

 [Top](#)

Entity Type Name - FireStationReport					
Description	The FS_REPORTS table supports specific dispatch, clear or administrative report formats per station. The FS_REPORTS contains Station, Report_type, ASP_FileName, and XSL_FileName information for each station. Each row represents a valid station that has customized ASP and XSL file info that is used to print a specific report format at fire station.				
Base Table Name	fs_reports				
View Name	cmvFireStationReport				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AspFilename	asp_filename	string(50)	no	readOnly	The custom ASP filename. This file contains the specific ASP format for a fire station.
Quantity [default = 1]	quantity	int32	no	readOnly	This defines how many reports to print for a given station printer.
 ReportType	report_type	string(1)	no	readOnly	Type of report - 'D' for dispatch, 'C' for clear, or 'A' for administrative
 StationId	station	string(10)	no	readOnly	Unit's station ID
XslFilename	xsl_filename	string(50)	no	readOnly	The custom XSL filename. This file contains the specific XSL format for a fire station.

 [Top](#)

Entity Type Name - GeneralTimer					
Description	Used to maintain data about individual timers				
Base Table Name	timer				
View Name	cmvGeneralTimer				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyId [Monitored]	ag_id	string(9)	yes	readOnly	Agency timer is associated with
Category {hidden}	category				EV = event, UN = unit, GE = general, not associated with event or unit

ClosingText [Monitored]	closing_text	string(160)	yes	readOnly	Text string associated with closing of the timer.		
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee id of creator		
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	Terminal node identifier of creator.		
CreatedTime [Monitored]	cdts	dateTimeOffset	no	readOnly	Date, time stamp of when timer is created.		
DispatchGroup [Monitored]	dgroup	string(5)	yes	readOnly	Dispatch group timer is associated with		
IsRepeating [Monitored]	repeat	boolean	no	readOnly	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of unique timer		
SetName [Monitored]	set_name	string(15)	yes	readOnly	Name of set that timer is associated.		
StartedTime [Monitored]	start_dts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer begins executing.		
StatusCode [Monitored]	status_code	int32	no	readOnly	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled		
Timeout [Monitored]	timeout	int32	no	readOnly	timer expiration in seconds. Range can be 1 to max int.		
TimeoutText [Monitored]	timeout_text	string(160)	yes	readOnly	Text string associated with expiration of timer.		
TimerId [Monitored]	timer_id	guid	no	readOnly	Uniquely identifies the row		
TimerName [Monitored]	object_id	string(30)	no	readOnly	For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name		
TimerType [Monitored]	type	int32	no	readOnly	The type of timer		
UpdatedEmployeeId [Monitored]	upers	int32	yes	readOnly	Employee id of updating person		
UpdatedTerminal [Monitored]	uterm	string(15)	yes	readOnly	Terminal node identifier of updater		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer is updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
GeneralTimer	GeneralTimerHistory	1	*	GeneralTimer	GeneralTimerHistories	TimerId	TimerId

[Top](#)

Entity Type Name - GeneralTimerHistory							
Description	Used to maintain data about individual timer history						
Base Table Name	timer_history						
View Name	cmvGeneralTimerHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	yes	readOnly	Agency timer is associated with		
Category {hidden}	category				EV = event, UN = unit, GE = general, not associated with event or unit		
ClosingText	closing_text	string(160)	yes	readOnly	Text string associated with closing of the timer.		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee id of creator		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal node identifier of creator.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Date, time stamp of when timer is created.		
DispatchGroup	dgroup	string(5)	yes	readOnly	Dispatch group timer is associated with		
IsRepeating	repeat	boolean	no	readOnly	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of unique timer		
SetName	set_name	string(15)	yes	readOnly	Name of set that timer is associated.		
StartedTime	start_dts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer begins executing.		
StatusCode	status_code	int32	no	readOnly	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled		
Timeout	timeout	int32	no	readOnly	timer expiration in seconds. Range can be 1 to max int.		
TimeoutText	timeout_text	string(160)	yes	readOnly	Text string associated with expiration of timer.		
TimerId	timer_id	guid	no	readOnly	Uniquely identifies the row		
TimerName	object_id	string(30)	no	readOnly	For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name		
TimerType	type	int32	no	readOnly	The type of timer		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
GeneralTimer	GeneralTimerHistory	1	*	GeneralTimer	GeneralTimerHistories	TimerId	TimerId

[Top](#)

Entity Type Name - HospitalDiversion					
Description	The divert table stores the hospital divert statuses.				
Base Table Name	divert				
View Name	cmvHospitalDiversion				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
CallerName	caller	string(30)	yes	readOnly	Caller Name.
CallerPhone	phone_num	string(14)	yes	readOnly	Phone Number of the caller
ClearAuthorityName	x_caller	string(30)	yes	readOnly	Name of clearing authority
ClearComment	x_comm	string(40)	yes	readOnly	Clearing Comments.
ClearEmployeeId	xpers	int32	yes	readOnly	Clearing person
ClearTerminal	xterm	string(15)	yes	readOnly	Clearing Terminal
ClearTime	xdts	dateTimeOffset	yes	readOnly	Close Date/Time Stamp
CreatedEmployeeId	cpers	int32	no	readOnly	Creation Person
CreatedTerminal	cterm	string(15)	no	readOnly	Creation Terminal
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp
DiversionComment	d_comm	string(40)	yes	readOnly	Diversion Comment.
DiversionType	d_type	string(10)	no	readOnly	Diversion type.
HospitalLocation	location	string(200)	yes	readOnly	Hospital location
IsActive	open_record	boolean	no	readOnly	T indicates the diversion is active, F indicates it has been closed
MapFeatureId	mslink	int32	no	readOnly	Map Graphics Link. Graphics link to a specific location.
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp



[Top](#)

Entity Type Name - LineupCrew							
Description	This table contains crew IDs associated with crews added to lineups.						
Base Table Name	lineup_crews						
View Name	cmvLineupCrew						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Agency ID.		
CrewId	crew_id	string(30)	no	readOnly	Crew ID.		
LineupName	lineup_name	string(30)	no	readOnly	Lineup name.		
StationId	station	string(10)	no	readOnly	Station ID.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedCrew	LineupCrew	1	*	DefinedCrew	LineupCrews	CrewId	CrewId



[Top](#)

Entity Type Name - LineupUnit							
Description	The lineup table defines the units, equipment, and personnel which are available per workshift. All units, vehicles and personnel must be defined in CADDDB prior to using them in a lineup.						
Base Table Name	lineup						
View Name	cmvLineupUnit						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Agency ID. Defines the agency to which the units/ personnel belong.		
Bay	bay	string(3)	yes	readOnly	Represents an individual bay in each fire station. Used to map individual units to an alert address that is defined in the fs_alert table		
Beat	lev3	string(7)	yes	readOnly	Level 3 Area. This column defines the current beat assignment.		
CreatedEmployeeId	cpers	int32	no	readOnly	Creating Person. This column contains the personnel identification number (empid) of the person who created the record.		
CreatedTerminal	cterm	string(15)	no	readOnly	Creating Terminal. The nodename of the terminal at which the record was created.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date. This column is the date/time stamp (yyyymmddhhmmss) in which the record was created.		
DefaultAvailableStatus [default = 0]	type_avail	int16	no	readOnly	Default availability status. This will be the unit's status when it is cleared from an event, returned to service, or another change occurs that makes it available. The possible values for this column come from the cad UnitStatus parameter list.		
DelayTime [default = 0]	delay_value	int32	no	readOnly	This value will be added to the unit's time/distance when recommending units by the road network		
DeploymentLocation	loc_comm	string(40)	yes	readOnly	Location Comment. The name of the permanent deployment location. This may be displayed in the Status Monitor in I/CAD when a unit is available.		
DispatchGroup	dgroup	string(5)	no	readOnly	Dispatch Group. Defines the dispatch group which is responsible for this unit in the lineup.		
ExtendedUnitAttributes	ext_unitattr	string(64)	no	readOnly	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).		
IsActive [default = true]	curent	boolean	no	readOnly	Flag used to reflect whether the lineup is active. (T) represents active lineup, (F) represents an inactive lineup		
IsLateRun [default = false]	resp_stop	boolean	no	readOnly	Response Stop Flag. Flag to indicate if associated with a late run. (Y)-- associated with a late run, (N)-- not associated with a late run.		
IsMdtVoiceAvailable	vflag	boolean	yes	readOnly	MDT Voice Flag. This field defines whether the MDT unit is available on voice (radio). Y = Yes, N = No.		
IsSharedCrew [default = false]	shared_crew	boolean	no	readOnly	Indicates whether or not this unit is a shared crew unit. Y = unit is a shared crew unit. N = unit is not a shared crew unit.		
LineupDesc	descript	string(80)	yes	readOnly	Description. This column contains a description of the lineup.		
LineupName	lineup_name	string(30)	no	readOnly	Lineup Name. This column defines the name of the lineup. The names should contain a definition of time and group. However, this is not a requisite.		
MaxHeight [default = 0]	max_ht	int32	no	readOnly	Maximum Height. Defines the maximum height of the vehicle. Will be used with the router in conjunction with street restrictions.		
MaxWeight [default = 0]	max_wt	int32	no	readOnly	Maximum Weight. Defines the maximum weight of the vehicle. Will be used with the router in conjunction with street restrictions.		
MaxWidth [default = 0]	max_wd	int32	no	readOnly	Maximum Width. Defines the maximum width of the vehicle. Will be used with the router in conjunction with street restrictions.		
PageDestination [default = 0]	page_unit_person	int16	no	readOnly	0 - Page unit only 1 - Page Employee only 2 - Page both unit & Employee		
PagerId	page_id	string(12)	yes	readOnly	The unit's pager id or pager group id. This value is carried forward at log on time.		
RecordNumber	rec_num	int16	yes	readOnly	Record Number. Unique identifier for each record in the table. Used by Skill and Roster when creating lineups.		
ShiftDuration [default = 0]	shift_duration	int32	no	readOnly	Scheduled shift length. Note that this value is in seconds, whereas the "Shift Duration" field on the CADDDB Lineup dialog is in hours.		
ShiftStartedTime	shift_start	dateTimeOffset	yes	readOnly	Scheduled shift start.		
SpecialDetail	sp_detail	string(80)	yes	readOnly	Special Detail. Defines any special detail that is assigned.		
StationId	station	string(10)	yes	readOnly	Station Name. This column contains the currently assigned station name.		
Status [default = 0]	unit_status	int16	no	readOnly	The unit's status when it is first logged on. The possible values for this column come from the cad UnitStatus parameter list.		
SymbolNumber [default = 0]	symnum	int32	no	readOnly	Symbol number. The symbol number is used to select a bitmap from the resource file. The bitmap is displayed on the map as the unit's symbol.		
UnitCustom1	ucust1	string(50)	yes	readWrite	Unit custom column 1		
UnitCustom2	ucust2	string(50)	yes	readWrite	Unit custom column 2		
UnitCustom3	ucust3	string(50)	yes	readWrite	Unit custom column 3		
UnitCustom4	ucust4	string(50)	yes	readWrite	Unit custom column 4		
UnitId	unid	string(10)	no	readOnly	Unit ID. This column contains the unit identification, usually the call letters.		
UnitType	unityp	string(6)	yes	readOnly	Unit Type. Defines the type of unit (for example: Patrol, Pumper, and ALS).		
VehicleId	carid	string(12)	yes	readOnly	Car Identification. This column defines the agency vehicle identification.		
WorkShift	work_shift	string(5)	yes	readOnly	Work Shift. When creating the lineup, CADDDB considers shift and only selects the employees who are scheduled to work that shift.		
XCoordinate [default = 0.0]	loc_x	double	no	readOnly	Location X-coordinate. Defines the x-coordinate in map units of the permanent deployment location. This is the location on the map where the unit will be displayed when available for dispatch.		
YCoordinate [default = 0.0]	loc_y	double	no	readOnly	Location Y-coordinate. Defines the y-coordinate in map units of the permanent deployment location. This is the location on the map where the unit will be displayed when it is available for dispatch.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyDispatchGroup	LineupUnit	1	*	AgencyDispatchGroup	LineupUnits	AgencyId, DispatchGroup	AgencyId, DispatchGroup
DefinedStation	LineupUnit	0..1	*	DefinedStation	LineupUnits	StationId	StationId
DefinedVehicle	LineupUnit	0..1	*	DefinedVehicle	LineupUnits	VehicleId	VehicleId
LineupUnit	LineupUnitDevice	1	*	LineupUnit	LineupUnitDevices	LineupName, UnitId	LineupName, UnitId
LineupUnit	LineupUnitEmployee	1	*	LineupUnit	LineupUnitEmployees	LineupName, UnitId	LineupName, UnitId
LineupUnit	LineupUnitEquipment	1	*	LineupUnit	LineupUnitEquipment	LineupName, UnitId	LineupName, UnitId
ValidUnit	LineupUnit	1	*	ValidUnit	LineupUnits	UnitId	UnitId

[Top](#)

Entity Type Name - LineupUnitDevice							
Description	Stores devices used by units, vehicles and personnel in a lineup. CR 1-6PGD42: PLT						
Base Table Name	lineup_device						
View Name	cmvLineupUnitDevice						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Description	description	string(50)	yes	readOnly	Description		
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device		
DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system		
DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT		
GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
IsTrackable	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForUnit	tdevice_for_unit	boolean	no	readOnly	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False		
LineupName	lineup_name	string(30)	no	readOnly	Lineup name		
Owner {hidden}	owner				Owner. 0 = unit, 1 = employee		
TdeviceForEmp {hidden}	tdevice_for_emp				Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False		
UnitId	unid	string(10)	no	readOnly	Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
LineupUnit	LineupUnitDevice	1	*	LineupUnit	LineupUnitDevices	LineupName, UnitId	LineupName, UnitId
ValidDevice	LineupUnitDevice	1	*	ValidDevice	LineupUnitDevices	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode

[Top](#)

Entity Type Name - LineupUnitEmployee							
Description	The employees associated with a unit for a given lineup.						
Base Table Name	lineup_persl						
View Name	cmvLineupUnitEmployee						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
EmployeeId	empid	int32	no	readOnly	Employee id		
IsPrimary [default = false]	primary_empid	boolean	no	readOnly	Primary employee on unit. T = True, F = False		
LineupName	lineup_name	string(30)	no	readOnly	The lineup name		
UnitId	unid	string(10)	no	readOnly	The unit identifier		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	LineupUnitEmployee	1	*	DefinedEmployee	LineupUnitEmployees	EmployeeId	EmployeeId
LineupUnitEmployee	LineupUnitEmployeeDevice	1	*	LineupUnitEmployee	LineupUnitEmployeeDevices	LineupName, UnitId, EmployeeId	LineupName, UnitId, EmployeeId
LineupUnit	LineupUnitEmployee	1	*	LineupUnit	LineupUnitEmployees	LineupName, UnitId	LineupName, UnitId

[Top](#)

Entity Type Name - LineupUnitEmployeeDevice							
Description	Stores devices used by units, vehicles and personnel in a lineup. CR 1-6PGD42: PLT						
Base Table Name	lineup_device						
View Name	cmvLineupUnitEmployeeDevice						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Description	description	string(50)	yes	readOnly	Description		
DeviceAlias	device_alias	string(20)	yes	readWrite	User-friendly alias name for device		
DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system		
DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT		
EmployeeId	empid	int32	no	readOnly	If owner = 1, this column has the employee that owns the device. Links to lineup_persl.empid		
GpsProtocol [default = 0]	gps_protocol	int16	no	readOnly	GPS protocol. I/Tracker uses the GPS protocol to know how to communicate with the device. The cad DeviceGpsProtocol parameter table defines the valid GPS protocols		
IsTrackable	is_trackable	boolean	no	readOnly	Is device trackable? 0 = False, 1 = True		
IsTrackingDeviceForEmployee	tdevice_for_emp	boolean	no	readOnly	Specifies if this device is used as the tracking device for the employee. 1= True, 0 = False		
IsTrackingDeviceForUnit	tdevice_for_unit	boolean	no	readOnly	Specifies if this device is used as the tracking device for the unit. 1= True, 0 = False		
LineupName	lineup_name	string(30)	no	readOnly	Lineup name		
Owner {hidden}	owner				Owner. 0 = unit, 1 = employee		
UnitId	unid	string(10)	no	readOnly	Unit ID. If owner = 0, this is the unit that owns the device. If owner = 1, this is the employee's unit.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
LineupUnitEmployee	LineupUnitEmployeeDevice	1	*	LineupUnitEmployee	LineupUnitEmployeeDevices	LineupName, UnitId, EmployeeId	LineupName, UnitId, EmployeeId
ValidDevice	LineupUnitEmployeeDevice	1	*	ValidDevice	LineupUnitEmployeeDevices	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode

[Top](#)

Entity Type Name - LineupUnitEquipment							
Description	The equipment for a unit in a given lineup						
Base Table Name	lineup equip						
View Name	cmvLineupUnitEquipment						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
EquipmentCount	num equip	int32	no	readOnly	Number of pieces of this equipment		
 EquipmentName	equip	string(10)	no	readOnly	The equipment		
 LineupName	lineup_name	string(30)	no	readOnly	Lineup name		
 UnitId	unid	string(10)	no	readOnly	The unit identifier		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
LineupUnit	LineupUnitEquipment	1	*	LineupUnit	LineupUnitEquipment	LineupName, UnitId	LineupName, UnitId

 [Top](#)

Entity Type Name - LocationOfInterestData					
Description	This table contains information about the type of data and where it is stored for the Location of Interest function in I/CAD.				
Base Table Name	loi_data				
View Name	cmv.LocationOfInterestData				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	num_1	string(12)	yes	readOnly	Agency Event Number. Contains the number corresponding to the events which occurred at the same location.
AssociatedDataCreatedTime	cdts	dateTimeOffset	no	readOnly	Associated data creation date/time stamp.
AssociatedDataId	idx	int32	no	readOnly	Contains the event id of a recent event or special situation mlsink or an Informer rec_num.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Contains the date/time of when the record was created.
IsActive {hidden}	current				T/F, indicates if row is active or deleted
 LOIDataId	unique_id	guid	no	readOnly	A binary value that uniquely identifies each row
LOIDataType	dtype	string(1)	no	readOnly	Data Type of LOI response. The valid values are defined in the CAD SearchInfo parameter table.
LOISchemaType	loi_schema	string(1)	yes	readOnly	Location of Interest schema. Indicates whether the schema for loi data is (C)ad or (R)ms.
Location	loc	string(80)	yes	readOnly	Location. Location found in the location of interest search.
Priority	priority	string(1)	yes	readOnly	Contains the priority value assigned to the location of interest data.
SearchId	eid	int32	no	readOnly	The employee or event id for which the search is conducted, note that employee ids are represented as negative numbers to distinguish them from event ids
SourceDbConfigName	db_config	string(30)	yes	readOnly	The source database configuration name
SourceType	source	string(16)	yes	readOnly	Defines the source event type or special situation type, or Informer.
SpecialSituationRemarks	remarks	string(20)	yes	readOnly	This column is retrieved from the remarks column in the special situation table.
SupplementalItemNumber	row_num	int32	yes	readOnly	This holds the row number associated with a supplemental table specified in the loi search.
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time stamp.

 [Top](#)

Entity Type Name - LocationOfInterestSearch					
Description	Stores location information needed for Location of Interest (LOI) searches				
Base Table Name	loi_search				
View Name	cmvLocationOfInterestSearch				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
Apartment	apt	string(128)	yes	readOnly	Apartment number component of the location
Area	area	string(128)	yes	readOnly	Area component of the location
CreatedTime	cdts	dateTimeOffset	no	readOnly	The timestamp when the record was created
CrossStreet1	xstreet1	string(128)	yes	readOnly	Feature name and type of one street which intersects the location
CrossStreet2	xstreet2	string(128)	yes	readOnly	Feature name and type of one street which intersects the location
DirectionPrefix	dirpre	string(128)	yes	readOnly	Direction prefix component of the location
DirectionSuffix	dirsuf	string(128)	yes	readOnly	Direction suffix component of the location
IsActive {hidden}	current				Indicates if record is active
Location1	loc_fld1	string(128)	yes	readOnly	Generic location component of the location
Location2	loc_fld2	string(128)	yes	readOnly	Generic location component of the location
Location3	loc_fld3	string(128)	yes	readOnly	Generic location component of the location
Location4	loc_fld4	string(128)	yes	readOnly	Generic location field
Municipality	mun	string(128)	yes	readOnly	Municipality component of the location
NoLOISearch	no_loi_search	boolean	no	readOnly	LOI Search Flag from the sp_ad table. If TRUE (T), no LOI search is conducted for events at this location
NullParseData	null_p_data	boolean	no	readOnly	T if null p_data passed in
ParseType	parse_type	int32	no	readOnly	Parse type. Indicates how the location was parsed. -1= unknown, 0= street, 1= intersection, 2= commonplace, 3= alarm, 4= X,Y location.
 SearchId	id	guid	no	readOnly	Guid to uniquely identify row
SpecialSituationSearch	search_flag	boolean	no	readOnly	Special Situation Seach flag from the sp_ad table. If TRUE(T), a Special Situation search is conducted for events at this location.
StreetName	feaname	string(240)	yes	readOnly	Feature name component (street name) of the location
StreetNumber	stnum	string(128)	yes	readOnly	Street number house number) component of the location
StreetType	featype	string(128)	yes	readOnly	Feature type component of the location
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The timestamp when the record was updated
XCoordinate	x_cord	int32	no	readOnly	X map coordinate for the location
YCoordinate	y_cord	int32	no	readOnly	Y map coordinate for the location

 [Top](#)

Entity Type Name - LocationOfInterestSearchStatus						
Description	Holds the status information for location of interest searches corresponding to an employee or event id.					
Base Table Name	loi_status					
View Name	cmvLocationOfInterestSearchSta					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
AssociatedId	id	int32	no	readOnly	The employee or event id for which the search is conducted, note that employee ids are represented as negative numbers to distinguish them from event ids	

CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp
DatabaseConfiguration	db_config	string(30)	no	readOnly	The database configuration fo the search
IsActive {hidden}	current				T/F, indicates if the row is active or deleted
IsForCommonEventId	is_cid	boolean	no	readOnly	0/1 - 0 for employee id, 1 for event id
SearchStatus	status	string(1)	no	readOnly	The status of the search. Defaults are: S= Started, O= Ok (finished successfully), F=Failed, but these defaults can be overridden in the cad LoiStatusTypes parameter list.
 SearchStatusId	unique_id	guid	no	readOnly	An arbitrary unique identifier for the row
SearchType	search_type	string(2)	no	readOnly	The type of search being conducted, such as SU (supplemental) or SS (special situation)
SearchTypeDescription	search_type_text	string(30)	no	readOnly	Search type description
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp

 [Top](#)

Entity Type Name - MapCommonPlace							
Description	The co_pl table contains common place related data used for location verification. CADDDBM has facilities for maintaining common place names by utilizing this table.						
Base Table Name	co_pl						
View Name	cmvMapCommonPlace						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CommentText	msg	string(2000)	yes	readOnly	This column contains a message about the commonplace name.		
LocationSubtype	location_subtype	string(10)	yes	readOnly	location subtype for MPS		
LocationType	location_type	string(10)	yes	readOnly	location type for MPS		
MapCommonPlaceId	mslink	int32	yes	readOnly	Link to graphic cell of the common place.		
 MapCommonPlaceName	com_nme	string(80)	no	readOnly	Common name assigned to a common place.		
MapSegmentId	fea_mslink	int32	yes	readOnly	Mslink of street segment		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The mslink of the associated special address.		
Soundex	soundex	string(4)	yes	readOnly	Soundex of common name that is assigned to common place.		
StreetNumber	str_num	string(15)	yes	readOnly	Street number at common place		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapCommonPlace	CommonPlaceContact	1	*	MapCommonPlace	CommonPlaceContacts	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName
MapCommonPlace	CommonPlacePerson	1	*	MapCommonPlace	CommonPlacePeople	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName
MapCommonPlace	CommonPlaceProperty	1	*	MapCommonPlace	CommonPlaceProperties	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName
MapCommonPlace	CommonPlaceVehicle	1	*	MapCommonPlace	CommonPlaceVehicles	MapSpecialAddressId, MapCommonPlaceName	MapSpecialAddressId, MapCommonPlaceName
MapSpecialAddress	MapCommonPlace	1	*	MapSpecialAddress	MapCommonPlaces	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - MapEdge							
Description	Geographic and traffic information about each individual street segment.						
Base Table Name	cd_edge						
View Name	cmvMapEdge						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
BlockageMask	blockage_mask	int32	yes	readOnly	Info about impediments to forward progress at both ends of street segment 1 = wrong way forward 2 = hard block forward 4 = soft block forward 256 = wrong way backward 512 = hard block backward 1024 = soft block backward		
EdgeLength	edge_length	double	yes	readOnly	Length of street segment in map UORs(units of resolution)		
EntryAngle	entry_angle	int32	yes	readOnly	Direction travelled to enter street from its beginning- node end.		
ExitAngle	exit_angle	int32	yes	readOnly	Direction travelled to exit street segment at its terminal node end.		
FeatureType	fcode	string(12)	yes	readOnly	Identifier for feature type this record represents. For example, fcode = 1 might translate to Interstate, fcode = S might translate to Shoreline.		
FromMapNodeId	from_node	int32	yes	readOnly	Link to the cd_node record describing coordinates at the begin point of the street segment		
 MapEdgeId	mslink	int32	no	readOnly	Unique identifier for each individual cd_edge record.		
MapSegmentId	fea_mslink	int32	yes	readOnly	Link to corresponding segme record containing location info for the street segment		
MapStreetNameId	text_id	int32	yes	readOnly	Actual name of the street represented in part or in full by segment described in this record		
MaxHeight	height	double	yes	readOnly	Maximum vehicle height street segment can accomodate		
MaxSpeed	speedlimit	int16	yes	readOnly	Maximum speed a vehicle may legally travel along street segment.		
MaxWeight	weight	double	yes	readOnly	Maximum vehicle weight the street segment can sustain.		
MaxWidth	width	double	yes	readOnly	Maximum vehicle width street segment can accomodate.		
ObstacleMask	obstacle_mask	int32	yes	readOnly	Info describing obstacles which delay, but do not completely impede, forward progress at the begin and/or end node of street segment. 1 = stop sign forward 2 = caution light forward 4 = red light forward 8 = flashing red forward 16 = no right on red forward 256 = stop sign backward 512 = caution light backward 1024 = red light backward 2048 = flashing red backward 4096 = no right on red backward		
TileNumber	tile_num	int32	yes	readOnly	The tile in which an edge is located.		
ToMapNodeId	to_node	int32	yes	readOnly	Link to cd_node record describing the coordinate location of the street segment termination point.		
TraversalRisk	riskcost	double	yes	readOnly	Assigned value indicating the risk involved traversing the street segment. For example, there is more risk traversing a street with an elementary school than there is traversing a country road.		
TraversalTime	timecost	double	yes	readOnly	Number of seconds it takes to traverse the street segment.		
TraversalTimeModifier	timefactor	double	yes	readOnly	Factor applied to timecost at certain times of day. For example, at 3 pm it may take twice as long as normal to traverse the segment		
TurnMask	turn_mask	int32	yes	readOnly	Info describing limitations on forward progress at both begin and end nodes of the street segment 1= no straight ahead forward 2 = no bear right forward 4 = no right turn forward 8 = no hard right forward 16 = no u turn forward 32 = no hard left forward 64 = no left turn forward 128 = no bear left forward 256 = no straight ahead backward 512 = no bear right backward 1024 = no right turn backward 2048 = no hard right backward 4096 = no u turn backward 8192 = no hard left backward 16384 = no left turn backward 32768 = no bear left backward		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapNode	MapEdge	0..1	*	ToMapNode	ToMapEdges	MapNodeId	ToMapNodeId
MapNode	MapEdge	0..1	*	FromMapNode	FromMapEdges	MapNodeId	FromMapNodeId
MapSegment	MapEdge	0..1	*	MapSegment	MapEdges	MapSegmentId	MapSegmentId
MapStreet	MapEdge	0..1	*	MapStreet	MapEdges	MapStreetId	MapStreetNameId

 [Top](#)

Entity Type Name - MapNode	
Description	Describes the end of every segment, including blockages, intersections, and coordinates. There is one record for every end of every segment.
Base Table Name	cd_node
View Name	cmvMapNode
Monitored	No

Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
BlockageMask	node_mask	int32	yes	readOnly	Mask indicating blockages. 1 = node blocked 2 = use overrides 4 = use obstacle costs		
MapIntersectionId	fea_mslink	int32	yes	readOnly	Map Linkage. Mslink of associated inter record.		
 MapNodeId	mslink	int32	no	readOnly	Unique graphic cell id		
TileNumber	tile_num	int32	yes	readOnly	The tile in which a node is located.		
XCoordinate	xvalue	int32	yes	readOnly	X-coordinate of the node.		
YCoordinate	yvalue	int32	yes	readOnly	Y-coordinate of the node.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapNode	MapEdge	0..1	*	ToMapNode	ToMapEdges	MapNodeId	ToMapNodeId
MapNode	MapEdge	0..1	*	FromMapNode	FromMapEdges	MapNodeId	FromMapNodeId

 [Top](#)

Entity Type Name - MapSegment							
Description	This table contains street segment data. A street segment is most often the portion of a street bounded by two intersections. This table holds the necessary geographical info for each segment.						
Base Table Name	segme						
View Name	cmvMapSegment						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AddressType	addtyp	int32	no	readOnly	Address Type. This column defines the address type code. If set=0, then the street addresses are odd/even, if set=1, then street addresses are contiguous.		
CrossStreetId1	xst_id1	int32	yes	readOnly	Cross Street ID 1. The text_id of the cross_street at the from node. Using this value the street information can be retrieved from the st_cd table.		
CrossStreetId2	xst_id2	int32	yes	readOnly	Cross Street ID 2. The text_id of the cross_street at the to_node. Using this value the street information can be retrieved from the st_cd table.		
LeftArea	areal	string(40)	yes	readOnly	Left Area. The area in which the left side of the street segment resides.		
LeftCensusBlock	bkl	string(8)	yes	readOnly	Left Census Block. Census block (small compact area bounded by streets and other prominent physical features with certain legal boundaries) associated with left side of segment. Not currently used by I/CAD.		
LeftCensusTrack	etkl	int32	yes	readOnly	Left Census Track. Small, locally delineated statistic area within the selected county, having stable bounds and designd to have homogenous demographic characteristics and associated w/ left side o segment. Not used by I/CAD.		
LeftCommonplaceName	copll	string(80)	yes	readOnly	Commonplace name for left side of street segment		
LeftEsz	eszl	int32	yes	readOnly	Left Emergency Service Zone. The ESZ value in which the left side of the street segment resides.		
LeftFromStreetNumber	fraddl	string(11)	yes	readOnly	Address at from node on left side.		
LeftLocation2	loc_fld2l	string(5)	yes	readOnly	Generic location field		
LeftLocation3	loc_fld3l	string(5)	yes	readOnly	Generic location field		
LeftLocation4	loc_fld4l	string(5)	yes	readOnly	Generic location field		
LeftMinorCivilDivision	muncdl	int32	yes	readOnly	Federal ID code on the left side of the segment. This column is a Minor Civil Division (MCD), which is a legally defined subcounty such as a town or township. Not currently used by I/CAD.		
LeftMunicipality	munl	string(40)	yes	readOnly	Left Municipality. The municipality in which the left side of the segment resides.		
LeftToStreetNumber	toaddl	string(11)	yes	readOnly	To Address Left. Stores the to address associated with the left side of the segment. Must be right justified.		
LeftZipCode	zipl	string(10)	yes	readOnly	Zip Code on Left. The zip code in which the left side of the segment resides.		
 MapSegmentId	mslink	int32	no	readOnly	Map Link. A link to the Map graphics element of the street segment.		
MapStreetId	text_id	int32	no	readOnly	Text ID. The text identification of the street name associated with this segment. This is the variable link to get information concerning the street from the st_cd table		
Mapid {hidden}	mapid						
RightArea	arear	string(40)	yes	readOnly	Right Area. The area in which the right side of the street segment resides.		
RightCensusBlock	bkr	string(8)	yes	readOnly	Right Census Block. Census block (small compact area bounded by streets and other prominent physical features with certain legal boundaries) associated with right side of the segment. Not currently used by I/CAD.		
RightCensusTrack	ctkr	int32	yes	readOnly	Right Census Track. Small, locally delineated statistic areas within selected county, having stable bounds and designed to have homogenous demographic characteristics and associated w/right side o segment. Not used by I/CAD.		
RightCommonPlaceName	coplr	string(80)	yes	readOnly	Commonplace name for right side of street segment		
RightEsz	eszr	int32	yes	readOnly	Right Emergency Service Zone The ESZ value in which the right side of the street segment resides.		
RightFromStreetNumber	fraddr	string(11)	yes	readOnly	From Address Right. Stores the from address associated with the right side of the segment. Must be right justified.		
RightLocation2	loc_fld2r	string(5)	yes	readOnly	Generic location field		
RightLocation3	loc_fld3r	string(5)	yes	readOnly	Generic location field		
RightLocation4	loc_fld4r	string(5)	yes	readOnly	Generic location field		
RightMinorCivilDivision	muncdr	int32	yes	readOnly	Federal ID code on the right side of the segment. This column is a Minor Civil Division (MCD), which is a legally defined subcounty such as a town or township. Not currently used by I/CAD.		
RightMunicipality	munr	string(40)	yes	readOnly	Right Municipality. The municipality in which the right side of the segment resides.		
RightToStreetNumber	toaddr	string(11)	yes	readOnly	To Address Right. Stores the address associated with the right side of the segment. Must be right justified.		
RightZipCode	zipr	string(10)	yes	readOnly	Zip Code on Right. The zip code in which the right side of the segment resides.		
Sdirpre {hidden}	sdirpre						
Sdirsuf {hidden}	sdirsuf						
Sfeaname {hidden}	sfeaname						
Sfeatyp {hidden}	sfeatyp						
StreetType	class	string(12)	yes	readOnly	Classification Code. The classification code of the segment describes the road type, the same as cfcc (Census Features Class Codes a census classification describing the road type).		
TigerId	segid	int32	yes	readOnly	Segment ID. The TIGER (Data) ID of the segment.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSegment	CatalogedAlarm	0..1	*	MapSegment	CatalogedAlarms	MapSegmentId	MapSegmentId
MapSegment	MapEdge	0..1	*	MapSegment	MapEdges	MapSegmentId	MapSegmentId
MapStreet	MapSegment	1	*	MapStreet	MapSegments	MapStreetId	MapStreetId
MapStreet	MapSegment	0..1	*	CrossStreet1	CrossStreet1Segments	MapStreetId	CrossStreetId1
MapStreet	MapSegment	0..1	*	CrossStreet2	CrossStreet2Segments	MapStreetId	CrossStreetId2
MapSegment	RoadRestriction	1	*	SourceSegment	SourceRestrictions	MapSegmentId	SourceSegmentId
MapSegment	RoadRestriction	0..1	*	DestSegment	DestRestrictions	MapSegmentId	DestSegmentId
MapSegment	RoadRestrictionSegment	1	*	MapSegment	RoadRestrictionSegments	MapSegmentId	MapSegmentId

 [Top](#)

Entity Type Name - MapSpecialAddress							
Description	The special address table is used to assign a different ESZ than the street segment where the address resides. This table is searched during Location Verify.						
Base Table Name	sp_ad						
View Name	cmvMapSpecialAddress						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AlarmSymbol	alarm_sym	string(6)	yes	readOnly	Alarm symbol		
Apartment	lv_aprt	string(5)	yes	readOnly	Apartment Number. This column contains the apartment number or suite number of the special address.		
Area	lv_area	string(40)	yes	readOnly	Area Indicator. This column contains the area code for the special address.		
CommentText	msg	string(2000)	yes	readOnly	Message. This column contains a message about the special address.		
CommonPlaceSymbol	copl_sym	string(6)	yes	readOnly	Commonplace symbol		
CrossStreetId1 [default = -1]	text_id	int32	no	readOnly	Text ID. This is a join column to the st_cd table. It defines the street name. Text_id is set to -1 for special addresses that are only defined by (X,Y) coordinates.		
CrossStreetId2 [default = -1]	text_id2	int32	no	readOnly	The link to the st_cd table for the second street in the intersection		
Esz	esz	int32	yes	readOnly	Emergency Service Zone. The ESZ of the special address. This could specify a unique ESZ, as in a firebox for a highrise building. This value corresponds to an s_esz value in the agency_esz table.		
ExpiredTime	edts	dateTimeOffset	yes	readOnly	The expiration date timestamp of a special address record		
IsLoiNotSearched	no_loi_search	string(1)	yes	readOnly	Location of Interest Search Flag. This column indicates whether a LOI search is to be conducted on the special address.		
IsSpecialSituationSearched	search_flag	string(1)	yes	readOnly	Special Situation Search Flag Indicator. This column indicates whether a special situation table search is to be conducted on this address.		
Location1	loc_fld1	string(5)	yes	readOnly	Generic location field		
Location2	loc_fld2	string(5)	yes	readOnly	Generic location field		
Location3	loc_fld3	string(5)	yes	readOnly	Generic location field		
Location4	loc_fld4	string(5)	yes	readOnly	Generic location field		
MajorEventId	majevt_id	string(10)	yes	readOnly	Major Event Identification. This coulumn contains the pointer to the major incident plan.		
MapCommonPlaceName	com_nme	string(80)	yes	readOnly	Common Place Name. This column contains the name of a common place defined for the Location Verify.		
MapFeatureId	fcode	string(12)	yes	readOnly	Maps to the netfea record containing the symbol (cell) to be placed on the map for this special address record.		
MapLevels	maplevs	string(200)	yes	readOnly	Assigned map level(s) for special address		
MapSegmentId	fea_mslink	int32	yes	readOnly	Feature Mslink. This is the linkage to the street segment of the special address.		
 MapSpecialAddressId	mslink	int32	no	readOnly	Map Link. This column allows the placement of a special symbol in the map to designate a special address. The symbol could be graphically selected to review this information. The mslink value is generated from the mscatalog table.		
Municipality	mun	string(40)	yes	readOnly	Municipality. This column defines the municipality of the special address.		
Priority	priority	int32	yes	readOnly	Location priority. Null if no priority.		
PriorityExpiredTime	priority_edts	dateTimeOffset	yes	readOnly	Priority expiration. Null if no expiration.		
SpecialAddressSymbol	spad_sym	string(6)	yes	readOnly	Special address symbol		
StreetNumber	st_num	string(15)	yes	readOnly	Street Number. The street number of the special address.		
XCoordinate [default = 0]	x_cord	int32	no	readOnly	X-coordinate. Location of the street segment which the special address references. X, Y coordinates will be set to (0,0) if user does not specify the coordinates.		
YCoordinate [default = 0]	y_cord	int32	no	readOnly	Y-coordinate. Location of the street segment which the special address references. X, Y coordinates will be set to (0,0) if user does not specify the coordinates.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSpecialAddress	CatalogedAlarm	1	*	MapSpecialAddress	CatalogedAlarms	MapSpecialAddressId	MapSpecialAddressId
MapSpecialAddress	MapCommonPlace	1	*	MapSpecialAddress	MapCommonPlaces	MapSpecialAddressId	MapSpecialAddressId
MapStreet	MapSpecialAddress	1	*	CrossStreet1	CrossStreet1SpecialAddresses	MapStreetId	CrossStreetId1
MapStreet	MapSpecialAddress	1	*	CrossStreet2	CrossStreet2SpecialAddresses	MapStreetId	CrossStreetId2
MapSpecialAddress	SpecialAddressContact	1	*	MapSpecialAddress	SpecialAddressContacts	MapSpecialAddressId	MapSpecialAddressId
MapSpecialAddress	SpecialAddressEventType	1	*	MapSpecialAddress	SpecialAddressEventTypes	MapSpecialAddressId	MapSpecialAddressId
MapSpecialAddress	SpecialAddressPerson	1	*	MapSpecialAddress	SpecialAddressPeople	MapSpecialAddressId	MapSpecialAddressId
MapSpecialAddress	SpecialAddressProperty	1	*	MapSpecialAddress	SpecialAddressProperties	MapSpecialAddressId	MapSpecialAddressId
MapSpecialAddress	SpecialAddressVehicle	1	*	MapSpecialAddress	SpecialAddressVehicles	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - MapStreet							
Description	This table contains all unique street names. Note that two different streets do not have different entries if they have the same name, but are located in separate municipalities. Rows with virtualcode =F' are generated by map data. Rows with virtualcode=T' may be generated by CADDBM. A row with virtualcode = T' may have the same feature name, feature type, direction prefix and direction suffix as a real row with virtualcode=F'.						
Base Table Name	st_cd						
View Name	cmvMapStreet						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AliasedStreetId	alias	int32	yes	readOnly	Alias Text ID. If this name is an alias for another street, the text_id of that street is stored in this field. Otherwise the field is NULL. The field is set when a street is assigned an alias.		
DirectionPrefix	dirpre	string(2)	yes	readOnly	Direction Prefix. The direction prefix, N, NW, SE, and so on.		
DirectionSuffix	dirsuf	string(2)	yes	readOnly	Direction Suffix. The direction suffix, N, NW, SE, and so on.		
IsVirtual	virtualcode	boolean	no	readOnly	If virtualcode = 'T', then this is a virtual st_cd record with no link to the segme, cd_edge or cd_node tables. Instead, this row links to record(s) in sp_ad. If virtualcode = 'F', then this is a normal st_cd record.		
 MapStreetId	text_id	int32	no	readOnly	Text ID. The text_id is a unique identifier assigned to each street name which is equal to the "text_id" column in the segme table.		
Soundex	soundex	string(4)	yes	readOnly	Soundex Code. The soundex code for the feature name.		
StreetName	feaname	string(30)	yes	readOnly	Feature Name. Stores the name of the street.		
StreetType	featyp	string(4)	yes	readOnly	Feature Type. Stores the feature type. For example, road or street.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapStreet	MapEdge	0..1	*	MapStreet	MapEdges	MapStreetId	MapStreetNameId
MapStreet	MapSegment	1	*	MapStreet	MapSegments	MapStreetId	MapStreetId
MapStreet	MapSegment	0..1	*	CrossStreet1	CrossStreet1Segments	MapStreetId	CrossStreetId1
MapStreet	MapSegment	0..1	*	CrossStreet2	CrossStreet2Segments	MapStreetId	CrossStreetId2
MapStreet	MapSpecialAddress	1	*	CrossStreet1	CrossStreet1SpecialAddresses	MapStreetId	CrossStreetId1
MapStreet	MapSpecialAddress	1	*	CrossStreet2	CrossStreet2SpecialAddresses	MapStreetId	CrossStreetId2

 [Top](#)

Entity Type Name - MdtLoggedOnEmployee	
Description	The employees that have been logged on via an MDT.
Base Table Name	mdt_logged_on_persl
View Name	cmvMdtLoggedOnEmployee
Monitored	No

Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs the device ID must be a positive integer.		
 DeviceSubTypeCode	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
 DeviceTypeCode	device_type	int16	no	readOnly	Device type. 6 = MDT. The cad DeviceType parameter list maps the device type number to a configurable display name		
 EmployeeId	empid	int32	no	readOnly	The employee that was logged on via the MDT.		
IsPrimary	primary_empid	boolean	no	readOnly	Is primary employee for the MDT. 1 = True, 0 = False. The primary employee is used to determine the security context for the MDT.		
 UnitId	unid	string(10)	no	readOnly	The unit id associated with the MDT.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ActiveUnit	MdtLoggedOnEmployee	1	*	ActiveUnit	MdtLoggedOnEmployees	UnitId	UnitId
ValidDevice	MdtLoggedOnEmployee	1	*	ValidDevice	MdtLoggedOnEmployees	DeviceId, DeviceTypeCode, DeviceSubTypeCode	DeviceId, DeviceTypeCode, DeviceSubTypeCode

 [Top](#)

Entity Type Name - Message							
Description	Holds all messages sent between nodes. NOTE: The Destinations table holds the message destination information. The Messa table holds the message origination information. The Msg_Text table has the text of the messages.						
Base Table Name	messa						
View Name	cmvMessage						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	yes	readOnly	The agency event number associated with the CAD message		
Attributes [default = 0] [Monitored]	flags	int32	no	readOnly	Flags column contains message attributes. Each bit represents a boolean value. 1 = Message has attachments		
CommonEventCallId	event_call_id	int32	yes	readOnly	For callback messages this is the associated event call		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time when the record was created		
ForwardedFromMessageId	fwd_from_msg_num	int32	yes	readOnly	Message number from which this message was forwarded		
IsReceiptRequested [Monitored]	critical	boolean	no	readOnly	T/F, critical, want receipt.		
 MessageId [Monitored]	msg_num	int32	no	readOnly	Message number. Unique number generated by CAD (ndxed num of message table) Used as the main pointer to all messages, lets receiver get messages from database. Only data sent in packets for administrative messages		
MessageSendType [Monitored]	message_send_type	int16	no	readOnly	Indicates how this message was sent: 0 - Regular message, 1 - Scheduled message, 2 - Active recurring message template, 3 - Inactive recurring message template		
MessageText	msg_text	string(Max)	yes	readOnly	The text of the message. This column requires a full text search index so that the contains predicate can be used in queries.		
MessageType [default = 0] [Monitored]	msg_type	int32	no	readOnly	0 (regular message) 1 (system message) 2 (notification message)		
OriginalMessageId	orig_msg_num	int32	no	readOnly	The original message number from which the message came		
Priority [default = 9] [Monitored]	msg_prior	int16	no	readOnly	0-9, The message priority specified by the sender.		
RepliedToMessageId	reply_to_msg_num	int32	yes	readOnly	Message number that was acknowledged (replied to)		
SendingEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee id number of the person originating the message. The id of the person logged on and sending the message comes from the persl table or the employee is of the person in the unit if it is from a MDT.		
SendingTerminal [Monitored]	cterm	string(15)	no	readOnly	Terminal of the Originating Message. The nodename of the sender.		
SendingTime [Monitored]	send_dts	dateTimeOffset	no	readOnly	Date/time stamp when message was actually sent		
Subject [Monitored]	subject	string(40)	yes	readOnly	Subject Header of Message. This field is seen on the Send Message and Receive Message forms.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The time when the record was updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	Message	0..1	*	AgencyEvent	Messages	AgencyEventId	AgencyEventId
Message	MessageAttachment	1	*	Message	MessageAttachments	MessageId	MessageId
CommonEventCall	Message	0..1	*	CommonEventCall	Messages	CommonEventCallId	CommonEventCallId
Message	MessageDestination	1	*	Message	MessageDestinations	MessageId	MessageId
Message	MessageReceive	1	*	Message	MessageReceives	MessageId	MessageId

 [Top](#)

Entity Type Name - MessageAttachment							
Description	Associates a message with an attachment						
Base Table Name	message_attachment						
View Name	cmvMessageAttachment						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AttachmentId	attachment_id	guid	no	readOnly	Uniquely identifies an attachment		
CreatedEmployeeId	cpers	int32	no	readOnly	The employee id of the person that created this record		
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that was used to create this record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The time when this record was created		
 MessageId	msg_num	int32	no	readOnly	Message number		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AttachmentInfo	MessageAttachment	1	*	AttachmentInfo	MessageAttachments	AttachmentId	AttachmentId
Message	MessageAttachment	1	*	Message	MessageAttachments	MessageId	MessageId

 [Top](#)

Entity Type Name - MessageDestination							
Description	This table holds the message destination information. The messa table holds the message origination information and the text of the message.						
Base Table Name	message_dest						
View Name	cmvMessageDestination						
Monitored	No						

Properties								
Property Name	Base Column	Data Type	NULL	Access Type	Description			
CreatedEmployeeId	cpers	int32	no	readOnly	Employee that created the record			
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where record was created			
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp of this record			
 Destination	destination	string(80)	no	readOnly	If destination_type is not a group or filter - the actual destination. If destination_type is a group or filter - the overall destination.			
DestinationSubtype	destination_subtype	int16	no	readOnly	Destination subtype. -1: Unknown, 0: CAD, 1: DISP, 2: CALL, 3: STATIC, 4: BG,CALLBACK, 5: MDT, 6: MDT_SERVER, 7: NETVIEWER, 8: EMAIL, 9: PAGER, 10: PRINTER. Parameter data maps the number to a user-configurable display name			
 DestinationType	destination_type	int16	no	readOnly	Destination main type: 0 = TERM, 1 = PERSON, 2 = PAGER, 3 = STATION, 4 = EMPID, 5 = GROUP, 6 = FILTER			
 MessageId	msg_num	int32	no	readOnly	Message number, a unique identifier for the message			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Message	MessageDestination		1	*	Message	MessageDestinations	MessageId	MessageId

 [Top](#)

Entity Type Name - MessageGroupMember							
Description	Used in caddbm and cad to define a group to which messages can be sent.						
Base Table Name	msg_group						
View Name	cmvMessageGroupMember						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp.		
Destination	destination	string(80)	yes	readOnly	The node name, unit id, page id, email address, etc.		
EmployeeId	empid	int32	yes	readOnly	Used to store empid when the message type is PERSON to ensure a unique selection.		
Filter	filter	string(15)	yes	readOnly	Used in CADDDBM and CAD for message group. The user defined Static group can associate to a filter and by selecting a filtered type, the group list is smaller and more specific.		
FirstName	fname	string(50)	yes	readOnly	The first name of a person.		
GroupName	grp_name	string(15)	no	readOnly	The name of a group.		
LastName	lname	string(50)	yes	readOnly	The last name of a person.		
 MemberId	unique_id	guid	no	readOnly	Unique identifier		
MemberSubtype	sub_type	string(15)	yes	readOnly	Destination sub-type, such as CAD, MDT, PAGER, EMAIL, or other application		
MemberType	main_type	string(8)	no	readOnly	Destination type, such as PERSON, PAGER, STATION, or GROUP.		
MiddleInitial	mi	string(1)	yes	readOnly	The middle initial of a person.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
DefinedEmployee	MessageGroupMember	0..1	*	DefinedEmployee	MessageGroupMembers	EmployeeId	EmployeeId

 [Top](#)

Entity Type Name - MessageReceive							
Description	This table is related to the message_dest table. Destinations are detailed from the message_dest table at a more granular (device/terminal or person) level. Status and auditing information is recorded.						
Base Table Name	message_receive						
View Name	cmvMessageReceive						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee that created the record		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal where record was created		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp of this record		
DeletedEmployeeId	deleted_pers	int32	yes	readOnly	Person who deleted the message		
DeletedTerminal	deleted_term	string(15)	yes	readOnly	Terminal on which the message was deleted		
DeletedTime	deleted_dts	dateTimeOffset	yes	readOnly	Date/time stamp when message was deleted		
DeliveredEmployeeId	delivered_pers	int32	yes	readOnly	Person to whom message was delivered (Mobile users)		
DeliveredTerminal	delivered_term	string(15)	yes	readOnly	Terminal or unit to which the message was delivered (Mobile users)		
DeliveredTime	delivered_dts	dateTimeOffset	yes	readOnly	Date/time stamp when message was delivered (Mobile users)		
 Destination [Monitored]	destination	string(80)	no	readOnly	More granular level of message_dest.destination		
 DestinationType [Monitored]	destination_type	int16	no	readOnly	0 = TERM, 1 = PERSON, 2 = PAGER, 3 = STATION, 4 = EMPID		
 MessageId [Monitored]	msg_num	int32	no	readOnly	Message number, a unique identifier for the message		
MessageStatus [Monitored]	status	int16	no	readOnly	Latest status of the message. -1 = Not Received, 0 = Received and New (not read), 1 = Delivered, 2 = Read, 3 = Deleted		
ReadEmployeeId	read_pers	int32	yes	readOnly	Person who read the message		
ReadTerminal	read_term	string(15)	yes	readOnly	Terminal on which message was read		
ReadTime	read_dts	dateTimeOffset	yes	readOnly	Date/time stamp when message was read		
ReceivedEmployeeId	received_pers	int32	yes	readOnly	Person who received the message		
ReceivedTerminal	received_term	string(15)	yes	readOnly	Terminal on which the message was received		
ReceivedTime	received_dts	dateTimeOffset	yes	readOnly	Date/time stamp when message was received.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp of this record		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Message	MessageReceive	1	*	Message	MessageReceives	MessageId	MessageId

 [Top](#)

Entity Type Name - MultiEventTransportLocation					
Description	This table stores a list of transport location information for use in Transport commands.				
Base Table Name	trans_des				
View Name	cmvMultiEventTransportLocation				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	num_1	string(12)	yes	readOnly	Agency event number.
CommonEventId	eid	int32	no	readOnly	Unique Event Id Number generated by the system. A value of 0 indicates that there is no associated event.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Create date time stamp.
DestinationLocation	location	string(240)	no	readOnly	Transport location text.
DestinationXCoordinate [default = 0]	x_coord	int32	no	readOnly	This column represents the X coordinate of the node associated with the transport destination.

DestinationYCoordinate [default = 0]	y_coord	int32	no	readOnly	This column represents the Y coordinate of the node associated with the transport destination.		
IsDestinationVerified	verified	boolean	no	readOnly	If the location verified. ("Y" or "N")		
IsOriginVerified [default = false]	origin_verified	boolean	no	readOnly	Origin verified flag		
OriginLocation	origin_location	string(240)	no	readOnly	Origin location text.		
OriginXCoordinate [default = 0]	origin_x_coord	int32	no	readOnly	X coordinate of the node associated with the origin		
OriginYCoordinate [default = 0]	origin_y_coord	int32	no	readOnly	Y coordinate of the node associated with the origin		
TransportLocationId	unique_id	guid	no	readOnly			
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	MultiEventTransportLocation	0..1	*	AgencyEvent	MultiEventTransportLocations	AgencyEventId	AgencyEventId
CommonEvent	MultiEventTransportLocation	1	*	CommonEvent	MultiEventTransportLocations	CommonEventId	CommonEventId

[Top](#)

Entity Type Name - NextNumber					
Description	The numbr table provides I/CAD with a means of generating unique sequential numerical identifiers. This table is used to generate a variety of sequences, including Event ID numbers (eid), which are used internally. The rows in this table are created in CADDDBM.				
Base Table Name	numbr				
View Name	cmvNextNumber				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
ExpiredTime	expire	dateTimeOffset	no	readOnly	The epoch time that the current number sequence expires and needs to rollover to a new sequence
IsActive {hidden}	curent				Busy Indicator. This flag prevents waiting on the next available number. The applications set curent='O' to temporarily lock the record.
IsMessageDisplayed	dsply_msg	boolean	yes	readOnly	Display Message Flag. A (T) in this column indicates that a realtime message is displayed. If the column contains an (F), no realtime message is displayed.
NumberPrefix	pre_id	string(1)	yes	readOnly	Prefix. This is an optional column containing a prefix value that will precede the generated number (for example, f28). The eid generator (num_id = []) requires that this field be empty.
NumberType	num_id	int32	no	readOnly	Number ID. The number ID is the unique identifier for the number generator. There MUST be a num_id of zero in the database. Negative values are used internally by CAD. Positive values are used by customers for event numbers, case numbers, etc.
NumberValue	n_num	string(11)	no	readOnly	Next Number. The next number to be returned. These numbers must be greater than 0.
Purpose	purpose	string(40)	yes	readOnly	Purpose. Identifies what the num_id is used for, that is, Broadcast, Alarm, Messages, and so on.
RolloverFormat	rollover	string(20)	yes	readOnly	The format of the number to be used when a rollover occurs due to reaching the time in expire

[Top](#)

Entity Type Name - OutOfServiceType							
Description	This table contains unit out-of-service types. Previously, this data was stored in ev_ty where e_u_type = 'U'						
Base Table Name	out_of_service_type						
View Name	cmvOutOfServiceType						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
IsUnitDispatchable [default = false]	can_dispatch	boolean	no	readOnly	Unit Dispatch Flag. Flag used to indicate if a unit can be dispatched while it is out of service. (T) = can dispatch, (F) = cannot dispatch while out of service.		
OutOfServiceTypeCode	tycod	string(16)	no	readOnly	The unit out-of-service type code.		
OutOfServiceTypeCodeDesc	eng	string(80)	yes	readOnly	English Description. This column contains the textual description of the event type.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
OutOfServiceType	ActiveUnit	0..1	*	OutOfServiceType	ActiveUnits	OutOfServiceTypeCode	OutOfServiceTypeCode
OutOfServiceType	OutOfServiceTypeAgency	1	*	OutOfServiceType	OutOfServiceTypeAgencies	OutOfServiceTypeCode	OutOfServiceTypeCode

[Top](#)

Entity Type Name - OutOfServiceTypeAgency							
Description	This table contains agency-specific (timer) information for unit out-of-service types. This table joins back to out_of_service_type. Previously, this data was stored in ev_ty where e_u_type = 'U'						
Base Table Name	out_of_service_type_agency						
View Name	cmvOutOfServiceTypeAgency						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	no	readOnly	Agency Id		
AlertTime [default = 0]	alert_timer	int32	no	readOnly	The alert timer. Previously called ev_ty.time1		
OutOfServiceTypeCode	tycod	string(16)	no	readOnly	The unit out-of-service type code.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	OutOfServiceTypeAgency	1	*	Agency	OutOfServiceTypeAgencies	AgencyId	AgencyId
OutOfServiceType	OutOfServiceTypeAgency	1	*	OutOfServiceType	OutOfServiceTypeAgencies	OutOfServiceTypeCode	OutOfServiceTypeCode

[Top](#)

Entity Type Name - RecommendHistory					
Description	Contains unit recommendation history				
Base Table Name	recom_hist				
View Name	cmvRecommendHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyEventId	num_1	string(12)	no	readOnly	Event number
AlarmLevel	alarm_lev	int32	no	readOnly	Alarm level
CreatedEmployeeId	cpers	int32	no	readOnly	Employee ID of person who created this record
CreatedTime	cdts	dateTimeOffset	no	readOnly	Date/time of insertion
IsUnitDispatched	disp_flag	boolean	no	readOnly	Y - unit dispatched. N - unit recommended but not dispatched
ItemDisplayColumn	item_col	int32	no	readOnly	Item display column in response plan editor that unit was recommended for, or -1 for manually dispatched unit
ItemDisplayRow	item_row	int32	no	readOnly	Item display row in response plan editor that unit was recommended for, or -1 for manually dispatched unit
ItemId	item_id	int32	no	readOnly	Item ID unit recommended for, or 1 for manually dispatched unit
 RecommendationHistoryId	unique_id	guid	no	readOnly	Unique ID for each row in table

RequirementName	req_name	string(500)	yes	readOnly	This is either the requirement group description or a concatenated string of requirement names within the group		
ResponsePlanRequirementId	resp_plan_unique_id	guid	no	readOnly	UNIQUE ID of item in RESP_PLAN table that this unit was recommended for		
RoutedToUnitId	routed_to_unit	string(10)	yes	readOnly	When routing between units, specifies the unit ID to which this unit was routed, or NULL if unit was routed straight to event		
UnitId	unit	string(10)	no	readOnly	Recommended unit ID		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	RecommendHistory	1	*	AgencyEvent	RecommendHistories	AgencyEventId	AgencyEventId
ResponsePlanRequirement	RecommendHistory	1	*	ResponsePlanRequirement	RecommendHistories	ResponsePlanRequirementId	ResponsePlanRequirementId
ValidUnit	RecommendHistory	1	*	ValidUnit	RecommendHistories	UnitId	UnitId

[Top](#)

Entity Type Name - RemoteAgencyEvent							
Description	This table holds information about events created on remote systems. It is only used by IFCAD.						
Base Table Name	remote_event						
View Name	cmvRemoteAgencyEvent						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	no	readOnly	The agency event number for the local event.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The creation date-time stamp of the record.		
 ExternalEventId	external_event_id	string(30)	no	readOnly	A unique identifier for the event provided by the remote system.		
Message	message	string(Max)	yes	readOnly	An artifact exchanged between systems that records information about the event.		
MessageType	message_type	string(32)	yes	readOnly	A label distinguishing different kinds of messages.		
RemoteOrganizationId	remote_organization_id	string(64)	no	readOnly	An identifier for the organization from which the event originated.		
RemoteOrganizationName	remote_organization_name	string(64)	no	readOnly	The name of the organization from which the event originated.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	The update date-time stamp of the record.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
RemoteAgencyEvent	RemoteAgencyEventComment	1	*	RemoteAgencyEvent	RemoteAgencyEventComments	ExternalEventId	ExternalEventId

[Top](#)

Entity Type Name - RemoteAgencyEventComment								
Description	This table holds information about comments added to events on remote systems. It tracks which comments have already been added so that duplicates don't occur in the local system. It is only used by IFCAD.							
Base Table Name	remote_event_comments							
View Name	cmvRemoteAgencyEventComment							
Monitored	No							
Properties								
Property Name	Base Column	Data Type	NULL	Access Type	Description			
 CommentId	comment_id	string(64)	no	readOnly	An identifier supplied by a remote system that uniquely identifies a comment for a particular event.			
CreatedTime	cdts	dateTimeOffset	no	readOnly	The creation date-time stamp of the record.			
 ExternalEventId	external_event_id	string(30)	no	readOnly	A unique identifier supplied by a remote system for the event associated with the comment.			
Associations								
Principal Entity Type	Dependent Entity Type		Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
RemoteAgencyEvent	RemoteAgencyEventComment		1	*	RemoteAgencyEvent	RemoteAgencyEventComments	ExternalEventId	ExternalEventId

[Top](#)

Entity Type Name - ResponsePlanPolygon						
Description	Defines response plans for polygons contained in a special response plan polygon file used by unit recommendation. Added for CAD 9.1 Recommend Unit CRs.					
Base Table Name	resp_plan_poly					
View Name	cmvResponsePlanPolygon					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	
 AgencyEventSubTypeCode [default = default]	sub_tycode	string(16)	no	readOnly	Event's subtype code	
 AgencyEventTypeCode	tycode	string(16)	no	readOnly	Event's type code	
 AgencyId	ag_id	string(9)	no	readOnly	Event's agency	
 AlarmLevel	alarm_lev	int32	no	readOnly	Event's alarm level	
CommentText	comm	string(80)	yes	readOnly	Special dispatching info	
PolygonId	polygon_id	int32	no	readOnly	ID of polygon from response plan polygon file	
ResponsePlanName	resp_plan_name	string(50)	no	readOnly	Response plan to use	

[Top](#)

Entity Type Name - ResponsePlanRequirement					
Description	Defines response plans for unit recommendation				
Base Table Name	resp_plan				
View Name	cmvResponsePlanRequirement				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AlternateUnitCount [default = 0]	alt_unit_count	int32	no	readOnly	Number of alternate units to recommend for the requirement group
CommentText	comm	string(80)	yes	readOnly	User-supplied comment string associated with the response plan and displayed during Recommend Unit
ConditionType	cond_type	int32	no	readOnly	0 - date/time condition 1 - recommended requirement 2 - already assigned requirement
FailureItemId	failure_item_id	int32	no	readOnly	ID of next item to process on failure
FromDay	from_day	int16	no	readOnly	From day (1-31). 0 means that day does not factor into the response plan condition.
FromHour	from_hour	int16	no	readOnly	From hour (0-23). 24 means that neither the hour nor the minute factors into the response plan condition.
FromMinute	from_minute	int16	no	readOnly	From minute (0-59)
FromMonth	from_month	int16	no	readOnly	From month (1=January, 12=December). 0 means that the month does not factor into the response plan condition.
FromWeekday	from_weekday	int16	no	readOnly	From weekday (0=Sunday, 6=Saturday). 7 means that the weekday does not factor into the response plan condition.
ItemDisplayColumn	item_col	int32	no	readOnly	Item display column in response plan editor
ItemDisplayRow	item_row	int32	no	readOnly	Item display row in response plan editor
ItemId	item_id	int32	no	readOnly	ID of item within plan
ItemType	item_type	int32	no	readOnly	0 - no-op condition item 1 - requirement group item 2 - condition item 3 - nested response plan item

RecommendMode [default = 3]	recommend_mode	int32	no	readOnly	Overrides default recommendation mode set for event. 0 - beats, 1 - street network, 3 - use default		
RequirementDisplayOrder [default = 0]	req_display_order	int32	no	readOnly	Optional override for ordering recommended units		
RequirementGroupDescription	req_descrip	string(50)	yes	readOnly	Optional description of requirements within a requirement group		
RequirementMaxBeat [default = 0]	req_max_beat	int32	no	readOnly	Maximum beat for the requirement		
RequirementMaxRoute [default = 0]	req_max_route	double	no	readOnly	Maximum route (distance or time) for the requirement		
RequirementName	req_name	string(50)	yes	readOnly	Descriptive name for response requirement		
RequirementNumber	req_number	int32	no	readOnly	Requirement number within response plan item beginning with zero		
RequirementQuantity	req_quan	int32	no	readOnly	Requirement quantity		
ResponsePlanName	resp_plan_name	string(50)	no	readOnly	Descriptive name for response plan		
ResponsePlanReference	plan_ref	string(50)	yes	readOnly	Descriptive name for nested response plan		
 ResponsePlanRequirementId	unique_id	guid	no	readOnly	Unique ID for each row in table (can be joined to RESP_PLAN_UNIQUE_ID in RECOM_HIST table to identify history records that go with this response plan item)		
ResponsePlanType [default = 0]	resp_type	int32	no	readOnly	Response Plan Type. 0 = Normal, 1 = Displayed on Additional Unit Recommend dialog.		
SuccessItemId	success_item_id	int32	no	readOnly	ID of next item to process on success		
ToDay	to_day	int16	no	readOnly	To day (1-31). 0 means that day does not factor into the response plan condition.		
ToHour	to_hour	int16	no	readOnly	To hour (0-23). 24 means that neither the hour nor the minute factors into the response plan condition.		
ToMinute	to_minute	int16	no	readOnly	To minute (0-59)		
ToMonth	to_month	int16	no	readOnly	To month (1=January, 12=December). 0 means that the month does not factor into the response plan condition.		
ToWeekday	to_weekday	int16	no	readOnly	To weekday (0=Sunday, 6=Saturday). 7 means that the weekday does not factor into the response plan condition.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ResponsePlanRequirement	RecommendHistory	1	*	ResponsePlanRequirement	RecommendHistories	ResponsePlanRequirementId	ResponsePlanRequirementId

 [Top](#)

Entity Type Name - ResponseReqCriterionResource							
Description	Defines resources included in response requirements						
Base Table Name	resp_req_res						
View Name	cmvResponseReqCriterionResource						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 CriteriaNumber	line_number	int32	no	readOnly	Criteria line number within requirement definition beginning with zero		
 RequirementName	req_name	string(50)	no	readOnly	Descriptive name for response requirement		
ResourceName	res_name	string(10)	no	readOnly	Resource name		
 ResourceOrder	res_order	int32	no	readOnly	Order of resource within criteria beginning with zero		
ResourceType	res_type	int32	no	readOnly	Resource type. 1 - equipment resource 2 - skills resource		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ResponseRequirementCriterion	ResponseReqCriterionResource	1	*	ResponseRequirementCriterion	ResponseReqCriterionResources	CriteriaNumber, RequirementName	CriteriaNumber, RequirementName

 [Top](#)

Entity Type Name - ResponseRequirementCriterion							
Description	Defines response requirements used in response plans						
Base Table Name	resp_req						
View Name	cmvResponseRequirementCriterio						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AttributeMatching	attr_opt	int32	no	readOnly	0 - unit must match all attributes 1 - unit must match at least one attribute		
Beat	lev3	string(7)	yes	readOnly	Beat criteria		
BeatModifier	same_beat	int32	no	readOnly	0 - units recommended for this requirement can come from any beat. 1 - units recommended for this requirement must come from same beat. 2 - units recommended for this requirement must come from different beats		
BeatRestriction	beat_opt	int32	no	readOnly	0 - unit can come from any beat 1 - unit can only come from primary beat 2 - unit can only come from backup beat 3 - unit can only come from beat defined in this criteria row (LEV3 must be non-null)		
 CriteriaNumber	line_number	int32	no	readOnly	Criteria line number within requirement definition, with zero being the first line		
CriteriaQuantity	quan	int32	no	readOnly	Criteria quantity		
ExtendedUnitAttributes	ext_unitattr	string(64)	no	readOnly	ext_unitattr is a bit-masked 256 bit field which indicates the customer-defined attributes that have been assigned to this unit. The attributes are defined in the cad UnitAttributes parameter list.The value must be 32 bytes (64 bytes as a hex string).		
HasResources	has_res	boolean	no	readOnly	0 - criteria does not include equipment or skills. 1 - criteria includes equipment and/or skills		
 RequirementName	req_name	string(50)	no	readOnly	Descriptive name for response requirement		
ResourceRestriction [default = 1]	resource_restrict	int32	no	readOnly	Defines the way equipment and skills are matched to units. 0 - equipment and skills must come from a single unit, 1 - equipment and skills can come from any unit		
RoutingTarget [default = 0]	route_target	int32	no	readOnly	Defines the target where the unit will be routed. 0 - route to event, 1 - route to next unit in requirement		
SkillRestriction [default = 0]	skill_restrict	int32	no	readOnly	Defines the way skills are filled by personnel. 0 - skills can be filled by any person, 1 - each skill requires a unique person		
StationId	station	string(10)	yes	readOnly	Station ID criteria		
UnitId	unitid	string(10)	yes	readOnly	Unit ID criteria		
UnitType	unityp	string(6)	yes	readOnly	Unit type criteria		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ResponseRequirementCriterion	ResponseReqCriterionResource	1	*	ResponseRequirementCriterion	ResponseReqCriterionResources	CriteriaNumber, RequirementName	CriteriaNumber, RequirementName
DefinedStation	ResponseRequirementCriterion	0..1	*	DefinedStation	ResponseRequirementCriteria	StationId	StationId
ValidUnit	ResponseRequirementCriterion	0..1	*	ValidUnit	ResponseRequirementCriteria	UnitId	UnitId

 [Top](#)

Entity Type Name - RoadRestriction	
Description	Road restrictions that override the base values in cd_edge. Added for CR 1-4UUSBR - Road Restrictions.
Base Table Name	road_restrict
View Name	cmvRoadRestriction

Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AverageSpeed	average_speed	int16	yes	readOnly	The average speed that should be applied to all of the segments in the restriction		
BaseAverageSpeed	base_average_speed	int16	no	readOnly	The base average speed for all of the segments in the restriction		
BaseTotalTravelTime	base_total_travel_time	double	yes	readOnly	The base total travel time for a restriction that corresponds to a route		
CalltakerNotified	calltaker_notified	string(20)	yes	readOnly	Calltaker that was notified of the restriction		
CreatedEmployeeId	cpers	int32	no	readOnly	The person that created the restriction		
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that created the restriction		
CreatedTime	cdts	dateTimeOffset	no	readOnly	When the restriction was created		
DestSegmentId	dest_segment_id	int32	yes	readOnly	The destination segment for a route		
Direction	direction	string(10)	yes	readOnly	TW = Two Way, OWFS = One Way From Source, OWFD = One Way From Dest, C = Closed		
IsActive	active	boolean	no	readOnly	T/ F, indicates if restriction is active		
IsDestUsingFromNode	dest_use_from_node	boolean	yes	readOnly	T if using from node, F is using to node		
IsSourceUsingFromNode	source_use_from_node	boolean	no	readOnly	T if using from node, F if using to node		
NotifySource	notify_source	string(40)	yes	readOnly	Source of notification		
Remarks	remarks	string(80)	yes	readOnly	Remarks for the restriction		
 RestrictId	restrict_id	guid	no	readOnly	A unique identifier that uniquely identifies a restriction		
RestrictName	restrict_name	string(60)	no	readOnly	A name that uniquely identifies the restriction		
RestrictShape	restrict_shape	string(10)	no	readOnly	Route or Fence		
RestrictType	restrict_type	string(30)	no	readOnly	One of the values from the RoadRestrictionType parameter table		
SourceSegmentId	source_segment_id	int32	no	readOnly	The source node for a route		
SpeedLimit	speed_limit	int16	yes	readOnly	The speed limit that should be applied to all of the segments in the restriction		
TotalTravelTime	total_travel_time	double	yes	readOnly	The total travel time for a restriction that corresponds to a route		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSegment	RoadRestriction	1	*	SourceSegment	SourceRestrictions	MapSegmentId	SourceSegmentId
MapSegment	RoadRestriction	0..1	*	DestSegment	DestRestrictions	MapSegmentId	DestSegmentId
RoadRestriction	RoadRestrictionSegment	1	*	RoadRestriction	RoadRestrictionSegments	RestrictId	RestrictId

 [Top](#)

Entity Type Name - RoadRestrictionHistory					
Description	Records the changes that have been made to road restrictions. Added for CR 1-4UUSBR - Road Restrictions.				
Base Table Name	road_restrict_hist				
View Name	cmvRoadRestrictionHistory				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AverageSpeed	average_speed	int16	yes	readOnly	The average speed that should be applied to all of the segments in the restriction
BaseAverageSpeed	base_average_speed	int16	no	readOnly	The average speed that should be applied to all of the segments in the restriction
BaseTotalTravelTime	base_total_travel_time	double	yes	readOnly	The base total travel time for a restriction that corresponds to a route
CalltakerNotified	calltaker_notified	string(20)	yes	readOnly	Calltaker that was notified of the restriction.
 ChangeId	change_id	guid	no	readOnly	Uniquely identifies each row in the table
ChangeType	change_type	string(10)	no	readOnly	Insert, Update, or Delete
CreatedEmployeeId	cpers	int32	no	readOnly	The person that changed the restriction
CreatedTerminal	cterm	string(15)	no	readOnly	The terminal that changed the restriction
CreatedTime	cdts	dateTimeOffset	no	readOnly	When the restriction was changed
DestSegmentId	dest_segment_id	int32	yes	readOnly	The destination segment for a route
Direction	direction	string(10)	yes	readOnly	TW = Two Way, OWFS = One Way From Source, OWFD = One Way From Dest, C = Closed
IsActive	active	boolean	no	readOnly	T/ F, indicates if restriction is active
IsDestUsingFromNode	dest_use_from_node	boolean	yes	readOnly	T if using from node, F is using to node
IsSourceUsingFromNode	source_use_from_node	boolean	no	readOnly	T if using from node, F if using to node
NotifySource	notify_source	string(40)	yes	readOnly	Source of notification
Remarks	remarks	string(80)	yes	readOnly	Remarks for the restriction
RestrictId	restrict_id	guid	no	readOnly	The unique identifier that uniquely identifies a restriction
RestrictName	restrict_name	string(60)	no	readOnly	The name that uniquely identified a restriction before it was removed
RestrictShape	restrict_shape	string(10)	no	readOnly	Route or Fence
RestrictType	restrict_type	string(30)	no	readOnly	One of the values from the RoadRestrictionType parameter table
SourceSegmentId	source_segment_id	int32	no	readOnly	The source segment for a route
SpeedLimit	speed_limit	int16	yes	readOnly	The speed limit that should be applied to all of the segments in the restriction
TotalTravelTime	total_travel_time	double	yes	readOnly	The total travel time for a restriction that corresponds to a route

 [Top](#)

Entity Type Name - RoadRestrictionSegment							
Description	The segments associated with current restrictions. Added for CR 1-4UUSBR - Road Restrictions.						
Base Table Name	road_restrict_seg						
View Name	cmvRoadRestrictionSegment						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 MapSegmentId	map_segment_id	int32	no	readOnly	The segment id from segme that is being restricted		
 RestrictId	restrict_id	guid	no	readOnly	Uniquely identifies a restriction		
SegmentOrder	segment_order	int32	yes	readOnly	The order in which the segments are traversed for a route		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSegment	RoadRestrictionSegment	1	*	MapSegment	RoadRestrictionSegments	MapSegmentId	MapSegmentId
RoadRestriction	RoadRestrictionSegment	1	*	RoadRestriction	RoadRestrictionSegments	RestrictId	RestrictId

 [Top](#)

Entity Type Name - RoadRestrictionSegmentHistory					
Description	The segments associated with current and removed restrictions. Added for CR 1-4UUSBR - Road Restrictions.				
Base Table Name	road_restrict_seg_hist				
View Name	cmvRoadRestrictionSegmentHisto				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
CreatedTime	cdts	dateTimeOffset	no	readOnly	When this restriction segment was removed

 MapSegmentId	map_segment_id	int32	no	readOnly	The segment id from segme that is being restricted
 RestrictId	restrict_id	guid	no	readOnly	Uniquely identifies a restriction
SegmentOrder	segment_order	int32	yes	readOnly	The order in which the segments are traversed for a route

 [Top](#)

Entity Type Name - RotationalServiceCompany							
Description	The rotate table is used to store information about the companies to be accessed for rotational services. The information is displayed in I/CAD using the Rotational Services Summary command. The Towing WPF dialogs in I/CAD also use the rotate table.						
Base Table Name	rotate						
View Name	cmvRotationalServiceCompany						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ActiveAfterTime	active_after_dts	dateTimeOffset	no	readOnly	Date/time after which this company becomes active. By specifying a date/time in the near future, a user can temporarily mark a company as inactive. This column replaces the old curent column.		
CompanyAddress	address	string(80)	yes	readOnly	Company address		
 CompanyId	comp_id	int32	no	readOnly	Company ID. This is a unique, system-generated number designated by num_id of -6 in the numbr table. This is initiated at one(1).		
CompanyName	comp_name	string(30)	no	readOnly	Company Name. This column contains the company name.		
ContactInfo	contact	string(50)	yes	readOnly	Company contact information		
DefaultTowLocation	default_tow_location	string(80)	yes	readOnly	The default tow location for this company.		
EditEmployeeId	editor_pers	int32	yes	readOnly	Rotation editor employee id for this company		
EditTerminal	editor_term	string(15)	yes	readOnly	Rotation editor terminal for this company		
EditTime	editor_dts	dateTimeOffset	yes	readOnly	Rotation editor datetime stamp for this company		
IsDefaultTowLocationVerified [default = false]	default_tow_loc_ver	boolean	no	readOnly	Flag indicating if the company's default tow location was verified. T= location verified, F= location was not verified		
SpecialInstructions	instructions	string(250)	yes	readOnly	Company special instructions		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
RotationalServiceCompany	RotationalServiceCompanyPhone	1	*	RotationalServiceCompany	RotationalServiceCompanyPhones	CompanyId	CompanyId
RotationalServiceCompany	RotationalServiceEquipment	1	*	RotationalServiceCompany	RotationalServiceEquipment	CompanyId	CompanyId

 [Top](#)

Entity Type Name - RotationalServiceCompanyPhone							
Description	Phone Numbers for a rotational service company						
Base Table Name	rotate_phone						
View Name	cmvRotationalServiceCompanyPho						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 CompanyId	comp_id	int32	no	readOnly	Company ID		
 PhoneNumber	phone	string(20)	no	readOnly	Phone number		
PhoneType	phone_type	string(15)	no	readOnly	Phone type		
 Priority	priority	int16	no	readOnly	Phone number sort priority, starts with zero as the highest priority		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
RotationalServiceCompany	RotationalServiceCompanyPhone	1	*	RotationalServiceCompany	RotationalServiceCompanyPhones	CompanyId	CompanyId

 [Top](#)

Entity Type Name - RotationalServiceEquipment					
Description	The rot_equip table is populated via CADDBM. It contains the rotational service equipment availability details for each company in the rotate table. The Rotational Service comands in CAD may update the last_dts, save_last_dts and select_flag columns.				
Base Table Name	rot_equip				
View Name	cmvRotationalServiceEquipment				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 CompanyId	comp_id	int32	no	readOnly	Company ID. This is a unique, system-generated number designated by num_id of -6 in the numbr table. This is initiated at one(1).
 EquipmentType	equip	string(10)	no	readOnly	Equipment. This column defines the equipment type offered by the company.
Esz	esz	int32	yes	readOnly	Emergency Service Zone. This column defines the Emergency Service Zone in which the company responds to calls.
FridayBeginTime [default = 0]	fri_fr	int32	no	readOnly	Friday From Time. Beginning hour of operation on Friday.
FridayEndTime [default = 2400]	fri_to	int32	no	readOnly	Friday To Time. Closing hour of operation on Friday.
HasAcceptedService [default = true]	rot_status	boolean	no	readOnly	Y/N flag for of service acceptance.
IsSelected [default = false]	select_flag	boolean	no	readOnly	Select Flag. This column defines whether the service is currently selected.
LastUsedTime	last_dts	dateTimeOffset	no	readOnly	Last Date/Time Stamp. This column defines the date/time stamp at which the company was last used. CAD uses last_dts to order equipment when it needs to pick a piece of equipment for a job.
LockingTerminal	updt_term	string(15)	yes	readOnly	Locking terminal
MainServiceType	main_type	string(8)	yes	readOnly	Main Type of Service. This column contains the main type of service offered by the company.
MondayBeginTime [default = 0]	mon_fr	int32	no	readOnly	Monday From Time. Beginning hour of operation on Monday.
MondayEndTime [default = 2400]	mon_to	int32	no	readOnly	Monday To Time. Closing hour of operation on Monday.
PreviousLastUsedTime	save_last_dts	dateTimeOffset	yes	readOnly	Resets dts in case of reassignment.
RowNumber	row_id	int32	no	readOnly	Row ID. This column defines the row in the multigadget control where the information is to be displayed. When inserting new rows, CADDBM sets row_id based on the order in which the equipment is listed in the Equipment Record control on the Rotational Services dialog.
SaturdayBeginTime [default = 0]	sat_fr	int32	no	readOnly	Saturday From Time. Beginning hour of operation on Saturday.
SaturdayEndTime [default = 2400]	sat_to	int32	no	readOnly	Saturday To Time. Closing hour of operation on Saturday.
SecondaryServiceType	subserv_type	string(8)	yes	readOnly	Secondary Service. This column defines the secondary type of service offered by the company.
SundayBeginTime [default = 0]	sun_fr	int32	no	readOnly	Sunday From Time. Beginning hour of operation on Sunday.
SundayEndTime [default = 2400]	sun_to	int32	no	readOnly	Sunday To Time. Closing hour of operation on Sunday.
ThursdayBeginTime [default = 0]	thur_fr	int32	no	readOnly	Thursday From Time. Beginning hour of operation on Thursdays.

ThursdayEndTime [default = 2400]	thur_to	int32	no	readOnly	Thursday To Time. Closing hour of operation on Thursdays.		
TuesdayBeginTime [default = 0]	tue_fr	int32	no	readOnly	Tuesday From Time. Beginning hour of operation on Tuesdays.		
TuesdayEndTime [default = 2400]	tue_to	int32	no	readOnly	Tuesday To Time. Closing hour of operation on Tuesdays.		
UpdatedEmployeeId	upers	int32	yes	readOnly	ID of person who last updated the corresponding record.		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal which updated the rotational equipment record.		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update Date/Time Stamp		
WednesdayBeginTime [default = 0]	wed_fr	int32	no	readOnly	Wednesday From Time. Beginning hour of operation on Wednesdays.		
WednesdayEndTime [default = 2400]	wed_to	int32	no	readOnly	Wednesday To Time. Closing hour of operation on Wednesdays.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
RotationalServiceCompany	RotationalServiceEquipment	1	*	RotationalServiceCompany	RotationalServiceEquipment	CompanyId	CompanyId
RotationalServiceEquipment	RotationalServiceInstance	1	*	RotationalServiceEquipment	RotationalServiceInstances	CompanyId, EquipmentType	CompanyId, EquipmentType
RotationalServiceEquipment	TowRequestVehicle	0..1	*	RotationalServiceEquipment	TowRequestVehicles	CompanyId, EquipmentType	CompanyId, EquipmentType

 [Top](#)

Entity Type Name - RotationalServiceInstance							
Description	This table contains the Rotational Services History information						
Base Table Name	rot_hist						
View Name	cmvRotationalServiceInstance						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CommonEventId	eid	int32	no	readOnly	The System Event ID of the event requiring service (cf. column "eid" of "common_event" table). A value of 0 indicates that there is no associated event.		
CompanyId	comp_id	int32	no	readOnly	The Company ID value		
CreatedEmployeeId	cpers	int32	no	readOnly	The i.d. of the operator who created the given record (cf. column "empid" of "persl" table)		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal i.d. of the terminal that created the given record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The creation date-time stamp that will hold the date when the given record was created (format YYYYMMDDHHMMSSZZ)		
EquipmentType	equip	string(10)	no	readOnly	Will hold equipment type		
EstimatedArrivalTime	est_time	int32	no	readOnly	Will hold estimated time of arrival (eta)		
 InstanceId	unique_id	guid	no	readOnly	Unique identifier		
InstanceLocation	location	string(80)	no	readOnly	Service location		
MainServiceType	main_type	string(8)	yes	readOnly	Main service type requested		
PersonContacted	person_con	string(25)	yes	readOnly	Name of person contacted		
ReasonForService	reason	string(8)	yes	readOnly	Reason for service		
Remarks	remarks	string(80)	yes	readOnly	Remarks concerning service		
RequestingUnitId	unid	string(10)	yes	readOnly	Unit ID requesting service		
RotationalServiceCode	rot_code	string(8)	no	readOnly	Service code		
SecondaryServiceType	subserv_type	string(8)	yes	readOnly	Sub service type requested		
VehicleDesc	vehic_desc	string(80)	yes	readOnly	Description of vehicle which was serviced.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEvent	RotationalServiceInstance	1	*	CommonEvent	RotationalServiceInstances	CommonEventId	CommonEventId
RotationalServiceEquipment	RotationalServiceInstance	1	*	RotationalServiceEquipment	RotationalServiceInstances	CompanyId, EquipmentType	CompanyId, EquipmentType

 [Top](#)

Entity Type Name - ScheduledDispatchAssignedEvent							
Description	Lists dispatch assigned events for units scheduled for future log-on as part of a lineup						
Base Table Name	dispass_sched_event						
View Name	cmvScheduledDispatchAssignedEv						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyEventId [Monitored]	num_1	string(12)	no	readOnly	Agency event number of assigned event		
LineupName [Monitored]	lineup_name	string(30)	yes	readOnly	Lineup name containing unit		
ListPosition [Monitored]	list_pos	int32	no	readOnly	Zero-based index of agency event within dispatch assigned list		
Status [default = 0] [Monitored]	status	int32	no	readOnly	Status of the event scheduled for dispatch assign. 0 = Planned, 1 = Committed		
UnitId [Monitored]	unid	string(10)	no	readOnly	Unit's ID		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	ScheduledDispatchAssignedEvent	1	0..1	AgencyEvent	ScheduledDispatchAssignedEvent	AgencyEventId	AgencyEventId
ValidUnit	ScheduledDispatchAssignedEvent	1	*	ValidUnit	ScheduledDispatchAssignedEvents	UnitId	UnitId

 [Top](#)

Entity Type Name - ScheduledItem					
Description	This table contains items which are scheduled for automatic execution for a particular day and time, or which are to occur every day at a set time.				
Base Table Name	scheduled_items				
View Name	cmvScheduledItem				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
AgencyId	ag_id	string(9)	yes	readOnly	Name of associated agency.
CancelledTime	xdts	dateTimeOffset	yes	readOnly	Inactive date/time stamp
CreatedEmployeeId	cpers	int32	no	readOnly	Empid of creating person
CreatedTerminal	cterm	string(15)	no	readOnly	Creating terminal
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp.

DayOfWeek	dow	int16	yes	readOnly	Day of week to schedule item. 0 = Sunday, 6 = Saturday, 7 = All days		
Destination	destination	string(80)	yes	readOnly	Destination for the item		
DestinationType	dest_type	int16	no	readOnly	Type of destination for item. 0 = All, 1= Terminal, 2 = Dispatch group, 3 = Group, 4 = Bgroup, 5 = Unit, 6 = Verbal, 7 = Remote, 8 = Pager, 9 = Station		
ExecuteCount	sched_count	int32	no	readOnly	The number of times that this item was scheduled to execute.		
ExecuteDate	exec_date	string(8)	yes	readOnly	Date item is to be activated		
ExecuteTime	exec_time	string(4)	yes	readOnly	Time item is to be activated		
ExpireTime	last_dts	dateTimeOffset	yes	readOnly	This field is upper-bound date/time stamp. If set, then once the next execution date-time stamp goes beyond this data/time, the scheduled item will be cancelled.		
IsDayOfWeekAndedWithDay [default = false]	and_dow_day	boolean	no	readOnly	The boolean variable indication whether or not the interval values for day and day of week should be ANDed together(1) or ORed together(0).		
IsOneTimeOnly	one_time	boolean	yes	readOnly	Schedule one time flag. T = schedule one time. F means schedule more than once.		
Item	item	string(240)	no	readOnly	Actual item scheduled		
 ItemNumber	item_number	int32	no	readOnly	Unique scheduled item ID		
ItemType	item_type	int16	no	readOnly	Type of item scheduled. 1 = Command 2 = Message 3 = Broadcast 4 = Late Unit 5 = Change SSM Plan 8 = Scheduled Event 9 = Scheduled Event to Pending		
LockingTerminal	updt_flag	string(21)	no	readOnly	Terminal name locking record		
NextExecuteTime	exec_dts	dateTimeOffset	yes	readOnly	The next time the scheduled item should be executed.		
StartTime	sds	dateTimeOffset	yes	readOnly	Time stamp when the user enters the initial data		
UpdatedEmployeeId	upers	int32	yes	readOnly	Person updating the record		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record.		
UpdateTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	ScheduledItem	0..1	*	Agency	ScheduledItems	AgencyId	AgencyId
ScheduledItem	ScheduledItemDestination	1	*	ScheduledItem	ScheduledItemDestinations	ItemNumber	ItemNumber
ScheduledItem	ScheduledItemHistory	1	*	ScheduledItem	ScheduledItemHistories	ItemNumber	ItemNumber
ScheduledItem	ScheduledItemInterval	1	*	ScheduledItem	ScheduledItemIntervals	ItemNumber	ItemNumber

 [Top](#)

Entity Type Name - ScheduledItemDestination							
Description	This table contains destinations for scheduled items referred to by the item number.						
Base Table Name	scheduled_dest						
View Name	cmvScheduledItemDestination						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 Destination	destination	string(80)	no	readOnly	Destination name for scheduled item.		
 ItemNumber	item_number	int32	no	readOnly	Scheduled item number from the scheduled_item table		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ScheduledItem	ScheduledItemDestination	1	*	ScheduledItem	ScheduledItemDestinations	ItemNumber	ItemNumber

 [Top](#)

Entity Type Name - ScheduledItemHistory							
Description	This table contains information about the history of scheduler execution. This table is used only when the WriteHistory parameter in the sched GeneralDetails parameter list is set to Y.						
Base Table Name	scheduled_hist						
View Name	cmvScheduledItemHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	yes	readOnly	The unique identifier for the agency with which the scheduled item is associated.		
CompletionStatus	status_msg	string(100)	yes	readOnly	The completion status for this instance of the items execution. It contains an error message if there was some problem with the execution of the item, otherwise if null, it was successful.		
CreatedEmployeeId	cpers	int32	no	readOnly	The personnel identification number of the person who created this record.		
CreatedTerminal	cterm	string(15)	no	readOnly	The node name of the terminal from which this record was created.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	The creation date/time stamp at which the record was created.		
Destination	destination	string(80)	yes	readOnly	The destination group to which the scheduled item was sent.		
DestinationType	dest_type	string(1)	yes	readOnly	Type of destination for item. 0 = All, 1 = Terminal, 2 = Dispatch group, 3 = Group, 4 = Bgroup, 5 = Unit, 6 = Verbal, 7 = Remote, 8 = Pager, 9 = Station		
ExecutionCount	sched_count	int32	no	readOnly	The number of times that the item was scheduled to execute.		
FinalExecutionTime	cmpl_dts	dateTimeOffset	yes	readOnly	The date/time stamp at which the scheduled item completed its final execution.		
Item	item	string(240)	yes	readOnly	The actual item scheduled for execution. The field may contain a message scheduled to be sent, a command scheduled to executed and so on.		
ItemNumber	item_number	int32	no	readOnly	The system generated number assigned to each scheduled item.		
ItemType	item_type	string(1)	no	readOnly	The type of item which was scheduled.		
ProcessId	cpid	int32	no	readOnly	The process ID number of the scheduler process from which this record was created.		
ScheduledExecutionTime	exec_dts	dateTimeOffset	yes	readOnly	The date/time stamp at which this instance of the scheduled item was scheduled to execute.		
 ScheduledItemHistoryId	unique_id	guid	no	readOnly	Uniquely identifies rows		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ScheduledItem	ScheduledItemHistory	1	*	ScheduledItem	ScheduledItemHistories	ItemNumber	ItemNumber

 [Top](#)

Entity Type Name - ScheduledItemInterval							
Description	This table contains information about the intervals for which items are scheduled for execution. Each item has a set of interval records that determines exactly when the next occurrence will take place.						
Base Table Name	scheduled_interval						
View Name	cmvScheduledItemInterval						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 IntervalType	field_type	int32	no	readOnly	The type of interval information that this record contains. 0=minute, 1=hour, 2=day, 3=month, 4=year, 5=day of week, 6=week of month, 8=hourly.		
IntervalValue	field_value	int32	no	readOnly	The actual value for the time interval.		
 ItemNumber	item_number	int32	no	readOnly	The unique identification number associated with the scheduled item record.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References

ScheduledItem	ScheduledItemInterval	1	*	ScheduledItem	ScheduledItemIntervals	ItemNumber	ItemNumber
-------------------------------	-----------------------	---	---	---------------	------------------------	------------	------------

 [Top](#)

Entity Type Name - ScratchPad							
Description	This table contains the information that the employee wants to have kept by I/CAD.This table does not contain the text. The only way a record should get added to this table is through I/CAD.						
Base Table Name	scratch						
View Name	cmvScratchPad						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ActiveTime	scr_period	int32	no	readOnly	Period of time scratch pad is to be active (in days).		
Classification	scr_class	string(10)	no	readOnly	Scratch pad classification		
CreatedEmployeeId	cpers	int32	no	readOnly	ID of person creating record		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal creating record		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp		
IsActive	active	boolean	yes	readOnly	T = active scratch pad, F = inactive ("deleted")		
OwnerEmployeeId	personal	int32	yes	readOnly	Empid of creator if record is personal, NULL otherwise.		
 ScratchPadId	scr_index	int32	no	readOnly	Unique id for scratch pad		
Title	scr_title	string(30)	no	readOnly	Title of the scratch pad		
UpdatedEmployeeId	upers	int32	yes	readOnly	Person updating the record		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Terminal updating record		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ScratchPad	ScratchPadGroup	1	*	ScratchPad	ScratchPadGroups	ScratchPadId	ScratchPadId
ScratchPad	ScratchPadTextLine	1	*	ScratchPad	ScratchPadTextLines	ScratchPadId	ScratchPadId

 [Top](#)

Entity Type Name - ScratchPadGroup							
Description	This table contains the Scratch Pad text that the employee wants to have access to in I/CAD.This table contains only the text and is linked to other info in scratch table.Only way a re- cords added is through I/ CAD						
Base Table Name	scrgrp						
View Name	cmvScratchPadGroup						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedEmployeeId	cpers	int32	no	readOnly	ID of person creating record		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal creating record.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp		
ScratchPadGroupAccess	grp_access	string(1)	no	readOnly	Group access code for scratch		
 ScratchPadGroupId	grpId	string(4)	no	readOnly	Access group for scratch pad		
 ScratchPadId	scrid	int32	no	readOnly	Unique Scratch ID number		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ScratchPad	ScratchPadGroup	1	*	ScratchPad	ScratchPadGroups	ScratchPadId	ScratchPadId

 [Top](#)

Entity Type Name - ScratchPadTextLine							
Description	This table contains the Scratch Pad text that the employee wants to have access to in I/CAD. This table contains only the text and is linked to other info in the scratch table.						
Base Table Name	scr_text						
View Name	cmvScratchPadTextLine						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp		
 LineNumber	line_num	int32	no	readOnly	Line number of text on form		
 ScratchPadId	scr_index	int32	no	readOnly	Unique scratch pad index num		
Text	scr_text	string(240)	yes	readOnly	Text retrieved from form		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update date/time stamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ScratchPad	ScratchPadTextLine	1	*	ScratchPad	ScratchPadTextLines	ScratchPadId	ScratchPadId

 [Top](#)

Entity Type Name - SpecialAddressContact					
Description	The CADDBM spad_cont_name table contains information describing the person to contact with respect to a special address, commonplace name, or alarm.				
Base Table Name	spad_cont_name				
View Name	cmvSpecialAddressContact				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
ContactDate	co_date	string(10)	yes	readOnly	Records date the individual named in the clname column was contacted about the alarm.
ContactName	clname	string(45)	yes	readOnly	Name of the individual to contact
ContactPhone	clnum	string(14)	yes	readOnly	Telephone number of the individual to contact
ContactPriority	priority	int32	yes	readOnly	Indicates priority order in which individual named within this record is to be contacted
ContactStreetAddress	cstr_add	string(36)	yes	readOnly	Full street address of the individual to contact
ContactTime	co_time	string(5)	yes	readOnly	Records time the individual named in clname column was contacted about the alarm.
DataSource	data_source	string(5)	yes	readOnly	Data source
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for the individual to contact

 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
OriginId {hidden}	origin_id				For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
OriginTable {hidden}	origin_table				Table name associated with this contact		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSpecialAddress	SpecialAddressContact	1	*	MapSpecialAddress	SpecialAddressContacts	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - SpecialAddressEventType							
Description	This table contains overrides for special address, event type, and event subtype combinations.						
Base Table Name	sp_ad_event_type						
View Name	cmvSpecialAddressEventType						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyEventSubTypeCode [default = default]	sub_tycode	string(16)	no	readOnly	Event subtype		
 AgencyEventTypeCode	tycod	string(16)	no	readOnly	Event type		
 MapSpecialAddressId	sp_ad_mslink	int32	no	readOnly	Special address mslink		
Priority	priority	int32	no	readOnly	Event priority override		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSpecialAddress	SpecialAddressEventType	1	*	MapSpecialAddress	SpecialAddressEventTypes	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - SpecialAddressPerson							
Description	The CADDBM perso table contains person information which is related to the special address, commonplace name, or alarm.						
Base Table Name	spad_perso						
View Name	cmvSpecialAddressPerson						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Age	age	int32	yes	readOnly	Age of the person related to the special address		
DateOfBirth	dob	string(10)	yes	readOnly	Date of birth of the person related to the special address		
EyeColor	eye	string(3)	yes	readOnly	Eye color of the person related to the special address		
HairColor	hair	string(3)	yes	readOnly	Hair color of the person related to the special address		
Height	height	int32	yes	readOnly	Height of the person related to the special address		
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for this person		
LicenseNumber	oln	string(20)	yes	readOnly	Operator license number related to the special address		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
Name	nme	string(50)	yes	readOnly	Name of the person related to the special address		
OriginId {hidden}	origin_id				For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
OriginTable {hidden}	origin_table				Table name associated with this person		
Race	race	string(1)	yes	readOnly	Race of the person related to the special address		
Remarks	remarks	string(20)	yes	readOnly	Descriptive remarks about the person related to the special address		
Sex	sex	string(1)	yes	readOnly	Sex of the person related to the special address		
State	state	string(2)	yes	readOnly	State of the operator license number		
Weight	weight	int32	yes	readOnly	Weight of the person related to the special address		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSpecialAddress	SpecialAddressPerson	1	*	MapSpecialAddress	SpecialAddressPeople	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - SpecialAddressProperty							
Description	This table contains property information related to special address, commonplace name, or alarm.						
Base Table Name	spad_propt						
View Name	cmvSpecialAddressProperty						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 ItemNumber	row_num	int32	no	readOnly	Uniquely identifies the supplemental information for the property		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
MonetaryValue	value	string(10)	yes	readOnly	Monetary value of the property item		
OriginId {hidden}	origin_id				For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
OriginTable {hidden}	origin_table				Table name associated with the item		
PropertyDesc	item	string(10)	yes	readOnly	Description of the item		
Remarks	remarks	string(20)	yes	readOnly	Remarks about the property item		
SerialNumber	serialnum	string(20)	yes	readOnly	Serial number of the item		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSpecialAddress	SpecialAddressProperty	1	*	MapSpecialAddress	SpecialAddressProperties	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - SpecialAddressVehicle							
Description	This table contains vehicle information which is related to the special address, commonplace name, or alarm.						
Base Table Name	spad_vehic						
View Name	cmvSpecialAddressVehicle						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Color	vehic_color	string(7)	yes	readOnly	Vehicle Color. This column contains the color of the vehicle.		
 ItemNumber	row_num	int32	no	readOnly	Row Number. This column stores the row number of the form in which the vehicle information is to be displayed. This column should be greater than 0.		
LicensePlateNumber	license	string(8)	yes	readOnly	License Plate Number.		
LicenseType	license_type	string(10)	yes	readOnly	License Type. This column contains the type of vehicle license.		
LicenseYear	license_yr	string(4)	yes	readOnly	License Year. This column contains the year of the license.		
Make	make	string(5)	yes	readOnly	Make of the Vehicle.		
 MapSpecialAddressId	spad_mslink	int32	no	readOnly	The associated special address mslink value		
Model	model	string(5)	yes	readOnly	Model of the Vehicle.		
ModelYear	model_year	int32	yes	readOnly	Year of the Vehicle.		
OriginId {hidden}	origin_id				For rows relating to alarm this is the alarm id, for rows relating to co_pl this is the common place name, otherwise for rows relating to sp_ad this is set to 'sp_ad'.		
OriginTable {hidden}	origin_table				Table name associated with this vehicle		
Remarks	remarks	string(20)	yes	readOnly	This column stores the remarks about the vehicle.		
State	state	string(4)	yes	readOnly	State Register of the Vehicle.		
Vin	vin	string(25)	yes	readOnly	Vehicle Identification Number		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
MapSpecialAddress	SpecialAddressVehicle	1	*	MapSpecialAddress	SpecialAddressVehicles	MapSpecialAddressId	MapSpecialAddressId

 [Top](#)

Entity Type Name - SpecialSituation							
Description	The special situation table is used to store addresses where a special situation exists. This could be any situation for which the agency would need a special response.						
Base Table Name	sp_st						
View Name	cmvSpecialSituation						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AdditionalInfo	msg	string(2000)	yes	readOnly	Message. Stores the file name or comment as denoted by the mes_switch flag. File name could be used for a graphic file of floor plans or for a text file for additional information (the street names).		
AdditionalInfoType	mes_switch	string(1)	yes	readOnly	Message Switch. This column defines what is stored in the message column. C = comment, T = temporary only, X = attached file name.		
Apartment	lv_apt	string(5)	yes	readOnly	Apartment Number. Stores the apartment number of the referenced address.		
Area	lv_area	string(40)	yes	readOnly	Area. Stores the area in which the special address is located.		
CreatedEmployeeId	cpers	int32	no	readOnly	Creating Person. This column stores the identification number of the person who created the record.		
CreatedTerminal	cterm	string(15)	no	readOnly	Creating Terminal. This column stores the nodename of the terminal from which the record was created.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation date/time stamp. Stores the date/time (yyyymmddhhmmss) at which the record was created.		
DirectionPrefix	dirpre	string(2)	yes	readOnly	Direction Prefix. If applicable, this column stores the direction prefix of the street segment referenced by feature name.		
DirectionSuffix	dirsurf	string(2)	yes	readOnly	Direction Suffix. If applicable, this column stores the direction suffix of the street segment referenced by feature name.		
ExpiredTime [Monitored]	edts	dateTimeOffset	yes	readOnly	Expiration Date/Time Stamp. This column stores the date/ time stamp (yyyymmddhhmmss) of when the special situation expires.		
HighStreetNumber	highaddr	string(11)	yes	readOnly	High address range for sp_st record		
IsReturnedOnAreaSearch	ss_area	boolean	no	readOnly	T/F is returned on area search		
Location1	loc_fld1	string(5)	yes	readOnly	Generic location field		
Location2	loc_fld2	string(5)	yes	readOnly	Generic location field		
Location3	loc_fld3	string(5)	yes	readOnly	Generic location field		
Location4	loc_fld4	string(5)	yes	readOnly	Generic location field.		
LowStreetNumber	lowaddr	string(11)	yes	readOnly	Low address range for sp_st record		
Municipality	mun	string(40)	yes	readOnly	Municipality. Stores the municipality in which the special situation occurs.		
Priority [Monitored]	priority	int32	yes	readOnly	Priority. This column contains the priority of the special situation.		
Remarks	remarks	string(20)	yes	readOnly	A very brief summary of the information in the record.		
RequestingEmployeeId	req_id	int32	yes	readOnly	Requestor ID. This column contains the ID of the requestor.		
RequestingEmployeeName	req_name	string(30)	yes	readOnly	Requestor Name. This column contains the name of the requestor.		
 SpecialSituationId [Monitored]	mslink	int32	no	readOnly	Map Link. This column allows the placement of a special symbol in the map to designate a special address. The symbol could be graphically selected to review this information. The mslink value is generated using the numbr table.		
SpecialSituationTypeCode	ss_type	string(16)	yes	readOnly	Special Situation Type. Specifies the type of special situation. Types are defined in the sp_st_type table.		
StreetName	feaname	string(30)	yes	readOnly	Feature Name. Defines the event feature name.		
StreetNameHash	hash	int32	no	readOnly	Stores the numeric hashing value. Queries search on the hash value to improve response time.		
StreetNumber	st_num	string(15)	yes	readOnly	Street Number. The street number of the special situation.		
StreetType	featyp	string(4)	yes	readOnly	Feature Type. Defines the event feature type, for example, road or street.		
XCoordinate [Monitored]	x_cord	int32	no	readOnly	X-coordinate. Location of the street segment on which the special situation is located.		
YCoordinate [Monitored]	y_cord	int32	no	readOnly	Y-coordinate. Location of the street segment on which the special situation is located.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
SpecialSituation	SpecialSituationAgency	1	*	SpecialSituation	SpecialSituationAgencies	SpecialSituationId	SpecialSituationId
SpecialSituationType	SpecialSituation	0..1	*	SpecialSituationType	SpecialSituations	SpecialSituationTypeCode	SpecialSituationTypeCode

 [Top](#)

Entity Type Name - SpecialSituationAgency					
Description	Stores information about which agencies have access to which special situation records				
Base Table Name	sp_st_ag				
View Name	cmvSpecialSituationAgency				
Monitored	Yes				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
 AgencyId [Monitored]	ag_id	string(9)	no	readOnly	Agency ID

 SpecialSituationId	mslink	int32	no	readOnly	Unique identifier of special situation record. Used for joining with sp_st table.		
[Monitored]							
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	SpecialSituationAgency	1	*	Agency	SpecialSituationAgencies	AgencyId	AgencyId
SpecialSituation	SpecialSituationAgency	1	*	SpecialSituation	SpecialSituationAgencies	SpecialSituationId	SpecialSituationId

 [Top](#)

Entity Type Name - SpecialSituationType							
Description	Defines the types of special situations. sp_st.ss_type will be restricted to these defined types. Added for CR 1-4URTWV.						
Base Table Name	sp_st_type						
View Name	cmvSpecialSituationType						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
Description	description	string(50)	yes	readOnly	Optional description		
ImageResourceName	image_resource_name	string(255)	yes	readOnly	Image resource name. This image will be displayed on the map for this type of special situation.		
 SpecialSituationTypeCode	ss_type	string(16)	no	readOnly	Special situation type.		
[Monitored]							
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
SpecialSituationType	SpecialSituation	0..1	*	SpecialSituationType	SpecialSituations	SpecialSituationTypeCode	SpecialSituationTypeCode
SpecialSituationType	SpecialSituationTypePriority	1	*	SpecialSituationDefinedType	SpecialSituationTypePriorities	SpecialSituationTypeCode	SpecialSituationTypeCode

 [Top](#)

Entity Type Name - SpecialSituationTypePriority							
Description	Special situation type priority override. For a particular special situation type and priority, you can override the image displayed on the map. Added for CR 1-4URTWV.						
Base Table Name	sp_st_type_priority						
View Name	cmvSpecialSituationTypePriorit						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ImageResourceName	image_resource_name	string(255)	no	readOnly	Image resource name. This image will be displayed on the map for special situations of this type and priority. This overrides the normal image used for special situations of this type.		
 Priority	priority	int32	no	readOnly	Priority		
 SpecialSituationTypeCode	ss_typ	string(16)	no	readOnly	Special situation type.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
SpecialSituationType	SpecialSituationTypePriority	1	*	SpecialSituationDefinedType	SpecialSituationTypePriorities	SpecialSituationTypeCode	SpecialSituationTypeCode

 [Top](#)

Entity Type Name - StackedEvent					
Description	This table is used to save information about events that have been stacked (stored) within the I/CAD system for later processing. This allows pertinent information regarding the stacked event to not have to be re-entered again.				
Base Table Name	save_stack				
View Name	cmvStackedEvent				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
CreatedTerminal	term	string(15)	no	readOnly	Creating terminal node
FormId	s_form	string(40)	yes	readOnly	This column contains the form id or name
GadgetColumn	g_col	int32	no	readOnly	Gadget column number
GadgetId	gadget	int32	no	readOnly	Gadget number on the form
GadgetRow	g_row	int32	no	readOnly	Gadget row number
GadgetText	g_text	string(4000)	yes	readOnly	The text on the gadget
GuiType	gui_type	int16	no	readOnly	Indicates the type of GUI associated with the data, 1 = MFC, 2 = WPF
 ItemNumber	unique_id	guid	no	readOnly	Uniquely identifies each row in the table
LockingTerminal	updt_flag	string(15)	no	readOnly	Contains the update terminal or NULLTERM if it is not locked
StackId	stack_id	int32	no	readOnly	This is a unique number that is assigned to a stacked event so it can be retrieved at a later date for processing.

 [Top](#)

Entity Type Name - Terminal							
Description	This table contains information unique to each terminal node.						
Base Table Name	term						
View Name	cmvTerminal						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
ConsolePosition	mux_id	int32	yes	readOnly	Multiplexer ID Code. Defines the ani/ali node that corresponds to a phone line of the E-9-1-1 mux. The mux_id is called the Console Position in CADDDBM. Links to an_al.position_id		
CurrentCallbackTerminal [default = 'F']	current_callback_term	string(1)	no	readOnly	Is this node currently a callback terminal? Y means node is currently a callback terminal, N means node is not currently a callback terminal, L means CAD is locked in Change Operator mode.		
DefaultCallbackTerminal [default = 'N']	default_callback_term	string(1)	no	readOnly	Default state of callback terminal status. This column is set by CADDDBM. Y means allowed but not set by default, N means Not allowed, D means allowed and assign by default.		
DomainNameOverride [default = default]	domain	string(50)	no	readOnly	Machine's domain name. If domain = 'default', Listener will check the DefaultDomain parameter in the ListenerConfig parameter list.		
FireStationAlertingOperatorId	fsa_opid	int32	yes	readOnly	The FSA_OPID column is used to define what console position (operator ID) orginated the alert. It is used for Fire Station Alerting-Moscad.		
IsForRemoteAccessOnly [default = false]	remote_only	boolean	no	readOnly	Is the machine defined for remote access only? Y means machine is defined for remote access only, and cannot run the I/CAD Listener locally. N means machine can run the Listener locally.		
TerminalDescription	description	string(50)	yes	readOnly	Description for terminal node.		
 TerminalName	term	string(15)	no	readOnly	Terminal Node Name		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References

Terminal	ChangeSubscriber	0..1	*	Terminal	ChangeSubscribers	TerminalName	TerminalName
Terminal	TerminalSpecialApplication	1	*	Terminal	TerminalSpecialApplications	TerminalName	TerminalName

 [Top](#)

Entity Type Name - TerminalSpecialApplication							
Description	This table stores the special applications that are allowed to run on each terminal node. The list of valid special applications is stored in the caddbm NodesSpecApps parameter list.						
Base Table Name	term_special_app						
View Name	cmvTerminalSpecialApplication						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 SpecialApplicationName	special_app	string(15)	no	readOnly	Special application		
 TerminalName	term	string(15)	no	readOnly	Terminal Node Name		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Terminal	TerminalSpecialApplication	1	*	Terminal	TerminalSpecialApplications	TerminalName	TerminalName

 [Top](#)

Entity Type Name - TowRequest							
Description	This table is used to store information about a request for towing a particular vehicle associated with an event via vehic supplemental information.						
Base Table Name	tow_request						
View Name	cmvTowRequest						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId [Monitored]	num_1	string(12)	no	readOnly	Event number for which vehicle tow service requested		
ChangeComment	history_comment	string(200)	yes	readWrite	Latest tow request history comment		
CommentText [Monitored]	comment_text	string(200)	yes	readWrite	Tow request creation comment		
CommonEventId	eid	int32	no	readOnly	Id of associated event record		
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee id of operator creating the tow service request		
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	The tow service request creation terminal		
CreatedTime [Monitored]	cdts	dateTimeOffset	no	readOnly	Tow service request creation date time stamp		
HasCancelBeenRequested [default = false] [Monitored]	cancel_requested	boolean	no	readOnly	A request to cancel the tow request has been made		
IsPickupLocationVerified	pickup_loc_ver	boolean	no	readOnly	Location verified status for the tow request pickup location		
LockingTerminal	updt_term	string(15)	yes	readOnly	If not NULL, then the record is locked by the terminal id in this column		
PickupLocation [Monitored]	pickup_location	string(80)	no	readOnly	Location for vehicle pickup		
PickupLocationXCoordinate	pickup_loc_x	int32	no	readOnly	Pickup location x coordinate in uors		
PickupLocationYCoordinate	pickup_loc_y	int32	no	readOnly	Pickup location y coordinate in uors		
RequestStatus [Monitored]	request_status	int16	no	readOnly	Overall status of tow request. Pending=0, InProgress=1, PartialService=2, CompleteService=3, Closed=4, Canceled=5		
RequestStatusChangeTime	status_dts	dateTimeOffset	no	readOnly	Date time stamp when request status changed to current status		
 TowRequestId [Monitored]	request_num	int32	no	readOnly	Tow service request number		
UnitId [Monitored]	unid	string(10)	yes	readOnly	Unit id assigned to event for which vehicle tow service requested		
UpdatedEmployeeId [default = 0]	upers	int32	yes	readOnly	Update employee id		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Update terminal		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update timestamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	TowRequest	1	*	AgencyEvent	TowRequests	AgencyEventId	AgencyEventId
CommonEvent	TowRequest	1	*	CommonEvent	TowRequests	CommonEventId	CommonEventId
TowRequest	TowRequestHistory	1	*	TowRequest	TowRequestHistories	TowRequestId	TowRequestId
ValidUnit	TowRequest	0..1	*	ValidUnit	TowRequests	UnitId	UnitId
TowRequest	TowRequestVehicle	1	*	TowRequest	TowRequestVehicles	TowRequestId	TowRequestId

 [Top](#)

Entity Type Name - TowRequestAndVehicleHistory							
Description	Maintains the relationship between rows in tow_request_history and those in tow_request_vehicle_history						
Base Table Name	tow_req_and_vehic_history						
View Name	cmvTowRequestAndVehicleHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Create timestamp		
RevisionNumber	rev_num	int32	no	readOnly	The revision number for this table		
 TowRequestAndVehicleHistoryId	unique_id	guid	no	readOnly	Uniquely identifies rows		
TowRequestId	request_num	int32	no	readOnly	The request_num from tow_request_history		
TowRequestRevisionNumber	request_rev_num	int32	no	readOnly	The rev_num from tow_request_history		
TowRequestVehicleId	vehicle_id	int32	yes	readOnly	The vehicle_id from tow_request_vehicle_history		
TowRequestVehicleRevisionNum	vehicle_rev_num	int32	yes	readOnly	The rev_num from tow_request_vehicle_history		
TowRequestVehicleTowRequestId	vehicle_request_num	int32	yes	readOnly	The request_num from tow_request_vehicle_history		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
TowRequestHistory	TowRequestAndVehicleHistory	1	*	TowRequestHistory	TowRequestAndVehicleHistories	TowRequestId, RevisionNumber	TowRequestId, TowRequestRevisionNumber
TowRequestVehicleHistory	TowRequestAndVehicleHistory	0..1	*	TowRequestVehicleHistory	TowRequestAndVehicleHistories	TowRequestId, TowRequestVehicleId, RevisionNumber	TowRequestVehicleTowRequestId, TowRequestVehicleId, TowRequestVehicleRevisionNum

 [Top](#)

Entity Type Name - TowRequestHistory							
Description	This table is used to store information about a request for towing a particular vehicle associated with an event via vehic supplemental information.						
Base Table Name	tow_request_history						
View Name	cmvTowRequestHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	no	readOnly	Event number for which vehicle tow service requested		
ChangeComment	history_comment	string(200)	yes	readOnly	Latest tow request history comment		
CommentText	comment_text	string(200)	yes	readOnly	Tow request creation comment		
CommonEventId	eid	int32	no	readOnly	Id of associated event		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee id of operator creating the tow service request		
CreatedTerminal	cterm	string(15)	no	readOnly	The tow service request creation terminal		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Tow service request creation date time stamp		
HasCancelBeenRequested [default = false]	cancel_requested	boolean	no	readOnly	A request to cancel the tow request has been made		
IsPickupLocationVerified	pickup_loc_ver	boolean	no	readOnly	Location verified status for the tow request pickup location		
PickupLocation	pickup_location	string(80)	no	readOnly	Location for vehicle pickup		
PickupLocationXCoordinate	pickup_loc_x	int32	no	readOnly	Pickup location x coordinate in uors		
PickupLocationYCoordinate	pickup_loc_y	int32	no	readOnly	Pickup location y coordinate in uors		
RequestStatus	request_status	int16	no	readOnly	Overall status of tow request. Pending=0, InProgress=1, PartialService=2, CompleteService=3, Closed=4, Canceled=5		
RequestStatusChangeTime	status_dts	dateTimeOffset	no	readOnly	Date time stamp when request status changed to current status		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of record.		
TowRequestId	request_num	int32	no	readOnly	Tow service request number		
UnitId	unid	string(10)	yes	readOnly	Unit id assigned to event for which vehicle tow service requested		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
TowRequestHistory	TowRequestAndVehicleHistory	1	*	TowRequestHistory	TowRequestAndVehicleHistories	TowRequestId, RevisionNumber	TowRequestId, TowRequestRevisionNumber
TowRequest	TowRequestHistory	1	*	TowRequest	TowRequestHistories	TowRequestId	TowRequestId

[Top](#)

Entity Type Name - TowRequestVehicle							
Description	This table contains vehicle records that are associated with a tow request						
Base Table Name	tow_request_vehicle						
View Name	cmvTowRequestVehicle						
Monitored	Yes						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
CancelledEmployeeId	cancel_pers	int32	yes	readOnly	Vehicle service cancellation operator employee id		
CancelledTerminal	cancel_term	string(15)	yes	readOnly	Vehicle service cancellation terminal		
CancelledTime	cancel_dts	dateTimeOffset	yes	readOnly	Vehicle service cancellation date time stamp		
CommonEventId	vehic_eid	int32	no	readOnly	Vehic supplemental information eid of vehicle		
CommonEventVehicleItemNumber	vehic_row_num	int32	no	readOnly	Vehic supplemental information row_num of vehicle		
CompanyId	company_id	int32	yes	readOnly	Company numeric id		
CompanyName	company_name	string(30)	yes	readOnly	Name of company from Special Request or associated with company_id		
CreatedEmployeeId	cpers	int32	no	readOnly	Creating employee id		
CreatedTerminal	cterm	string(15)	no	readOnly	Creating terminal		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Tow service request vehicle creation date time stamp		
EquipmentType	equipment	string(10)	yes	readOnly	Equipment type		
EstimatedArrivalTime	eta	int32	yes	readWrite	Estimated time of arrival for service		
IsSpecialRequest [default = false]	special_company	boolean	no	readOnly	This is a special company request and any rotation is bypassed.		
IsTowedLocationVerified [default = false]	towed_loc_ver	boolean	no	readOnly	Location verified status for the vehicle's towed location		
MainServiceType	main_svc_type	string(8)	yes	readOnly	Main service type		
PersonContacted	person_contacted	string(25)	yes	readWrite	Name of the company contact		
ReasonForService	reason	string(8)	yes	readWrite	Reason for service		
Remarks	remarks	string(1000)	yes	readWrite	Remarks concerning service		
RotationalServiceCode	rotation_code	string(8)	yes	readOnly	Rotational service code		
SecondaryServiceType	sub_svc_type	string(8)	yes	readOnly	Sub service type		
TowRequestId [Monitored]	request_num	int32	no	readOnly	Tow service request number		
TowRequestVehicleId [Monitored]	vehicle_id	int32	no	readOnly	Vehicle numeric id for tow request		
TowStatus	tow_status	int16	no	readOnly	Status of the tow equipment assigned to the tow request vehicle. The valid values come from the ID column in the cad UnitStatus parameter table. The towing user interface in Dispatcher shows the mnemonic value from UnitStatus. 0: AV (Available), 2: AP (Available on Pager), 7: DP (Dispatched), 8: ER (Enroute), 9: AR (arrive), 13: TR (Transport), 14: TA (Transport Arrive), 15: AK (Acknowledge)		
TowStatusChangeTime	tow_status_dts	dateTimeOffset	no	readOnly	Date time stamp when tow service changed to current status		
TowedLocation	towed_location	string(80)	yes	readOnly	Towed location for vehicle		
UpdatedEmployeeId	upers	int32	yes	readOnly	Updating employee id		
UpdatedTerminal	uterm	string(15)	yes	readOnly	Updating terminal		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Update timestamp		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
CommonEventVehicle	TowRequestVehicle	1	*	CommonEventVehicle	TowRequestVehicles	CommonEventId, ItemNumber	CommonEventId, CommonEventVehicleItemNumber
TowRequestVehicle	TowRequestVehicleHistory	1	*	TowRequestVehicle	TowRequestVehicleHistories	TowRequestId, TowRequestVehicleId	TowRequestId, TowRequestVehicleId
RotationalServiceEquipment	TowRequestVehicle	0..1	*	RotationalServiceEquipment	TowRequestVehicles	CompanyId, EquipmentType	CompanyId, EquipmentType
TowRequest	TowRequestVehicle	1	*	TowRequest	TowRequestVehicles	TowRequestId	TowRequestId

[Top](#)

Entity Type Name - TowRequestVehicleHistory						
Description	This table contains history records about vehicles that are associated with a tow request					
Base Table Name	tow_request_vehicle_history					
View Name	cmvTowRequestVehicleHistory					
Monitored	No					
Properties						
Property Name	Base Column	Data Type	NULL	Access Type	Description	

CancelledEmployeeId	cancel_pers	int32	yes	readOnly	Vehicle service cancellation operator employee id		
CancelledTerminal	cancel_term	string(15)	yes	readOnly	Vehicle service cancellation terminal		
CancelledTime	cancel_dts	dateTimeOffset	yes	readOnly	Vehicle service cancellation date time stamp		
CommonEventId	vehic_eid	int32	no	readOnly	Vehic supplemental information eid of vehicle		
CommonEventVehicleItemNumber	vehic_row_num	int32	no	readOnly	Vehic supplemental information row_num of vehicle		
CompanyId	company_id	int32	yes	readOnly	Company numeric id		
CompanyName	company_name	string(30)	yes	readOnly	Name of company from Special Request or associated with company_id		
CreatedEmployeeId	cpers	int32	no	readOnly	Creating employee id		
CreatedTerminal	cterm	string(15)	no	readOnly	Creating terminal		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Tow service request vehicle creation date time stamp		
EquipmentType	equipment	string(10)	yes	readOnly	Equipment type		
EstimatedArrivalTime	eta	int32	yes	readOnly	Estimated time of arrival for service		
IsSpecialRequest [default = false]	special_company	boolean	no	readOnly	This is a special company request and any rotation is bypassed.		
IsTowedLocationVerified	towed_loc_ver	boolean	no	readOnly	Location verified status for the vehicle's towed location		
MainServiceType	main_svc_type	string(8)	yes	readOnly	Main service type		
PersonContacted	person_contacted	string(25)	yes	readOnly	Name of the company contact		
ReasonForService	reason	string(8)	yes	readOnly	Reason for service		
Remarks	remarks	string(1000)	yes	readOnly	Remarks concerning service		
 RevisionNumber	rev_num	int32	no	readOnly	Revision number of history record		
RotationalServiceCode	rotation_code	string(8)	yes	readOnly	Rotational service code		
SecondaryServiceType	sub_svc_type	string(8)	yes	readOnly	Sub service type		
 TowRequestId	request_num	int32	no	readOnly	Tow service request number		
 TowRequestVehicleId	vehicle_id	int32	no	readOnly	Vehicle numeric id for tow request		
TowStatus	tow_status	int16	no	readOnly	Status of tow service for vehicle		
TowStatusChangeTime	tow_status_dts	dateTimeOffset	no	readOnly	Date time stamp when tow service changed to current status		
TowedLocation	towed_location	string(80)	yes	readOnly	Towed location for vehicle		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
TowRequestVehicleHistory	TowRequestAndVehicleHistory	0..1	*	TowRequestVehicleHistory	TowRequestAndVehicleHistories	TowRequestId, TowRequestVehicleId, RevisionNumber	TowRequestVehicleTowRequestId, TowRequestVehicleId, TowRequestVehicleRevisionNum
TowRequestVehicle	TowRequestVehicleHistory	1	*	TowRequestVehicle	TowRequestVehicleHistories	TowRequestId, TowRequestVehicleId	TowRequestId, TowRequestVehicleId

 [Top](#)

Entity Type Name - TransportLocation							
Description	This table stores a list of transport location information for use in Transport commands.						
Base Table Name	trans_des						
View Name	cmvTransportLocation						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyEventId	num_1	string(12)	yes	readOnly	Agency event number.		
AgencyEventScheduleId	sched_id	string(12)	yes	readOnly	Scheduled event id.		
CommonEventId	eid	int32	no	readOnly	Unique Event Id Number generated by the system. A value of 0 indicates that there is no associated event.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Create date time stamp.		
IsOriginVerified [default = false]	origin_verified	boolean	no	readOnly	Origin verified flag		
IsVerified	verified	boolean	no	readOnly	If the location verified. ("Y" or "N")		
Location	location	string(240)	no	readOnly	Transport location text.		
OriginLocation	origin_location	string(240)	yes	readOnly	Origin location text.		
OriginXCoordinate [default = 0]	origin_x_coord	int32	no	readOnly	X coordinate of the node associated with the origin		
OriginYCoordinate [default = 0]	origin_y_coord	int32	no	readOnly	Y coordinate of the node associated with the origin		
 TransportLocationId	unique_id	guid	no	readOnly			
XCoordinate [default = 0]	x_coord	int32	no	readOnly	This column represents the X coordinate of the node associated with the transport destination.		
YCoordinate [default = 0]	y_coord	int32	no	readOnly	This column represents the Y coordinate of the node associated with the transport destination.		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
AgencyEvent	TransportLocation	0..1	*	AgencyEvent	TransportLocations	AgencyEventId	AgencyEventId
CommonEvent	TransportLocation	1	*	CommonEvent	TransportLocations	CommonEventId	CommonEventId

 [Top](#)

Entity Type Name - UnitAgencyRestriction							
Description	Defines which agencies a unit can be dispatched to in a cross-agency dispatch scenario. The unit will be restricted to the agencies listed in this table. This table is only used if the cad EnforcementLevel parameter in the GeneralDetails list is set to 5						
Base Table Name	def_unit_restr_ag_avail						
View Name	cmvUnitAgencyRestriction						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 AgencyId	ag_id	string(9)	no	readOnly	Agency ID. The unit can be dispatched to this agency in a cross-agency dispatch scenario.		
 UnitId	unid	string(10)	no	readOnly	Unit ID		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
Agency	UnitAgencyRestriction	1	*	Agency	UnitAgencyRestrictions	AgencyId	AgencyId
ValidUnit	UnitAgencyRestriction	1	*	ValidUnit	UnitAgencyRestrictions	UnitId	UnitId

 [Top](#)

Entity Type Name - UnitTimer	
Description	Used to maintain data about individual timers
Base Table Name	timer
View Name	cmvUnitTimer
Monitored	Yes
Properties	

Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId [Monitored]	ag_id	string(9)	yes	readOnly	Agency timer is associated with		
Category {hidden}	category				EV = event, UN = unit, GE = general, not associated with event or unit		
ClosingText [Monitored]	closing_text	string(160)	yes	readOnly	Text string associated with closing of the timer.		
CreatedEmployeeId [Monitored]	cpers	int32	no	readOnly	Employee id of creator		
CreatedTerminal [Monitored]	cterm	string(15)	no	readOnly	Terminal node identifier of creator.		
CreatedTime [Monitored]	cdts	dateTimeOffset	no	readOnly	Date, time stamp of when timer is created.		
DispatchGroup [Monitored]	dgroup	string(5)	yes	readOnly	Dispatch group timer is associated with		
IsRepeating [Monitored]	repeat	boolean	no	readOnly	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.		
RevisionNumber	rev_num	int32	no	readOnly	Revision number of unique timer		
SetName [Monitored]	set_name	string(15)	yes	readOnly	Name of set that timer is associated.		
StartedTime [Monitored]	start_dts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer begins executing.		
StatusCode [Monitored]	status_code	int32	no	readOnly	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled		
Timeout [Monitored]	timeout	int32	no	readOnly	timer expiration in seconds. Range can be 1 to max int.		
TimeoutText [Monitored]	timeout_text	string(160)	yes	readOnly	Text string associated with expiration of timer.		
 TimerId [Monitored]	timer_id	guid	no	readOnly	Uniquely identifies the row		
TimerType [Monitored]	type	int32	no	readOnly	The type of timer		
UnitId [Monitored]	object_id	string(30)	no	readOnly	For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name		
UpdatedEmployeeId [Monitored]	upers	int32	yes	readOnly	Employee id of updating person		
UpdatedTerminal [Monitored]	uterm	string(15)	yes	readOnly	Terminal node identifier of updater		
UpdatedTime	udts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer is updated		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
UnitTimer	UnitTimerHistory	1	*	UnitTimer	UnitTimerHistories	TimerId	TimerId
ValidUnit	UnitTimer	1	*	ValidUnit	UnitTimers	UnitId	UnitId

 [Top](#)

Entity Type Name - UnitTimerHistory							
Description	Used to maintain data about individual timer history						
Base Table Name	timer_history						
View Name	cmvUnitTimerHistory						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
AgencyId	ag_id	string(9)	yes	readOnly	Agency timer is associated with		
Category {hidden}	category				EV = event, UN = unit, GE = general, not associated with event or unit		
ClosingText	closing_text	string(160)	yes	readOnly	Text string associated with closing of the timer.		
CreatedEmployeeId	cpers	int32	no	readOnly	Employee id of creator		
CreatedTerminal	cterm	string(15)	no	readOnly	Terminal node identifier of creator.		
CreatedTime	cdts	dateTimeOffset	no	readOnly	Date, time stamp of when timer is created.		
DispatchGroup	dgroup	string(5)	yes	readOnly	Dispatch group timer is associated with		
IsRepeating	repeat	boolean	no	readOnly	Flag to indicate if timer will repeat until cancelled. Valid values are 'T', 'F'.		
 RevisionNumber	rev_num	int32	no	readOnly	Revision number of unique timer		
SetName	set_name	string(15)	yes	readOnly	Name of set that timer is associated.		
StartedTime	start_dts	dateTimeOffset	yes	readOnly	Date, time stamp of when timer begins executing.		
StatusCode	status_code	int32	no	readOnly	Status of the timer: 0 = Created, 1 = Executing, 2 = Closed, 3 = Cancelled		
Timeout	timeout	int32	no	readOnly	timer expiration in seconds. Range can be 1 to max int.		
TimeoutText	timeout_text	string(160)	yes	readOnly	Text string associated with expiration of timer.		
 TimerId	timer_id	guid	no	readOnly	Uniquely identifies the row		
TimerType	type	int32	no	readOnly	The type of timer		
UnitId	object_id	string(30)	no	readOnly	For type EV this is the agency event number, For type UN this is the unit id, For type GE this is a name		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
UnitTimer	UnitTimerHistory	1	*	UnitTimer	UnitTimerHistories	TimerId	TimerId

 [Top](#)

Entity Type Name - UnitWorkload					
Description	This table stores statistics about unit workload. Statistics are maintained about a unit while the unit is logged on. When the unit logs off, the unit's workload statistics are inserted into this table for reporting purposes. Statistics are only written to this table if the UnitStatOut parameter in the cad GeneralDetails parameter list is set to Y.				
Base Table Name	unit_wkload				
View Name	cmvUnitWorkload				
Monitored	No				
Properties					
Property Name	Base Column	Data Type	NULL	Access Type	Description
ActiveTime	time_active	int32	no	readOnly	Number of seconds the unit was logged on.
AvailableStationTime	avail_station	int32	no	readOnly	Available Station Time. Time a unit was available at station headquarters.
CreatedTime	cdts	dateTimeOffset	no	readOnly	Creation Date/Time Stamp for this record. This will correspond to the unit's log off time.
EmergencyEventsWorked	total_emg_wk	int16	no	readOnly	Number of emergency events worked since unit logged on.
EventTime	total_ev_time	int32	no	readOnly	Total amount of time, in seconds, that unit has spent on events since log on.
EventsWorked	total_evt_wk	int16	no	readOnly	Number of events worked.
ScheduledStartTime	started_dts	dateTimeOffset	no	readOnly	Scheduled shift start date/time stamp.
StartDelta	start_delta	int32	no	readOnly	Difference in time of true start of shift from scheduled start of shift.
StationMoves	station_move	int16	no	readOnly	Total number of station/post moves.

TransportCount	transp_count	int16	no	readOnly	Total number of transports that a unit has worked since logon.		
UnavailableTime	unavail_time	int32	no	readOnly	Total time, in seconds, that the unit was unavailable, not including out of service time, since logon. Unavailable means that the unit was on an assignment and not available to be dispatched to a new event.		
UnitId	unid	string(10)	no	readOnly	The unit id for which this record was inserted.		
 UnitWorkloadId	unique_id	guid	no	readOnly	Uniquely identifies rows		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ValidUnit	UnitWorkload	1	*	ValidUnit	UnitWorkloads	UnitId	UnitId

[Top](#)

Entity Type Name - ValidDevice							
Description	Stores all the valid device ids in the system. This table is populated via triggers on device-related tables. This table is needed for the conceptual model, so that all devices are guaranteed to have a parent record. CR 1-6PGD42: PLT						
Base Table Name	valid_device						
View Name	cmvValidDevice						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 DeviceId	device_id	string(40)	no	readOnly	Unique device id for the specified device type. For MDTs and SMTs, the device ID must be a positive integer. For radios mounted in a vehicle, this may be the radio alias. For hand held radios, this may be the radio id. This may also be a GUID or UUID received from an external system		
 DeviceSubtypeCode [default = 0]	device_sub_type	int16	no	readOnly	Qualifier on the device type. Used when CAD system has interfaces to multiple external systems of the same type, such as multiple RADIO systems, each of which may have its own set of unique ids. The cad DeviceSubType parameter table defines the valid sub-types for each device type, and it maps the sub-type numbers to a configurable name.		
 DeviceTypeCode	device_type	int16	no	readOnly	Device type. 0 = Unknown, 1 = Other, 2 = GPS Device, 3 = Radio Alias, 4 = HT Radio, 5 = SMT, 6 = MDT		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ValidDevice	ActiveUnitDeviceHistory	1	*	ValidDevice	ActiveUnitDeviceHistories	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode
ValidDevice	ActiveUnitDevice	1	*	ValidDevice	ActiveUnitDevices	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode
ValidDevice	ActiveUnitEmployeeDeviceHist	1	*	ValidDevice	ActiveUnitEmployeeDeviceHists	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode
ValidDevice	ActiveUnitEmployeeDevice	1	*	ValidDevice	ActiveUnitEmployeeDevices	DeviceTypeCode, DeviceSubtypeCode, DeviceId	DeviceTypeCode, DeviceSubtypeCode, DeviceId
ValidDevice	DefinedDevice	1	0..1	ValidDevice	DefinedDevice	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode
ValidDevice	LineupUnitDevice	1	*	ValidDevice	LineupUnitDevices	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode
ValidDevice	LineupUnitEmployeeDevice	1	*	ValidDevice	LineupUnitEmployeeDevices	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubtypeCode
ValidDevice	MdtLoggedOnEmployee	1	*	ValidDevice	MdtLoggedOnEmployees	DeviceId, DeviceTypeCode, DeviceSubtypeCode	DeviceId, DeviceTypeCode, DeviceSubTypeCode

[Top](#)

Entity Type Name - ValidUnit							
Description	Defines all of the valid unit ids for the system. This table is populated via triggers on unit-related tables.						
Base Table Name	valid_unit						
View Name	cmvValidUnit						
Monitored	No						
Properties							
Property Name	Base Column	Data Type	NULL	Access Type	Description		
 UnitId	unid	string(10)	no	readOnly	Unit ID		
Associations							
Principal Entity Type	Dependent Entity Type	Principal Multiplicity	Dependent Multiplicity	Navigation Property To Principal	Navigation Property To Dependent	Principal Property References	Dependent Property References
ValidUnit	ActiveUnitHistory	1	*	ValidUnit	ActiveUnitHistories	UnitId	UnitId
ValidUnit	ActiveUnit	1	0..1	ValidUnit	ActiveUnit	UnitId	UnitId
ValidUnit	AgencyEventDisposition	0..1	*	ValidUnit	AgencyEventDispositions	UnitId	UnitId
ValidUnit	AgencyRosterUnitEmployee	1	*	ValidUnit	AgencyRosterUnitEmployees	UnitId	UnitId
ValidUnit	DefinedUnit	1	0..1	ValidUnit	DefinedUnit	UnitId	UnitId
ValidUnit	DeploymentRunCardUnit	1	*	ValidUnit	DeploymentRunCardUnits	UnitId	UnitId
ValidUnit	ExternalRequestedResource	1	*	ValidUnit	ExternalRequestedResources	UnitId	UnitId
ValidUnit	LineupUnit	1	*	ValidUnit	LineupUnits	UnitId	UnitId
ValidUnit	RecommendHistory	1	*	ValidUnit	RecommendHistories	UnitId	UnitId
ValidUnit	ResponseRequirementCriterion	0..1	*	ValidUnit	ResponseRequirementCriteria	UnitId	UnitId
ValidUnit	ScheduledDispatchAssignedEvent	1	*	ValidUnit	ScheduledDispatchAssignedEvents	UnitId	UnitId
ValidUnit	TowRequest	0..1	*	ValidUnit	TowRequests	UnitId	UnitId
ValidUnit	UnitAgencyRestriction	1	*	ValidUnit	UnitAgencyRestrictions	UnitId	UnitId
ValidUnit	UnitTimer	1	*	ValidUnit	UnitTimers	UnitId	UnitId
ValidUnit	UnitWorkload	1	*	ValidUnit	UnitWorkloads	UnitId	UnitId

[Top](#)

Functions

Function Name	For Database	Oracle: Deterministic	Sql Server: Schema Bound	Description
add_tz	both	No	No	Adds timezone information to a timestamp.
ansi_concat	oracle	No	No	Concatenates two strings.
big_epoch_seconds	both	No	No	Return the number of seconds since 1/1/1970 12:00 a.m. UTC. Supports dates beyond 2038.
bigint_to_datetimeoffset	both	No	No	Converts the number of seconds since midnight, January 1, 1970 to a UTC datetime value. Supports dates beyond 2038.
binary_to_guid	both	No	No	Converts a binary value to a guid
boolean_to_integer	both	No	No	Converts a boolean value to an integer
boolean_to_string	both	No	No	Converts a boolean value to a string
compare_dts	both	No	No	Date/time stamp comparison function
convert_to_xml_format	sqlServer	No	No	Converts input to xml format.
create_date	both	No	No	Creates a datetime value given a year, month, day of week, day instance, hour, and minute. The first day of the week is assumed to be Sunday.
datetime_to_bigint	both	No	No	Converts a UTC datetime value to the number of seconds since midnight, January 1, 1970. Supports dates beyond 2038.
datetime_to_local_dow	both	No	No	Converts a UTC datetime value to the day of week. Sunday = 1 through Saturday = 7 Null = 0
datetime_to_string	both	No	No	Converts a UTC datetime value to a timestamp string in either UTC or local time
datetimeoffset_to_bigint	both	No	No	Converts a UTC datetime value to the number of seconds since midnight, January 1, 1970. Supports dates beyond 2038.
datetimeoffset_to_local_dow	both	No	No	Converts a UTC datetime value to the day of week. Sunday = 1 through Saturday = 7 Null = 0
datetimeoffset_to_string	both	No	No	Converts a UTC datetime value to a timestamp string in either UTC or local time

get_dst_day_instance	both	No	No	Returns the instance number of the day when the time changes from standard time to daylight savings time. First occurrence = 1, Second = 2, Third = 3, Fourth = 4, Last = 5
get_dst_day_of_week	both	No	No	Returns the day of the week when the time changes from standard time to daylight savings time. Sunday = 1 to Saturday = 7
get_dst_hour	both	No	No	Returns the hour when the time changes from standard time to daylight savings time. 0 to 23
get_dst_minute	both	No	No	Returns the minute when the time changes from standard time to daylight savings time. 0 to 59
get_dst_month	both	No	No	Returns the month when the time changes from standard time to daylight savings time. January = 1 to December = 12
get_dst_name	both	No	Yes	Return the daylight savings time identifier
get_dst_offset	both	No	Yes	Returns the offset of daylight savings time from standard time in minutes
get_dis	both	No	No	Return the current date/time stamp
get_offset_from_utc	both	No	Yes	Returns the offset of local time from UTC time in minutes offset = UTC - local time
get_parameter_value	oracle	No	No	Returns a parameter value based on the given set name, list name, parameter name, and override list
get_std_day_instance	both	No	No	Returns the instance number of the day when the time changes from daylight savings time to standard time. First occurrence = 1, Second = 2, Third = 3, Fourth = 4, Last = 5
get_std_day_of_week	both	No	No	Returns the day of the week when the time changes from daylight savings time to standard time. Sunday = 1 to Saturday = 7
get_std_hour	both	No	No	Returns the hour when the time changes from daylight savings time to standard time. 0 to 23
get_std_minute	both	No	No	Returns the minute when the time changes from daylight savings time to standard time. 0 to 59
get_std_month	both	No	No	Returns the month when the time changes from daylight savings time to standard time. January = 1 to December = 12
get_std_name	both	No	Yes	Return the standard time identifier
get_time_skew_tolerance	both	No	No	Returns the time skew tolerance in seconds. This is the amount of time that clocks can differ between the clients and the database server.
GetCreateMapViewStatement	both	No	No	Get statement that will create a view on the specified map table. The create view statement will only contain columns that have supported data types. If the base table does not exist, the function returns null. CR 1-5LXDSV: Create MAP A/B views with specific columns
guid_to_binary	both	No	No	Converts a guid value to a binary
integer_to_boolean	both	No	No	Converts an integer value to a boolean
is_dst_now	both	No	No	Returns true if daylight savings time is currently in effect
is_dst_used	both	No	Yes	True if daylight savings time is used false otherwise
is_hex_number	sqlServer	No	No	Returns 1 if a string consists of 1 or more hex digits else 0
is_utc_used	both	No	Yes	True if UTC is used, false otherwise
last_day_of_month	sqlServer	No	No	Returns the date of last day of the month specified by the given date
local_to_utc	both	No	No	Converts a local timestamp string to a UTC timestamp string
next_occurrence_of_day	sqlServer	No	No	Returns the date of the next specified weekday after the given date
put_tz_after_hour	both	No	No	Reorder date/time stamps that have timezones at the end so that string compare will work
put_tz_at_end	both	No	No	Reorder date/time stamps that have timezones after the hour and put it at the end
string_to_boolean	both	No	No	Converts a string to a boolean value
string_to_datetime	both	No	No	Converts a local or UTC timestamp string to a UTC datetime value
string_to_datetimeoffset	both	Yes	Yes	Converts a local or UTC timestamp string to a UTC datetime value
tz_to_offset	both	No	Yes	Returns the offset from UTC in hours and minutes that corresponds to the timestamp suffix
utc_to_local	both	No	No	Converts utc timestamp string to a local timestamp string

 [Top](#)

Procedures

Procedure Name	For Database	Description
CreateAevenViewWithCustomCols	both	Rather than simply using the static delivered view definition, create or replace the view with the custom columns included.
CreateEventViewWithCustomCols	both	Rather than simply using the static delivered view definition, create or replace the view with the custom columns included.
CreateMapView	both	Create one map view, given the table name and view name. CR 1-5LXDSV: Create MAP A/B views with specific columns
CreateMapViews	both	Create map views, based on views listed in map_views. This procedure creates the appropriate views on a live database and a map staging database. CR 1-5LXDSV: Create MAP A/B views with specific columns
get_parameter_value	sqlServer	Returns a parameter value based on the given set name, list name, parameter name, and override list
pcsGetChange	both	The procedure pcsGetChange returns a change record. pcsGetChange reads and deletes from the change_record table, which acts as a FIFO queue. Triggers populate the change_record table. pcsGetChange is called from the Change Publisher Service. Input: wait_time_sec: Number of seconds to wait for data to arrive in table Output: status: Status of operation. 0 = success, 1 = timeout expired change_id: Change identifier change_data: Formatted XML describing change error_str: unused max_age_minutes: Only return data that is newer than this many minutes old. Change Publisher throws away data older than this limit, so don't bother passing it to Change Publisher. Defaults to 10 minutes
pcsPurgeChangeRecords	both	Purge records from the change_record table. A job calls this procedure. Parameters: deleteRowsOlderThanMinutes number default 60: Delete rows older than this number of minutes batchSizeIntervalRows number default 10000: Delete (and commit in Oracle) in batches of this size sleepIntervalSeconds number default 1: Sleep this many seconds in between each batch of deletes.
pcsRecordChange	both	Record a change by inserting a row into the change_record table. The Change Subscription triggers call this procedure.
PurgeConnTransCount	both	This procedure is called by the purge_conn_trans_count job, to periodically remove old records from the conn_trans_count table. Parameter deleteRowsOlderThanHours must be 7 days (7 * 24 hours) or more.

 [Top](#)

Oracle Sequences

Sequence Name	Minimum	Maximum	Increment By	Cache Size	Starting Value	Cycle	Order	Description
change_record_seq	1	9223372036854775807	1	100	1	yes	no	The procedure pcsGetChange uses this sequence to generate a unique id for each change.

 [Top](#)

Oracle Packages

Package Name	Description
ingr_xml_util	Contains functions to convert various input data types into an XML formatted string. Used by Change Subscription mechanism.

 [Top](#)

Database Procedural Code

Object Name	For Database	Description
avl_poll_grp	both	Add default rows to avl_poll_grp, if the table is empty
create_ag_com_event_temp_lock_checks	oracle	Optionally, create certification constraints which ensure that when the application issues a commit, temp_lock is set to F in agency_event and common_event. This prevents events from disappearing because they are locked. The CAD DB Utility doesn't fully support deferred constraints, which is why we use an anonymous block.
create_service	oracle	Create CADDB service. I/CAD applications will connect to the primary database using this service. This service is a critical component of the Data Guard client failover solution.
create_string_constraints	sqlServer	Create the optional certification constraints on all string columns. These constraints prevent the applications from mistakenly inserting an empty string instead of NULL.
CreateAevenViewWithCustomCols	both	Rather than simply using the static delivered view definition, create or replace the view with the custom columns included.
CreateEventViewWithCustomCols	both	Rather than simply using the static delivered view definition, create or replace the view with the custom columns included.
CreateFullTextIndexes	both	Add a full text search index for messa.msg_text column
CreateMapViews	both	Run CreateMapViews procedure to create map views. CR 1-5LXDSV: Create MAP A/B views with specific columns
drop_primary_key_triggers	both	Drop the certification primary key triggers prior to running this file
drop_udts_triggers	both	Drop the certification udts triggers prior to running this file.
grant_dictionary_permission	oracle	Specifically grant select any dictionary privilege to cad owner, so that Data Guard startup and shutdown triggers work properly. Cad user should already have this permission via a role, but the triggers require that the user be specifically granted this permission.
GrantPrivsToCadUserRole	oracle	If the database is setup to use a different Oracle login for the user and owner, grant permissions to the cad_user_role on any new objects that this file has created.
initialize_map_switch_table	both	Insert default row into map_switch_table, if table is empty
initialize_map_views	both	Insert default rows into the map_views table

setup_purge_change_records_job	both	Setup job to purge old change records. The job runs every hour and purges records older than 1 hour. In the SQL Server version, the job is created for the current database on the local server, and the job is owned by the current login.
setup_purge_conn_trans_count_job	both	Setup job to purge old conn_trans_count records.
SetupBlockingAndDeadlockExtendedEventSession	sqlServer	Setup SQL Server extended event session to log deadlocks and blocked processes to an XEL file on the server
SetupDBMirroringExtendedEventSession	sqlServer	Setup SQL Server extended event session to log database mirroring state change information to an XEL file on the server
start_service	oracle	If this is the primary database, start CADDDB service if it is not already started.

 [Top](#)

Miscellaneous Items

Object Name	Object Type	For Database	Description
check_database_setup	checkDatabaseSetup	both	Check that database is setup correctly
CheckAlwaysOnClusterSettings	executeCustomFunction	sqlServer	Check AlwaysOn failover threshold and failover period cluster settings
gather_oracle_system_stats	gatherInitialOracleSystemStats	oracle	If requested, tell Oracle to gather system statistics, such as I/O and memory, for the database server machine.
grant_permissions	executeExternalProgram	oracle	Grant execute on dbms_service to cad user. This permission is needed for the Data Guard startup and shutdown triggers.
set_replace_virtual_columns_false	executeExternalProgram	oracle	Set_replace_virtual_columns parameter to false to workaround Oracle bug with function based indexes

 [Top](#)

Conceptual Model Database Procedural Code

Object Name	For Database	Description
change_item	both	If the user asks to create the change subscription objects, then modify the data in the change_item table so that it matches which entities, properties and associations are flagged for monitoring.
change_item_temp	both	If the CAD Database Utility is going to modify the data in change_item, create a temporary table, change_item_temp, to use when processing data.
DropChangeSubscriptionTriggers	both	If the user asked to create the change subscription objects, first drop any triggers with the tce or tcd prefix.
DropOldViews	both	
GrantPrivsToCadUserRole	oracle	If the database is setup to use a different Oracle login for the user and owner, grant permissions to the cad_user_role on any new conceptual model views.
subscription_change_item	both	If the user asks to create the change subscription objects, then remove any entries from subscription_change_item that don't have corresponding entries in change_item