

MIT-IIT Robotics Program

Amartya Shankha Biswas

May 27, 2017

Outline

- 1 Recap
- 2 Logical Expressions
 - Booleans
 - New Operators
- 3 Conditionals
 - If Else Statements
 - Nested Conditionals
- 4 Exercises

Outline

- 1 Recap
- 2 Logical Expressions
 - Booleans
 - New Operators
- 3 Conditionals
 - If Else Statements
 - Nested Conditionals
- 4 Exercises


Booleans

A New Data Type

Booleans only have two possible values – True or False

Statement

Schrodinger's cat is dead !



Booleans

A New Data Type

- In C++ we have a **bool** data-type

```
bool var = true;
```

- Actually stored as integer (**true** is 1 and **false** is 0)

Booleans

A New Data Type

- In C++ we have a **bool** data-type

```
bool var = true;
```

- Actually stored as integer (**true** is 1 and **false** is 0)
- In the other direction
 - Zero value is **true**
 - Non-Zero value is **false**

Outline

- 1 Recap
- 2 Logical Expressions
 - Booleans
 - New Operators
- 3 Conditionals
 - If Else Statements
 - Nested Conditionals
- 4 Exercises

Relational Operators

Operation	Common Symbol	C++ Symbol	Expression
Equals	$=$	<code>==</code>	$(a == b)$
Not Equals	\neq	<code>!=</code>	$(a != b)$
Less Than	$<$	<code><</code>	$(a < b)$
Greater Than	$>$	<code>></code>	$(a > b)$
Less Than Equals	\leq	<code><=</code>	$(a \leq b)$
Greater Than Equals	\geq	<code>>=</code>	$(a \geq b)$

Logical Operators

Operation	Symbol	Expression
And	<code>&&</code>	$(a \neq b) \ \&\& \ (a \% 2 == 0)$
Or	<code> </code>	$(a > b) \ \ (a/2 > 4)$
Not	<code>!</code>	$!(a == b)$

Outline

- 1 Recap
- 2 Logical Expressions
 - Booleans
 - New Operators
- 3 Conditionals
 - If Else Statements
 - Nested Conditionals
- 4 Exercises

If and Else


The **else** statement is optional.

```
if (temperature >= 38)
    cout << "Buy an ice cream cone" << endl;
else
    cout << "Buy a lollipop" << endl;
```

Must use a block (surrounded by curly braces) for more than one line.

```
if (number_of_lines > 1) {
    cout << "More than one line.";
    cout << "Have to use a block.";
}
else{
    cout << "Curly braces are optional.";
}
```

The if...else if...else Statement



The if...else if...else Statement

To test multiple conditions, we can cascade if statements

```
if (temperature >= 35) {  
    cout << "Buy an ice cream cone" << endl;  
}  
else if (temperature >= 25) {  
    cout << "Buy a lollipop" << endl;  
}  
else if (temperature >= 15) {  
    cout << "Buy a coffee" << endl;  
}  
else {  
    cout << "Buy a sweater !" << endl;  
}
```


The **if...else if...else** Statement

- The first statement must be an *if*.
- After this, there can be any number of *if else* statements.
- At the end, there can be one (or zero) *else* statement.

Outline

- 1 Recap
- 2 Logical Expressions
 - Booleans
 - New Operators
- 3 Conditionals
 - If Else Statements
 - Nested Conditionals
- 4 Exercises

Nested Conditionals



Nested Conditionals

```
if (temperature >= 35) {  
    if (money >= 45) {  
        cout << "Buy a Cornetto" << endl;  
        money -= 45;  
        if (money > 0) {  
            cout << "Buy a candy" << endl;  
        }  
        else  
            cout << "Out of Money :(" << endl;  
    }  
    else  
        cout << "Buy a Pepsi" << endl;  
}  
else {  
    cout << "Buy a lollipop" << endl;  
}
```

Lab Time !

Write programs for each of the following specifications

Input	Output
Four integers	Maximum and second max value
Three points (vertices of triangle) in terms of (x, y) coordinates	Whether the triangle is equilateral, isosceles, or scalene
Cutoff for A, B, C grades, and also marks of one student (out of 100)	Whether the cutoffs are valid, and what grade the student received.
All number from 1 to 5 ?	d
c	d

Age Guessing Game

Write a program that asks the user questions of the form " Is your age less than 50". The user can only respond with 1 (yes) or 0 (no).

Challenge – Guess age in seven questions or less.