


Local P-adaptivity with the Discontinuous Galerkin Method

Devin Light
Scott Moe

March 13th, 2015

1D DG-FEM



Conservation law weak form:

- Multiply by test function:

$$\frac{1}{2} \int_{-1}^1 \varphi^{(\ell)} \{q_{,t} + f(q)_{,x}\} d\xi = 0$$


- Integrate by parts

$$\frac{1}{2} \int_{-1}^1 \varphi^{(\ell)} q_{,t} d\xi = \frac{1}{\Delta x} \left(\int_{-1}^1 f(q^h) \varphi_{\xi}^{(k)} d\xi - \left[(\varphi^{(k)} f(q))|_{\xi=1} - (\varphi^{(k)} f(q))|_{\xi=-1} \right] \right)$$

- Galerkin ansatz:

$$q(t, \xi) \sim \sum_{k=0}^N Q^{(k)}(t) \varphi^{(k)}(\xi)$$

1D DG-FEM



Conservation law weak form:

- Use an Orthogonal Basis:

$$\frac{1}{2} \int_{-1}^1 \varphi^{(\ell)} q_{,t} = \frac{1}{2k+1} \dot{Q}^{(k)}$$

- Semi-discrete:

$$\dot{Q}_i^{(k)} = \frac{2k+1}{\Delta x} \int_{-1}^1 f(q^h) \varphi_\xi^{(k)} d\xi - \frac{2k+1}{\Delta x} \left[\varphi^{(k)}(1) F_{i+\frac{1}{2}} - \varphi^{(k)}(-1) F_{i-\frac{1}{2}} \right]$$


- For $k=0$:

$$\dot{Q}_i^{(0)} = -\frac{1}{\Delta x} \left[F_{i+\frac{1}{2}} - F_{i-\frac{1}{2}} \right]$$

Orthogonal Series

- For continuous functions series coefficients converge.
- Coefficients give us a proxy for error.
- Small coefficients have little effect on our solution.
- If f has a derivative ν of bounded variation

$$\|f - f_p\| = \sum_{i=p+1}^{\infty} c_k \varphi^{(k)}(\xi) \leq \frac{1}{\nu(p - \nu)^{\nu}}$$



hp-Adaptivity

- Discretize domain with cells of size h
- h -adaptivity \rightarrow Adaptive Mesh Refinement
- Discretize using piecewise continuous polynomials of order p .
- p -adaptivity \rightarrow Add higher order polynomials:

$$q(t, \xi) = \sum_{k=0}^p Q^{(k)}(t) \varphi^{(k)}(\xi)$$

- For smooth functions:
higher order polynomials \rightarrow **MUCH** better approximation

Constructing an Algorithm

- For DG p can be different on each cell
- The highest coefficient gives an indication of error on each cell
- Each coefficient requires extra work
- Idea:
 - 1 Very small coefficients \rightarrow can be ignored
 - 2 Large coefficients \rightarrow need more resolution
- This is complicated by the PDE
 - 1 All PDEs \rightarrow propagate information
 - 2 Hyperbolic PDEs \rightarrow propagation is finite
 - 3 Cells with high-order neighbors may soon need high-order


Outline of the Algorithm

- Pick a maximum order p_M and project initial conditions

Our P-adaptive algorithm:

- 1 Eliminate coefficients below a tolerance ϵ
- 2 Determine time-interval between local order modifications
- 3 Set buffer region (determined from characteristic speeds)
- 4 Evolve coefficients over the interval
- 5 Repeat until we have reached the final time

Buffer Regions



Buffer Regions

