

LESSON 307 (1.5 AATD)

Lesson Objective

This lesson continues to develop the student's knowledge and skill with respect to attitude instrument flying. Also, VOR and DME arc procedures will be introduced.

Briefing

- Review homework assigned in the previous lesson.
- Outline the objectives and completion standards of the lesson.
- Establish the student and instructor responsibilities.
- Student questions.

Lesson Content (Simulator)

System Power Up

- Student Tells, Student Does.
 - Have the student start the simulator using the checklist and assist.
 - Ensure that the student checks GPS database currency.
 - Half-left, half-up, flag out of view.
 - Ensure that there are no red 'x's.
 - Have the student start the engine using the checklist.

Instrument Cockpit Check

- Student Tells, Student Does.
 - Have the student read each item from the checklist out loud.
 - Demonstrate to the student what needs to be done for each item.
 - Discipline the student to set bugs, bearing pointers, and any auxiliary features.

Before Taxi Checks

- Student Tells, Student Does.
 - Airspeed indicator (PFD and standby): zero.
 - Attitude indicator (PFD): pitch/bank deviations +/- 5 degrees.
 - Standby attitude indicator: discuss standby battery check and adjust the miniature aircraft (cannot be performed in the ATD).
 - Altimeter (PFD and standby): +/- 75 feet of station elevation.
 - Vertical speed indicator (PFD): reads 0 or use current indication.
 - Trim coordinator: wings level or no vector when still; inclinometer centered when still; skids when turning.
 - HSI: matches compass and turns appropriately.
 - Magnetic compass: indicates heading properly, no bubbles, card present, and swings freely.

Give the student a departure via radar vectors. The instructor simulates ATC. Have the student switch to the appropriate frequencies throughout the simulator lesson.

VOR Intercepting and Tracking

- *The autopilot can be used at first in order for the student to get a better understanding of what to do.*
- Intercepting Within 5NM:
 - Instructor Tells, Student Does.
 - Specify a radial for the student to intercept outbound.
 - Have the student make note of the distance.
 - The proper radial is to be tuned before the intercept is applied with a FROM indication.
 - Coach the student on bugging the proper intercept angle.
 - If the autopilot is in HDG NAV mode, the autopilot will intercept the radial on its own.
- Tracking VOR Radial:
 - Instructor Tells, Student Does.
 - Note that the autopilot will transition to CAP, CAP SOFT, SOFT (NAV) modes.
 - The autopilot will lead the radial and set up a wind correction angle.
 - While the autopilot is tracking, tell the student about anticipating wind using wind direction indicators and the track bugs.
- Intercepting Outside 5NM:
 - Instructor Tells, Student Does.
 - Give the student another radial to intercept outbound from the VOR.
 - Listen for the student to note the current radial.
 - Ensure that the student notes the difference and doubles.
 - Guide the student in twisting the desired course before applying any intercept.
 - Ask the student which direction the airplane should fly to intercept – the shortest turn should be used.
 - Guard the student against using $<20^\circ$ or $>90^\circ$.
 - Have the student bug the intercept heading and intercept the radial.
 - Repeat the above steps as time permits, challenging the student with Inbound to Outbound or Outbound to Inbound turns.
- VOR Orientation (Optional):
 - Instructor Tells, Student Does.
 - This exercise can be used if the student is struggling with VOR orientation.
 - The instructor will click and drag the student to various locations around a VOR.
 - Next the instructor asks which radial the student is on.
 - This can be repeated rapidly and as often as needed, with either a CDI, HSI, or RMI.

Intercepting and Tracking DME Arcs

- Intercepting from a Radial:
 - Instructor Tells, Student Does.
 - Note the radial, direction, and distance from the station.
 - Pause if needed – Give ARC Instructions with Compass Direction, Distance, and

the Fix.

- Make sure the student understands the instruction.
- The no-wind intercept is 100° to the present radial (Advance OBS 10° and add 90° in direction of the arc).
- Join the arc at 0.5 nm prior to the arc – immediately advance OBS 10°
- Make sure OBS is set up in the FROM indication.
- If undershooting the arc, roll out early; If overshooting, continue turn to intercept the arc.
- Tracking a DME Arc:
 - Instructor Tells, Student Does.
 - For this lesson, focus on the turn 10 / twist 10 method.
 - Coach the student on Turn 10°, Twist 10°.
 - Tell the student how to anticipate wind using wind direction indicators and the track bugs.
 - Correct 10° at a time if DME distance increases or decreases – do not tolerate 0.5 NM error.
- Joining a Radial from a DME Arc:
 - Instructor Tells, Student Does.
 - Choose a radial inbound or outbound a reasonable angular distance away.
 - Tell the student that it is best to set the HSI or CDI #1 to the desired course.
 - The Bearing Pointer or CDI #2 is best used for the arc.
 - Coach the student on using the Bearing Pointer to continue the arc.
 - Guide the student in selecting a Lead Radial 5° prior to the desired course.
 - Upon reaching the lead radial, begin a turn to the desired course.

Localizer Intercepting and Tracking

- Intercepting the Localizer:
 - Instructor Tells, Student Does.
 - Choose a localizer, such as I-MLB, to track.
 - Vector the student toward the localizer (simulate how approach would do it).
 - Coach the student through setting up the instruments:
 - Weather (obtain the ATIS).
 - Instruments (load the procedure, tune and ID the localizer, set up the PFD to the correct NAV source, and set the approach course).
 - Radios (set COM1/COM2).
 - Enroute brief (this step can be skipped in stage 1).
 - Descent and arrival checklist.
 - Stress to the student to turn early once the needle leaves full scale deflection.
 - Add flaps 10 prior to joining the localizer.

- Tracking the Localizer:
 - Instructor Tells, Student Does.
 - Remind the student of any wind direction indicators or track bugs.
 - Stress the use of early, small corrections.
 - Have the student track inbound until the runway threshold.
 - If the student can, then have them follow the glideslope.
 - If not, then instruct them to do a constant rate descent at 90 knots starting at the final approach fix (tell them where that is).

Post-Brief

- Student Self Critique.
- Instructor critique.
- Questions from the student.
- Lesson grading.
- Logbook completion.
- Schedule the next lesson.
- Preview the next lesson → 308.
- Assign Homework:
 - FIT procedures for VOR Intercepting and Tracking.
 - FIT procedures for Intercepting and Tracking DME Arcs from radials and radar vectors.

Completion Standards

The student should:

1. Demonstrate both the instrument cross-check and interpretation necessary to maintain control with respect to attitude instrument flying.
2. Demonstrate an understanding of VOR, DME arc, and localizer procedures.