

# Tcl Variable Utilities

Version 0.6

Alex Baker

<https://github.com/ambaker1/vutil>

July 26, 2023

## **Abstract**

This package provides various utilities for working with variables in Tcl, including read-only variables, TclOO garbage collection, and an object-variable type system.

---

# Printing Variables to Screen

The *pvar* command is a short-hand function for printing the name and values of Tcl variables, in the same style as the Tcl *parray* command.

```
pvar $name1 $name2 ...
```

`$name1 $name2 ...`      Name(s) of variables to print

## Example 1: Printing variables to screen

*Code:*

```
set a 5
set b 7
set c(1) 5
set c(2) 6
pvar a b c
```

*Output:*

```
a = 5
b = 7
c(1) = 5
c(2) = 6
```

---

# Initializing Local Namespace Variables

The command *local* is the counterpart to the Tcl *global* command, and creates local variables linked to variables in the current namespace, by simply calling the Tcl *variable* command multiple times.

```
local $name1 $name2 ...
```

`$name1 $name2 ...`      Name(s) of variables to initialize

## Example 2: Access namespace variables in a procedure

*Code:*

```
# Define global variables
global a b c
set a 1
set b 2
set c 3
namespace eval ::foo {
    # Define local variables
    local a b c
    set a 4
    set b 5
    set c 6
}
proc ::foo::bar1 {} {
    # Access global variables
    global a b c
    list $a $b $c
}
proc ::foo::bar2 {} {
    # Access local variables
    local a b c
    list $a $b $c
}
puts [::foo::bar1]; # global a b c
puts [::foo::bar2]; # local a b c
```

---

*Output:*

```
1 2 3
4 5 6
```

---

## Default Values

The command *default* assigns values to variables if they do not exist.

```
default $varName $value
```

**\$varName**                      Name of variable to set

**\$value**                        Default value for variable

The example below shows how default values are only applied if the variable does not exist.

### Example 3: Variable defaults

*Code:*

```
set a 5
default a 7; # equivalent to "if {[info exists a]} {set a 7}"
puts $a
unset a
default a 7
puts $a
```

*Output:*

```
5
7
```

---

## Variable Locks

The command *lock* uses Tcl variable traces to make a read-only variable. This is especially useful for controlling a parameter study of an analysis from a top-level.

```
lock $varName <$value>
```

**\$varName**                      Variable name to lock.

**\$value**                      Value to lock variable at. Default self-locks (uses current value).

The command *unlock* unlocks previously locked variables so that they can be modified again.

```
unlock $name1 $name2 ...
```

**\$name1 \$name2 ...**              Variables to unlock.

### Example 4: Variable locks

*Code:*

```
lock a 5
set a 7
puts $a
unlock a
set a 7
puts $a
```

*Output:*

```
5
7
```

---

## Variable-Object Ties

As of Tcl version 8.6, there is no garbage collection for Tcl objects, they have to be removed manually with the “destroy” method. The command *tie* is a solution for this problem, using variable traces to destroy the corresponding object when the variable is unset or modified. For example, if an object is tied to a local procedure variable, the object will be destroyed when the procedure returns. Tie is separate from lock; a tie will override a lock, and a lock will override a tie.

```
tie $refName <$object>
```

**\$refName**                      Name of reference variable to tie to object.

**\$object**                      Object to tie variable to. Default self-ties (uses current value).

In similar fashion to *unlock*, tied variables can be untied with the command *untie*.

```
untie $name1 $name2 ...
```

**\$name1 \$name2 ...**              Variables to untie.

### Example 5: Variable-object ties

*Code:*

```
oo::class create foo {
    method hi {} {
        puts hi
    }
}
tie a [foo create bar]
set b $a; # alias variable
unset a; # triggers ``destroy''
$b hi; # throws error
```

*Output:*

```
invalid command name "::bar"
```

---

## Variable-Object Links

The command *link* links a global variable to a TclOO object, using the name of the object as the variable name. The value of the linked object variable is accessed by calling the TclOO object with no arguments (the “unknown” method), and writing to the object-variable calls the object’s “=” method. Unsetting the linked object variable also calls the object’s “destroy” method, and destroying the object unsets the linked object variable. Linked object-variables are unlinked when the object is destroyed, but can also be unlinked with the command *unlink*.

```
link $Object
```

```
unlink $Object ...
```

*\$Object* ...                      Object(s) to link/unlink.

### Example 6: Linking an object variable

*Code:*

```
::oo::class create number {
    variable value
    constructor {args} {
        set value [uplevel 1 expr $args]
    }
    method unknown {args} {
        if {[llength $args] == 0} {
            return $value
        }
        next {*}$args
    }
    unexport unknown
    method = {args} {
        set value [uplevel 1 expr $args]
    }
    export =
}
link [tie a [number new 5]]; # garbage collection and obj-var link
puts [$a]; # 5
$a = 10 * [$a]
puts [$a]; # 50
incr $a
puts [subst $$a]; # 51
```

*Output:*

```
5
50
51
```

---

## Object Variable Class

The TclOO class *var* creates linked object variables that are tied to local variables, using *link* and *tie*.

Object variables can be manipulated directly with Tcl commands, and calling the object variable directly as a command with no arguments (e.g. [*\$varObj*]) returns the object variable value.

```
var new $refName <$value>
var create $objName $refName <$value>
```

<b>\$objName</b>	Explicit name for object.
<b>\$refName</b>	Name of reference variable to tie to object.
<b>\$value</b>	Value to set object variable to.

### Example 7: Object variables with garbage collection

*Code:*

```
# Example showing how object variables behave in procedures
proc foo {value} {
    # Create named object with reference variable "result"
    var create myObj result $value
    append $result { world}
    return [list $result [$result]]; # Returns name and value of object
}
set result [foo hello]; # Not the same "result"
lassign $result name value
puts $name; # ::myObj
puts $value; # hello world
puts [info object isa object $name]; # 0 (object was deleted when procedure returned)
```

*Output:*

```
::myObj
hello world
0
```



## Object Variable Operators

In addition to being able to manipulate object variables directly with Tcl commands, variables can also be manipulated with object variable operators.

The operators “=” and “:=” assign the value of the object variable, and return the name of the object.

```
$varObj = $value
```

```
$varObj := $expr
```

**\$value**                      Value to set object variable to.

**\$expr**                      Math expression to evaluate and set as object value.

The operator “<-” assigns the value of the object directly from another object variable of the same class, and, like the operator “=”, returns the name of the object.

```
$varObj <- $otherVarObj
```

**\$otherVarObj**              Other object variable to assign value from.

The operator “-->” copies the object to a new reference variable, and returns the name of the new object.

```
$varObj --> $refName
```

**\$refName**                      Name of reference variable to tie to object.

The example below demonstrates the myriad of ways object variables can be manipulated:

### Example 8: Object variable manipulation features

*Code:*

```
var new x; # Create blank variable $x
[$x --> y] = 5; # Copy $x to $y, and set to 5
[var new z] <- [$x <- $y]; # Create $z and set to x after setting $x to $y.
$z := {[$z] + [$x]}; # Add $x to $z
append $y [set $x 0]; # Append $y the value of $x after setting $x to 0
puts [list [$x] [$y] [$z]]
```

*Output:*

```
0 50 10
```

## Object Variable Methods

Additional information about the object variable can be accessed with object variable methods:

The operator “&” simply returns the name of the object.

```
$varObj &
```

The method *info* accesses all object variable metadata. Fields “exists” and “type” always exist, and “value” is populated when the variable is initialized.

```
$varObj info <$field>
```

**\$field** Info field to get. Default returns dictionary of all info.

The method *print* is a short-hand way to print the value of the variable to screen.

```
$varObj print <-newline> <$channelID>
```

**-newline** Option to print without newline.

**\$channelID** Channel ID open for writing. Default stdout.

### Example 9: Printing the value of a variable

*Code:*

```
var new x {Hello World}
puts [$x info]
$x print
```

*Output:*

```
exists 1 type var value {Hello World}
Hello World
```

---

## Object Variable Types

The TclOO class *var* acts as a superclass for a pure-Tcl type system, managed through the metaclass *type*.

```
type $method $arg ...
```

<code>\$method</code>	Method name.
<code>\$arg ...</code>	Arguments for method.

New type classes can be created using the method *new*. The resulting class, named “`::vutil::type.$type`”, uses “`::vutil::var`” as a superclass.

```
type new $type $arg ...
```

<code>\$type</code>	Name of type.
<code>\$arg ...</code>	Class definition arguments.

Existing classes can be added to the type library directly with the method *add*. These classes do not need to be subclasses of “`::vutil::var`”, but it is recommended to utilize “`::vutil::var`” as a superclass.

```
type add $type $class
```

<code>\$type</code>	Name of type.
<code>\$class</code>	Type class.

To remove a type, use the method *remove*. This does not destroy the associated class, but simply removes the class from the type list.

```
type remove $type
```

<code>\$type</code>	Name of type.
---------------------	---------------

## Type Queries

A list of all defined types can be queried with the method *names*.

```
type names
```

The existence of a type can be queried with the method *exists*, and the class associated with a type can be queried with the method *class*.

```
type exists $type
```

```
type class $type
```

**\$type**                      Name of type.

The method *isa* checks if an object is of a specific type or of one of its subtypes. If the type or object does not exist, this command will return an error.

```
type isa $type $objName
```

**\$type**                      Name of type.

**\$objName**                  Name of object.

### Example 10: Type assertion

Code:

```
proc foo {bar} {  
    if {![type isa list $bar]} {  
        return -code error "bar must be a list object"  
    }  
    $bar @ end  
}
```

## Creating Type Variables

Then, using the types defined by *type*, the command *new* creates a new variable object of a specified type.

```
new $type $refName <$value>
```

<b>\$type</b>	Name of type.
<b>\$refName</b>	Name of reference variable to tie to object.
<b>\$value</b>	Value to set object variable to.

### Example 11: New type and object variables

*Code:*

```
type new str {
  method info {args} {
    set (length) [my length]
    next {*} $args
  }
  method length {} {
    string length $(value)
  }
  method @ {i} {
    string index $(value) $i
  }
  export @
}
new str x
set $x {hello world}
puts [$x length]
puts [$x info]
puts [$x @ end]
$x print
```

*Output:*

```
11
exists 1 length 11 type str value {hello world}
d
hello world
```

---

## Type Library

This package provides a few basic object variable types: *var*, *string*, *bool*, *int*, *float*, *list*, and *dict*. If you want to create your own datatype, check out the source code implementation for API documentation.

### Type “var”

The type “*var*” is just an alternative way to create an object variable (same syntax as “new” method for *var* class). It does not have any additional metadata or methods.

```
new var $refName <$value>
```

<b>\$refName</b>	Name of reference variable to tie to object.
<b>\$value</b>	Value to set object variable to.

### Type “string”

The type “*string*” does not do any validation on input (because in Tcl, “everything is a string”), but additionally provides methods for getting string length and string index, and adds the field “length” to the variable info.

```
new string $refName <$value>
```

<b>\$refName</b>	Name of reference variable to tie to object.
<b>\$value</b>	String value.

The method *length* returns the string length. This is the same as “`$stringObj info length`”.

```
$stringObj length
```

The method “@” returns the character at the specified index.

```
$stringObj @ $i
```

<b>\$i</b>	String index.
------------	---------------

## Type “bool” (boolean)

The type “bool” validates that the input is a valid boolean.

```
new bool $refName <$value>
```

**\$refName**                      Name of reference variable to tie to object.

**\$value**                        Boolean value.

In addition to the standard object variable methods, the “bool” type provides a shorthand if-statement control flow method:

```
$boolObj "?" $body1 <":" $body2>
```

**\$body1**                        Body to evaluate if boolean is true.

**\$body2**                        Body to evaluate if boolean is false (optional, required with “:” keyword).

### Example 12: String and boolean example

*Code:*

```
# proc with types
proc foo {a b c} {
    new string a $a
    new string b $b
    new bool c $c
    $c ? {$a} : {$b}
}
puts [foo hello world true]; # hello
puts [foo hello world false]; # world
```

*Output:*

```
hello
world
```

## Type “int” (integer)

The type “int” validates that the input is a valid integer, and additionally has increment/decrement methods.

```
new int $refName <$value>
```

**\$refName**                      Name of reference variable to tie to object.

**\$value**                        Integer value.

In addition to the standard assignment operators “=” and “:=”, the “int” type provides the increment/decrement assignment operators “+=” and “-=”.

```
$intObj $op $expr
```

**\$op**                            Assignment operator:

“+=” Increments the variable by the value of **\$expr**.

“-=” Decrements the variable by the value of **\$expr**.

**\$expr**                        Tcl math expression to evaluate.

There are also two short-hand increment/decrement operators, “++” and “--”, which simply increment or decrement the integer object by 1.

```
$intObj ++
```

```
$intObj --
```

### Example 13: Integer example (for loop)

*Code:*

```
for {new int i 0} {[i] < 3} {[i] ++} {  
    puts [i]  
}
```

*Output:*

```
0  
1  
2
```



## Type “float” (double-precision floating-point decimal)

The type “float” validates that input is a double-precision floating-point number, passing input through the Tcl `::tcl::mathfunc::double` command.

```
new float $refName <$value>
```

**\$refName**                      Name of reference variable to tie to object.

**\$value**                      Float value.

In addition to the standard assignment operators “=” and “:=”, the “float” type provides the following:

```
$floatObj $op $expr
```

**\$op**                      Assignment operator:

“+=” Adds the value of **\$expr** to the variable.

“-=” Subtracts the value of **\$expr** from the variable.

“\*=” Multiplies the variable by the value of **\$expr**.

“/=” Divides the variable by the value of **\$expr**.

**\$expr**                      Tcl math expression to evaluate.

### Example 14: Float example (procedure with type assertion)

*Code:*

```
# Harmonic mean of two numbers (converts to float)
proc hmean {x y} {
    new float x $x
    new float y $y
    [new float z] := {2*[$x]*[$y]}
    if {[$z] != 0} {
        $z /= {[$x] + [$y]}
    }
    return [$z]
}
puts [hmean 1 2]; # 1.3333
```

*Output:*

```
1.3333333333333333
```

## Type “list”

The type “list” validates that the input is a list, and provides methods for list indexing/setting and getting list length. Additionally, it adds the field “length” to the variable info.

```
new list $refName <$value>
```

**\$refName**                      Name of reference variable to tie to object.

**\$value**                      List value.

The method *length* returns the list length. This is the same as “`$listObj info length`”.

```
$listObj length
```

The method “@” acts as either list indexing or list setting, depending on whether the “=” or “:=” keywords are used. If indexing, it returns the value at the specified index. If setting, it sets the value and returns the object name.

```
$listObj @ $i ... < "=" $value | ":" $expr>
```

**\$i ...**                      List indices.

**\$value**                      Value to set.

**\$expr**                      Math expression to set.

### Example 15: List example

*Code:*

```
[new list list1] = {hello world}
puts [$list1 length]; # 2
$list1 @ 0 = "hey"
$list1 @ 1 = "there"
$list1 @ end+1 = "world"
puts [$list1 @ end]; # world
set a 5
$list1 @ end+1 := {$a + 1}
puts [$list1 info]; # exists 1 length 4 type list value {hey there world 6}
```

*Output:*

```
2
world
exists 1 length 4 type list value {hey there world 6}
```

## Type “dict”

The type “*dict*” validates that the input is a Tcl dictionary, and provides methods for getting/setting/unsetting dictionary values, checking if values exist, and getting the dictionary size. Additionally, it adds the field “size” to the variable info.

```
new dict $refName <$value>
```

**\$refName**                      Name of reference variable to tie to object.

**\$value**                        Dictionary value.

The method `$dictObj size` returns the dictionary size. This is the same as “`$dictObj info size`”.

```
$dictObj size
```

The methods *set* and *unset* set and unset values in the dictionary, and return the object name. The method *get* returns values in the dictionary, and the method *exists* returns whether the key pairing exists.

```
$dictObj set $key ... $value
```

```
$dictObj unset $key ...
```

```
$dictObj get $key ...
```

```
$dictObj exists $key ...
```

**\$key ...**                      Dictionary keys.

**\$value**                        Value to set.

### Example 16: Dictionary example

*Code:*

```
# Create dictionary record
new dict record {
  name {John Doe}
  address {
    streetAddress {123 Main Street}
    city {New York}
    state {NY}
    zip {10001}
  }
  phone {555-1234}
}

# Get values
puts [$record size]; # Number of keys (3)
puts [$record get name]; # John Doe
# Set/unset and get
$record set address street [$record get address streetAddress]
$record unset address streetAddress
puts [$record get address street]; # 123 Main Street
puts [$record exists address streetAddress]; # 0
```

---

*Output:*

```
3
John Doe
123 Main Street
0
```