

N-Dimensional Lists (ndlist)

Version 0.11

Alex Baker

<https://github.com/ambaker1/ndlist>

May 24, 2025

Abstract

One of the drawbacks of the Tcl programming language is its lack of data structures. This package is an attempt to fill that gap, to provide the basic data structures that every programmer is familiar with: vectors, matrices, tables, and higher-dimensional arrays.

This package is also a [Tin](#) package, and can be loaded in as shown below:

Example 1: Installing and loading “ndlist”

Code:

```
package require tin 2.1
tin autoadd ndlist https://github.com/ambaker1/ndlist install.tcl
tin import ndlist
```

1-Dimensional Lists (Vectors)

Lists are foundational to Tcl, so in addition to providing utilities for ND-lists, this package also provides utilities for working with 1D-lists, or vectors.

Range Generator

The command *range* simply generates a list of integer values. This can be used in conjunction with the Tcl *foreach* loop to simplify writing “for” loops. There are two ways of calling this command, as shown below.

```
range $n
range $start $stop <$step>
```

\$n	Number of indices, starting at 0 (e.g. 3 returns 0 1 2).
\$start	Starting value.
\$stop	Stop value.
\$step	Step size. Default 1 or -1, depending on direction of start to stop.

Example 2: Integer range generation

Code:

```
puts [range 3]
puts [range 0 2]
puts [range 10 3 -2]
```

Output:

```
0 1 2
0 1 2
10 8 6 4
```

Example 3: Simpler for-loop

Code:

```
foreach i [range 3] {
    puts $i
}
```

Output:

```
0
1
2
```

Logical Indexing

The command *find* returns the indices of non-zero elements of a boolean list, or indices of elements that satisfy a given criterion. Can be used in conjunction with *nget* to perform logical indexing.

```
find $list <$op $scalar>
```

\$list	List of values to compare.
\$op	Comparison operator. Default “!=”.
\$scalar	Comparison value. Default 0.

Example 4: Filtering a list

Code:

```
set x {0.5 2.3 4.0 2.5 1.6 2.0 1.4 5.6}
puts [nget $x [find $x > 2]]
```

Output:

```
2.3 4.0 2.5 5.6
```

Linear Interpolation

The command *linterp* performs linear 1D interpolation. Converts input to double.

```
linterp $x $xList $yList
```

\$x	Value to query in \$xList
\$xList	List of x points, strictly increasing
\$yList	List of y points, same length as \$xList

Example 5: Linear interpolation

Code:

```
puts [linterp 2 {1 2 3} {4 5 6}]
puts [linterp 8.2 {0 10 20} {2 -4 5}]
```

Output:

```
5.0
-2.92
```

Vector Generation

The command *linspace* can be used to generate a vector of specified length and equal spacing between two specified values. Converts input to double.

```
linspace $n $start $stop
```

\$n	Number of points
\$start	Starting value
\$stop	End value

Example 6: Linearly spaced vector generation

Code:

```
puts [linspace 5 0 1]
```

Output:

```
0.0 0.25 0.5 0.75 1.0
```

The command *linspace* generates intermediate values given an increment size and a sequence of targets. Converts input to double.

```
linspace $step $x1 $x2 ...
```

\$step	Maximum step size
\$x1 \$x2 ...	Targets to hit.

Example 7: Intermediate value vector generation

Code:

```
puts [linspace 0.25 0 1 0]
```

Output:

```
0.0 0.25 0.5 0.75 1.0 0.75 0.5 0.25 0.0
```

Functional Mapping

The command *lapply* simply applies a command over each element of a list, and returns the result. The command *lapply2* maps element-wise over two equal length lists.

```
lapply $command $list $arg ...
```

```
lapply2 $command $list1 $list2 $arg ...
```

<code>\$list</code>	List to map over.
<code>\$list1 \$list2</code>	Lists to map over, element-wise.
<code>\$command</code>	Command prefix to map with.
<code>\$arg ...</code>	Additional arguments to append to command after list elements.

Example 8: Applying a math function to a list

Code:

```
# Add Tcl math functions to the current namespace path
namespace path [concat [namespace path] ::tcl::mathfunc]
puts [lapply abs {-5 1 2 -2}]
```

Output:

```
5 1 2 2
```

Example 9: Mapping over two lists

Code:

```
lapply puts [lapply2 {format "%s %s"} {hello goodbye} {world moon}]
```

Output:

```
hello world
goodbye moon
```

List Statistics

The commands *max*, *min*, *sum*, *product*, *mean*, *median*, *stdev* and *pstdev* compute the maximum, minimum, sum, product, mean, median, sample and population standard deviation of values in a list. For more advanced statistics, check out the Tellib `math::statistics` package.

```
max $list
```

```
min $list
```

```
sum $list
```

```
product $list
```

```
mean $list
```

```
median $list
```

```
stdev $list
```

```
pstdev $list
```

`$list` List to compute statistic of.

Example 10: List Statistics

Code:

```
set list {-5 3 4 0}
foreach stat {max min sum product mean median stdev pstdev} {
  puts [list $stat [$stat $list]]
}
```

Output:

```
max 4
min -5
sum 2
product 0
mean 0.5
median 1.5
stdev 4.041451884327381
pstdev 3.5
```

Vector Algebra

The dot product of two equal length vectors can be computed with *dot*. The cross product of two vectors of length 3 can be computed with *cross*.

```
dot $a $b
```

```
cross $a $b
```

`$a` First vector.

`$b` Second vector.

The norm, or magnitude, of a vector can be computed with *norm*.

```
norm $a <$p>
```

`$a` Vector to compute norm of.

`$p` Norm type. 1 is sum of absolute values, 2 is euclidean distance, and Inf is absolute maximum value. Default 2.

Example 11: Dot and cross product

Code:

```
set x {1 2 3}
set y {-2 -4 6}
puts [dot $x $y]
puts [cross $x $y]
```

Output:

```
8
24 -12 0
```

For more advanced vector algebra routines, check out the Tcllib `math::linearalgebra` package.

2-Dimensional Lists (Matrices)

A matrix is a two-dimensional list, or a list of row vectors. This is consistent with the format used in the Tcllib `math::linearalgebra` package. See the example below for how matrices are interpreted.

$$A = \begin{bmatrix} 2 & 5 & 1 & 3 \\ 4 & 1 & 7 & 9 \\ 6 & 8 & 3 & 2 \\ 7 & 8 & 1 & 4 \end{bmatrix}, \quad B = \begin{bmatrix} 9 \\ 3 \\ 0 \\ -3 \end{bmatrix}, \quad C = \begin{bmatrix} 3 & 7 & -5 & -2 \end{bmatrix}$$

Example 12: Matrices and vectors

Code:

```
# Define matrices, column vectors, and row vectors
set A {{2 5 1 3} {4 1 7 9} {6 8 3 2} {7 8 1 4}}
set B {9 3 0 -3}
set C {{3 7 -5 -2}}
# Print out matrices (join with newline to print out each row)
puts "A ="
puts [join $A \n]
puts "B ="
puts [join $B \n]
puts "C ="
puts [join $C \n]
```

Output:

```
A =
2 5 1 3
4 1 7 9
6 8 3 2
7 8 1 4
B =
9
3
0
-3
C =
3 7 -5 -2
```


Generating Matrices

The commands *zeros*, *ones*, and *eye* generate common matrices.

```
zeros $n $m
```

```
ones $n $m
```

`$n` Number of rows

`$m` Number of columns

The command *eye* generates an identity matrix of a specified size.

```
eye $n
```

`$n` Size of identity matrix

Example 13: Generating standard matrices

Code:

```
puts [zeros 2 3]
puts [ones 3 2]
puts [eye 3]
```

Output:

```
{0 0 0} {0 0 0}
{1 1} {1 1} {1 1}
{1 0 0} {0 1 0} {0 0 1}
```

Combining Matrices

The commands *stack* and *augment* can be used to combine matrices, row or column-wise.

```
stack $mat1 $mat2 ...
```

```
augment $mat1 $mat2 ...
```

`$mat1 $mat2 ...` Arbitrary number of matrices to stack/augment (number of columns/rows must match)

The command *block* combines a matrix of matrices into a block matrix.

```
block $matrices
```

`$matrices` Matrix of matrices.

Example 14: Combining matrices

Code:

```
set A [stack {{1 2}} {{3 4}}]
set B [augment {1 2} {3 4}]
set C [block [list [list $A $B] [list $B $A]]]
puts $A
puts $B
puts [join $C \n]; # prints each row on a new line
```

Output:

```
{1 2} {3 4}
{1 3} {2 4}
1 2 1 3
3 4 2 4
1 3 1 2
2 4 3 4
```

Matrix Transpose

The command *transpose* simply swaps the rows and columns of a matrix.

```
transpose $A
```

\$A Matrix to transpose, nxm.

Returns an mxn matrix.

Example 15: Transposing a matrix

Code:

```
puts [transpose {{1 2} {3 4}}]
```

Output:

```
{1 3} {2 4}
```

Matrix Multiplication

The command *matmul* performs matrix multiplication for two matrices. Inner dimensions must match.

```
matmul $A $B
```

\$A Left matrix, nxq.

\$B Right matrix, qxm.

Returns an nxm matrix (or the corresponding dimensions from additional matrices)

Example 16: Multiplying a matrix

Code:

```
puts [matmul {{2 5 1 3} {4 1 7 9} {6 8 3 2} {7 8 1 4}} {9 3 0 -3}]
```

Output:

```
24 12 72 75
```

Miscellaneous Linear Algebra Routines

The command *outerprod* takes the outer product of two vectors, $\mathbf{a} \otimes \mathbf{b} = \mathbf{a}\mathbf{b}^T$.

```
outerprod $a $b
```

\$a \$b Vectors with lengths n and m. Returns a matrix, shape nxm.

The command *kronprod* takes the Kronecker product of two matrices, as shown in Eq. (1).

```
kronprod $A $B
```

\$A \$B Matrices, shapes nxm and pxq. Returns a matrix, shape (np)x(mq).

$$\mathbf{A} \otimes \mathbf{B} = \begin{bmatrix} a_{11}\mathbf{B} & \dots & a_{1n}\mathbf{B} \\ \vdots & \ddots & \vdots \\ a_{n1}\mathbf{B} & \dots & a_{nn}\mathbf{B} \end{bmatrix} \quad (1)$$

Example 17: Outer product and Kronecker product

Code:

```
set A [eye 3]
set B [outerprod {1 2} {3 4}]
set C [kronprod $A $B]
puts [join $C \n]; # prints out each row on a new line
```

Output:

```
3 4 0 0 0 0
6 8 0 0 0 0
0 0 3 4 0 0
0 0 6 8 0 0
0 0 0 0 3 4
0 0 0 0 6 8
```

For more advanced matrix algebra routines, check out the Tcllib `math::linearalgebra` package.

Iteration Tools

The commands *zip* zips two lists into a list of tuples, and *zip3* zip three lists into a list of triples. Lists must be the same length.

```
zip $a $b
```

```
zip3 $a $b $c
```

`$a $b $c`

Lists to zip together.

Example 18: Zipping and unzipping lists

Code:

```
# Zipping
set x [zip {A B C} {1 2 3}]
set y [zip3 {Do Re Mi} {A B C} {1 2 3}]
puts $x
puts $y
# Unzipping (using transpose)
puts [transpose $x]
```

Output:

```
{A 1} {B 2} {C 3}
{Do A 1} {Re B 2} {Mi C 3}
{A B C} {1 2 3}
```

The command *cartprod* computes the Cartesian product of an arbitrary number of vectors, returning a matrix where the columns correspond to the input vectors and the rows correspond to all the combinations of the vector elements.

```
cartprod $a $b ...
```

`$a $b ...`

Arbitrary number of vectors to take Cartesian product of.

Example 19: Cartesian product

Code:

```
puts [cartprod {A B C} {1 2 3}]
```

Output:

```
{A 1} {A 2} {A 3} {B 1} {B 2} {B 3} {C 1} {C 2} {C 3}
```

N-Dimensional Lists (Tensors)

A ND-list is defined as a list of equal length (N-1)D-lists, which are defined as equal length (N-2)D-lists, and so on until (N-N)D-lists, which are scalars of arbitrary size. This definition is flexible, and allows for different interpretations of the same data. For example, the list “1 2 3” can be interpreted as a scalar with value “1 2 3”, a vector with values “1”, “2”, and “3”, or a matrix with row vectors “1”, “2”, and “3”. In general, if a value is valid for N dimensions, it will also be valid for dimensions 0 to N-1.

The command *ndims* returns the rank of an ND-list, and the command *ndims_multiple* returns the rank that is compatible with multiple ND-lists. By default, it automatically determines the rank for the data, but if a rank is provided, it will validate that the ND-list or ND-lists are compatible with the provided rank.

```
ndims $ndlist <$rank>
```

```
ndims_multiple $ndlists <$rank>
```

\$ndlist ND-list.

\$ndlists List of ND-lists.

\$rank Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.

Example 20: Rank of an ND-list

Code:

```
set x {1}
set y {1 2 {hello world}}; # note that this is not a valid 2D list
set z {{1 2 3} {4 5 6}}
puts [ndims $x]; # 0
puts [ndims $y]; # 1
puts [ndims $z]; # 2
puts [ndims_multiple [list $x $y $z]]; # 1
```

Output:

```
0
1
2
1
```

Note: All Tcl values are ND-lists, because a 0D-list is just a string that can’t be parsed as a Tcl list, and in Tcl, everything is a string.

Shape and Size

The commands *nshape* and *nsiz*e return the shape and size of an ND-list, respectively. The shape is a list of the dimensions, and the size is the product of the shape.

```
nshape $ndlist <$rank>
```

```
nsiz
```

e \$ndlist <\$rank>

\$ndlist ND-list to get shape/size of.

\$rank Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.

Example 21: Getting shape and size of an ND-list

Code:

```
set x {{1 2 3} {4 5 6}}
puts [nshape $x]
puts [nsiz
```

e \$x]

Output:

```
2 3
6
```

Initialization

The command *nfull* initializes a valid ND-list of any size filled with a single value.

```
nfull $value $n ...
```

<code>\$value</code>	Value to repeat
<code>\$n ...</code>	Shape (list of dimensions) of ND-list.

Example 22: Generate ND-list filled with one value

Code:

```
puts [nfull foo 3 2]; # 3x2 matrix filled with "foo"  
puts [nfull 0 2 2 2]; # 2x2x2 tensor filled with zeros
```

Output:

```
{foo foo} {foo foo} {foo foo}  
{0 0} {0 0} {0 0} {0 0}
```

The command *nrand* initializes a valid ND-list of any size filled with random values between 0 and 1.

```
nrand $n ...
```

<code>\$n ...</code>	Shape (list of dimensions) of ND-list.
----------------------	--

Example 23: Generate random matrix

Code:

```
expr {srand(0)}; # resets the random number seed (for the example)  
puts [nrand 1 2]; # 1x2 matrix filled with random numbers
```

Output:

```
{0.013469574513598146 0.3831388500440581}
```


Repeating and Expanding

The command *nrepeat* repeats portions of an ND-list a specified number of times.

```
nrepeat $ndlist $n ...
```

\$value	Value to repeat
\$n ...	Repetitions at each level.

Example 24: Repeat elements of a matrix

Code:

```
puts [nrepeat {{1 2} {3 4}} 1 2]
```

Output:

```
{1 2 1 2} {3 4 3 4}
```

The command *nexpand* repeats portions of an ND-list to expand to new dimensions. New dimensions must be divisible by old dimensions. For example, 1x1, 2x1, 4x1, 1x3, 2x3 and 4x3 are compatible with 4x3.

```
nexpand $ndlist $n ...
```

\$ndlist	ND-list to expand.
\$n ...	New shape of ND-list. If -1 is used, it keeps that axis the same.

Example 25: Expand an ND-list to new dimensions

Code:

```
puts [nexpand {1 2 3} -1 2]  
puts [nexpand {{1 2}} 2 4]
```

Output:

```
{1 1} {2 2} {3 3}  
{1 2 1 2} {1 2 1 2}
```

Padding and Extending

The command *npad* pads an ND-list along its axes by a specified number of elements.

```
npad $ndlist $value $n ...
```

\$ndlist	ND-list to pad.
\$value	Value to pad with.
\$n ...	Number of elements to pad.

Example 26: Padding an ND-list with zeros

Code:

```
set a {{1 2 3} {4 5 6} {7 8 9}}
puts [npad $a 0 2 1]
```

Output:

```
{1 2 3 0} {4 5 6 0} {7 8 9 0} {0 0 0 0} {0 0 0 0}
```

The command *nextend* extends an ND-list to a new shape by padding.

```
nextend $ndlist $value $n ...
```

\$ndlist	ND-list to extend.
\$value	Value to pad with.
\$n ...	New shape of ND-list.

Example 27: Extending an ND-list to a new shape with a filler value

Code:

```
set a {hello hi hey howdy}
puts [nextend $a world -1 2]
```

Output:

```
{hello world} {hi world} {hey world} {howdy world}
```

Flattening and Reshaping

The command *nflatten* flattens an ND-list to a vector.

```
nflatten $ndlist <$rank>
```

\$ndlist ND-list to flatten.

\$rank Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.

Example 28: Reshape a matrix to a 3D tensor

Code:

```
set x [nflatten {{1 2 3 4} {5 6 7 8}}]
puts [nreshape $x 2 2 2]
```

Output:

```
{{1 2} {3 4}} {{5 6} {7 8}}
```

The command *nreshape* reshapes a vector into specified dimensions. Sizes must be compatible.

```
nreshape $vector $n ...
```

\$vector Vector (1D-list) to reshape.

\$n ... Shape (list of dimensions) of ND-list. One axis may be dynamic, denoted with a "*".

Example 29: Reshape a vector to a matrix with three columns

Code:

```
puts [nreshape {1 2 3 4 5 6} * 3]
```

Output:

```
{1 2 3} {4 5 6}
```

Index Notation

This package provides generalized N-dimensional list access/modification commands, using an index notation parsed by the command `::ndlist::ParseIndex`, which returns the index type and an index list for the type.

```
::ndlist::ParseIndex $n $input
```

\$n	Number of elements in list.
\$input	Index input. Options are shown below:
:	All indices
\$start:\$stop	Range of indices (e.g. 0:4 or 1:end-2).
\$start:\$step:\$stop	Stepped range of indices (e.g. 0:2:-2 or 2:3:end).
\$iList	List of indices (e.g. {0 end-1 5} or 3).
\$i*	Single index with a asterisk, “flattens” the ndlist (e.g. 0* or end-3*).

Additionally, indices get passed through the `::ndlist::Index2Integer` command, which converts the inputs “end”, “end-integer”, “integer±integer” and negative wrap-around indexing (where -1 is equivalent to “end”) into normal integer indices. Note that this command will return an error if the index is out of range.

```
::ndlist::Index2Integer $n $index
```

\$n	Number of elements in list.
\$index	Single index.

Example 30: Index Notation

Code:

```
set n 10
puts [::ndlist::ParseIndex $n :]
puts [::ndlist::ParseIndex $n 1:8]
puts [::ndlist::ParseIndex $n 0:2:6]
puts [::ndlist::ParseIndex $n {0 5 end-1}]
puts [::ndlist::ParseIndex $n end*]
```

Output:

```
A {}
R {1 8}
L {0 2 4 6}
L {0 5 8}
S 9
```

Access

Portions of an ND-list can be accessed with the command *nget*, using the index parser *::ndlist::ParseIndex* for each dimension being indexed. Note that unlike the Tcl *lindex* and *lrange* commands, *nget* will return an error if the indices are out of range.

```
nget $ndlist $i ...
```

\$ndlist ND-list value.

\$i ... Index inputs, parsed with *::ndlist::ParseIndex*.

Example 31: ND-list access

Code:

```
set A {{1 2 3} {4 5 6} {7 8 9}}
puts [nget $A 0 :]; # get row matrix
puts [nget $A 0* :]; # flatten row matrix to a vector
puts [nget $A 0:1 0:1]; # get matrix subset
puts [nget $A end:0 end:0]; # can have reverse ranges
puts [nget $A {0 0 0} 1*]; # can repeat indices
```

Output:

```
{1 2 3}
1 2 3
{1 2} {4 5}
{9 8 7} {6 5 4} {3 2 1}
2 2 2
```

Modification

A ND-list can be modified by reference with *nset*, and by value with *nreplace*, using the index parser *::ndlist::ParseIndex* for each dimension being indexed. Note that unlike the Tcl *lset* and *lreplace* commands, the commands *nset* and *nreplace* will return an error if the indices are out of range. If all the index inputs are “:” except for one, and the replacement list is blank, it will delete values along that axis by calling *nremove*. Otherwise, the replacement ND-list must be expandable to the target index dimensions.

```
nset $varName $i ... $sublist
```

```
nreplace $ndlist $i ... $sublist
```

\$varName	Variable that contains an ND-list.
\$ndlist	ND-list to modify.
\$i ...	Index inputs, parsed with <i>::ndlist::ParseIndex</i> .
\$sublist	Replacement list, or blank to delete values.

Example 32: Replace range with a single value

Code:

```
puts [nreplace [range 10] 0:2:end 0]
```

Output:

```
0 1 0 3 0 5 0 7 0 9
```

Example 33: Swapping matrix rows

Code:

```
set a {{1 2 3} {4 5 6} {7 8 9}}
nset a {1 0} : [nget $a {0 1} :]; # Swap rows and columns (modify by reference)
puts $a
```

Output:

```
{4 5 6} {1 2 3} {7 8 9}
```

Removal

The command *nremove* removes portions of an ND-list at a specified axis.

```
nremove $ndlist $i <$axis>
```

<code>\$ndlist</code>	ND-list to modify.
<code>\$i</code>	Index input, parsed with <code>::ndlist::ParseIndex</code> .
<code>\$axis</code>	Axis to remove at. Default 0.

Example 34: Filtering a list by removing elements

Code:

```
set x [range 10]
puts [nremove $x [find $x > 4]]
```

Output:

```
0 1 2 3 4
```

Example 35: Deleting a column from a matrix

Code:

```
set a {{1 2 3} {4 5 6} {7 8 9}}
puts [nremove $a 2 1]
```

Output:

```
{1 2} {4 5} {7 8}
```

Insertion and Concatenation

The command *ninsert* inserts an ND-list into another ND-list at a specified index and axis. The ND-lists must agree in dimension at all other axes. If “end” or “end-integer” is used for the index, it will insert after the index. Otherwise, it will insert before the index. The command *ncat* is shorthand for inserting at “end”, and concatenates two ND-lists.

```
ninsert $ndlist1 $index $ndlist2 <$axis> <$rank>
```

```
ncat $ndlist1 $ndlist2 <$axis> <$rank>
```

\$ndlist1 \$ndlist2	ND-lists to combine.
\$index	Index to insert at.
\$axis	Axis to insert/concatenate at (default 0).
\$rank	Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.

Example 36: Inserting a column into a matrix

Code:

```
set matrix {{1 2} {3 4} {5 6}}
set column {A B C}
puts [ninsert $matrix 1 $column 1 2]
```

Output:

```
{1 A 2} {3 B 4} {5 C 6}
```

Example 37: Concatenate tensors

Code:

```
set x [nreshape {1 2 3 4 5 6 7 8 9} 3 3 1]
set y [nreshape {A B C D E F G H I} 3 3 1]
puts [ncat $x $y 2 3]
```

Output:

```
{{1 A} {2 B} {3 C}} {{4 D} {5 E} {6 F}} {{7 G} {8 H} {9 I}}
```


Changing Order of Axes

The command *nswapaxes* is a general purpose transposing function that swaps the axes of an ND-list. For simple matrix transposing, the command *transpose* can be used instead.

```
nswapaxes $ndlist $axis1 $axis2
```

\$ndlist ND-list to manipulate.

\$axis1 \$axis2 Axes to swap.

The command *nmoveaxis* moves a specified source axis to a target position. For example, moving axis 0 to position 2 would change “i,j,k” to “j,k,i”.

```
nmoveaxis $ndlist $source $target
```

\$ndlist ND-list to manipulate.

\$source Source axis.

\$target Target position.

The command *npermute* is more general purpose, and defines a new order for the axes of an ND-list. For example, the axis list “1 0 2” would change “i,j,k” to “j,i,k”.

```
npermute $ndlist $axis ...
```

\$ndlist ND-list to manipulate.

\$axis ... List of axes defining new order.

Example 38: Changing tensor axes

Code:

```
set x {{{1 2} {3 4}} {{5 6} {7 8}}}  
set y [nswapaxes $x 0 2]  
set z [nmoveaxis $x 0 2]  
puts [lindex $x 0 0 1]  
puts [lindex $y 1 0 0]  
puts [lindex $z 0 1 0]
```

Output:

```
2  
2  
2
```

ND Functional Mapping

The command *napply* applies a command over each element of an ND-list, and returns the result. The commands *napply2* maps element-wise over two ND-lists. If the input lists have different shapes, they will be expanded to their maximum dimensions with *nexpand* (if compatible).

```
napply $command $ndlist <$suffix> <$rank>
```

```
napply2 $command $ndlist1 $ndlist2 <$suffix> <$rank>
```

\$ndlist	ND-list to map over.
\$ndlist1 \$ndlist2	ND-lists to map over, element-wise.
\$command	Command prefix to map with.
\$suffix	Additional arguments to append to command after ND-list elements. Default blank.
\$rank	Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.

Example 39: Chained functional mapping over a matrix

Code:

```
napply puts [napply {format %.2f} [napply expr {{1 2} {3 4}} {+ 1}]]
```

Output:

```
2.00
3.00
4.00
5.00
```

Example 40: Format columns of a matrix

Code:

```
set data {{1 2 3} {4 5 6} {7 8 9}}
set formats {{%.1f %.2f %.3f}}
puts [napply2 format $formats $data]
```

Output:

```
{1.0 2.00 3.000} {4.0 5.00 6.000} {7.0 8.00 9.000}
```

Reducing an ND-list

The command *nreduce* combines *nmoveaxis* and *napply* to reduce an axis of an ND-list with a function that reduces a vector to a scalar, like *max* or *sum*.

```
nreduce $command $ndlist <$axis> <$suffix> <$rank>
```

\$command	Command prefix to map with.
\$ndlist	ND-list to map over.
\$axis	Axis to reduce. Default 0.
\$suffix	Additional arguments to append to command after ND-list elements. Default blank.
\$rank	Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.

Example 41: Matrix row and column statistics

Code:

```
set x {{1 2} {3 4} {5 6} {7 8}}
puts [nreduce max $x]; # max of each column
puts [nreduce max $x 1]; # max of each row
puts [nreduce sum $x]; # sum of each column
puts [nreduce sum $x 1]; # sum of each row
```

Output:

```
7 8
2 4 6 8
16 20
3 7 11 15
```

Generalized N-Dimensional Mapping

The command *nmap* is a general purpose mapping function for N-dimensional lists in Tcl. If multiple ND-lists are provided for iteration, they must be expandable to their maximum dimensions. The actual implementation flattens all the ND-lists and calls the Tcl *lmap* command, and then reshapes the result to the target dimensions. So, if “continue” or “break” are used in the map body, it will return an error.

```
nmap <$rank> $varName $ndlist <$varName $ndlist ...> $body
```

\$rank	Rank of ND-list (e.g. 2 for matrix) or “auto” for auto-rank. Default “auto”.
\$varName	Variable name to iterate with.
\$ndlist	ND-list to iterate over.
\$body	Tcl script to evaluate at every loop iteration.

Example 42: Expand and map over matrices

Code:

```
set phrases [nmap 2 greeting {{hello goodbye}} subject {world moon} {  
    list $greeting $subject  
}]  
napply puts $phrases {} 2
```

Output:

```
hello world  
goodbye world  
hello moon  
goodbye moon
```

Loop Index Access

The iteration indices of *nmap* can be accessed with the commands *i*, *j*, and *k*. The commands *j* and *k* are simply shorthand for *i* with axes 1 and 2.

i <\$axis>

j

k

\$axis Dimension to access mapping index at. Default 0.
If -1, returns the linear index of the loop.

Example 43: Finding index tuples that match criteria

Code:

```
set x {{1 2 3} {4 5 6} {7 8 9}}
set indices {}
nmap xi $x {
  if {$xi > 4} {
    lappend indices [list [i] [j]]
  }
}
puts $indices
```

Output:

```
{1 1} {1 2} {2 0} {2 1} {2 2}
```

File Import/Export

The commands *readFile* and *writeFile* perform simple data import/export, while the commands *readMatrix* and *writeMatrix* dynamically convert files to matrix format and matrices to file format.

```
readFile <$option $value ...> <-newline> $file
```

```
readMatrix <$option $value ...> <-newline> $file
```

\$option \$value ... File configuration options, see Tcl *fconfigure* command.

-newline Option to read the final newline if it exists.

\$file File to read data from.

```
writeFile <$option $value ...> <-newline> $file $data
```

```
writeMatrix <$option $value ...> <-newline> $file $data
```

\$option \$value ... File configuration options, see Tcl *fconfigure* command.

-newline Option to not write a final newline.

\$file File to write data to.

\$data Data to write to file.

Example 44: File import/export

Code:

```
# Export matrix to file (converts to csv)
writeMatrix example.csv {{foo bar} {hello world}}
# Read CSV file
puts [readFile example.csv]
puts [readMatrix example.csv]; # converts from csv to matrix
file delete example.csv
```

Output:

```
foo,bar
hello,world
{foo bar} {hello world}
```

Data Conversions

The commands *mat2txt* and *txt2mat* convert between matrix and space-delimited text, where new-lines separate rows. Escaping of spaces and newlines is consistent with Tcl rules for valid lists.

```
mat2txt $mat
```

```
txt2mat $txt
```

\$mat Matrix value.

\$txt Space-delimited values.

The commands *mat2csv* and *csv2mat* convert between matrix and CSV-formatted text, where new lines separate rows. Commas and newlines are escaped with quotes, and quotes are escaped with double-quotes.

```
mat2csv $mat
```

```
csv2mat $csv
```

\$mat Matrix value.

\$csv Comma-separated values.

Example 45: Data conversions

Code:

```
set matrix {{A B C} {{hello world} foo,bar {"hi"}}}
puts {TXT format:}
puts [mat2txt $matrix]
puts {CSV format:}
puts [mat2csv $matrix]
```

Output:

```
TXT format:
A B C
{hello world} foo,bar {"hi"}
CSV format:
A,B,C
hello world,"foo,bar","""hi"""
```

Command Index

`::ndlist::Index2Integer`, 20
`::ndlist::ParseIndex`, 20

`augment`, 10

`block`, 10

`cartprod`, 13
`cross`, 7
`csv2mat`, 31

`dot`, 7

`eye`, 9

`find`, 3

`i`, 29

`j`, 29

`k`, 29
`kronprod`, 12

`lapply`, 5
`lapply2`, 5
`linspace`, 4
`linspace`, 4
`linterp`, 3

`mat2csv`, 31
`mat2txt`, 31
`matmul`, 11
`max`, 6
`mean`, 6
`median`, 6
`min`, 6

`napply`, 26
`napply2`, 26
`ncat`, 24
`ndims`, 14
`ndims_multiple`, 14
`nexpand`, 17
`nextend`, 18
`nflatten`, 19
`nfull`, 16
`nget`, 21
`ninsert`, 24
`nmap`, 28
`nmoveaxis`, 25
`norm`, 7
`npad`, 18
`npermute`, 25
`nrnd`, 16
`nreduce`, 27
`nremove`, 23
`nrepeat`, 17
`nreplace`, 22
`nreshape`, 19
`nset`, 22
`nshape`, 15
`nsize`, 15
`nswapaxes`, 25

`ones`, 9
`outerprod`, 12

`product`, 6
`pstdev`, 6

`range`, 2

readFile, 30

readMatrix, 30

stack, 10

stdev, 6

sum, 6

transpose, 11

txt2mat, 31

writeFile, 30

writeMatrix, 30

zeros, 9

zip, 13

zip3, 13