

```
☒ CREATE TABLE Accounts (  
    AccountID NUMBER PRIMARY KEY,  
    CustomerName VARCHAR2(50),  
    Balance NUMBER  
);  
  
INSERT INTO Accounts VALUES (101, 'Rahul', 10000);  
INSERT INTO Accounts VALUES (102, 'Priya', 5000);  
  
COMMIT;  
  
☒ CREATE OR REPLACE PROCEDURE SafeTransferFunds(  
    p_fromAccount NUMBER,  
    p_toAccount NUMBER,  
    p_amount NUMBER  
)  
IS  
    v_balance NUMBER;  
BEGIN
```

BEGIN

SELECT Balance
INTO v_balance
FROM Accounts
WHERE AccountID = p_fromAccount;

IF v_balance < p_amount THEN
 RAISE_APPLICATION_ERROR(-20001, 'Insufficient Funds');
END IF;

UPDATE Accounts
SET Balance = Balance - p_amount
WHERE AccountID = p_fromAccount;

UPDATE Accounts
SET Balance = Balance + p_amount
WHERE AccountID = p_toAccount;

COMMIT;

```
DBMS_OUTPUT.PUT_LINE('Transfer Successful');
```

```
EXCEPTION
```

```
    WHEN OTHERS THEN
```

```
        ROLLBACK;
```

```
        DBMS_OUTPUT.PUT_LINE (SQLERRM);
```

```
END;
```

```
/
```

```
BEGIN
```

```
    SafeTransferFunds (101,102,3000);
```

```
END;
```

```
/
```

```
 CREATE TABLE Employees(  
    EmployeeID NUMBER PRIMARY KEY,  
    EmployeeName VARCHAR2(50),  
    Salary NUMBER
```

```
EmployeeName VARCHAR2(50),  
Salary NUMBER  
);
```

```
INSERT INTO Employees VALUES(1,'Amit',50000);
```

```
INSERT INTO Employees VALUES(2,'Neha',60000);
```

```
COMMIT;
```

```
CREATE OR REPLACE PROCEDURE UpdateSalary(  
    p_empid NUMBER,  
    p_percent NUMBER  
)  
IS  
BEGIN
```

```
    UPDATE Employees
```

```
    SET Salary = Salary + (Salary*p_percent/100)
```

```
    WHERE EmployeeID = p_empid;
```

```
IF SQL%ROWCOUNT = 0 THEN  
    RAISE NO_DATA_FOUND;  
END IF;
```

```
COMMIT;
```

```
DBMS_OUTPUT.PUT_LINE('Salary Updated');
```

```
EXCEPTION
```

```
    WHEN NO_DATA_FOUND THEN
```

```
        DBMS_OUTPUT.PUT_LINE('Employee ID Not Found');
```

```
END;
```

```
/
```

```
BEGIN
```

```
BEGIN
```

```
    UpdateSalary(1,10);
```

```
END;
```

```
/
```

```
CREATE OR REPLACE PROCEDURE AddNewCustomer(
```

```
    p_id NUMBER,
```

```
    p_name VARCHAR2,
```

```
    p_age NUMBER,
```

```
    p_balance NUMBER
```

```
)
```

```
IS
```

```
BEGIN
```

INSERT INTO Customers
VALUES (p_id,p_name,p_age,p_balance,'FALSE');

COMMIT;

DBMS_OUTPUT.PUT_LINE('Customer Added');

EXCEPTION

WHEN DUP_VAL_ON_INDEX THEN

DBMS_OUTPUT.PUT_LINE('Customer ID Already Exists');

END;

/

BEGIN

AddNewCustomer(105,'Riya',28,15000);

END;

/