



AI on IBM Z

Fraud detection solution template

This solution template provides an example on how to deploy AI using an IBM Z environment, while making use of open source frameworks, Machine Learning for IBM z/OS (MLz), and more.

Within this solution template, there are various phases of the AI lifecycle included. Work through each of the following steps to deploy your own fraud detection solution on IBM Z.

Table of contents

AI model training.....3

AI model deployment.....7

AI model analysis.....11

AI model integration.....16

Ecommerce web application.....17

CICS-cobol application.....24



Step 1

AI model training

We will build a fraud detection AI model by training with the provided rapid AI on IBM Z development Jupyter notebook. Simply point the Jupyter notebook to your dataset and run it to generate your AI model. This trained AI model can then be deployed with MLz.

All sample code for this section is within

```
ai-st-fraud-detection/zST-model-training-jupyter
```

Prerequisites

1. Must have Python (3.9 or 3.10) installed

Dataset guidance

Sample open source credit card transaction dataset can be found on Kaggle -

<https://www.kaggle.com/datasets/ealtman2019/credit-card-transactions>

There are several files included within the download. You can use *credit_card_transactions-ibm_v2.csv* for training. Due to the size of the sample dataset, the provided Jupyter notebook takes a subset of the data to decrease the training time. Please modify the code in the “Fetch and process data” cell of the provided Jupyter notebook later to use more data during training.

Required features

- User (integer) – unique ID for user making transaction
- Card (integer) – unique ID for credit card
- Year (integer) – year of the transaction
- Month (integer) – month of the transaction
- Day (integer) – day of the month of the transaction
- Time (integer) - time of the transaction (HH:MM)
- Amount (float) – dollar amount of the transaction
- Use Chip (string) – the type of transaction (swipe transaction, etc)
- Merchant Name (integer) – unique ID for merchant name
- Zip (integer) – zip code of the transaction

[Access rapid AI on IBM Z development environment](#)

[Provide data](#)

[Model training](#)

[Access trained AI model](#)

Access rapid AI on IBM Z development environment

1. Create and activate Python virtual environment

```
python -m venv env
source env/bin/activate
```

2. Install required Python packages

```
pip install -r requirements.txt
```

3. Run Jupyter

```
jupyter notebook
```

4. View Jupyter interface

Go to localhost:8888 in a web browser

```

AI on IBM Z Model Development

Import required python packages

In [ ]: import numpy as np
import pandas as pd
import sys
import time

# Model training
from sklearn.pipeline import Pipeline
from sklearn.model_selection import train_test_split, GridSearchCV
from sklearn.ensemble import GradientBoostingClassifier, RandomForestClassifier
from sklearn.metrics import precision_score, recall_score, f1_score, accuracy_score

# Data preprocessing
from sklearn.preprocessing import OrdinalEncoder, StandardScaler

# FUNC
from sklearn.pipeline import make_pipeline
from sklearn.compose import ColumnTransformer
from sklearn.pipeline import Pipeline

Input dataset and label

In [ ]: # User must provide filepath to dataset and label name
DATASET_FILENAME = 'datasets/credit_card_transactions.csv'
DATASET_LABEL_NAME = 'Is Fraud?'

Split features and labels from dataset

In [ ]: def split_features_and_labels(dataset_df, label):
    features = dataset_df.copy()
    labels = features.pop(label)
    return features, labels
  
```

Provide data

1. Add your input dataset (csv) into datasets/ directory
2. Add input data to Jupyter notebook
 - Set DATASET_FILENAME to the path to your dataset
 - Set DATASET_LABEL_NAME to the name of the column you're predicting from the dataset



[Access rapid AI on IBM Z development environment](#)

[Provide data](#)

[Model training](#)

[Access trained AI model](#)

Model training

1. Step through and run Jupyter notebook from web browser

```

AI on IBM Z

Import req
In [1]: import numpy
import pandas
import json
import time

# Model training
from sklearn.pipeline import Pipeline
from sklearn.model_selection import train_test_split, GridSearchCV
from sklearn.metrics import GradientBoostingClassifier, RandomForestClassifier
from sklearn.metrics import precision_score, recall_score, f1_score, accuracy_score

# Data preprocessing
from sklearn.preprocessing import OrdinalEncoder, StandardScaler

# Train
from sklearn.dummy import sklearn_dummy
from sklearn.compose import ColumnTransformer
from sklearn.pipeline import Pipeline

Input dataset and label
In [2]: # User must provide filepath to dataset and label name
DATASET_FILEPATH = 'dataset/crowdai_rapid_transactions.csv'
DATASET_LABEL_NAME = 'Is Fraud?'

Split features and labels from dataset
In [3]: def split_features_and_labels(dataset_filepath, label):
features = dataset_filepath.copy()
labels = features.pop(label)
return features, labels
  
```

Access trained AI model

1. Once training is complete, you can find your AI models within the models/directory (choose one for the following AI model deployment step)



☒ 1. AI model training

☐ 2. AI model deployment

☐ 3. AI model analysis

☐ 4. AI model integration

☒ AI model training complete



Prerequisites

1. Must have MLz installed

Step 2

AI model deployment

We will deploy our fraud detection AI model using MLz. We can utilize the model import functionality on the MLz UI. This deployed AI model can then be integrated into applications within the IBM Z environment.

[Go to MLz UI](#)


[Import AI model](#)

[Deploy AI model](#)

[View deployed AI model](#)


Go to MLz UI

1. Sign in with username/password



Import AI model

1. Go to models tab
2. Click import model
3. Enter model name
4. Choose model type
Choose PMML if using your previously trained model
5. Drag and drop model file
Use your previously trained model
6. Click import



[Go to MLz UI](#)


[Import AI model](#)

[Deploy AI model](#)

[View deployed AI model](#)


Deploy AI model

1. Go to models tab
2. Click action button for your model (on right side)
3. Click deploy
4. Enter deployment name
5. Choose deployment type
6. Choose model version
7. Choose scoring service
Note: you should choose the correct scoring service based on your application (e.g. CICS or REST)
8. Click create



View deployed AI model

1. Go to deployments tab
2. Click on action button for your deployed model (on right side)
3. Click view details




✓ 1. AI model training

✓ 2. AI model deployment

○ 3. AI model analysis

○ 4. AI model integration

✓ AI model deployment complete



Prerequisites

1. Must have MLz installed
2. Must have Python installed
3. Must have Git installed
4. Must have Docker or Podman installed

Step 3

AI model analysis

We will analyze our fraud detection AI model using a sample AI on IBM Z Fraud Detection Dashboard. We can invoke the API of this sample dashboard from another sample application to visualize the AI model inferencing.

All sample code for this section is within

```
ai-st-fraud-detection/zST-model-analysis
```

[Get model details for inferencing](#)

[Configure sample application](#)

[Build sample application](#)

[Deploy sample application](#)


[Access sample application](#)

[Analyze credit card events](#)

[Make predication](#)

Get model details for inferencing

1. Go to MLz UI
2. Go to deployments tab
3. Click on action button for your deployed model (on right side)
4. Click view details
5. Copy scoring endpoint



Configure sample application

1. Set the enrionment variables within

```
ai-st-fraud-detection/zST-model-analysis/
env.list
```

- WML_IP_W_PORT (IP address of MLz with port)
- WML_USER (MLz username)
- WML_PASS (MLz password)
- WMLZ_ENDPOINT (scoring endpoint for deployed AI model)

[Get model details for inferencing](#)

[Configure sample application](#)

[Build sample application](#)

[Deploy sample application](#)

[Access sample application](#)

[Analyze credit card events](#)

[Make predication](#)

Build sample application

1. Run command in terminal

```
docker build -t model-analysis .
```

Deploy sample application

1. Run command in terminal (e.g. port 5002)

```
docker run --rm -p 5002:5002 --env-file  
env.list --name model-analysis-app  
model-analysis
```

Access sample application

1. View the following URL in a web browser
<http://{ip address}:{port}>
 - IP address: IP of server you deployed application in
 - Port: port you used with Docker run

[Get model details for inferencing](#)

[Configure sample application](#)

[Build sample application](#)

[Deploy sample application](#)

[Access sample application](#)

[Analyze credit card events](#)

[Make predication](#)

Analyze credit card events

1. Go to sample insights dashboard in web browser
<http://{ip address}:{port}>
2. Go to latest predictions tab



prediction	deployment id	time
Not Fraud	7c6a5801-c0b1-4473-a07b-d0305a9a0177	2020-08-10 13:30:28
Not Fraud	7c6a5801-c0b1-4473-a07b-d0305a9a0177	2020-08-10 13:30:31

Make predication

1. Go to sample insights dashboard in web browser
<http://{ip address}:{port}>
2. Go to latest make predication tab
3. Input json data
4. Click submit



Sample AI on IBM Z Analytics Dashboard - Make Prediction

Make Prediction

Prediction

Transaction Data

```
{  
  "features": [  
    { "feature": 1, "value": 1.0 },  
    { "feature": 2, "value": 1.0 },  
    { "feature": 3, "value": 1.0 },  
    { "feature": 4, "value": 1.0 }  
  ]  
}
```

Submit

✓ 1. AI model training

✓ 2. AI model deployment

✓ 3. AI model analysis

○ 4. AI model integration

✓ AI model analysis complete



Step 4

AI model integration

Choose One:

Ecommerce web application

CICS-COBOL application

We can use our deployed MLz fraud detection AI model and integrate it into different types of applications. The AI model can be analyzed and/or provide inferencing APIs using the sample AI on IBM Z Fraud Detection Dashboard.

Ecommerce web application

The sample e-commerce application is based on the open source EverShop Storefront and has been extended to integrate with the AI on IBM Z Solution Template. EverShop is a GraphQL Based and React ecommerce platform with essential commerce features. Built with React, modular and fully customizable.

All sample code for this section is within

```
ai-st-fraud-detection/zST-storefront-evershop
```

Prerequisites

1. Must have AI on IBM Z Sample Fraud Detection Dashboard deployed for inferencing and analysis
2. Must have Docker installed

[Install and deploy sample
ecommerce application](#)

[Configure sample
ecommerce application](#)

[Access admin panel from
web browser](#)

[Add products](#)

[Configure store settings](#)

[Configure payment
settings](#)

[Configure shipping
settings](#)

[Access sampe ecommerce
application](#)

[Use fraud detection AI model
with EverShop Storefront](#)

Install and deploy sample ecommerce application

1. Set app_url_w_port variable in CheckoutForm.jsx to your server IP and port (ip:port)

```
ai-st-fraud-detection/zST-storefront-  
evershop/packages/evershop/src/components/  
frontStore/stripe/checkout/CheckoutForm.  
jsx
```

2. Run command in terminal

```
docker-compose up
```

Configure sample ecommerce application

Access admin panel from web browser

1. Enter URL in web browser using app url (e.g. localhost)

```
http://localhost:3000/admin
```

2. Login with default admin credentials

- Email: admin@test.com
- Password: password

[Install and deploy sample
ecommerce application](#)

[Configure sample
ecommerce application](#)

[Access admin panel from
web browser](#)

[Add products](#)

[Configure store settings](#)

[Configure payment
settings](#)

[Configure shipping
settings](#)

[Access sampe ecommerce
application](#)

[Use fraud detection AI model
with EverShop Storefront](#)



Add products

1. Create categories

- Click categories from the catalog section
- Click new category
- Add category details
 - Add name (e.g. Kids)
 - Add url key
 - Add meta title
 - Change status to enabled
 - Change include in store menu to yes
- Click save

2. Add products

- Click products from the catalog section
- Click new product
- Add category details
 - Make sure to change add category
 - Make sure to change status to enabled
 - Make sure to change visibility to visible



Install and deploy sample
ecommerce application

[Configure sample
ecommerce application](#)

[Access admin panel from
web browser](#)

[Add products](#)

[Configure store settings](#)

[Configure payment
settings](#)

[Configure shipping
settings](#)

Access sampe ecommerce
application

Use fraud detection AI model
with EverShop Storefront

Configure store settings



1. Enter URL in web browser using app url
(e.g. localhost)
2. Click settings on the bottom left
3. Click store setting

Configure payment settings

1. Click payment setting
2. Enable stripe payment
3. Click save

Configure shipping settings

1. Click shipping setting
2. Add shipping zone
 - Click create new shipping zone
 - Add shipping details
3. Click save



✓ 1. AI model training

Install and deploy sample
ecommerce application

[Configure sample
ecommerce application](#)

Access admin panel from
web browser

Add products

Configure store settings

Configure payment
settings

[Configure shipping
settings](#)

[Access sampe ecommerce
application](#)

Use fraud detection AI model
with EverShop Storefront


✓ 2. AI model deployment

2. Add payment method

- Click add method
- Add method name (e.g. FedEx)
- Enable status
- Add flat rate (e.g. 10)
- Click save

✓ 3. AI model analysis


4. AI model integration



Access sampe ecommerce application

1. Enter URL in web browser using app url
(e.g. localhost)

`http://localhost:3000`



[Install and deploy sample
ecommerce application](#)

[Configure sample
ecommerce application](#)

[Access admin panel from
web browser](#)

[Add products](#)

[Configure store settings](#)

[Configure payment
settings](#)


[Configure shipping
settings](#)

[Access sampe ecommerce
application](#)

[Use fraud detection AI model
with EverShop Storefront](#)

Use fraud detection AI model with EverShop Storefront

1. Make sure you have AI on IBM Z Sample Fraud Detection Dashboard deployed for inferencing and analysis on the same local system
2. AI on IBM Z Sample Fraud Detection Dashboard is configured to invoke MLz AI model
3. Add items to cart
4. Place order
 - Choose test failure as payment method for fraud transaction example
 - Choose test success as payment method for non fraud transaction example



✓ 1. AI model training

✓ 2. AI model deployment

✓ 3. AI model analysis

✓ 4. AI model integration

✓ AI model integration complete

CICS-COBOL application

We can use our deployed MLz fraud detection AI model and integrate it into different types of applications. Guidance on integrating the AI model into a sample CICS-COBOL application is below.

All sample code for this section is within

```
ai-st-fraud-detection/zST-model-integration-CICS
```

Prerequisites

1. Must have access to z/OS CICS environment
2. Must have MLz installed
3. Must have model deployed with the CICS-scoring server as scoring service
4. Must have the JVM server and bundle setup and running. To verify the same execute the below commands in the CICS.

JMVSERVER

```
CEMT INQUIRE JVMSERVER(ALNSCSER)
```

BUNDLE


```
CEMT INQUIRE BUNDLE(ALNSCBDL)
```


[Get model details for inferencing](#)

[Integrate into CICS Application](#)

Get model details for inferencing

1. Go to MLz UI
2. Go to deployments tab
3. Click on action button for your deployed model (on right side)
4. Click view details
5. Copy scoring endpoint



Get model details for inferencing

Integrate into CICS Application

Integrate into CICS application

1. Review the input and output copybooks from the MLz UI

2. Generate input and output Java helper classes
3. Run the

```
$IML_INSTALL_ENT_DIR/cics-scoring/bin/gen_
helper_class.sh
```

script to generate helper classes

- `SERVER_NAME` is the name of the scoring service the model is deployed to.
- `DEPLOYMENT_ID` is the deployment ID of the model.
- `JCLASS_PREFIX` is the prefix to be used for the generated class.
- The generated input class will be named as:
`<JCLASS_PREFIX>InWrapper.class`
- The generated output class will be named as:
`<JCLASS_PREFIX>OutWrapper.class`

Ex:

```
$IML_INSTALL_ENT_DIR/cics-scoring/bin/gen_
helper_class.sh SERVER_NAME DEPLOYMENT_ID
JCLASS_PREFIX
```



Get model details for
inferencing

[Integrate into CICS
Application](#)

3. Create COBOL program

- Create ALNJCGEN JCL
- Copy provided sample COBOL program

```
ai-st-fraud-detection/zST-model-
integration-CICS/FRAUDET.cob
```

- Paste sample COBOL program into FRAUDET
- Copy deployment ID from MLz UI
- Replace DEPLOYMENT_ID in sample COBOL program with your deployment ID
- Update the names of the input and output wrapper classes created in the previous

```

AIONZ,POC,COBOL(FRAUDET) - 01.32          Columns 00001 00072
@ ==>                                     Scroll ==> CSR
-----
1000-CALL-CICS.
-----

*      MLZ Model deployment ID = PMML
*PASS THE DEPLOYMENT ID OF THE MODEL TO SCORING VIA CICS
*CHANNEL AND CONTAINER ALN_DEPLOYMENT_ID
EXEC CICS PUT CONTAINER('ALN_DEPLOY_ID') CHANNEL('CHAN')
      CHAR
      FROM('65d26708-afbc-4d12-aed6-1c113d818b52')
      END-EXEC.

*PASS THE JAVA CLASS NAME OF THE MODEL INPUT TO SCORING VIA
*CICS CHANNEL AND CONTAINER ALN_INPUT_CLASS
*      PMML Input Wrapper Class Generated through ALNJCGEN
EXEC CICS PUT CONTAINER('ALN_INPUT_CLASS') CHANNEL('CHAN')
      CHAR FROM('FRAUDInPipeWrapper')

```

4. Compile and link-edit CICS-COBOL program

- Create COMPILE file
- Copy provided sample COMPILE file

```
ai-st-fraud-detection/zST-model-
integration-CICS/COMPILE.jcl
```

- Paste sample COMPILE file into COMPILE file
- Paste sample COMPILE file into COMPILE file
- Submit job
- Verify job ran successfully (MAXCC = 0)

```

AIONZ,POC,JCL(COMPILE) - 01.18          Columns 00001 00072
@ ==>                                     Scroll ==> CSR
***** Top of Data *****
//COMPILE JOB (SYSTEMS), 'AIONZ',MSGCLASS=H,NOTIFY=&SYSUID,
//      LINES=999999,TIME=1440,CLASS=A
//*
//*****
//*      COMPILE A CICS COBOL PROGRAM
//*****
//COMPI EXEC PGM=IGYCRCTL,REGION=0M,COND=(4,LT),
//      PARM=('NODYNAM,LIB,MAP,XREF,ADATA,CICS(''COBOL3'')')
//STEPLIB DD DISP=SHR,DSN=IGY.SIGYCOMP
//      DD DISP=SHR,DSN=CICSTS61.CICS.SDFHLOAD
//SYSIN DD DISP=SHR,DSN=AIONZ.POC.COBOLE(CRAURL)
//SYSPRINT DD SYSOUT=*
//SYSLIN DD DSN=&ALOADSET,DISP=(NEW,KEEP),
//      UNIT=SYSDA,SPACE=(80,(250,10))

```

[Get model details for inferencing](#)

[Integrate into CICS Application](#)

5. Define the transaction and program in the CICS region

- Transaction:

```
CEDA DEFINE TRANS(FRDT) GROUP(ALNSCGRP)
PROGRAM(FRAUDET) DESCRIPTION(TRAN to
execute FRAUDET)
```

- Program:

```
CEDA DEFINE PROGRAM(FRAUDET)
GROUP(ALNSCGRP) LANGUAGE(COBOL)
DESCRIPTION(FRAUD DETECTION)
```

```
CEDA DEFINE TRANS(FRDT) GROUP(ALNSCGRP)
PROGRAM(FRAUDET) DESCRIPTION(TRAN to execute FRAUDET)
```

```
CEDA DEFINE PROGRAM(FRAUDET) GROUP(ALNSCGRP)
LANGUAGE(COBOL) DESCRIPTION(FRAUD DETECTION)
```

6. Install transaction and program in the CICS region

- Transaction:

```
CEDA INS TRANS(FRDT) GROUP(ALNSCGRP)
```

- Program:

```
CEDA INS PROGRAM(FRAUDET) GROUP
(ALNSCGRP)
```

```
CEDA INS TRANS(FRDT) GROUP(ALNSCGRP)
```

```
CEDA INS PROGRAM(FRAUDET) GROUP(ALNSCGRP)
```

7. Run transaction

```
FRDT
```

```
FRDT
```

Get model details for
inferencing

[Integrate into CICS
Application](#)

8. View output results

- Go to the Spool of the started task for CICS (e.g. CICSSA01)
 - Navigate to the CEEMSG dataset
 - View displays from the module in this dataset
- Sample output is shown as below

```
SDSF OUTPUT DISPLAY CICSSA01 STC09971 DSID 106 LINE 1,653 COLUMNS 02- 01
COMMAND INPUT ==>
ACBPCSR1 202300010121427
ACBPCSR1 20230001012137 Amount :0000.03
ACBPCSR1 20230001012137 Card :3
ACBPCSR1 20230001012137 Expire :982558
ACBPCSR1 20230001012137 Merchant_City :Caracas
ACBPCSR1 20230001012137 Merchant_Name :Riviera Supermarket
ACBPCSR1 20230001012137 Merchant_State :Venezuela
ACBPCSR1 20230001012137 Use_Chip :Chip Transaction
ACBPCSR1 20230001012137 User :0003
ACBPCSR1 20230001012137 Zip :37931
ACBPCSR1 20230001012137
ACBPCSR1 20230001012130 probability(0) :00.0000000000000000
ACBPCSR1 20230001012130 probability(1) :00.0000000000000000
ACBPCSR1 20230001012130 FRAUD
```

✓ 1. AI model training

✓ 2. AI model deployment

✓ 3. AI model analysis

✓ 4. AI model integration

✓ AI model integration complete