UTFT

Arduino and chipKit Universal TFT display library

Supported display modules & LCD Controllers

These display modules have been tested, and works with the UTFT library. Other modules may work as long as they have one of the supported controllers.

Supplier:	ITead Studio				
Website:	http://imall.iteads	http://imall.iteadstudio.com/			
Module	Model for UTFT()	Controller	Notes		
ITDB02-1.8SP	ITDB18SP	ST7735	5V only ¹		
ITDB02-2.2SP	ITDB22SP	HX8340-B(N)	Retired, 5V only ¹		
ITDB02-2.2	ITDB22	HX8340-B(T)			
ITDB02-2.4	ITDB24	ILI9325C	Retired		
ITDB02-2.4D	ITDB24D	ILI9325D	Retired		
ITDB02-2.4DWOT	ITDB24DWOT	ILI9325D	Retired		
ITDB02-2.4E	ITDB24E_8	S6D1121	8bit mode		
ITDB02-2.4E	ITDB24E_16	S6D1121	16bit mode		
ITDB02-2.5H	ITDB25H	S1D19122	Retired		
ITDB02-2.8	ITDB28	ILI9325D			
ITDB02-3.2	ITDB32	HX8347-A	Retired		
ITDB02-3.2WC	ITDB32WC	ILI9327	Retired		
ITDB02-3.2S	ITDB32S	SSD1289			
ITDB02-3.2WD	ITDB32WD	HX8352-A			
ITDB02-4.3	ITDB43	SSD1963			
ITDB02-5.0	ITDB50	SSD1963			

Supplier:	ElecFreaks			
Website:	http://www.elecfreaks.com/store/			
Module	Model for UTFT()	Controller	Notes	
TFT01-1.8SP	TFT01_18SP	ST7735S	May require external power	
TFT01-2.2	TFT01_22	S6D0164		
TFT01-2.2SP	TFT01_22SP	ILI9341	May require external power	
TFT01-2.4	TFT01_24_8	ILI9325D	8bit model, Retired	
TFT01-2.4	TFT01_24_16	ILI9325D	16bit model, Retired	
TFT01-2.4 v1.2	TFT01_24R2	S6D1121		
TFT01-2.8	TFT01_28	ILI9325D		
TFT01-3.2	TFT01_32	SSD1289		
TFT01_3.2W	TFT01_32W	ILI9327	Retired	
TFT01_3.2WD	TFT01_32WD	HX8352-A		
TFT01-4.3	TFT01_43	SSD1963		
TFT01-5.0	TFT01_50	SSD1963	_	
TFT01-7.0	TFT01_70	SSD1963		

Supplier:	NKC Electronics			
Website:	http://store.nkcelect	http://store.nkcelectronics.com/		
Module	Model for UTFT()	Controller	Notes	
RGB LCD 65K color module	LPH9135	PCF8833		

Supplier:	Electronics Lee			
Website:	http://stores.ebay.com/electronics-lee			
Module	Model for UTFT()	Controller	Notes	
3.2" TFT LCD Arduino Shield Revision A	ELEE32_REVA ²	SSD1289	Uses 16bit latched mode ³ Arduino Shield not supported on chipKit or Arduino Due	
3.2" TFT LCD Arduino Shield Revision B	ELEE32_REVB	SSD1289	8bit mode ⁴ Arduino Shield not supported on chipKit or Arduino Due	

Supplier:	General Electronic	cs-Tech	
Website:	http://www.geeetech.com/		
Module	Model for UTFT()	Controller	Notes
2.2" TFT LCD	GEEE22	HX8340-B(T)	
TFT 2.4" With SD Touch Module	GEEE24	ILI9320	5V only ¹
TFT 2.8" With SD Touch Module	GEEE28	ILI9320	5V only ¹
TFT 3.2" With SD Touch Module	GEEE32	SSD1289	

May work on 3.3v boards (chipKit and Arduino Due) but this has not been verified Changed from INFINIT32
Use UTFT myGLCD(ELEE32_REVA,A1,A2,A0,A3,A5); to initialize
Use UTFT myGLCD(ELEE32_REVB,A1,A2,A0,99); to initialize

Supplier: Website:	Coldtears Electronics http://stores.ebay.com/coldtears-electronics-store			
Module	Model for UTFT() Controller Notes			
2.2" TFT LCD Module	CTE22	S6D0164	Basic support only ⁵	
2.8" TFT LCD Module	CTE28	ILI9325D	Basic support only ⁵	
3.2" TFT LCD Module	CTE32	SSD1289	Basic support only ⁵	
3.2" (480x320) TFT LCD Module	CTE32HR	ILI9481	Basic support only ⁵	
3.2" Wide TFT LCD Module	CTE32W	HX8352-A	Basic support only ⁵	
3.5" IPS TFT LCD Module	CTE35IPS	R61581	Basic support only ⁵	
4.0" TFT LCD Module	CTE40	ILI9486	Basic support only ⁵	
5.0" TFT LCD Module	CTE50	SSD1963	Basic support only ⁵	
7.0" TFT LCD Module	CTE70	SSD1963	Basic support only ⁵	

Supplier:	Watterott electronic			
Website:	http://www.watterott.com/			
Module	Model for UTFT()	Controller	Notes	
MI0283QT-9A	MI0283QT9	ILI9341	Only tested on Arduino Uno	

-

 $^{^{\}rm 5}$ UTFT does not make use of the on-board Font and Icon Flash chip.

If you are unsure which module you have you can try these model codes for the supported controllers instead: $\ensuremath{\mathsf{C}}$

		Supported mode		
Controller	Model for UTFT()	8bit	16bit	Serial
HX8340-B(N)	HX8340B_S			✓
HX8340-B(T)	HX8340B_8	√		
HX8347-A	HX8347A		✓	
HX8352-A	HX8352A		✓	
ILI9320	ILI9320_8	✓		
	ILI9320_16		✓	
ILI9325C	ILI9325C	✓		
ILI9325D	ILI9325D_8	✓		
	ILI9325D_16		✓	
	ILI9325D_16ALT ⁶		✓	
ILI9327	ILI9327		✓	
ILI9341	ILI9341_S4P ⁷			✓
	ILI9341_S5P ⁸			✓
ILI9481	ILI9481		✓	
ILI9486	ILI9486		✓	
PCF8833	PCF8833			✓
R61581	R61581		✓	
S1D19122	S1D19122		✓	
S6D0164	S6D0164	✓		
S6D1121	S6D1121_8	✓		
	S6D1121_16		✓	
SSD1289	SSD1289		✓	
	SSD1289_8	✓		
	SSD1289LATCHED ⁹		LATCHED	
SSD1963	SSD1963_480		✓	
	SSD1963_800		✓	
	SSD1963_800ALT ¹⁰		✓	
ST7735	ST7735			✓
ST7735S	ST7735S			✓

⁶ Alternative initialization for some 2.8" display modules
⁷ Use this for 4 Pin serial modules
⁸ Use this for 5 Pin serial modules
⁹ Currently only supported on 5v Arduino board, and not on chipKit or Arduino Due
¹⁰ Alternative initialization for 7" displays