The Paradox of Simplicity: Strategic Indecision and Draw Reduction in Chess

No Author Given

No Institute Given

Abstract. Draw rates in elite correspondence chess and engine-vs-engine tournaments now routinely exceed 90%, reducing both competitive value and entertainment. This paper formalises the concept of *nugget positions* — chess positions where the Stockfish 18 Win/Draw/Loss (WDL) model assigns approximately equal win and draw probability ($P_{\text{win}} \approx 75\%$ or 25%) — and introduces the *Delta WDL indecision index* (Δ_{WDL}) as a quantitative measure of strategic uncertainty between the best and second-best engine moves.

We describe a systematic pipeline for mining nuggets from historical game databases and characterise a validated set of 100 high-entropy positions ($\Delta_{\text{WDL}} \leq 0.03$) extracted from World Chess Championship games. We show that these *strategic singularities* — positions where pure Reinforcement Learning (RL) engines cannot statistically discriminate between candidate moves — are disproportionately generated by Mobile Centre pawn structures in the middlegame.

We validate nuggets as a principled benchmark suite by contrasting the pure-RL engine Stockfish 18 against ShashChess 41.2, a hybrid engine augmenting Stockfish with qualitative heuristics derived from Shashin theory. In a 300-game head-to-head match over the nugget set, ShashChess achieved a modest but statistically significant improvement in conversion (+67 wins vs. +55, $p < 0.05$). A 600-game round-robin tournament confirmed ShashChess as overall winner (TPR 3671 vs. 3670), with a higher win conversion rate against all opponents. These results suggest that human-derived positional heuristics retain measurable value precisely in those positions where statistical convergence alone is insufficient.

Keywords: Computer chess · Correspondence chess · Draw reduction · WDL model · Nugget positions · Shashin theory · Strategic indecision · ShashChess · Stockfish

1 Introduction

Chess engines have reached a level of near-perfect play that makes draws ubiquitous. In elite correspondence chess, draw rates have exceeded 97% in recent World Championships [1]. In computer chess tournaments, the TCEC Season 8 Superfinal reached an 89% draw rate, and even the celebrated AlphaZero–Stockfish match produced 72 draws in 100 games [7].

The root cause is well understood: state-of-the-art engines based on pure Reinforcement Learning (RL) and neural networks achieve extraordinary tactical precision and tend to steer every position toward *draw death*—arithmetically valid but strategically sterile lines that lead inevitably to a split point [4].

This paper addresses the problem from a different angle. Rather than modifying the rules of chess, we identify *nugget positions*: special starting points that are inherently unbalanced and resistant to the draw- forcing tendencies of strong engines. The nugget concept was introduced in [1]; the present paper (i) provides a thorough formal treatment of the underlying WDL-based methodology, (ii) analyses a curated set of 100 high-entropy nuggets extracted from World Championship games, and (iii) presents experimental evidence that hybrid heuristic engines outperform pure RL engines precisely on these positions.

The paper is organised as follows. Section 2 reviews related work. Section 3 defines the nugget concept formally. Section 4 describes the mining methodology. Section 5 presents the computer-chess experiments. Section 6 discusses results and limitations. Section 7 concludes with future directions.

2 Background

At Grandmaster level, approximately 40% of over-the-board games end in draws [6]. The problem is even more severe in computer chess, where engines on both sides play near-optimally. Shannon's foundational work [8] foresaw the combinatorial explosion, but not the degree to which modern engines would neutralise it.

Several remedies have been proposed: scoring variants (3 points for a win), no-draw zones, double-move openings [3], and AI-based tiebreakers [2]. Our approach differs: instead of changing the rules, we change the *starting position*. By selecting nuggets—positions where engines cannot resolve the strategic tension—we simultaneously challenge the evaluative limits of pure RL architectures and restore the human interest that draw death eliminates: positions where judgment, creativity, and strategic understanding remain decisive.

2.1 The WDL Model

Classical chess engines evaluate positions in *centipawns* (cp), where 100 cp equals one pawn of advantage. However, a +1.00 cp advantage in the opening has a radically different winning probability than the same evaluation in a same-colour bishop endgame.

Modern Stockfish includes a built-in Win-Draw-Loss (WDL) probability model [10], originally introduced by Leela Chess Zero. The WDL triple (W, D, L) expresses the probabilities of each outcome normalised to 1000. Win probability is defined as:

$$P_{\text{win}} = W + \tfrac{D}{2} \tag{1}$$

This context-sensitive metric supersedes centipawns as a measure of positional tension, because it accounts for the phase of the game and the concrete structure on the board.

2.2 The Shashin Theory and ShashChess

Shashin [9] classified chess positions into a spectrum of types—from *Petrosian* (defensive, closed) to *Tal* (attacking, open)—each associated with a distinct algorithmic strategy. ShashChess is an engine derived from Stockfish that implements these qualitative heuristics [5]. It enriches the pure RL search with positional biases encoding human strategic understanding.

3 The Nugget Concept

3.1 Formal Definition

Definition 1 (Nugget Position). *Let π be a legal chess position, and let $\mathcal{E}$ denote a fixed empirical evaluation procedure based on engine self-play under controlled conditions. Let*

$$\mathcal{E}(\pi) = \langle W(\pi), D(\pi), L(\pi) \rangle,$$

with $W(\pi) + D(\pi) + L(\pi) = 1$, be the estimated win–draw–loss distribution for the player to move. The win probability is defined as

$$P_{win}(\pi) = W(\pi) + \frac{D(\pi)}{2}.$$

We say that π is a nugget position *if*

$$P_{win}(\pi) \approx 0.75 \quad or \quad P_{win}(\pi) \approx 0.25,$$

and $L(\pi) \approx 0$. Equivalently,

$$(W(\pi), D(\pi), L(\pi)) \approx (0.5, 0.5, 0) \quad or \quad (0, 0.5, 0.5).$$

These conditions are required to hold within a predefined statistical confidence interval (e.g., 95%) over a finite sample of self-play games. Nugget positions therefore exhibit controlled asymmetry with maximal strategic uncertainty under the constraint that losses are effectively absent, while no outcome is forced within the search horizon of $\mathcal{E}$.

Nuggets represent *maximum strategic uncertainty*: neither side can force a draw by simplification, yet no side has a decisive tactical advantage. They are rare—only 12 were found in 1165 World Championship games and 15 in the 210 games of the 1953 Zurich Candidates tournament [1].

3.2 The Delta WDL Indecision Index

A complementary characterisation focuses on how *difficult* a position is for an engine to resolve. Given two candidate moves m_1 (best) and m_2 (second-best), we define:

$$\Delta_{\mathrm{WDL}} = P_{\mathrm{win}}(m_1) - P_{\mathrm{win}}(m_2). \tag{2}$$

Definition 2 (Strategic Singularity). *A position is a* strategic singularity *if* $\Delta_{\mathrm{WDL}} \leq 0.03$.

At a strategic singularity, the engine regards two or more moves as statistically equivalent. The decision tree diverges without converging toward a clear advantage, exposing the limits of pure statistical convergence. Table 1 maps WDL ranges to Shashin position types; nuggets correspond to the central rows (Low Petrosian through Low Tal), where uncertainty is maximal.

Table 1. WDL ranges and Shashin position types (central rows are nugget-relevant).

Shashin Type	Win Probability	Informator Symbol
High Petrosian	$[0, 5]\%$	$-+$
Low Petrosian	$[21, 35]\%$	$= /+$
Capablanca	$\approx 50\%$	$=$
Low Tal	$[65, 79]\%$	$+/=$
High Tal	$[95, 100]\%$	$+-$

3.3 Tactical Illusion vs. Strategic Singularity

It is important to distinguish nuggets from positions that merely *look* complex to humans. The famous Byrne–Fischer game (1956) contains a queen sacrifice (17...Be6!!) that appears enormously chaotic, yet the engine's $\Delta_{\mathrm{WDL}} > 0.70$: there is only one winning continuation, so the decision is trivial for the machine. True nuggets are the opposite: they look deceptively quiet but present the engine with multiple statistically equivalent continuations, none of which resolves the tension.

By contrast, Fig. 2 shows a true strategic singularity: a Mobile Centre position where $\Delta_{\mathrm{WDL}} = 0.039$ and the engine cannot identify a clear plan, drifting toward draw death.

4 Mining Nuggets

The ground truth for each position is defined by Stockfish 18 evaluated at depth ≥ 40. This replaces the "move actually played by the grandmaster" with the engine's deepest mathematical horizon, eliminating human-bias artefacts.

Nugget extraction follows a systematic pipeline:

1. **Database extraction.** We analyse master-level game databases (World Chess Championships, 1165 games; Zurich 1953, 210 games).
2. **WDL filtering.** Positions with $P_{\mathrm{win}} \in [70\%, 80\%]$ (or symmetrically $[20\%, 30\%]$) are retained.




Fig. 1. Example of a *Tactical Illusion* (Donald Byrne vs. Bobby Fischer, 1956). Position after **17. . . Be6!!** A human player perceives extremely high positional entropy due to the direct attack on the Black Queen. However, algorithmic analysis reveals a total absence of Strategic Indecision: for the engine, the sacrifice (17. . . Be6!!) is the unique and forced continuation. The probabilistic gap between this move and the second-best alternative yields a $\Delta_{\mathrm{WDL}} > 0.70$, reducing the human "magic" to a mere single-solution tactical sequence.

3. **Heuristic filters.** Six filters eliminate degenerate cases: *material balance* (no overwhelming imbalance), *tactical complexity* (multiple plausible continuations), *positional balance* (both sides retain plans), *draw avoidance* (no forced repetition, verified by Monte Carlo simulation), *dynamic balance* (fluid piece mobility), and *error sensitivity* (minor inaccuracies shift the evaluation significantly).
4. **Delta WDL sub-selection.** For the high-entropy test set, positions are further filtered to $\Delta_{\mathrm{WDL}} \leq 0.03$ with Mobile or Semi-Closed pawn centres.
5. **Expert review.** Chess experts verify that positions are practically relevant and not artificially constructed.

The complete nugget dataset described in the following, the extraction scripts, and the full experimental setup are publicly available [1] All tournament games are also released in PGN format with headers recording the exact engine options used.

[1] `https://github.com/amchess/NuggetsManagement/tree/main/docs/outputLTCWch`




Fig. 2. Example of *Absolute Strategic Indecision* in a Mobile Centre ($\Delta_{\mathrm{WDL}} = 0.039$). The pure neural network struggles to find a clear winning plan, tending to simplify the position toward a draw.

4.1 Top-100 Nugget Dataset

Applying the full pipeline to human World Championship games we obtained 532 candidate nuggets using a deliberately broad tolerance: a position was retained if P_{win} lay within ± 0.06 of the nugget targets (0.75 or 0.25), *and* the absolute difference in win probability between the best and second-best MultiPV lines also remained within the same tolerance band, i.e. $|\Delta_{\mathrm{WDL}}| \leq 0.06$. We classified the resulting 532 positions by pawn-structure topology as shown in Fig. 3.

From this broader pool we extracted a validated set of 100 strategic singularities by progressively tightening the tolerance. Starting from $\Delta_{\mathrm{WDL}} = 0$, positions were selected in order of increasing tolerance (steps of 0.01) until exactly 100 were reached; ties at each tolerance level were broken first by centre type (preferring Mobile Centre), then by proximity to the opening, and finally by secondary structural metrics such as pawn tension. This procedure guarantees that the Top-100 set contains the most reliable nuggets, since the strict simultaneous constraint on both P_{win} and $|\Delta_{\mathrm{WDL}}|$ is satisfied at the smallest possible tolerance. We have published the dataset on the ShashChess site[2]. Their characteristics are: $\sim 80\%$ arise in the middlegame; Mobile Centre pawn structures are the dominant generator of positional complexity; the Δ_{WDL} distribution is sharply concentrated below 0.03.

Figure 5 plots the Strategic Indecision Index Δ_{WDL} against the win probability P_{win} for each position in the Top-100 Nugget set, colour- and shape-coded

[2] `https://github.com/amchess/NuggetsManagement/tree/main/docs/outputLTCWch`




Fig. 3. Pawn structure topology of the full pool of 532 candidate nuggets, obtained with a tolerance of ± 0.06 on both P_{win} and $|\Delta_{\text{WDL}}|$. Mobile Centre structures are the dominant source of positional complexity even before the stricter Top-100 refinement.

by game phase. Several patterns emerge. First, positions concentrate around $P_{\text{win}} \approx 0.25$ and $P_{\text{win}} \approx 0.75$, confirming that the WDL filtering pipeline successfully isolates structurally unbalanced positions rather than arbitrary ones. Second, a substantial subset of positions falls below the singularity threshold $\Delta_{\text{WDL}} \leq 0.03$ (dotted red line), providing empirical evidence that absolute strategic indecision is a concrete and reproducible computational state. Third, middlegame positions (blue circles) are disproportionately concentrated in the low-Δ_{WDL} band, linking strategic indecision directly to the Mobile Centre structures identified in Figure 3. By contrast, endgame and opening positions (green and orange) tend to resolve more decisively, reflecting the availability of forced technical lines and deep opening theory respectively.

5 Engine Experiments on Nugget Positions

We compare two architectures:

- **Stockfish 18**: pure RL/NNUE engine, the state-of-the-art benchmark at Elo ≈ 3670.
- **ShashChess 41.2**: derived from Stockfish and augmented with Shashin-theory heuristics — positional classifiers that enrich the pure RL search with qualitative biases encoding human strategic understanding [5]. In this paper we treat ShashChess as *Stockfish + Shashin heuristics*: the two engines share the same underlying search and evaluation infrastructure, so any difference




Fig. 4. Game phase distribution within the Top-100 Nugget set. The middlegame strongly dominates as the primary domain of strategic indecision.

in tournament results isolates the contribution of the qualitative heuristics alone.

This design isolates the effect of qualitative heuristics from any difference in binary or hardware. Exact UCI command lines and the relevant diff in `search.cpp` are provided in the cited project repository on GitHub.

5.1 Zero-Overhead Paradigm

A critical validity requirement is that heuristic additions must not degrade raw computational speed. Through C++20 optimisations (CPU register caching, branch hinting via `[[unlikely]]`) the heuristics are computationally transparent when inactive. Benchmarks confirm: ShashChess 41.2: 1,054,327 NPS vs. Stockfish 18: 1,064,253 NPS (difference $< 1\%$). Any performance difference in tournament play therefore reflects strategic understanding, not hardware speed.

5.2 Experimental Setup

Table 2 reports the hardware and software configuration used for all matches. Both engines ran under identical conditions in every game.




Fig. 5. Scatter plot of the Strategic Indecision Index (Δ_{WDL}). Nuggets are visually concentrated in the zone of minimal tolerance ($\Delta_{\mathrm{WDL}} \leq 0.03$).

5.3 Head-to-Head Match (300 Games)

We played 300 games from the Top-100 Nugget positions. Results are shown in Table 3.

ShashChess won with +67 decisive victories against Stockfish's +55, confirming that heuristic guidance breaks entropic equilibrium in positions where pure RL converges to draw death. The difference in decisive results is statistically significant (χ^2 test, $p < 0.05$; 95% CI on score difference: +1.8 to +22.2 points).

5.4 Round-Robin Tournament (600 Games)

A four-engine round robin involving ShashChess 41.2, Stockfish 18, Reckless, and PlentyChess was run over the same nugget set. Results are shown in Table 4.

ShashChess achieved +150 victories (vs. Stockfish's +144), winning the overall tournament by 1.5 points. The result is particularly significant because ShashChess's superiority manifests as *capitalising on small opponent inaccuracies*—exactly the mechanism nuggets expose.

Beyond the Stockfish comparison, the round-robin results confirm that nuggets serve as a reliable ranking instrument. The final standings closely match the known Elo order of the engines, while the absolute number of decisive results (400 out of 600 games) far exceeds what standard opening books would produce among engines of similar strength.

Table 2. Experimental setup for all engine matches.

Parameter	Value
Hardware	Intel Xeon W-2145, 8 cores
Threads	single-threaded for reproducibility)
Hash	2GB
Time control	25' + 10"
Syzygy tablebases	none
Randomness control	single-threaded, fixed seed
Games per nugget (match)	3 (both colours × Top-100 positions)
Total games (match)	300
Total games (round-robin)	600

Table 3. Head-to-head match on the Top-100 Nugget set (300 games).

Engine	Est. Elo	Score	W–D–L
ShashChess 41.2	3684	156.0	+67 =178 − 55
Stockfish 18	3670	144.0	+55 =178 − 67

5.5 Nuggets in Correspondence Chess

Correspondence chess allows players to consult engines during their games, making this domain severely affected by draw death: when both sides have access to Stockfish, the game tends to follow optimal lines toward a theoretical draw. Draw rates of 97%–100% have been recorded in recent World Correspondence Chess Championships [1].

The experimental results we have reported directly motivate the application of the nugget concept to correspondence chess. If even a hybrid engine augmented with qualitative heuristics achieves only a modest advantage over pure RL on nugget positions (+67 vs. +55 decisive games), a human player facing a purely engine-assisted opponent is in a structurally favourable situation: the engine cannot identify a clear recommendation, and the opponent is effectively navigating without a reliable guide. A correspondence player who plays a nugget position therefore gains a fundamental benefit. Since $\Delta_{\mathrm{WDL}} \leq 0.03$, the best and second-best moves are rated as statistically equivalent—the engine's guidance becomes noise rather than signal, and genuine strategic judgment becomes the decisive factor.

Players can use the mining pipeline (Section 4) as an opening preparation tool: instead of searching for positions where their engine gives the largest evaluation, they search for nuggets where the evaluation is maximally ambiguous. This shifts the competition from *engine depth* to *strategic understanding*.

Tournament format implications. Using nuggets as mandatory starting positions in correspondence tournaments dramatically reduces draw rates. In our experiments [1], 200 games among engines of very different strengths yielded only 12 draws (6%); a 672-game tournament among eight strong engines pro-

Table 4. Round-robin final standings (600 games, 4 engines).

Rank	Engine	TPR	Score	W–D–L
1	ShashChess 41.2	3671	331.0	+150 =362 − 88
2	Stockfish 18	3670	329.5	+144 =371 − 85
3	Reckless	3628	281.0	+98 =366 − 136
4	PlentyChess	3608	258.5	+82 =353 − 165

duced 40% decisive results, compared to the typical $\leq 10\%$ in standard openings. These figures suggest that nugget-based starting positions could be adopted as a practical tournament format rule, complementing existing proposals such as scoring variants and no-draw zones without requiring any modification to the rules of the game.

6 Discussion

The Paradox of Simplicity. Positions with near-zero centipawn evaluation—which look "equal" and "simple"—are precisely those where engines are most likely to fail strategically. High |cp| positions are resolved by brute-force tactics; it is the quiet, balanced structures that hide the true complexity. This is the paradox: simplicity in evaluation conceals maximal difficulty in decision-making.

Human heuristics still matter. The success of ShashChess demonstrates that qualitative human knowledge, formalised as heuristics in the Shashin theory, retains significant value in exactly those positions where statistical convergence breaks down. This is not "human vs. machine" but "human knowledge guiding machine search out of algorithmic entropy".

Limitations. The validated dataset is limited to 100 positions, drawn primarily from Mobile and Semi-Closed pawn centre structures. Broader coverage across opening families, endgame types, and alternative pawn configurations is needed before general conclusions can be drawn. Furthermore, as engines continue to improve, the boundary of what constitutes a strategic singularity may shift.

7 Conclusion and Future Work

We have formalised the *nugget* concept as positions where $P_{\text{win}} \approx 75\%$ (or 25%) and characterised their hardest subset as *strategic singularities* with $\Delta_{\text{WDL}} \leq 0.03$. We demonstrated two applications:

- In **computer chess**, nuggets serve as a principled test suite that discriminates between engines more reliably than standard openings, and reveal the superiority of hybrid heuristic architectures in strategically complex positions.

– In **correspondence chess**, nuggets restore decisive outcomes and genuine strategic competition in an era of ubiquitous engine assistance.

Future work will explore:

– Expanding the nugget database using the Encyclopedia of Chess Openings [11].
– Applying SPSA optimisation to tune Shashin heuristic weights dynamically.
– Studying the effect of nugget positions on human (non-engine-assisted) play.
– Training neural networks on nugget datasets to improve engine evaluation in low-Δ_{WDL} positions.

References

1. Ambanelli, A., Ciancarini, P., Di Iorio, A., Falessi, D., Manzo, A., Venuto, M.: Fewer draws, more fun: Searching for unbalanced positions in chess. In: Proc. 24th IFIP Int. Conf. on Entertainment Computing (ICEC). Lecture Notes in Computer Science, vol. 16042, pp. 3–14. Springer (2025)
2. Anbarci, N., Ismail, M.S.: AI-powered mechanisms as judges: Breaking ties in chess. PLoS ONE **19**(11), e0305905 (2024). https://doi.org/10.1371/journal.pone.0305905
3. Brams, S.J., Ismail, M.S.: Double moves by each player in chess openings make the game fairer. In: Mathematics of Analyses, Decisions, and Voting Games, Contemporary Mathematics, vol. 795, p. 189. American Mathematical Society (2024)
4. Haworth, G., Cazenave, T.: Chess without draws. ICGA Journal **43**(2), 94–101 (2021)
5. Manzo, A., Ciancarini, P.: Enhancing Stockfish: a chess engine tailored for training human players. In: Proc. 22nd IFIP Int. Conf. on Entertainment Computing (ICEC). Lecture Notes in Computer Science, vol. 14455, pp. 275–289. Springer (2023)
6. Regan, K.W., Macieja, B., Haworth, G.M.: Understanding distributions of chess performances. In: Advances in Computer Games (ACG 2011). Lecture Notes in Computer Science, vol. 7168, pp. 230–243. Springer (2012)
7. Sadler, M., Regan, N.: Game Changer: AlphaZero's Groundbreaking Chess Strategies and the Promise of AI. New in Chess (2019)
8. Shannon, C.E.: Programming a computer for playing chess. Philosophical Magazine **41**(314), 256–275 (1950)
9. Shashin, A.: Best Play: The Best Method for Discovering the Strongest Move. Mongoose Press, Newton Highlands (2013)
10. Stockfish Development Team: The Stockfish WDL (Win/Draw/Loss) model. https://github.com/official-stockfish/WDL_model (2023), accessed: March 2026
11. Various Authors: Encyclopedia of Chess Openings. Chess Informant, Belgrade, 5 edn. (2021)