

Get better WordPress performance with Cloudways managed hosting. Start with \$100, free →

We're
hiring

Blog

Docs

Get
Support

Contact
Sales



Tutorials

Questions

Learning Paths

For Businesses

Product Docs

Social Impact

C

CONTENTS

If Statement

Else Statement

Else if Statement

Ternary Operator

Conclusion

RELATED

CodeIgniter: Getting Started With a Simple Example

[View](#)

How To Install Express, a Node.js Framework, and Set Up Socket.io on a VPS

[View](#)

Tutorial Series: How To Code in JavaScript



21/37 How To Write Conditional ...

22/37 How To Use the Switch S...



// Tutorial //

How To Write Conditional Statements in JavaScript


Published on August 29, 2017 · Updated on August 25, 2021

JavaScript

Development



By [Tania Rascia](#)



Introduction

In programming, there will be many occasions in which you will want different blocks of code to run depending on user input or other factors.

As an example, you might want a form to submit if each field is filled out properly, but you might want to prevent that form from submitting if some required fields are missing. In order to achieve tasks like these we have **conditional statements**, which are an integral part of all programming languages.

Conditional statements execute a specific action based on the results of an outcome of true or false.

A few ples of JavaScript conditional statements you might see include:

- Check the location of a user and display the correct language based on country

- Send a form on submit, or display warnings next to missing required fields
- Open a dropdown on a click event, or close a dropdown if it is already open
- Display an alcohol purveyor's website if the user is over the legal drinking age
- Display the booking form for a hotel but not if the hotel is booked

Conditional statements are part of the logic, decision making, or flow control of a computer program. You can compare a conditional statement to a "[Choose Your Own Adventure](#)" book, or a flowchart.

In this tutorial, we will go over conditional statements, including the `if`, `else`, and `else if` keywords. We will also cover the ternary operator.

If Statement

The most fundamental of the conditional statements is the `if` statement. An `if` statement will evaluate whether a statement is true or false, and only run if the statement returns `true`. The code block will be ignored in the case of a `false` result, and the program will skip to the next section.

An `if` statement is written with the `if` keyword, followed by a condition in parentheses, with the code to be executed in between curly brackets. In short, it can be written as `if () { }`.

Here is a longer examination of the basic `if` statement.

```
if (condition) {  
    // code that will execute if condition is true  
}
```

Copy

The contents of an `if` statement are indented, and the curly brackets containing the block of code to run do not end in a semicolon, just like a function block.

As an example, let's consider a shopping app. Say, for the functionality of this app, a user who has deposited a certain amount of funds into their account would then like to buy an item from the store.

shop.js

```
// Set balance and price of item  
const balance = 500;  
const price = 40;  
  
// Check if there are enough funds to purchase item
```

Copy

```
if (jeans <= balance) {  
  console.log("You have enough money to purchase the item!");  
}
```

Output

You have enough money to purchase the item!

We have an account balance of 500, and want to buy a pair of jeans for 40. Using the less than or equal to operator, we can check if the price of jeans is less than or equal to the amount of funds we have. Since `jeans <= balance` evaluates to `true`, the condition will pass and the block of code will run.

In a new example, we will create a new shop item that costs more than the available balance.

shop.js

```
// Set balance and price of item  
const balance = 500;  
const phone = 600;  
  
// Check if there is enough funds to purchase item  
if (phone <= balance) {  
  console.log("You have enough money to purchase the item!");  
}
```

Copy

This example will have no output, since `phone <= balance` evaluates to `false`. The code block will simply be ignored, and the program will proceed to the next line.

Else Statement

With `if` statements, we only execute code when a statement evaluates to `true`, but often we will want something else to happen if the condition fails.

For example, we might want to display a message telling the user which fields were filled out correctly if a form did not submit properly. In this case, we would utilize the `else` statement, which is the code that will execute if the original condition does not succeed.

The `else` statement is written after the `if` statement, and it has no condition in parentheses. Here is the syntax for a basic `if...else` statement.



[Copy](#)

```
if (condition) {  
    // code that will execute if condition is true  
} else {  
    // code that will execute if condition is false  
}
```

Using the same example as above, we can add a message to display if the funds in the account are too low.

shop.js

[Copy](#)

```
// Set balance and price of item  
const balance = 500;  
const phone = 600;  
  
// Check if there is enough funds to purchase item  
if (phone <= balance) {  
    console.log("You have enough money to purchase the item!");  
} else {  
    console.log("You do not have enough money in your account to purchase this item.");  
}
```

Output

You do not have enough money in your account to purchase this item.

Since the `if` condition did not succeed, the code moves on to what's in the `else` statement.

This can be very useful for showing warnings, or letting the user know what actions to take to move forward. Usually an action will be required on both success and failure, so `if...else` is more common than a solo `if` statement.

Else if Statement

With `if` and `else`, we can run blocks of code depending on whether a condition is `true` or `false`. However, sometimes we might have multiple possible conditions and outputs, and need more than simply two options. One way to do this is with the `else if` statement, which can evaluate more than two possible outcomes.

Here's a basic example of a block of code that contains an `if` statement, multiple `else if` statements, and an `else` statement in case none of the conditions evaluated to `true`.

Copy

```
if (condition a) {  
    // code that will execute if condition a is true  
} else if (condition b) {  
    // code that will execute if condition b is true  
} else if (condition c) {  
    // code that will execute if condition c is true  
} else {  
    // code that will execute if all above conditions are false  
}
```

JavaScript will attempt to run all the statements in order, and if none of them are successful, it will default to the `else` block.

You can have as many `else if` statements as necessary. In the case of many `else if` statements, the [switch statement](#) might be preferred for readability.

As an example of multiple `else if` statements, we can create a grading app that will output a letter grade based on a score out of 100.

The requirements of this app are as follows:

- Grade of 90 and above is an A
- Grade of 80 to 89 is a B
- Grade of 70 to 79 is a C
- Grade of 60 to 69 is a D
- Grade of 59 or below is an F

Below we will create a simple set of `if`, `else`, and `else if` statements, and test them against a given grade.

grades.js

Copy

```
// Set the current grade of the student  
let grade = 87;  
  
// Check if grade is an A, B, C, D, or F  
if (grade >= 90) {  
    console.log("A");  
} else if (grade >= 80) {  
    console.log("B");  
} else if (grade >= 70) {  
    console.log("C");  
} else if (grade >= 60) {  
    console.log("D");  
} else {
```

```
console.log("F");  
}
```

Output

B

In our example, we first check for the highest score, which will be greater than or equal to 90. After that, the `else if` statements will check for greater than 80, 70, and 60 until it reaches the default `else` of a failing grade.

Although our `grade` value of 87 is technically also true for `c`, `D` and `F`, the statements will stop at the first one that is successful. Therefore, we get an output of `B`, which is the first match.

Ternary Operator

The **ternary operator**, also known as the conditional operator, is used as shorthand for an `if...else` statement.

A ternary operator is written with the syntax of a question mark (`?`) followed by a colon (`:`), as demonstrated below.

```
(condition) ? expression on true : expression on false
```

Copy

In the above statement, the condition is written first, followed by a `?`. The first expression will execute on `true`, and the second expression will execute on `false`. It is very similar to an `if...else` statement, with more compact syntax.

In this example, we will create a program that checks if a user is 21 or older. If they are, it will print "You may enter" to the console. If they are not, it will print "You may not enter." to the console.

age.js

```
// Set age of user  
let age = 20;  
  
// Place result of ternary operation in a variable  
const oldEnough = (age >= 21) ? "You may enter." : "You may not enter.";
```

Copy



```
// Print output  
oldEnough;
```

Output

```
'You may not enter.'
```

Since the `age` of the user was less than `21`, the fail message was output to the console. The `if...else` equivalent to this would be `"You may enter."` in the `if` statement, and `"You may not enter."` in the `else` statement.

Conclusion

Conditional statements provide us with flow control to determine the output of our programs. They are one of the foundational building blocks of programming, and can be found in virtually all programming languages.

In this article, we learned about how to use the `if`, `else`, and `else if` keywords, and covered nesting of statements, and use of the ternary operator.

Thanks for learning with the DigitalOcean Community. Check out our offerings for compute, storage, networking, and managed databases.

[Learn more about us →](#)

Next in series: [How To Use the Switch Statement in JavaScript →](#)

Want to learn more? Join the DigitalOcean Community!

Join our DigitalOcean community of over a million developers for free! Get help and share knowledge in our Questions & Answers section, find tutorials and tools that will help you grow as a developer and scale your project or business, and subscribe to the newsletter of interest.



[Sign up now →](#)

Tutorial Series: How To Code in JavaScript

JavaScript is a high-level, object-based, dynamic scripting language popular as a tool for making webpages interactive.

[Subscribe](#)

JavaScript Development

Browse Series: 37 articles

[1/37 How To Use the JavaScript Developer Console](#)

[2/37 How To Add JavaScript to HTML](#)

[3/37 How To Write Your First JavaScript Program](#)

[Expand to view all](#)

About the authors



[Tania Rascia](#) Author



[Lisa Tagliaferri](#) Editor



Still looking for an answer?

Ask a question

Search for more help

Was this helpful?

Yes

No



Comments

1 Comments

B *I* U



Leave a comment...

This textbox defaults to using **Markdown** to format your answer.

You can type `!ref` in this text area to quickly search our full set of tutorials, documentation & marketplace offerings and insert the link!

Sign In or Sign Up to Comment

[stef5cbfae72eedfb901ba976f](#) • September 4, 2017



In the example with the grades.js is maybe a better example to use the switch instead of the if () else if construction. And a nice addition to the article could be explaining the triple = with the type checking. "0" === 0 will fail but "0" == 0 will work. <https://codepen.io/stefferd/pen/OjqaoM>



[Reply](#)

This work is licensed under a Creative Commons Attribution-NonCommercial- ShareAlike 4.0 International License.

Try DigitalOcean for free

Click below to sign up and get **\$200 of credit** to try our products over 60 days!

Sign up →

Popular Topics

Ubuntu

Linux Basics

JavaScript

Python

MySQL

Docker

Kubernetes

[All tutorials →](#)

[Free Managed Hosting →](#)



Congratulations on unlocking the whale ambience easter egg! Click the whale button in the bottom left of your screen to toggle some ambient whale noises while you read.




Thank you to the [Glacier Bay National Park & Preserve](#) and [Merrick079](#) for the sounds behind this easter egg.



Interested in whales, protecting them, and their connection to helping prevent climate change? We recommend checking out the [Whale and Dolphin Conservation](#).


[Reset easter egg to be discovered again](#) / [Permanently dismiss and hide easter egg](#)



Get our biweekly newsletter

Sign up for Infrastructure as a Newsletter.


[Sign up →](#)



Hollie's Hub for Good

Working on improving health and education, reducing inequality, and spurring economic growth? We'd like to help.

[Learn more →](#)



Become a
contributor

You get paid; we donate to tech nonprofits.

[Learn more →](#)

Featured on Community

[Kubernetes Course](#)

[Learn Python 3](#)

[Machine Learning in Python](#)

[Getting started with Go](#)

[Intro to Kubernetes](#)

DigitalOcean Products

[Cloudways](#)

[Virtual Machines](#)

[Managed Databases](#)

[Managed Kubernetes](#)

[Block Storage](#)

[Object Storage](#)

[Marketplace](#)


[VPC](#)

[Load Balancers](#)

Welcome to the developer cloud

DigitalOcean makes it simple to launch in the cloud and scale up as you grow – whether you're running one virtual machine or ten thousand.

[Learn more →](#)



Company	Products	Community	Solutions	Contact
About	Products Overview	Tutorials	Website Hosting	Support
Leadership		Q&A	VPS Hosting	Sales
Blog	Droplets	CSS-Tricks	Web & Mobile Apps	Report Abuse
Careers	Kubernetes	Write for DOnations	Game Development	System Status
Customers	App Platform			Share your ideas
Partners	Functions	Currents Research	Streaming	
Channel Partners	Cloudways	Hatch Startup Program	VPN	
Referral Program	Managed Databases		SaaS Platforms	
Affiliate Program	Spaces	deploy by DigitalOcean	Cloud Hosting for Blockchain	
Press	Marketplace	Shop Swag		
Legal	Load Balancers	Research Program	Startup Resources	
Security	Block Storage			
Investor Relations	Tools & Integrations	Open Source		
DO Impact	API	Code of Conduct		
	Pricing	Newsletter Signup		
	Documentation	Meetups		
	Release Notes			
	Uptime			

© 2023 DigitalOcean, LLC. All rights reserved.

