

Get better WordPress performance with Cloudways managed hosting. Start with \$100, free →

We're  
hiring

Blog

Docs

Get  
Support

Contact  
Sales



Tutorials

Questions

Learning Paths

For Businesses

For Builders

Social Impact



## CONTENTS

Overview

Accessing Elements by ID

Accessing Elements by Class

Accessing Elements by Tag

Query Selectors

Complete JavaScript Code

Conclusion

## RELATED

Codelgniter: Getting Started With a Simple Example

[View](#)

How To Install Express, a Node.js Framework, and Set Up Socket.io on a VPS

[View](#)

## Tutorial Series: Understanding the DOM — Document Object Model

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

MANAGE CHOICES

AGREE & PROCEED

// Tutorial //


# How To Access Elements in the DOM

Published on November 20, 2017 · Updated on June 23, 2022

JavaScript   Development



By [Tania Rascia](#)



## # Introduction

In [Understanding the DOM Tree and Nodes](#), we went over how the DOM is structured as a tree of objects called nodes, and that nodes can be text, comments, or elements. Usually when we access content in the DOM, it will be through an HTML element node.

In order to be confident in accessing elements in the DOM, it's good to have a working

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Here is a table overview of the five methods we will cover in this tutorial.

Gets	Selector Syntax	Method
ID	#demo	<code>getElementById()</code>
Class	.demo	<code>getElementsByClassName()</code>
Tag	demo	<code>getElementsByTagName()</code>
Selector (single)		<code>querySelector()</code>
Selector (all)		<code>querySelectorAll()</code>

It is helpful when studying the DOM to work with the examples on your own to ensure that you are understanding and retaining the information you learn.

Create a new file, `access.html`, in your own project to work through the examples along with this article. If you are unsure how to work with JavaScript and HTML locally, review our [How To Add JavaScript to HTML](#) tutorial.

access.html

Copy

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Accessing Elements in the DOM</title>
```

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
</head>

<body>

  <h1>Accessing Elements in the DOM</h1>

  <h2>ID (#demo)</h2>
  <div id="demo">Access me by ID</div>

  <h2>Class (.demo)</h2>
  <div class="demo">Access me by class (1)</div>
  <div class="demo">Access me by class (2)</div>

  <h2>Tag (article)</h2>
  <article>Access me by tag (1)</article>
  <article>Access me by tag (2)</article>

  <h2>Query Selector</h2>
  <div id="demo-query">Access me by query</div>


  <h2>Query Selector All</h2>
  <div class="demo-query-all">Access me by query all (1)</div>
  <div class="demo-query-all">Access me by query all (2)</div>

</body>

</html>
```

In this HTML file, we have many elements that we will access with different document methods. When we render the file in a browser, it will look similar to this:

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



We'll be using the different methods that we outlined in the [Overview](#) above to access the available elements in the file.

## # Accessing Elements by ID

The easiest way to access a single element in the DOM is by its unique [ID](#). You can get an element by ID with the `getElementById()` method of the `document` object.

```
document.getElementById();
```

Copy

In order to be accessed by ID, the HTML element must have an `id` attribute. You have a `div` element with an ID of `demo` you can use:

```
<div id="demo">Access me by ID</div>
```

Copy

In the *Console*, get the element and assign it to the `demoId` variable

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
> console.log(demoId);
```

Copy

### Output


```
<div id="demo">Access me by ID</div>
```

You can be sure you're accessing the correct element by changing the `border` property to `purple`.

```
> demoId.style.border = '1px solid purple';
```

Copy

Once you do so, your live page will look like this:



Accessing an element by ID is an effective way to get an element quickly in the DOM. However, it has drawbacks: an ID must always be unique to the page, and therefore you will only ever be able to access a single element at a time with the `getElementById()` method. If you wanted to add a function to many elements throughout the page, your code would quickly become repetitious.

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
document.getElementsByClassName();
```

[Copy](#)

Now we want to access more than one element, and in our example we have two elements with a `demo` class.

```
<div class="demo">Access me by class (1)</div>
<div class="demo">Access me by class (2)</div>
```

[Copy](#)

Access these elements in the *Console* and put them in a variable called `demoClass`.

```
> const demoClass = document.getElementsByClassName('demo');
```

[Copy](#)

At this point, it might be tempting to modify the elements the same way you did with the ID example. However, if you try to run the following code and change the `border` property of the class `demo` elements to orange, you will get an error.

```
> demoClass.style.border = '1px solid orange';
```

[Copy](#)

#### Output

```
Uncaught TypeError: Cannot set property 'border' of undefined
```

The reason this doesn't work is because instead of just getting one element, you have an array-like object of elements.

```
> console.log(demoClass);
```

[Copy](#)

#### Output

```
(2) [div.demo, div.demo]
```


[JavaScript arrays](#) must be accessed with an index number. You can change the first element of this array by using an index of `0`.

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
> for (i = 0; i < demoClass.length; i++) {
>   demoClass[i].style.border = '1px solid orange';
> }
```

Copy

When you run this code, your live page will be rendered like this:



You have now selected every element on the page that has a `demo` class, and changed the `border` property to `orange`.

## # Accessing Elements by Tag

A less specific way to access multiple elements on the page would be by its HTML tag name. You access an element by tag with the `getElementsByTagName()` method.

```
document.getElementsByTagName();
```

Copy

For our tag example, we're using `article` elements.


This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



```
> const demoTag = document.getElementsByTagName('article');
>
> for (i = 0; i < demoTag.length; i++) {
>   demoTag[i].style.border = '1px solid blue';
> }
```

Copy

Upon running the code, the live page will be modified like so:



The loop changed the `border` property of all `article` elements to `blue`.

## # Query Selectors

If you have any experience with the [jQuery](#) API, you may be familiar with jQuery's method of accessing the DOM with CSS selectors.

```
$('#demo'); // returns the demo ID element in jQuery
```

Copy

You can do the same in plain JavaScript with the `querySelector()` and

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

To access a single element, you can use the [querySelector\(\)](#) method. In our HTML file, we have a `demo-query` element

```
<div id="demo-query">Access me by query</div>
```

[Copy](#)

The selector for an `id` attribute is the hash symbol (`#`). You can assign the element with the `demo-query` id to the `demoQuery` variable.

```
> const demoQuery = document.querySelector('#demo-query');
```

[Copy](#)

In the case of a selector with multiple elements, such as a class or a tag, `querySelector()` will return the first element that matches the query. You can use the [querySelectorAll\(\)](#) method to collect all the elements that match a specific query.

In the example file, you have two elements with the `demo-query-all` class applied to them.

```
<div class="demo-query-all">Access me by query all (1)</div>
<div class="demo-query-all">Access me by query all (2)</div>
```

[Copy](#)

The selector for a `class` attribute is a period or full stop (`.`), so you can access the class with `.demo-query-all`.

```
> const demoQueryAll = document.querySelectorAll('.demo-query-all');
```


[Copy](#)

Using the `forEach()` method, you can apply the color `green` to the `border` property of all matching elements.

```
> demoQueryAll.forEach(query => {
>   query.style.border = '1px solid green';
> });
```

[Copy](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



With `querySelector()`, comma-separated values function as an OR operator. For example, `querySelector('div, article')` will match `div` *or* `article`, whichever appears first in the document. With `querySelectorAll()`, comma-separated values function as an AND operator, and `querySelectorAll('div, article')` will match all `div` *and* `article` values in the document.

Using the query selector methods is extremely powerful, as you can access any element or group of elements in the DOM the same way you would in a CSS file. For a complete list of selectors, review [CSS Selectors](#) on the Mozilla Developer Network.

## # Complete JavaScript Code

Below is the complete script of the work you did above. You can use it to access all the elements on our example page. Save the file as `access.js` and load it in to the HTML file right before the closing `body` tag.

`access.js`

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
// Change border of ID demo to purple
demoId.style.border = '1px solid purple';

// Change border of class demo to orange
for (i = 0; i < demoClass.length; i++) {
  demoClass[i].style.border = '1px solid orange';
}

// Change border of tag demo to blue
for (i = 0; i < demoTag.length; i++) {
  demoTag[i].style.border = '1px solid blue';
}

// Change border of ID demo-query to red
demoQuery.style.border = '1px solid red';

// Change border of class query-all to green
demoQueryAll.forEach(query => {
  query.style.border = '1px solid green';
});
```

Your final HTML file will look like this:

access.html

Copy

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Accessing Elements in the DOM</title>

  <style>
    html { font-family: sans-serif; color: #333; }
    body { max-width: 500px; margin: 0 auto; padding: 0 15px; }
    div, article { padding: 10px; margin: 5px; border: 1px solid #dedede; }
  </style>

</head>
```

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
<h2>Class (.demo)</h2>
<div class="demo">Access me by class (1)</div>
<div class="demo">Access me by class (2)</div>

<h2>Tag (article)</h2>
<article>Access me by tag (1)</article>
<article>Access me by tag (2)</article>

<h2>Query Selector</h2>
<div id="demo-query">Access me by query</div>

<h2>Query Selector All</h2>
<div class="demo-query-all">Access me by query all (1)</div>
<div class="demo-query-all">Access me by query all (2)</div>

<script src="access.js"></script>

</body>

</html>
```

You can continue to work on these template files to make additional changes by accessing HTML elements.

## # Conclusion

In this tutorial, we went over 5 ways to access HTML elements in the DOM — by ID, by class, by HTML tag name, and by selector. The method you will use to get an element or group of elements will depend on browser support and how many elements you will be manipulating. You should now feel confident to access any HTML element in a document with JavaScript through the DOM.

Thanks for learning with the DigitalOcean Community. Check out our offerings for compute, storage, networking, and managed databases.

[Learn more about us →](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

## Want to learn more? Join the DigitalOcean Community!

Join our DigitalOcean community of over a million developers for free! Get help and share knowledge in our Questions & Answers section, find tutorials and tools that will help you grow as a developer and scale your project or business, and subscribe to topics of interest.

Sign up now →

## Tutorial Series: Understanding the DOM – Document Object Model

The Document Object Model, usually referred to as the DOM, is an essential part of making websites interactive. It is an interface that allows a programming language to manipulate the content, structure, and style of a website. JavaScript is the client-side scripting language that connects to the DOM in an internet browser.

Subscribe

JavaScript   Development

### Browse Series: 8 articles

[1/8 Introduction to the DOM](#)

[2/8 Understanding the DOM Tree and Nodes](#)

[3/8 How To Access Elements in the DOM](#)

Expand to view all

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



[Tania Rascia](#) Author



[Lisa Tagliaferri](#) Editor



[Madison Scott-Clary](#) Editor  
Tech Writer at DigitalOcean

Still looking for an answer?

Ask a question

Search for more help

Was this helpful?

Yes

No



## Comments

### 3 Comments

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

This textbox defaults to using **Markdown** to format your answer.

You can type `!ref` in this text area to quickly search our full set of tutorials, documentation & marketplace offerings and insert the link!

### Sign In or Sign Up to Comment

[jantjehofje](#) • September 3, 2020 

Thanks, really helped me out. Great tutorial and easy to follow

[Reply](#)

[Peter Roche](#) • April 25, 2019 

Hi Tania, I too thought it was a great tutorial – all of them are so far. Really helpful. There is one thing, though, that I think could be improved. When you are processing elements that were accessed using `.getElementsByClassName`, or `.getElementsByTagName`, you handle the returned variable with a for loop, but when you are processing elements that were accessed using `.querySelectorAll` you handle the returned variable with the `.forEach` method. I think it would have been good to have some explanation for why – which, if I understand correctly, is because the “`getElementsBy...`” methods return “HTMLCollection” objects, which cannot be processed with `.forEach` like arrays, while the `querySelectorAll()` method returns “NodeList” objects, which, in modern browsers, CAN be processed with `.forEach` like arrays. I think a little explanation about that would have been helpful.

[Reply](#)

[I Miguel Aquilera](#) • March 9, 2019 

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



[Reply](#)

This work is licensed under a Creative Commons Attribution-NonCommercial- ShareAlike 4.0 International License.

### Try DigitalOcean for free

Click below to sign up and get **\$200 of credit** to try our products over 60 days!

Sign up →

### Popular Topics

Ubuntu

Linux Basics

JavaScript

Python


MySQL

Docker

Kubernetes

[All tutorials →](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



## Get our biweekly newsletter

Sign up for Infrastructure as a Newsletter.

[Sign up →](#)

HOLLIE'S  
HUB




FOR  
GOOD

## Hollie's Hub for Good

Working on improving health and education, reducing inequality, and spurring economic growth? We'd like to help.

[Learn more →](#)



## Become a contributor

You get paid; we donate to tech nonprofits.

[Learn more →](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

[Kubernetes Course](#)[Learn Python 3](#)[Machine Learning in Python](#)[Getting started with Go](#)[Intro to Kubernetes](#)


## DigitalOcean Products

[Cloudways](#)[Virtual Machines](#)[Managed Databases](#)[Managed Kubernetes](#)[Block Storage](#)[Object Storage](#)[Marketplace](#)[VPC](#)[Load Balancers](#)

## Welcome to the developer cloud

DigitalOcean makes it simple to launch in the cloud and scale up as you grow – whether you're running one virtual machine or ten thousand.

Learn more →



### Company

[About](#)

### Products

[Products](#)

### Community

[Tutorials](#)

### Solutions

[Website Hosting](#)



### Contact

[Support](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Partners	Functions	Currents	Streaming
Channel Partners	Cloudways	Research	VPN
Referral Program	Managed Databases	Hatch Startup Program	SaaS Platforms
Affiliate Program	Spaces	deploy by DigitalOcean	Cloud Hosting for Blockchain
Press	Marketplace	Shop Swag	Startup Resources
Legal	Load Balancers	Research Program	
Security	Block Storage	Open Source	
Investor Relations	Tools & Integrations	Code of Conduct	
DO Impact	API	Newsletter Signup	
	Pricing	Meetups	
	Documentation		
	Release Notes		
	Uptime		

© 2023 DigitalOcean, LLC. All rights reserved.



This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.