

Need response times for mission critical applications within 30 minutes? Learn more →

We're
hiring

Blog

Docs

Get
Support

Contact
Sales



Tutorials

Questions

Learning Paths

For Businesses

Product Docs

Social Impact

C

CONTENTS

For Loop

For...In Loop

For...Of Loop

Conclusion

RELATED


Codelgniter: Getting Started With a Simple Example

[View](#)

How To Install Express, a Node.js Framework, and Set Up Socket.io on a VPS

[View](#)

Tutorial Series: How To Code in JavaScript




For Loops, For...Of Loops and For...In Loops in JavaScript

Published on October 2, 2017 · Updated on August 26, 2021

JavaScript Development



By [Tania Rascia](#)



Introduction

[Loops](#) are used in programming to automate repetitive tasks. The most basic types of loops used in JavaScript are the `while` and `do...while` statements, which you can review in [“How To Construct While and Do...While Loops in JavaScript.”](#)

Because `while` and `do...while` statements are [conditionally based](#), they execute when a given statement returns as evaluating to `true`. Similar in that they are also conditionally based, `for` statements also include extra features such as a **loop counter**, allowing you to set the number of iterations of the loop beforehand.

In this tutorial, we will learn about the `for` statement, including the `for...of` and `for...in` statements, which are essential elements of the JavaScript programming language.

Loop

The `for` statement is a type of loop that will use up to three optional expressions to implement the repeated execution of a code block.

Let's take a look at an example of what that means.

```
for (initialization; condition; final expression) {  
    // code to be executed  
}
```

[Copy](#)

In the syntax above there are three expressions inside the `for` statement: the **initialization**, the **condition**, and the **final expression**, also known as incrementation.

Let's use a basic example to demonstrate what each of these statements does.

forExample.js

```
// Initialize a for statement with 5 iterations  
for (let i = 0; i < 4; i++) {  
    // Print each iteration to the console  
    console.log(i);  
}
```

[Copy](#)

When we run the code above, we'll receive the following output:

Output

```
0  
1  
2  
3
```

In the above example, we initialized the `for` loop with `let i = 0`, which begins the loop at 0. We set the condition to be `i < 4`, meaning that as long as `i` evaluates as less than 4, the loop will continue to run. Our final expression of `i++` increments the count for each iteration through the loop. The `console.log(i)` prints out the numbers, starting with 0 and stopping as soon as `i` is evaluated as 4.

Without using a loop, we could have achieved that same output by using the following code.

noLoop.js

```
// Set initial variable to 0  
let i = 0;
```

[Copy](#)

```
// Manually increment variable by 1 four times  
console.log(i++);  
console.log(i++);  
console.log(i++);  
console.log(i++);
```

Without the loop in place, the code block is repetitive and consists of more lines. If we needed to increment through more numbers we would have needed to write even more lines of code.

Let's go over each expression in the loop to understand them fully.

Initialization

Our first expression is the **initialization**. This is what it looks like.

```
let i = 0;
```

Copy

We're declaring a variable called `i` with the `let` keyword (the keyword `var` may also be used) and giving it a value of `0`. While the variable can be named anything, `i` is most frequently used. The variable `i` stands for **iteration**, is consistent, and keeps the code compact.

Condition

Just as we saw in the `while` and `do...while` loops, `for` loops usually contain a **condition**. Here is our condition statement.

```
i < 4;
```

Copy

We already established that our iteration variable, `i`, represents `0` to start. Now we are saying that the condition is `true` as long as `i` is less than `4` in this example.

Final Expression

The **final expression** is a statement that is executed at the end of each loop. It is most often used to increment or decrement a value, but it can be used for any purpose.



Copy

In our example, we are incrementing the variable by one, with `i++`. This is the same as running `i = i + 1`.

Unlike the initialization and condition expressions, the final expression does not end with a semicolon.

Putting it Together

Now that we've reviewed our three expressions contained in the `for` loop, we can take a look at the complete loop again.

```
// Initialize a for statement with 5 iterations
for (let i = 0; i < 4; i++) {
    console.log(i);
}
```

[Copy](#)

First, we are declaring `i` and setting it to `0`. Then, we are setting a condition for the loop to run until `i` is less than `4`. Finally, we're incrementing `i` by one `1` each iteration. Our code block prints the value of `i` to the console, so our result is `0`, `1`, `2`, and `3` as output.

Optional Expressions

All three expressions in the `for` loop are optional. For example, we can write the same `for` statement without the initialization expression by initializing the variable outside of the loop.

```
// Declare variable outside the loop
let i = 0;


// Initialize the loop
for (; i < 4; i++) {
    console.log(i);
}
```

[Copy](#)

Output

```
0
1
2
3
```



In this , the first `;` is necessary to denote whether the statement refers to initialization, condition, or final expression, even when it's omitted.

Below, we can also remove the condition from the loop. We will use an `if` statement combined with `break` to tell the loop to stop running once `i` is greater than `3`, which is the reverse of the `true` condition.

```
// Declare variable outside the loop
let i = 0;

// Omit initialization and condition
for (; ; i++) {
    if (i > 3) {
        break;
    }
    console.log(i);
}
```

[Copy](#)

Output

```
0
1
2
3
```

Warning: The `break` statement *must* be included if the condition is omitted, otherwise the loop will run forever as an [infinite loop](#) and potentially crash the browser.

Lastly, the final expression can be removed by putting it at the end of the loop instead. Both semicolons must still be included, or the loop will not function.

```
// Declare variable outside the loop
let i = 0;

// Omit all statements
for (; ;) {
    if (i > 3) {
        break;
    }
    console.log(i);
    i++;
}
```

[Copy](#)

```
0
1
```

2
3

As we can see from the above examples, including all three statements generally produces the most concise and readable code. However, it's useful to know that statements can be omitted in case you encounter it in the future.

Modifying an Array

We can use `for` loops to modify an [array](#).

In the next example, we'll create an empty array and populate it with the loop counter variable.

modifyArray.js

```
// Initialize empty array
let arrayExample = [];

// Initialize loop to run 3 times
for (let i = 0; i < 3; i++) {
    // Update array with variable value
    arrayExample.push(i);
    console.log(arrayExample);
}
```

Copy

Running the JavaScript code above will result in the following output.

Output

```
[ 0 ]
[ 0, 1 ]
[ 0, 1, 2 ]
```

We set a loop that runs until `i < 3` is no longer `true`, and we're telling the console to print the `arrayExample` array to the console at the end of each iteration. With this method, we can see how the array updates with the new values.

Length of an Array

Sometimes, we might want a loop to run a number of times without being certain of what the number of iterations will be. Instead of declaring a static number, as we did in previous examples, we can make use of the [length property](#) of an array to have the loop run as many times as there are items in the array.

loopThroughArray.js

Copy

```
// Declare array with 3 items
let fish = [ "flounder", "salmon", "pike" ];

// Initialize for loop to run for the total length of an array
for (let i = 0; i < fish.length; i++) {
    // Print each item to the console
    console.log(fish[i]);
}
```

We'll receive the following output.

Output

```
flounder
salmon
pike
```

In this example, we increment through each index of the array with `fish[i]` (e.g. the loop will increment through `fish[0]`, `fish[1]`, etc.). This causes the index to dynamically update with each iteration.

More detail on the [for statement is available on the Mozilla Developer Network](#).

For...In Loop

The `for...in` statement iterates over the properties of an object. To demonstrate, we will make a simple `shark` object with a few *name:value* pairs.

shark.js

Copy

```
const shark = {
    species: "great white",
    color: "white",
    numberOfTeeth: Infinity
}
```

Using the `for...in` loop, we can easily access each of the property names.

Copy

```
// Print property names of object
for (attribute in shark) {
    console.log(attribute);
}
```


Output

```
species  
color  
numberOfTeeth
```

We can also access the values of each property by using the property name as the index value of the object.

```
// Print property values of object  
for (attribute in shark) {  
    console.log(shark[attribute]);  
}
```

[Copy](#)

Output

```
great white  
white  
Infinity
```

Putting them together, we can access all the names and values of an object.

```
// Print names and values of object properties  
for (attribute in shark) {  
    console.log(`${attribute}.toUpperCase() + `: ${shark[attribute]}`);  
}
```

[Copy](#)

Output

```
SPECIES: great white  
COLOR: white  
NUMBEROFTEETH: Infinity
```

We used the `toUpperCase()` method to modify the property name, and following it by the property value. `for...in` is an extremely useful way to iterate through object properties.

Review [for...in on the Mozilla Developer Network](#) for more detailed information.

For...Of Loop

The `for...in` statement is useful for iterating over object properties, but to iterate over iterable objects like [arrays](#) and [strings](#), we can use the `for...of` statement. The `for...of`

statement is a newer feature as of [ECMAScript 6](#). ECMAScript (or ES) is a scripting-language specification created to standardize JavaScript.

In this example of a `for...of` loop, we will create an array and print each item in the array to the console.

sharks.js

```
// Initialize array of shark species
let sharks = [ "great white", "tiger", "hammerhead" ];

// Print out each type of shark
for (let shark of sharks) {
    console.log(shark);
}
```

Copy

We'll receive the following as output from the `for...of` statement.

Output

```
great white
tiger
hammerhead
```

It is also possible to print out the index associated with the index elements using the `entries()` method.

sharks.js

```
...
// Loop through both index and element
for (let [index, shark] of sharks.entries()) {
    console.log(index, shark);
}
```

Copy

Output

```
0 'great white'
1 'tiger'
2 'hammerhead'
```

A string can be iterated through in the same way as an array.



sharkString.js

[Copy](#)

```
// Assign string to a variable
let sharkString = "sharks";

// Iterate through each index in the string
for (let shark of sharkString) {
  console.log(shark);
}
```

Output

```
s
h
a
r
k
s
```

In this case, we looped through each character in the string, printing them in sequential order.

For a more detailed account of the differences between `for...in` and `for...of`, read about [for...of loops on the Mozilla Developer Network](#).

Conclusion

In this tutorial, we learned how to construct `for` loops in JavaScript, consisting of the `for`, `for...of` and `for...in` statements.

Loops are an integral part of programming in JavaScript, and are used for automating repetitive tasks and making code more concise and efficient.

Thanks for learning with the DigitalOcean Community. Check out our offerings for compute, storage, networking, and managed databases.

[Learn more about us →](#)

Next in series: [How To Define Functions in JavaScript →](#)



Want to learn more? Join the DigitalOcean Community!

Join our DigitalOcean community of over a million developers for free! Get help and share knowledge in our Questions & Answers section, find tutorials and tools that will help you grow as a developer and scale your project or business, and subscribe to topics of interest.

Sign up now →

Tutorial Series: How To Code in JavaScript

JavaScript is a high-level, object-based, dynamic scripting language popular as a tool for making webpages interactive.

Subscribe

JavaScript Development

Browse Series: 37 articles

[1/37 How To Use the JavaScript Developer Console](#)

[2/37 How To Add JavaScript to HTML](#)

[3/37 How To Write Your First JavaScript Program](#)

Expand to view all

About the authors



[Tania Rascia](#) Author



[Lisa Tagliaferri](#) Editor

Still looking for an answer?

Ask a question

Search for more help

Was this helpful?

Yes

No



Comments

1 Comments

B *I* U



Leave a comment...

This textbox defaults to using **Markdown** to format your answer.

You can type `!ref` in this text area to quickly search our full set of tutorials, documentation & marketplace offerings and insert the link!

Sign In or Sign Up to Comment



[anapimolodec](#) • July 19, 2022



Hello, thank you for this post. Is there any difference between using For Loop and For Of Loop for arrays? I have the same code but with different loop types and they are giving different answers. And I cannot understand why, please help! thanks!

[Reply](#)



This work is licensed under a Creative Commons Attribution-NonCommercial- ShareAlike 4.0 International License.

Try DigitalOcean for free

Click below to sign up and get **\$200 of credit** to try our products over 60 days!

Sign up →

Popular Topics

Ubuntu

Linux Basics

JavaScript

Python




MySQL

Doc


Kubern



[All tutorials →](#)[Free Managed Hosting →](#)

-  Congratulations on unlocking the whale ambience easter egg! Click the whale button in the bottom left of your screen to toggle some ambient whale noises while you read.
-  Thank you to the [Glacier Bay National Park & Preserve](#) and [Merrick079](#) for the sounds behind this easter egg.
-  Interested in whales, protecting them, and their connection to helping prevent climate change? We recommend checking out the [Whale and Dolphin Conservation](#).

[Reset easter egg to be discovered again](#) / [Permanently dismiss and hide easter egg](#)



Get our biweekly newsletter

Sign up for Infrastructure as a Newsletter.

[Sign up →](#)




Hollie's Hub for Good

Working on improving health and education, reducing inequality, and spurring economic growth? We'd like to help.

[Learn more →](#)





Become a contributor

You get paid; we donate to tech nonprofits.

[Learn more](#) →

Featured on Community

[Kubernetes Course](#)

[Learn Python 3](#)

[Machine Learning in Python](#)

[Getting started with Go](#)

[Intro to Kubernetes](#)

DigitalOcean Products

[Cloudways](#)

[Virtual Machines](#)

[Managed Databases](#)

[Managed Kubernetes](#)

[Block Storage](#)

[Object Storage](#)

[Marketplace](#)

[VPC](#)


[Load Balancers](#)

Welcome to the developer cloud

DigitalOcean makes it simple to launch in the cloud and scale up as you grow – whether you're running one virtual machine or ten thousand.



[Learn more](#) →



Company	Products	Community	Solutions	Contact
About	Products Overview	Tutorials	Website Hosting	Support
Leadership		Q&A	VPS Hosting	Sales
Blog	Droplets	CSS-Tricks	Web & Mobile Apps	Report Abuse
Careers	Kubernetes	Write for DOnations	Game Development	System Status
Customers	App Platform	Currents Research	Streaming	Share your ideas
Partners	Cloudways	Hatch Startup Program	VPN	
Channel Partners	Managed Databases	deploy by DigitalOcean	SaaS Platforms	
Referral Program	Spaces	Shop Swag	Cloud Hosting for Blockchain	
Affiliate Program	Marketplace	Research Program	Startup Resources	
Press	Load Balancers	Open Source		
Legal	Block Storage	Code of Conduct		
Security	Tools & Integrations	Newsletter Signup		
Investor Relations	API	Meetups		
DO Impact	Pricing			
	Documentation			
	Release Notes			
	Uptime			



© 2023 DigitalOcean, LLC. All rights reserved.

