

Get better WordPress performance with Cloudways managed hosting. Start with \$100, free →

We're
hiring

Blog

Docs

Get
Support

Contact
Sales



Tutorials

Questions

Learning Paths

For Businesses

For Builders

Social Impact



CONTENTS

Defining a Function

Function Parameters

Returning Values

Function Expressions

Arrow Functions

Conclusion

RELATED

CodeIgniter: Getting Started With a Simple Example

[View](#)

How To Install Express, a Node.js Framework, and Set Up Socket.io on a VPS

[View](#)

Tutorial Series: How To Code in JavaScript



05/07/2019 · 10 min read · 1,234 views

05/07/2019 · 10 min read · 1,234 views



This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

MANAGE CHOICES

AGREE & PROCEED

// Tutorial //


How To Define Functions in JavaScript

Published on October 9, 2017 · Updated on August 26, 2021

JavaScript Development



By [Tania Rascia](#)



Introduction

A **function** is a block of code that performs an action or returns a value. Functions are custom code defined by programmers that are reusable, and can therefore make your programs more modular and efficient.

In this tutorial, we will learn several ways to define a function, call a function, and use function parameters in JavaScript.

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Functions are defined, or declared, with the `function` keyword. Below is the syntax for a function in JavaScript.

```
function nameOfFunction() {  
    // Code to be executed  
}
```

[Copy](#)

The declaration begins with the `function` keyword, followed by the name of the function. Function names follow the same rules as variables — they can contain letters, numbers, underscores and dollar signs, and are frequently written in [camel case](#). The name is followed by a set of parentheses, which can be used for optional parameters. The code of the function is contained in curly brackets, just like a [for statement](#) or an [if statement](#).

In our first example, we'll make a **function declaration** to print a greeting statement to the console.

```
// Initialize greeting function  
function greet() {  
    console.log("Hello, World!");  
}
```

[Copy](#)

Here we have the code to print `Hello, World!` to the console contained inside the `greet()` function. However, nothing will happen and no code will execute until we **invoke**, or call the function. You can invoke a function by writing the name of the function followed by the parentheses.

```
// Invoke the function  
greet();
```

[Copy](#)

Now we will put those together, defining our function and invoking it.

greet.js

```
// Initialize greeting function  
function greet() {  
    console.log("Hello, World!");  
}
```

[Copy](#)

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

With the call for `greet();`, the function will run and we will receive the `Hello, World!` as the program's output.

Output

```
Hello, World!
```

Now we have our `greet()` code contained in a function, and can reuse it as many times as we want.

Using parameters, we can make the code more dynamic.

Function Parameters

In our `greet.js` file, we created a basic function that prints `Hello, World` to the console. Using parameters, we can add additional functionality that will make the code more flexible. **Parameters** are input that get passed into functions as names and behave as local variables.

When a user logs in to an application, we may want the program to greet them by name, instead of just saying, "Hello, World!".

We'll add a parameter into our function, called `name`, to represent the name of the person being greeted.

```
// Initialize custom greeting function
function greet(name) {
  console.log(`Hello, ${name}!`);
}
```

[Copy](#)

The name of the function is `greet`, and now we have a single parameter inside the parentheses. The name of the parameter follows the same rules as naming a variable. Inside of the function, instead of a static string consisting of `Hello, World`, we have a [template literal](#) string containing our parameter, which is now behaving as a local variable.

You'll notice we haven't defined our `name` parameter anywhere. We assign it a value when we invoke our function. Assuming our user is named Sammy, we'll call the function and

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

The value of "sammy" is being passed into the function through the `name` parameter. Now every time `name` is used throughout the function, it will represent the "sammy" value. Here is the whole code.

greetSammy.js

```
// Initialize custom greeting function
function greet(name) {
    console.log(`Hello, ${name}!`);
}

// Invoke greet function with "Sammy" as the argument
greet("Sammy");
```

[Copy](#)

When we run the program above, we'll receive the following output.

Output

```
Hello, Sammy!
```

Now we have an example of how a function can be reused. In a real world example, the function would pull the username from a database instead of directly supplying the name as an argument value.

In addition to parameters, variables can be declared inside of functions. These variables are known as **local variables**, and will only exist inside the *scope* of their own function block. Variable scope determines variables' accessibility; variables that are defined inside of a function are not accessible from outside of the function, but they can be used as many times as their function is used throughout a program.

Returning Values

More than one parameter can be used in a function. We can pass multiple values into a function and return a value. We will create a function to find the sum of two values, represented by `x` and `y`.

sum.js

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

```
// Invoke function to find the sum  
add(9, 7);
```

In the program above, we defined a function with the parameters `x` and `y`, and then passed the values of `9` and `7` to the function. When we run the program, we'll receive the sum of those numbers as the output.

Output

```
16
```

In this case, with `9` and `7` passed to the `sum()` function, the program returned `16`.

When the `return` keyword is used, the function ceases to execute and the value of the expression is returned. Although in this case the browser will display the value in the console, it is not the same as using `console.log()` to print to the console. Invoking the function will output the value exactly where the function was invoked. This value can be used immediately or placed into a variable.

Function Expressions

In the last section, we used a function declaration to get the sum of two numbers and return that value. We can also create a [function expression](#) by assigning a function to a variable.

Using our same `add` function example, we can directly apply the returned value to a variable, in this case `sum`.

functionExpression.js

```
// Assign add function to sum constant  
const sum = function add(x, y) {  
    return x + y;  
}  
  
// Invoke function to find the sum  
sum(20, 5);
```

[Copy](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Now the `sum` constant is a function. We can make this expression more concise by turning it into an **anonymous function**, which is an unnamed function. Currently, our function has the name `add`, but with function expressions it is not necessary to name the function and the name is usually omitted.

anonymousExpression.js

```
// Assign function to sum constant
const sum = function(x, y) {
    return x + y;
}

// Invoke function to find the sum
sum(100, 3);
```

Copy

Output

103

In this example, we've removed the name of the function, which was `add`, and turned it into an anonymous function. A named function expression could be used to aid in debugging, but it is usually omitted.

Arrow Functions

So far, we have gone through how to define functions using the `function` keyword. However, there is a newer, more concise method of defining a function known as **arrow function expressions** as of [ECMAScript 6](#). Arrow functions, as they are commonly known, are represented by an equals sign followed by a greater than sign: `=>`.

Arrow functions are always anonymous functions and a type of function expression. We can create a basic example to find the product of two numbers.

arrowFunction.js

```
// Define multiply function
const multiply = (x, y) => {
    return x * y;
}
```

Copy

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Output

120

Instead of writing out the keyword `function`, we use the `=>` arrow to indicate a function. Otherwise, it works similarly to a regular function expression, with some advanced differences which you can read about under [Arrow Functions on the Mozilla Developer Network](#).

In the case of only one parameter, the parentheses can be excluded. In this example, we're squaring `x`, which only requires one number to be passed as an argument. The parentheses have been omitted.

```
// Define square function
const square = x => {
    return x * x;
}

// Invoke function to find product
square(8);
```

Copy

Output

64

Note: In the case of no parameters, an empty set of parentheses `()` is required in the arrow functions.

With these particular examples that only consist of a `return` statement, arrow functions allow the syntax to be reduced even further. If the function is only a single line `return`, both the curly brackets and the `return` statement can be omitted, as seen in the example below.

```
// Define square function
const square = x => x * x;

// Invoke function to find product
```

Copy

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

All three of these types of syntax result in the same output. It is generally a matter of preference or company coding standards to decide how you will structure your own functions.

Conclusion

In this tutorial, we covered function declarations and function expressions, returning values from functions, assigning function values to variables, and ES6 arrow functions.

Functions are blocks of code that return a value or perform an action, making programs scalable and modular.

Thanks for learning with the DigitalOcean Community. Check out our offerings for compute, storage, networking, and managed databases.

[Learn more about us →](#)

Next in series: Understanding Prototypes and Inheritance in JavaScript -
>

Want to learn more? Join the DigitalOcean Community!

Join our DigitalOcean community of over a million developers for free! Get help and share knowledge in our Questions & Answers section, find tutorials and tools that will help you grow as a developer and scale your project or business, and subscribe to topics of interest.

Sign up now →

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

JavaScript is a high-level, object-based, dynamic scripting language popular as a tool for making webpages interactive.

Subscribe

JavaScript Development

Browse Series: 37 articles

[1/37 How To Use the JavaScript Developer Console](#)

[2/37 How To Add JavaScript to HTML](#)

[3/37 How To Write Your First JavaScript Program](#)

Expand to view all

About the authors



[Tania Rascia](#) Author



[Lisa Tagliaferri](#) Editor

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Was this helpful?

Yes

No



Comments

5 Comments

B *I* U H₁ H₂ H₃ “”



Leave a comment...

This textbox defaults to using **Markdown** to format your answer.

You can type `!ref` in this text area to quickly search our full set of tutorials, documentation & marketplace offerings and insert the link!

Sign In or Sign Up to Comment

[engdanishjan619](#) • January 24, 2022



it is very nice to understand and easy to use the given and work with it .

[Reply](#)

[jainayushjain95](#) • March 8, 2019



That's a great article. Inspired me to write a complete series over JS:

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

4)[Arrays In JavaScript: Part 3]

(https://fullstackgeek.blogspot.com/2019/01/filtering-sorting-arrays-javascript_31.html)

[Reply](#)

[Cassyemmanuel](#) • November 27, 2018 

Hello everyone i need an assist on something in javascript please, the issue at hand is take for instance a php website with multiple pages, were the header and footer is in different files using php include statement to include the header and footer i. e <?php include "header" ; ?> And an external javascript file linked in the header or footer. I. e for instance <javascript src="mm.js"> And a button located in the header page, since the header is included in all pages, that makes the one button appear in all pages, the button is to trigger a javascript function inside the linked javascript file for instance a function to alert "hello world ", now when the button is clicked on the index page it triggers the function but when the same button is clicked in the other pages the function Will not be triggered...

[Reply](#)

[Leonardo Martinez](#) • November 7, 2017 

Excellent, it is clear that anyone can understand it, I appreciate very much your effort, thank you.

[Reply](#)

[ravikiran yadav](#) • October 31, 2017 

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

[Reply](#)

This work is licensed under a Creative Commons Attribution-NonCommercial- ShareAlike 4.0 International License.

Try DigitalOcean for free

Click below to sign up and get **\$200 of credit** to try our products over 60 days!

Sign up →

Popular Topics

Ubuntu

Linux Basics

JavaScript

Python


MySQL

Docker

Kubernetes

[All tutorials →](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.



Get our biweekly newsletter

Sign up for Infrastructure as a Newsletter.

[Sign up →](#)

HOLLIE'S
HUB




FOR
GOOD

Hollie's Hub for Good

Working on improving health and education, reducing inequality, and spurring economic growth? We'd like to help.

[Learn more →](#)



Become a contributor

You get paid; we donate to tech nonprofits.

[Learn more →](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

[Kubernetes Course](#)[Learn Python 3](#)[Machine Learning in Python](#)[Getting started with Go](#)[Intro to Kubernetes](#)


DigitalOcean Products

[Cloudways](#)[Virtual Machines](#)[Managed Databases](#)[Managed Kubernetes](#)[Block Storage](#)[Object Storage](#)[Marketplace](#)[VPC](#)[Load Balancers](#)

Welcome to the developer cloud

DigitalOcean makes it simple to launch in the cloud and scale up as you grow – whether you're running one virtual machine or ten thousand.

Learn more →



Company

Products

Community

Solutions



Contact

[About](#)[Products](#)[Tutorials](#)[Website Hosting](#)[Support](#)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Partners	Functions	Currents	Streaming
Channel Partners	Cloudways	Research	VPN
Referral Program	Managed Databases	Hatch Startup Program	SaaS Platforms
Affiliate Program	Spaces	deploy by DigitalOcean	Cloud Hosting for Blockchain
Press	Marketplace	Shop Swag	Startup Resources
Legal	Load Balancers	Research Program	
Security	Block Storage	Open Source	
Investor Relations	Tools & Integrations	Code of Conduct	
DO Impact	API	Newsletter Signup	
	Pricing	Meetups	
	Documentation		
	Release Notes		
	Uptime		

© 2023 DigitalOcean, LLC. All rights reserved.



This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.