Problem 1: Administering

Student: Amy Dalziel
Cohort: SD 9

Screenshot of PostgreSQL command line

```
● ● ●                          📁 keyinstudent — psql ‹ runpsql.sh — 124×49
Last login: Wed Jan 10 09:28:55 on ttys009
/Library/PostgreSQL/16/scripts/runpsql.sh; exit
keyinstudent@Admins-MacBook-Pro ~ % /Library/PostgreSQL/16/scripts/runpsql.sh; exit
Server [localhost]:
Database [postgres]:
Port [5433]:
Username [postgres]:
Password for user postgres:
[psql (16.1)                                                                                                           ]
Type "help" for help.

postgres=# select version();
[                                              version                                                                 ]
--------------------------------------------------------------------------------------------------------------------
 PostgreSQL 16.1 on x86_64-apple-darwin20.6.0, compiled by Apple clang version 12.0.5 (clang-1205.0.22.9), 64-bit
(1 row)

postgres=# \l
                                        List of databases
      Name        |  Owner   | Encoding | Locale Provider | Collate | Ctype | ICU Locale | ICU Rules |  Access privileges
[------------------+----------+----------+-----------------+---------+-------+------------+-----------+---------------------]
--
 Lecture3          | postgres | UTF8     | libc            | C       | C     |            |           |
 Sample            | postgres | UTF8     | libc            | C       | C     |            |           |
 community_college | postgres | UTF8     | libc            | C       | C     |            |           |
 dvdrental         | postgres | UTF8     | libc            | C       | C     |            |           |
 postgres          | postgres | UTF8     | libc            | C       | C     |            |           |
 template0         | postgres | UTF8     | libc            | C       | C     |            |           | =c/postgres
 +
                   |          |          |                 |         |       |            |           | postgres=CTc/postgre
s
 template1         | postgres | UTF8     | libc            | C       | C     |            |           | =c/postgres
 +
                   |          |          |                 |         |       |            |           | postgres=CTc/postgre
s
(7 rows)

[postgres=# select timeofday();                                                                                        ]
             timeofday
-------------------------------------
 Wed Jan 10 14:14:29.914106 2024 NST
(1 row)

postgres=# █
```