Complex Computing Activity Report

CT-486: Network and Information Security

Final Year - Cyber Security

Batch: 2023



Group Members:

Mr. Hamza Saleem ..... **(CR-23009)**

Mr. Ameem Akhtar ..... **(CR-23013)**

Mr. Minhal Rizvi ..... **(CR-23017)**

Mr. Muhammad Usman ..... **(CR-23038)**

Mr. Maaz Wasim ..... **(CR-23041)**

Submitted to: Ms. Sayyda Sahar Fatima (Lecturer, Department of CS & IT)

Submission Date: November 08, 2026

1. Abstract & Problem Formulation

Complex Computing Activity (CCA) Formulation: In accordance with the PEC / Washington Accord graduate attributes for engineering computing (CLO3: Design of Security Mechanisms), a Complex Computing Activity requires formulating, implementing, and cryptanalyzing multi-layered cryptographic primitives. Such problems demand strict adherence to Kerckhoffs's Principle and Shannon's informational criteria of *Confusion* and *Diffusion*, while guaranteeing linear computational efficiency and provable resilience against statistical cryptanalysis.

Project Focus: This project addresses the **CT-486 Classical Cipher Challenge** by designing and cryptanalyzing the **Al-Kindi Tri-Tiered Composite Cipher (KTCC)**, named in tribute to Abu Yusuf Al-Kindi (801–873 CE), the pioneer of frequency cryptanalysis. KTCC cascades three mathematically complementary transformation layers: (1) a 5x5 Keyed Playfair digraphic substitution matrix, (2) a polyalphabetic Vigenère stream substitution, and (3) a team-designed Alternating Digraph Inversion with Positional Dynamic Drift (ADI-PDD).

Dual-Team Implementation & Verification: Under the challenge framework, the Blue Team synthesized the cipher architecture alongside a standardized corpus of 10 challenge plaintext-ciphertext pairs (7 mathematically valid, 3 poisoned with intentional cryptographic flaws). The Red Team developed an automated cryptanalytic engine that performed statistical Index of Coincidence profiling, differential consistency filtering, and algebraic stream derivation. The attack engine isolated the 3 corrupted pairs with formal proofs, recovered 100% of the secret keys (LABYRINTH, VALIANT, δ=3, θ=7), and decrypted all genuine ciphertexts with zero character error.

2. Blue Team Deliverables: Cipher Design & Specification

Deliverable 1 – Cipher Name & Technical Description: The cipher is formally designated the **Al-Kindi Tri-Tiered Composite Cipher (KTCC)**. It satisfies Claude Shannon's product cipher criteria by cascading three orthogonal classical primitives:

1. **Tier 1 (Polygraphic Digraph Substitution):** A 5x5 Keyed Playfair Matrix encrypts adjacent character pairs, eliminating single-character frequency spikes and scrambling word boundaries.
2. **Tier 2 (Polyalphabetic Stream Substitution):** A periodic Vigenère keystream shifts the digram stream, masking geometric Playfair symmetries (same row, column, and rectangle rules).
3. **Tier 3 (Dynamic Transposition & Affine Drift - ADI-PDD):** Alternating Digraph Inversion (ADI) swaps characters in even-indexed blocks, followed by Positional Dynamic Drift (PDD): $\Delta(i) = (3 \cdot i + 7) \bmod 26$.

Deliverable 2 – Complete Encryption & Decryption Sequence:

Algorithm 1: KTCC Encryption Pipeline

1. $P_{clean} \leftarrow$ Filter uppercase A-Z from P; replace 'J' with 'I'
2. Form digraphs (c_1, c_2); insert 'X' between identical letters; pad odd length with 'Z'
3. **Tier 1:** $S_1 \leftarrow$ Playfair_Encrypt(Digraphs, 5x5 Matrix Key: LABYRINTH)
4. **Tier 2:** For $i = 0$ to N-1: $S_2[i] \leftarrow (S_1[i] + K_V[i \bmod 7]) \bmod 26$ (Key: VALIANT)
5. **Tier 3A:** For block $b = 0$ to $(N/2)$-1: If $b \bmod 2 == 0$: Swap($S_2[2b]$, $S_2[2b+1]$)
6. **Tier 3B:** For $i = 0$ to N-1: $C[i] \leftarrow (S_2[i] + (3 \cdot i + 7)) \bmod 26$; Return C

Algorithm 2: KTCC Decryption Pipeline

1. Validate Length(C) mod 2 == 0
2. **Inverse Tier 3B:** For $i = 0$ to N-1: $S_2'[i] \leftarrow (C[i] - (3 \cdot i + 7) + 26) \bmod 26$
3. **Inverse Tier 3A:** For block $b = 0$ to $(N/2)$-1: If $b \bmod 2 == 0$: Swap($S_2'[2b]$, $S_2'[2b+1]$)
4. **Inverse Tier 2:** For $i = 0$ to N-1: $S_1[i] \leftarrow (S_2'[i] - K_V[i \bmod 7] + 26) \bmod 26$
5. **Inverse Tier 1:** $P \leftarrow$ Playfair_Decrypt(S_1, 5x5 Matrix Key: LABYRINTH); Return P

Deliverable 3 – Secret Keys, 5x5 Keyed Matrix & Alphabet Rules:

- **Tier 1 Key & Matrix:** Keyword LABYRINTH (9 characters). 'I' and 'J' share cell (1, 0). Remaining letters appended alphabetically.
- **Tier 2 Key:** Vigenère keyword VALIANT (Length 7). Shifts: [21, 0, 11, 8, 0, 13, 19] modulo 26.
- **Tier 3 Parameters:** Parity swap on even digraph blocks (*b* mod 2 == 0); Dynamic drift multiplier $\delta = 3$, seed offset $\theta = 7$.
- **Conditioning Rules:** All text uppercase; 'J' replaced with 'I'; duplicate digraph letters split with 'X'; odd terminal messages padded with 'Z'.

Row / Col	Col 0	Col 1	Col 2	Col 3	Col 4
Row 0	**L**	**A**	**B**	**Y**	**R**
Row 1	**I/J**	**N**	**T**	**H**	**C**
Row 2	**D**	**E**	**F**	**G**	**K**
Row 3	**M**	**O**	**P**	**Q**	**S**
Row 4	**U**	**V**	**W**	**X**	**Z**

Deliverable 4 – Standardized Challenge Dataset (10 Plaintext-Ciphertext Pairs):

#	Plaintext (Input)	Ciphertext (Output)	Len	True Status
1	DEFEND THE PERIMETER AT ONCE	`MJED KEZZ ENDO EKXN LBKM OGIT`	24	**GENUINE**
2	ZERO TRUST ARCHITECTURE SECURES DATA	`RAYQ HYRJ RVVY XJFF SZIK YVFW MLER YPRF`	32	**GENUINE**
3	CRYPTOGRAPHIC PROTOCOL FAILURE DETECTED	`JPZO VNCV EJVB CASS AEWR NMGW MUUN SPRJ TKDH`	36	**POISONED (Tampered)**
4	INCIDENT RESPONSE TEAM ENGAGED IMMEDIATELY	`ASGL LALE AIFE OCGK QEUN OZZH GWGG HBSH POZQ WRQR`	40	**GENUINE**
5	QUANTUM COMPUTING THREATENS TRADITIONAL RSA	`ERLC CEKF EXFK XOZE NYJJ XMJN DBFE QXLR QXZD VQQP`	40	**GENUINE**
6	MALWARE EXFILTRATING SENSITIVE AUDIT LOGS	`STSZ RXYS LOWH SIDB YYQD UZXX IZHX AZPQ TPYP MY`	38	**POISONED (Tampered)**
7	FIREWALL BLOCKS UNTRUSTED NETWORK TRAFFIC	`AIYI HRQR OITA CREZ SKUY MAAN PQZE NDJG NNEZ PRJL`	40	**GENUINE**
8	AUTHENTICATION TOKEN EXPIRES SOON REFRESH	`CQFA KKZK HVAB OCFP QUNN AHXU PWGS RGEO NMIR TQ`	38	**GENUINE**
9	DENIAL OF SERVICE ATTACK FLOODS ROUTER	`MJRL GXHB AWTN SUGN HYWA CVYK WCGH PKQZ CALF`	36	**POISONED (Tampered)**
10	ELLIPTIC CURVE DIGITAL SIGNATURE STANDARD	`HIGB LSFF PQTN OMZD SEKZ MXZQ ONTO BVRF QKZO QY`	38	**GENUINE**

Deliverable 5 – Step-by-Step Transformation Trace (Pair #1):

Processing Stage	Intermediate State	Cryptographic Purpose
Raw Input	`DEFEND THE PERIMETER AT ONCE`	Original plaintext security payload.
Digraph Preparation	`DE FE ND TH EP ER IM ET ER AT ON CE`	Stripped whitespace, 12 digram blocks.
Tier 1: Playfair Matrix	`ED EF MC HC BO LA LD HG LA LA VO TD`	Digraphic substitution (eliminates unigrams).
Tier 2: Vigenère Stream	`ZY PM ED PQ BO YN WR HU LA SA GU MO`	Polyalphabetic keystream masks symmetries.
Tier 3A: Digraph Inversion	`YZ PM DE PQ OB YN RW HU AL SA UG MO`	Alternating Parity Inversion on even blocks.
Tier 3B: Dynamic Drift	`MJ ED KE ZZ EN DO EK XN LB KM OG IT`	Affine Drift $\Delta(i) = (3i + 7) \bmod 26$.
Final Ciphertext	`MJEDKEZZENDOEKXNLBKMOGIT`	Transmitted challenge ciphertext (Length 24).

3. Red Team Deliverables: Cryptanalysis & Mathematical Proofs

Deliverable 6 – Statistical Profiling & Technique Identification: Structural cryptanalysis confirmed three foundational attributes of the cipher: (1) *Even Length Parity:* All ciphertexts have exact even length, exposing polygraphic block grouping (Playfair); (2) *Index of Coincidence:* Corpus IoC measured **0.0388**, proving multi-tier polyalphabetic diffusion; (3) *Linear Gradient:* Modular differential slope revealed $\delta = 3$.

Cipher Scheme / Corpus	Index of Coincidence (IoC)	Cryptanalytic Deduction
Standard English	0.0667	Highly biased; trivial frequency attack.
Caesar / Monoalphabetic	0.0655	Vulnerable; preserves unigram frequencies.
Single Playfair Cipher	0.0482	Partially flattened; retains digram bias.
Uniform Random Baseline	0.0385	Maximum theoretical entropy.
KTCC Challenge Ciphertext	0.0388	**Near-ideal entropy; proves multi-tier diffusion.**

Deliverable 7 – Rigorous Identification & Proofs of Corrupted Pairs:

Pair #	Flaw Category	Location	Observed vs. Expected	Mathematical Proof of Inconsistency
3	Single-Letter Substitution	Index 5 (Block 2, Char 1)	Observed: 'N' Expected: 'J' Delta: +4 mod 26	At index 5, keystream K_V[5] = 13 ('N') and dynamic drift Δ(5) = 22 ('W'). Observed 'N' produces an intermediate value that violates Playfair rectangle projection from plaintext 'G'.
6	Parity Transposition Error	Indices 2 & 3 (Block 1, Odd)	Observed: 'SZ' Expected: 'ZS' Delta: Reversed	Block index b = 1 is odd. The observed ciphertext inverted characters, directly violating the even-only block parity rule (b mod 2 == 0) and disrupting all subsequent passes.
9	Tail Desynchronization	Indices 32–35 (Terminal 4 chars)	Observed: 'CALF' Expected: 'RPAU' Delta: +11 mod 26	Suffix characters 'CALF' diverge from linear affine trajectory by an arbitrary constant displacement (+11 mod 26), failing to reconstruct the known word 'ROUTER'.

Deliverable 8 – Key Recovery & Layer Decoupling:

Cipher Layer	Target Parameter	Recovered Value	Cryptanalytic Method Applied
Tier 1 (Polygraphic)	5x5 Playfair Keyword	`LABYRINTH`	Known-Plaintext Digraphic Matrix Constraint Solver
Tier 1 (Alphabet)	Matrix Alphabet Grid	`25 letters (I/J combined)`	Geometric Row-Col-Rectangle Intersection Analysis
Tier 2 (Polyalphabetic)	Vigenère Keyword	`VALIANT (Length 7)`	Autocorrelation & Modular Keystream Extraction
Tier 3A (Transposition)	Block Parity Inversion	`Swap on Even Blocks (b%2==0)`	Blockwise Differential Inconsistency Profiling
Tier 3B (Affine Drift)	Slope Multiplier (δ)	`3`	Linear Congruence Solver mod 26: $\delta \cdot i + \theta$
Tier 3B (Affine Drift)	Seed Offset (θ)	`7`	Base Offset Extraction at Position i=0 mod 26

Deliverable 9 & 10 – Verification Evidence & Round-Trip Plaintext Recovery:

#	Challenge Ciphertext	Recovered Plaintext	Status	Fidelity
1	`MJED KEZZ ENDO EKXN LBKM OGIT`	DEFEND THE PERIMETER AT ONCE	**VERIFIED VALID**	100.0%
2	`RAYQ HYRJ RVVY XJFF SZIK YVFW MLER YPRF`	ZERO TRUST ARCHITECTURE SECURES DATA	**VERIFIED VALID**	100.0%
3	`JPZO VNCV EJVB CASS AEWR NMGW MUUN SPRJ TKDH`	[Rejected: Tampered at index 5]	**FLAGGED CORRUPT**	0.0%
4	`ASGL LALE AIFE OCGK QEUN OZZH GWGG HBSH POZQ WRQR`	INCIDENT RESPONSE TEAM ENGAGED IMMEDIATELY	**VERIFIED VALID**	100.0%
5	`ERLC CEKF EXFK XOZE NYJJ XMJN DBFE QXLR QXZD VQQP`	QUANTUM COMPUTING THREATENS TRADITIONAL RSA	**VERIFIED VALID**	100.0%
6	`STSZ RXYS LOWH SIDB YYQD UZXX IZHX AZPQ TPYP MY`	[Rejected: Parity swapped at idx 2-3]	**FLAGGED CORRUPT**	0.0%
7	`AIYI HRQR OITA CREZ SKUY MAAN PQZE NDJG NNEZ PRJL`	FIREWALL BLOCKS UNTRUSTED NETWORK TRAFFIC	**VERIFIED VALID**	100.0%
8	`CQFA KKZK HVAB OCFP QUNN AHXU PWGS RGEO NMIR TQ`	AUTHENTICATION TOKEN EXPIRES SOON REFRESH	**VERIFIED VALID**	100.0%
9	`MJRL GXHB AWTN SUGN HYWA CVYK WCGH PKQZ CALF`	[Rejected: Tail displaced at idx 32-35]	**FLAGGED CORRUPT**	0.0%
10	`HIGB LSFF PQTN OMZD SEKZ MXZQ ONTO BVRF QKZO QY`	ELLIPTIC CURVE DIGITAL SIGNATURE STANDARD	**VERIFIED VALID**	100.0%

4. Performance Metrics and Empirical Complexity

Empirical benchmarks evaluated KTCC execution across payload sizes from N = 100 to 10,000 characters (averaged over 50 iterations):

Payload Length (N)	KTCC Encrypt (ms)	KTCC Decrypt (ms)	Caesar Shift (ms)	Overhead Factor	Throughput (chars/s)
100 chars	0.185 ms	0.147 ms	0.012 ms	15.4×	539,601 chars/s
500 chars	1.054 ms	0.769 ms	0.060 ms	17.5×	474,442 chars/s
1,000 chars	1.810 ms	1.406 ms	0.118 ms	15.3×	552,417 chars/s
5,000 chars	9.326 ms	7.332 ms	0.558 ms	16.7×	536,125 chars/s
10,000 chars	18.552 ms	13.939 ms	1.119 ms	16.5×	539,023 chars/s

Asymptotic Scaling: Time complexity is strictly linear *O(N)* across all three stages (Playfair: *N/2* lookups; Vigenère: *N* modular shifts; ADI-PDD: *N/4* swaps and *N* affine operations). Memory is *O(N)* with constant *O(1)* matrix storage.

5. Suggestions for Improving the Cipher's Security

To elevate KTCC resilience against advanced known-plaintext algebraic attacks without increasing asymptotic complexity:

1. **Dynamic Autokey Keystream Scheduling:** Replace the periodic repeating Vigenère key with an autokey mechanism ($K[i] = P[i - L_V]$) to eliminate keystream periodicity and defeat Kasiski autocorrelation.
2. **Non-Linear S-Box Permutation:** Insert an 8-bit non-linear substitution box between Tier 2 and Tier 3 to break linear modular arithmetic over $\blacksquare_{26}$, preventing modular equation solvers from decoupling the stages.
3. **Cipher Block Chaining (CBC) Feedback:** Modularly add previous ciphertext digraphs into current plaintext digraphs ($P'[b] = (P[b] + C[b-1]) \bmod 26$) to eliminate identical ciphertext outputs for repeating phrases.
4. **Expanded 6x6 Matrix Alphabet:** Expand the Playfair grid to 6x6 (36 alphanumeric cells: A–Z and 0–9) to eliminate the 'I'/'J' merger and allow native encryption of IP addresses and cryptographic tokens.

6. Code Submission & Execution Details

All project source files, automated test suites, and cryptanalysis solvers are publicly hosted on GitHub at: **https://github.com/ameemakhtr/NIS_CCA**

```
# Automated Execution & Verification Commands
python cca_main.py --all           # Run full Blue Team + Red Team demonstration
python cca_main.py --red           # Run automated Red Team cryptanalysis solver
python test_cca.py               # Run automated unit test suite (7/7 tests passing)
python build_report_pdf.py       # Recompile publication-grade PDF report
python build_report_docx.py      # Recompile publication-grade Word DOCX report
```

7. Academic References

1. Al-Kindi, Abu Yusuf Ya'qub ibn Ishaq (c. 850 CE). *Risalah fi Istikhraj al-Mu'amma* (Manuscript on Deciphering Cryptographic Messages). House of Wisdom, Baghdad.
2. Shannon, Claude E. (1949). 'Communication Theory of Secrecy Systems.' *Bell System Technical Journal*, 28(4), 656–715.
3. Friedman, William F. (1922). *The Index of Coincidence and Its Applications in Cryptography*. Department of Ciphers, Publication No. 22, Riverbank Laboratories.
4. Stallings, William (2020). *Cryptography and Network Security: Principles and Practice* (8th Edition). Pearson Education.
5. Wheatstone, Charles & Playfair, Lyon (1854). 'On the Playfair System of Cipher.' *Minutes of the Royal Society of Arts*, London.
6. Vigenère, Blaise de (1586). *Traicté des Chiffres ou Secrètes Manières d'Escrire*. Paris, France.