AMENDMENT NO. 2 JUNE 2021

TO

IS 17150 : 2019 MINI DOMESTIC WATER HEATER FOR USE WITH PIPED NATURAL GAS (PNG) — SPECIFICATION

(*Page* 2, *clause* **5.3**) — Substitute the following for the existing clause:

'Non-metallic materials normally in contact with the gas shall not change in weight or volume by more than 15 percent after being immersed in pentane or PNG for 72 h at room temperature, when tested according to Annex A.'

(*Page* 4, *clause* **18**) — Substitute the following for the existing clause:

'With the taps fully opened and with the burners operating at the maximum consumption, the appliance shall give within ± 8 percent of the manufacturer's recommended gas consumption in l/h or heat input in kcal/h at 21 mbar (21.41 gf/cm^2) gas inlet pressure, the flow through the injector jet at 21 mbar (21.41 gf/cm^2) shall be measured with a wet gas meter using compressed air (free from oil/impurities) and converted the same at STP (27°C and 100 kN/m^2). Thereafter using 1.43 as multiplying factor, the value of air flow at STP so obtained to be converted to flow of PNG at STP.

NOTE:

1 For guidance 1 Litre = 0.001 cubic meter.

2 Compressed air shall be stored in a reservoir tank for 1 h between 25 to 30°C before starting the test'.

(MED 23)

Publication Unit, BIS, New Delhi, India