

Requirement Analysis

Solution Requirements (Functional and Non-functional)

Date	02 October 2026
Team ID	SWTID-2026-9494
Project Name	Script-Controlled ACL – Restrict Record Access Based on Custom Script
Maximum Marks	5 Marks

Functional requirements

FR No.	Functional requirement (Epic)	Sub requirement (Story / Sub-task)
FR-1	User and role management	Create users; create roles u_record_admin and u_record_user; assign roles to users.
FR-2	Data model	Create the Confidential Record table with name, department, status, confidential flag and owner fields.
FR-3	READ access control	Admin reads all; owner reads own; users read non-confidential only; others none.
FR-4	CREATE access control	Only users holding u_record_admin or u_record_user can create records.
FR-5	WRITE access control	Admin edits all; owner edits own record until it is Closed; others read-only.
FR-6	DELETE access control	Only the administrator role can delete records.
FR-7	Verification	Impersonate every user and confirm each operation behaves as designed.

Non-functional requirements

NFR No.	Non-functional requirement	Description
NFR-1	Usability	Denied actions must hide or lock UI elements instead of showing errors wherever possible.
NFR-2	Security	Access decisions are made on the server; the default for any unmatched case is deny.
NFR-3	Reliability	The ACL script must always return a value for <i>answer</i> (true or false) without runtime errors.
NFR-4	Performance	Scripts avoid database queries so list loading is not slowed.
NFR-5	Availability	Runs on the ServiceNow cloud instance; availability follows the platform.
NFR-6	Scalability	Rules apply to any number of records and users without code changes.