

STM32CubeMX Untitled* - STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx Untitled - Pinout & Configuration GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Categories A-Z

- System Core
- Analog
- Timers
- Connectivity
 - CAN
 - I2C1
 - I2C2**
 - SP1
 - SP2
 - USART1
 - USART2
 - USART3
 - USB
- Computing
- Middleware and Software Packs

I2C2 Mode and Configuration

Mode

I2C I2C

Configuration

Reset Configuration

- NVIC Settings
- DMA Settings
- GPIO Settings
- Parameter Settings**
- User Constants

Configure the below parameters:

Search (Ctrl+F)

Master Features

- I2C Speed Mode Standard Mode
- I2C Clock Speed (Hz) 100000

Slave Features

- Clock No Stretch Mode Disabled
- Primary Address Length selection 7-bit
- Dual Address Acknowledged Disabled

Pinout view System view

Pinout view

System view

STM32F103C8Tx LQFP48

23°C Mostly clear

Search

ENG 10:21 PM 7/2/2026

STM32CubeMX Untitled*: STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx Untitled - Pinout & Configuration GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Categories A-Z

- System Core
- Analog
- Timers
 - RTC
 - TIM1
 - TIM2
 - TIM3**
 - TIM4
- Connectivity
- Computing
- Middleware and Software Packs

TIM3 Mode and Configuration

Mode

Slave Mode **Disable**

Trigger Source **Disable**

☒ Internal Clock

Channel1 **Disable**

Channel2 **Disable**

Channel3 **Disable**

Channel4 **Disable**

Combined Channels **Disable**

☐ XOR activation

☐ One Pulse Mode

Configuration

Reset Configuration

User Constants NVIC Settings DMA Settings

Parameter Settings

Configure the below parameters:

Search (Ctrl+F)

Counter Settings

Prescaler (PSC - 16 bits value) 7199

Counter Mode Up

Counter Period (AutoReload Regis. 4999

Internal Clock Division (CKD) **No Division**

auto-reload preload Disable

Trioser Output (TRGO) Parameters

Pinout view System view

STM32F103C8Tx LQFP48

Pinout diagram showing the chip and its pins.

23°C Mostly clear

Search

ENG 10:23 PM 7/2/2026

STM32CubeMX Untitled* - STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx Untitled - Pinout & Configuration GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Categories A-Z

- System Core
- Analog
- Timers
 - RTC
 - TIM1
 - TIM2
 - TIM3**
 - TIM4
- Connectivity
- Computing
- Middleware and Software Packs

TIM3 Mode and Configuration

Mode

Slave Mode

Trigger Source

☒ Internal Clock

Channel1

Channel2

Channel3

Channel4

Combined Channels

☐ XOR activation

☐ One Pulse Mode

Configuration

Reset Configuration

User Constants NVIC Settings DMA Settings

Parameter Settings

NVIC Interrupt Table	Enabled	Preemption Priority	Sub Priority
TIM3 global interrupt	☒	0	0

Pinout view System view

23°C Mostly clear

Search

ENG 10:24 PM 7/2/2026

STM32CubeMX Untitled*- STM32F103C8Tx

STM32CubeMX

FileWindowHelp

myST

100

f

YouTube

X

GitHub

ST

HomeSTM32F103C8TxUntitled - Pinout & ConfigurationGENERATE CODE

Pinout & Configuration

Clock Configuration

Project Manager

Tools

CategoriesA-Z

System Core

DMA

GPIO

NVIC

RCC

SYS

WWDG

Analog

Timers

Connectivity

Computing

Middleware and Software Packs

Configuration

Group By Peripherals

GPIO

I2C

Search Signals

Search (Ctrl+F)

Show only Modified Pins

Pin N°	Signal on	GPIO out	GPIO mo	GPIO Pul	Maximum	User Label	Modified
PA0-WK...	n/a	n/a	Input mode	Pull-up	n/a		☒
PA1	n/a	n/a	Input mode	Pull-up	n/a		☒
PA2	n/a	n/a	Input mode	Pull-up	n/a		☒
PA3	n/a	Low	Output P...	No pull-u...	Low		☐

PA2 Configuration :

GPIO mode

Input mode

GPIO Pull-up/Pull-down

Pull-up

User Label

Pinout view

System view

Pinout view

System view

23°C

Mostly clear

Search

ENG

10:25 PM

7/2/2026

STM32CubeMX LabHomeworkIoc*: STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx LabHomeworkIoc - Pinout & Configuration GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Software Packs Pinout

RCC Mode and Configuration

Mode

High Speed Clock (HSE) Crystal/Ceramic Resonator

Low Speed Clock (LSE) Disable

☐ Master Clock Output

Configuration

Reset Configuration

User Constants NVIC Settings GPIO Settings

Parameter Settings

Configure the below parameters:

Search (Ctrl+F)

System Parameters

VDD voltage (V) 3.3 V

Prefetch Buffer Enabled

Flash Latency (WS) 0 WS (1 CPU cycle)

RCC Parameters

HSI Calibration Value 16

HSE Startuo Timeout Value (ms) 100

Pinout view System view

Pinout view

STM32F103C8Tx LQFP48

Pinout diagram showing the chip and its connections.

22°C Mostly clear

Search

10:59 PM 7/2/2026

STM32CubeMX LabHomeworkIoc*: STM32F103C8Tx

File Window Help myST

Home STM32F103C8Tx LabHomeworkIoc - Pinout & Configuration GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Categories A-Z

System Core

- DMA
- GPIO
- IWDG
- NVIC
- ✓ RCC
- ▲ SYS
- WWDG

Analog >

Timers >

Connectivity >

Computing >

Middleware and Software Packs >

SYS Mode and Configuration

Mode

Debug Serial Wire

System Wake-Up

Timebase Source SysTick

Configuration

Warning: This peripheral has no parameters to be configured.

Pinout view System view

STM32F103C8Tx LQFP48

Pinout diagram showing various pins and their connections.

22°C Mostly clear 10:59 PM 7/2/2026

