RAJALAKSHMI ENGINEERING COLLEGE

Ameera Fathima M 250701048-2025-CSE

A2

Started on	Wednesday, 19 August 2026, 8:32 AM
State	Finished
Completed on	Wednesday, 19 August 2026, 8:47 AM
Time taken	14 mins 55 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int majorityElement(int *nums, int n) {
    int candidate = 0, count = 0;

    for (int i = 0; i < n; i++) {
        if (count == 0) {
            candidate = nums[i];
            count = 1;
        } else if (nums[i] == candidate) {
            count++;
        } else {
            count--;
        }
    }
    return candidate;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) {
        return 0; // Invalid input, exit silently
    }

    int *nums = malloc(n * sizeof(int));
    if (!nums) return 0; // Memory allocation failed

    for (int i = 0; i < n; i++) {
        if (scanf("%d", &nums[i]) != 1) {
            free(nums);
            return 0; // Invalid input
        }
    }
```

```
35
36      printf("%d\n", majorityElement(nums, n));
37
38      free(nums);
39      return 0;
40  }
41
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course