Status	Finished
Started	Sunday, 25 October 2026, 11:38 AM
Completed	Sunday, 25 October 2026, 11:42 AM
Duration	3 mins 21 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write_list()
b. write()
c. writelines() ✓
d. write_all()

The correct answer is: writelines()

Question **2**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

a. read(1)
b. readline() ✓
c. line()
d. readlines(1)

The correct answer is: readline()

Question **3**

Correct

Mark 1.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Appends to an existing file

b. Opens an existing file in read mode

c. Opens a file in binary mode

d. Creates a new file for writing ✓

The correct answer is: Creates a new file for writing

Question **4**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Binary

b. Write

c. Read ✓

d. Append

The correct answer is: Read

Question **5**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It does nothing

b. It raises an error

c. It appends data to the file

d. It clears the old data and starts fresh ✓

The correct answer is: It clears the old data and starts fresh

Question **6**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of single characters

b. str

c. a list of lines ✓

d. a list of integers

The correct answer is:
a list of lines

Question **7**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters behind from the current position

b. move the file pointer to beginning of the file

c. move the file pointer five characters ahead from the current position ✓

d. moves the file pointer to the end of a file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **8**

Correct

Mark 1.00 out of 1.00

How can you read a file line by line efficiently in Python?

a. Using the readline() method

b. Using a for loop ✓

c. Using the readlines() method

d. Using the read() method

The correct answer is: Using a for loop

Question **9**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

- True ✓
- False

The correct answer is 'True'.

Question **10**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

a. Prints the first 10 characters of the file

b. Prints the entire content of the file ✓

c. Prints an error message

d. Prints each line of the file

The correct answer is: Prints the entire content of the file

Question **11**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

a. To read data from a file

b. To automatically close the file after its suite finishes ✓

c. To delete a file

d. To write data to a file

The correct answer is: To automatically close the file after its suite finishes

Question **12**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

- a. The buffer size for the file operations ✓
- b. The encoding of the file
- c. The file's read/write position
- d. The access mode of the file

The correct answer is: The buffer size for the file operations

Question **13**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

- a. write() ✓
- b. append()
- c. insert()
- d. read()

The correct answer is: write()

Question **14**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

- a. The buffer size
- b. The encoding format of the file ✓
- c. The size of the file
- d. The mode of the file

The correct answer is: The encoding format of the file

Question **15**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. ftell()
b. tell()
c. seek() ✓
d. fseek()

The correct answer is: seek()