

# Unbalanced multisection in the stochastic block model

Amelia Perry (MIT)

Joint work with Alex Wein (MIT)

3 July 2017

# Community detection in networks

**Goal:** find subsets of more tightly interconnected nodes in a graph

# Community detection in networks

**Goal:** find subsets of more tightly interconnected nodes in a graph

- e.g. finding social communities in Facebook

# Community detection in networks

**Goal:** find subsets of more tightly interconnected nodes in a graph

- e.g. finding social communities in Facebook
- e.g. finding biological subsystems in protein–protein interaction nets

# Community detection in networks

**Goal:** find subsets of more tightly interconnected nodes in a graph

- e.g. finding social communities in Facebook
- e.g. finding biological subsystems in protein–protein interaction nets
- In general, the analogue of clustering for network data.

# Community detection in networks

**Goal:** find subsets of more tightly interconnected nodes in a graph

- e.g. finding social communities in Facebook
- e.g. finding biological subsystems in protein–protein interaction nets
- In general, the analogue of clustering for network data.

**This talk:** a robust, statistically strong, poly-time algorithm to find communities.


## Stochastic block model (Holland et al. 1983)

Generative model for graphs with community structure, studied in statistics, information theory, computer science, statistical physics. . .

# Stochastic block model (Holland et al. 1983)

Generative model for graphs with community structure, studied in statistics, information theory, computer science, statistical physics. . .

- $n$  vertices partitioned into  $k$  'communities'






# Stochastic block model (Holland et al. 1983)

Generative model for graphs with community structure, studied in statistics, information theory, computer science, statistical physics. . .

- $n$  vertices partitioned into  $k$  'communities'
- Edges drawn independently with probabilities  $p > q$




# Stochastic block model (Holland et al. 1983)

Generative model for graphs with community structure, studied in statistics, information theory, computer science, statistical physics. . .

- $n$  vertices partitioned into  $k$  'communities'
- Edges drawn independently with probabilities  $p > q$

**Goal:** recover the planted communities (exactly or approximately)



# Many algorithmic approaches

- Girvan–Newman modularity [GN02]

# Many algorithmic approaches

- Girvan–Newman modularity [GN02]
- Spectral clustering [Bop87, McS01, RCY11, AS15]

# Many algorithmic approaches

- Girvan–Newman modularity [GN02]
- Spectral clustering [Bop87, McS01, RCY11, AS15]
- Belief propagation [DMKZ11, MNS14]

# Many algorithmic approaches

- Girvan–Newman modularity [GN02]
- Spectral clustering [Bop87, McS01, RCY11, AS15]
- Belief propagation [DMKZ11, MNS14]
- Semidefinite programming [GW94, ABH14, HWX15, ABKK15]

# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

Denser regime

$$p = a \log n / n, \quad q = b \log n / n.$$

# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

Denser regime

$p = a \log n / n$ ,  $q = b \log n / n$ .

Average degree is order  $\log n$ .



# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

## Denser regime

$p = a \log n/n$ ,  $q = b \log n/n$ .

Average degree is order  $\log n$ .

**Theorem** [ABH14, MNS14, HWX15] With equal-size communities, exact recovery is possible iff

$$\sqrt{a} - \sqrt{b} \geq \sqrt{k}.$$

# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

## Denser regime

$p = a \log n/n$ ,  $q = b \log n/n$ .

Average degree is order  $\log n$ .

**Theorem** [ABH14, MNS14, HWX15] With equal-size communities, exact recovery is possible iff

$$\sqrt{a} - \sqrt{b} \geq \sqrt{k}.$$

## Sparser regime

# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

## Denser regime

$$p = a \log n / n, \quad q = b \log n / n.$$

Average degree is order  $\log n$ .

**Theorem** [ABH14, MNS14, HWX15] With equal-size communities, exact recovery is possible iff

$$\sqrt{a} - \sqrt{b} \geq \sqrt{k}.$$

## Sparser regime

$$p = a / n, \quad q = b / n.$$

# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

## Denser regime

$p = a \log n / n$ ,  $q = b \log n / n$ .  
Average degree is order  $\log n$ .

**Theorem** [ABH14, MNS14, HWX15] With equal-size communities, exact recovery is possible iff

$$\sqrt{a} - \sqrt{b} \geq \sqrt{k}.$$

## Sparser regime

$p = a / n$ ,  $q = b / n$ .  
Average degree is constant.

# Sharp thresholds

$n$  — number of vertices  
 $k$  — number of communities  
 $p$  — internal edge probability  
 $q$  — external edge probability

## Denser regime

$p = a \log n/n$ ,  $q = b \log n/n$ .  
Average degree is order  $\log n$ .

**Theorem** [ABH14, MNS14, HWX15] With equal-size communities, exact recovery is possible iff

$$\sqrt{a} - \sqrt{b} \geq \sqrt{k}.$$

## Sparser regime

$p = a/n$ ,  $q = b/n$ .  
Average degree is constant.

**Theorem** [ABH14, MNS14, HWX15] With **two** equal-size communities, partial recovery is possible iff

$$(a - b)^2 > 2(a + b).$$

# Robustness to model misspecification

- Many papers prove that with high probability, some chosen algorithm recovers the communities.

# Robustness to model misspecification

- Many papers prove that with high probability, some chosen algorithm recovers the communities.
- But many of these algorithms fail on real-world data, and even on tiny modifications of the SBM!

# Robustness to model misspecification

- Many papers prove that with high probability, some chosen algorithm recovers the communities.
- But many of these algorithms fail on real-world data, and even on tiny modifications of the SBM!
- [RJM16]: planting **just a few tetrahedra** into a large SBM graph causes spectral clustering to fail.



# Robustness to model misspecification

- Many papers prove that with high probability, some chosen algorithm recovers the communities.
- But many of these algorithms fail on real-world data, and even on tiny modifications of the SBM!
- [RJM16]: planting **just a few tetrahedra** into a large SBM graph causes spectral clustering to fail.
- **Q:** How do we design algorithms that transfer to e.g. power-law graphs and many other models? Algorithms that are robust to model misspecification?

# Semirandom models


Models between average-case (generative) and worst-case.

# Semirandom models

Models between average-case (generative) and worst-case.

For SBM: [FK00]

- Draw a graph from the usual SBM




# Semirandom models

Models between average-case (generative) and worst-case.

For SBM: [FK00]

- Draw a graph from the usual SBM
- An adversary may perform any number of **monotone** ('helpful') changes:
  - add edges within communities
  - remove edges within communities




# Semirandom models

Models between average-case (generative) and worst-case.

For SBM: [FK00]

- Draw a graph from the usual SBM
- An adversary may perform any number of **monotone** ('helpful') changes:
  - add edges within communities
  - remove edges within communities




# Semirandom models

Models between average-case (generative) and worst-case.

For SBM: [FK00]

- Draw a graph from the usual SBM
- An adversary may perform any number of **monotone** ('helpful') changes:
  - add edges within communities
  - remove edges within communities




# Semirandom models

Models between average-case (generative) and worst-case.

For SBM: [FK00]

- Draw a graph from the usual SBM
- An adversary may perform any number of **monotone** ('helpful') changes:
  - add edges within communities
  - remove edges within communities




# Semirandom models

Models between average-case (generative) and worst-case.

For SBM: [FK00]

- Draw a graph from the usual SBM
- An adversary may perform any number of **monotone** ('helpful') changes:
  - add edges within communities
  - remove edges within communities
- Prevents algorithms from over-tuning to specific model statistics (degree distribution, spectrum, etc.)





## SDPs are robust [FK00]

Convex programs such as SDPs tend to be **robust to monotone changes**: if they succeeded before the changes then they still succeed afterward.

## SDPs are robust [FK00]

Convex programs such as SDPs tend to be **robust to monotone changes**: if they succeeded before the changes then they still succeed afterward.

**Reason:** under a monotone change, the true SDP solution increases in value more than any other feasible solution.

## SDPs are robust [FK00]

Convex programs such as SDPs tend to be **robust to monotone changes**: if they succeeded before the changes then they still succeed afterward.

**Reason:** under a monotone change, the true SDP solution increases in value more than any other feasible solution.

If the true solution was optimal before the change, it remains optimal afterward.

## Our convex program

$$\begin{aligned} \max \quad & \langle A, X \rangle - \omega \langle \mathbf{1}\mathbf{1}^\top, X \rangle \\ \text{s.t.} \quad & \forall u \quad X_{uu} = 1, \\ & \forall u, v \quad X_{uv} \geq \frac{-1}{k-1}, \\ & X \succeq 0. \end{aligned}$$

## Our convex program

$$\begin{aligned} \max \quad & \langle A, X \rangle - \omega \langle \mathbf{1}\mathbf{1}^\top, X \rangle \\ \text{s.t.} \quad & \forall u \quad X_{uu} = 1, \\ & \forall u, v \quad X_{uv} \geq \frac{-1}{k-1}, \\ & X \succeq 0. \end{aligned}$$

- First suggested for the SBM in [ABKK15], based on classical multicut SDPs [FJ94].

## Our convex program

$$\begin{aligned} \max \quad & \langle A, X \rangle - \omega \langle \mathbf{1}\mathbf{1}^\top, X \rangle \\ \text{s.t.} \quad & \forall u \quad X_{uu} = 1, \\ & \forall u, v \quad X_{uv} \geq \frac{-1}{k-1}, \\ & X \succeq 0. \end{aligned}$$

- First suggested for the SBM in [ABKK15], based on classical multicut SDPs [FJ94].
- We analyze this program on the SBM.

# Our convex program

$$\begin{aligned} \max \quad & \langle A, X \rangle - \omega \langle \mathbf{1}\mathbf{1}^\top, X \rangle \\ \text{s.t.} \quad & \forall u \quad X_{uu} = 1, \\ & \forall u, v \quad X_{uv} \geq \frac{-1}{k-1}, \\ & X \succeq 0. \end{aligned}$$

- First suggested for the SBM in [ABKK15], based on classical multicut SDPs [FJ94].
- We analyze this program on the SBM.
- Allows  $k$  communities of different sizes.

## Our convex program

$$\begin{aligned} \max \quad & \langle A, X \rangle - \omega \langle \mathbf{1}\mathbf{1}^\top, X \rangle \\ \text{s.t.} \quad & \forall u \quad X_{uu} = 1, \\ & \forall u, v \quad X_{uv} \geq \frac{-1}{k-1}, \\ & X \succeq 0. \end{aligned}$$

- First suggested for the SBM in [ABKK15], based on classical multicut SDPs [FJ94].
- We analyze this program on the SBM.
- Allows  $k$  communities of different sizes.
- The [hyperparameter](#)  $\omega$  is necessary for a robust algorithm.



# Main theorem

**Theorem:** our SDP achieves exact recovery w.h.p., and is robust to monotone changes, for all  $a, b, k$  and all community proportions for which the problem is statistically possible as  $n \rightarrow \infty$ .

# Main theorem

**Theorem:** our SDP achieves exact recovery w.h.p., and is robust to monotone changes, for all  $a, b, k$  and all community proportions for which the problem is statistically possible as  $n \rightarrow \infty$ .

Depends on roughly the right choice of  $\omega \approx \frac{a-b}{\log a - \log b} \frac{\log n}{n}$ .

# Conclusion

- When tuning heavily to specific generative models, we should care about robustness to model misspecification.

# Conclusion

- When tuning heavily to specific generative models, we should care about robustness to model misspecification.
- Robustness is achievable: convex programming.

# Conclusion

- When tuning heavily to specific generative models, we should care about robustness to model misspecification.
- Robustness is achievable: convex programming.
- **Open:** can we find cheaper algorithms with similar robustness guarantees?

# Conclusion

- When tuning heavily to specific generative models, we should care about robustness to model misspecification.
- Robustness is achievable: convex programming.
- **Open:** can we find cheaper algorithms with similar robustness guarantees?

Thanks for listening! Any questions?