

# データベース課題

## 課題1

```
insert into profiles() values(1,'田中実','012-345-6789',30,'1994-02-01');  
insert into profiles() values(2,'鈴木茂','090-1122-3344',37,'1987-08-12');  
insert into profiles() values(3,'鈴木実','080-5566-7788',24,'2000-12-24');  
insert into profiles() values(4,'佐藤清','012-0987-6543',19,'2005-08-01');  
insert into profiles() values(5,'高橋清','090-9900-1234',24,'2000-12-24');
```

```
mysql> select * from profiles;
```

profilesID	name	tell	age	birthday
1	田中実	012-345-6789	30	1994-02-01
2	鈴木茂	090-1122-3344	37	1987-08-12
3	鈴木実	080-5566-7788	24	2000-12-24
4	佐藤清	012-0987-6543	19	2005-08-01
5	高橋清	090-9900-1234	24	2000-12-24

```
5 rows in set (0.03 sec)
```

## 課題2

select \* from profiles where(profilesID=3);

```
[mysql> select * from profiles where(profilesID=3);
```

profilesID	name	tell	age	birthday
3	鈴木実	080-5566-7788	24	2000-12-24

```
1 row in set (0.01 sec)
```

### 課題3

mysql> select \* from profiles where(name='高橋清');

```
[mysql> select * from profiles where(name='高橋清');
```

profilesID	name	tell	age	birthday
5	高橋清	090-9900-1234	24	2000-12-24

1 row in set (0.01 sec)

#### 課題4

mysql> select \* from profiles where(age=24);

```
[mysql> select * from profiles where(age=24);
```

profilesID	name	tell	age	birthday
3	鈴木実	080-5566-7788	24	2000-12-24
5	高橋清	090-9900-1234	24	2000-12-24

2 rows in set (0.00 sec)

## 課題5

```
mysql> select * from profiles where(age>25);
```

```
[mysql> select * from profiles where(age>25);
```

profilesID	name	tell	age	birthday
1	田中実	012-345-6789	30	1994-02-01
2	鈴木茂	090-1122-3344	37	1987-08-12

```
2 rows in set (0.00 sec)
```

## 課題6

```
mysql> select * from profiles where(name like '%実');
```

```
mysql> select * from profiles where(name like '%実');
```

profilesID	name	tell	age	birthday
1	田中実	012-345-6789	30	1994-02-01
3	鈴木実	080-5566-7788	24	2000-12-24

```
2 rows in set (0.00 sec)
```

## 課題7

```
mysql> update profiles set name='吉田茂' where profilesID=2;
```

```
mysql> select * from profiles where profilesID=2;
```

```
mysql> select * from profiles where profilesID=2;
```

profilesID	name	tell	age	birthday
2	吉田茂	090-1122-3344	37	1987-08-12

```
1 row in set (0.00 sec)
```



## 課題8

```
delete from profiles where(birthday='2000-12-24');  
select * from profiles;
```

```
[mysql> select * from profiles;
```

profilesID	name	tell	age	birthday
1	田中実	012-345-6789	30	1994-02-01
2	吉田茂	090-1122-3344	37	1987-08-12
4	佐藤清	012-0987-6543	19	2005-08-01

```
3 rows in set (0.00 sec)
```

## 課題9

table department の作成

```
create table department(departmentID int primary key,departmentName varchar(225));  
insert into department() values(1,'開発部');  
insert into department() values(2,'営業部');  
insert into department() values(3,'総務部');
```

table station の作成

```
create table station(stationID int primary key,stationName varchar(225));  
insert into station() values(1,'九段下');  
insert into station() values(2,'永田町');  
insert into station() values(3,'渋谷');  
insert into station() values(4,'神保町');  
insert into station() values(5,'上井草');
```

## 課題9の続き

table user の作成

```
create table user(userID int primary key,name varchar(225),tell varchar(225),age  
int,birthday date,departmentID int,stationID int, foreign key(departmentID) references  
department(departmentID), foreign key(stationID) references station(stationID));
```

```
insert into user() values(1,'田中実','012-345-6789',30,'1994-02-01',3,1);  
insert into user() values(2,'鈴木茂','090-1122-3344',37,'1987-08-12',3,4);  
insert into user() values(3,'鈴木実','080-5566-7788',24,'2000-12-24',2,5);  
insert into user() values(4,'佐藤清','012-0987-6543',19,'2005-08-01',1,5);  
insert into user() values(5,'高橋清','090-9900-1234',24,'2000-12-24',3,5);
```

```
[mysql> select * from user;
```

userID	name	tell	age	birthday	departmentID	stationID
1	田中実	012-345-6789	30	1994-02-01	3	1
2	鈴木茂	090-1122-3344	37	1987-08-12	3	4
3	鈴木実	080-5566-7788	24	2000-12-24	2	5
4	佐藤清	012-0987-6543	19	2005-08-01	1	5
5	高橋清	090-9900-1234	24	2000-12-24	3	5

5 rows in set (0.00 sec)

mysql> ■

```
[mysql> select * from department;
```

departmentID	departmentName
1	開発部
2	営業部
3	総務部

3 rows in set (0.00 sec)

```
[mysql> select * from station;
```

stationID	stationName
1	九段下
2	永田町
3	渋谷
4	神保町
5	上井草

5 rows in set (0.00 sec)