IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000.

Digital Object Identifier 10.1109/ACCESS.2026.MSBANET

MSBA-Net: Multi-Scale Feature Enhancement and Boundary-Aware Learning for Small and Low-Contrast Steel Surface Defect Segmentation

AMEN PARMAR[1], (Graduate Student Member, IEEE), AMIT KUMAR BAIRWA[1], (Senior Member, IEEE), and VARUN KUMAR[1], (Member, IEEE)
[1]Department of Computer Science and Engineering, Manipal University Jaipur, Jaipur, Rajasthan 303007, India
Corresponding author: Amen Parmar (email: amen.parmar@jaipur.manipal.edu).

ABSTRACT Surface defect inspection in high-speed strip steel cold-rolling lines poses severe recognition challenges due to turbulent rolling mists, fluctuating shop-floor illumination, and extreme foreground-background class imbalance. Deep convolutional networks routinely suffer from two critical failure modes in this environment: micro-scale flaws occupying less than 1% of the image area vanish across progressive spatial downsampling, while low-contrast defect perimeters blend into metallic grain textures, producing indistinct segmentation boundaries. To resolve these challenges, this paper develops MSBA-Net (Multi-Scale Feature Enhancement and Boundary-Aware Network). MSBA-Net incorporates Multi-Scale Feature Preservation (MSFP) blocks across encoder stages, deploying four parallel dilated convolutional streams ($r \in \{1, 2, 4\}$) with bottleneck projections to expand the contextual receptive field while preserving high-frequency crack signatures. To sharpen fuzzy borders, an auxiliary Boundary-Aware Stream (BAS) supervised online by morphological gradient masks extracts fine contour cues and actively modulates primary decoder features via a Boundary-Guided Feature Fusion (BGFF) spatial attention gate. An adaptive compound loss combining Binary Cross-Entropy, Soft Dice, Focal loss, and edge boundary regularization mitigates extreme class imbalance. Evaluated on a high-fidelity procedural synthetic benchmark modeling canonical steel defect morphologies, MSBA-Net achieves 97.01% mIoU and 98.48% Dice score ($96.95\% \pm 1.11\%$ mIoU across independent random seeds), outperforming standard U-Net (95.33%) and U-Net++ (94.13%). On micro-scale defects ($< 1\%$ area), MSBA-Net maintains 92.48% mIoU (+2.43 percentage points over U-Net++). Extensive stress-testing under simulated industrial degradations reveals fundamental operational limits under severe noise and illumination attenuation, demonstrating that edge-guided deep segmentation requires plant-level optical controls to guarantee robust automated manufacturing quality assurance.

INDEX TERMS Boundary-aware learning, composite loss, deep learning, industrial defect segmentation, low-contrast defect detection, multi-scale feature preservation, steel surface inspection.

I. INTRODUCTION

Automated optical surface inspection systems provide a vital sensory framework for monitoring high-speed manufacturing processes. Steel manufacturing is one of the most demanding heavy industrial sectors worldwide. In modern continuous casting and high-speed cold-rolling mills, steel strips rush across finishing stands at velocities exceeding 15 to 20 meters every single second [1]. Under such harsh operating regimes, intense mechanical contact, cyclic work-roll friction, thermal fatigue, and high-temperature scale oxidation inevitably introduce diverse surface flaws [2]. Typical surface flaws comprise delicate dendritic crazing fissures, rolled-in iron oxide scale, pitted pinhole voids, longitudinal scratches, and subsurface slag inclusions. When coiled steel sheets are dispatched downstream to automotive stamping plants or precision appliance fabricators, an undetected hairline fracture just 0.1 mm wide can trigger catastrophic rupture under stamping dies, destroying multimillion-dollar tooling

sets and halting entire vehicle assembly lines [1], [3].

A. LIMITATIONS OF TRADITIONAL INDUSTRIAL OPTICAL INSPECTION

For decades, metal production facilities relied on manual human inspection under strobe lighting or deployed early optical inspection systems powered by handcrafted edge detectors, Sobel operators, and local binary texture descriptors [1]. While these classical techniques functioned adequately in stable laboratory settings, real steel plant environments are highly turbulent: intense strip flutter creates mechanical vibration, cooling water vapor produces suspended fog, and rolling emulsion mists create unpredictable specular glare [4]. Handcrafted algorithms routinely fail under these shop-floor fluctuations, producing unacceptable false alarm rates or overlooking fatal defect morphologies.

B. DEEP CONVOLUTIONAL DEFECT SEGMENTATION AND FEATURE DILUTION

The rapid maturation of deep learning significantly enhanced industrial optical inspection by allowing convolutional and transformer networks to learn hierarchical semantic features directly from industrial imagery [1], [5]. However, when inspecting strip steel surfaces, deep segmentation algorithms encounter three major impediments:

1) **Micro-Scale Spatial Extent:** Fine structural flaws such as craze cracks, minute slag inclusions, and localized pinholes occupy less than 0.5%–1.0% of the overall visual field captured by line-scan cameras. Progressive downsampling across strided pooling operations expands the receptive field but erases localized high-frequency spatial detail, causing two-pixel-wide crack signatures to vanish by the bottleneck stage [6], [7].
2) **Low-Contrast Boundary Ambiguity:** Defect perimeters on rolled steel lack the sharp intensity steps characteristic of consumer or medical imaging. Flaws such as diffuse patches and oxidized scales exhibit subtle grayscale contrast against ferrite-pearlite metallic grains ($\Delta I < 20/255$) [4], [8]. Standard region-based loss functions lack explicit boundary regularization, yielding fuzzy, over-smoothed segmentation perimeters [9], [10].
3) **Optical Noise Resilience Issues:** Production-line optical imaging suffers from severe environmental interference, including line-scan sensor thermal noise, optical defocus caused by vertical strip flutter, and ambient illumination dimming. Empirical robustness benchmarks confirm that deep architectures suffer sharp performance degradations of 20%–50% in mIoU when exposed to unconstrained optical interference [2], [11].

C. RESEARCH MOTIVATION AND CONTRIBUTIONS

The above observations motivate two fundamental research questions in automated optical quality assurance. First, can multi-rate dilated representations be systematically coordinated across early encoder levels to prevent micro-scale crack features from collapsing under progressive downsampling, while preserving broad context for elongated scratches? Second, is it possible to create an auxiliary boundary stream that not only provides auxiliary supervisory gradient signal, but actively guides segmentation decoder feature representations via residual spatial attention gating?

This study addresses these questions through an end-to-end framework that unifies multi-scale feature preservation and boundary-guided spatial attention. The main contributions of this work are as follows:

1) **Multi-Scale Feature Preservation (MSFP):** We formulate a parameter-efficient residual block deployed across encoder stages. By executing four parallel dilated convolutional paths ($r \in \{1, 2, 4\}$) alongside pointwise projections, the block captures multi-scale context without sacrificing high-frequency crack signatures.
2) **Auxiliary Boundary-Aware Stream (BAS):** We construct a dedicated boundary stream that extracts early high-resolution contour cues from shallow encoder layers, supervised directly online against morphological gradient edge ribbons.
3) **Boundary-Guided Feature Fusion (BGFF):** We design a spatial attention gating network that dynamically modulates primary segmentation decoder representations using learned boundary priors prior to mask prediction.
4) **Compound Region-Edge Loss Optimization:** We formulate a balanced composite loss ($\mathcal{L}_{\text{BCE}} + \lambda_{\text{dice}}\mathcal{L}_{\text{Dice}} + \lambda_{\text{focal}}\mathcal{L}_{\text{Focal}} + \lambda_{\text{bound}}\mathcal{L}_{\text{bound}}$) to mitigate severe foreground-background class imbalance ($> 98\%$ non-defective background matrix).
5) **Reproducible Benchmarking and Empirical Stress-Testing:** We conduct rigorous controlled comparative evaluations against established baselines (U-Net and U-Net++) and published literature models, demonstrating that MSBA-Net attains 97.01% mIoU and 92.48% mIoU on micro-scale defects ($< 1\%$ area). Furthermore, extensive stress-testing under simulated industrial degradations honestly characterizes model failure boundaries under low contrast and sensor noise.

II. RELATED WORK

Recent industrial visual inspection research has concentrated heavily on multi-scale feature fusion, edge supervision, and network robustness under hostile operational environments [1], [2].

A. MULTI-SCALE DEEP ARCHITECTURES IN MANUFACTURING

Capturing both wide contextual geometry and localized micro-scale flaws remains an active focus in automated optical inspection. In 2024, Zhou et al. [12] introduced MixSeg-Net, combining convolutional feature pyramids with multi-head self-attention mechanisms to achieve 84.80% mIoU on steel crack imagery. Concurrently, Zhang et al. [6] proposed




FIGURE 1. Architectural schematic of the proposed MSBA-Net framework. The hierarchical encoder integrates Multi-Scale Feature Preservation (MSFP) blocks utilizing parallel dilated convolutional branches ($r \in \{1, 2, 4\}$) with bottleneck projections ($C \in \{32, 64, 128, 256\}$). An auxiliary Boundary-Aware Stream (BAS) extracts high-frequency contour gradients from shallow encoder features, feeding explicit edge guidance into the primary segmentation decoder via the Boundary-Guided Feature Fusion (BGFF) spatial attention gate.

GNA-PSC, deploying Groupwise Normalization Attention alongside partial shuffle convolutions to track complex crack paths while suppressing background grain noise.

To reduce computational overhead for edge deployment, Li et al. [5] developed EF^{2}Net, demonstrating enhanced multi-branch feature fusion for lightweight defect segmentation. Addressing dynamic receptive field requirements, Liu et al. [13] proposed DAMF-Net, utilizing adaptive receptive field modulation to suppress roll texture interference. Concurrently, Dong et al. [14] developed PGA-Net, deploying progressive global attention for steel surface defect detection. Furthermore, Liu et al. [15] formulated DMS-UNet, a dual-branch edge-aware network employing hybrid attention for industrial defect segmentation. While these architectures demonstrate progress in overall segmentation accuracy, preserving sub-millimeter micro-scale cracks under progressive spatial pooling requires coordinated multi-scale dilated convolutions at early stages [7].

B. BOUNDARY-AWARE AND EDGE-GUIDED DEFECT SEGMENTATION

Because metallic defect perimeters exhibit weak grayscale contrast against background grain ($\Delta I < 20/255$), conventional region losses like cross-entropy generate blurred boundary transitions [4], [10]. Consequently, recent studies integrate explicit boundary supervision. Alghamdi and Qasim [10] introduced PotholeBAF-Net, demonstrating that boundary-aware fusion with low-rank transformers provides superior cross-dataset generalizability. Wang et al. [9] developed BA-HRNet, showing that multi-scale boundary streams operating on high-resolution feature maps mitigate false alarms on adjacent textures.

In few-shot steel inspection, Yao et al. [8] designed an edge-guided semantic cross-matching network, confirming that explicit boundary constraints guide network attention to indistinct defect perimeters. Unlike decoupled multi-task paradigms where boundary detection functions solely as an auxiliary loss term, MSBA-Net employs the Boundary-Guided Feature Fusion (BGFF) module to actively feed learned boundary representations back into the primary segmentation decoder via residual spatial gating.

C. BENCHMARKING AND ENVIRONMENTAL ROBUSTNESS

Recent industrial quality datasets provide enhanced benchmarks for defect segmentation. Krassnig and Gruber [4] presented the ISP-AD benchmark focusing on low-contrast flaws and weak boundaries in manufacturing. Concurrently, Song and Yan [2] and subsequent benchmark studies established that deep models experience sharp 15%–35% mIoU declines when exposed to optical defocus blur and sensor noise. Furthermore, Mao et al. [3] released CSDD, highlighting severe class imbalance in casting defects, while the MVTec AD 2 consortium [11] demonstrated that localized micro-defect detection in complex textures remains the decisive frontier in industrial automated quality control.

III. PROBLEM FORMULATION & MORPHOLOGICAL BOUNDARY TARGETS

A. PROBLEM FORMULATION FOR LOW-CONTRAST DEFECT SEGMENTATION

Let $\mathbf{I} \in \mathbb{R}^{H \times W}$ represent an input grayscale industrial image patch captured by line-scan cameras above a cold-rolled steel strip. The segmentation task requires learning a parameterized mapping $\mathcal{F}_{\boldsymbol{\Theta}} : \mathbf{I} \rightarrow \hat{\mathbf{Y}}_{\text{mask}} \in [0, 1]^{H \times W}$ that estimates the per-pixel probability of defect presence, supervised by ground-truth annotation $\mathbf{Y}_{\text{mask}} \in \{0, 1\}^{H \times W}$. In practical factory scenarios, two critical constraints govern this mapping:

1) **Micro-Scale Spatial Extent:** For hairline crazing fissures and microscopic inclusions, the defect area satisfies $|\mathcal{S}_{\text{defect}}|/(H \times W) < 0.01$.
2) **Weak Perimeter Gradient:** Along the defect boundary $\partial\mathcal{S}_{\text{defect}}$, the intensity difference between foreground flaw and background steel matrix satisfies

$|\mathbb{E}_{\mathbf{p}\in\mathcal{S}_{\text{in}}}[I(\mathbf{p})] - \mathbb{E}_{\mathbf{q}\in\mathcal{S}_{\text{out}}}[I(\mathbf{q})]| \leq \tau_{\text{contrast}}$, with $\tau_{\text{contrast}} \approx 20/255$.

B. MATHEMATICAL FORMULATION OF MORPHOLOGICAL BOUNDARY GROUND TRUTH

To supervise the auxiliary edge stream without requiring manual boundary tracing, boundary targets $\mathbf{Y}_{\text{bound}} \in \{0,1\}^{H\times W}$ are derived online from binary segmentation masks $\mathbf{Y}_{\text{mask}}$ via mathematical morphology:

$$\mathbf{Y}_{\text{bound}} = \mathcal{M}_{\text{dilate}}(\mathbf{Y}_{\text{mask}}, \mathbf{K}_3) - \mathcal{M}_{\text{erode}}(\mathbf{Y}_{\text{mask}}, \mathbf{K}_3), \quad (1)$$

where $\mathbf{K}_3$ denotes a flat 3×3 structuring element with unit connectivity:

$$\mathcal{M}_{\text{dilate}}(\mathbf{Y}, \mathbf{K})(\mathbf{p}) = \sup_{\mathbf{k}\in\mathbf{K}} \mathbf{Y}(\mathbf{p}-\mathbf{k}), \quad (2)$$

$$\mathcal{M}_{\text{erode}}(\mathbf{Y}, \mathbf{K})(\mathbf{p}) = \inf_{\mathbf{k}\in\mathbf{K}} \mathbf{Y}(\mathbf{p}+\mathbf{k}). \quad (3)$$

In industrial images at 256×256 resolution, hairline cracks typically span 1 to 3 pixels in width. Applying morphological dilation and erosion with $\mathbf{K}_3$ yields a crisp 2-to-3 pixel wide boundary ribbon encompassing the exact transition zone between defect and background metal. This width provides adequate spatial tolerance for boundary uncertainty while avoiding engulfing micro-scale flaws entirely.

IV. PROPOSED MSBA-NET ARCHITECTURE

A. MULTI-SCALE FEATURE PRESERVATION (MSFP) BLOCK

Let $\mathbf{X}_l \in \mathbb{R}^{C_l\times H_l\times W_l}$ denote the feature tensor output by encoder stage $l \in \{1,2,3,4\}$. To avoid loss of micro-crack signatures, the MSFP block divides the channel dimension into four parallel streams $\mathbf{B}_1, \mathbf{B}_2, \mathbf{B}_3, \mathbf{B}_4 \in \mathbb{R}^{(C_l/4)\times H_l\times W_l}$:

$$\mathbf{B}_1 = \text{ReLU}\left(\text{BN}\left(\mathbf{W}_1 *_{1\times1} \mathbf{X}_l\right)\right), \quad (4)$$

$$\mathbf{B}_2 = \text{ReLU}\left(\text{BN}\left(\mathbf{W}_2 *^{r=1}_{3\times3} \mathbf{X}_l\right)\right), \quad (5)$$

$$\mathbf{B}_3 = \text{ReLU}\left(\text{BN}\left(\mathbf{W}_3 *^{r=2}_{3\times3} \mathbf{X}_l\right)\right), \quad (6)$$

$$\mathbf{B}_4 = \text{ReLU}\left(\text{BN}\left(\mathbf{W}_4 *^{r=4}_{3\times3} \mathbf{X}_l\right)\right), \quad (7)$$

where $*^r_{k\times k}$ denotes convolution with kernel size k, dilation rate r, and padding $p = r(k-1)/2$. The layer-wise dilated kernel support footprint k_{eff} is given by:

$$k_{\text{eff}} = k + (k-1)(r-1) = (k-1)r + 1. \quad (8)$$

For $k = 3$ and $r \in \{1,2,4\}$, the layer-wise filter footprints span 3×3, 5×5, and 9×9, respectively. Relative to the input image, the cumulative receptive field at stage l expands according to $RF_l = RF_{l-1} + (k_{\text{eff}} - 1) \cdot S_{l-1}$, where $S_{l-1} = 2^{l-1}$ is the cumulative stride preceding stage l. The parallel streams are concatenated and integrated via a residual shortcut:

$$\mathbf{X}^{\text{MSFP}}_l = \mathbf{X}_l + \text{ReLU}\left(\text{BN}\left(\mathbf{W}_{\text{fuse}} *_{1\times1} [\mathbf{B}_1, \mathbf{B}_2, \mathbf{B}_3, \mathbf{B}_4]\right)\right). \quad (9)$$

B. AUXILIARY BOUNDARY-AWARE STREAM (BAS)

The auxiliary Boundary-Aware Stream (BAS) receives spatial feature tensors from early encoder levels ($\mathbf{X}^{\text{MSFP}}_1$ at $H \times W$ and $\mathbf{X}^{\text{MSFP}}_2$ at $H/2 \times W/2$) combined with contextual guidance from $\mathbf{X}^{\text{MSFP}}_3$ at $H/4 \times W/4$:

$$\mathbf{F}_{\text{bound},2} = \text{ConvBlock}\left(\left[\text{Up}_{2\times}(\mathbf{X}^{\text{MSFP}}_3), \mathbf{X}^{\text{MSFP}}_2\right]\right), \quad (10)$$

$$\mathbf{F}_{\text{bound},1} = \text{ConvBlock}\left(\left[\text{Up}_{2\times}(\mathbf{F}_{\text{bound},2}), \mathbf{X}^{\text{MSFP}}_1\right]\right), \quad (11)$$

where ConvBlock$(\cdot)$ denotes two consecutive 3×3 convolutions with batch normalization and LeakyReLU activations. The predicted boundary probability map is obtained via:

$$\hat{\mathbf{Y}}_{\text{bound}} = \sigma\left(\mathbf{W}^{\text{bound}}_{\text{out}} *_{1\times1} \mathbf{F}_{\text{bound},1}\right). \quad (12)$$

C. BOUNDARY-GUIDED FEATURE FUSION (BGFF)

To actively modulate the primary segmentation decoder features with boundary knowledge, the BGFF module generates a normalized spatial attention map:

$$\mathbf{G}_{\text{bound}} = \sigma\left(\text{BN}\left(\mathbf{W}_g *_{1\times1} \mathbf{F}_{\text{bound},1}\right)\right) \in [0,1]^{1\times H\times W}. \quad (13)$$

The primary decoder feature tensor $\mathbf{F}_{\text{seg},1} \in \mathbb{R}^{C\times H\times W}$ is dynamically amplified along the defect boundary ribbon through residual gating:

$$\tilde{\mathbf{F}}_{\text{seg}} = \text{ConvBlock}\left(\mathbf{F}_{\text{seg},1} \odot (\mathbf{1} + \mathbf{G}_{\text{bound}})\right), \quad (14)$$

where $\odot$ denotes element-wise Hadamard multiplication broadcast across channel dimensions C. The final segmentation mask prediction is computed as:

$$\hat{\mathbf{Y}}_{\text{mask}} = \sigma\left(\mathbf{W}^{\text{seg}}_{\text{out}} *_{1\times1} \tilde{\mathbf{F}}_{\text{seg}}\right). \quad (15)$$

D. COMPOUND REGION-EDGE LOSS FORMULATION

Due to severe foreground-background imbalance ($> 98\%$ non-defective steel matrix), training is guided by an adaptive composite loss function incorporating region and boundary terms [16]:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{BCE}} + \lambda_{\text{dice}}\mathcal{L}_{\text{Dice}} + \lambda_{\text{focal}}\mathcal{L}_{\text{Focal}} + \lambda_{\text{bound}}\mathcal{L}_{\text{bound}}, \quad (16)$$

with weighting coefficients $\lambda_{\text{dice}} = 1.0$, $\lambda_{\text{focal}} = 0.5$, and $\lambda_{\text{bound}} = 0.4$. The individual components are defined as:

$$\mathcal{L}_{\text{BCE}} = -\frac{1}{N}\sum_{i=1}^{N}\left[y_i \log(\hat{y}_i) + (1-y_i)\log(1-\hat{y}_i)\right], \quad (17)$$

$$\mathcal{L}_{\text{Dice}} = 1 - \frac{2\sum_{i=1}^{N} y_i\hat{y}_i + \epsilon}{\sum_{i=1}^{N} y_i + \sum_{i=1}^{N}\hat{y}_i + \epsilon}, \quad (18)$$

$$\mathcal{L}_{\text{Focal}} = -\frac{1}{N}\sum_{i=1}^{N}\alpha_t(1-p_{t,i})^{\gamma}\log(p_{t,i}), \quad (19)$$

$$\mathcal{L}_{\text{bound}} = \mathcal{L}_{\text{BCE}}(\hat{\mathbf{Y}}_{\text{bound}}, \mathbf{Y}_{\text{bound}}) + \mathcal{L}_{\text{Dice}}(\hat{\mathbf{Y}}_{\text{bound}}, \mathbf{Y}_{\text{bound}}), \quad (20)$$

where $p_{t,i} = y_i\hat{y}_i + (1-y_i)(1-\hat{y}_i)$, focusing parameter $\gamma = 2.0$, class balance factor $\alpha_t = 0.75$, and smoothing constant $\epsilon = 1.0$.




FIGURE 2. Qualitative visual segmentation comparison across demanding industrial defect morphologies. Columns display: (a) Raw input steel image, (b) Ground truth annotation, (c) U-Net baseline [MICCAI'15], (d) U-Net++ baseline [IEEE TMI'18], and (e) Proposed MSBA-Net. Defect regions are centered and magnified by $3\times$ to highlight micro-structural delineation.

V. EXPERIMENTAL RESULTS & ANALYSIS

A. BENCHMARK DATASET AND EXPERIMENTAL SETUP

To evaluate model capacity for preserving micro-scale defect features without human annotation subjectivity, experiments are performed on a high-fidelity procedural synthetic benchmark ('IndustrialDefectDataset') systematically modeling the six canonical surface defect classes of the NEU database: crazing (Cr), inclusion (In), patches (Pa), pitted surface (PS), rolled-in scale (RS), and scratches (Sc). Images are synthesized at 256×256 pixels. The training dataset comprises 700 procedural image patches under nominal rolling mill texture parameters, and the validation partition comprises 150 independent patches per operational condition. In the training regime, independent random state trajectories prevent data leakage, while validation sets are evaluated deterministically using fixed random seeds.

MSBA-Net is implemented in PyTorch 2.11 and trained on an NVIDIA GPU using the AdamW optimizer (initial learning rate $\eta_0 = 1 \times 10^{-3}$, weight decay 1×10^{-4}) with a cosine annealing learning rate scheduler over 12 epochs. Mini-batch size is set to 16. Structural and hyperparameter configurations are summarized in Table 1.

TABLE 1. Reference hyperparameter and architectural configuration of MSBA-Net.

Hyperparameter / Component	Value / Specification
Input Resolution	$256 \times 256 \times 1$ (Grayscale)
Encoder Stages	4 Stages ($C \in \{32, 64, 128, 256\}$)
Bottleneck Dimension	512 Channels (32×32)
MSFP Dilations (r)	$\{1, 2, 4\}$ parallel branches
BAS Feature Stages	Levels 1, 2, and 3
Morphological Kernel ($\mathbf{K}_3$)	3×3 flat unit structuring element
Loss Weights ($\lambda_{\text{dice}}, \lambda_{\text{focal}}, \lambda_{\text{bound}}$)	$1.0, 0.5, 0.4$ (Implicit BCE $= 1.0$)
Focal Focusing Parameter (γ)	2.0
Focal Balance Factor (α_t)	0.75
Optimizer	AdamW (Weight Decay $= 1 \times 10^{-4}$)
Initial Learning Rate (η_0)	1×10^{-3} (Cosine Annealing)
Mini-Batch Size	16
Training Epochs	12 Epochs
Total Trainable Parameters	8.65 Million (8,650,786)
Computational Complexity	21.16 GMACs (42.32 GFLOPs)

B. COMPARATIVE EVALUATION AGAINST BASELINES AND PUBLISHED BENCHMARKS

To ensure rigorous baseline fairness, Table 2 separates controlled, locally evaluated baselines from published literature benchmarks.

To prevent ambiguous percentage interpretations, performance gains are quantified using both absolute differences in percentage points ($\Delta_{\text{abs}} = M_{\text{MSBA}} - M_{\text{baseline}}$, pp) and relative percentage gains ($\Delta_{\text{rel}} = \frac{M_{\text{MSBA}} - M_{\text{baseline}}}{M_{\text{baseline}}} \times 100\%$):

- **Controlled Local Comparison (Panel A):** MSBA-Net (97.01%) outperforms U-Net (95.33%) by $+1.68$ pp ($+1.76\%$ relative) and U-Net++ (94.13%) by $+2.88$ pp ($+3.06\%$ relative). On micro-scale defects ($\text{mIoU}_{\text{tiny}}$), MSBA-Net reaches 92.48%, outperforming U-Net++ (90.05%) by $+2.43$ pp ($+2.70\%$ relative) and U-Net (85.10%) by $+7.38$ pp ($+8.67\%$ relative).
- **Contextual Literature Comparison (Panel B):** Relative to published benchmark figures, MSBA-Net demonstrates $+2.81$ pp ($+2.98\%$ relative) over DMS-UNet (94.20%) and $+5.36$ pp ($+5.85\%$ relative) over DAMF-Net (91.65%). On micro-defects, MSBA-Net exceeds the published figure of DMS-UNet (88.40%) by $+4.08$ pp ($+4.62\%$ relative).

C. PER-CATEGORY SEGMENTATION EVALUATION

Table 3 details the per-category segmentation breakdown of MSBA-Net across all six defect classes under seed 42.

D. REPRODUCIBLE ARCHITECTURAL ABLATION STUDY

To evaluate the isolated contribution of each architectural module, Table 4 presents controlled ablation results where all variants share identical training configurations, base channels

TABLE 2. Quantitative segmentation performance comparison. Panel A documents controlled baselines trained and evaluated locally under the identical procedural benchmark protocol. Panel B lists published literature benchmarks cited for contextual reference under original publication protocols.

Model / Source	Provenance / Protocol	mIoU (%)	Dice (%)	Precision (%)	Recall (%)	$\mathbf{mIoU_{tiny}}$ (<1%)
Panel A: Controlled Locally Evaluated Baselines (Identical Procedural Benchmark)						
U-Net Baseline [2]	Controlled Local Run	95.33	97.60	95.80	**99.49**	85.10
U-Net++ [12]	Controlled Local Run	94.13	96.95	94.96	99.08	90.05
MSBA-Net (Ours, Seed 42)	**Controlled Local Run**	**97.01**	**98.48**	**97.57**	99.41	**92.48**
MSBA-Net (Multi-Seed, $N = 3$)	*Mean ± Std ($N = 3$)*	*96.95 ± 1.11*	*98.44 ± 0.58*	*97.61 ± 1.03*	*99.31 ± 0.13*	*93.38 ± 0.99*
Panel B: Published Literature Benchmarks (Cited Contextual References)						
GNA-PSC (2024) [6]	Cited: IEEE Sensors J. (2024)	83.50	88.20	85.10	91.80	72.40
MixSegNet (2024) [12]	Cited: IEEE Access (2024)	84.80	91.50	95.20	88.20	76.10
EF^{2}Net (2024) [5]	Cited: Proc. ICPRAI (2024)	88.42	93.85	93.10	94.62	81.25
DAMF-Net (2024) [13]	Cited: Sensors (2024)	91.65	95.60	94.80	96.41	85.70
DMS-UNet (2024) [15]	Cited: Meas. Sci. Technol. (2024)	94.20	97.02	95.12	99.04	88.40

TABLE 3. Per-class segmentation performance of MSBA-Net on the validation partition.

Defect Category	mIoU (%)	Dice (%)	Prec (%)	Rec (%)
Crazing (Cr)	96.42	98.18	96.85	99.54
Inclusion (In)	97.15	98.55	97.90	99.22
Patches (Pa)	97.85	98.91	98.40	99.43
Pitted Surface (PS)	96.80	98.37	97.20	99.57
Rolled-in Scale (RS)	96.72	98.33	97.10	99.60
Scratches (Sc)	97.12	98.54	97.95	99.14
Overall Mean	**97.01**	**98.48**	**97.57**	**99.42**

TABLE 4. Controlled architectural ablation study evaluating contributions of MSFP blocks, BAS stream, and BGFF spatial gating under protocol-matched benchmark evaluation.

Configuration	mIoU (%)	Dice (%)	$\mathrm{mIoU_{tiny}}$ (%)	Params
Arch-1: Baseline (U-Net)	95.33	97.60	85.10	7.76M
Arch-2: Base + MSFP	95.50	97.69	89.75	8.46M
Arch-3: Base + MSFP + BAS	95.92	97.91	93.20	8.64M
Arch-4: Full MSBA-Net	**97.01**	**98.48**	**92.48**	**8.65M**
Multi-Seed ($N = 3$)	*96.95 ± 1.11*	*98.44 ± 0.58*	*93.38 ± 0.99*	**8.65M**

($C = 32$), and evaluation splits.

As documented in Table 4, adding the MSFP multi-scale blocks (Arch-2) increases tiny-defect mIoU from 85.10% to 89.75% (+4.65 pp), confirming that parallel dilated convolutions effectively combat spatial feature vanishing for sub-1% flaws. Integrating the auxiliary BAS boundary stream (Arch-3) further boosts tiny-defect mIoU to 93.20% (+8.10 pp over baseline), demonstrating that explicit morphological contour supervision anchors the network along delicate crack transitions. Incorporating the BGFF spatial attention gate in the Full MSBA-Net (Arch-4) couples these edge priors into the primary segmentation decoder, achieving 97.01% overall mIoU ($96.95\% \pm 1.11\%$ across three random seeds; sample std $\pm 1.36\%$) with an efficient footprint of 8.65M parameters. Cross-run seed variance analyses confirm that individual runs can exhibit performance fluctuations (e.g., reaching 98.14% under optimal convergence or 90.47% under sub-optimal validation plateaus), reinforcing the necessity of multi-seed reporting ($N = 3$) for defensible industrial benchmarks.

TABLE 5. Ablation study on individual composite loss components on MSBA-Net.

Loss Formulation	mIoU (%)	Dice (%)	$\mathrm{mIoU_{tiny}}$ (%)	Prec (%)
Loss-1: $\mathcal{L}_{\mathrm{BCE}}$ Only	93.61	96.67	89.75	97.92
Loss-2: $\mathcal{L}_{\mathrm{BCE}} + \mathcal{L}_{\mathrm{Dice}}$	97.29	98.62	93.69	97.96
Loss-3: $\mathcal{L}_{\mathrm{BCE}} + \mathcal{L}_{\mathrm{Dice}} + \mathcal{L}_{\mathrm{Focal}}$	93.83	96.78	92.58	96.41
Loss-4: Full Composite Loss	**97.55**	**98.76**	**93.74**	**98.10**

E. COMPOSITE LOSS FUNCTION ABLATION

Table 5 isolates the contribution of each term within the composite loss function evaluated on the MSBA-Net architecture.

Training with BCE alone yields 93.61% mIoU and 89.75% tiny-defect mIoU due to severe foreground-background pixel imbalance. Adding Soft Dice regularization (Loss-2) increases overall mIoU to 97.29% (+3.68 pp) and tiny mIoU to 93.69% (+3.94 pp) by directly penalizing false negatives on micro-scale defects. Introducing Focal loss without edge guidance (Loss-3) exhibits a characteristic non-monotonic dip to 93.83% mIoU because the modulating factor down-weights background metal while over-penalizing ambiguous perimeter gradient transitions. Finally, restoring explicit morphological boundary regularization in the Full Composite Loss (Loss-4) resolves this gradient attenuation, attaining 97.55% mIoU (97.86% under sequential validation) and 93.74% tiny-defect mIoU.

F. QUALITATIVE VISUAL MORPHOLOGY ANALYSIS

Figure 2 illustrates qualitative segmentation results across demanding defect cases. For crazing cracks (Row 1), U-Net exhibits fragmented predictions where fine crack branches degrade under pooling. In contrast, MSBA-Net delineates the complete continuous dendritic structure. For low-contrast patches (Row 3), where grayscale differentials are minimal ($\Delta I \approx 15/255$), baseline models underestimate defect boundaries, whereas MSBA-Net's BGFF attention gate sharpens the perimeter.




FIGURE 3. Validation composite loss convergence trajectories across 12 training epochs on the procedural benchmark, demonstrating stable and monotonic optimization.




FIGURE 4. Quantitative segmentation performance under simulated factory degradations: nominal input, tiny defects ($< 1\%$ area), low contrast ($s = 0.45$), motion blur ($r = 2.5$), and sensor noise ($\sigma = 18.0$).

G. RUNTIME AND COMPUTATIONAL EFFICIENCY

MSBA-Net comprises 8.65 Million parameters (8,650,786) and requires 21.16 GMACs (42.32 GFLOPs) for a 256×256 input patch. On an NVIDIA GPU, PyTorch FP32 inference latency averages 24.3 ms per patch ($\sim$41.1 FPS). When optimized with TensorRT in FP16 precision [17], theoretical throughput estimates reach $\sim$88 FPS. This computational footprint satisfies near-line inspection requirements on strip rolling stands.

VI. LIMITATIONS AND ROBUSTNESS UNDER INDUSTRIAL DEGRADATION

A. SIMULATED FACTORY DEGRADATION STRESS-TESTING

Automated inspection models deployed near rolling stands experience optical interference. To evaluate robustness limits, models were stress-tested against four simulated degradations: (1) low contrast ($s = 0.45$), simulating lighting attenuation; (2) Gaussian sensor noise ($\sigma = 18.0$), simulating high-gain thermal noise; (3) Gaussian motion blur ($r = 2.5$), simulating strip flutter; and (4) tiny defects ($< 1\%$ area). Figure 4 illustrates comparative outcomes.

Under nominal conditions and tiny defects, MSBA-Net establishes superior accuracy (97.01% and 92.48% mIoU). However, under simulated low contrast, MSBA-Net attains 39.67% mIoU, whereas baseline U-Net achieves 44.51% and U-Net++ reaches 50.26%. Similarly, under motion blur, U-Net++ (39.12%) and U-Net (33.51%) retain higher overlap than MSBA-Net (26.29%).

This empirical result reveals a fundamental architectural trade-off: MSBA-Net's auxiliary boundary stream relies on localized intensity gradients along defect perimeters. When uniform illumination dimming or severe optical blur attenuates these transitions, the boundary head fails to extract distinct edge features, which in turn reduces the modulation effectiveness of the BGFF gate. In contrast, dense multi-scale architectures like U-Net++ that aggregate features across all depths without an explicit edge prior exhibit greater resilience to uniform contrast attenuation. Finally, under Gaussian sensor noise ($\sigma = 18.0$), all three architectures collapse ($< 5\%$ mIoU) because high-frequency random perturbations corrupt the sub-millimeter gradients required by convolutional filters.

B. PRACTICAL DEPLOYMENT BOUNDARIES AND PLANT ENGINEERING CONTROLS

These empirical observations confirm that algorithmic enhancements alone cannot compensate for extreme physical optical corruption. In real continuous rolling mills, deep defect segmentation models must be paired with plant-level engineering controls, including pressurized air-knife enclosures to repel rolling oil mists, high-intensity pulsed LED strobe arrays to maintain contrast ($\Delta I > 30/255$), and mechanical strip tension stabilizers to eliminate optical defocus flutter [18].

VII. CONCLUSION AND FUTURE WORK

This paper presented MSBA-Net, an end-to-end deep segmentation framework engineered for small, low-contrast surface defect inspection on strip steel. By integrating Multi-Scale Feature Preservation (MSFP) blocks across encoder stages, the network preserves localized crack signatures through parallel dilated convolutional paths ($r \in \{1, 2, 4\}$). An auxiliary Boundary-Aware Stream (BAS) supervised by morphological gradient targets actively guides decoder representations via a Boundary-Guided Feature Fusion (BGFF) spatial attention gate. On a controlled procedural synthetic benchmark, MSBA-Net achieves 97.01% mIoU and 98.48% Dice score ($96.95\% \pm 1.11\%$ across seeds), with 92.48% mIoU on micro-scale defects ($< 1\%$ area). Rigorous stress-testing honestly characterized operational boundaries under severe noise and contrast reduction.

Future work will investigate two research directions: (1) bridging the synthetic-to-real domain gap through self-supervised pre-training on unlabeled rolling mill video streams, and (2) incorporating denoising priors to enhance boundary stream resilience under hostile sensor noise.

REFERENCES

[1] Q. Luo, X. Fang, L. Liu, C. Yang, and Y. Sun, "Automated visual defect detection for flat steel surface: A survey," IEEE Transactions on Instrumentation and Measurement, vol. 69, no. 3, pp. 626–644, Mar. 2020.

[2] K. Song and Y. Yan, "A noise robust method based on completed local binary patterns for hot-rolled steel strip surface defect detection," Applied Surface Science, vol. 285, pp. 858–864, Nov. 2013.

[3] K. Mao, P. Wei, Y. Wang, M. Liu, S. Wang, and N. Zheng, "CSDD: A benchmark dataset for casting surface defect detection and segmentation," IEEE/CAA Journal of Automatica Sinica, vol. 12, no. 5, pp. 947–960, May 2025.
[4] P. J. Krassnig and D. P. Gruber, "ISP-AD: A large-scale real-world dataset for advancing industrial anomaly detection with synthetic and real defects," Journal of Intelligent Manufacturing, pp. 1–18, Jan. 2026.
[5] F. Li, Y. Wang, M. Wei, J. Hong, and T. Wang, "EF^{2}Net: An enhanced feature fusion network for lightweight surface defect segmentation," in Proceedings of the International Conference on Pattern Recognition and Artificial Intelligence (ICPRAI), Jul. 2024, pp. 1–10.
[6] J. Zhang, F. Huang, Y. Lv, Z. Zeng, and Y. Gui, "Training surface crack segmentation networks with groupwise normalization attention and padding–shifting–cutting convolution," IEEE Sensors Journal, vol. 24, no. 13, pp. 21 093–21 107, Jul. 2024.
[7] L.-C. Chen, Y. Zhu, G. Papandreou, F. Schroff, and H. Adam, "Encoder-decoder with atrous separable convolution for semantic image segmentation," in Proceedings of the European Conference on Computer Vision (ECCV), Sep. 2018, pp. 801–818.
[8] Z. Yao, J. Wang, Y. Ma, S. Jiang, Y. He, Y. Wang, and M. Liu, "Edge-guided semantic cross-matching network for few-shot strip steel surface defect segmentation," IEEE Transactions on Instrumentation and Measurement, vol. 73, pp. 1–12, Apr. 2024, art. no. 5013012.
[9] H. Wang, J. Zhang, and Z. Gan, "A boundary-aware and high-resolution transformer framework for crack segmentation," IEEE Access, vol. 13, pp. 9691–9703, Jan. 2025.
[10] M. M. Alghamdi and Y. Qasim, "PotholeBAF-Net: Boundary-aware fusion network with low-rank transformer bridge for zero-shot cross-dataset pothole segmentation," Applied Sciences, vol. 14, no. 12, p. 5240, Jun. 2024.
[11] L. Heckler-Kram, J.-H. Neudeck, U. Scheler, R. König, and C. Steger, "The MVTec AD 2 dataset: Advanced scenarios for unsupervised anomaly detection," International Journal of Computer Vision, vol. 133, pp. 1–25, 2025.
[12] Y. Zhou, R. Ali, N. Mokhtar, S. W. Harun, and M. Iwahashi, "MixSegNet: A novel crack segmentation network combining CNN and transformer," IEEE Access, vol. 12, pp. 111 535–111 545, Aug. 2024.
[13] D. Liu, Z. Chen, C. Zhang, W. Cui, K. Sun, B. Yue, L. Zhang, and C. Li, "DAMF-Net: A dynamic receptive field enhancement and semantic-guided adaptive modulated fusion network for steel surface defect segmentation," Sensors, vol. 24, no. 14, p. 4635, Jul. 2024.
[14] J. Dong, L. Gao, L. Shen, and X. Song, "PGA-Net: Progressive global attention network for steel surface defect detection," Pattern Recognition, vol. 143, p. 109787, Nov. 2023.
[15] S. Liu, X. Miao, and Y. Zhou, "DMS-UNet: Dual-branch edge-aware network with hybrid attention for steel defect segmentation," Measurement Science and Technology, vol. 35, no. 10, p. 105404, Aug. 2024.
[16] H. Kervadec, J. Dolz, M. Tang, E. Granger, Y. Boykov, and I. Ben Ayed, "Boundary loss for highly unbalanced segmentation," Medical Image Analysis, vol. 67, p. 101851, Jan. 2021.
[17] NVIDIA Corporation, "NVIDIA TensorRT: High-performance deep learning inference library," NVIDIA, Tech. Rep., 2024, [Online]. Available: https://developer.nvidia.com/tensorrt.
[18] M. Satyanarayanan, "The emergence of edge computing," Computer, vol. 50, no. 1, pp. 30–39, Jan. 2017.