## **LOGIN TO SYSTEM**

## :Description.1

This API is used for the agent to login.

## **Request Parameters .2**

Field	Description	Format	Presence
identifier	The agent's wallet identifier	AN	Mandatory
password	The agent's wallet password	AN	Mandatory

#### Notes:

- Content-Type: application/json
- Method:post

## **Response Parameter .3**

Field	Description	Format	Presence
access_token	The access token	AN	Mandatory
org_value	Agent's organization Value	AN	Mandatory
org_name	Agent's organization Name	AN	Mandatory

# Sample Request .4

```
{
"header" : {
  "serviceDetail" : {
  "corrID" : "59ba381c-1f5f-4480-90cc-0660b9cc850e",
  "domainName" : "WalletDomain",
  "serviceName" : "PAYWA.WALLETAUTHENTICATION"
  },
  "signonDetail" : {
  "clientID" : "WeCash",
  "orgID" : "xxxxxx",
  "userID" : "xxxxxx",
  "externalUser" : "xxxxxx"
  },
  "messageContext" : {
```

```
"clientDate" : "202211101156",
"bodyType" : "Clear"
}
},
  "body" : {
  "identifier" : "xxxxxx",
    "password":"xxxxxx"
}
}
```

## **Sample Response.5**

```
{
 "header": {
   "serviceDetail":
    "corrID": "59ba381c-1f5f-4480-90cc-0660b9cc850e",
    "domainName": "WalletDomain",
    "serviceName": "PAYWA.WALLETAUTHENTICATION"
   },
   "signonDetail":
    "orgID": "xxxxxx",
    "userID": "xxxxxx",
    "externalUser": "xxxxx",
    "clientID": "WeCash"
   },
   "messageContext":
    "clientDate": "202211101156",
    "bodyType": "Clear"
   }
 },
 "responseBody": {
   "access_token": "ebc9527b-a949-4e44-b989-4bd9b923cc1a",
   "org_value": "xxxxx",
   "org name": "xxx xxxx xxxx"
 },
 "responseStatus": {
   "systemStatus": "0",
   "systemStatusDesc": "Success",
   "systemStatusDescNative": "Success"
```

} }