

I. APPLICABLE STANDARDS/SPECIFICATIONS:
A. ASME Y14.100-2004

2) FOR INDICATED ITEMS, PARTS FROM ALTERNATE MANUFACTURERS WITH THE SAME OR BETTER FAILURE RATES AND/OR TOLERANCE MAY BE USED.

3 S25FL164K0XNFA013 IS THE PREFERRED PART FOR ITEM 72. IF THIS PART IS NOT AVAILABLE, CYPRESS SEMICONDUCTOR PART NO. S25FL064LABNF1013 OR S25FL064LABNFA013 (CODE IDENT 65786) MAY BE USED.

4. FOR SCHEMATIC DRAWING SEE 19200-13045930.

5. ASSEMBLY SHALL CONFORM TO PERFORMANCE SPECIFICATION 19200-13045907. VERIFICATION OF FUNCTIONAL PERFORMANCE SHALL BE DONE USING UNIVERSAL AUTOMATIC TEST EQUIPMENT (ATE) P/N 19200-13045793 OR EQUIVALENT.

6. ASSEMBLY SHALL BE SUBJECTED TO ENVIRONMENTAL STRESS SCREENING IN ACCORDANCE WITH REQUIREMENTS OF DETAIL PARAMETER DRAWING 19200-13045912.

7. PROGRAM CIRCUIT CARD ASSEMBLY (CCA) IN ACCORDANCE WITH LOGIC VERSION DESCRIPTION DOCUMENT (LVDD) NO. 19200-13045906.

8. ASSEMBLY SHALL BE MANUFACTURED IN ACCORDANCE WITH SPECIFICATION IPC-J-STD-001, CLASS 3, AND SHALL CONFORM TO THE REQUIREMENTS OF SPECIFICATION IPC-A-610, CLASS 3.

9. SOLDER USED IN THIS ASSEMBLY SHALL BE TIN/LEAD (Sn-Pb) SOLDER OF ALLOY TYPE SN60 OR SN63. LEAD-FREE PARTS MUST BE HOT-SOLDER DIPPED OR RE-BALLED WITH TIN/LEAD (Sn-Pb) SOLDER OF ALLOY TYPE SN60 OR SN63 IAW WITH GEIA-STD-0005-2-A LEVEL 2B RISK MITIGATION STRATEGY. REFERENCE NOTE 18 FOR SPECIFIC INSTRUCTIONS.

10 CONFORMAL COAT BOTH SIDES OF BOARD IN ACCORDANCE WITH THE REQUIREMENTS OF IPC-2221, USING INSULATION COMPOUND TYPE UR, SPEC MIL-I-46058, .002-.006 THK, INDICATED AREAS SHALL BE FREE OF CONFORMAL COAT.

11 INK STAMP OR SILK SCREEN OR LABEL SERIAL NUMBER IN APPROXIMATE LOCATION SHOWN AFTER ASSEMBLY, USING .05-.12 HEIGHT CHARACTERS. USE INK TYPE I OR III, COLOR WHITE OR BLACK, SPEC A-A-00208, IN ACCORDANCE WITH MIL-STD-130.

12 USING NON-ACID BASE (WHITE OR BLACK) INK, TYPE I, SPEC A-A-00208, INK STAMP OR SILK SCREEN ON THIS SURFACE IN .05-.50 HIGH CHARACTERS PER MIL-STD-130: 19200-13045872

13. SQUARE PAD DESIGNATES: PIN 1 OF MICROCIRCUITS, CONNECTORS (HEADERS), CATHODE OF DIODES, ANODE OF LEDs.

14 STAKE DOWN COMPONENT USING ITEM 79, EPOXY ADHESIVE. APPLY STAKING MATERIAL WHERE SHOWN BY DOTS.

15 CAGE CODE: 1A9T3
3M CO
DIV. INDUSTRIAL ADHESIVES AND TAPES
3M CENTER
SAINT PAUL, MN 55144

16> 100% LEAD ON PAD FOR THESE CONNECTORS.

[17] NOTE ORIENTATION OF HEADER CONNECTORS.

18 THESE LEAD-FREE PARTS MUST BE HOT-SOLDER DIPPED OR RE-BALLED WITH TIN/LEAD (Sn-Pb) SOLDER OF ALLOY TYPE SN60 OR SN63 1AW WITH GEIA-STD-0005-2-A LEVEL 2B RISK MITIGATION STRATEGY.

19. ADDITIONAL OR ALTERNATE PACKAGING CODES MAY BE INSERTED IN THE PART NUMBER THAT INDICATE THE ORDER QUANTITY AND PACKAGING TYPE ONLY (TAPE AND REEL, AMMO PACK, ETC.). ALL OTHER VARIABLES THAT AFFECT A TECHNICAL REQUIREMENT OF THE PART SUCH AS LEAD FINISH, PART PACKAGE TYPE, NUMBER OF TERMINALS, ETC. SHALL BE ORDERED EXACTLY AS DOCUMENTED IN THE DRAWING IN ACCORDANCE WITH THE MANUFACTURER'S PART IDENTIFICATION NUMBER IN THE PARTS LIST. ANY DEVIATION SHALL BE CONSIDERED A NON-CONFORMANCE.

20. FACILITY PRODUCING THIS ASSEMBLY SHALL HAVE AN ELECTROSTATIC DISCHARGE CONTROL PROGRAM FOR THE PROTECTION OF ELECTRICAL AND ELECTRONIC PARTS IN ACCORDANCE WITH ANSI/ESD S20.20.

21. MAXIMUM HEIGHT OF ANY COMPONENT ABOVE SURFACE OF THE BOARD SHALL BE AS FOLLOWS:
TOP (EXCEPT J4): 0.205
TOP (J4): .574
BOTTOM: 0.130

22. IDENTIFICATION OF THE APPROVED SOURCE(S) OF SUPPLY HEREON IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEMS DESCRIBED ON THIS DRAWING.

23. ONLY ITEMS DESCRIBED ON THIS DRAWING ARE APPROVED FOR USE IN THE APPLICATIONS SPECIFIED HEREON. A SUBSTITUTE ITEM SHALL NOT BE USED WITHOUT PRIOR APPROVAL BY THE QUALIFYING ACTIVITY.

24 FDC5612 IS THE PREFERRED PART FOR ITEM 36. IF THIS PART IS NOT AVAILABLE, DIODES INCORPORATED PART NO. DMN6040SVT (CODE IDENT 12060) MAY BE USED.

25 BU-64843T8-E02 IS THE PREFERRED PART FOR ITEM 78. IF THIS PART IS NOT AVAILABLE, DATA DEVICE CORPORATION PART NO. BU-64843T8-102 (CODE IDENT 19645) MAY BE USED.

26 SCI5921STR1 IS THE PREFERRED PART FOR ITEM 73. IF THIS PART IS NOT AVAILABLE, SEMTECH CORPORATION PART NO. SCI592MSTR1 (CODE IDENT 14099) MAY BE USED.

DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO THE DEPARTMENT OF DEFENSE AND U.S. DOD CONTRACTORS ONLY (REASON: CRITICAL TECHNOLOGY, EXPORT CONTROLLED) (DATE OF DETERMINATION: 09 JULY 2015). OTHER REQUESTS SHALL BE REFERRED TO PM-AFV, US ARMY TACOM. ATTN: SFAE-GCS-F, 6501 EAST 11 MILE ROAD, WARREN, MI 48397.

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C. SEC 2751, ET SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979 (TITLE 50, U.S.C. APP. 2401 ET SEQ.), AS AMENDED. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.

DESTROY BY SHREDDING OR TEARING TO MAKE UNREADABLE, WHEN NO LONGER NEEDED.

COPYRIGHT © 2019 BAE SYSTEMS LAND & ARMAMENTS L.P.



SOURCE CONTROL DRAWING

ALL SHEETS ARE THE SAME REVISION

PART NO. 13045872

DESIGN ACTIVITY										U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER PICATINNY ARSENAL, NJ 07806-5000									
TITLE																			
CIRCUIT CARD ASSEMBLY, CML WILDCARD																			
SIZE		CAGE CODE/DAT				DWG. NO.										RE-			
E		19200				13045872													
SCALE		3/1		UNIT WT		0.21 LB		SHEET 1				OF		3					

REVISIONS					
ZONE	LTR	DESCRIPTION	DATE(YR-MO-DA)	APPROVED	
		ALL REVISIONS LISTED ON SH 1			
	-	PRODUCT BASELINE ECP/ERR FOM-W1905	2019-10-06	RT TC	TF

[illegible]

	79	AR	IA9T3	DP620NS	EPOXY ADHESIVE	STAKING COMPOUND	3M COMPANY	15
U9	78	I	I9645	BU-64843T8-E02	TOTAL-ACE SSRT	CONTROLLER	DATA DEVICE CORP	25
REFERENCE DESIGNATION	ITEM NO.	QTY REQD	CODE IDENT	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL	SPECIFICATION/ MANUFACTURER	
LIST OF MATERIALS OR PARTS LIST								

DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO THE DEPARTMENT OF DEFENSE AND U.S. DOD CONTRACTORS ONLY (REASON: CRITICAL TECHNOLOGY, EXPORT CONTROLLED)
(DATE OF DETERMINATION: 09 JULY 2015). OTHER REQUESTS SHALL BE REFERRED TO PM-AFV,
US ARMY TACOM. ATTN: SFAE-GCS-F, 6501 EAST 11 MILE ROAD, WARREN, MI 48397.

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C. SEC 2751, ET SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979 (TITLE 50, U.S.C. APP. 2401 ET SEQ.), AS AMENDED. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DD DIRECTIVE 5230.25.

DESTROY BY SHREDDING OR TEARING TO MAKE UNREADABLE, WHEN NO LONGER NEEDED.

COPYRIGHT © 2019 BAE SYSTEMS LAND & ARMAMENTS L.P.

SOURCE CONTROL DRAWING

PART NO. 13045872

DO NOT SCALE DRAWING	DESIGN ACTIVITY: U. S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER PICATINNY ARSENAL, NJ 07806-5000		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES ANGLES ± . 1 PL ± . 2 PL ± . 3 PL ± .	TITLE: CIRCUIT CARD ASSEMBLY, CML WILDCARD		
THIRD ANGLE PROJECTION	SIZE: CASE CODE/DATE DWG. NO. 13045872 REV - SCALE: 4/1 SHEET 3 OF 3		