



Global sensitivity analysis of bistable energy harvesting systems via Sobol indices

João Pedro C. V. Norenberg¹ Americo Cunha Jr²

Samuel da Silva¹ Paulo Sérgio Varoto³


¹São Paulo State University – UNESP

²Rio de Janeiro State University – UERJ

³University of São Paulo – USP

SR40 - Stochastic Resonance 40 years

Perugia, Italy, September 13-15, 2021



L. Xuyang et al., *Overview of Spintronic Sensors With Internet of Things for Smart Living*. IEEE Transactions on Magnetics, 0018-9464, 2019.

*Picture from this reference.

Up to 78 million batteries will be discarded daily by 2025, researchers warn

An EU-funded project makes it plain: batteries need to live longer than the Internet of things (IoT) devices they power. A position paper published by the project outlines the key actions to power IoT devices reliably and sustainably.



CLIMATE CHANGE AND
ENVIRONMENT



ENERGY

SCIENTIFIC ADVANCES




© Dmitry Naumov, Shutterstock




CORDIS — European Commission, *Up to 78 million batteries will be discarded daily by 2025, researchers warn* (July 23, 2021)

ENERGY HARVESTING AS ALTERNATIVE FOR MICROPOWERING




- ▶ Capture wasted energy from external sources
- ▶ Store this wasted energy for future use
- ▶ Use the stored energy to supply other devices

Vibration Energy Harvesting Scale




Adapted from: <https://passive-components.eu/energy-harvesting-is-not-fiction-anymore-2/>

Monostable system driven by regular signal




S. Roundy, P. K. Wright and J. Rabaey, A study of low level vibrations as a power source for wireless sensor nodes. *Computer Communications*, 26: 1131-1144, 2003.

Bistable system driven by a noisy signal




F. Cottone, H. Vocca and L. Gammaitoni, Nonlinear energy harvesting. *Physical Review Letters*, 102: 080601, 2009.

Bistable system driven by regular signal (linear transduction)




A. Erturk, J. Hoffmann and D. J. Inman, *A piezomagnetoelastic structure for broadband vibration energy harvesting*. *Applied Physics Letters*, 2009.

Bistable system driven by regular signal (**nonlinear transduction**)



A Triplet, DD Quinn, *The effect of non-linear piezoelectric coupling on vibration-based energy harvesting*, Journal of Intelligent Material Systems and Structures, 2009.


Asymmetric bistable system driven by regular signal (nonlinear transduction)



W. Wang, . Cao, C. R. Bowen, D. J. Inman and J. Lin, *Performance enhancement of nonlinear asymmetric bistable energy harvesting from harmonic, random and human motion excitations*, *Applied Physics Letters*, 2018.

- ▶ Study variability effects on a asymmetric bistable energy harvester with nonlinear transduction, seeking to find paths to optimize the energy recovering process
- ▶ Apply global sensitivity analysis to:
 1. extract features of the dynamic behavior;
 2. identify the most sensitivity parameters.

Bistable harvester: symmetric + linear coupling




$$\ddot{x} + 2\xi\dot{x} - \frac{1}{2}x(1-x^2) - \chi v = f \cos(\Omega t)$$

$$\dot{v} + \lambda v + \kappa \dot{x} = 0$$

+ initial conditions

Bistable harvester: symmetric + nonlinear coupling




$$\ddot{x} + 2\xi\dot{x} - \frac{1}{2}x(1 - x^2) - \widehat{\Theta}(x)\chi v = f \cos(\Omega t)$$

$$\dot{v} + \lambda v + \widehat{\Theta}(x)\kappa \dot{x} = 0$$

+ initial conditions

$$\widehat{\Theta}(x) = (1 + \beta |x|)$$

Bistable harvester: asymmetric + nonlinear coupling



$$\ddot{x} + 2\xi\dot{x} - \frac{1}{2}x(1 + 2\delta x - x^2) - \hat{\Theta}(x)\chi v =$$


$$f \cos(\Omega t) + p \sin(\phi)$$

$$\dot{v} + \lambda v + \hat{\Theta}(x)\kappa \dot{x} = 0$$

+ initial conditions

$$\hat{\Theta}(x) = (1 + \beta |x|)$$

Bistable harvester: asymmetric + nonlinear coupling



$$\ddot{x} + 2\xi\dot{x} - \frac{1}{2}x(1 + 2\delta x - x^2) - \hat{\Theta}(x)\chi v =$$

$$f \cos(\Omega t) + p \sin(\phi)$$

$$\dot{v} + \lambda v + \hat{\Theta}(x)\kappa \dot{x} = 0$$

+ initial conditions

$$\hat{\Theta}(x) = (1 + \beta |x|)$$

$$P_{avg} = \frac{1}{T} \int_{t_0}^{t_0+T} \lambda v(t)^2 dt$$

Dynamic animation (symmetric + linear coupling)




Dynamic animation (symmetric + nonlinear coupling)




Dynamic animation (asymmetric + nonlinear coupling)




Time series (symmetric + linear coupling)



Time series (symmetric + nonlinear coupling)



Time series (asymmetric + nonlinear coupling)





Main contributions:

- ▶ Simpler probabilistic model constructions
- ▶ Nontrivial insight into the behavior
- ▶ Important step for robustness and optimization problems

Mathematical Model:

$$\text{Quantity of Interest} = \mathcal{M}(\text{system parameters})$$

$$Y = \mathcal{M}(x) , \quad x_i \sim \mathcal{U}(0, 1)$$

Hoeffding-Sobol decomposition:

$$Y = \mathcal{M}_0 + \sum_{i=1}^k \mathcal{M}_i(x_i) + \sum_{i < j}^k \mathcal{M}_{ij}(x_i, x_j) + \dots + \mathcal{M}_{1\dots k}(x_1 \dots x_k)$$

An **orthogonal decomposition** in terms of conditional expectations:

- ▶ $\mathcal{M}_0 = \mathbb{E}\{Y\}$
- ▶ $\mathcal{M}_i(x_i) = \mathbb{E}\{Y|x_i\} - \mathcal{M}_0$
- ▶ $\mathcal{M}_{ij}(x_i, x_j) = \mathbb{E}\{Y|x_i, x_j\} - \mathcal{M}_i - \mathcal{M}_j - \mathcal{M}_0$
- ▶ ...

Sobol' indices

First-order Sobol' indices:

$$S_i = \text{Var}[\mathcal{M}_i(x_i)] / \text{Var}[\mathcal{M}(\mathbf{x})]$$

(quantify the additive effect of each input separately)

Second-order Sobol' indices:

$$S_{ij} = \text{Var}[\mathcal{M}_{ij}(x_i, x_j)] / \text{Var}[\mathcal{M}(\mathbf{x})]$$

(quantify interaction effect of inputs X_i and X_j)



I.M. Sobol' *Global sensitivity indices for nonlinear mathematical models and their Monte Carlo estimates*. *Mathematics and Computers in Simulation*, 55(1-3):

271-280, 2001.

Polynomial Chaos Expansion:

$$Y = \mathcal{M}(\mathbf{x}) \approx \sum_{\alpha \in \mathcal{A}} y_\alpha \psi_\alpha(\mathbf{x})$$

Analytical calculation of Sobol' indices:


$$S_u = \frac{\sum_{\alpha \in \mathcal{A}_u} y_\alpha^2}{\sum_{\alpha \in \mathcal{A} \setminus 0} y_\alpha^2}$$

$$\mathcal{A}_u = \{\alpha \in \mathcal{A} : i \in u \iff \alpha_i \neq 0\}$$




B. Sudret, *Global sensitivity analysis using polynomial chaos expansions*. Reliability Engineering & System Safety, 2016, 93(7): 964–979, 2008.

Global sensitivity analysis framework




Mean power sensitivity (symmetric + linear piezo)

$$\beta = 0 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$




Mean power sensitivity (symmetric + nonlinear piezo)

$$\beta = 0.5 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$




Mean power sensitivity (symmetric + nonlinear piezo)

$$\beta = 1.0 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$




Mean power sensitivity (symmetric + nonlinear piezo)

$$\beta = 1.5 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$




Mean power sensitivity (symmetric + nonlinear piezo)

$$\beta = 2.0 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$




Mean power sensitivity (symmetric + nonlinear piezo)

$$\beta = 2.5 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$




Mean power sensitivity (symmetric + nonlinear piezo)

$$\beta = 3.0 \quad \phi = 0^\circ \quad f = 0.147 \quad \Omega = 0.8$$



Mean power sensitivity (asymmetric + nonlinear piezo)

$$\beta = 1.0 \quad \phi \in [-15^\circ, 15^\circ] \quad f = 0.147 \quad \Omega = 0.8$$



Sensitivities in a nutshell

parameter	sensitivity	optimal condition
ξ	no	-
χ	no	-
λ	low	high energy
κ	high	high energy
f	high	low and middle energy
Ω	high	all spectrum
β	low	high values
δ	no	-
ϕ	high	low and middle energy

Conclusions and perspectives



Findings:

- ▶ The order of importance of the parameters changes a lot with vibration regime
- ▶ Frequency and amplitude of excitation, asymmetric bias angle, and piezoelectric coupling at the electrical domain are the most influential parameters that affect the mean power harvested
- ▶ Bias angle is a better parameter to optimize the harvested power for middle and low forcing amplitudes
- ▶ Piezoelectric electrical properties are better parameters to optimize the harvested power for high forcing amplitude

Ongoing research:

- ▶ Uncertainty quantification for parameters disturbances
- ▶ Experimental analysis

Experimental analysis (ongoing research)



Acknowledgments



Institutional support:



Financial support:



Thank you for your attention!

americo.cunha@uerj.br

WEBSITE



www.americocunha.org



@AmericoCunhaJr



@AmericoCunhaJr



J. P. Norenberg, A. Cunha Jr, S. da Silva, P. S. Varoto,

Global sensitivity analysis of (a)symmetric energy harvesters,

[arXiv:2107.04647](https://arxiv.org/abs/2107.04647), 2021.

<https://arxiv.org/abs/2107.04647>

PAPER

