

Probabilistically Exercising

Tutorial 04

Prof. Americo Cunha Jr

Rio de Janeiro State University – UERJ

americo.cunha@uerj.br


www.americocunha.org



 @AmericoCunhaJr

 @AmericoCunhaJr

 @AmericoCunhaJr

 @AmericoCunhaJr



Training algebro-probabilistic skills

Show that:

- $\int_{-\infty}^{+\infty} \exp(-x^2) dx = \sqrt{\pi}$
- $\mathbb{E}\{X\} = \mu$ and $\mathbb{E}\{(X - \mathbb{E}\{X\})^2\} = \sigma^2$
when $X \sim \mathcal{N}(\mu, \sigma^2)$
- $\mathbb{E}\{X\} = \frac{(a+b)}{2}$ and $\mathbb{E}\{(X - \mathbb{E}\{X\})^2\} = \frac{(b-a)^2}{12}$
when $X \sim \mathcal{U}(a, b)$



Flip a coin experiment



Toss N times a coin that has probability p of coming up head.

Do you expect to see a sequence of 10 heads?



CoinFlip.m


```
1  clc; clear; close all
2
3  % number of tosses / head probability
4  Ntoss = 1000; p = 0.5;
5  % sequence of heads size
6  s = 10; Hseq = ones(1,s);
7  % experiment realizations (head = 1 / tail = 0)
8  HTexp = rand(1,Ntoss) < p;
9  disp('-----')
10 disp(' Flip a Coin Experiment')
11 disp('-----')
12 for i=1:Ntoss
13     if HTexp(i) == 1
14         disp(' H')
15     else
16         disp(' T')
17     end
18 end
19 H = sum(HTexp); T = Ntoss-H; N_Hseq = length(strfind(HTexp,Hseq));
20 disp(['Heads: ',num2str(H)])
21 disp(['Tails: ',num2str(T)])
22 disp(['Sequences with ',num2str(s), ' heads : ',num2str(N_Hseq)])
```



References



G. Grimmett and D. Welsh, **Probability: An Introduction**. Oxford University Press, 2 edition, 2014.



How to cite this material?


A. Cunha Jr, *Probabilistically Exercising*, Rio de Janeiro State University – UERJ, 2021.




 @AmericoCunhaJr

 @AmericoCunhaJr

 @AmericoCunhaJr

 @AmericoCunhaJr

These class notes may be shared under the terms of
Creative Commons BY-NC-ND 4.0 license,
for educational purposes only.



Content excluded from our Creative Commons license

- Portinari Coin:
<https://www.bcb.gov.br/cedulasemoedas/moedascomemorativas>

