

Acknowledgement

All praise and thanks are due to Allah Almighty, whose endless mercy, guidance, and support made it possible for us to successfully complete this project. Without His blessings, none of this would have been achieved. We would like to express our deepest gratitude to our supervisor, Dr. Simon Azzet, and Eng. Naglaa Saeed for their continuous support, valuable guidance, and constant encouragement throughout this journey. Their knowledge, advice, and supervision played a major role in the success of this work. We are also deeply grateful to our families for their endless love, patience, and support. They have always been a source of motivation, and their belief in us kept us going through all challenges. We would also like to thank HITU for providing the necessary resources and a supportive academic environment that contributed significantly to the completion of this project. The knowledge and experience

gained during our studies have greatly enhanced our understanding and helped in achieving this work.

Finally, we extend our sincere appreciation to everyone who contributed to this project, no matter how small their role was. Your support, encouragement, and kindness will always be remembered and appreciated.

Abstract

This project presents a smart solar energy system based on Artificial Intelligence to improve the efficiency of solar panel positioning and energy utilization. The system uses sensors (LDRs) to detect sunlight intensity from different directions, allowing the system to identify the strongest light source.

An ESP32 microcontroller processes the collected data and makes real-time decisions to control servo motors that adjust the position of the solar panel automatically. This ensures that the panel continuously aligns with the sun for maximum energy absorption throughout the day. The current version of the system focuses on real-time tracking and automatic adjustment; however, future enhancements can significantly improve its performance. These improvements may include AI-based prediction models to estimate sun movement more accurately, cloud detection systems to reduce energy loss during weather

changes, and IoT integration to monitor system performance remotely through mobile or web applications.

Additionally, the system can be expanded with data analytics features to analyze energy production over time and optimize efficiency. Alerts and notifications can also be added to inform users about system status, maintenance needs, or performance issues.

In conclusion, this project aims to provide an intelligent, efficient, and sustainable solar energy solution that reduces manual intervention and maximizes renewable energy usage. With further development, it can contribute to smarter energy management systems and support the transition toward clean energy technologies

➤ Introduction

This project presents a Smart Solar Energy System integrated with Artificial Intelligence (AI) designed to improve the efficiency and reliability of solar power generation. The system aims to automatically track the sun's position throughout the day, ensuring that solar panels are always oriented at the optimal angle to capture maximum sunlight.

In addition to sun tracking, the system incorporates automated cleaning mechanisms to remove dust and debris from the surface of solar panels, which can significantly reduce their efficiency over time.

Furthermore, it includes protective features to safeguard the panels against harsh environmental conditions such as rain and strong winds.

By combining IoT technologies, sensors, and intelligent decision-making algorithms, this project provides a modern, automated solution for enhancing solar energy utilization. The system reduces the need for human

intervention, increases energy output, and ensures long-term sustainability.

➤ **Problem Statement**

Solar energy systems are widely used as a clean and renewable source of energy. However, they face several challenges that reduce their overall efficiency and performance.

One of the main problems is that traditional solar panels are fixed in position, meaning they cannot continuously face the sun throughout the day. This results in a significant loss of potential energy. Additionally, dust and dirt accumulation on the surface of the panels can block sunlight and further decrease their efficiency.

Another issue is the exposure of solar panels to harsh environmental conditions such as heavy rain and strong winds, which may damage the system or reduce its lifespan. Moreover, most existing systems require manual

monitoring and maintenance, which increases operational costs and effort.

Therefore, there is a need for an intelligent, automated system that can maximize energy production, reduce maintenance requirements, and protect the solar panels from environmental factors.

➤ **Proposed Solution**

To overcome the limitations of traditional solar systems, this project proposes a Smart Solar Energy System integrated with AI and IoT technologies.

The system uses light sensors (LDRs) to detect the intensity of sunlight from different directions. Based on this data, a microcontroller (such as ESP32) processes the inputs and controls servo motors to automatically adjust the position of the solar panel toward the direction of maximum sunlight, ensuring optimal energy absorption.

In addition, an automated cleaning mechanism is implemented to periodically remove dust and dirt from the panel surface, maintaining high efficiency without human intervention. The system also includes environmental sensors (such as rain and wind sensors) to detect harsh conditions and activate protective

actions, such as adjusting the panel position to prevent damage. Furthermore, the system can be connected to a mobile application, allowing users to monitor performance, receive alerts, and control the system remotely. Overall, this solution enhances energy efficiency, reduces maintenance efforts, and provides a reliable and intelligent solar energy system.

➤ **System Overview**

The proposed system is a Smart Solar Energy System that combines hardware and software components to create an automated and efficient solution for solar power generation.

The system operates by continuously monitoring sunlight intensity using multiple light sensors placed around the solar panel. These sensors send real-time data to the microcontroller, which analyzes the inputs and determines the optimal direction for the panel. Based on this analysis, the system adjusts the panel position using servo motors to ensure maximum exposure to sunlight. mechanism that operates at scheduled intervals or when dust levels increase, helping maintain the panel's efficiency. Environmental sensors are also integrated to detect weather conditions such as rain and strong winds, allowing the system to take protective actions automatically.

The system is further enhanced with a mobile application

interface, enabling users to monitor system status, view performance data, and control certain functions remotely. Overall, the system provides a fully automated, intelligent, and user-friendly approach to improving solar energy utilization.

➤ **System Architecture**

The System Architecture illustrates the overall structure of the proposed smart solar system and how different components interact with each other.

The system is mainly divided into three layers:

1. Sensing Layer

This layer includes all sensors used in the system, such as:

- ❖ Light sensors (LDRs) to detect sunlight intensity from different directions
- ❖ Rain sensor to detect rainfall
- ❖ Wind sensor to measure wind speed

These sensors collect real-time data from the environment and send it to the processing unit.

2. Processing Layer

This layer is responsible for decision-making. It consists of a

microcontroller (ESP32) that:

- ❖ Receives data from sensors
- ❖ Analyzes the data using programmed logic or AI algorithms
- ❖ Determines the appropriate action (e.g., adjusting panel direction or activating protection system)

3. Actuation Layer

This layer includes the components that perform actions based on decisions, such as:


- ❖ Servo motors to move the solar panel
- ❖ Cleaning motor/system to remove dust
- ❖ Protection mechanisms to adjust panel position during harsh conditions

4. Communication Layer

This layer enables communication between the system and the user through:

- ❖ Wi-Fi module (built-in with ESP32)
- ❖ Mobile application for monitoring and control
- ❖ The interaction between these layers ensures that the system operates in a fully automated, efficient.

System Architecture



➤ **Hardware Components**

the hardware used in this project, it is important to understand that the system is built using different types of components that work together to achieve smart monitoring and control.

These components are divided into sensors, processing unit, and

actuators, where each part has a specific role in making the system work efficiently and automatically .. Hardware

Components

1. Voltage Sensor Module

- is responsible for measuring the electrical voltage produced by the solar panel or stored in the battery. It converts high voltage values into safe, readable signals that can be processed by the microcontroller.
- It measures high voltage values and converts them into a safe level that can be read by a microcontroller such as ESP32.

2. (L298N) Motor Driver

- **Definition:**

A module used to control motors.

- **Function:**

Controls motor direction and speed

- **Why it is Important:**

The ESP32 cannot drive motors directly, so a driver is required.

3. AC Current Sensor

- The current sensor module is used to measure the amount of electric current flowing in the system. This helps in monitoring the power generation and consumption in real time, ensuring system stability and efficiency.

19 | P a g e

4. Microcontroller (ESP32 38pin)

- **Definition:**

A powerful microcontroller

used to control electronic systems.

- **Features:**

- Built-in Wi-Fi and Bluetooth
- High processing speed
- Large number of GPIO pins (38 pins)

- **Function in the Project:**

Acts as the main controller (brain) that reads data from sensors and controls motors.

5. DC Water Pump

- **Definition:**

- A device used to move water.
- Pumps water from one place to another

- **Use in Project:**

Used for cooling or irrigation.

6. DC Gear Motor

- **Definition:**

A DC motor with gears to increase torque and reduce

speed.

- **Function:**

Provides high torque

- **Use in Project:**

Used to move heavy parts like the solar panel base.

7. MG996R Servo Motor

- **Definition:**

A motor that can rotate to a specific angle.

- **Features:**

Moves between 0° and 180°

- **Use in Project:**

Used to precisely adjust the angle of the solar panel.

8. Temperature & Humidity Sensor (DHT11)

- **Definition:**

A sensor used to measure temperature and humidity.

- **Function:**

➤ Measures temperature (°C)

➤ Measures humidity (%)

- **Use in Project:**

Monitoring environmental conditions to improve system efficiency.

9. Rain Sensor

- **Definition:**

A sensor used to detect the presence of water.

- **Function:**

Detects water level or leakage

- **Use in Project:**

Used for water detection and controlling the water system.

10. LDR Sensor (Light Dependent Resistor)

- **Definition:**

A light sensor whose resistance changes based on light intensity.

- **Function:**

Detects light level (bright/dark)

- **Use in Project:**

Helps track the sun's position for solar panel alignment.

11. Breadboard

- **Definition:**

A board used to connect electronic components without soldering.

- **Function:**

Helps in building and testing circuits

- **Advantage:**

Reusable and easy to modify.

12.

LCD 16x2 (I2C)

- **Definition:**

A display screen with 16 characters and 2 rows.

- **Function:**

Displays system data (temperature, voltage, status)

- **I2C Advantage:**

Uses fewer wires

4. Software Components

the system consists of several software components that work together to ensure efficient operation and full integration between all parts:

1. Embedded Software

The Arduino IDE is used to program the microcontroller (ESP32). It

continuously reads data from various sensors such as light, rain, and wind sensors.

The system processes this data and makes appropriate decisions,

such as adjusting the solar panel position or activating protection

and cleaning mechanisms. Additionally, the data is transmitted via Wi-Fi to enable real-time monitoring.

2. Front-End

The user interface is developed using HTML, CSS, and JavaScript to

display data in an interactive and user-friendly way.

It allows users to monitor system status, including light intensity,

weather conditions, and panel position. The interface is designed to be simple and well-organized for ease of use, even for non-technical users.

3. Back-End

Firebase is used as the back-end service to store and retrieve data in real time (Real-Time Database).

This enables instant display of sensor readings on the application

without delay. It also stores historical data for future performance

analysis and ensures secure and efficient communication between

the system and the application.

1. Overall Idea

The system is designed to:

- ❖ Generate energy from solar panels**
- ❖ Monitor performance using sensors**
- ❖ Use AI to optimize operation**
- ❖ Automatically clean and adjust the panels**

2. Main Components(Hardware System)

This is the physical part of the system:

- ❖ Solar panel (captures sunlight)**
- ❖ Battery/storage unit**
- ❖ Connections and basic electronics**
- ❖ It receives energy from the sun and converts it into electricity.**

3. AI System (System AI++)

This is the “brain” of the system:

- ❖ Analyzes sensor data**
- ❖ Makes decisions automatically**
- ❖ Controls movement and cleaning**

❖ It improves efficiency by adjusting panel direction and maintenance.

3. Data Components

- (Sensors _Data)

This block stores readings from sensors:

- ❖ Sensor _id (Primary Key)

- ❖ Temperature

- ❖ Humidity

- ❖ Voltage

- ❖ Current

- ❖ These values help the AI understand the system condition.

- (Energy _Data)

This block stores energy-related data:

- ❖ Energy _id (Primary Key)

- ❖ Energy values

- ❖ Data logs

- ❖ Used to track how much energy is produced

and system performance.

4. Supporting Systems

- **Servo Motors**

- ❖ **Used to move the solar panel**
- ❖ **Adjust direction toward the sun**
- ❖ **Helps maximize sunlight exposure.**

- **Cleaning System**

Includes:

- ❖ **Water pump**
- ❖ **Nozzles**
- ❖ **Wiper**
- ❖ **Automatically cleans the solar panel to maintain efficiency.**

- **Sensors**

Measure:

- ❖ **Temperature**
- ❖ **Voltage**
- ❖ **Provide real-time data to the system.**

5. How the System Works (Flow)

- ❖ **Sunlight hits the solar panel**
- ❖ **Hardware system converts it into electricity**
- ❖ **Sensors collect environmental and electrical data**
- ❖ **Data is stored in Sensors _Data**
- ❖ **AI system analyzes the data**
- ❖ **AI sends commands to:**
 - ❖ **Servo motors → adjust panel direction**
 - ❖ **Cleaning system → clean the panel**
 - ❖ **Energy data is saved in Energy _Data**

6. Key Purpose

The system aims to:

- ❖ **Increase energy efficiency**
- ❖ **Reduce manual work**
- ❖ **Enable smart automation using AI**