

Master Test Cases

Central portal · Admin console & server · Desktop agent (Windows / macOS / Linux). 128 test cases covering core functionality and every QA-phase defect (A1–A8, B1–B15). Execute each case and record Pass/Fail against the matching row in the Excel workbook.

Date: 2026-07-23

Rev: QA-01

Total: 128

Central: 23

Admin: 64

Agent: 41

Author: SmartEPT Dev

Central — 23 test cases

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
CEN-001	Portal & Auth	Admin login	Super-admin signs in to Central	Central portal reachable; valid super-admin account	1. Open the Central portal URL. 2. Enter valid email + password. 3. Submit.	super-admin credentials	Signed in; dashboard loads; role = super admin.	High Functional
CEN-002	Portal & Auth	Invalid login	Wrong password is rejected	Central reachable	1. Enter valid email + wrong password. 2. Submit.	wrong password	Login rejected with a clear message; no session created.	High Negative
CEN-003	Portal & Auth	Throttling	Repeated failed logins are throttled	Central reachable	1. Submit wrong credentials 10+ times quickly.	-	Further attempts are rate-limited (429/lockout); brute force blocked.	Medium Security
CEN-004	Provisioning	New tenant	Provision a new client company	Super admin signed in; provisioning secret configured	1. Create a new client/company with plan + seats. 2. Submit.	company name, plan, seat count	Tenant created; provisioning record + signed payload returned; appears in the client list.	High Functional
CEN-005	Provisioning	Secret signing	Provision requires the shared secret	Provisioning endpoint	1. Call provision without/with a wrong secret signature.	invalid signature	Request refused; no tenant created (secret-signed provisioning enforced).	High Security
CEN-006	Provisioning	Seat count	Seat count carries to the tenant	Tenant provisioned with N seats	1. Provision with N seats. 2. Open the tenant record.	seats=25	Tenant shows the licensed seat count; agent registration is bounded by it.	High Functional
CEN-007	Licensing	Issue licence	Issue an offline node-locked .lic	Tenant exists; RSA key pair configured (private key server-side only)	1. Open the tenant. 2. Issue licence with plan + expiry + node lock. 3. Download the .lic.	plan, expiry date, machine/node id	A signed .lic is generated and downloadable; private key never exposed in output or logs.	High Functional
CEN-008	Licensing	Renew with date	Renew a licence to a new expiry	An issued licence exists	1. Open the licence. 2. Pick a new expiry via the Renew date picker. 3. Confirm.	new expiry date	Licence renewed to the chosen date; new .lic reflects it; history kept (EPT-30).	High Functional
CEN-009	Licensing	Edit licence	Edit licence attributes	An issued licence exists	1. Open the licence. 2. Edit plan/seats/node. 3. Save.	revised plan/seats	Licence updated (PUT licences/{id}); re-issued .lic matches; audit recorded.	High Functional
CEN-010	Licensing	Signature validity	Tampered .lic is rejected by the product	A valid .lic issued	1. Modify a byte of the .lic. 2. Load it in the product server.	tampered .lic	Product rejects the licence (signature invalid); no activation.	High Security
CEN-011	Licensing	Node lock	Licence bound to the registered node	Node-locked .lic issued for machine A	1. Install the .lic on a different machine B.	wrong node	Licence refuses to validate on B; only the locked node activates.	High Security

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
CEN-012	Licensing	Eval period	7-day evaluation works then expires	Fresh install without a paid licence	1. Start the product in eval. 2. Advance the clock past 7 days.	eval window	Eval runs for 7 days then blocks per the hard wall; prompts for a licence.	Medium Functional
CEN-013	Downloads	Catalogue list	Downloads catalogue lists installers	Super admin; catalogue seeded	1. Open Central → Downloads.	-	Server + agent installers (Win/Linux/Mac) listed with version + notes (DB-backed).	Medium Functional
CEN-014	Downloads	Manage catalogue	Super admin adds/edits a download entry	Super admin	1. Add a new download (name, version, file, notes). 2. Save. 3. Verify it appears.	installer metadata	Entry saved and shown; client portal reflects it; legacy build-drop fallback still works.	Medium Functional
CEN-015	Downloads	Client access	Client sees deployment-aware downloads	Client tenant with a deployment model set	1. Sign in as the client. 2. Open Install & Downloads.	-	Client sees the installers relevant to their deployment (LAN / cloud); no other tenant's files.	Medium Functional
CEN-016	Pricing	Price calculator	Pricing calc computes plan totals	Pricing configured	1. Open the pricing calculator. 2. Select plan + cycle + seats + storage.	plan, Quarterly/Half-yearly/Annual, seats	Correct total incl. setup and cycle discounts; matches the plan config.	Medium Functional
CEN-017	Pricing	Setup invoice	Generate a setup invoice	Client + plan selected	1. Generate the setup invoice for a client.	client, plan	Branded invoice with GST + amounts; public pay link where configured.	Medium Functional
CEN-018	SSO	Ticket sign-in	Signed SSO ticket signs the tenant admin in	Client tenant provisioned; SSO enabled	1. From Central, open the client app via the SSO link (?sso=ticket).	signed ticket	Tenant admin lands signed-in on their SmartEPT console; ticket stripped from the URL.	High Integration
CEN-019	SSO	Expired ticket	Expired/invalid SSO ticket is refused	SSO enabled	1. Use an expired or tampered ticket.	invalid ticket	Sign-in refused with a clear message; falls back to the normal login.	High Security
CEN-020	Multi-tenant	Isolation	One tenant cannot see another's data	Two tenants A and B	1. As tenant A, attempt to open tenant B's licence/download/company by id or URL.	cross-tenant id	Access denied / not found; strict tenant isolation server-side.	High Security
CEN-021	Multi-tenant	Client login	Every client login is recorded	Client account	1. Client signs in. 2. Check the login record.	-	Login captured (who/when); visible to super admin.	Low Functional
CEN-022	Security	No private key leak	Private signing key never leaves the server	Licensing configured	1. Inspect API responses, downloads and logs during issue/renew.	-	Only the public verify key / signed .lic is ever emitted; the RSA private key is never present.	High Security
CEN-023	Security	Transport	Portal enforces HTTPS	Production Central	1. Attempt plain HTTP access.	-	Redirected/forced to HTTPS; no credentials over plain HTTP.	Medium Security

Admin (Console & Server) — 64 test cases

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
ADM-001	Auth & RBAC	Login	Admin signs in to the console	Console reachable; seeded admin	1. Open the console. 2. Enter email + password. 3. Submit.	admin@...	Signed in; session restored on refresh; role name shown.	High Functional
ADM-002	Auth & RBAC	Forced password	Temp-password user must change password	User created with a one-time temp password	1. Log in with the temp password.	temp password	Forced-password modal blocks the app until a new password is set.	Medium Functional

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
ADM-003	Auth & RBAC	Permission nav	Nav hides modules the role lacks	Non-admin role missing some permissions	1. Sign in as that role. 2. Inspect the sidebar.	manager/auditor	Only permitted modules show (dashboard/screenshots/... per permission).	High Functional B5
ADM-004	Auth & RBAC	API guard	Direct API call without permission is 403	Role without screenshot.view	1. Call GET /reports/screenshots with that token.	-	403 FORBIDDEN — server enforces the permission regardless of UI.	High Security B5
ADM-005	Auth & RBAC	Roles matrix	New granular permissions appear in the matrix	Company admin; Roles screen	1. Open Roles → Permissions for a role.	-	All permissions incl. meeting.* , audit.export, evidence.view, gate.override are listed and tickable.	Medium Functional B5
ADM-006	Auth & RBAC	Lockout guard	Super/Company admin keep full access	Company admin	1. Try to remove permissions from the Company Admin role.	-	Locked — those roles always keep full access (no self-lockout).	Medium Functional B5
ADM-007	Users	Create user	Create a login with a temp password	Company/HR admin	1. Users → Add. 2. Fill name/email/role. 3. Save.	new user	User created; one-time credentials shown once; user appears in the list.	High Functional
ADM-008	Users	Reset password	Reset a user's password	Existing user	1. Open the user → Reset password.	-	New temp password issued; must_change_password set.	Medium Functional
ADM-009	Users	Disable user	Soft-disable a login	Existing active user	1. Set the user status to DISABLED.	-	User can no longer sign in; record retained.	Medium Functional
ADM-010	Employees	Create employee	Add an employee with a shift	Org + shift exist	1. Employees → Add. 2. Fill code/name/shift/branch. 3. Save.	E-XXXX	Employee created and listed; linked login optional.	High Functional
ADM-011	Employees	Bulk import	Bulk onboard employees from CSV	CSV template	1. Employees → Bulk import. 2. Upload the CSV.	valid CSV	Rows imported; errors reported per row; valid rows created.	Medium Functional
ADM-012	Employees	Tracking mode	Set an employee to Presence-only / Excluded	Employee exists	1. Edit the employee → Tracking mode = Presence only.	-	Agent for that person captures no screenshots/activity (mode honoured in the bundle).	Medium Functional
ADM-013	Employees	Relieve	Offboard an employee	Active employee with devices	1. Employees → Relieve with a reason.	reason	Login disabled, agent stopped, seats freed; audit-logged.	Medium Functional
ADM-014	Organisation	CRUD	Manage branches/departments/teams /designations/shifts	Company admin	1. Org → add/edit/delete each type.	-	Entities saved, tenant-scoped, and selectable on the employee form.	Medium Functional
ADM-015	Organisation	Shift working days	Shift working days drive attendance	Shift with MON–FRI	1. Set working_days. 2. Observe attendance marking on a Saturday.	MON-FRI	Weekly-off days produce no ABSENT/late; only working days count.	Medium Functional
ADM-016	Holidays	Holiday calendar	Add a holiday and verify no ABSENT	HR admin	1. Add a company holiday. 2. Run the nightly attendance for that date.	holiday date	No ABSENT/late is recorded on the holiday.	Medium Functional
ADM-017	Policies	Assign policy	Assign a monitoring/screenshot policy	Policies exist	1. Assign a policy at company/team/employee level.	-	Most-specific assignment wins in the resolved agent bundle.	High Functional
ADM-018	Policies	Screenshot interval	10-minute policy resolves to 600s	Screenshot policy interval = 10 min	1. Fetch the agent bundle for a covered employee.	-	policies.screenshot.effective_interval_seconds = 600 and a policy_version is present.	High Functional B11
ADM-019	Policies	App/Web rules	Blocked app/site flagged as a violation	Application/Website policy with blocked items	1. Add a blocked app. 2. Agent opens it.	steam.exe	A compliance event is raised; action per policy (warn/screenshot).	Medium Functional

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
ADM-020	Attendance	Sheet view	Attendance sheet lists derived values	Attendance data present	1. Open Attendance for a date.	-	Rows show check-in/out, late, status + how each was derived (source columns).	Medium Functional B7 B8
ADM-021	Attendance	Regularize	Correct a day with a reason	HR admin; an existing row	1. Edit a day (status/in/out) with a reason. 2. Save.	reason	Row updated to MANUAL, reason kept on notes, audit-logged; feeds payroll.	High Functional
ADM-022	Attendance	Future checkout	Reject a future manual check-out	HR admin; server time = now	1. Set check-out later than now. 2. Save.	checkout > now	Rejected: 'Check-out time cannot be later than the current time.'	High Negative B9
ADM-023	Attendance	Overnight	Accept a valid overnight checkout	HR admin	1. Add in=22:00 (prev day), out=06:00 (today). 2. Save.	overnight	Accepted (out after in, not future); overnight handled.	Medium Functional B9
ADM-024	Attendance	Checkout > checkin	Reject checkout before checkin	HR admin	1. Set check-out earlier than check-in.	-	Rejected with a validation message.	Medium Negative B9
ADM-025	Biometric & Gate	Device setup	Add a cloud biometric device	HR admin	1. Biometric → add device (provider, API, IN/OUT machine ids). 2. Test connection.	eTimeOffice creds	Connection probe reports parsed punches; device saved.	High Functional B6
ADM-026	Biometric & Gate	Auto-sync	Punches sync automatically every 5 min	Active device; scheduler running	1. Wait for the 5-minute cycle (or Sync now).	-	Punches import without a manual click; last-sync counts shown.	High Functional B6
ADM-027	Biometric & Gate	Sync failure cap	Broken feed auto-disables after repeated failures	Device with wrong credentials	1. Let it fail repeatedly (5×).	bad creds	Device flips to ERROR and stops auto-syncing; Troubleshooting tile flags it.	Medium Negative B6
ADM-028	Biometric & Gate	Map employee	Map a biometric id to an employee	Unmapped punches exist	1. Biometric → map id → employee.	BIO-xxx	One employee → one active biometric id; historical punches backfilled.	Medium Functional
ADM-029	Biometric & Gate	Shift-aware checkout	Lunch OUT is not an early checkout	Mapped employee; day IN, OUT(lunch), IN, OUT(end)	1. Import the four punches.	09:00 IN,13:00 OUT,14:00 IN,18:00 OUT	Check-in=09:00, Check-out=18:00 (the lunch OUT is not the checkout).	High Functional B7
ADM-030	Biometric & Gate	Delayed recompute	A late end punch recomputes checkout	Employee currently 'still inside'	1. After IN/OUT/IN, later import the end OUT.	18:00 OUT arrives late	Checkout recomputes to the trailing OUT (idempotent).	Medium Functional B7
ADM-031	Biometric & Gate	Configurable late	Late per the configured arrival source	Company late_arrival_source set; shift start+grace	1. Import a first IN after the permitted time.	09:30 IN, permitted 09:10	Late minutes = 20; arrival source recorded; biometric-only employee also gets late.	High Functional B8
ADM-032	Biometric & Gate	Gate override	Admin emergency gate override is audited	Gate closed for an employee	1. Admin posts a gate override with a reason.	reason	Gate lifts; GATE_OVERRIDE + audit recorded; employee-role cannot override (403).	High Security A3
ADM-033	Breaks	Break report	Permitted vs actual with excess + reason	Break data present	1. Open the break report.	-	Per-type permitted/actual/excess with the employee's reason; meeting is never a break.	Medium Functional
ADM-034	Breaks	Conflict 409	Break while on a different break is rejected	Employee on Tea break	1. Start a Lunch break via the API without ending Tea.	-	409 STATUS_CONFLICT; single open status enforced.	High Negative A6 D1

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
ADM-035	Meetings	Schedule permission	Only a permitted role can schedule	Manager has meeting.schedule; auditor does not	1. As manager POST /meetings. 2. As auditor POST /meetings.	valid meeting	Manager → 201; auditor → 403.	High Security B5
ADM-036	Meetings	Cross-tenant	Cannot open another tenant's meeting	Meeting belongs to company B	1. As company A, GET that meeting by id.	-	404 (tenant scope) — no cross-tenant access.	High Security B5
ADM-037	Meetings	Modal on-theme	Meeting modal is centred and not clipped	Console; meeting screen	1. Open Schedule meeting at 100/125/150% zoom.	-	Modal centred, header/footer fixed, participant list scrolls inside, on-theme.	Medium UI B4
ADM-038	Meetings	Participation	Scheduled vs actual attendance	Meeting with sessions	1. Open the meeting's participation.	-	Per-participant scheduled/actual + ATTENDED/ABSENT/PENDING.	Low Functional
ADM-039	Screenshots & Evidence	Timeline	View an employee's screenshot timeline	screenshot.view permission; shots exist	1. Open the employee's screenshots for a date.	-	Thumbnails load (token-authed); every view is access-logged.	Medium Functional
ADM-040	Screenshots & Evidence	Violation evidence	Evidence modal shows only that violation's shots	A violation with a linked shot + unrelated interval shots	1. Violations → View evidence on the violation.	-	Modal shows only the linked shot(s); not the full-day wall.	High Functional B10
ADM-041	Screenshots & Evidence	Evidence tenant-safe	Cross-tenant evidence is refused	A violation in company B	1. As company A call /violations/{B}/evidence.	-	403 — tenant-guarded; no leakage.	High Security B10
ADM-042	Screenshots & Evidence	Expired evidence	Purged evidence reports EXPIRED	Violation captured a shot; retention purged it	1. Open its evidence.	-	available=false, reason=EXPIRED with a clear message (not a broken image).	Medium Functional B10
ADM-043	Live Dashboard	Break status live	Dashboard reflects break status in near real-time	Employee on a break	1. Watch the live dashboard.	-	Status shows BREAK (sub-type)/MEETING; flips promptly on a session event.	High Functional B1 B15
ADM-044	Live Dashboard	Break widgets	Break/idle/meeting widgets open the filtered list	Live dashboard	1. Click the Break widget.	-	Opens the SAME filtered live list as Active/Idle — never the Attendance tab.	High UI B2 B3
ADM-045	Live Dashboard	Totals parity	Dashboard totals match the reports	A day of data	1. Compare live/summary totals with the timeline report.	-	Active/idle/break totals agree across dashboard and reports.	Medium Functional A4 B15
ADM-046	Reports & Exports	Attendance CSV	Export attendance with derivation columns	export.data permission	1. Export attendance for a range.	-	CSV opens in Excel with check-in/out + source + late columns.	Medium Functional B7 B8
ADM-047	Reports & Exports	Productivity CSV	Export per-employee active/idle/break	export.data permission	1. Export productivity for a range.	-	Correct hh:mm totals per employee.	Low Functional
ADM-048	Reports & Exports	Permission	Export blocked without permission	Role without export.data	1. Attempt an export.	-	403 — export gated by permission.	Medium Security
ADM-049	Audit Trail	Explicit range	Audit honours the exact From/To	Auditor/admin; audit rows across dates	1. Set From/To to a specific window. 2. Search.	23-Jul 14:00–14:15	Only rows in that window return — never collapses to 'last hour'.	High Functional B13
ADM-050	Audit Trail	Pagination filters	Filters persist across pages	A filtered range with >1 page	1. Search, then page next.	per_page=1	Next-page link carries the From/To (and other) filters.	Medium Functional B13

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
ADM-051	Audit Trail	Invalid range	Invalid From>To shows a message	Audit screen	1. Set From after To. 2. Search/Export.	-	Clear 'From must be on or before To' message; no bad query.	Low Negative B13
ADM-052	Audit Trail	Export full	Export the full filtered audit trail	audit.export permission	1. Set filters. 2. Export CSV.	-	CSV = the full filtered result (not just the page), with a timezone column.	High Functional B14
ADM-053	Audit Trail	Formula safety	CSV neutralises spreadsheet-formula cells	An audit action starting with '='	1. Export and open the CSV.	action = "cmd()"	The leading = is prefixed with an apostrophe; Excel cannot execute it.	High Security B14
ADM-054	Audit Trail	Export permission	Export blocked without audit.export	Role lacking audit.export (e.g. manager)	1. Call /export/audit-logs.	-	403 — audit export gated by its own permission.	High Security B14
ADM-055	Audit Trail	No secrets	Export redacts secret-looking values	An audit row whose changes include a password/token key	1. Export and inspect the Details column.	-	Sensitive keys are blanked (***); no passwords/tokens in the file.	High Security B14
ADM-056	Ops & Troubleshooting	Diagnostics	System-health self-check runs	Company admin	1. Help → Troubleshooting → run checks.	-	DB, migrations, storage, mail, agents, OPcache, scheduler, biometric tiles show ok/warn/down with a fix link.	Medium Functional B6
ADM-057	Ops & Troubleshooting	Scheduler tile	Scheduler-health tile goes green	Task Scheduler runs schedule:run every minute	1. Open Troubleshooting after 2 minutes.	-	'Background scheduler' tile is green; turns red if schedule:run stops.	Medium Functional B6
ADM-058	Ops & Troubleshooting	Log viewer	In-app log tail for non-technical staff	Company admin	1. Open the log viewer.	-	Recent log lines shown with a 'copy for developer' option.	Low Functional
ADM-059	Ops & Troubleshooting	Storage cleanup	Bulk cleanup never touches attendance/audit	Company admin; date range	1. Run storage cleanup for a range.	-	Evidence/logs removed; attendance, breaks and the audit trail untouched; violation evidence protected by default.	Medium Functional
ADM-060	Licensing	Enter key	Admin sets/validates the licence key	Company admin	1. Licence → set key → validate.	licence key	Key stored; validation status + seats shown; daily phone-home.	Medium Functional
ADM-061	Integrations	API key	Create + revoke an API key	Company admin	1. Create an ingest/read key. 2. Revoke it.	-	Key created (shown once) and later revoked; scoped ingest/read.	Low Functional
ADM-062	Integrations	Outbound push	Push attendance to SmartPRS target	Outbound target configured	1. Trigger a push to the target.	SmartPRS endpoint	Signed attendance JSON delivered; failures don't break the app.	Low Integration
ADM-063	Storage & Backups	GCS config	Configure + test cloud storage	Company admin	1. Set GCS creds → Test.	-	Test succeeds; new evidence stored to GCS.	Low Functional
ADM-064	Storage & Backups	Backup now	Run a database backup	Company admin	1. Ops → Backup now.	-	A gzipped backup is created; newest N retained.	Low Functional

Agent (Desktop) — 41 test cases

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
AGT-001	Install & Pairing	Fresh install	Install the agent on a clean PC	Windows test PC; installer available	1. Run the installer. 2. Complete setup.	installer	Agent installs, starts, and shows the pairing/login screen.	High Functional
AGT-002	Install & Pairing	Upgrade install	Upgrade preserves pairing	Agent already paired	1. Install the newer build over it.	new build	Existing device pairing/token preserved; no re-registration needed.	High Functional
AGT-003	Install & Pairing	Register device	Device registers against the server	Valid employee login	1. Sign in on the agent. 2. Register the device.	device uuid	Device bound to the employee; a device token is issued.	High Functional
AGT-004	Install & Pairing	Seat limit	Registration bounded by licensed seats	All seats used	1. Try to register one more device.	-	Registration refused / requires an admin to free a seat.	Medium Negative
AGT-005	Consent	Consent wall	Consent required before tracking	Policy requires consent	1. First run. 2. Review + acknowledge consent.	-	No tracking until consent is recorded; consent hash stored.	High Functional
AGT-006	Login/Session	Login time shown	Login time never blanks	Paired agent	1. Log in. 2. Observe the 'logged in at' value.	-	Shows a real time (Loading → value); never blank or 'Invalid Date'.	High Functional A1
AGT-007	Login/Session	Offline login value	Cached login time on a fetch error	Agent online then briefly offline	1. Log in. 2. Drop the network. 3. Observe today panel.	-	Last server-confirmed login time is retained with an offline/last-synced hint.	Medium Functional A1
AGT-008	Login/Session	First login pinned	Re-login keeps the first login time	Logged in earlier today	1. Log out/in again later. 2. Check today.	-	The shown login time stays the FIRST login of the day, not the latest.	High Functional A2
AGT-009	Login/Session	Single device	2nd concurrent PC login is controlled	Employee already active on PC A	1. Log in on PC B.	-	409 SINGLE_SESSION_ACTIVE (or admin-controlled takeover), per policy.	Medium Negative
AGT-010	Gate-to-PC	No punch → no start	Gate blocks the session without a punch	Company gate enabled; no IN punch today	1. Sign in on the agent.	-	Gate wall shown; work session does not start (423 on attendance/tracking).	High Functional A3
AGT-011	Gate-to-PC	Open after punch	Session starts after a synced IN punch	Gate enabled	1. Punch IN at the reader. 2. Wait for sync. 3. Agent retries.	IN punch	Gate opens; tracking begins only after the verified punch.	High Functional A3
AGT-012	Gate-to-PC	No capture while denied	No tracking/screenshots while gate closed	Gate closed (pre-punch or punched-out)	1. Observe activity/screenshot posts.	-	Ingestion refused (423); nothing captured until the gate opens.	High Security A3
AGT-013	Gate-to-PC	Fail closed	Gate fails closed on a server error	Gate status endpoint unreachable; org not confirmed non-gated	1. Start the agent while the gate check errors.	-	Wall stays up and polls; never starts tracking on an unknown state.	High Security A3
AGT-014	Activity Tracking	Active/Idle	Active and idle stretches are recorded	Tracking running	1. Work, then leave idle past the threshold.	-	ACTIVE then IDLE segments recorded; durations correct.	High Functional A4
AGT-015	Activity Tracking	Lock → idle	Locking the PC forces idle	Tracking running	1. Lock the workstation.	-	Status forces IDLE instantly; no active time credited while locked.	High Functional A4
AGT-016	Activity Tracking	Display off / sleep	No capture while display-off/suspended	Tracking running	1. Turn the display off / sleep the PC.	-	No screenshots; idle/paused; resumes cleanly on wake.	Medium Functional A4

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
AGT-017	Breaks	One break at a time	Buttons prevent overlapping breaks	On a Tea break	1. Try to start a Lunch break.	-	Other break/meeting buttons disabled; 'end current break first'.	High Functional A6 D1
AGT-018	Breaks	Break elapsed	Break elapsed uses server time	On a break	1. Observe the running elapsed.	-	Elapsed advances on the server-corrected clock (not the local wall clock).	Medium Functional A5
AGT-019	Meetings	Join in window	Participant can join within the window	Employee is a participant; meeting live	1. Press the Meeting button.	-	Meeting status starts; only appears when authorised + in-window.	Medium Functional A7
AGT-020	Meetings	No break+meeting	Meeting and break cannot run together	In a meeting	1. Try to start a break (and vice-versa).	-	Rejected; meeting and break are mutually exclusive.	High Functional A7
AGT-021	Meetings	Non-participant	A non-participant cannot join	Employee not on the meeting	1. Attempt to join.	-	403 — server-authorised join only.	Medium Negative
AGT-022	Screenshots	Interval honoured	10-min policy = ~1 shot / 10 min	Screenshot policy interval 10 min; rebuilt agent	1. Run for ~30 minutes.	-	About 3 captures — NOT one per minute; the resolved interval is honoured.	High Functional B11
AGT-023	Screenshots	Live refresh	Interval change applies without restart	Agent running; admin changes the interval	1. Change the policy interval. 2. Wait for the next policy refresh.	10 → 5 min	New cadence applies live; the old timer is cleared (no double scheduler).	High Functional B11 D5
AGT-024	Screenshots	No stacked timers	Reconnect/refresh doesn't stack timers	Agent reconnects / policy re-applies	1. Force several policy refreshes.	-	Exactly one scheduler runs; capture rate stays at the configured interval.	High Functional B11
AGT-025	Screenshots	Violation evidence tag	A blocked-app shot carries a correlation id	on_blocked_app policy on	1. Open a blocked app.	-	A screenshot + a compliance event are posted sharing one correlation id (links on the server).	Medium Integration B10
AGT-026	Screenshots	Privacy raw-IP	No shot of a raw-IP/localhost page	exclude_ip_sites on; browser on a bare IP	1. Trigger a capture while a raw-IP page is in front.	http://10.x	No screenshot of that content is grabbed or stored.	Medium Security
AGT-027	Time Integrity	Server clock	Server-corrected time is used for stamps	Agent synced to the server	1. Compare stamped times with the server.	-	Stamps derive from the server offset + a monotonic base.	High Functional A5
AGT-028	Time Integrity	Clock forward	Moving the PC clock forward doesn't inflate time	Tracking running	1. Set the PC clock ahead by 2 hours.	clock +2h	Recorded durations follow real elapsed time, not the tampered clock.	High Security A5
AGT-029	Time Integrity	Clock backward	Moving the clock back doesn't shrink time	Tracking running	1. Set the PC clock back.	clock -1h	Elapsed cannot shrink; monotonic base protects duration.	High Security A5
AGT-030	Time Integrity	Offline reconcile	Offline events keep their order + times	Agent offline then reconnects	1. Generate events offline. 2. Reconnect and sync.	-	Events reconcile with server time; original sequence preserved.	Medium Functional A5
AGT-031	Exit & Tamper	Exit lock	Exit requires the admin password	exit_lock_enabled with a password set	1. Try to exit the agent from the tray.	wrong then right password	Plain Exit is replaced; wrong password blocked (5-try → lockout); correct password exits.	High Security A8

ID	MODULE	FEATURE	SCENARIO	PRECONDITIONS	STEPS	DATA	EXPECTED RESULT	PRIO / TYPE / REF
AGT-032	Exit & Tamper	Window close	Closing the window minimises to tray	Agent running	1. Click the window close (X).	-	App minimises to the tray; tracking continues (no silent exit).	Medium Functional A8
AGT-033	Exit & Tamper	Tamper log	Exit/stop/uninstall attempts are reported	Agent online	1. Attempt a blocked exit / service stop.	-	A tamper event is recorded on the server (attempt/outcome).	High Security A8
AGT-034	Exit & Tamper	Standard-user uninstall	Standard user cannot silently uninstall	Non-admin Windows user	1. Attempt to uninstall the agent.	-	Blocked by the NSIS uninstall guard (residual admin/physical limit documented).	High Security A8
AGT-035	Exit & Tamper	Authorized maintenance	Admin can perform maintenance/uninstall	Authorized admin	1. Perform the authorized maintenance/uninstall.	admin	Allowed and audited; the intended admin path works.	Medium Functional A8
AGT-036	Offline & Sync	Network drop	Data queues offline and drains on reconnect	Tracking running	1. Drop the network for a while. 2. Reconnect.	-	Events/screenshots stash locally and upload on reconnect; nothing lost.	High Functional
AGT-037	Offline & Sync	Pending screenshots	Stashed captures retry until delivered	Uploads failed while offline	1. Reconnect.	-	Pending shots drain via the retry loop; duplicates avoided.	Medium Functional
AGT-038	Cross-platform	macOS login time	macOS shows correct login + org timezone	macOS agent build	1. Sign in on macOS.	-	Login time + durations correct; timestamps org-consistent (no locale drift).	High Functional B12
AGT-039	Cross-platform	macOS sleep/wake	Ordering holds after sleep/wake	macOS agent	1. Sleep then wake the Mac.	-	Event ordering + durations remain correct after wake.	Medium Functional B12
AGT-040	Cross-platform	macOS clock change	Local time change doesn't corrupt times	macOS agent	1. Change the Mac's local time.	-	Server-time authority keeps recorded durations correct.	Medium Security B12
AGT-041	Cross-platform	Linux agent	Linux build tracks correctly	Linux agent build	1. Run active/idle + a break on Linux.	-	Active/idle + break durations recorded correctly.	Low Functional