

# PDR WORLD

## MASTER PRODUCT CATALOGUE 2024-2025

### Empowering Global Connectivity

Discover our comprehensive suite of state-of-the-art optical fiber solutions, carrier-grade passive and active components, advanced cable management systems, and precision testing equipment.

[www.pdrworld.com](http://www.pdrworld.com)

[info@pdrworld.com](mailto:info@pdrworld.com)

ISO 9001:2015 & 14001:2015 Certified

# Table of Contents

---

## Active Components

- Active Optical Cable (AOC)
- Direct Attached Cable (DAC)
- 100G & 100G BIDI
- SFP+ 10G Dual Fiber
- 1G SFP Dual Fiber
- 400G
- Copper SFP+
- Bypass Switch
- Optical Line Protection System (OLPS)
- SFP+ 10G BIDI
- 1G SFP BIDI
- 25G & 25G BIDI
- 40G
- Smart SFP Transceiver

## Passive Components

- Armoured Patchcord
- Bare Fiber Adapter
- Cassette Cleaner
- Fiber Optic Cleaner Pen
- CWDM Mux / DeMux Module
- FanOut Patch Cords
- Fiber Optic Connector, Field Installable
- SC/APC to SC/UPC Adapter
- Loop Back Patch Cord
- Mode Conditioning Patchcord
- Fiber Optic Cleaner Pen MPO
- POF — Plastic Optical Fiber Patchcord
- SMPTE Cable Assembly
- VFL — Visual Fault Locator
- Variable Fiber Attenuator
- Bendiboot Patchcord
- CAT 6 Patch Cord
- CPRI Patchcord
- DWDM Mux/DeMux Module
- Fiber Spool / Fiber Drum
- Fiber Optic Patch Cords & Pigtails
- LC Uniboot Patchcord
- Mating Sleeve / Alignment Sleeve
- MPO Cable Assembly
- PLC Splitter
- Rapid Push Cable Assembly
- Splice-On Connector (SOC)

## Specialty Drones

- Drone Optical Fiber Kit

## Cable Management Devices

- CAT 6 Patch Panel
- Heat Shrink Splice Closure
- Home Termination Box (HTB)
- Rack Mount Fiber Management System
- Fiber Distribution Box (FDB)
- Fiber Optic Splitter Closure GJS 2016
- Optical Distribution Frames
- Optical Fiber Wall Mount Enclosure

## Test and Measurement Equipment

- EasyCheck V2 Digital Fiber Endface Inspector
- Fusion Splicer PDR618H
- Next Gen Optical Fusion Splicer (OPM + VFL)
- PON Power Meter
- EasyGet WiFi Wireless Fiber Endface Microscope
- Mini Optical Power Meter
- Pocket OTDR
- Regular Optical Power Meter

ACTIVE COMPONENTS

# Active Optical Cable (AOC)

*Highly reliable transceiver alternative*

Highly reliable transceiver alternative

## Key Features

- Highly reliable transceiver alternative
- Embedded optical transceivers
- Lighter and more flexible than copper DAC

## Applications

- High Performance Computing
- Campus Networks
- Hyperscale Data Centers

## Technical Specifications

| Parameter / Specification | Value / Detail         |
|---------------------------|------------------------|
| Cable Type                | Multimode Fiber        |
| Data Rate                 | 10G / 25G / 40G / 100G |
| Reach                     | Up to 100m             |

PASSIVE COMPONENTS

# Armoured Patchcord

*Stainless steel interlocking armour protection*

Stainless steel interlocking armour protection

## Key Features

- Stainless steel interlocking armour protection
- High crush and rodent resistance
- Retains flexibility of standard patchcords

## Applications

- Harsh Environments
- Industrial Plants
- Direct Burial / Outdoor

## Technical Specifications

| Parameter / Specification | Value / Detail  |
|---------------------------|-----------------|
| Armour Material           | Stainless Steel |
| Fiber Type                | SM / MM         |
| Jacket Type               | LSZH / PVC / PE |

PASSIVE COMPONENTS

# Variable Fiber Attenuator

Digital variable fiber attenuator with up to 60 dB attenuation range

Digital variable fiber attenuator with up to 60 dB attenuation range

## Key Features

- Attenuation range up to 60 dB (SM)
- Digital attenuating mode
- Calibrated wavelengths: 1310 nm / 1490 nm / 1550 nm

## Applications

- Test and Measurement
- Fiber Optic Lab Use
- Optical Link Simulation

## Technical Specifications

| Parameter / Specification | Value / Detail              |
|---------------------------|-----------------------------|
| Attenuation Range         | 40 dB / 60 dB               |
| Calibrated Wavelengths    | 1310 nm / 1490 nm / 1550 nm |
| Fiber Mode                | SM                          |
| Attenuating Mode          | Digital                     |

PASSIVE COMPONENTS

# Bare Fiber Adapter

*Temporary link for bare optical fiber*

Temporary link for bare optical fiber

## Key Features

- Temporary link for bare optical fiber
- Push-button fiber locking mechanism
- Easy cleaning and maintenance

## Applications

- Lab Testing
- Emergency Field Restoration
- Fiber Spool Testing

## Technical Specifications

| Parameter / Specification | Value / Detail    |
|---------------------------|-------------------|
| Interface Types           | SC / LC / FC / ST |
| Ferrule                   | Zirconia Ceramic  |
| Insertion Loss            | < 0.2 dB          |



PASSIVE COMPONENTS

# Bendiboot Patchcord

*90-degree angled boot design*

90-degree angled boot design

## Key Features

- 90-degree angled boot design
- Prevents micro-bending losses at the connector
- Minimizes cable footprint in tight spaces

## Applications

- High-Density Data Centres
- Tight Space Routing
- Wall-Mount Enclosures

## Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Boot Angle                | 90°            |
| Connector Options         | LC, SC         |
| Cable Diameter            | 1.6mm / 2.0mm  |

ACTIVE COMPONENTS

# Bypass Switch

*Automatic bypass of optical path on failure*

Automatic bypass of optical path on failure

## Key Features

- Automatic bypass of optical path on failure
- Maintains network continuity
- Low insertion loss

## Applications

- Network Security Systems
- Inline Monitoring
- Fail-safe Architectures

## Technical Specifications

| Parameter / Specification | Value / Detail       |
|---------------------------|----------------------|
| Function                  | Optical path control |
| Insertion Loss            | < 1.0 dB             |
| Switching Time            | < 10ms               |

PASSIVE COMPONENTS

# Cassette Cleaner

*High-performance dry cleaning technology*

High-performance dry cleaning technology

## Key Features

- High-performance dry cleaning technology
- Anti-static properties prevent dust re-accumulation
- Replaceable cleaning tape reels

## Applications

- Lab Testing Environments
- Optical Network Maintenance
- Production Lines

## Technical Specifications

| Parameter / Specification | Value / Detail                |
|---------------------------|-------------------------------|
| Clean Cycles              | 400+ cleans per reel          |
| Compatibility             | SC, FC, ST, LC, MU, MPO, MTRJ |
| Material                  | Ultra-clean micro-fiber cloth |

CABLE MANAGEMENT DEVICES

# CAT 6 Patch Panel

*High speed Network distribution panel*

High speed Network distribution panel

## Key Features

- High speed Network distribution panel
- Confirms to ISO/IEC standards
- Cable management bar included

## Applications

- Enterprise LAN
- AV over IP setups
- Server Room Copper Distribution

## Technical Specifications

| Parameter / Specification | Value / Detail  |
|---------------------------|-----------------|
| Ports                     | 24 / 48 Port    |
| Category                  | Cat 6 UTP/STP   |
| Size                      | 1U / 2U 19-inch |

PASSIVE COMPONENTS

# CAT 6 Patch Cord

*High-speed copper patch cord*

High-speed copper patch cord

## Key Features

- High-speed copper patch cord
- Factory terminated and tested
- Snagless boot design

## Applications

- LAN Networking
- Server Racks
- Workstation Connectivity

## Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Category                  | Cat 6          |
| Connector                 | RJ45           |
| Jacket                    | PVC / LSZH     |

PASSIVE COMPONENTS

# Fiber Optic Cleaner Pen

*One-click cleaning mechanism*

One-click cleaning mechanism

## Key Features

- One-click cleaning mechanism
- Extendable nozzle for recessed connectors
- Lint-free anti-static microfiber fabric

## Applications

- Field Maintenance
- Data Centre Operations
- FTTx Installations

## Technical Specifications

| Parameter / Specification | Value / Detail                      |
|---------------------------|-------------------------------------|
| Ferrule Compatibility     | 1.25mm (LC/MU) / 2.5mm (SC/FC/ST)   |
| Clean Cycles              | 800+ cleans per pen                 |
| Application               | In-adapter or standalone connectors |

PASSIVE COMPONENTS

# CPRI Patchcord

*Outdoor waterproof fiber optic assembly*

Outdoor waterproof fiber optic assembly

## Key Features

- Outdoor waterproof fiber optic assembly
- Harsh environment protection
- Compatible with RRU/BBU

## Applications

- 5G Cell Towers
- FTTA Deployments
- Outdoor Broadcast

## Technical Specifications

| Parameter / Specification | Value / Detail      |
|---------------------------|---------------------|
| Connector Type            | ODVA/IP/FX/PDLC/NSN |
| Cable Type                | Armored / Tactical  |
| IP Rating                 | IP67                |

PASSIVE COMPONENTS

# CWDM Mux / DeMux Module

*Coarse WDM for cost-effective bandwidth expansion*

Coarse WDM for cost-effective bandwidth expansion

## Key Features

- Coarse WDM for cost-effective bandwidth expansion
- High isolation and low insertion loss
- Passive operation (no power required)

## Applications

- Metro Access Networks
- Enterprise DCI
- CATV Infrastructure

## Technical Specifications

| Parameter / Specification | Value / Detail     |
|---------------------------|--------------------|
| Channel Count             | 4 / 8 / 16 / 18 Ch |
| Spacing                   | 20nm               |
| Operating Temp            | -40Â°C to +85Â°C   |



ACTIVE COMPONENTS

# Direct Attached Cable (DAC)

*Hot-swappable direct attach copper cable*

Hot-swappable direct attach copper cable

## Key Features

- Hot-swappable direct attach copper cable
- Low power consumption
- Pre-terminated with SFP+ connectors

## Applications

- Top-of-Rack (ToR) Switching
- Server Interconnects
- Storage Area Networks

## Technical Specifications

| Parameter / Specification | Value / Detail         |
|---------------------------|------------------------|
| Cable Type                | Twinax Copper          |
| Data Rate                 | 10G / 25G / 40G / 100G |
| Length                    | 0.5m to 7m             |

SPECIALTY DRONES

# Drone Optical Fiber Kit

*Secure, jam-proof fiber-optic communication for defence and FPV drones.*

Secure, jam-proof fiber-optic communication for defence and FPV drones.

## Key Features

- Fiber-tethered data link — immune to jamming, interception, and RF interference
- Secure real-time HD / 4K + thermal video downlink
- Lightweight payload spool for FPV and tactical UAVs
- Selectable fiber length from 1 km to 50 km (custom lengths on request)

## Applications

- Defence ISR & secure communications
- FPV reconnaissance & tactical missions
- Perimeter / border surveillance
- EW / jam-resistant operations

## Technical Specifications

| Parameter / Specification | Value / Detail                          |
|---------------------------|-----------------------------------------|
| Fiber Length              | 1-50 km, selectable (custom available)  |
| Camera                    | 4K / Thermal                            |
| Data Link                 | Secure fiber-optic — EW / jam-resistant |
| Deployment                | High-speed aerial spooling              |

PASSIVE COMPONENTS

# DWDM Mux/DeMux Module

*Dense WDM for maximum fiber utilization*

Dense WDM for maximum fiber utilization

## Key Features

- Dense WDM for maximum fiber utilization
- Based on thin film filter or AWG technology
- High channel isolation

## Applications

- Long Haul Core Networks
- High Capacity DCI
- 5G Fronthaul

## Technical Specifications

| Parameter / Specification | Value / Detail      |
|---------------------------|---------------------|
| Channel Count             | 8 / 16 / 40 / 80 Ch |
| Spacing                   | 100GHz / 50GHz      |
| Grid                      | ITU Standard        |

TEST AND MEASUREMENT EQUIPMENT

# EasyCheck V2 Digital Fiber Endface Inspector

*Desktop digital fiber inspector*

Desktop digital fiber inspector

## Key Features

- Desktop digital fiber inspector
- Large integrated display screen
- Automated pass/fail analysis software

## Applications

- Factory Quality Control (QC)
- Cable Assembly Production
- Lab Testing

## Technical Specifications

| Parameter / Specification | Value / Detail         |
|---------------------------|------------------------|
| Display                   | Integrated LCD         |
| Analysis                  | IEC Standard Pass/Fail |
| Image Storage             | SD Card / USB          |

TEST AND MEASUREMENT EQUIPMENT

# EasyGet WiFi Wireless Fiber Endface Microscope

*Wireless transmission to smartphone/tablet*

Wireless transmission to smartphone/tablet

## Key Features

- Wireless transmission to smartphone/tablet
- Eliminates direct eye exposure to lasers
- High-resolution endface imaging

## Applications

- Connector Endface Inspection
- Transceiver Port Checking
- Patch Panel Cleaning Verification

## Technical Specifications

| Parameter / Specification | Value / Detail          |
|---------------------------|-------------------------|
| Connectivity              | WiFi / USB              |
| Magnification             | 400X                    |
| App Support               | iOS / Android / Windows |

PASSIVE COMPONENTS

# FanOut Patch Cords

*Small form factor high-density assembly*

Small form factor high-density assembly

## Key Features

- Small form factor high-density assembly
- Breakout multi-fiber to simplex/duplex
- Precision MT ferrule

## Applications

- High-Density Racks
- SAN Switches
- Core Routing

## Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Connector A               | MTP/MPO        |
| Connector B               | LC/SC/FC/ST    |
| Fiber Count               | 8 / 12 / 24    |

CABLE MANAGEMENT DEVICES

# Fiber Distribution Box (FDB)

*Compact termination box for building premises*

Compact termination box for building premises

## Key Features

- Compact termination box for building premises
- Connects drop cable with feeder cable
- Integrates splicing and splitting

## Applications

- FTTx Distribution Nodes
- Multi-Dwelling Units (MDU)
- Street Cabinets

## Technical Specifications

| Parameter / Specification | Value / Detail       |
|---------------------------|----------------------|
| Capacity                  | 4 to 32 Cores        |
| Environment               | Indoor/Outdoor IP65  |
| Splitter Support          | Cassette or Tube PLC |

PASSIVE COMPONENTS

# Fiber Spool / Fiber Drum

*Precision low-stress winding technique*

Precision low-stress winding technique

## Key Features

- Precision low-stress winding technique
- Available with custom fiber types and lengths
- Rugged flange design for safe transport

## Applications

- Lab Simulation Testing
- Emergency Network Restoration
- Field Deployment Dispatch

## Technical Specifications

| Parameter / Specification | Value / Detail             |
|---------------------------|----------------------------|
| Lengths Available         | 500m, 1km, 2km, Custom     |
| Fiber Options             | G.652D, G.657A, OM3, OM4   |
| Spool Material            | High-Impact Plastic / Wood |



PASSIVE COMPONENTS

# Fiber Optic Connector, Field Installable

*Fast Field Assembly Optical Connector*

Fast Field Assembly Optical Connector

## Key Features

- Fast Field Assembly Optical Connector
- No epoxy or polishing required
- Index matching gel inside

## Applications

- FTTx Drop Cable Termination
- Emergency Repairs
- LAN Installations

## Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Connector Type            | SC / LC / FC   |
| Polishing                 | UPC / APC      |
| Assembly Time             | < 2 minutes    |

PASSIVE COMPONENTS

# Fiber Optic Patch Cords & Pigtails

*Broadest choice of patchcords in the industry*

Broadest choice of patchcords in the industry

## Key Features

- Broadest choice of patchcords in the industry
- 100% interferometry tested
- Low insertion and high return loss

## Applications

- Telecom Networks
- FTTH Drop Cables
- Optical Distribution Frames

## Technical Specifications

| Parameter / Specification | Value / Detail                   |
|---------------------------|----------------------------------|
| Fiber Type                | SM (G.652D/G.657) / MM (OM1-OM5) |
| Connectors                | LC/SC/FC/ST/E2000                |
| Insertion Loss            | < 0.3 dB                         |

TEST AND MEASUREMENT EQUIPMENT

# Fusion Splicer PDR618H

*Handheld, small and light*

Handheld, small and light

## Key Features

- Handheld, small and light
- Core alignment technology
- Fast 8s splicing and 26s tube heating

## Applications

- Outside Plant Splicing
- FTTH Drop Cables
- Emergency Network Repair

## Technical Specifications

| Parameter / Specification | Value / Detail    |
|---------------------------|-------------------|
| Alignment                 | Core to Core      |
| Battery                   | 5800mAh Pluggable |
| Display                   | High-res LCD      |

CABLE MANAGEMENT DEVICES

# Heat Shrink Splice Closure

*Heat shrink sealing for harsh environments*

Heat shrink sealing for harsh environments

## Key Features

- Heat shrink sealing for harsh environments
- Accommodates multiple splice trays
- Excellent waterproof and dustproof performance

## Applications

- Outside Plant (OSP) Networks
- Long Haul Routes
- Underground Splicing

## Technical Specifications

| Parameter / Specification | Value / Detail               |
|---------------------------|------------------------------|
| Sealing Type              | Heat Shrink                  |
| Capacity                  | Up to 288 Cores              |
| Environment               | Aerial/Buried/Manhole (IP68) |

CABLE MANAGEMENT DEVICES

# Fiber Optic Splitter Closure GJS 2016

*Mechanical sealing structure*

Mechanical sealing structure

## Key Features

- Mechanical sealing structure
- Oval shaped cable port entrances in base
- Supports direct splicing and branching

## Applications

- FTTx Distribution Splicing
- Aerial Messenger Wire
- Wall/Pole Mount Splices

## Technical Specifications

| Parameter / Specification | Value / Detail      |
|---------------------------|---------------------|
| Sealing Type              | Mechanical          |
| Shape                     | Horizontal / Dome   |
| Ports                     | Multiple entry/exit |

CABLE MANAGEMENT DEVICES

# Home Termination Box (HTB)

*Aesthetic design for indoor customer premises*

Aesthetic design for indoor customer premises

## Key Features

- Aesthetic design for indoor customer premises
- Provides fiber termination points and housing
- Wall mountable

## Applications

- FTTH Customer Premises
- Residential Broadband
- Office Workstations

## Technical Specifications

| Parameter / Specification | Value / Detail    |
|---------------------------|-------------------|
| Capacity                  | 1 to 4 Cores      |
| Material                  | ABS plastic       |
| Size                      | Compact footprint |

PASSIVE COMPONENTS

# SC/APC to SC/UPC Adapter

*Hybrid fixed type adapter converter*

Hybrid fixed type adapter converter

## Key Features

- Hybrid fixed type adapter converter
- Converts APC polish to UPC polish
- Zero attenuation design

## Applications

- Network Integration
- Test Equipment Interfacing
- Cross-connection

## Technical Specifications

| Parameter / Specification | Value / Detail    |
|---------------------------|-------------------|
| Fiber Type                | Single Mode 9/125 |
| Loss                      | 0dB               |
| Housing                   | Plastic/Metal     |

PASSIVE COMPONENTS

# LC Uniboot Patchcord

Single-jacket duplex design saves 50% space

Single-jacket duplex design saves 50% space

## Key Features

- Single-jacket duplex design saves 50% space
- Optimized for high-density environments
- Tool-less reversible polarity

## Applications

- Spine-Leaf Architectures
- SAN Networks
- High-Density MPO Breakouts

## Technical Specifications

| Parameter / Specification | Value / Detail         |
|---------------------------|------------------------|
| Fiber Type                | OM3 / OM4 / SM         |
| Polarity                  | A-B / A-A (Reversible) |
| Cable Diameter            | 2.0mm / 3.0mm          |



PASSIVE COMPONENTS

# Loop Back Patch Cord

*Provides return signal for testing*

Provides return signal for testing

## Key Features

- Provides return signal for testing
- Compact housing design
- High stability and reliability

## Applications

- Equipment Burn-in Testing
- Network Diagnostics
- Transceiver Loopback

## Technical Specifications

| Parameter / Specification | Value / Detail           |
|---------------------------|--------------------------|
| Connector Type            | LC / SC / MPO            |
| Fiber Type                | Single-mode / Multi-mode |
| Attenuation               | Customizable             |

PASSIVE COMPONENTS

# Mating Sleeve / Alignment Sleeve

*Precision split sleeve for accurate alignment*

Precision split sleeve for accurate alignment

## Key Features

- Precision split sleeve for accurate alignment
- Available in Zirconia Ceramic or Phosphor Bronze
- Low insertion loss coupling

## Applications

- Adapter Manufacturing
- Bare Fiber Testing
- Temporary Splicing

## Technical Specifications

| Parameter / Specification | Value / Detail                 |
|---------------------------|--------------------------------|
| Material                  | Ceramic / Bronze               |
| Inner Diameter            | 2.5mm (SC/FC/ST) / 1.25mm (LC) |
| Durability                | >1000 matings                  |

TEST AND MEASUREMENT EQUIPMENT

# Mini Optical Power Meter

*Pocket-sized, lightweight design*

Pocket-sized, lightweight design

## Key Features

- Pocket-sized, lightweight design
- High precision measurements
- Long battery life with auto-off

## Applications

- Daily Fiber Link Testing
- Attenuation Measurement
- Optical Power Checks

## Technical Specifications

| Parameter / Specification | Value / Detail                 |
|---------------------------|--------------------------------|
| Calibrated Wavelengths    | 850/1300/1310/1490/1550/1625nm |
| Detector                  | InGaAs                         |
| Power                     | AAA Batteries / USB            |

PASSIVE COMPONENTS

# Mode Conditioning Patchcord

*Eliminates differential mode delay (DMD) effects*

Eliminates differential mode delay (DMD) effects

## Key Features

- Eliminates differential mode delay (DMD) effects
- Enables Gigabit Ethernet over legacy MM fiber
- Offset single-mode to multi-mode splice

## Applications

- Gigabit Ethernet LX/LH
- Legacy Fiber Upgrades
- Campus Networks

## Technical Specifications

| Parameter / Specification | Value / Detail           |
|---------------------------|--------------------------|
| Offset                    | Precision core alignment |
| Cable Type                | Duplex zipcord           |
| Connectors                | SC/LC/FC                 |

PASSIVE COMPONENTS

# MPO Cable Assembly

High-density multi-fiber connector system

High-density multi-fiber connector system

## Key Features

- High-density multi-fiber connector system
- Precision molded MT ferrule
- Push-pull latching mechanism

## Applications

- 40G/100G Networks
- Data Center Backbone
- High-Density Interconnects

## Technical Specifications

| Parameter / Specification | Value / Detail      |
|---------------------------|---------------------|
| Fiber Count               | 8/12/24/48          |
| Polarity                  | Type A / B / C      |
| Insertion Loss            | Standard / Low Loss |

PASSIVE COMPONENTS

# Fiber Optic Cleaner Pen MPO

*Designed specifically for multi-fiber connectors*

Designed specifically for multi-fiber connectors

## Key Features

- Designed specifically for multi-fiber connectors
- Cleans both male (with pins) and female (without pins) MPO/MTP
- Easy pushing motion engagement

## Applications

- Hyperscale Data Centres
- 40G/100G/400G Networks
- Backbone Cabling

## Technical Specifications

| Parameter / Specification | Value / Detail  |
|---------------------------|-----------------|
| Connector Type            | MPO / MTP       |
| Clean Cycles              | 600+ cleans     |
| Cleaning Action           | Dry cloth sweep |

TEST AND MEASUREMENT EQUIPMENT

# Next Gen Optical Fusion Splicer (OPM + VFL)

*Integrated OPM and VFL modules*

Integrated OPM and VFL modules

## Key Features

- Integrated OPM and VFL modules
- Core alignment technology for ultra-low loss
- Fast 8s splicing and 18s heating times

## Applications

- Backbone Network Construction
- High-Precision Laboratory Splicing
- Advanced Field Maintenance

## Technical Specifications

| Parameter / Specification | Value / Detail              |
|---------------------------|-----------------------------|
| Alignment Method          | Core-to-Core                |
| Integrated Tools          | OPM (-70~+6dBm), VFL (10mW) |
| Battery Capacity          | >250 splice/heat cycles     |

CABLE MANAGEMENT DEVICES

# Optical Distribution Frames

*Multi-purpose high-capacity distribution frame*

Multi-purpose high-capacity distribution frame

## Key Features

- Multi-purpose high-capacity distribution frame
- High-quality ABS plastic or metal build
- Efficient cable routing and protection

## Applications

- Telecom Central Office
- Main Distribution Area (MDA)
- Large Data Centers

## Technical Specifications

| Parameter / Specification | Value / Detail              |
|---------------------------|-----------------------------|
| Capacity                  | Up to 576 Cores             |
| Type                      | Floor standing / Rack mount |
| Pigtail Management        | Integrated                  |



ACTIVE COMPONENTS

# Optical Line Protection System (OLPS)

*Uses spare optical fiber to build a backup path*

Uses spare optical fiber to build a backup path

## Key Features

- Uses spare optical fiber to build a backup path
- Automatic route switching on fiber break
- Real-time line status monitoring

## Applications

- DWDM Networks
- Long Haul Transmission
- Critical Infrastructure

## Technical Specifications

| Parameter / Specification | Value / Detail          |
|---------------------------|-------------------------|
| Protection Type           | 1+1 / 1:1               |
| Switching Time            | < 20ms                  |
| Monitoring                | Real-time optical power |

PASSIVE COMPONENTS

# PLC Splitter

*Planar Lightwave Circuit technology*

Planar Lightwave Circuit technology

## Key Features

- Planar Lightwave Circuit technology
- Uniform power splitting
- Broad operating wavelength

## Applications

- FTTH/PON Networks
- CATV Links
- Optical Signal Distribution

## Technical Specifications

| Parameter / Specification | Value / Detail                    |
|---------------------------|-----------------------------------|
| Split Ratio               | 1×2 up to 1×128                   |
| Wavelength                | 1260nm - 1650nm                   |
| Packaging                 | Bare fiber / Blockless / Cassette |

TEST AND MEASUREMENT EQUIPMENT

# Pocket OTDR

*Ultra-compact smartphone-sized form factor*

Ultra-compact smartphone-sized form factor

## Key Features

- Ultra-compact smartphone-sized form factor
- Fast boot-up and auto-test functionality
- Event map view for intuitive fault location

## Applications

- Last-Mile FTTx Troubleshooting
- Quick Field Checks
- Access Network Installation

## Technical Specifications

| Parameter / Specification | Value / Detail                  |
|---------------------------|---------------------------------|
| Dynamic Range             | 22dB to 26dB                    |
| Fiber Type                | Single-mode / Multimode Options |
| Display                   | Touchscreen LCD                 |

PASSIVE COMPONENTS

# POF — Plastic Optical Fiber Patchcord

*Large PMMA core for easy alignment*

Large PMMA core for easy alignment

## Key Features

- Large PMMA core for easy alignment
- Immune to electromagnetic interference (EMI)
- Cost-effective for short-range links

## Applications

- Automotive Networking
- Industrial Control Systems
- Home AV Connections

## Technical Specifications

| Parameter / Specification | Value / Detail                 |
|---------------------------|--------------------------------|
| Core Material             | Polymethyl Methacrylate (PMMA) |
| Wavelength                | 650nm                          |
| Core Diameter             | 1mm (Typical)                  |

TEST AND MEASUREMENT EQUIPMENT

# PON Power Meter

*Pass-through measurement for live PON*

Pass-through measurement for live PON

## Key Features

- Pass-through measurement for live PON
- Simultaneous testing of 1310/1490/1550nm
- Burst mode measurement for 1310nm upstream

## Applications

- FTTx Network Turn-up
- PON Maintenance
- OLT/ONT Verification

## Technical Specifications

| Parameter / Specification | Value / Detail   |
|---------------------------|------------------|
| Wavelengths               | 1310/1490/1550nm |
| Network Type              | BPON/EPON/GPON   |
| Display                   | Color LCD        |

CABLE MANAGEMENT DEVICES

# Rack Mount Fiber Management System

19" Rack Mount fiber-optic enclosure

19

## Key Features

- 19" Rack Mount fiber-optic enclosure
- Slide-out drawer for easy access
- Modular adapter panels

## Applications

- Data Center Racks
- Telecom Central Office
- Enterprise Server Rooms

## Technical Specifications

| Parameter / Specification | Value / Detail        |
|---------------------------|-----------------------|
| Capacity                  | Up to 144 cores (4U)  |
| Material                  | Cold rolled steel     |
| Mounting                  | Standard 19-inch rack |

PASSIVE COMPONENTS

# Rapid Push Cable Assembly

*FTTX smart pushable preterminated drop solution*

FTTX smart pushable preterminated drop solution

## Key Features

- FTTX smart pushable preterminated drop solution
- Eliminates field splicing
- Designed for microduct deployment

## Applications

- FTTH Last Mile
- Microduct Installations
- MDU Deployments

## Technical Specifications

| Parameter / Specification | Value / Detail  |
|---------------------------|-----------------|
| Cable Outer Dia           | 2.0mm to 5.0mm  |
| Connector                 | SC/APC Pushable |
| Tensile Strength          | High            |

TEST AND MEASUREMENT EQUIPMENT

# Regular Optical Power Meter

*Auto-wavelength recognition capability*

Auto-wavelength recognition capability

## Key Features

- Auto-wavelength recognition capability
- Wide dynamic measurement range
- Backlit LCD for low-light environments

## Applications

- Link Acceptance Testing
- Power Level Monitoring
- Optical Loss Measurement

## Technical Specifications

| Parameter / Specification | Value / Detail                  |
|---------------------------|---------------------------------|
| Wavelength Range          | 800nm to 1700nm                 |
| Calibrated Wavelengths    | 850/1300/1310/1490/1550/1625nm  |
| Power Range               | -70 to +10 dBm / -50 to +26 dBm |



## ACTIVE COMPONENTS

# 100G & 100G BIDI

*High-density 100G transmission*

---

High-density 100G transmission

## Key Features

---

- High-density 100G transmission
- BIDI variant saves fiber infrastructure
- Low insertion loss

## Applications

---

- Enterprise Core
- Carrier Routing
- Metro Networks

# Technical Specifications

| Parameter / Specification | Value / Detail    |
|---------------------------|-------------------|
| Form Factor               | QSFP28            |
| Data Rate                 | 100G              |
| Connector                 | LC / MPO          |
| DOM Support               | Yes               |
| Wavelength                | CWDM4 / LR4 / SR4 |
| Operating Temp            | 0°C to 70°C       |

## ACTIVE COMPONENTS

# SFP+ 10G BIDI

*Doubles fiber capacity using WDM technology*

---

Doubles fiber capacity using WDM technology

## Key Features

---

- Doubles fiber capacity using WDM technology
- Hot-swappable
- Built-in digital diagnostic monitoring

## Applications

---

- Access Networks
- Enterprise LAN
- Campus Networks

## Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Form Factor               | SFP+           |
| Data Rate                 | 10G            |
| Connector                 | LC Simplex     |
| DOM Support               | Yes            |
| Wavelength                | 1270nm/1330nm  |
| Operating Temp            | 0°C to 70°C    |

## ACTIVE COMPONENTS

# SFP+ 10G Dual Fiber

*Standard dual-fiber 10G transmission*

---

Standard dual-fiber 10G transmission

## Key Features

---

- Standard dual-fiber 10G transmission
- Broad vendor compatibility
- High reliability

## Applications

---

- SAN / NAS
- Edge Routing
- Data Center Racks

# Technical Specifications

| Parameter / Specification | Value / Detail          |
|---------------------------|-------------------------|
| Form Factor               | SFP+                    |
| Data Rate                 | 10G                     |
| Connector                 | LC Duplex               |
| DOM Support               | Yes                     |
| Wavelength                | 850nm / 1310nm / 1550nm |
| Operating Temp            | 0°C to 70°C             |

## ACTIVE COMPONENTS

# 1G SFP BIDI

*Cost-effective 1G bi-directional link*

---

Cost-effective 1G bi-directional link

## Key Features

---

- Cost-effective 1G bi-directional link
- Single fiber optimization
- Low power dissipation

## Applications

---

- FTTH
- Access Rings
- CPE Equipment

## Technical Specifications

| Parameter / Specification | Value / Detail          |
|---------------------------|-------------------------|
| Form Factor               | SFP                     |
| Data Rate                 | 1.25G                   |
| Connector                 | LC Simplex / SC Simplex |
| DOM Support               | Yes                     |
| Wavelength                | 1310nm/1550nm           |
| Operating Temp            | -40°C to +85°C          |



## ACTIVE COMPONENTS

# 1G SFP Dual Fiber

*Legacy compatible 1G module*

---

Legacy compatible 1G module

## Key Features

---

- Legacy compatible 1G module
- Wide operating temperature range
- Cost-effective

## Applications

---

- Legacy Switching
- Enterprise Access
- Industrial Ethernet

# Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Form Factor               | SFP            |
| Data Rate                 | 1.25G          |
| Connector                 | LC Duplex      |
| DOM Support               | Yes            |
| Wavelength                | 850nm / 1310nm |
| Operating Temp            | -40°C to +85°C |

ACTIVE COMPONENTS

# 25G & 25G BIDI

*Optimized for 5G fronthaul*

Optimized for 5G fronthaul

## Key Features

- Optimized for 5G fronthaul
- Low latency
- Single fiber bi-directional transmission (BIDI)

## Applications

- 5G Fronthaul
- High-Speed Access
- Server Connectivity

# Technical Specifications

| Parameter / Specification | Value / Detail      |
|---------------------------|---------------------|
| Form Factor               | SFP28               |
| Data Rate                 | 25G                 |
| Connector                 | LC Duplex / Simplex |
| DOM Support               | Yes                 |
| Wavelength                | 850nm / 1310nm      |
| Operating Temp            | -40°C to +85°C      |

## ACTIVE COMPONENTS

# 400G

*Next-generation high-capacity throughput*

---

Next-generation high-capacity throughput

## Key Features

---

- Next-generation high-capacity throughput
- Low power consumption
- Hot-pluggable form factor

## Applications

---

- Hyperscale Data Centers
- Core Routing
- 5G Backhaul

# Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Form Factor               | QSFP-DD / OSFP |
| Data Rate                 | 400G           |
| Connector                 | LC / MPO       |
| DOM Support               | Yes            |
| Wavelength                | 850nm / 1310nm |
| Operating Temp            | 0°C to 70°C    |

## ACTIVE COMPONENTS

# 40G

*Reliable mid-tier aggregation*

---

Reliable mid-tier aggregation

## Key Features

---

- Reliable mid-tier aggregation
- Hot-pluggable
- IEEE 802.3ba compliant

## Applications

---

- Mid-tier Aggregation
- Data Center Edge
- SAN Switches

# Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Form Factor               | QSFP+          |
| Data Rate                 | 40G            |
| Connector                 | LC / MPO       |
| DOM Support               | Yes            |
| Wavelength                | 850nm / 1310nm |
| Operating Temp            | 0°C to 70°C    |



## ACTIVE COMPONENTS

# Copper SFP+

*RJ-45 interface for twisted pair copper*

---

RJ-45 interface for twisted pair copper

## Key Features

---

- RJ-45 interface for twisted pair copper
- Up to 30m reach on Cat6a/7
- Auto-negotiation

## Applications

---

- Server Connectivity
- ToR Switches
- Legacy Copper Infrastructure

# Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Form Factor               | SFP+           |
| Data Rate                 | 10G Base-T     |
| Connector                 | RJ-45          |
| DOM Support               | No             |
| Wavelength                | N/A            |
| Operating Temp            | 0°C to 70°C    |

ACTIVE COMPONENTS

# Smart SFP Transceiver

*Integrated OAM (Operations, Administration, and Maintenance)*

Integrated OAM (Operations, Administration, and Maintenance)

## Key Features

- Integrated OAM (Operations, Administration, and Maintenance)
- Real-time performance monitoring
- Micro-loopback capability

## Applications

- Service Provider Edge
- Mobile Backhaul
- SLA Monitoring

## Technical Specifications

| Parameter / Specification | Value / Detail         |
|---------------------------|------------------------|
| Interface                 | 1G / 10G SFP           |
| Protocol                  | IEEE 802.3ah / 802.1ag |
| Diagnostics               | DDM/DOM                |
| Latency                   | Ultra-Low              |

PASSIVE COMPONENTS

# SMPTE Cable Assembly

Hybrid fiber and copper camera cable

Hybrid fiber and copper camera cable

## Key Features

- Hybrid fiber and copper camera cable
- Ruggedized and dirt protected connectors
- Compliant with SMPTE 311M and 304M

## Applications

- HDTV Broadcasting
- Stadium Infrastructure
- Mobile OB Vans

## Technical Specifications

| Parameter / Specification | Value / Detail                    |
|---------------------------|-----------------------------------|
| Components                | 2 SM Fibers + 4 Copper Conductors |
| Jacket                    | PUR / Lemo                        |
| Durability                | > 2000 Mating Cycles              |

PASSIVE COMPONENTS

# Splice-On Connector (SOC)

*Factory-polished endface ensures low loss*

Factory-polished endface ensures low loss

## Key Features

- Factory-polished endface ensures low loss
- Eliminates need for epoxy and field polishing
- Compatible with standard fusion splicers

## Applications

- FTTx Drop Cables
- Data Centre Links
- Field Repair & Maintenance

## Technical Specifications

| Parameter / Specification | Value / Detail  |
|---------------------------|-----------------|
| Insertion Loss (IL)       | < 0.2dB         |
| Return Loss (RL)          | > 60dB (APC)    |
| Assembly Method           | Fusion Splicing |

PASSIVE COMPONENTS

# VFL — Visual Fault Locator

Bright 650nm visible red laser

Bright 650nm visible red laser

## Key Features

- Bright 650nm visible red laser
- Continuous and flashing modes
- Ruggedized metal housing for field use

## Applications

- Fault Location
- Continuity Testing
- Fiber Identification

## Technical Specifications

| Parameter / Specification | Value / Detail |
|---------------------------|----------------|
| Output Power              | 1mW (Standard) |
| Wavelength                | 650nm          |
| Detection Range           | Up to 10km     |

CABLE MANAGEMENT DEVICES

# Optical Fiber Wall Mount Enclosure

*Two door wall mounted enclosure*

Two door wall mounted enclosure

## Key Features

- Two door wall mounted enclosure
- Secure lockable doors
- Separate compartments for splicing and patching

## Applications

- Building Distribution
- Security Camera Hubs
- Campus Networks

## Technical Specifications

| Parameter / Specification | Value / Detail    |
|---------------------------|-------------------|
| Capacity                  | Up to 96 Cores    |
| Type                      | Indoor Wall Mount |
| Security                  | Keyed locks       |