

PDR WORLD

MASTER PRODUCT CATALOGUE 2024-2025

Empowering Global Connectivity

Discover our comprehensive suite of state-of-the-art optical fiber solutions, carrier-grade passive and active components, advanced cable management systems, and precision testing equipment.

www.pdrworld.com

info@pdrworld.com

ISO 9001:2015 & 14001:2015 Certified

Table of Contents

Active Components

- Active Optical Cable (AOC)
- Direct Attached Cable (DAC)
- 100G & 100G BIDI
- SFP+ 10G Dual Fiber
- 1G SFP Dual Fiber
- 400G
- Copper SFP+
- Bypass Switch
- Optical Line Protection System (OLPS)
- SFP+ 10G BIDI
- 1G SFP BIDI
- 25G & 25G BIDI
- 40G
- Smart SFP Transceiver

Passive Components

- Armoured Patchcord
- Bare Fiber Adapter
- Cassette Cleaner
- Fiber Optic Cleaner Pen
- CWDM Mux / DeMux Module
- FanOut Patch Cords
- Fiber Optic Connector, Field Installable
- SC/APC to SC/UPC Adapter
- Loop Back Patch Cord
- Mode Conditioning Patchcord
- Fiber Optic Cleaner Pen MPO
- POF — Plastic Optical Fiber Patchcord
- SMPTE Cable Assembly
- VFL — Visual Fault Locator
- Variable Fiber Attenuator
- Bendiboot Patchcord
- CAT 6 Patch Cord
- CPRI Patchcord
- DWDM Mux/DeMux Module
- Fiber Spool / Fiber Drum
- Fiber Optic Patch Cords & Pigtails
- LC Uniboot Patchcord
- Mating Sleeve / Alignment Sleeve
- MPO Cable Assembly
- PLC Splitter
- Rapid Push Cable Assembly
- Splice-On Connector (SOC)

Specialty Drones

- Drone Optical Fiber Kit

Cable Management Devices

- CAT 6 Patch Panel
- Heat Shrink Splice Closure
- Home Termination Box (HTB)
- Rack Mount Fiber Management System
- Fiber Distribution Box (FDB)
- Fiber Optic Splitter Closure GJS 2016
- Optical Distribution Frames
- Optical Fiber Wall Mount Enclosure

Test and Measurement Equipment

- EasyCheck V2 Digital Fiber Endface Inspector
- Fusion Splicer PDR618H
- Next Gen Optical Fusion Splicer (OPM + VFL)
- PON Power Meter
- EasyGet WiFi Wireless Fiber Endface Microscope
- Mini Optical Power Meter
- Pocket OTDR
- Regular Optical Power Meter

ACTIVE COMPONENTS

Active Optical Cable (AOC)

Highly reliable transceiver alternative

Highly reliable transceiver alternative

Key Features

- Highly reliable transceiver alternative
- Embedded optical transceivers
- Lighter and more flexible than copper DAC

Applications

- High Performance Computing
- Campus Networks
- Hyperscale Data Centers

Technical Specifications

Parameter / Specification	Value / Detail
Cable Type	Multimode Fiber
Data Rate	10G / 25G / 40G / 100G
Reach	Up to 100m

PASSIVE COMPONENTS

Armoured Patchcord

Stainless steel interlocking armour protection

Stainless steel interlocking armour protection

Key Features

- Stainless steel interlocking armour protection
- High crush and rodent resistance
- Retains flexibility of standard patchcords

Applications

- Harsh Environments
- Industrial Plants
- Direct Burial / Outdoor

Technical Specifications

Parameter / Specification	Value / Detail
Armour Material	Stainless Steel
Fiber Type	SM / MM
Jacket Type	LSZH / PVC / PE

PASSIVE COMPONENTS

Variable Fiber Attenuator

Digital variable fiber attenuator with up to 60 dB attenuation range

Digital variable fiber attenuator with up to 60 dB attenuation range

Key Features

- Attenuation range up to 60 dB (SM)
- Digital attenuating mode
- Calibrated wavelengths: 1310 nm / 1490 nm / 1550 nm

Applications

- Test and Measurement
- Fiber Optic Lab Use
- Optical Link Simulation

Technical Specifications

Parameter / Specification	Value / Detail
Attenuation Range	40 dB / 60 dB
Calibrated Wavelengths	1310 nm / 1490 nm / 1550 nm
Fiber Mode	SM
Attenuating Mode	Digital

PASSIVE COMPONENTS

Bare Fiber Adapter

Temporary link for bare optical fiber

Temporary link for bare optical fiber

Key Features

- Temporary link for bare optical fiber
- Push-button fiber locking mechanism
- Easy cleaning and maintenance

Applications

- Lab Testing
- Emergency Field Restoration
- Fiber Spool Testing

Technical Specifications

Parameter / Specification	Value / Detail
Interface Types	SC / LC / FC / ST
Ferrule	Zirconia Ceramic
Insertion Loss	< 0.2 dB

PASSIVE COMPONENTS

Bendiboot Patchcord

90-degree angled boot design

90-degree angled boot design

Key Features

- 90-degree angled boot design
- Minimizes cable footprint in tight spaces
- Prevents micro-bending losses at the connector

Applications

- High-Density Data Centres
- Wall-Mount Enclosures
- Tight Space Routing

Technical Specifications

Parameter / Specification	Value / Detail
Boot Angle	90°
Connector Options	LC, SC
Cable Diameter	1.6mm / 2.0mm

ACTIVE COMPONENTS

Bypass Switch

Automatic bypass of optical path on failure

Automatic bypass of optical path on failure

Key Features

- Automatic bypass of optical path on failure
- Maintains network continuity
- Low insertion loss

Applications

- Network Security Systems
- Inline Monitoring
- Fail-safe Architectures

Technical Specifications

Parameter / Specification	Value / Detail
Function	Optical path control
Insertion Loss	< 1.0 dB
Switching Time	< 10ms

PASSIVE COMPONENTS

Cassette Cleaner

High-performance dry cleaning technology

High-performance dry cleaning technology

Key Features

- High-performance dry cleaning technology
- Anti-static properties prevent dust re-accumulation
- Replaceable cleaning tape reels

Applications

- Lab Testing Environments
- Optical Network Maintenance
- Production Lines

Technical Specifications

Parameter / Specification	Value / Detail
Clean Cycles	400+ cleans per reel
Compatibility	SC, FC, ST, LC, MU, MPO, MTRJ
Material	Ultra-clean micro-fiber cloth

CABLE MANAGEMENT DEVICES

CAT 6 Patch Panel

High speed Network distribution panel

High speed Network distribution panel

Key Features

- High speed Network distribution panel
- Confirms to ISO/IEC standards
- Cable management bar included

Applications

- Enterprise LAN
- AV over IP setups
- Server Room Copper Distribution

Technical Specifications

Parameter / Specification	Value / Detail
Ports	24 / 48 Port
Category	Cat 6 UTP/STP
Size	1U / 2U 19-inch

PASSIVE COMPONENTS

CAT 6 Patch Cord

High-speed copper patch cord

High-speed copper patch cord

Key Features

- High-speed copper patch cord
- Factory terminated and tested
- Snagless boot design

Applications

- LAN Networking
- Server Racks
- Workstation Connectivity

Technical Specifications

Parameter / Specification	Value / Detail
Category	Cat 6
Connector	RJ45
Jacket	PVC / LSZH

PASSIVE COMPONENTS

Fiber Optic Cleaner Pen

One-click cleaning mechanism

One-click cleaning mechanism

Key Features

- One-click cleaning mechanism
- Extendable nozzle for recessed connectors
- Lint-free anti-static microfiber fabric

Applications

- Field Maintenance
- Data Centre Operations
- FTTx Installations

Technical Specifications

Parameter / Specification	Value / Detail
Ferrule Compatibility	1.25mm (LC/MU) / 2.5mm (SC/FC/ST)
Clean Cycles	800+ cleans per pen
Application	In-adapter or standalone connectors

PASSIVE COMPONENTS

CPRI Patchcord

Outdoor waterproof fiber optic assembly

Outdoor waterproof fiber optic assembly

Key Features

- Outdoor waterproof fiber optic assembly
- Harsh environment protection
- Compatible with RRU/BBU

Applications

- 5G Cell Towers
- FTTA Deployments
- Outdoor Broadcast

Technical Specifications

Parameter / Specification	Value / Detail
Connector Type	ODVA/IP/FX/PDLC/NSN
Cable Type	Armored / Tactical
IP Rating	IP67

PASSIVE COMPONENTS

CWDM Mux / DeMux Module

Coarse WDM for cost-effective bandwidth expansion

Coarse WDM for cost-effective bandwidth expansion

Key Features

- Coarse WDM for cost-effective bandwidth expansion
- High isolation and low insertion loss
- Passive operation (no power required)

Applications

- Metro Access Networks
- Enterprise DCI
- CATV Infrastructure

Technical Specifications

Parameter / Specification	Value / Detail
Channel Count	4 / 8 / 16 / 18 Ch
Spacing	20nm
Operating Temp	-40Â°C to +85Â°C

ACTIVE COMPONENTS

Direct Attached Cable (DAC)

Hot-swappable direct attach copper cable

Hot-swappable direct attach copper cable

Key Features

- Hot-swappable direct attach copper cable
- Low power consumption
- Pre-terminated with SFP+ connectors

Applications

- Top-of-Rack (ToR) Switching
- Server Interconnects
- Storage Area Networks

Technical Specifications

Parameter / Specification	Value / Detail
Cable Type	Twinax Copper
Data Rate	10G / 25G / 40G / 100G
Length	0.5m to 7m

SPECIALTY DRONES

Drone Optical Fiber Kit

Secure, jam-proof fiber-optic communication for defence and FPV drones.

Secure, jam-proof fiber-optic communication for defence and FPV drones.

Key Features

- Fiber-tethered data link — immune to jamming, interception, and RF interference
- Secure real-time HD / 4K + thermal video downlink
- Lightweight payload spool for FPV and tactical UAVs
- Selectable fiber length from 1 km to 50 km (custom lengths on request)

Applications

- Defence ISR & secure communications
- FPV reconnaissance & tactical missions
- Perimeter / border surveillance
- EW / jam-resistant operations

Technical Specifications

Parameter / Specification	Value / Detail
Fiber Length	1-50 km, selectable (custom available)
Camera	4K / Thermal
Data Link	Secure fiber-optic — EW / jam-resistant
Deployment	High-speed aerial spooling

PASSIVE COMPONENTS

DWDM Mux/DeMux Module

Dense WDM for maximum fiber utilization

Dense WDM for maximum fiber utilization

Key Features

- Dense WDM for maximum fiber utilization
- Based on thin film filter or AWG technology
- High channel isolation

Applications

- Long Haul Core Networks
- High Capacity DCI
- 5G Fronthaul

Technical Specifications

Parameter / Specification	Value / Detail
Channel Count	8 / 16 / 40 / 80 Ch
Spacing	100GHz / 50GHz
Grid	ITU Standard

TEST AND MEASUREMENT EQUIPMENT

EasyCheck V2 Digital Fiber Endface Inspector

Desktop digital fiber inspector

Desktop digital fiber inspector

Key Features

- Desktop digital fiber inspector
- Large integrated display screen
- Automated pass/fail analysis software

Applications

- Factory Quality Control (QC)
- Cable Assembly Production
- Lab Testing

Technical Specifications

Parameter / Specification	Value / Detail
Display	Integrated LCD
Analysis	IEC Standard Pass/Fail
Image Storage	SD Card / USB

TEST AND MEASUREMENT EQUIPMENT

EasyGet WiFi Wireless Fiber Endface Microscope

Wireless transmission to smartphone/tablet

Wireless transmission to smartphone/tablet

Key Features

- Wireless transmission to smartphone/tablet
- High-resolution endface imaging
- Eliminates direct eye exposure to lasers

Applications

- Connector Endface Inspection
- Patch Panel Cleaning Verification
- Transceiver Port Checking

Technical Specifications

Parameter / Specification	Value / Detail
Connectivity	WiFi / USB
Magnification	400X
App Support	iOS / Android / Windows

PASSIVE COMPONENTS

FanOut Patch Cords

Small form factor high-density assembly

Small form factor high-density assembly

Key Features

- Small form factor high-density assembly
- Breakout multi-fiber to simplex/duplex
- Precision MT ferrule

Applications

- High-Density Racks
- SAN Switches
- Core Routing

Technical Specifications

Parameter / Specification	Value / Detail
Connector A	MTP/MPO
Connector B	LC/SC/FC/ST
Fiber Count	8 / 12 / 24

CABLE MANAGEMENT DEVICES

Fiber Distribution Box (FDB)

Compact termination box for building premises

Compact termination box for building premises

Key Features

- Compact termination box for building premises
- Connects drop cable with feeder cable
- Integrates splicing and splitting

Applications

- FTTx Distribution Nodes
- Multi-Dwelling Units (MDU)
- Street Cabinets

Technical Specifications

Parameter / Specification	Value / Detail
Capacity	4 to 32 Cores
Environment	Indoor/Outdoor IP65
Splitter Support	Cassette or Tube PLC

PASSIVE COMPONENTS

Fiber Spool / Fiber Drum

Precision low-stress winding technique

Precision low-stress winding technique

Key Features

- Precision low-stress winding technique
- Available with custom fiber types and lengths
- Rugged flange design for safe transport

Applications

- Lab Simulation Testing
- Emergency Network Restoration
- Field Deployment Dispatch

Technical Specifications

Parameter / Specification	Value / Detail
Lengths Available	500m, 1km, 2km, Custom
Fiber Options	G.652D, G.657A, OM3, OM4
Spool Material	High-Impact Plastic / Wood

PASSIVE COMPONENTS

Fiber Optic Connector, Field Installable

Fast Field Assembly Optical Connector

Fast Field Assembly Optical Connector

Key Features

- Fast Field Assembly Optical Connector
- No epoxy or polishing required
- Index matching gel inside

Applications

- FTTx Drop Cable Termination
- Emergency Repairs
- LAN Installations

Technical Specifications

Parameter / Specification	Value / Detail
Connector Type	SC / LC / FC
Polishing	UPC / APC
Assembly Time	< 2 minutes

PASSIVE COMPONENTS

Fiber Optic Patch Cords & Pigtails

Broadest choice of patchcords in the industry

Broadest choice of patchcords in the industry

Key Features

- Broadest choice of patchcords in the industry
- 100% interferometry tested
- Low insertion and high return loss

Applications

- Telecom Networks
- FTTH Drop Cables
- Optical Distribution Frames

Technical Specifications

Parameter / Specification	Value / Detail
Fiber Type	SM (G.652D/G.657) / MM (OM1-OM5)
Connectors	LC/SC/FC/ST/E2000
Insertion Loss	< 0.3 dB

TEST AND MEASUREMENT EQUIPMENT

Fusion Splicer PDR618H

Handheld, small and light

Handheld, small and light

Key Features

- Handheld, small and light
- Core alignment technology
- Fast 8s splicing and 26s tube heating

Applications

- Outside Plant Splicing
- FTTH Drop Cables
- Emergency Network Repair

Technical Specifications

Parameter / Specification	Value / Detail
Alignment	Core to Core
Battery	5800mAh Pluggable
Display	High-res LCD

CABLE MANAGEMENT DEVICES

Heat Shrink Splice Closure

Heat shrink sealing for harsh environments

Heat shrink sealing for harsh environments

Key Features

- Heat shrink sealing for harsh environments
- Accommodates multiple splice trays
- Excellent waterproof and dustproof performance

Applications

- Outside Plant (OSP) Networks
- Long Haul Routes
- Underground Splicing

Technical Specifications

Parameter / Specification	Value / Detail
Sealing Type	Heat Shrink
Capacity	Up to 288 Cores
Environment	Aerial/Buried/Manhole (IP68)

CABLE MANAGEMENT DEVICES

Fiber Optic Splitter Closure GJS 2016

Mechanical sealing structure

Mechanical sealing structure

Key Features

- Mechanical sealing structure
- Oval shaped cable port entrances in base
- Supports direct splicing and branching

Applications

- FTTx Distribution Splicing
- Aerial Messenger Wire
- Wall/Pole Mount Splices

Technical Specifications

Parameter / Specification	Value / Detail
Sealing Type	Mechanical
Shape	Horizontal / Dome
Ports	Multiple entry/exit

CABLE MANAGEMENT DEVICES

Home Termination Box (HTB)

Aesthetic design for indoor customer premises

Aesthetic design for indoor customer premises

Key Features

- Aesthetic design for indoor customer premises
- Provides fiber termination points and housing
- Wall mountable

Applications

- FTTH Customer Premises
- Residential Broadband
- Office Workstations

Technical Specifications

Parameter / Specification	Value / Detail
Capacity	1 to 4 Cores
Material	ABS plastic
Size	Compact footprint

PASSIVE COMPONENTS

SC/APC to SC/UPC Adapter

Hybrid fixed type adapter converter

Hybrid fixed type adapter converter

Key Features

- Hybrid fixed type adapter converter
- Converts APC polish to UPC polish
- Zero attenuation design

Applications

- Network Integration
- Test Equipment Interfacing
- Cross-connection

Technical Specifications

Parameter / Specification	Value / Detail
Fiber Type	Single Mode 9/125
Loss	0dB
Housing	Plastic/Metal

PASSIVE COMPONENTS

LC Uniboot Patchcord

Single-jacket duplex design saves 50% space

Single-jacket duplex design saves 50% space

Key Features

- Single-jacket duplex design saves 50% space
- Optimized for high-density environments
- Tool-less reversible polarity

Applications

- Spine-Leaf Architectures
- SAN Networks
- High-Density MPO Breakouts

Technical Specifications

Parameter / Specification	Value / Detail
Fiber Type	OM3 / OM4 / SM
Polarity	A-B / A-A (Reversible)
Cable Diameter	2.0mm / 3.0mm

PASSIVE COMPONENTS

Loop Back Patch Cord

Provides return signal for testing

Provides return signal for testing

Key Features

- Provides return signal for testing
- Compact housing design
- High stability and reliability

Applications

- Equipment Burn-in Testing
- Network Diagnostics
- Transceiver Loopback

Technical Specifications

Parameter / Specification	Value / Detail
Connector Type	LC / SC / MPO
Fiber Type	Single-mode / Multi-mode
Attenuation	Customizable

PASSIVE COMPONENTS

Mating Sleeve / Alignment Sleeve

Precision split sleeve for accurate alignment

Precision split sleeve for accurate alignment

Key Features

- Precision split sleeve for accurate alignment
- Available in Zirconia Ceramic or Phosphor Bronze
- Low insertion loss coupling

Applications

- Adapter Manufacturing
- Bare Fiber Testing
- Temporary Splicing

Technical Specifications

Parameter / Specification	Value / Detail
Material	Ceramic / Bronze
Inner Diameter	2.5mm (SC/FC/ST) / 1.25mm (LC)
Durability	>1000 matings

TEST AND MEASUREMENT EQUIPMENT

Mini Optical Power Meter

Pocket-sized, lightweight design

Pocket-sized, lightweight design

Key Features

- Pocket-sized, lightweight design
- High precision measurements
- Long battery life with auto-off

Applications

- Daily Fiber Link Testing
- Attenuation Measurement
- Optical Power Checks

Technical Specifications

Parameter / Specification	Value / Detail
Calibrated Wavelengths	850/1300/1310/1490/1550/1625nm
Detector	InGaAs
Power	AAA Batteries / USB

PASSIVE COMPONENTS

Mode Conditioning Patchcord

Eliminates differential mode delay (DMD) effects

Eliminates differential mode delay (DMD) effects

Key Features

- Eliminates differential mode delay (DMD) effects
- Enables Gigabit Ethernet over legacy MM fiber
- Offset single-mode to multi-mode splice

Applications

- Gigabit Ethernet LX/LH
- Legacy Fiber Upgrades
- Campus Networks

Technical Specifications

Parameter / Specification	Value / Detail
Offset	Precision core alignment
Cable Type	Duplex zipcord
Connectors	SC/LC/FC

PASSIVE COMPONENTS

MPO Cable Assembly

High-density multi-fiber connector system

High-density multi-fiber connector system

Key Features

- High-density multi-fiber connector system
- Precision molded MT ferrule
- Push-pull latching mechanism

Applications

- 40G/100G Networks
- Data Center Backbone
- High-Density Interconnects

Technical Specifications

Parameter / Specification	Value / Detail
Fiber Count	8/12/24/48
Polarity	Type A / B / C
Insertion Loss	Standard / Low Loss

PASSIVE COMPONENTS

Fiber Optic Cleaner Pen MPO

Designed specifically for multi-fiber connectors

Designed specifically for multi-fiber connectors

Key Features

- Designed specifically for multi-fiber connectors
- Cleans both male (with pins) and female (without pins) MPO/MTP
- Easy pushing motion engagement

Applications

- Hyperscale Data Centres
- 40G/100G/400G Networks
- Backbone Cabling

Technical Specifications

Parameter / Specification	Value / Detail
Connector Type	MPO / MTP
Clean Cycles	600+ cleans
Cleaning Action	Dry cloth sweep

TEST AND MEASUREMENT EQUIPMENT

Next Gen Optical Fusion Splicer (OPM + VFL)

Integrated OPM and VFL modules

Integrated OPM and VFL modules

Key Features

- Integrated OPM and VFL modules
- Core alignment technology for ultra-low loss
- Fast 8s splicing and 18s heating times

Applications

- Backbone Network Construction
- High-Precision Laboratory Splicing
- Advanced Field Maintenance

Technical Specifications

Parameter / Specification	Value / Detail
Alignment Method	Core-to-Core
Integrated Tools	OPM (-70~+6dBm), VFL (10mW)
Battery Capacity	>250 splice/heat cycles

CABLE MANAGEMENT DEVICES

Optical Distribution Frames

Multi-purpose high-capacity distribution frame

Multi-purpose high-capacity distribution frame

Key Features

- Multi-purpose high-capacity distribution frame
- High-quality ABS plastic or metal build
- Efficient cable routing and protection

Applications

- Telecom Central Office
- Main Distribution Area (MDA)
- Large Data Centers

Technical Specifications

Parameter / Specification	Value / Detail
Capacity	Up to 576 Cores
Type	Floor standing / Rack mount
Pigtail Management	Integrated

ACTIVE COMPONENTS

Optical Line Protection System (OLPS)

Uses spare optical fiber to build a backup path

Uses spare optical fiber to build a backup path

Key Features

- Uses spare optical fiber to build a backup path
- Automatic route switching on fiber break
- Real-time line status monitoring

Applications

- DWDM Networks
- Long Haul Transmission
- Critical Infrastructure

Technical Specifications

Parameter / Specification	Value / Detail
Protection Type	1+1 / 1:1
Switching Time	< 20ms
Monitoring	Real-time optical power

PASSIVE COMPONENTS

PLC Splitter

Planar Lightwave Circuit technology

Planar Lightwave Circuit technology

Key Features

- Planar Lightwave Circuit technology
- Uniform power splitting
- Broad operating wavelength

Applications

- FTTH/PON Networks
- CATV Links
- Optical Signal Distribution

Technical Specifications

Parameter / Specification	Value / Detail
Split Ratio	1×2 up to 1×128
Wavelength	1260nm - 1650nm
Packaging	Bare fiber / Blockless / Cassette

TEST AND MEASUREMENT EQUIPMENT

Pocket OTDR

Ultra-compact smartphone-sized form factor

Ultra-compact smartphone-sized form factor

Key Features

- Ultra-compact smartphone-sized form factor
- Fast boot-up and auto-test functionality
- Event map view for intuitive fault location

Applications

- Last-Mile FTTx Troubleshooting
- Quick Field Checks
- Access Network Installation

Technical Specifications

Parameter / Specification	Value / Detail
Dynamic Range	22dB to 26dB
Fiber Type	Single-mode / Multimode Options
Display	Touchscreen LCD

PASSIVE COMPONENTS

POF — Plastic Optical Fiber Patchcord

Large PMMA core for easy alignment

Large PMMA core for easy alignment

Key Features

- Large PMMA core for easy alignment
- Immune to electromagnetic interference (EMI)
- Cost-effective for short-range links

Applications

- Automotive Networking
- Industrial Control Systems
- Home AV Connections

Technical Specifications

Parameter / Specification	Value / Detail
Core Material	Polymethyl Methacrylate (PMMA)
Wavelength	650nm
Core Diameter	1mm (Typical)

TEST AND MEASUREMENT EQUIPMENT

PON Power Meter

Pass-through measurement for live PON

Pass-through measurement for live PON

Key Features

- Pass-through measurement for live PON
- Simultaneous testing of 1310/1490/1550nm
- Burst mode measurement for 1310nm upstream

Applications

- FTTx Network Turn-up
- PON Maintenance
- OLT/ONT Verification

Technical Specifications

Parameter / Specification	Value / Detail
Wavelengths	1310/1490/1550nm
Network Type	BPON/EPON/GPON
Display	Color LCD

CABLE MANAGEMENT DEVICES

Rack Mount Fiber Management System

19" Rack Mount fiber-optic enclosure

19

Key Features

- 19" Rack Mount fiber-optic enclosure
- Slide-out drawer for easy access
- Modular adapter panels

Applications

- Data Center Racks
- Telecom Central Office
- Enterprise Server Rooms

Technical Specifications

Parameter / Specification	Value / Detail
Capacity	Up to 144 cores (4U)
Material	Cold rolled steel
Mounting	Standard 19-inch rack

PASSIVE COMPONENTS

Rapid Push Cable Assembly

FTTX smart pushable preterminated drop solution

FTTX smart pushable preterminated drop solution

Key Features

- FTTX smart pushable preterminated drop solution
- Eliminates field splicing
- Designed for microduct deployment

Applications

- FTTH Last Mile
- Microduct Installations
- MDU Deployments

Technical Specifications

Parameter / Specification	Value / Detail
Cable Outer Dia	2.0mm to 5.0mm
Connector	SC/APC Pushable
Tensile Strength	High

TEST AND MEASUREMENT EQUIPMENT

Regular Optical Power Meter

Auto-wavelength recognition capability

Auto-wavelength recognition capability

Key Features

- Auto-wavelength recognition capability
- Wide dynamic measurement range
- Backlit LCD for low-light environments

Applications

- Link Acceptance Testing
- Power Level Monitoring
- Optical Loss Measurement

Technical Specifications

Parameter / Specification	Value / Detail
Wavelength Range	800nm to 1700nm
Calibrated Wavelengths	850/1300/1310/1490/1550/1625nm
Power Range	-70 to +10 dBm / -50 to +26 dBm

ACTIVE COMPONENTS

100G & 100G BIDI

High-density 100G transmission

High-density 100G transmission

Key Features

- High-density 100G transmission
- BIDI variant saves fiber infrastructure
- Low insertion loss

Applications

- Enterprise Core
- Carrier Routing
- Metro Networks

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	QSFP28
Data Rate	100G
Connector	LC / MPO
DOM Support	Yes
Wavelength	CWDM4 / LR4 / SR4
Operating Temp	0°C to 70°C

ACTIVE COMPONENTS

SFP+ 10G BIDI

Doubles fiber capacity using WDM technology

Doubles fiber capacity using WDM technology

Key Features

- Doubles fiber capacity using WDM technology
- Hot-swappable
- Built-in digital diagnostic monitoring

Applications

- Access Networks
- Enterprise LAN
- Campus Networks

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	SFP+
Data Rate	10G
Connector	LC Simplex
DOM Support	Yes
Wavelength	1270nm/1330nm
Operating Temp	0°C to 70°C

ACTIVE COMPONENTS

SFP+ 10G Dual Fiber

Standard dual-fiber 10G transmission

Standard dual-fiber 10G transmission

Key Features

- Standard dual-fiber 10G transmission
- Broad vendor compatibility
- High reliability

Applications

- SAN / NAS
- Edge Routing
- Data Center Racks

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	SFP+
Data Rate	10G
Connector	LC Duplex
DOM Support	Yes
Wavelength	850nm / 1310nm / 1550nm
Operating Temp	0°C to 70°C

ACTIVE COMPONENTS

1G SFP BIDI

Cost-effective 1G bi-directional link

Cost-effective 1G bi-directional link

Key Features

- Cost-effective 1G bi-directional link
- Single fiber optimization
- Low power dissipation

Applications

- FTTH
- Access Rings
- CPE Equipment

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	SFP
Data Rate	1.25G
Connector	LC Simplex / SC Simplex
DOM Support	Yes
Wavelength	1310nm/1550nm
Operating Temp	-40°C to +85°C

ACTIVE COMPONENTS

1G SFP Dual Fiber

Legacy compatible 1G module

Legacy compatible 1G module

Key Features

- Legacy compatible 1G module
- Wide operating temperature range
- Cost-effective

Applications

- Legacy Switching
- Enterprise Access
- Industrial Ethernet

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	SFP
Data Rate	1.25G
Connector	LC Duplex
DOM Support	Yes
Wavelength	850nm / 1310nm
Operating Temp	-40°C to +85°C

ACTIVE COMPONENTS

25G & 25G BIDI

Optimized for 5G fronthaul

Optimized for 5G fronthaul

Key Features

- Optimized for 5G fronthaul
- Low latency
- Single fiber bi-directional transmission (BIDI)

Applications

- 5G Fronthaul
- High-Speed Access
- Server Connectivity

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	SFP28
Data Rate	25G
Connector	LC Duplex / Simplex
DOM Support	Yes
Wavelength	850nm / 1310nm
Operating Temp	-40°C to +85°C

ACTIVE COMPONENTS

400G

Next-generation high-capacity throughput

Next-generation high-capacity throughput

Key Features

- Next-generation high-capacity throughput
- Low power consumption
- Hot-pluggable form factor

Applications

- Hyperscale Data Centers
- Core Routing
- 5G Backhaul

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	QSFP-DD / OSFP
Data Rate	400G
Connector	LC / MPO
DOM Support	Yes
Wavelength	850nm / 1310nm
Operating Temp	0°C to 70°C

ACTIVE COMPONENTS

40G

Reliable mid-tier aggregation

Reliable mid-tier aggregation

Key Features

- Reliable mid-tier aggregation
- Hot-pluggable
- IEEE 802.3ba compliant

Applications

- Mid-tier Aggregation
- Data Center Edge
- SAN Switches

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	QSFP+
Data Rate	40G
Connector	LC / MPO
DOM Support	Yes
Wavelength	850nm / 1310nm
Operating Temp	0°C to 70°C

ACTIVE COMPONENTS

Copper SFP+

RJ-45 interface for twisted pair copper

RJ-45 interface for twisted pair copper

Key Features

- RJ-45 interface for twisted pair copper
- Up to 30m reach on Cat6a/7
- Auto-negotiation

Applications

- Server Connectivity
- ToR Switches
- Legacy Copper Infrastructure

Technical Specifications

Parameter / Specification	Value / Detail
Form Factor	SFP+
Data Rate	10G Base-T
Connector	RJ-45
DOM Support	No
Wavelength	N/A
Operating Temp	0°C to 70°C

ACTIVE COMPONENTS

Smart SFP Transceiver

Integrated OAM (Operations, Administration, and Maintenance)

Integrated OAM (Operations, Administration, and Maintenance)

Key Features

- Integrated OAM (Operations, Administration, and Maintenance)
- Real-time performance monitoring
- Micro-loopback capability

Applications

- Service Provider Edge
- Mobile Backhaul
- SLA Monitoring

Technical Specifications

Parameter / Specification	Value / Detail
Interface	1G / 10G SFP
Protocol	IEEE 802.3ah / 802.1ag
Diagnostics	DDM/DOM
Latency	Ultra-Low

PASSIVE COMPONENTS

SMPTE Cable Assembly

Hybrid fiber and copper camera cable

Hybrid fiber and copper camera cable

Key Features

- Hybrid fiber and copper camera cable
- Ruggedized and dirt protected connectors
- Compliant with SMPTE 311M and 304M

Applications

- HDTV Broadcasting
- Stadium Infrastructure
- Mobile OB Vans

Technical Specifications

Parameter / Specification	Value / Detail
Components	2 SM Fibers + 4 Copper Conductors
Jacket	PUR / Lemo
Durability	> 2000 Mating Cycles

PASSIVE COMPONENTS

Splice-On Connector (SOC)

Factory-polished endface ensures low loss

Factory-polished endface ensures low loss

Key Features

- Factory-polished endface ensures low loss
- Eliminates need for epoxy and field polishing
- Compatible with standard fusion splicers

Applications

- FTTx Drop Cables
- Data Centre Links
- Field Repair & Maintenance

Technical Specifications

Parameter / Specification	Value / Detail
Insertion Loss (IL)	< 0.2dB
Return Loss (RL)	> 60dB (APC)
Assembly Method	Fusion Splicing

PASSIVE COMPONENTS

VFL — Visual Fault Locator

Bright 650nm visible red laser

Bright 650nm visible red laser

Key Features

- Bright 650nm visible red laser
- Continuous and flashing modes
- Ruggedized metal housing for field use

Applications

- Fault Location
- Continuity Testing
- Fiber Identification

Technical Specifications

Parameter / Specification	Value / Detail
Output Power	1mW (Standard)
Wavelength	650nm
Detection Range	Up to 10km

CABLE MANAGEMENT DEVICES

Optical Fiber Wall Mount Enclosure

Two door wall mounted enclosure

Two door wall mounted enclosure

Key Features

- Two door wall mounted enclosure
- Secure lockable doors
- Separate compartments for splicing and patching

Applications

- Building Distribution
- Security Camera Hubs
- Campus Networks

Technical Specifications

Parameter / Specification	Value / Detail
Capacity	Up to 96 Cores
Type	Indoor Wall Mount
Security	Keyed locks