

Laboratory Exercise-4 (Part-A)

(Gaussian Elimination)

9-Sep-2020

1. **Aim** Here you will solve $AX = B$, where A is a $N \times N$ matrix and B is a $N \times 1$ matrix.

2. **Write a code**

System of linear equations can be solved by Gaussian elimination in MATLAB using $X = A \backslash B$ (with a backslash). Write a code that will do the following

- Choose a value of N (size of linear system)
- Construct matrices A and B by assigning random values to elements of A and B . This can be done in MATLAB using $A = \text{rand}(N, N)$ and $B = \text{rand}(N, 1)$.
- Solve the resulting equation for X using MATLAB function for Gaussian elimination.
- Measure the run time of the Gaussian elimination procedure. *Do not include run time for generation of A & B .* Later you should compare this with Jacobi method.

Check <https://in.mathworks.com/help/matlab/ref/toc.html> on how to do this.

3. **Test the code** for some simple system of 2 & 3 linear equations. Does your code give the correct answer for your chosen system of linear equations? *Never skip this step of testing your code.*

4. **Run the code**

Run your code for different values of N ranging from 10 to 30000. Measure the time for each N . How does time (T) change with N . Plot N vs T .

Laboratory Exercise-4 (Part-B)

(Jacobi method)

9-Sep-2020 & 16-Sep-2020

1. **Aim** Here you will solve $AX = B$ using Jacobi Method

2. **Write a Jacobi method code**

- Construct matrices A and B by assigning random values to elements of A and B .
- Verify if the matrix is diagonally dominant. If it satisfies this condition only then carry on with the procedure of Jacobi method.
- Also verify that the spectral radius of $T = D^{-1}(L + U)$ for the matrix generated is less than one. For diagonally dominant matrix spectral radius of T should be less than one (condition required for convergence)

Check MATLAB documentation for the MATLAB function to find out eigenvalue of a matrix and then its largest value (magnitude). Use these. In a later lab you will write your own code to do the same.

- Write a code to implement the iterative steps of Jacobi method to get solution of
- Measure the run time of the iterative steps of the code.

3. **Test the code** for a system of 3 linear equations for which A is diagonally dominant/

4. **Run the code**

Run the Jacobi method code for different values of N ranging from 10 to 30000. Measure the time for each N .

- (a) How does time (T) change with N . Plot N vs T .
- (b) Compare T for Jacobi and Gaussian method. Which one is preferable in terms of speed?