

INDIA'S ONLY BRAND HAVING PATENT CERTIFICATE FOR AIR QUALITY AND HUMIDITY SOLUTIONS.

PROTECTS YOU AND YOUR VALUABLES



AMFAH PORTABLE DEHUMIDIFIER

SUPERDRY FDNP 62

TECHNICAL SPECIFICATION



- High Dehumidification Capacity – 62L/Day
- Energy-Efficient Performance – Up to 890W
- Hot Gas Defrosting System for Low Temps
- Powerful 550 m³/h Airflow & Air Purification
- Large 14L Tank with Flexible Drainage
- Tank Capacity: 14 L

Parameter	SUPERDRY 62
Rated Avg. Power Consumption (27°C, 60% RH)	750 W
Maximum Power Consumption (35°C, 70% RH)	890 W
Maximum Current Consumption (F.L.A.)	4.4 A
Start-up Current (L.R.A.)	24 A
Air Flow	550 m ³ /h
Sound Pressure Level (3m in open field)	50 dB(A)
Refrigerant	R1234yf
Condensate Tank Capacity	14 kg
Condensate Drain Fitting	3/4"
Operational Temperature Range	1°C – 32°C
Humidity Range (T < 30°C)	30% – 98% RH
Humidity Range (T 30–32°C)	30% – 90% RH
Humidity Range (T 32–35°C)	30% – 70% RH



9324516326



info.india@amfah.com



www.amfah.com