JSLint

Fork on GitHub

Edition: v2024.11.24

- **Read the instructions.**
- *How JavaScript Works* **by Douglas Crockford.**
- **Report a bug or issue.**

Source

```
255                         clearInterval(fadeOutLoading);
256                     }
257                 }, 10);
258             }
259
260             // If there is an error enable card and submit button to fix it
261             card.update({ "disabled": false});
262             $("#submit-button").attr("disabled", false);
263         } else {
264             // If payment intent is succsessful, submit the form
265             if (result.paymentIntent.status === "succeeded") {
266                 form.submit();
267             }
268         }
269     });
270 }).fail(function() {
271     // Reload the page, the error will be in django messages
272     location.reload();
273 });
274 });
```

JSLint   **Clear Source**   **Clear Options**

Options

Env...
- ☑ browser
- ☐ devel
- ☐ node
- ☐ trace

Allow...
- ☐ beta
- ☐ bitwise
- ☐ convert
- ☐ eval

- ☐ fart
- ☐ for
- ☐ getset
- ☐ indent2

- ☐ long
- ☐ nomen
- ☐ single
- ☐ subscript

- ☐ this
- ☑ unordered
- ☐ variable
- ☐ white

$

Report: Warnings (1)

1. *Unexpected ': card'.*   *166: 21*

```
card: card,
```

Report: Properties (64)

```
/*property
    addEventListener, address, adults, attr, billing_details, card,
    check_in_date, check_out_date, checked, children, city, client_secret,
    confirmCardPayment, country, county, create, csrfmiddlewaretoken, disabled,
    display, done, elements, email, error, fail, full_name, getElementById,
    html, infants, innerHTML, line1, line2, message, mount, name, opacity,
    paymentIntent, payment_method, phone, phone_number, post, postal_code,
```

Report: Functions (13)

global $, Boolean, Stripe, card, clearInterval, clientSecret, csrfToken, document, elements, form, location, opacity, postData, saveInfo, setInterval, stripePublicKey

«change»(event)   *32: 33*
   parameter   event
   variable   errorDiv
    global   document

«submit»(ev)   *54: 33*
   parameter   ev
   variable   adults, check_in_date, check_out_date, children, fadeIn, fadeInOverlay, fadeOut, fadeOutOverlay, infants, loadingOverlay, paymentForm, room, room_id, total_cost, total_days, url
   closure   fadeIn, fadeInOverlay, fadeOut, fadeOutOverlay, loadingOverlay, paymentForm
   global $, Boolean, card, clientSecret, csrfToken, document, opacity, postData, saveInfo, setInterval

  «setInterval»()   *83: 36*
    outer   fadeIn, paymentForm
    global   clearInterval, opacity

  «setInterval»()   *92: 37*
    outer   fadeOut, paymentForm
    global   clearInterval, opacity

  «setInterval»()   *107: 43*
    outer   fadeInOverlay, paymentForm
    global   clearInterval, opacity

  «setInterval»()   *116: 44*
    outer   fadeOutOverlay, paymentForm
    global   clearInterval, opacity

  «done»()   *158: 32*
    global   Stripe, card, clientSecret, form

  «then»(result)   *195: 17*
    parameter   result
    variable   errorDiv, fadeInLoading, fadeInPayment, fadeOutLoading, fadeOutPayment, html
    closure   fadeInLoading, fadeInPayment, fadeOutLoading, fadeOutPayment
    outer   loadingOverlay, paymentForm
    global $, card, document, form, opacity, setInterval

   «setInterval»()   *216: 55*
     outer   fadeInPayment, paymentForm
     global   clearInterval, opacity

   «setInterval»()   *225: 56*
     outer   fadeOutPayment, paymentForm
     global   clearInterval, opacity

   «setInterval»()   *241: 55*
     outer   fadeInLoading, paymentForm

global   clearInterval, opacity

«setInterval»()   *250: 56*

    outer   fadeOutLoading, paymentForm

    global   clearInterval, opacity

«fail»()   *270: 13*

    global   location