Customer-service sales API

Use these four calls from the customer-service app. Paths are relative to the ERP host. This key can list customers, list sales users, and create a query. It cannot edit a quotation, receive a purchase order, or create a job.

Call users and customers first, then create the query.

Shared rules

Send the API key on every request as `Authorization: Bearer <key>`. `x-api-key: <key>` is also accepted. A missing or unknown key returns `401`.

Every call sends `companyExternalId`. It must match the company already stored for that API key. A mismatch returns `403` with `Company external id does not match this API key`.

If the key has an allowed-domain list, send a matching `Origin` header, for example `Origin: https://your-app.example.com`. An empty list does not require `Origin`.

Success is `{ "success": true, "data": ... }`. Error is `{ "success": false, "error": "..." }`.

Optional header `x-idempotency-key`. If that key already succeeded, the earlier success is returned again and `replayed: true` is added to `data`. If it already failed, the earlier error is returned and the work is not tried again.

---

1. List customers

`GET /api/integrations/sales/customers`

Find an existing customer before creating a query.

QUERY	REQUIRED	NOTES
`companyExternalId`	yes	Company id stored on the API key
`search`	no	Matches name, phone, email, or contact person
`limit`	no	Default 100, maximum 1000
`offset`	no	Default 0

`data` is `{ items, total }`. Each item has `id`, `name`, `phone`, `email`, `contactPerson`, `address`, `isActive`.

```
{
  "items": [
    {
      "id": "customer-id",
      "name": "Demo Customer LLC",
      "phone": "+971500000000",
      "email": "ops@example.com",
      "contactPerson": "John Smith",
      "address": "Jebel Ali",
      "isActive": true
    }
  ],
  "total": 1
}
```

`422` when `companyExternalId` is missing.

---

2. Get one customer

`GET /api/integrations/sales/customers/{id}?companyExternalId=`

Same customer fields as the list, plus contacts. A customer that belongs to another company returns `404` (`Customer not found`).

QUERY	REQUIRED	NOTES
`companyExternalId`	yes	Company id stored on the API key

`data.contacts` is `[{ "name", "phone", "email" }]`.

---

3. List sales users

`GET /api/integrations/sales/users?companyExternalId=`

These ids are the only valid values for `salesmanId` and `assigneeId`. The list is active users of this company who are a super admin or whose role has any sales permission.

QUERY	REQUIRED	NOTES
`companyExternalId`	yes	Company id stored on the API key

`data` is an array, not wrapped in `items`:

```
[
  { "id": "erp-user-id", "name": "Mahmud", "email": "sales@example.com" }
]
```

---

4. Create a query

`POST /api/integrations/sales/queries`

Creates a sales query. `salesmanId` is always required and is the person recorded as the salesman. It is not copied into the assignee.

FIELD	REQUIRED	NOTES
`companyExternalId`	yes	Company id stored on the API key
`customerId`	one of these	Existing customer id from the list or detail call
`customer`	one of these	{ name, phone, contactPerson? }. name max 100, phone max 30, contactPerson max 100
`projectLocation`	yes	Max 200
`projectDescription`	yes	Max 1000
`projectScope`	yes	Max 500
`extraNotes`	no	Max 5000
`salesmanId`	yes	Id from the sales users call
`forwardToQuotation`	no	Default false. When true, the query is also turned into a quotation
`assigneeId`	when forwarding	Required only if forwardToQuotation is true. May be the same user as salesmanId or a different sales user
`requestedBy`	no	Max 120. Stored only in the working-log note. If omitted, the note says Customer service API

Send `customerId` or `customer`, never both and never neither. The same name plus the same phone digits reuses the existing customer (`customerCreated: false`). Otherwise a customer is created (`customerCreated: true`). If more than one customer already has that name and phone, the call returns `400` and the other app should send `customerId` instead.

Example, new customer and forwarded:

```
{
  "companyExternalId": "PM-COMPANY-001",
  "customer": {
    "name": "Demo Customer LLC",
    "phone": "+971500000000",
    "contactPerson": "John Smith"
  },
  "projectLocation": "Jebel Ali Site",
  "projectDescription": "GRP lining for the plant room",
  "projectScope": "Lining",
  "extraNotes": "Site visit requested",
  "salesmanId": "erp-user-id-from-sales-users",
  "forwardToQuotation": true,
  "assigneeId": "erp-user-id-from-sales-users",
  "requestedBy": "Amina from customer service"
}
```

`201` `data` when the query stays a query:

```
{
  "id": "sales-query-id",
```

```
  "queryNumber": "QR26-0001",
  "customerId": "customer-id",
  "customerCreated": true,
  "stage": "QUERY",
  "salesman": { "id": "erp-user-id", "name": "Mahmud" }
}
```

When `forwardToQuotation` is `true`, `stage` is `QUOTATION` and `data` also includes `quotationNumber` and `assignedTo: { "id", "name" }`.

STATUS	WHEN
422	Invalid JSON, missing companyExternalId, both or neither customer form, missing assigneeId while forwarding, or a field over its max length
400	salesmanId or assigneeId is not an active sales user for this company, or customerId is not in this company
403	Company id does not match the API key, or Origin is not allowed