
QUIZ 1

1. Let $L = \{010, 101, 001, 011\}$, and $K = \{w \mid 0w \in L\}$. Which of the following strings is a member of K ?

- (A) 0101
- (B) 01
- (C) 011
- (D) 0110

The correct answer is (B). K is the set of strings formed by removing the leading 0 from a string in L . Thus, $K = \{10, 01, 11\}$.

2. Let Σ_1 and Σ_2 be two alphabets, with $\Sigma_1 \neq \Sigma_2$. Which of the following is necessarily true?

- (A) $\Sigma_1^* = \Sigma_2^*$
- (B) $\Sigma_1^n = \Sigma_2^n$ for all n
- (C) $|\Sigma_1^n| = |\Sigma_2^n|$, for all n . Here $|A|$ denotes the number of elements in the set A .
- (D) $\Sigma_1^0 = \Sigma_2^0$

The correct answer is (D). $\Sigma^0 = \{\epsilon\}$ for any Σ . The first two options are wrong because $\Sigma_1 \neq \Sigma_2$ and hence, there is at least one symbol (say x) in one of them which is not present in the other. Strings containing x will be present in sets described in options (A) and (B) for one of the alphabets, but not the other. (C) is incorrect because the number of elements in the 2 alphabets may differ.




Figure 1: DFA M for questions 4 and 5

3. Consider the DFA M over the alphabet $\{0, 1\}$ shown in Figure 1. Which of the following strings is accepted by M ?

- (A) ϵ
- (B) 0011
- (C) 1111000
- (D) 1011

The correct answer is (D). $\hat{\delta}_M(q_0, \epsilon) = \{q_0\}$, $\hat{\delta}_M(q_0, 0011) = \{q_0\}$, $\hat{\delta}_M(q_0, 1111000) = \{q_3\}$, $\hat{\delta}_M(q_0, 1011) = \{q_2\}$. The only accepting state is q_2 .

4. The language recognized by DFA M in Figure 1 is

- (A) $\{w \mid w \text{ has even length}\}$
- (B) $\{w \mid w \text{ has an odd number of 1s and an odd number of 0s}\}$
- (C) $\{w \mid w \text{ has an equal number of 0s and 1s}\}$
- (D) $\{w \mid w \text{ has an odd number of 1s}\}.$

The correct answer is (B). It can be established by proving the following system of equivalences by induction on length of w .

- $\hat{\delta}_M(q_0, w) = \{q_0\} \Leftrightarrow w$ has even number of 1s and even number of 0s
- $\hat{\delta}_M(q_0, w) = \{q_3\} \Leftrightarrow w$ has even number of 1s and odd number of 0s
- $\hat{\delta}_M(q_0, w) = \{q_1\} \Leftrightarrow w$ has odd number of 1s and even number of 0s
- $\hat{\delta}_M(q_0, w) = \{q_2\} \Leftrightarrow w$ has odd number of 1s and odd number of 0s

Observe that options (A) and (D) describe sets that are *strict* supersets of the set of strings accepted by the DFA.




Figure 2: NFA N for problem 5

5. Consider the NFA N shown in Figure 2. Which of the following strings is *not* accepted by N ?

- (A) 001
- (B) 001100
- (C) 10011001
- (D) 1001

The correct answer is (A). Observe that any string accepted by N must contain a 1 followed by two 0s.

6. Let $N = (Q, \Sigma, \delta, q_0, F)$ be an NFA. Recall that $\hat{\Delta} : Q \times \Sigma^* \rightarrow 2^Q$ is a function that given a state q and string w returns the set of all states that N could be in after reading w from state q . Formally, $\hat{\Delta}(q, w) = \{q' \mid q \xrightarrow{w}_N q'\}$. We can say that N accepts a string w iff

- (A) $\hat{\Delta}(q_0, w) \in F$
- (B) $\hat{\Delta}(q_0, w) = F$
- (C) $\hat{\Delta}(q_0, w) \cap F \neq \emptyset$
- (D) $\hat{\Delta}(q_0, w) \subseteq F$

The correct answer is (C). An NFA accepts a string if and only if there is any way to reach a final state after reading the string. Therefore, all that we require is that the intersection of $\hat{\Delta}(q_0, w)$ and F is nonempty.