

CIS 450 – Computer Architecture and Organization

Lecture 20: Control Flow (cont.)

Mitch Neilsen

(neilsen@ksu.edu)


219D Nichols Hall

Topics

- **Process Hierarchy**
- **Shells**
- **Signals**
- **Non-local Jumps**

wait: Synchronizing with children

```
void fork9() {  
    int child_status;  
  
    if (fork() == 0) {  
        printf("HC: hello from child\n");  
    }  
    else {  
        printf("HP: hello from parent\n");  
        wait(&child_status);  
        printf("CT: child has terminated\n");  
    }  
    printf("Bye\n");  
    exit(3);  
}
```



exec : Running new programs

`int execl(char *path, char *arg0, char *arg1, ..., 0)`

- loads and runs executable at `path` with args `arg0`, `arg1`, ...
 - `path` is the complete path of an executable
 - `arg0` becomes the name of the process
 - » typically `arg0` is either identical to `path`, or else it contains only the executable filename from `path`
 - “real” arguments to the executable start with `arg1`, etc.
 - list of args is terminated by a `(char *)0` argument
- returns `-1` if error, otherwise doesn't return!

```
main() {
    if (fork() == 0) {
        execl("/usr/bin/cp", "cp", "foo", "bar", 0);
        exit(-1);
    }
    wait(NULL);
    printf("copy completed\n");
    exit(0);
}
```

Control Flow Exists at All Levels of a System

Exceptions

- Hardware and operating system kernel software

Concurrent processes

- Hardware timer and kernel software

Signals

- Kernel software

Non-local jumps

- Application code

**Previous Lecture
And Slides**

This Lecture

The World of Multitasking

System Runs Many Processes Concurrently

- **Process: executing program**
 - State consists of memory image + register values + program counter
- **Continually switches from one process to another**
 - Suspend process when it needs I/O resource or timer event occurs
 - Resume process when I/O available or given scheduling priority
- **Appears to user(s) as if all processes executing simultaneously**
 - Even though most systems can only execute one process at a time
 - Except possibly with lower performance than if running alone

Programmer's Model of Multitasking


Basic Functions

- `fork()` spawns new process
 - Called once, returns twice
- `exit()` terminates own process
 - Called once, never returns
 - Puts the process into “zombie” state
- `wait()` and `waitpid()` wait for and reap terminated children
- `exec1()` and `execve()` run a new program in an existing process
 - Called once, (normally) never returns

Programming Challenge

- Understanding the nonstandard semantics of the functions
- Avoiding improper use of system resources
 - E.g. “fork bombs” can disable a system; e.g., `while(1) fork();`

Unix Process Hierarchy



The ps command

```
cislinux> ps aux -w --forest
```

(output edited to fit slide)


USER	PID	%CPU	%MEM	VSZ	RSS	TTY	STAT	START	TIME	COMMAND
root	1	0.0	0.0	1516	248	?	Ss	Sep24	0:10	init [3]
root	2	0.0	0.0	0	0	?	S	Sep24	0:02	[migration/0]
root	3	0.0	0.0	0	0	?	SN	Sep24	0:00	[ksoftirqd/0]
root	4	0.0	0.0	0	0	?	S	Sep24	1:44	[migration/1]
root	5	0.0	0.0	0	0	?	SN	Sep24	0:00	[ksoftirqd/1]
root	6	0.0	0.0	0	0	?	S<	Sep24	0:00	[events/0]
root	8	0.0	0.0	0	0	?	S<	Sep24	0:00	[khelper]
root	9	0.0	0.0	0	0	?	S<	Sep24	0:00	[kthread]
root	12	0.0	0.0	0	0	?	S<	Sep24	0:10	_ [kblockd/0]
root	13	0.0	0.0	0	0	?	S<	Sep24	0:00	_ [kblockd/1]
...										
matts	584	0.0	0.0	5788	1376	?	Ss	Sep28	0:01	SCREEN
matts	585	0.0	0.0	2892	196	pts/8	Ss	Sep28	0:00	_ -/bin/bash
matts	589	0.0	0.0	6764	1008	pts/8	S+	Sep28	0:00	_ mysql >
matts	1768	0.0	0.0	2888	548	pts/15	Ss+	Sep28	0:00	_ -/bin/bash
matts	10119	0.0	0.0	2888	876	pts/37	Ss	Sep28	0:00	_ -/bin/bash
matts	25748	0.0	0.0	1920	748	pts/37	S+	Oct26	0:00	_ less F>
eab9844	3178	0.0	0.0	5508	1036	?	Ss	Sep28	0:01	SCREEN
eab9844	3179	0.0	0.0	3556	188	pts/34	Ss	Sep28	0:00	_ -/bin/tcsh
eab9844	3189	0.0	0.0	6816	1748	pts/34	S+	Sep28	0:09	_ irssi >

The ps Command (cont.)

```
USER      PID  TTY      STAT  COMMAND
root      889  tty1     S      /bin/login -- agn
agn       900  tty1     S      \_ xinit -- :0
root      921  ?        SL     \_ /etc/X11/X -auth /usr1/agn/.Xauthority :0
agn       948  tty1     S      \_ /bin/sh /afs/cs.cmu.edu/user/agn/.xinitrc
agn       958  tty1     S      \_ \_ xterm -geometry 80x45+1+1 -C -j -ls -n
agn       966  pts/0    S      \_ \_ -tcsh
agn       1184 pts/0    S      \_ \_ /usr/local/bin/wish8.0 -f /usr
agn       1212 pts/0    S      |   \_ /usr/local/bin/wish8.0 -f
agn       3346 pts/0    S      |   \_ \_ aspell -a -S
agn       1191 pts/0    S      \_ \_ /bin/sh /usr/local/libexec/moz
agn       1204 8 pts/0    S      \_ \_ /usr/local/libexec/mozilla
agn       1207 8 pts/0    S      |   \_ /usr/local/libexec/moz
agn       1208 8 pts/0    S      |   \_ \_ /usr/local/libexec
agn       1209 8 pts/0    S      |   \_ \_ /usr/local/libexec
agn       17814 8 pts/0    S      |   \_ \_ /usr/local/libexec
agn       2469 pts/0    S      \_ \_ usr/local/lib/Acrobat
agn       2483 pts/0    S      \_ \_ java_vm
agn       2484 pts/0    S      \_ \_ java_vm
agn       2485 pts/0    S      \_ \_ java_vm
agn       3042 pts/0    S      \_ \_ java_vm
agn       959  tty1     S      \_ \_ /bin/sh /usr/local/libexec/kde/bin/sta
agn       1020 tty1     S      \_ \_ kwrapper ksmserver
```

Unix Startup: Step 1

1. Pushing reset button loads the PC with the address of a small bootstrap program.
2. Bootstrap program loads the boot block (disk block 0).
3. Boot block program loads kernel binary (e.g., `/boot/vmlinux`).
4. Boot block program passes control to kernel.
5. Kernel handcrafts the data structures for process 0.




Some PC Start-up Details

Boot Disk / CD / Floppy



Start
Execution at
`0xfffffffff0`



Power OK
Deassert Reset

`0xfffffffff`
`0xffff0000`

BIOS ROM

The Linux kernel is
loaded and
begins initialization
CPU executes LILO

BIOS verifies MBR
and jumps to
`0x00007c00`


Copy

Master Boot Record
into memory

`0x00007c00`
`0x00000000`


LILO (or GRUB)
is loaded from
first sector of
active partition

Unix Startup: Step 2




**init forks and execs
daemons per
/etc/inittab, and forks
and execs a getty program
for the console**

Unix Startup: Step 3



**The getty process
execs a login
program**

Unix Startup: Step 4



login reads login-ID and passwd.
if OK, it execs a *shell*.
if not OK, it execs another **getty**

In case of **login** on the console
xinit may be used instead of
a shell to start the window manger

Shell Programs

A ***shell*** is an application program that runs programs on behalf of the user.

- **sh** – Original Unix Bourne Shell
- **csh** – BSD Unix C Shell, **tcsh** – Enhanced C Shell
- **bash** – Bourne-Again Shell

```
int main()
{
    char cmdline[MAXLINE];

    while (1) {
        /* read */
        printf("> ");
        fgets(cmdline, MAXLINE, stdin);
        if (feof(stdin))
            exit(0);

        /* evaluate */
        eval(cmdline);
    }
}
```

Execution is a sequence of
read/evaluate steps

Simple Shell eval Function

```
void eval(char *cmdline)
{
    char *argv[MAXARGS]; /* argv for execve() */
    int bg;               /* should the job run in bg or fg? */
    pid_t pid;           /* process id */

    bg = parseline(cmdline, argv);
    if (!builtin_command(argv)) {
        if ((pid = fork()) == 0) { /* child runs user job */
            if (execve(argv[0], argv, environ) < 0) {
                printf("%s: Command not found.\n", argv[0]);
                exit(0);
            }
        }

        if (!bg) { /* parent waits for fg job to terminate */
            int status;
            if (waitpid(pid, &status, 0) < 0)
                unix_error("waitfg: waitpid error");
        }
        else /* otherwise, don't wait for bg job */
            printf("%d %s", pid, cmdline);
    }
}
```

Problem with Simple Shell Example

Shell correctly waits for and reaps foreground jobs.

But what about background jobs?

- Will become zombies when they terminate.
- Will never be reaped because shell (typically) will not terminate.
- Creates a memory leak that will eventually crash the kernel when it runs out of memory.

Solution: Reaping background jobs requires a mechanism called a *signal*.

Signals

A **signal** is a small message that notifies a process that an event of some type has occurred in the system.

- Kernel abstraction for exceptions and interrupts.
- Sent from the kernel (sometimes at the request of another process) to a process.
- Different signals are identified by small integer ID's (1-30)
- The only information in a signal is its ID and the fact that it arrived.

ID	Name	Default Action	Corresponding Event
2	SIGINT	Terminate	Interrupt from keyboard (ctrl-c)
9	SIGKILL	Terminate	Kill program (cannot override or ignore)
11	SIGSEGV	Terminate & Dump	Segmentation violation
14	SIGALRM	Terminate	Timer signal
17	SIGCHLD	Ignore	Child stopped or terminated

Signal Concepts

Sending a signal

- Kernel ***sends*** (delivers) a signal to a ***destination process*** by updating some state in the context of the destination process.
- Kernel sends a signal for one of the following reasons:
 - Kernel has detected a system event such as divide-by-zero (SIGFPE) or the termination of a child process (SIGCHLD)
 - Another process has invoked the `kill` system call to explicitly request the kernel to send a signal to the destination process.

Signal Concepts (continued)

Receiving a signal

- A destination process **receives** a signal when it is forced by the kernel to react in some way to the delivery of the signal.
- Three possible ways to react:
 - Ignore the signal (do nothing)
 - Terminate the process (with optional core dump).
 - **Catch** the signal by executing a user-level function called a **signal handler**.
 - » Akin to a hardware exception handler being called in response to an asynchronous interrupt.

Signal Concepts (continued)

A signal is ***pending*** if it has been sent but not yet received.

- There can be at most one pending signal of any particular type.
- Important: Signals are not queued
 - If a process has a pending signal of type k, then subsequent signals of type k that are sent to that process are discarded.

A process can ***block*** the receipt of certain signals.

- Blocked signals can be delivered, but will not be received until the signal is unblocked.

A pending signal is received at most once.


Signal Concepts

Kernel maintains `pending` and `blocked` bit vectors in the context of each process.

- **`pending` – represents the set of pending signals**
 - Kernel sets bit `k` in `pending` whenever a signal of type `k` is delivered.
 - Kernel clears bit `k` in `pending` whenever a signal of type `k` is received
- **`blocked` – represents the set of blocked signals**
 - Can be set and cleared by the application using the `sigprocmask` function.

Process Groups

Every process belongs to exactly one process group



Sending Signals with `kill` Program

`kill` program sends arbitrary signal to a process or process group

Examples

- `kill -9 24818`
 - Send SIGKILL to process 24818
- `kill -9 -24817`
 - Send SIGKILL to every process in process group 24817.

```
linux> ./forks 16
linux> Child1: pid=24818 pgrp=24817
Child2: pid=24819 pgrp=24817
```


```
linux> ps
  PID TTY          TIME CMD
24788 pts/2        00:00:00 tcsh
24818 pts/2        00:00:02 forks
24819 pts/2        00:00:02 forks
24820 pts/2        00:00:00 ps
linux> kill -9 -24817
linux> ps
```

```
  PID TTY          TIME CMD
24788 pts/2        00:00:00 tcsh
24823 pts/2        00:00:00 ps
linux>
```

Sending Signals from the Keyboard

Typing ctrl-c (ctrl-z) sends a SIGINT (SIGTSTP) to every job in the foreground process group.

- SIGINT – default action is to terminate each process
- SIGTSTP – default action is to stop (suspend) each process



Example of `ctrl-c` and `ctrl-z`

```
linux> ./forks 17
Child: pid=24868 pgrp=24867
Parent: pid=24867 pgrp=24867
<typed ctrl-z>
Suspended
linux> ps a
  PID TTY          STAT       TIME COMMAND
 24788 pts/2        S           0:00 -usr/local/bin/tcsh -i
 24867 pts/2        T           0:01 ./forks 17
 24868 pts/2        T           0:01 ./forks 17
 24869 pts/2        R           0:00 ps a
bass> fg
./forks 17
<typed ctrl-c>
linux> ps a
  PID TTY          STAT       TIME COMMAND
 24788 pts/2        S           0:00 -usr/local/bin/tcsh -i
 24870 pts/2        R           0:00 ps a
```

Sending Signals with `kill` Function

```
void fork12()
{
    pid_t pid[N];
    int i, child_status;
    for (i = 0; i < N; i++)
        if ((pid[i] = fork()) == 0)
            while(1); /* Child infinite loop */

    /* Parent terminates the child processes */
    for (i = 0; i < N; i++) {
        printf("Killing process %d\n", pid[i]);
        kill(pid[i], SIGINT);
    }

    /* Parent reaps terminated children */
    for (i = 0; i < N; i++) {
        pid_t wpid = wait(&child_status);
        if (WIFEXITED(child_status))
            printf("Child %d terminated with exit status %d\n",
                wpid, WEXITSTATUS(child_status));
        else
            printf("Child %d terminated abnormally\n", wpid);
    }
}
```

Receiving Signals

Suppose kernel is returning from an exception handler and is ready to pass control to process p .

Kernel computes $\text{pnb} = \text{pending} \ \& \ \sim\text{blocked}$

- The set of pending nonblocked signals for process p

If ($\text{pnb} == 0$)

- Pass control to next instruction in the logical flow for p .

Else

- Choose least nonzero bit k in pnb and force process p to **receive** signal k .
- The receipt of the signal triggers some **action** by p
- Repeat for all nonzero k in pnb .
- Pass control to next instruction in logical flow for p .

Default Actions

Each signal type has a predefined ***default action***, which is one of:

- The process terminates
- The process terminates and dumps core.
- The process stops until restarted by a SIGCONT signal.
- The process ignores the signal.

Installing Signal Handlers

The `signal` function modifies the default action associated with the receipt of signal `signum`:

```
■ handler_t *signal(int signum, handler_t *handler)
```

Different values for `handler`:

- **SIG_IGN**: ignore signals of type `signum`
- **SIG_DFL**: revert to the default action on receipt of signals of type `signum`.
- Otherwise, `handler` is the address of a ***signal handler***
 - Called when process receives signal of type `signum`
 - Referred to as “***installing***” the handler.
 - Executing handler is called “***catching***” or “***handling***” the signal.
 - When the handler executes its return statement, control passes back to instruction in the control flow of the process that was interrupted by receipt of the signal.

Signal Handling Example

```
void int_handler(int sig)
{
    printf("Process %d received signal %d\n",
           getpid(), sig);
    exit(0);
}

void fork13()
{
    pid_t pid[N];
    int i, child_status;
    signal(SIGINT, int_handler);

    . . .
}
```

```
linux> ./forks 13
Killing process 24973
Killing process 24974
Killing process 24975
Killing process 24976
Killing process 24977
Process 24977 received signal 2
Child 24977 terminated with exit status 0
Process 24976 received signal 2
Child 24976 terminated with exit status 0
Process 24975 received signal 2
Child 24975 terminated with exit status 0
Process 24974 received signal 2
Child 24974 terminated with exit status 0
Process 24973 received signal 2
Child 24973 terminated with exit status 0
linux>
```


Signal Handler Funkiness

```
int ccount = 0;
void child_handler(int sig)
{
    int child_status;
    pid_t pid = wait(&child_status);
    ccount--;
    printf("Received signal %d from process %d\n",
           sig, pid);
}

void fork14()
{
    pid_t pid[N];
    int i, child_status;
    ccount = N;
    signal(SIGCHLD, child_handler);
    for (i = 0; i < N; i++)
        if ((pid[i] = fork()) == 0) {
            /* Child: Exit */
            exit(0);
        }
    while (ccount > 0)
        pause(); /* Suspend until signal occurs */
}
```

Pending signals are not queued

- For each signal type, just have single bit indicating whether or not signal is pending
- Even if multiple processes have sent this signal

Living With Non-Queuing Signals

Must check for all terminated jobs

- Typically loop with `wait`

```
void child_handler2(int sig)
{
    int child_status;
    pid_t pid;
    while ((pid = waitpid(-1, &child_status, WNOHANG)) > 0) {
        ccount--;
        printf("Received signal %d from process %d\n", sig, pid);
    }
}

void fork15()
{
    . . .
    signal(SIGCHLD, child_handler2);
    . . .
}
```

Signal Handler Funkiness (Cont.)

Signal arrival during long system calls (say a `read`)

- Signal handler interrupts `read()` call
- Linux: upon return from signal handler, the `read()` call is restarted automatically
- Some other flavors of Unix can cause the `read()` call to fail with an `EINTR` error number (`errno`); in this case, the application program can restart the slow system call

Subtle differences like these complicate the writing of portable code that uses signals.

A Program That Reacts to Externally Generated Events (ctrl-c)

```
#include <stdlib.h>
#include <stdio.h>
#include <signal.h>

void handler(int sig) {
    printf("You think hitting ctrl-c will stop the bomb?\n");
    sleep(2);
    printf("Well...");
    fflush(stdout);
    sleep(1);
    printf("OK\n");
    exit(0);
}

main() {
    signal(SIGINT, handler); /* installs ctrl-c handler */
    while(1) {
    }
}
```

A Program That Reacts to Internally Generated Events

```
#include <stdio.h>
#include <signal.h>

int beeps = 0;

/* SIGALRM handler */
void handler(int sig) {
    printf("BEEP\n");
    fflush(stdout);

    if (++beeps < 5)
        alarm(1);
    else {
        printf("BOOM!\n");
        exit(0);
    }
}
```

```
main() {
    signal(SIGALRM, handler);
    alarm(1); /* send SIGALRM in
               1 second */

    while (1) {
        /* handler returns here */
    }
}
```

```
cislinux> a.out
BEEP
BEEP
BEEP
BEEP
BEEP
BOOM!
cislinux>
```

Non-local Jumps: `setjmp/longjmp`

Powerful (but dangerous) user-level mechanism for transferring control to an arbitrary location.

- **Controlled to way to break the procedure call / return discipline**
- **Useful for error recovery and signal handling**

```
int setjmp( jmp_buf j )
```

- **Must be called before `longjmp`**
- **Identifies a return site for a subsequent `longjmp`.**
- **Called once, returns one or more times**

Implementation:

- **Remember where you are by storing the current register context, stack pointer, and PC value in `jmp_buf`.**
- **Return 0**

set jmp / long jmp (cont)

```
void longjmp(jmp_buf j, int i)
```

- **Meaning:**

- return from the `set jmp` remembered by jump buffer `j` again...
- ...this time returning `i` instead of 0

- **Called after `set jmp`**

- **Called once, but never returns**

long jmp Implementation:

- **Restore register context from jump buffer `j`**
- **Set `%eax` (the return value) to `i`**
- **Jump to the location indicated by the PC stored in jump buf `j`.**

setjmp/longjmp Example

```
#include <setjmp.h>
jmp_buf buf;

main() {
    if (setjmp(buf) != 0) {
        printf("back in main due to an error\n");
    } else {
        printf("first time through\n");
        p1(); /* p1 calls p2, which calls p3 */
    }
    ...
    p3() {
        <error checking code>
        if (error)
            longjmp(buf, 1)
    }
}
```


Putting It All Together: A Program That Restarts Itself When `ctrl-c`'d

```
#include <stdio.h>
#include <signal.h>
#include <setjmp.h>

sigjmp_buf buf;

void handler(int sig) {
    siglongjmp(buf, 1);
}

main() {
    signal(SIGINT, handler);

    if (!sigsetjmp(buf, 1))
        printf("starting\n");
    else
        printf("restarting\n");
```

```
while(1) {
    sleep(1);
    printf("processing...\n");
}
```

```
bass> a.out
starting
processing...
processing...
restarting
processing...
processing...
restarting
processing...
```

← Ctrl-c


← Ctrl-c

Limitations of Nonlocal Jumps

Works within stack discipline

- Can only long jump to environment of function that has been called but not yet completed

```
jmp_buf env;  
  
P1()  
{  
    if (setjmp(env)) {  
        /* Long Jump to here */  
    } else {  
        P2();  
    }  
}  
  
P2()  
{  
    . . . P2(); . . . P3();  
}  
  
P3()  
{  
    longjmp(env, 1);  
}
```




Limitations of Long Jumps (cont.)

Works within stack discipline

- Can only long jump to environment of function that has been called but not yet completed

```
jmp_buf env;  
  
P1()  
{  
    P2(); P3();  
}  
  
P2()  
{  
    if (setjmp(env)) {  
        /* Long Jump to here */  
    }  
}  
  
P3()  
{  
    longjmp(env, 1);  
}
```



Summary

Signals provide process-level exception handling

- Can generate from user programs
- Can define effect by declaring signal handler

Some caveats

- Very high overhead
 - >10,000 clock cycles
 - Only use for exceptional conditions
- Don't have queues
 - Just one bit for each pending signal type

Non-local jumps provide exceptional control flow within process

- Within constraints of stack discipline