

CIS 200: Fundamentals of Software Design

Exam 2 (50 points)

Practice Exam

You may use one 8.5"x11" page of handwritten notes, but no books, computers, calculators, or cell phones on the exam. Please do your own work.

Name: _____

Lab section (day and time): _____

EXAM SCORE: _____

1. (6 pts) Consider the following questions about arrays.
 - a) (2 pts) Declare a two-dimensional array of character values with 3 rows and 2 columns. You may call the array anything you like.

```
char [] [] grid = new char[3][2];
```

- b) (4 pts) Initialize the appropriate spots in the array to make the array look like this:

'a'	'A'
'b'	'B'
'c'	'C'

```
grid[0][0]='a';  
grid[0][1]='A';  
  
grid[1][0]='b';  
grid[1][1]='B';  
etc.
```

2. (10 pts) Write a method called **sumDoubleDigits**. This method should take an integer array as a parameter. It should then return the sum of all double-digit numbers in the array (for example, both 99 and -10 count as double-digit numbers).

```
public static int sumDoubleDigits (int [ ] arr) {  
    int sum = 0;  
    for (int i = 0; i < arr.length; i++) {  
        if (arr[i] >= 10 && arr[i] <=99) sum+= arr[i];  
        else if (arr[i] > -100 && arr[i] < -9) sum+= arr[i];  
    }  
  
    return sum;  
}
```

3. (4 pts) Suppose you are in the same class as the **sumDoubleDigits** method. Further suppose that an integer array called **values** has been declared and filled with values. Finally, suppose an integer variable called **answer** has been declared. Write ONE line of code that stores the sum of the double digit elements in **values** in the **answer** variable.

```
answer = sumDoubleDigits (values);
```

4. (10 pts) Suppose **numbers.txt** is an input file that contains several numbers with decimals, one per line. It might look like this:

3.42
17.0
47.151

Write a code fragment that reads every line in the file, and prints the decimal portion of each number to an output file called **afterDecimal.txt**. For the example above, the resulting **afterDecimal.txt** file should look like this:

42
0
151

Do not assume that there are only three lines in the file – your code should work no matter how many lines there are.

```
Scanner inFile = new Scanner (new File("numbers.txt"));
```

```
PrintWriter pw = new PrintWriter (new FileWriter  
("afterDecimal.txt"));
```

```
while (inFile.hasNext()) {  
    String line = inFile.nextLine();  
    String [ ] pieces = line.split(".");  
    pw.println(pieces[1]);  
}  
inFile.close();  
pw.close();
```

5. (8 pts) Consider the following full Java program. When this program runs, what is printed?

```
public class Exam {
    public static void main(String[] args) {
        System.out.println("main");
        int[] arr = {1,2,3,4};
        int val = 10;
        int result = second(arr, val);    // result = 11
        System.out.println(val);
        System.out.println(result);
        System.out.println(arr[0]);
    }

    public static void first(int[] list) {
        System.out.println("first");
        list[0] = 4;    // arr[0] replaced with 4
    }

    public static int second(int[] nums, int x) {
        System.out.println("second");
        first(nums);
        System.out.println("middle of second");
        x = 7;
        return nums[0]+x;    // 4 + 7 = 11
    }
}
```

arr = 1,2,3,4...arr[0] replaced w/4 in method “first”

val = 10

Output

main

second

first

middle of second

10

11

4

6. (4 pts) Consider the following statements. What is printed?

```
String example = "problem3onexam";  
System.out.println(example.substring(9));  
System.out.println(4 + 5 + example.substring(7,8) + 9); // 9+"3"+9  
System.out.println(example.charAt(3)+example.substring(5,8));
```

```
example[0] = p  
example[3] = b  
example[9] = n
```

OUTPUT

nexam

939

bem3

7. (8 pts) We would like to be able to call a **multiply** method like this:

```
double times = multiply(4.6, 3.2);
```

and have `times` hold 14.72 (which is 4.6 times 3.2). In general, we'd like to be able to pass two numbers and get back their product. **Write the method `multiply` that satisfies those criteria.**

```
public static double multiply (double first, double second)  
{ double product = first * second;  
  return product;  
}
```

```
or { return first * second;  
}
```