

| | | | |
|----------------------|-------------------------------------------------------------|---------------------------------------------|--|
| Keybindings | | | |
| C-x | Control-x | Control-x | |
| M-x | Meta-x | Alt/Option-x | |
| S-x | Super-x | Command-x | |
| Emacs | | | |
| Finding Files | | | |
| C-x C-f | Prompt to open file | ido-find-file | |
| s-d | Start dirtree, prompts for directory | dirtree | |
| s-f | Find file in project (current dir up to the .git directory) | find-file-in-project | |
| | Find file by regex | find-grep-dired | |
| C-x C-v | Revert file to version on disk | revert-buffer | |
| Movement | | | |
| C-n | Next line | next-line | |
| M-f | Forward a word | forward-word | |
| M-b | Backwards a word | backward-word | |
| C-M-b | Go to previous open brace/comma/bracket | backward-sexp | |
| C-M-f | Go to next ending brace/comma/bracket | forward-sexp | |
| C-M-u | Move up in parenthesis structure | backward-up-list | |
| C-M-d | Move down in parenthesis structure | down-list | |
| M-< | Beginning of buffer | beginning-of-buffer | |
| M-> | End of buffer | end-of-buffer | |
| M-m | Back to indendation | back-to-indentation | |
| Shift-TAB | Undent | scala-indent:indent-with-reluctant-strategy | |
| C-u C-x TAB | Indent region 4 spaces | universal-argument indent-rigidly | |
| C-v | Scroll up | scroll-down-command | |
| C-k | Kill remainder of line | kill-line | |
| M-k | Kill whole line | kill-whole-line | |
| C-a | Beginning of line | move-beginning-of-line | |
| C-e | Ending of line | move-end-of-line | |

| | | | |
|--------------------------------|-----------------------------------------|----------------------------|--|
| M-v | Scroll down | scroll-down-command | |
| S-l (ell) | Goto line | goto-line | |
| C-c SPACE | Ace Jump to a word | ace-jump-word-mode | |
| C-u C-c SPACE | Ace Jump Character Mode | ace-jump-char-mode | |
| C-u C-u C-c SPACE OR S-1 (one) | Ace Jump Line Mode | ace-jump-line-mode | |
| M-s } | Jump to next } | search-to-close-brace | |
| M-S } | Jump to previous } | search-to-prev-close-brace | |
| M-s { | Jump to next { | search-to-brace | |
| M-S { | Jump to previous { | search-to-prev-brace | |
| M-S d | Jump to previous “def “ | search-to-next-def | |
| M-s d | Jump to next “def “ | search-to-next-def | |
| General | | | |
| C-h t | Start tutorial | | |
| C-h i | Emacs Documentation Index | info | |
| M-s M-s OR S-s | Save all modified buffers | save-silently | |
| C-u 3 | Repeat next command 3 times | universal-argument | |
| | Prompt for input mode (tex for unicode) | toggle-input-mode | |
| C-l (ell) | Center screen on current line | | |
| M-t | Transpose words | transpose-words | |
| C-x C-t | Transpose lines | transpose-lines | |
| C-t | Transpose characters | transpose-chars | |
| C-M-o | Open line at insertion point | split-line | |
| M-^ | Join the current and previous line | delete-indentation | |
| C-x C-b | List all buffers | list-buffers | |
| C-x k | Kill buffer | ido-kill-buffer | |
| C-h c | Show command run by given key sequence | describe-key-briefly | |
| C-x b | Select another buffer | ido-switch-buffer | |
| M-up | Move current line or selection up | move-text-up | |
| M-down | Move current line or selection down | move-text-down | |
| C-s | Start an incremental search forward. | isearch-forward | |
| C-r | Start an incremental search backwards | isearch-backward | |

| | | | |
|------------------|--------------------------------------------------------------------------|------------------------------------------|--|
| C-w | Kill (Cut) | kill | |
| M-W | Kill Ring Save (Copy) | kill-ring-save | |
| C-y | Yank (Paste) | yank | |
| M-^ | Delete Indentation | delete-indentation | |
| S-z | Undo | undo | |
| M-s { | Search to brace | search-to-brace | |
| M-S { | Search to prev brace | search-to-prev-brace | |
| M-s } | Search to close brace | search-to-close-brace | |
| M-S } | Search to previous close brace | search-to-prev-brace | |
| M-s d | Search to next def | search-to-next-def | |
| M-S d | Search to previous def | search-to-prev-def | |
| Enzyme | | | |
| S-e | Start Enzyme | enzyme | |
| C-c C-b b | Rebuild entire project (clean build) | enzyme-builder-build | |
| C-c C-b r | Rebuild project incrementally | enzyme-builder-rebuild | |
| | Reload the .enzyme file and recompile the project | enzyme-reload | |
| | Start the automatic configuration file generator | enzyme-config-get | |
| C-c C-v z | Launch REPL (or switch to it if already running) | enzyme-inf-switch | |
| | Load a file in the Scala interpreter | enzyme-inf-load-file | |
| S-R | Send whole buffer to the Scala interpreter | enzyme-inf-eval-buffer | |
| S-r | Send the current region to the Scala interpreter | enzyme-inf-eval-region | |
| | Quit Scala interpreter | enzyme-inf-quit-interpreter | |
| | Send the current definition to the Scala interpreter | enzyme-inf-eval-definition | |
| C-c C-v 5 i | Launch type inspector on symbol under cursor in other frame | enzyme-inspect-type-at-point-other-frame | |
| C-c C-v o | Open the inspector on the current project's main package | | |
| | Open inspector on arbitrary type or package | enzyme-inspect-by-path | |
| C-s | Search through completion candidates | | |
| C-c C-o i | Organize imports | enzyme-refactor-organize-imports | |
| C-c C-v v or s-o | Search globally for methods or types | enzyme-search | |
| C-c C-v . | Select the surrounding syntactic context. Use . and , to grow and shrink | enzyme-expand-selection-command | |
| M-, | Pop back to previously visited position | enzyme-pop-find-definition-stack | |

| | | | |
|---------------------------|--------------------------------------------------------------------|-------------------------------------|--|
| M-. | Jump to definition of symbol under cursor | ensime-edit-definition | |
| C-c C-v i | Inspect type under cursor (.=forward page ,=back page C-n/TAB=forw | ensime-inspect-type-at-point | |
| TAB | Start completion | | |
| C-c C-v v | Global type and method search (type uppercase for case-sensitive) | ensime-search | |
| C-c C-v a | Typecheck all files in the project | ensime-typecheck-all | |
| C-c C-v c | Typecheck the current file | ensime-typecheck-current-file | |
| C-c C-b s | Switch to SBT | ensime-sbt-switch | |
| C-c C-b s | SBT do compile | ensime-sbt-do-compile | |
| C-c C-b n | SBT do clean | ensime-sbt-do-clean | |
| C-c C-b p | SBT do package | ensime-sbt-do-package | |
| C-c C-v r | List all references to the symbol under the cursor. Find Usages | ensime-show-uses-of-symbol-at-point | |
| C-c C-v p | Inspect the package of the current source file. | ensime-inspect-package-at-point | |
| M-p | Go to the previous compilation note in the current buffer | ensime-backward-note | |
| M-n | Go to the next compilation note in current buffer | ensime-forward-note | |
| C-c C-v u | Undo a refactoring or formatting change | ensime-undo-peek | |
| C-c C-v f | Format the current Scala file | ensime-format-source | |
| C-c C-v e | Show all errors and warnings in the project | ensime-show-all-errors-and-warnings | |
| C-c C-v x | Scalex Documentation Search | ensime-scalex | |
| M-s M-t | Test-Only Current Buffer | scala-test-only | |
| M-s M-T OR S-t | Jump to test | jump-to-test | |
| S-n | Scala Find Name | scala-find-name | |
| S-N | Scala Find class/trait | scala-find-class | |
| Ensime Refactoring | | | |
| C-c C-r t | Add import for type at point | ensime-import-type-at-point | |
| C-c C-r r | Rename | ensime-refactor-rename | |
| C-c C-r m | Extract method (C-space at beginning, move to end) | ensime-refactor-extract-method | |
| C-c C-r i | Inline Local | ensime-refactor-inline-local | |
| C-c C-r l | Extract local | ensime-refactor-extract-local | |
| C-c C-r o | Organize imports | ensime-refactor-organize-imports | |
| Ensime Debugger | | | |
| C-c C-d d | Start debugger | ensime-db-start | |

| | | | |
|--------------------------|-----------------------------------------|----------------------------------|--|
| C-c C-d b | Set breakpoint | ensime-db-set-break | |
| C-c C-d u | Clear breakpoint | ensime-db-clear-break | |
| C-c C-d s | Step | ensime-db-step | |
| C-c C-d n | Step over | ensime-db-next | |
| C-c C-d o | Step out | ensime-db-step-out | |
| C-c C-d r | Run | ensime-db-run | |
| C-c C-d c | Continue from breakpoint | ensime-db-continue | |
| C-c C-d q | Quit debug session | ensime-db-quit | |
| C-c C-d i | Inspect variable at cursor in debugger | ensime-db-inspect-value-at-point | |
| C-c C-d t | Show backtrace in debugger | ensime-db-backtrace | |
| C-c C-d a | Clear all breakpoints | ensime-db-clear-all-breaks | |
| Magit | | | |
| | Enter magit mode, view status | magit-status | |
| S-TAB | Toggle visibility of current section | | |
| M-S | Show all sections | | |
| I I | Show history, short form | | |
| I L | Show history, more verbose form | | |
| s | Move hunk into staging area | | |
| u | Move hunk out of staging area (unstage) | | |
| S | Move all hunks into staging | | |
| U | Move all hunks out of staging | | |
| c | Prompt for Commit message | | |
| C-c C-c | Commit | magit-commit | |
| P P | Push | magit-push | |
| F F | Pull | magit-pull | |
| Ensime Sbt Window | | | |
| M-p | Previously entered command | | |
| M-n | Next entered command | | |
| Shell Commands | | | |
| M-! | Execute a shell command | shell-command | |

| | | | |
|-----------------------|---------------------------------------------------|---------------------------------------------|--|
| M- | | Run shell command on region | |
| C-u M- | | Filter region through shell command | |
| | Start shell in window shell | shell | |
| Org Mode | | | |
| TAB | Expand or contract current selection | | |
| | Scala indent with reluctant strategy | scala-indent:indent-with-reluctant-strategy | |
| C-c C-t | Rotate TODO state | org-todo | |
| s-T | Show TODO list in prio order for current file | todo-agenda-current-file | |
| NeoTree | | | |
| s-d | Start dirtree in it's own buffer | neotree | |
| <space> OR RET OR TAB | Open current item, or unfold if directory | neotree-enter | |
| p | Previous node | | |
| n | Next node | | |
| A | Maximize/Minimize NeoTree window | neotree-stretch-toggle | |
| C-c C-n | Create file (or directory if name ends in /) | neotree-create-node | |
| H | Toggle display hidden files | neotree-hidden-file-toggle | |
| C-c C-d | Delete file or directory | neotree-delete-note | |
| C-c C-r | Rename file or directory | neotree-rename-node | |
| C-c C-c | Change root directory | neotree-change-root | |
| | Show neotree window and specify directory as root | neotree-dir | |
| | Hide neotree window | neotree-hide | |
| | Togge hide NeoTree window | neotree-toggle | |
| | Show neotree window and use current file as root | neotree-find | |
| g | Refresh tree | neotree-refresh | |
| Table Mode | | | |
| | Insert new table | table-insert | |
| C-+ | Insert row | table-insert-row | |
| C-+ | Insert column | table-insert-column | |
| | Delete row | table-delete-row | |
| | Delete column | table-delete-column | |

| | | | |
|------------------------|------------------------------------------------------------------------|---------------------------------|--|
| | Recognize all table in current buffer | table-recognize | |
| | Unrecognize tables in current buffer | table-unrecognize | |
| | Recognize in region | table-recognize-region | |
| | Unrecognize in region | table-unrecognize-region | |
| | Recognize single table | table-recognize-table | |
| | Unrecognize single table | table-unrecognize-table | |
| | Recognize a cell at current point | table-recognize-cell | |
| | Unrecognize cell at point | table-unrecognize-cell | |
| | Move forward to next Nth cell | table-forward-cell | |
| | Move previous Nth cell | table-backward-cell | |
| C-* | Span current cell in specified direction | table-span-cell | |
| C- | Split current cell vertically | table-split-cell-vertically | |
| C- | | Split current cell horizontally | |
| | Split current cell vertically or horizontally | table-split-cell | |
| C-} | Increase height of current cell | table-heighten-cell | |
| C-{ | Decrease height of current cell | table-shorten-cell | |
| C-< | Narrow current cell | table-narrow-cell | |
| C-> | Widen current cell | table-widen-cell | |
| C-! | Toggle fixed width mode | table-fixed-width-mode | |
| C-# | Compute and report current table dimension | table-query-dimension | |
| C-^ | Generate source in specified language and insert into specified buffer | table-generate-source | |
| | Travel forward inserting specified sequence in cells | table-insert-sequence | |
| | Convert plant text into table by capturing text in the region | table-capture | |
| | Convert table into plain text | table-release | |
| C-: | Justify contents of cells | table-justify | |
| | Disable all table advice | table-disable-advice | |
| | Enable table advice | table-enable-advice | |
| | Show version of table mode | table-version | |
| TAB | Move point to beginning of next cell | | |
| Window Commands | | | |
| C-x 2 OR S- | Divide the current window horizontally in two | split-window-horizontally | |

| | | | |
|-----------------------------|---------------------------------------------------------------|-------------------------------|--|
| S-- (super-dash) | Split window vertically | split-window-vertically | |
| S-+ | Remove split | remove-split | |
| C-x 5 | Divide the current window vertically in two. | split-windws-vertically | |
| C-x > | Scroll the window right. | scroll-right | |
| C-x < | Scroll the window left. | scroll-left | |
| C-x 0 | Delete the current window. | delete-window | |
| C-x 1 | Delete all the windows except this one. | delete-other-windows | |
| | Delete all windows open to a particular buff. | delete-windows-on | |
| C-x ^ OR S-<up> | Make the current window taller. | enlarge-window | |
| S-<down> | Make the current window smaller. | shrink-window | |
| C-x } OR S-<right> | Make the window wider. | enlarge-window-horizontally | |
| C-x { OR S-<left> | Make the window less wide. | shrink-window-horizontally | |
| M-C-v | Scroll the other window. | scroll-other-window | |
| C-x 4 f | Find a file in the other window. | find-file-other-window | |
| C-x 4 b | Select a buffer in the other window. | switch-to-buffer-other-window | |
| | Compare two buffers and show the first diff. | compare-windows | |
| C-x C-j 1 OR M-1 (M-2, etc) | Jump to window number 1 (any number) | | |
| Capitalization | | | |
| M-c | Capitalize the first letter of current word. | capitalize-word | |
| M-u | Make the word all uppercase. | upcase-word | |
| M-l | Make the word all lowercase. | downcase-word | |
| C-x C-l | Make the region all lowercase. | downcase-region | |
| C-x C-u | Make the region all uppercase. | upcase-region | |
| Getting Help | | | |
| C-h a | What commands work like this...? | command-apropos | |
| | What functions and variables work like this.? | apropos | |
| C-h c | What command does this key sequence do? | describe-key-briefly | |
| C-h b | What are the key bindings for this buffer? | describe-bindings | |
| C-h k | What command does this sequence do,and tell me about it. | describe-key | |
| C-h l | What are the last 100 characters typed? | view-lossage | |
| C-h w | What is the key binding for the specified function (prompts)? | where-is | |

| | | | |
|-----------------|------------------------------------------------------------------------|------------------------------------|--|
| C-h f | What does this function do? What keys is it bound to? | describe-function | |
| C-h v | What is this variable? | describe-variable | |
| C-h m | Tell me about this mode. | describe-mode | |
| C-h s | What is the syntax table for this buffer? | describe-syntax | |
| Dired | | | |
| C-x d | Start dired in a specified directory (prompts for directory) | dired | |
| C-n | Next node | dired-next-line | |
| n | Next node | | |
| C-p | Previous node | dired-prev-dirline | |
| | Move up and unflag | | |
| j | Prompt for filename, move to the line with that file name | dired-goto-file | |
| i | Insert contents of directory at point | dired-maybe-insert-subdir | |
| l | Refresh directory contents | dired-do-redisplay | |
| ^ | Move point to parent directory entry | | |
| \$ | Hide/Unhide subdirectory, leaving only header line visible | | |
| M-\$ | Hide/Unhide all subdirectories, leaving only header lines visible | | |
| C-M-n | Go to next subdirectory header line, regardless of level | dired-next-subdir | |
| C-M-p | Go to previous subdirectory header line, regardless of level | dired-prev-subdir | |
| C-M-u | Go up to the parent directory's header line | dired-tree-up | |
| C-M-d | Go down in the directory tree, to the first subdirectory's header line | dired-tree-down | |
| M-x image-dired | Enter image-dired mode, show thumbnails of images in this directory | image-dired | |
| C-t d | Display thumbnails of marked images in this directory | image-dired-display-thumbs | |
| < | Move up to the previous directory-file line | dired-prev-dirline | |
| > | Move down to the next directory-file line | dired-prev-dirline | |
| C-x C-q | Toggle WDired mode, Dired Manual | dired-toggle-read-only | |
| d | Flag this file for deletion | dired-flag-file-deletion | |
| u | Remove the deletion flag | dired-unmark | |
| | Move point to previous line and remove the deletion flag on that line | dired-unmark-backward | |
| x | Delete files flagged for deletion | dired-do-flagged-delete | |
| * % regexp | Mark with a '*' all files whose name matches the specified regexp | dired-mark-files-regexp | |
| % g regexp | Mark with a '*' all files whose contents match the specified regexp | dired-mark-files-containing-regexp | |

| | | | |
|-------------------------|------------------------------------------------------------------|----------------------------|--|
| C-/ | Undo changes in the dired buffer | dired-undo | |
| C | Copy File | dired-do-copy | |
| s-j | Jump to dired of directory containing the current file | dired-jump | |
| D | Delete file | dired-do-delete | |
| R | Rename file | dired-do-rename | |
| M | Change mode of file | dired-do-chmod | |
| A | Search all the specified files for the regular expression regexp | dired-do-search | |
| m | Mark current file/directory | dired-mark | |
| u | Unmark current file/directory | dired-unmark | |
| U | Unmark all marked in current directory | dired-unmark-all-marks | |
| M- | Toggle Tree View | | |
|) | Show more details on each file/dir | | |
| (| Show less details on each file/dir | | |
| Multiple Cursors | | | |
| C-S-c C-S-c | Multiple cursors on lines in active region | mc/edit-lines | |
| C-> | Mark next line like this | mc/mark-next-like-this | |
| C-< | Mark previous line like this | mc/mark-previous-like-this | |
| C-c C-< | Mark all like this (select a region to match first) | mc/mark-all-like-this | |
| C-g | Cancel multiple cursor mode | | |
| RET | Exit multiple cursor mode | mc/keyboard-quit | |
| C-j | Insert a newline in multiple-cursor mode | | |
| Expand Region | | | |
| C-= | Expand-region | er/expand-region | |
| Yas Snippets | | | |
| | Reload all snippet definitions | yas-reload-all | |
| Amethyst | | | |
| M-S-RET | Swap focussed window with main window | | |
| M-S-SPC | Cycle layout forward | | |
| C-M-S-SPC | Cycle layout backward | | |

| | | | |
|--------------------------------|-------------------------------------------------------|--|--|
| M-H | Shrink main pane | | |
| M-L | Expand main pane | | |
| M-<shift>-, | Increase main pane count | | |
| M-<shift>-. | Decrease main pane count | | |
| M-J | Move focus counter clockwise | | |
| M-K | Move focus clockwise | | |
| M-I (uppercase eye) | Display the current layout for each screen | | |
| C-M-T | Toggle globally whether amethyst tiles windows | | |
| M-T | Toggle whether or not the focussed window is floating | | |
| M-W | Focus 1st screen | | |
| M-E | Focus 2nd screen | | |
| C-M-W | Move focussed window to 1st screen | | |
| C-M-E | Move focussed window to 2nd screen | | |
| | | | |
| Alfred | | | |
| M-Space | Prompt for app name | | |
| | | | |
| ITerm 2 | | | |
| S-t | New tab | | |
| C-<space> | Toggle hotkey window | | |
| C-<right> | Cycle tabs forward | | |
| S-<up> | Scroll one line up | | |
| S-<down> | Scroll one line down | | |
| S-<shift>-<left> | Move tab left | | |
| S-<right> | Next tab | | |
| S-<left> | Previous tab | | |
| S-<shift>-<right> | Move tab right | | |
| S-<home> | Scroll to top | | |
| S-<end> | Scroll to end | | |
| S-<page-up> OR C-<page-up> | Scroll page up | | |
| S-<page-down> OR C-<page-down> | Scroll page down | | |

| | | | |
|-------------------|---------------------------------------------------------|--|--|
| | | | |
| Flowdock | | | |
| /help | Display help | | |
| /status [message] | Send this status message (or clear if no message given) | | |
| /away [message] | As above | | |
| /hangout | Start a new Google Hangout with your flow | | |
| /room | Start a new Room video chat with your flow | | |
| /room @Nick | Start a new Room video chat with specified person | | |
| /hero | Start a ScreenHero call | | |
| /hero @Nick | Start a ScreenHero call with specified person | | |
| /query @Nick | Start new 1-on-1 conversation with specified person | | |
| /slap @Nick | Slap Nick with a fish | | |
| / /query | Sends a normal message that starts with /query | | |
| ESC | Unfocus text field | | |
| S-1 | Switch to tab 1 (or any other number) | | |
| M-S-<up> | Go to previous tab | | |
| M-S-<down> | Go to next tab | | |
| S-w | Close tab | | |
| S-t | Open new tab | | |
| S-, | Open preferences | | |
| ESC U | Show or hide flow users | | |
| ESC D | Do not disturb for 30 seconds | | |
| ESC F | Focus search | | |
| ESC I | Focus chat | | |
| ESC ESC | Toggle thread | | |
| TAB | Refocus last focussed field | | |
| BACKSPACE | Go back | | |
| <up> | Edit your last message (when in chat) | | |
| C-S-<up> | Open previous thread (when in chat) | | |
| C-S-<down> | Open next thread (when in chat) | | |
| ESC S | Flip thread to right or left side (with open thread) | | |

| | | | |
|-----------------|------------------------|--|--|
| | | | |
| Emacsome | | | |
| C-n | Next line | | |
| C-p | Previous line | | |
| C-o | Far right | | |
| C-a | Far left | | |
| C-v | Page down | | |
| M-v | Page up | | |
| M-> | Bottom of page | | |
| M-< | Top of page | | |
| C-b | Back history | | |
| C-f | Forward history | | |
| M-n | Next tab | | |
| M-p | Previous tab | | |
| C-x b | Browse tabs | | |
| C-s | Highlight next tab | | |
| C-r | Highlight previous tab | | |
| C-x C-f | Show links | | |
| number-RET | Go to that link | | |