

Test Plan 6 — QA Agent (Orchestrator + Test-Plan Generator)

Project	agent
Specs	tests/agent/orchestrator/orchestrator.spec.ts , tests/agent/test-plan/test-plan-agent.spec.ts
Default filter	@other-smoke
Target	Offline — pure stubs, no network or browser
Code under test	src/agent/** (Orchestrator , TestPlanAgent , connectors)
Cases	2
Skips	None — deterministic stubs

Scope

Unit-level regression of the QA agent, run entirely against in-memory stubs so it needs no network or browser. Two capabilities are covered:

1. **Orchestrator** — the run loop that reads a plan, executes cases, isolates a crashing runner, and writes results back idempotently.
2. **TestPlanAgent** — the URL→plan generator that explores a page through the Playwright MCP (PageExplorer) and synthesises a TestSuite .

Preconditions

- None beyond a typecheck. All connectors are stubs / fakes.

Cases

orchestrator.spec.ts — "QA agent orchestrator"

ID	CASE	ASSERTS	TAGS
AGT-01	Marks runner crashes as blocked and continues running the suite	A thrown runner error isolates that case as <code>blocked</code> , the next case still runs, an error-log artifact is attached, and results are reported (<code>blocked</code> , <code>passed</code>)	<code>@other-smoke</code>

`test-plan-agent.spec.ts` — "TestPlanAgent"

ID	CASE	ASSERTS	TAGS
AGT-02	Generates a plan from a URL via the Playwright MCP explorer	The input URL reaches the MCP <code>navigate</code> call; ids/name derive from host + page title; every case is <code>@generated</code> ; a page-load case, a headings case, one de-duped case per nav link, and a form case are produced (fields + submit picked up)	<code>@other-smoke</code>

Run

```
npx playwright test --project=agent
# Try the generator against any URL (offline stub explorer):
npm run agent:plan -- https://www.organuz.ai
```

Notes

- Both cases are `@other-smoke` so both run in the default suite — the `agent` project count is 2. Adding/removing an `@other-smoke` agent test changes that count; update `CLAUDE.md`, the parity skill, and `Readme.md`.
- `TestPlanAgent` emits the same `TestSuite` shape the `Orchestrator` consumes, so a generated plan can flow straight into the run loop (see `src/agent/README.md`).