

Test Plan 4 — Product Roles E2E (Live Per-Role Sessions)

Projects	product-setup → product-authenticated
Specs	tests/product/support/auth.setup.ts , tests/product/flows/roles.spec.ts
Target	Dev calculator — QA_TARGET_ENV (default dev), per-role phone+OTP login
Cases	13 (setup 3 + authenticated 10)
Skips	Per role — no credential (setup) or no saved session (authenticated)
Skills	product-roles-e2e , organuz-product-roles

Scope

Live, per-role browser coverage. product-setup signs each role in once via phone+OTP and saves its storageState ; product-authenticated resumes that session and runs read-only checks of each role's personal area. This is the live counterpart to Plan 3's offline role contract. Dormant on CI until per-role secrets exist — the suite stays green without them.

Preconditions

- Live dev app + gate (PRODUCT_PLATFORM_PASSWORD).
- Per-role credentials in the gitignored .env / CI secrets: <ROLE>_PHONE / <ROLE>_OTP_CODE for CUSTOMER , CONSULTANT , COMPANY .

Gating (sanctioned skip)

- product-setup : a role with no <ROLE>_PHONE (or when the dev app/OTP is down) is skipped — no session is written for it.
- product-authenticated : each role's specs skip when it has no saved session (hasSavedSession(role) false) or the session cannot resume.

Cases

auth.setup.ts — per-role sign-in (project product-setup)

ID	CASE	ASSERTS
SET-01	Authenticate customer and save storageState	Customer phone+OTP login succeeds; session persisted
SET-02	Authenticate consultant and save storageState	Consultant phone+OTP login succeeds; session persisted
SET-03	Authenticate company and save storageState	Company phone+OTP login succeeds; session persisted

roles.spec.ts — live role sessions (project product-authenticated , @product @roles @e2e)

ID	CASE	ASSERTS
CUS-01	Customer resumes its saved session into the calculator shell	Session resumes; shell authenticated
CUS-02	Customer can open its personal area	Customer personal area opens
CUS-03	Customer session persists across a reload	Session survives a page reload
CON-01	Consultant resumes its saved session into the calculator shell	Session resumes; shell authenticated
CON-02	Consultant can open its personal area	Consultant personal area opens
CON-03	Consultant session persists across a reload	Session survives a page reload
COM-01	Company resumes its saved session into the calculator shell	Session resumes; shell authenticated
COM-02	Company can open its personal area	Company personal area opens
COM-03	Company session persists across a reload	Session survives a page reload
COM-04	Company can open the contractor pricing area	Company-only pricing area opens

Run

```
# Runs product-setup first (its dependency), then the authenticated flows:  
QA_TARGET_ENV=dev npx playwright test --project=product-authenticated
```

Notes

- Keep skip/lifecycle logic at the test edge (spec/fixture), not in `ProductAppPage` or `ProductFlows` — those **throw** typed errors.
- `product-authenticated` depends on `product-setup`; run the dependent project and Playwright pulls the setup in. Don't shard the setup separately (double login).