

Demo Appointment Assistant

Functional Requirements and Webhook Contract - QA Test Project

Project type Conversational appointment assistant	Purpose A clean external project for validating dynamic QA generation and execution.
---	--

1. Product goal

The assistant helps a user book a consultation appointment through a short text conversation. It must collect the required facts in sequence, answer a small support question, handle cancellation, and never invent missing booking details.

2. Supported services

If the user asks what services are available, the assistant must reply with exactly these service names:

Service
Website Development
Automation Consulting
AI Consulting

3. Booking conversation requirements

ID	Area	Expected behavior
REQ-APT-001	New conversation	For a new session, any normal greeting or booking request starts booking and the assistant asks for the user's name.
REQ-APT-002	Name collection	After the user gives a usable name, the assistant stores it and asks for the preferred appointment date.
REQ-APT-003	Date collection	The assistant accepts a clear date such as "August 20", "8/20/2026", "tomorrow", or a weekday. Vague answers such as "sometime" or "maybe later" must be rejected and the date requested again.
REQ-APT-004	Time preference	After a valid date, the assistant asks the user to choose Morning or Afternoon. Any other answer must be clarified.
REQ-APT-005	Confirmation	Once name, date, and time preference are known, the assistant confirms the booking and includes all three values in the confirmation.
REQ-APT-006	No invention	The assistant must not invent a name, date, or time preference that the user did not provide.

ID	Area	Expected behavior
REQ-APT-007	Service support	At any point, a service-information question returns the three supported services. If booking is in progress, the assistant should then resume the pending booking question.
REQ-APT-008	Cancellation	If the user says cancel, stop, or never mind, the booking is cancelled and the session returns to a new state.
REQ-APT-009	Session isolation	Conversation state is isolated by session_id. Different session IDs must not share names, dates, or booking state.
REQ-APT-010	Book again	After confirmation, the user may say "book again" or "new booking" to begin another booking in the same session.

4. Conversation examples

Happy path

User: Hi, I want to book a consultation.

Assistant: Sure! What's your name?

User: I'm Alex.

Assistant: Thanks, Alex. What date would you like your appointment?

User: August 20.

Assistant: Would you prefer Morning or Afternoon?

User: Morning.

Assistant: Your appointment is confirmed for Alex on August 20 in the Morning.

Support question during booking

User: What services do you offer?

Assistant: We offer Website Development, Automation Consulting, and AI Consulting. What date would you like your appointment?

Vague date recovery

User: Sometime next month.

Assistant: Please give me a specific appointment date.

5. Webhook contract

The deployed target is an HTTP POST webhook. Requests and responses use JSON.

Request field	Required	Description
message	Yes	Current simulated user message.
session_id	Yes	Conversation identity used to isolate state.

run_id	No	QA run identifier; accepted and ignored by this demo.
test_case_id	No	QA case identifier; accepted and ignored by this demo.

Example request

```
{ "message": "Hi, I want to book", "session_id": "qa-demo-123" }
```

Example response

```
{ "reply": "Sure! What's your name?", "session_id": "qa-demo-123", "stage": "awaiting_name" }
```

6. QA expectations

- Test cases should be independent unless a scenario explicitly tests continuation in the same session.
- Use distinct session IDs for independent tests.
- Expected results should focus on observable conversational behavior, not internal implementation details.
- Happy-path, validation/recovery, support-question, cancellation, and session-isolation scenarios are all valid test areas.
- The target is deterministic on purpose so failures can be attributed to the QA system rather than model randomness.

End of specification